

Internet Engineering Task Force
Internet-Draft
Intended status: Experimental
Expires: April 25, 2019

G. Galimberti, Ed.
Cisco
R. Kunze
Deutsche Telekom
D. Hiremagalur, Ed.
G. Grammel, Ed.
Juniper
October 22, 2018

A YANG model to manage the optical interface parameters for an external
transponder in a WDM network

[draft-dharini-ccamp-dwdm-if-param-yang-06](#)

Abstract

This memo defines a Yang model related to the Optical Transceiver parameters characterising coherent 100G and above interfaces. 100G and above Transceivers support coherent modulation, multiple modulation formats, multiple FEC codes including some not yet specified (or by in phase of specification by) ITU-T G.698.2 [[ITU.G698.2](#)] or any other ITU-T recommendation. More context about the state of the Coherent transceivers is described in [draft-many-coherent-DWDM-if-control](#). Use cases are described in [RFC7698](#)

The Yang model defined in this memo can be used for Optical Parameters monitoring and/or configuration of the endpoints of a multi-vendor IaDI optical link. The use of this model does not guarantee interworking of transceivers over a DWDM. Optical path feasibility and interoperability has to be determined by means outside the scope of this document. The purpose of this model is to program interface parameters to consistently configure the mode of operation of transceivers.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 25, 2019.

Copyright Notice

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	The Internet-Standard Management Framework	3
3.	Conventions	4
4.	Overview	4
4.1.	Optical Parameters Description	5
4.1.1.	Parameters at Ss	5
4.1.2.	Interface at point Rs	5
4.2.	Use Cases	5
4.3.	Optical Interface for external transponder in a WDM network	5
5.	Structure of the Yang Module	8
6.	Yang Module	8
7.	Security Considerations	21
8.	IANA Considerations	21
9.	Acknowledgements	22
10.	Contributors	22
11.	References	23
11.1.	Normative References	23
11.2.	Informative References	25
Appendix A.	Change Log	25
Appendix B.	Open Issues	25
	Authors' Addresses	26

1. Introduction

This memo defines a Yang model that translates and obsolete the SNMP mib module defined in [draft-galikunze-ccamp-dwdm-if-snmp-mib](#) for managing single channel optical interface parameters of DWDM applications, using the approach specified in G.698.2. This model supports parameters to characterize coherent transceivers found in current implementations to specify the mode of operation. As application identifiers like those specified in ITU-T G.874.1 [[ITU.G874.1](#)] are not available we use mode templates instead. A mode template describes transceiver characteristics in detail and can be identified by a mode-id.

This draft refers and supports the [RFC7698](#) and [draft-many-coherent-DWDM-if-control](#).

The YANG model describing and extending the optical parameters allows different vendors and operators to retrieve, provision and exchange information across the multi-vendor IaDI interfaces in an abstract manner.

The they concept introduced by this YANG model is the notion of a mode. A mode is a combination of parameters or parameter ranges that is supported by a transceiver. As an example, operating a device in QPSK mode may use a different FEC and requires less OSNR to reach the FEC limit than the same transceiver operating in QAM16 mode. Given the number of parameters and their possible combinations it is important for vendors to be able to qualify a set of combinations which is the basis to define a mode. The YANG model furthermore provides means to selecting one mode as current-mode from that pre-defined list of modes supported by the transceiver module. Once selected, current-opt-if-och-mode-params provide the means to configure specific parameters at run time and retrieve actual parameters from the module. For example, the frequency is a parameter that can be set within min/max boundaries set by the current mode. Laser Temperature however is a ro parameter available at run-time that can be checked against the mode boundaries and may trigger an event.

2. The Internet-Standard Management Framework

For a detailed overview of the documents that describe the current Internet-Standard Management Framework, please refer to [section 7 of RFC 3410](#) [[RFC3410](#)].


This memo specifies a Yang model for optical interfaces.

3. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)]. In the description of OIDs the convention: Set (S) Get (G) and Trap (T) conventions will describe the action allowed by the parameter.

4. Overview

Figure 1 shows a set of reference points, for single-channel connection between transmitters (Tx) and receivers (Rx). Here the DWDM network elements include an OM and an OD (which are used as a pair with the opposing element), one or more optical amplifiers and may also include one or more OADMs.



Ss = reference point at the DWDM network element tributary output

Rs = reference point at the DWDM network element tributary input

Lx = Lambda x

OM = Optical Mux

OD = Optical Demux

ROADM = Reconfigurable Optical Add Drop Mux

from Fig. 5.1/G.698.2

Figure 1: External transponder in WDM networks

4.1. Optical Parameters Description

The link between the external transponders through a WDM network media channels are managed at the edges, i.e. at the transmitters (Tx) and receivers (Rx) attached to the S and R reference points respectively.

Definitions of the optical parameters are provided below to increase the readability of the document.

4.1.1. Parameters at Ss

output-power:

The mean launched power at Ss is the average power (in dBm) of a pseudo-random data sequence coupled into the DWDM link.

central frequency:

This parameter indicates the Central frequency value that Ss and Rs will be set to work (in THz)

4.1.2. Interface at point Rs

input-power:

The average received power (in dBm) at point Rs.

Curr-OSNR:

Current Optical Signal to Noise Ratio (OSNR) estimated at Rx Transceiver port.

Curr-q-factor:

"Q" factor estimated at Rx Transceiver port.

4.2. Use Cases

The use cases are described in [draft-ietf-ccamp-dwdm-if-mng-ctrl-fwk](#)

4.3. Optical Interface for external transponder in a WDM network

The ietf-ext-xponder-wdm-if is an augment to the ietf-interface. It allows the user to set the operating mode of transceivers as well as other operational parameters. The module provides also threshold settings and notifications to supervise measured parameters and notify the client.

```
module: ietf-ext-xponder-wdm-if
  augment /if:interfaces/if:interface:
    +--rw optIfOChRsSs
    +--rw if-current-mode
```



```
|  +--ro mode-id?                string
|  +--ro min-central-frequency?  uint32
|  +--ro max-central-frequency?  uint32
|  +--ro min-input-power?        dbm-t
|  +--ro max-input-power?        dbm-t
|  +--ro min-output-power?       dbm-t
|  +--ro max-output-power?       dbm-t
|  +--ro osnr-margin?            int32
|  +--ro q-margin?               int32
|  +--ro fec-info?               string
|  +--ro fec-bitrate?            string
|  +--ro fec-gain?                string
|  +--rw fec-ber-mantissa-threshold? uint32
|  +--rw fec-ber-exponent-threshold? int32
|  +--ro number-of-lanes?        uint32
|  +--ro min-laser-temperature?   int32
|  +--ro max-laser-temperature?   int32
|  +--ro min-rx-optical-power?    dbm-t
|  +--ro max-rx-optical-power?    dbm-t
|  +--ro min-chromatic-dispersion? int32
|  +--ro max-chromatic-dispersion? int32
|  +--ro min-diff-group-delay?    int32
|  +--ro max-diff-group-delay?    int32
|  +--ro modulation-format?       string
|  +--rw bits-per-symbol?         uint32
|  +--rw num-symbols-in-alphabet?  uint32
|  +--rw symbols-index?           uint32
|  +--ro i-center?                int32
|  +--ro q-center?                int32
|  +--ro i-noise-variance?         int32
|  +--ro q-noise-variance?         int32
|  +--ro a-noise-variance?         int32
|  +--ro p-noise-variance?         int32
+--ro if-supported-mode
|  +--ro number-of-modes-supported? uint32
|  +--ro mode-list* [mode-id]
|    +--ro mode-id                string
|    +--ro min-central-frequency?  uint32
|    +--ro max-central-frequency?  uint32
|    +--ro min-input-power?        dbm-t
|    +--ro max-input-power?        dbm-t
|    +--ro min-output-power?       dbm-t
|    +--ro max-output-power?       dbm-t
|    +--ro osnr-margin?            int32
|    +--ro q-margin?               int32
|    +--ro fec-info?               string
|    +--ro fec-bitrate?            string
|    +--ro fec-gain?                string
```



```

|   +--ro fec-ber-mantissa-threshold?  uint32
|   +--ro fec-ber-exponent-threshold?  int32
|   +--ro number-of-lanes?             uint32
|   +--ro min-laser-temperature?       int32
|   +--ro max-laser-temperature?       int32
|   +--ro min-rx-optical-power?         dbm-t
|   +--ro max-rx-optical-power?         dbm-t
|   +--ro min-chromatic-dispersion?     int32
|   +--ro max-chromatic-dispersion?     int32
|   +--ro min-diff-group-delay?         int32
|   +--ro max-diff-group-delay?         int32
|   +--ro modulation-format?           string
|   +--ro bits-per-symbol?              uint32
|   +--ro num-symbols-in-alphabet?      uint32
|   +--ro symbols-index?               uint32
|   +--ro i-center?                    int32
|   +--ro q-center?                    int32
|   +--ro i-noise-variance?             int32
|   +--ro q-noise-variance?             int32
|   +--ro a-noise-variance?             int32
|   +--ro p-noise-variance?             int32
+--rw current-opt-if-och-mode-params
   +--rw mode-id?                      string
   +--ro osnr-margin?                  int32
   +--ro q-margin?                     int32
   +--rw central-frequency?            uint32
   +--rw output-power?                 int32
   +--ro input-power?                  int32
   +--rw min-fec-ber-mantissa-threshold? uint32
   +--rw min-fec-ber-exponent-threshold? int32
   +--rw max-fec-ber-mantissa-threshold? uint32
   +--rw max-fec-ber-exponent-threshold? int32
   +--rw number-of-tcas-supported?      uint32
   +--rw mode-list* [tca-type]
     | +--rw tca-type                  opt-if-och-tca-types
     | +--rw min-threshold?            int32
     | +--rw max-threshold?            int32
   +--ro cur-osnr?                      int32
   +--ro cur-q-factor?                  int32
   +--ro uncorrected-words?             uint64
   +--ro fec-ber-mantissa?              uint32
   +--ro fec-ber-exponent?              int32

```

notifications:

```

+---n opt-if-och-central-frequency-change
| +--ro if-name?  -> /if:interfaces/interface/name
| +--ro new-opt-if-och-central-frequency
|   +--ro central-frequency?          uint32

```



```
+---n opt-if-och-mode-change
| +-ro if-name?   -> /if:interfaces/interface/name
| +-ro mode-id?           string
+---n opt-if-och-min-tca
  +-ro if-name?   -> /if:interfaces/interface/name
  +-ro tca-type?   opt-if-och-tca-types
```

5. Structure of the Yang Module

ietf-ext-xponder-wdm-if is a top level model for the support of this feature.

6. Yang Module

The ietf-ext-xponder-wdm-if is defined as an extension to ietf interfaces.

```
<CODE BEGINS> file "ietf-ext-xponder-wdm-if.yang"

module ietf-ext-xponder-wdm-if {
  namespace "urn:ietf:params:xml:ns:yang:ietf-ext-xponder-wdm-if";
  prefix ietf-ext-xponder-wdm-if;

  import ietf-interfaces {
    prefix if;
  }

  organization
    "IETF CCAMP
    Working Group";

  contact
    "WG Web:  <http://tools.ietf.org/wg/ccamp/>
    WG List:  <mailto:ccamp@ietf.org>

    Editor:   Dharini Hiremagalur
              <mailto:dharithi@juniper.net>";

  description
    "This module contains a collection of YANG definitions for
    configuring Optical interfaces.

    Copyright (c) 2016 IETF Trust and the persons identified
    as authors of the code. All rights reserved."
```


Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).";

```
revision "2018-10-22" {  
    description  
        "Revision 1.2";  
    reference  
        "";  
}
```

```
revision "2018-03-06" {  
    description  
        "Revision 1.1";  
    reference  
        "";  
}
```

```
revision "2017-03-06" {  
    description  
        "Revision 1.0";  
    reference  
        "";  
}
```

```
revision "2016-03-17" {  
    description  
        "Initial revision.";  
    reference  
        "";  
}
```

```
typedef dbm-t {  
    type decimal64 {  
        fraction-digits 2;  
        range "-50..-30 | -10..5 | 10000000";  
    }  
    description "  
        Amplifier Power in dBm ";  
}  
typedef opt-if-och-tca-types {
```

```
    type enumeration {  
        enum max-laser-linewdt {
```



```
    description " The maximum laser linewidth";
}
enum min-tx-power-tca {
    description " The min tx power tca";
}
enum max-tx-power-tca {
    description " The min tx power tca";
}
enum min-rx-power-tca{
    description " The min tx power tca";
}
enum max-rx-power-tca{
    description " The min tx power tca";
}
enum max-pol-power-diff-tca{
    description " The power diff. between polariz. tca";
}
enum max-pol-skew-diff-tca{
    description " The Skew between the two polariz. tca";
}
enum min-frequency-offset-tca{
    description " Min Frequency offset tca";
}
enum max-frequency-offset-tca{
    description " Max Frequency offset tca";
}
enum min-osnr-tca{
    description " Min OSNR tca";
}
enum max-osnr-tca{
    description " Max OSNR tca";
}
enum min-laser-temperature-tca{
    description " The min tx power tca";
}
enum max-laser-temperature-tca{
    description " Temperature tca";
}
enum min-fec-ber-tca{
    description " Min Pre Fec BER tca";
}
enum max-fec-ber-tca{
    description " Max Pre Fec BER tca";
}
enum min-q-tca{
    description "Min Q tca";
}
enum max-q-tca {
```



```
        description "Max Q tca";
    }
}
description " The different types of TCA's";
}

grouping opt-if-och-power {
    description "Interface optical Power";
    leaf output-power {
        type int32;
        units ".01dbm";
        description "The output power for this interface
                    in .01 dBm.
                    The setting of the output power is
                    optional";
    }

    leaf input-power {
        type int32;
        units ".01dbm";
        config false;
        description "The current input power of this
                    interface";
    }
}

grouping opt-if-och-tca-thresholds {
    description "Thresholds for TCA's";
    leaf tca-type {
        type opt-if-och-tca-types;
        description "type of the TCA eg TX Power";
    }
    leaf min-threshold {
        type int32;
        description " A TCA is generated if the variable is
                    less than this value";

    }
    leaf max-threshold {
        type int32;
        description " A TCA is generated if the variable is
                    more than this value";
    }
}

grouping opt-if-och-fec {
    description "Fec info";
```



```
    leaf fec-info {
      type string {
        length "1..255";
      }
      config false;
      description
        "Fec Type - eg GFEC";
    }
    leaf fec-bitrate {
      type string {
        length "1..255";
      }
      config false;
      description
        "Fec Overhead rate ";
    }
    leaf fec-gain {
      type string {
        length "1..255";
      }
      config false;
      description
        "Fec Overhead rate ";
    }
    leaf fec-ber-mantissa-threshold {
      type uint32;
      description " Mantissa of the FEC BER threshold";
    }
    leaf fec-ber-exponent-threshold {
      type int32;
      description " Exponent of the FEC BER threshold";
    }
  }
}

grouping opt-if-och-central-frequency {
  description "Interface Central Frequency";
  leaf central-frequency {
    type uint32;
    description " This parameter indicates the frequency
                  of this interface ";
  }
}

grouping opt-if-och-constellation {
  description "Optical constellation parameters";
  leaf i-center {
    type int32;
```



```
        units ".0001";
        config false;
        description "The In-phase coordinate of the selected
                     constellation symbol for this mode";
    }
    leaf q-center {
        type int32;
        units ".0001";
        config false;
        description "The Quadrature coordinate of the selected
                     constellation symbol for this mode";
    }
    leaf i-noise-variance {
        type int32;
        units ".001";
        config false;
        description "The Variance of the in-phase noise
                     component for this mode";
    }
    leaf q-noise-variance {
        type int32;
        units ".001";
        config false;
        description "The Variance of the quadrature noise
                     component for this mode";
    }
    leaf a-noise-variance {
        type int32;
        units ".001";
        config false;
        description "The Variance of the radial noise
                     component for this mode";
    }
    leaf p-noise-variance {
        type int32;
        units ".001";
        config false;
        description "The Variance of the phase noise
                     component for this mode";
    }
}

grouping opt-if-och-modulation-params {
    description "Optical modulation parameters for the lane";
    leaf modulation-format {
        type string {
            length "1..255";
        }
    }
}
```



```
        config false;
        description
            "Modulation format for this mode";
    }
    leaf bits-per-symbol {
        type uint32;
        description " This parameter the bits per symbol for
            this mode.";
    }
    leaf num-symbols-in-alphabet {
        type uint32;
        description " This parameter the bits per symbol for
            this mode.";
    }
    leaf symbols-index {
        type uint32;
        description " This parameter is the symbol index this
            mode.";
    }
    uses opt-if-och-constellation;
}

grouping opt-if-och-lane-param {
    description "Optical parameters for the lane";
    leaf number-of-lanes {
        type uint32;
        config false;
        description
            "Number of optical lanes of this interface";
    }
    leaf min-laser-temperature {
        type int32;
        units ".01C";
        config false;
        description
            "Minimum Laser Temperature of this mode for
            this interface";
    }
    leaf max-laser-temperature {
        type int32;
        units ".01C";
        config false;
        description
            "Maximum Laser Temperature of this mode for
```



```
        this interface";
    }
    leaf min-rx-optical-power {
        type dbm-t;
        config false;
        description
            "Minimum rx optical power of this mode for
             this interface";
    }
    leaf max-rx-optical-power {
        type dbm-t;
        config false;
        description
            "Maximum rx optical power of this mode for
             this interface";
    }
    leaf min-chromatic-dispersion {
        type int32;
        config false;
        description
            "Minimum chromatic dispersion of this mode
             for this interface";
    }
    leaf max-chromatic-dispersion {
        type int32;
        config false;
        description
            "Maximum chromatic dispersion of this
             mode for this interface";
    }
    leaf min-diff-group-delay {
        type int32;
        config false;
        description
            "Minimum Differential group delay of this
             mode for this interface";
    }
    leaf max-diff-group-delay {
        type int32;
        config false;
        description
            "Maximum Differential group delay of this
             mode for this interface";
    }
    uses opt-if-och-modulation-params;
}
```



```
grouping opt-if-och-tca-list {
  description "List of TCA's.";
  leaf number-of-tcas-supported {
    type uint32;
    description "Number of tcas
                  supported by this interface";
  }
  list mode-list {
    key "tca-type";
    description "List of the tcas";
    uses opt-if-och-tca-thresholds;
  }
}

grouping opt-if-och-fec-tca-thresholds {
  description "Pre FEC BER Thresholds for TCA's";
  leaf min-fec-ber-mantissa-threshold {
    type uint32;
    description " Min Mantissa of the FEC BER threshold";
  }
  leaf min-fec-ber-exponent-threshold {
    type int32;
    description " Min Exponent of the FEC BER threshold";
  }
  leaf max-fec-ber-mantissa-threshold {
    type uint32;
    description " Max Mantissa of the FEC BER threshold";
  }
  leaf max-fec-ber-exponent-threshold {
    type int32;
    description " Max Exponent of the FEC BER threshold";
  }
}

grouping opt-if-och-mode-params {
  description "OCh mode parameters.";
  leaf mode-id {
    type string {
      length "1..255";
    }
    description
      "Id for the OCh mode template";
  }
}
```



```
    leaf osnr-margin {
        type int32;
        units "dB";
        config false;
        description " OSNR margin to FEC threshold";
    }
    leaf q-margin {
        type int32;
        units "dB";
        config false;
        description " Q-Factor margin to FEC threshold";
    }
    uses opt-if-och-central-frequency;
    uses opt-if-och-power;
    uses opt-if-och-fec-tca-thresholds;
    uses opt-if-och-tca-list;
}

grouping opt-if-och-statistics {
    description "OCh statistics.";
    leaf cur-osnr {
        type int32;
        units "dB";
        config false;
        description " OSNR margin to FEC threshold";
    }
    leaf cur-q-factor {
        type int32;
        units "dB";
        config false;
        description " Q-Factor of the interface";
    }
    leaf uncorrected-words {
        type uint64;
        config false;
        description " Post FEC errored words";
    }
    leaf fec-ber-mantissa {
        type uint32;
        config false;
        description " Pre fec FEC errored words mantissa";
    }
    leaf fec-ber-exponent {
        type int32;
        config false;
        description " Pre fec FEC errored words exponent";
    }
}
```



```
}

grouping opt-if-och-mode {
  description "OCh mode template.";
  leaf mode-id {
    type string {
      length "1..255";
    }
    config false;
    description
      "Id for the OCh mode template";
  }
  leaf min-central-frequency {
    type uint32;
    config false;
    description "This parameter indicates the minimum
      frequency for this template ";
  }
  leaf max-central-frequency {
    type uint32;
    config false;
    description "This parameter indicates the minimum
      frequency for this template ";
  }
  leaf min-input-power {
    type dbm-t;
    config false;
    description "The minimum input power of this
      interface";
  }
  leaf max-input-power {
    type dbm-t;
    config false;
    description "The maximum input power of this
      interface";
  }
  leaf min-output-power {
    type dbm-t;
    config false;
    description "The minimum output power of this
      interface";
  }
  leaf max-output-power {
    type dbm-t;
    config false;
    description "The maximum output power of this
      interface";
  }
}
```



```
        leaf osnr-margin {
            type int32;
            units "dB";
            config false;
            description "OSNR margin to FEC threshold";
        }
        leaf q-margin {
            type int32;
            units "dB";
            config false;
            description "Q-Factor margin to FEC threshold";
        }
        uses opt-if-och-fec;
        uses opt-if-och-lane-param;
    }
```

```
grouping opt-if-och-mode-list {
    description "List of Mode list group.";
    leaf number-of-modes-supported {
        type uint32;
        description "Number of modes
                    supported by this interface";
    }
    list mode-list {
        key "mode-id";
        description "List of the modes ";
        uses opt-if-och-mode;
    }
}
```

```
notification opt-if-och-central-frequency-change {
    description "A change of Central Frequency has been
                detected.";
    leaf "if-name" {
        type leafref {
            path "/if:interfaces/if:interface/if:name";
        }
        description "Interface name";
    }
    container new-opt-if-och-central-frequency {
        description "The new Central Frequency of the
                    interface";
        uses opt-if-och-central-frequency;
    }
}
```



```
    }
  }

  notification opt-if-och-mode-change {
    description "A change of Mode Template has been
                detected.";
    leaf "if-name" {
      type leafref {
        path "/if:interfaces/if:interface/if:name";
      }
      description "Interface name";
    }
    leaf mode-id {
      type string {
        length "1..255";
      }
      description "Id for the OCh mode template";
    }
  }
}

notification opt-if-och-min-tca {
  description "A min output TCA notification.";
  leaf "if-name" {
    type leafref {
      path "/if:interfaces/if:interface/if:name";
    }
    description "Interface name";
  }
  leaf tca-type {
    type opt-if-och-tca-types;
    description "Type of TCA for eg min tx power TCA";
  }
}

augment "/if:interfaces/if:interface" {
  description "Parameters for an optical interface";
  container optIfOChRsSs {
    description "RsSs path configuration for an interface";
    container if-current-mode {
      description "Current mode template of the
                  interface";
      uses opt-if-och-mode;
    }

    container if-supported-mode {
      config false;
      description "Supported mode list of
```



```
        this interface";
        uses opt-if-och-mode-list;
    }
    container current-opt-if-och-mode-params {
        description "Current parameters of
                    this interface";
        uses opt-if-och-mode-params;
        uses opt-if-och-statistics;
    }
}
}
```

<CODE ENDS>

7. Security Considerations

The YANG module defined in this memo is designed to be accessed via the NETCONF protocol [[RFC6241](#)]. The lowest NETCONF layer is the secure transport layer and the mandatory-to-implement secure transport is SSH [[RFC6242](#)]. The NETCONF access control model [[RFC6536](#)] provides the means to restrict access for particular NETCONF users to a pre-configured subset of all available NETCONF protocol operation and content.

8. IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-interfaces:ietf-ext-xponder-wdm-if

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

prefix: ietf-ext-xponder-wdm-if reference: RFC XXXX

9. Acknowledgements

10. Contributors

Dean Bogdanovic
Westford
U.S.A.
email ivandean@gmail.com

Bernd Zeuner
Deutsche Telekom
Darmstadt
Germany
email B.Zeuner@telekom.de

Massimiliano Salsi
Juniper Networks
1133 Innovation Way
Sunnyvale, CA, 94089
U.S.A.
+1 408936847
email msalsi@juniper.net

Arnold Mattheus
Deutsche Telekom
Darmstadt
Germany
email a.mattheus@telekom.de

Manuel Paul
Deutsche Telekom
Berlin
Germany
email Manuel.Paul@telekom.de

Walid Wakim
Cisco
9501 Technology Blvd
ROSEMONT, ILLINOIS 60018
UNITED STATES
email wwakim@cisco.com

Kam Lam
Nokia
USA
+1 732 331 3476
kam.lam@nokia.com

11. References

11.1. Normative References

- [ITU.G694.1]
International Telecommunications Union, "Spectral grids for WDM applications: DWDM frequency grid", ITU-T Recommendation G.694.1, February 2012.
- [ITU.G698.2]
International Telecommunications Union, "Amplified multichannel dense wavelength division multiplexing applications with single channel optical interfaces", ITU-T Recommendation G.698.2, November 2009.
- [ITU.G709]
International Telecommunications Union, "Interface for the Optical Transport Network (OTN)", ITU-T Recommendation G.709, June 2016.
- [ITU.G7710]
International Telecommunications Union, "Common equipment management function requirements", ITU-T Recommendation G.7710, August 2017.
- [ITU.G798]
International Telecommunications Union, "Characteristics of optical transport network hierarchy equipment functional blocks", ITU-T Recommendation G.798, December 2017.
- [ITU.G8201]
International Telecommunications Union, "Error performance parameters and objectives for multi-operator international paths within the Optical Transport Network (OTN)", ITU-T Recommendation G.8201, April 2011.
- [ITU.G826]
International Telecommunications Union, "End-to-end error performance parameters and objectives for international, constant bit-rate digital paths and connections", ITU-T Recommendation G.826, December 2002.
- [ITU.G872]
International Telecommunications Union, "Architecture of optical transport networks", ITU-T Recommendation G.872, January 2017.

[ITU.G874]

International Telecommunications Union, "Management aspects of optical transport network elements", ITU-T Recommendation G.874, July 2010.

[ITU.G874.1]

International Telecommunications Union, "Optical transport network (OTN): Protocol-neutral management information model for the network element view", ITU-T Recommendation G.874.1, November 2016.

[ITU.G959.1]

International Telecommunications Union, "Optical transport network physical layer interfaces", ITU-T Recommendation G.959.1, November 2009.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, [RFC 2578](#), DOI 10.17487/RFC2578, April 1999, <<https://www.rfc-editor.org/info/rfc2578>>.

[RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD 58, [RFC 2579](#), DOI 10.17487/RFC2579, April 1999, <<https://www.rfc-editor.org/info/rfc2579>>.

[RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIv2", STD 58, [RFC 2580](#), DOI 10.17487/RFC2580, April 1999, <<https://www.rfc-editor.org/info/rfc2580>>.

[RFC2863] McCloghrie, K. and F. Kastenholz, "The Interfaces Group MIB", [RFC 2863](#), DOI 10.17487/RFC2863, June 2000, <<https://www.rfc-editor.org/info/rfc2863>>.

[RFC3591] Lam, H-K., Stewart, M., and A. Huynh, "Definitions of Managed Objects for the Optical Interface Type", [RFC 3591](#), DOI 10.17487/RFC3591, September 2003, <<https://www.rfc-editor.org/info/rfc3591>>.

- [RFC6205] Otani, T., Ed. and D. Li, Ed., "Generalized Labels for Lambda-Switch-Capable (LSC) Label Switching Routers", [RFC 6205](#), DOI 10.17487/RFC6205, March 2011, <<https://www.rfc-editor.org/info/rfc6205>>.

[11.2.](#) Informative References

- [I-D.ietf-ccamp-dwdm-if-mng-ctrl-fwk]
Kunze, R., Grammel, G., Beller, D., Galimberti, G., and J. Meuric, "A framework for Management and Control of DWDM optical interface parameters", [draft-ietf-ccamp-dwdm-if-mng-ctrl-fwk-11](#) (work in progress), June 2018.
- [RFC2629] Rose, M., "Writing I-Ds and RFCs using XML", [RFC 2629](#), DOI 10.17487/RFC2629, June 1999, <<https://www.rfc-editor.org/info/rfc2629>>.
- [RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", [RFC 3410](#), DOI 10.17487/RFC3410, December 2002, <<https://www.rfc-editor.org/info/rfc3410>>.
- [RFC4054] Strand, J., Ed. and A. Chiu, Ed., "Impairments and Other Constraints on Optical Layer Routing", [RFC 4054](#), DOI 10.17487/RFC4054, May 2005, <<https://www.rfc-editor.org/info/rfc4054>>.
- [RFC4181] Heard, C., Ed., "Guidelines for Authors and Reviewers of MIB Documents", [BCP 111](#), [RFC 4181](#), DOI 10.17487/RFC4181, September 2005, <<https://www.rfc-editor.org/info/rfc4181>>.

[Appendix A.](#) Change Log

This optional section should be removed before the internet draft is submitted to the IESG for publication as an RFC.

Note to RFC Editor: please remove this appendix before publication as an RFC.

[Appendix B.](#) Open Issues

Note to RFC Editor: please remove this appendix before publication as an RFC.

Authors' Addresses

Gabriele Galimberti (editor)
Cisco
Via Santa Maria Molgora, 48 c
20871 - Vimercate
Italy

Phone: +390392091462
Email: ggalimbe@cisco.com

Ruediger Kunze
Deutsche Telekom
Winterfeldtstr. 21-27
10781 Berlin
Germany

Phone: +491702275321
Email: RKunze@telekom.de

Dharini Hiremagalur (editor)
Juniper
1133 Innovation Way
Sunnyvale - 94089 California
USA

Email: dharinih@juniper.net

Gert Grammel (editor)
Juniper
Oskar-Schlemmer Str. 15
80807 Muenchen
Germany

Phone: +49 1725186386
Email: ggrammel@juniper.net

