

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: August 18, 2014

W. Cervený  
Arbor Networks  
R. Bonica  
Juniper Networks  
February 14, 2014

Benchmarking Neighbor Discovery  
draft-cervený-bmwg-ipv6-nd-04

Abstract

This document is a benchmarking instantiation of RFC 6583: "Operational Neighbor Discovery Problems" [RFC6583]. It describes a general testing procedure and measurements that can be performed to evaluate how the problems described in RFC 6583 may impact the functionality or performance of intermediate nodes.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC 2119 [RFC2119].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 18, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

1. Introduction . . . . .	2
2. Terminology . . . . .	3
3. Overview of Relevant NDP and Intermediate Node Behavior . . .	3
4. Test Setup . . . . .	5
4.1. Testing Interfaces . . . . .	6
5. Modifiers (Variables) . . . . .	6
5.1. Frequency of NDP Triggering Packets . . . . .	6
6. Tests . . . . .	7
6.1. Stale Entry Time Determination . . . . .	7
6.1.1. General Testing Procedure . . . . .	7
6.2. Neighbor Cache Exhaustion Determination . . . . .	7
6.2.1. General Testing Procedure . . . . .	8
6.3. Determine Neighbor Discovery Behavior during address scan	8
6.3.1. General Testing Procedure . . . . .	8
6.4. Pre-established Flow Treatment . . . . .	8
6.4.1. General Testing Procedure . . . . .	8
6.5. Stopped Flow Recovery Behavior . . . . .	9
6.5.1. General Testing Procedure . . . . .	9
7. Measurements Explicitly Excluded . . . . .	9
7.1. DUT CPU Utilization . . . . .	9
7.2. Malformed Packets . . . . .	9
8. DUT Initialization . . . . .	9
9. IANA Considerations . . . . .	10
10. Security Considerations . . . . .	10
11. Acknowledgements . . . . .	10
12. References . . . . .	10
12.1. Normative References . . . . .	10
12.2. Informative References . . . . .	11
Authors' Addresses . . . . .	11

## 1. Introduction

This document is a benchmarking instantiation of RFC 6583: "Operational Neighbor Discovery Problems" [RFC6583]. It describes a general testing procedure and measurements that can be performed to evaluate how the problems described in RFC 6583 may impact the functionality or performance of intermediate nodes.

## 2. Terminology

**Intermediate Node** A router, switch, firewall or any other device which separates end-nodes. The tests in this document can be completed with any intermediate node which maintains a neighbor cache, although not all measurements and performance characteristics may apply.

**Neighbor Cache** The neighbor cache is a database which correlates the link-layer address and the adjacent interface with an IPv6 address.

**Neighbor Discovery** See Section 1 of RFC 4861 [RFC4861]

**Scanner Network** The network from which the scanning tested is connected.

**Scanning Interface** The interface from which the scanning activity is conducted.

**Stale Entry Time** This is the duration for which a neighbor cache entry marked "Reachable" will continue to be marked "Reachable" if an update for the address is not received.

**Target Network** The network for which the scanning tests is targeted.

**Target Network Destination Interface** The interface that resides on the target network, which is primarily used to measure DUT performance while the scanning activity is occurring.

## 3. Overview of Relevant NDP and Intermediate Node Behavior

In a traditional network, an intermediate node must support a mapping between a connected node's IP address and the connected node's link-layer address and interface the node is connected to. With IPv4, this process is handled by ARP [RFC0826]. With IPv6, this process is handled by NDP and is documented in [RFC4861]. With IPv6, when a packet arrives on one of an intermediate node's interfaces and the destination address is determined to be reachable via an adjacent network:

1. The intermediate node first determines if the destination IPv6 address is present in its neighbor cache.
2. If the address is present in the neighbor cache, the intermediate node forwards the packet to the destination node using the appropriate link-layer address and interface.

3. If the destination IPv6 address is not in the intermediate node's neighbor cache:
  1. An entry for the IPv6 address is added to the neighbor cache and the entry is marked "INCOMPLETE".
  2. The intermediate node sends a neighbor solicitation packet to the solicited-node multicast address on the interface considered on-link.
  3. If a solicited neighbor advertisement for the IPv6 address is received by the intermediate node, the neighbor cache entry is marked "REACHABLE" and remains in this state for 30 seconds.
  4. If a neighbor advertisement is not received, the intermediate node will continue sending neighbor solicitation packets every second until either a neighbor solicitation is received or the maximum number of solicitations has been sent. If a neighbor advertisement is not received in this period, the entry can be discarded.

There are two scenarios where a neighbor cache can grow to a very large size:

1. There are a large number of real nodes connected via an intermediate node's interface and a large number of these nodes are sending and receiving traffic simultaneously.
2. There are a large number of addresses for which a scanning activity is occurring and no real node will respond to the neighbor solicitation. This scanning activity can be unintentional or malicious. In addition to maintaining the "INCOMPLETE" neighbor cache entry, the intermediate node must send a neighbor solicitation packet every second for the maximum number of solicitations. With today's network link bandwidths, a scanning event could cause a lot of entries to be added to the neighbor cache and solicited for in the time that it takes for a neighbor cache entry to be discarded.

An intermediate node's neighbor cache is of a finite size and can only accommodate a specific number of entries, which can be limited by available memory or a preset operating system limit. If the maximum number of entries in a neighbor cache is reached, the intermediate node must either drop an existing entry to make space for the new entry or deny the new IP address to MAC address/interface mapping with an entry in the neighbor cache. In an extreme

case, the intermediate node's memory may become exhausted, causing the intermediate node to crash or begin paging memory.

At the core of the neighbor discovery problems presented in RFC 6583 [RFC6583], unintentional or malicious IPv6 traffic can transit the intermediate node that resembles an IP address scan similar to an IPv4-based network scan. Unlike IPv4 networks, an IPv6 end network is typically configured with a /64 address block, allowing for upwards of  $2^{64}$  addresses. When a network node attempts to scan all the addresses in a /64 address block directly attached to the intermediate node, it is possible to create a huge amount of state in the intermediate node's neighbor cache, which may stress processing or memory resources.

Section 7.1 of RFC 6583 recommends how intermediate nodes should behave when the neighbor cache is exceeded. Section 6 of RFC 6583 [RFC6583] recommends how damage from an IPv6 address scan may be mitigated. Section 6.2 of RFC 6583 [RFC6583] discusses queue tuning.

#### 4. Test Setup

The network needs to minimally have two subnets: one from which the scanner(s) source their scanning activity and the other which is the target network of the address scans.


It is assumed that the latency for all network segments is negligible. By default, the target network's subnet shall be 64-bits in length, although some tests may involve increasing the prefix length.

Although packet size shouldn't have a direct impact, packet per second (pps) rates will have an impact. Smaller packet sizes should be utilized to facilitate higher packet per second rates.

For purposes of this test, the packet type being sent by the scanning device isn't important, although most scanning applications might want to send packets that would elicit responses from nodes within a subnet (such as an ICMPv6 echo request). Since it is not intended that responses be evoked from the target network node, such packets aren't necessary.

At the beginning of each test the intermediate node should be initialized. Minimally, the neighbor cache should be cleared.

Basic format of test network. Note that optional "non-participating network" is a third network not related to the scanner or target network.



#### 4.1. Testing Interfaces

Two tester interfaces are configured for most tests:

- o Scanning source (src) interface: This is the interface from which test packets are sourced. This interface sources traffic to destination IPv6 addresses on the target network from a single link-local address, similar to how an adjacent intermediate node would transit traffic through the intermediate node.
- o Target network destination (dst) interface: This interface responds to neighbor solicitations as appropriate and confirms when an intermediate node has forwarded a packet to the interface for consumption. Where appropriate, the target network destination interface will respond to neighbor solicitations with a unique link-layer address per IPv6 address solicited.

#### 5. Modifiers (Variables)

##### 5.1. Frequency of NDP Triggering Packets

The frequency of NDP triggering packets could be as high as the maximum packet per second rate that the scanner network will support (or is rated for). However, it may not be necessary to send packets at a particularly high rate. In fact a goal of testing could be to identify if the DUT is able to withstand scans at rates which otherwise would not impact the performance of the DUT.

Optimistically, the scanning rate should be incremented until the DUT's performance begins deteriorating. Depending on the software and system being used to implement the scanning, it may be challenging to achieve a sufficient rate. Where this maximum threshold cannot be determined, the test results should note the highest rate tested and that DUT performance deterioration was not noticed at this rate.

The lowest rate tested should be the rate for which packets can be expected to have an impact on the DUT -- this value is of course, subjective.

## 6. Tests

### 6.1. Stale Entry Time Determination

This test determines the time interval when the intermediate node (DUT) identifies an address as stale.

RFC 4861, section 6.3.2 [RFC4861] states that an address can be marked "stale" at a random value between 15 and 45 seconds (as defined via constants in the RFC). This test confirms what value is being used by the intermediate node. Note that RFC 4861 states that this random time can be changed "at least every few hours."

#### 6.1.1. General Testing Procedure

1. Send a packet to an address in target network. Observe that the intermediate node sends neighbor solicitation to the solicited-node multicast address on the target network, for which tester destination interface responds with a neighbor advertisement. The intermediate node should create an entry in neighbor cache for the address, marking the address as "reachable". The packet should be forwarded to the tester destination interface.
2. Wait one second.
3. Send packet from tester source address to tester destination address. Determine if intermediate node sends neighbor solicitation. If intermediate node does send neighbor solicitation, the stale entry time has not been exceeded.
4. If a neighbor solicitation was not sent after one second, wait 2 seconds send packet. If neighbor solicitation was not received, incrementing the wait time by one second and repeat this process until the intermediate node sends a neighbor solicitation for the address. The stale entry time is the number of seconds that elapsed between the first packet and when the neighbor solicitation was sent.

### 6.2. Neighbor Cache Exhaustion Determination

Discover the point at which the neighbor cache is exhausted and evaluate intermediate node behavior when this threshold is reached.

#### 6.2.1. General Testing Procedure

1. Send packets incrementally to addresses, simultaneously resending packets of previously discovered addresses within the stale entry time.
2. Observe what happens when one address greater than the maximum neighbor cache size ("n") is reached. When "n+1" is reached, if either the first or most recent cache entry are dropped, this may be acceptable.
3. Confirm intermediate node doesn't crash when "n+1" is reached.

#### 6.3. Determine Neighbor Discovery Behavior during address scan

This test is a prerequisite for later tests, for which it is confirmed how an intermediate node behaves in the presence of an address scan. If adding the flow after the address scan results in abnormal behavior, it will be difficult to evaluate correct behavior for later tests.

##### 6.3.1. General Testing Procedure

1. Start sending  $n/2$  (n determined in "Neighbor Cache Exhaustion" test) flows at a rate of one packet per second to valid addresses (valid addresses are defined as addresses for which the tester responds to neighbor solicitation).
2. Send  $n/2 + 1$  flow and determine if intermediate node takes a long time to process NS/NA for valid addresses.

#### 6.4. Pre-established Flow Treatment

This test expands on "Determine neighbor discovery behavior during address scan". This test confirms behavior described in RFC 6483, where it is expected that in the presence of an address scan, flows for successfully cached addresses will continue to flow across the intermediate node.

##### 6.4.1. General Testing Procedure

1. Start  $n/2$  flows (one packet per second per flow) to valid addresses.
2. Start address scan to invalid addresses (addresses without responding host).



3. Determine if flows continue for existing, valid flows continue without unexpected loss or delay.

#### 6.5. Stopped Flow Recovery Behavior

This test determines how a stopped flow recovers from the stale state in the presence of an address scan. It confirms that the intermediate node continues to prefer addresses that had previously been added to the neighbor cache, even when the address is marked "stale" in the neighbor cache.

##### 6.5.1. General Testing Procedure

1. Start  $n/2$  flows (one packet per second per flow) to valid addresses.
2. Start address scan to invalid addresses (addresses without responding host).
3. Stop one flow to valid address.
4. Wait stale time period for address to be marked "stale" in intermediate node neighbor cache.
5. Restart stopped flow and confirm that address is marked "active" immediately (not stuck behind address scan).

#### 7. Measurements Explicitly Excluded

These are measurements which aren't recommended because of the itemized reasons below:

##### 7.1. DUT CPU Utilization

This measurement relies on the DUT to provide utilization information, which is subjective.

##### 7.2. Malformed Packets

This benchmarking test is not intended to test DUT behavior in the presence of malformed packets.

#### 8. DUT Initialization

At the beginning of each test, the neighbor cache of the DUT should be initialized.

## 9. IANA Considerations

This document makes no request of IANA.

Note to RFC Editor: this section may be removed on publication as an RFC.

## 10. Security Considerations

Benchmarking activities as described in this memo are limited to technology characterization using controlled stimuli in a laboratory environment, with dedicated address space and the constraints specified in the sections above.

The benchmarking network topology will be an independent test setup and MUST NOT be connected to devices that may forward the test traffic into a production network, or misroute traffic to the test management network.

Further, benchmarking is performed on a "black-box" basis, relying solely on measurements observable external to the DUT/SUT. Special capabilities SHOULD NOT exist in the DUT/SUT specifically for benchmarking purposes.

Any implications for network security arising from the DUT/SUT SHOULD be identical in the lab and in production networks.

## 11. Acknowledgements

Helpful comments and suggestions were offered by Al Morton, Joel Jaeggli, Nalini Elkins, Scott Bradner, and Ram Krishnan, on the BMWG e-mail list and at BMWG meetings. Precise grammatical corrections and suggestions were offered by Ann Cerveny.

## 12. References

### 12.1. Normative References

- [RFC0826] Plummer, D., "Ethernet Address Resolution Protocol: Or converting network protocol addresses to 48.bit Ethernet address for transmission on Ethernet hardware", STD 37, RFC 826, November 1982.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2544] Bradner, S. and J. McQuaid, "Benchmarking Methodology for Network Interconnect Devices", RFC 2544, March 1999.

- [RFC4861] Narten, T., Nordmark, E., Simpson, W., and H. Soliman, "Neighbor Discovery for IP version 6 (IPv6)", RFC 4861, September 2007.
- [RFC5180] Popoviciu, C., Hamza, A., Van de Velde, G., and D. Dugatkin, "IPv6 Benchmarking Methodology for Network Interconnect Devices", RFC 5180, May 2008.
- [RFC6583] Gashinsky, I., Jaeggli, J., and W. Kumari, "Operational Neighbor Discovery Problems", RFC 6583, March 2012.

## 12.2. Informative References

- [RFC7048] Nordmark, E. and I. Gashinsky, "Neighbor Unreachability Detection Is Too Impatient", RFC 7048, January 2014.

## Authors' Addresses

Bill Cerveney  
Arbor Networks  
2727 South State Street  
Ann Arbor, MI 48104  
USA

Email: [wcerveney@arbor.net](mailto:wcerveney@arbor.net)

Ron Bonica  
Juniper Networks  
2251 Corporate Park Drive  
Herndon, VA 20170  
USA

Email: [rbonica@juniper.net](mailto:rbonica@juniper.net)