

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: August 18, 2014

F. Zhang, Ed.
Huawei
O. Gonzalez de Dios, Ed.
Telefonica Global CTO
D. Li
Huawei
C. Margaria

M. Hartley
Z. Ali
Cisco
February 14, 2014

RSVP-TE Extensions for Collecting SRLG Information
draft-ietf-ccamp-rsvp-te-srlg-collect-04

Abstract

This document provides extensions for the Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) to support automatic collection of Shared Risk Link Group (SRLG) Information for the TE link formed by a LSP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 18, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. RSVP-TE Requirements	3
2.1. SRLG Collection Indication	3
2.2. SRLG Collection	3
2.3. SRLG Update	3
3. RSVP-TE Extensions (Encoding)	3
3.1. SRLG Collection Flag	3
3.2. SRLG sub-object	4
4. Signaling Procedures	4
4.1. SRLG Collection	4
4.2. SRLG Update	6
5. Manageability Considerations	6
5.1. Policy Configuration	6
5.2. Coherent SRLG IDs	6
6. Security Considerations	7
7. IANA Considerations	7
7.1. RSVP Attribute Bit Flags	7
7.2. ROUTE_RECORD Object	7
7.3. Policy Control Failure Error subcodes	8
8. Acknowledgements	8
9. Normative References	8
Authors' Addresses	9

1. Introduction

It is important to understand which TE links in the network might be at risk from the same failures. In this sense, a set of links may constitute a 'shared risk link group' (SRLG) if they share a resource whose failure may affect all links in the set [RFC4202].

On the other hand, as described in [RFC4206] and [RFC6107], H-LSP (Hierarchical LSP) or S-LSP (stitched LSP) can be used for carrying one or more other LSPs. Both of the H-LSP and S-LSP can be formed as a TE link. In such cases, it is important to know the SRLG information of the LSPs that will be used to carry further LSPs.

This document provides an automatic mechanism to collect the SRLG for the TE link formed by a LSP. Note that how to use the collected SRLG information is out of scope of this document

2. RSVP-TE Requirements

2.1. SRLG Collection Indication

The head nodes of the LSP must be capable of indicating whether the SRLG information of the LSP should be collected during the signaling procedure of setting up an LSP. SRLG information should not be collected without an explicit request for it being made by the head node.

2.2. SRLG Collection

If requested, the SRLG information should be collected during the setup of an LSP. The endpoints of the LSP may use the collected SRLG information and use it for routing, sharing and TE link configuration purposes.

2.3. SRLG Update

When the SRLG information of an existing LSP for which SRLG information was collected during signaling changes, the relevant nodes of the LSP must be capable of updating the SRLG information of the LSP. This means that that the signaling procedure must be capable of updating the new SRLG information.

3. RSVP-TE Extensions (Encoding)

3.1. SRLG Collection Flag

In order to indicate nodes that SRLG collection is desired, this document defines a new flag in the Attribute Flags TLV, which is carried in an LSP_REQUIRED_ATTRIBUTES or LSP_ATTRIBUTE Object:


- o Bit Number (to be assigned by IANA, recommended bit 12): SRLG Collection flag

The SRLG Collection flag is meaningful on a Path message. If the SRLG Collection flag is set to 1, it means that the SRLG information should be reported to the head and tail node along the setup of the LSP.

The rules of the processing of the Attribute Flags TLV are not changed.

3.2. SRLG sub-object

This document defines a new RRO sub-object (ROUTE_RECORD sub-object) to record the SRLG information of the LSP. Its format is modeled on the RRO sub-objects defined in RFC 3209 [RFC3209].



Type

The type of the sub-object, to be assigned by IANA, which is recommended 34.

Length

The Length contains the total length of the sub-object in bytes, including the Type and Length fields. The Length depends on the number of SRLG IDs.

The rules of the processing of the LSP_REQUIRED_ATTRIBUTES, LSP_ATTRIBUTE and ROUTE_RECORD Objects are not changed.

4. Signaling Procedures

4.1. SRLG Collection

Typically, the head node gets the route information of an LSP by adding a RRO which contains the sender's IP addresses in the Path message. If a head node also desires SRLG recording, it sets the SRLG Collection Flag in the Attribute Flags TLV which can be carried either in an LSP_REQUIRED_ATTRIBUTES Object if the collection is mandatory, or in an LSP_ATTRIBUTES Object if the collection is desired, but not mandatory

When a node receives a Path message which carries an LSP_REQUIRED_ATTRIBUTES Object and the SRLG Collection Flag is set, if local policy determines that the SRLG information should not be provided to the endpoints, it MUST return a PathErr message with

Error Code 2 (policy) and Error subcode "SRLG Recording Rejected" (value to be assigned by IANA, suggest value 108) to reject the Path message.

When a node receives a Path message which carries an LSP_ATTRIBUTES Object and the SRLG Collection Flag is set, if local policy determines that the SRLG information should not be provided to the endpoints, the Path message SHOULD NOT be rejected due to SRLG recording restriction and the Path message SHOULD be forwarded without the SRLG sub-object(s) in the Path RRO.

If local policy permits the recording of the SRLG information, the processing node SHOULD add an SRLG sub-object to the RRO to carry the local SRLG information. It then forwards the Path message to the next node in the downstream direction.

Following the steps described above, the intermediate nodes of the LSP can collect the SRLG information in the RRO during the forwarding of the Path message hop by hop. When the Path message arrives at the tail node, the tail node can get the SRLG information from the RRO.

Before the Resv message is sent to the upstream node, the tail node adds the SRLG subobject with the SRLG value(s) associated with the local hop to the Resv RRO in a similar manner to that specified above for the addition of Path RRO sub-objects by midpoint nodes.

When a node receives a Resv message for an LSP for which SRLG Collection is specified, if local policy determines that the SRLG information should not be provided to the endpoints, if the SRLG-recording request was in a LSP_REQUIRED_ATTRIBUTES object, then a ResvErr with Error code 2 (policy) and Error subcode "SRLG Recording Rejected" (value to be assigned by IANA, suggest value 108) MUST be sent. If the request was in a LSP_ATTRIBUTES object, then a ResvErr SHOULD NOT be generated, but SRLG information must not be added in the RRO. Otherwise, if local policy allows to provide the SRLG information, it MUST add an SRLG sub-object to the RRO to carry the SRLG information in the upstream direction. When the Resv message arrives at the head node, the head node can get the SRLG information from the RRO in the same way as the tail node.

Note that a link's SRLG information for the upstream direction cannot be assumed to be the same as that in the downstream.

- o For Path and Resv messages for a unidirectional LSP, a node SHOULD include SRLG sub-objects in the RRO for the downstream data link only.

- o For Path and Resv messages for a bidirectional LSP, a node SHOULD include SRLG sub-objects in the RRO for both the upstream data link and the downstream data link from the local node. In this case, the node MUST include the information in the same order for both Path messages and Resv messages. That is, the SRLG sub-object for the upstream link is added to the RRO before the SRLG sub-object for the downstream link.

Based on the above procedure, the endpoints can get the SRLG information automatically. Then the endpoints can for instance advertise it as a TE link to the routing instance based on the procedure described in [RFC6107] and configure the SRLG information of the FA automatically.

4.2. SRLG Update

When the SRLG information of a link is changed, the LSPs using that link should be aware of the changes. The procedures defined in Section 4.4.3 of RFC 3209 [RFC3209] MUST be used to refresh the SRLG information if the SRLG change is to be communicated to other nodes according to the local node's policy. If local policy is that the SRLG change should be suppressed or would result in no change to the previously signaled SRLG-list, the node need not send an update.

5. Manageability Considerations

5.1. Policy Configuration

In a border node of inter-domain or inter-layer network, the following SRLG processing policy should be capable of being configured:

- o Whether the SRLG IDs of the domain or specific layer network can be exposed to the nodes outside the domain or layer network, or whether they should be summarized or removed entirely.

5.2. Coherent SRLG IDs

In a multi-layer multi-domain scenario, SRLG ids may be configured by different management entities in each layer/domain. In such scenarios, maintaining a coherent set of SRLG IDs is a key requirement in order to be able to use the SRLG information properly. Thus, SRLG IDs must be unique. Note that current procedure is targeted towards a scenario where the different layers and domains belong to the same operator, or to several coordinated administrative groups. Ensuring the aforementioned coherence of SRLG IDs is beyond the scope of this document.

Further scenarios, where coherence in the SRLG IDs cannot be guaranteed are out of the scope of the present document and are left for further study.

6. Security Considerations

This document does not introduce any additional security issues above those identified in [RFC5920][RFC3209][RFC3473]

7. IANA Considerations

7.1. RSVP Attribute Bit Flags

IANA has created a registry and manages the space of attributes bit flags of Attribute Flags TLV, as described in section 11.3 of [RFC5420], in the "Attributes TLV Space" section of the "Resource Reservation Protocol-Traffic Engineering (RSVP-TE) Parameters" registry located in <https://www.iana.org/assignments/rsvp-te-parameters/rsvp-te-parameters.xhtml>. It is requested that IANA makes assignments from the Attribute Bit Flags.

This document introduces a new Attribute Bit Flag:

- o Bit number: TBD (10)
- o Defining RFC: this I-D
- o Name of bit: SRLG Collection Flag
- o The meaning of the SRLG Collection Flag is defined in this I-D.

7.2. ROUTE_RECORD Object

IANA has made the following assignments in the "Class Names, Class Numbers, and Class Types" section of the "RSVP PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-parameters>. We request that IANA make assignments from the ROUTE_RECORD RFC 3209 [RFC3209] portions of this registry.

This document introduces a new RRO sub-object:

Type	Name	Reference
-----	-----	-----
TBD (34)	SRLG sub-object	This I-D

7.3. Policy Control Failure Error subcodes

IANA has made the following assignments in the "Error Codes and Globally-Defined Error Value Sub-Codes" section of the "RSVP PARAMETERS" registry located at <http://www.iana.org/assignments/rsvp-parameters>. We request that IANA make assignments from the Policy Control Failure Sub-Codes registry.

This document introduces a new Policy Control Failure Error sub-code:

- o Error sub-code: TBD (108)
- o Defining RFC: this I-D
- o Name of error sub-code: SRLG Recording Rejected
- o The meaning of the SRLG Recording Rejected error sub-code is defined in this I-D

8. Acknowledgements

The authors would like to thank Igor Bryskin, Ramon Casellas, Lou Berger and Alan Davey for their useful comments and improvements to the document.

9. Normative References

- [RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", RFC 3209, December 2001.
- [RFC3473] Berger, L., "Generalized Multi-Protocol Label Switching (GMPLS) Signaling Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) Extensions", RFC 3473, January 2003.
- [RFC4202] Kompella, K. and Y. Rekhter, "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", RFC 4202, October 2005.
- [RFC4206] Kompella, K. and Y. Rekhter, "Label Switched Paths (LSP) Hierarchy with Generalized Multi-Protocol Label Switching (GMPLS) Traffic Engineering (TE)", RFC 4206, October 2005.
- [RFC5150] Ayyangar, A., Kompella, K., Vasseur, JP., and A. Farrel, "Label Switched Path Stitching with Generalized Multiprotocol Label Switching Traffic Engineering (GMPLS TE)", RFC 5150, February 2008.

[RFC5920] Fang, L., "Security Framework for MPLS and GMPLS Networks", RFC 5920, July 2010.

[RFC6107] Shiomoto, K. and A. Farrel, "Procedures for Dynamically Signaled Hierarchical Label Switched Paths", RFC 6107, February 2011.

Authors' Addresses

Fatai Zhang (editor)
Huawei
F3-5-B RD Center
Bantian, Longgang District, Shenzhen 518129
P.R.China

Email: zhangfatai@huawei.com

Oscar Gonzalez de Dios (editor)
Telefonica Global CTO
Don Ramon de la Cruz
Madrid 28006
Spain

Phone: +34 913328832
Email: ogondio@tid.es

Dan Li
Huawei
F3-5-B RD Center
Bantian, Longgang District, Shenzhen 518129
P.R.China

Email: danli@huawei.com

Cyril Margaria
SabenerStr. 44
Munich 81547
Germany

Phone: +49 89 5159 16934
Email: cyril.margaria@gmail.com

Matt Hartley
Cisco

Email: mhartley@cisco.com

Zafar Ali
Cisco

Email: zali@cisco.com