

Benchmarking Methodology Working Group
Internet-Draft
Intended status: Informational
Expires: May 16, 2015

C. Davids
Illinois Institute of Technology
V. Gurbani
Bell Laboratories,
Alcatel-Lucent
S. Poretsky
Allot Communications
November 12, 2014

Terminology for Benchmarking Session Initiation Protocol (SIP) Devices:
Basic session setup and registration
draft-ietf-bmwg-sip-bench-term-12

Abstract

This document provides a terminology for benchmarking the Session Initiation Protocol (SIP) performance of devices. Methodology related to benchmarking SIP devices is described in the companion methodology document. Using these two documents, benchmarks can be obtained and compared for different types of devices such as SIP Proxy Servers, Registrars and Session Border Controllers. The term "performance" in this context means the capacity of the device-under-test (DUT) to process SIP messages. Media streams are used only to study how they impact the signaling behavior. The intent of the two documents is to provide a normalized set of tests that will enable an objective comparison of the capacity of SIP devices. Test setup parameters and a methodology is necessary because SIP allows a wide range of configuration and operational conditions that can influence performance benchmark measurements. A standard terminology and methodology will ensure that benchmarks have consistent definition and were obtained following the same procedures.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 16, 2015.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Terminology	4
2. Introduction	4
2.1. Scope	6
3. Term Definitions	7
3.1. Protocol Components	7
3.1.1. Session	7
3.1.2. Signaling Plane	8
3.1.3. Media Plane	8
3.1.4. Associated Media	9
3.1.5. Overload	9
3.1.6. Session Attempt	10
3.1.7. Established Session	10
3.1.8. Session Attempt Failure	11
3.2. Test Components	11
3.2.1. Emulated Agent	11
3.2.2. Signaling Server	12
3.2.3. SIP Transport Protocol	12
3.3. Test Setup Parameters	13
3.3.1. Session Attempt Rate	13
3.3.2. Establishment Threshold Time	13
3.3.3. Session Duration	14
3.3.4. Media Packet Size	14
3.3.5. Codec Type	15
3.4. Benchmarks	15
3.4.1. Session Establishment Rate	16
3.4.2. Registration Rate	16
3.4.3. Registration Attempt Rate	17
4. IANA Considerations	17
5. Security Considerations	17
6. Acknowledgments	18
7. References	18
7.1. Normative References	18
7.2. Informational References	19
Authors' Addresses	19

1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14, RFC2119 [RFC2119]. RFC 2119 defines the use of these key words to help make the intent of standards track documents as clear as possible. While this document uses these keywords, this document is not a standards track document. The term Throughput is defined in RFC2544 [RFC2544].

For the sake of clarity and continuity, this document adopts the template for definitions set out in Section 2 of RFC 1242 [RFC1242].

The term Device Under Test (DUT) is defined in the following BMWG documents:

Device Under Test (DUT) (c.f., Section 3.1.1 RFC 2285 [RFC2285]).

Many commonly used SIP terms in this document are defined in RFC 3261 [RFC3261]. For convenience the most important of these are reproduced below. Use of these terms in this document is consistent with their corresponding definition in the base SIP specification [RFC3261] as amended by [RFC4320], [RFC5393] and [RFC6026].

- o Call Stateful: A proxy is call stateful if it retains state for a dialog from the initiating INVITE to the terminating BYE request. A call stateful proxy is always transaction stateful, but the converse is not necessarily true.
- o Stateful Proxy: A logical entity, as defined by [RFC3261], that maintains the client and server transaction state machines during the processing of a request. (Also known as a transaction stateful proxy.) The behavior of a stateful proxy is further defined in Section 16 of RFC 3261 [RFC3261]. A transaction stateful proxy is not the same as a call stateful proxy.
- o Back-to-back User Agent: A back-to-back user agent (B2BUA) is a logical entity that receives a request and processes it as a user agent server (UAS). In order to determine how the request should be answered, it acts as a user agent client (UAC) and generates requests. Unlike a proxy server, it maintains dialog state and must participate in all requests sent on the dialogues it has established. Since it is a concatenation of a UAC and a UAS, no explicit definitions are needed for its behavior.

2. Introduction

Service Providers and IT Organizations deliver Voice Over IP (VoIP) and Multimedia network services based on the IETF Session Initiation

Protocol (SIP) [RFC3261]. SIP is a signaling protocol originally intended to be used to dynamically establish, disconnect and modify streams of media between end users. As it has evolved it has been adopted for use in a growing number of services and applications. Many of these result in the creation of a media session, but some do not. Examples of this latter group include text messaging and subscription services. The set of benchmarking terms provided in this document is intended for use with any SIP-enabled device performing SIP functions in the interior of the network, whether or not these result in the creation of media sessions. The performance of end-user devices is outside the scope of this document.

A number of networking devices have been developed to support SIP-based VoIP services. These include SIP Servers, Session Border Controllers (SBC) and Back-to-back User Agents (B2BUA). These devices contain a mix of voice and IP functions whose performance may be reported using metrics defined by the equipment manufacturer or vendor. The Service Provider or IT Organization seeking to compare the performance of such devices will not be able to do so using these vendor-specific metrics, whose conditions of test and algorithms for collection are often unspecified.

SIP functional elements and the devices that include them can be configured many different ways and can be organized into various topologies. These configuration and topological choices impact the value of any chosen signaling benchmark. Unless these conditions-of-test are defined, a true comparison of performance metrics across multiple vendor implementations will not be possible.

Some SIP-enabled devices terminate or relay media as well as signaling. The processing of media by the device impacts the signaling performance. As a result, the conditions-of-test must include information as to whether or not the device under test processes media. If the device processes media during the test, a description of the media must be provided. This document and its companion methodology document [I-D.ietf-bmwg-sip-bench-meth] provide a set of black-box benchmarks for describing and comparing the performance of devices that incorporate the SIP User Agent Client and Server functions and that operate in the network's core.

The definition of SIP performance benchmarks necessarily includes definitions of Test Setup Parameters and a test methodology. These enable the Tester to perform benchmarking tests on different devices and to achieve comparable results. This document provides a common set of definitions for Test Components, Test Setup Parameters, and Benchmarks. All the benchmarks defined are black-box measurements of the SIP signaling plane. The Test Setup Parameters and Benchmarks defined in this document are intended for use with the companion

Methodology document.

2.1. Scope

The scope of this document is summarized as follows:

- o This terminology document describes SIP signaling performance benchmarks for black-box measurements of SIP networking devices. Stress and debug scenarios are not addressed in this document.
- o The DUT must be RFC 3261 capable network equipment. This may be a Registrar, Redirect Server, or Stateful Proxy. This document does not require the intermediary to assume the role of a stateless proxy. A DUT may also include a B2BUA, SBC functionality.
- o The Tester acts as multiple "Emulated Agents" (EA) that initiate (or respond to) SIP messages as session endpoints and source (or receive) associated media for established connections.
- o SIP Signaling in presence of media
 - * The media performance is not benchmarked.
 - * Some tests require media, but the use of media is limited to observing the performance of SIP signaling. Tests that require media will annotate the media characteristics as a condition of test.
 - * The type of DUT dictates whether the associated media streams traverse the DUT. Both scenarios are within the scope of this document.
 - * SIP is frequently used to create media streams; the signaling plane and media plane are treated as orthogonal to each other in this document. While many devices support the creation of media streams, benchmarks that measure the performance of these streams are outside the scope of this document and its companion methodology document [I-D.ietf-bmwg-sip-bench-meth]. Tests may be performed with or without the creation of media streams. The presence or absence of media streams MUST be noted as a condition of the test as the performance of SIP devices may vary accordingly. Even if the media is used during benchmarking, only the SIP performance will be benchmarked, not the media performance or quality.
- o Both INVITE and non-INVITE scenarios (registrations) are addressed in this document. However, benchmarking SIP presence or subscribe-notify extensions is not a part of this document.
- o Different transport -- such as UDP, TCP, SCTP, or TLS -- may be used. The specific transport mechanism MUST be noted as a condition of the test as the performance of SIP devices may vary accordingly.
- o REGISTER and INVITE requests may be challenged or remain unchallenged for authentication purpose. Whether or not the REGISTER and INVITE requests are challenged is a condition of test which will be recorded along with other such parameters which may impact the SIP performance of the device or system under test.

- o Re-INVITE requests are not considered in scope of this document since the benchmarks for INVITEs are based on the dialog created by the INVITE and not on the transactions that take place within that dialog.
- o Only session establishment is considered for the performance benchmarks. Session disconnect is not considered in the scope of this document. This is because our goal is to determine the maximum capacity of the device or system under test, that is the number of simultaneous SIP sessions that the device or system can support. It is true that there are BYE requests being created during the test process. These transactions do contribute to the load on the device or system under test and thus are accounted for in the metric we derive. We do not seek a separate metric for the number of BYE transactions a device or system can support.
- o IMS-specific scenarios are not considered, but test cases can be applied with 3GPP-specific SIP signaling and the P-CSCF as a DUT.
- o The benchmarks described in this document are intended for a laboratory environment and are not intended to be used on a production network. Some of the benchmarks send enough traffic that a denial of service attack is possible if used in production networks.

3. Term Definitions

3.1. Protocol Components

3.1.1. Session

Definition:

The combination of signaling and media messages and associated processing that enable a single SIP-based audio or video call, or SIP registration.

Discussion:

The term "session" commonly implies a media session. In this document the term is extended to cover the signaling and any media specified and invoked by the corresponding signaling.

Measurement Units:

N/A.

Issues:

None.

See Also:

- Media Plane
- Signaling Plane
- Associated Media

3.1.2. Signaling Plane

Definition:

The plane in which SIP messages [RFC3261] are exchanged between SIP Agents [RFC3261].

Discussion:

SIP messages are used to establish sessions in several ways: directly between two User Agents [RFC3261], through a Proxy Server [RFC3261], or through a series of Proxy Servers. The Session Description Protocol (SDP) is included in the Signaling Plane.

Measurement Units:

N/A.

Issues:

None.

See Also:

- Media Plane
- EAs

3.1.3. Media Plane

Definition:

The data plane in which one or more media streams and their associated media control protocols (e.g., RTCP [RFC3550]) are exchanged between User Agents after a media connection has been created by the exchange of signaling messages in the Signaling Plane.

Discussion:

Media may also be known as the "bearer channel". The Media Plane MUST include the media control protocol, if one is used, and the media stream(s). Examples of media are audio and video. The media streams are described in the SDP of the Signaling Plane.

Measurement Units:

N/A.

Issues:

None.

See Also:

Signaling Plane

3.1.4. Associated Media

Definition:

Media that corresponds to an 'm' line in the SDP payload of the Signaling Plane.

Discussion:

The format of the media is determined by the SDP attributes for the corresponding 'm' line.

Measurement Units:

N/A.

Issues:

None.

3.1.5. Overload

Definition:

Overload is defined as the state where a SIP server does not have sufficient resources to process all incoming SIP messages [RFC6357].

Discussion:

The distinction between an overload condition and other failure scenarios is outside the scope of black box testing and of this document. Under overload conditions, all or a percentage of Session Attempts will fail due to lack of resources. In black box testing the cause of the failure is not explored. The fact that a failure occurred for whatever reason, will trigger the tester to reduce the offered load, as described in the companion methodology document, [I-D.ietf-bmwg-sip-bench-meth]. SIP server resources may include CPU processing capacity, network bandwidth, input/output queues, or disk resources. Any combination of resources may be fully utilized when a SIP server (the DUT) is in the overload condition. For proxy-only (or intermediary) devices, it is expected that the proxy will be driven into overload based on the delivery rate of signaling requests.

Measurement Units:

N/A.

3.1.6. Session Attempt

Definition:

A SIP INVITE or REGISTER request sent by the EA that has not received a final response.

Discussion:

The attempted session may be either an invitation to an audio/video communication or a registration attempt. When counting the number of session attempts we include all requests that are rejected for lack of authentication information. The EA needs to record the total number of session attempts including those attempts that are routinely rejected by a proxy that requires the UA to authenticate itself. The EA is provisioned to deliver a specific number of session attempts per second. But the EA must also count the actual number of session attempts per given time interval.

Measurement Units:

N/A.

Issues:

None.

See Also:

Session

Session Attempt Rate

3.1.7. Established Session

Definition:

A SIP session for which the EA acting as the UE/UA has received a 200 OK message.

Discussion:

An Established Session may be either an invitation to an audio/video communication or a registration attempt. Early dialogues for INVITE requests are out of scope for this work.

Measurement Units:

N/A.

Issues:

None.

See Also:

None.

3.1.8. Session Attempt Failure

Definition:

A session attempt that does not result in an Established Session.

Discussion:

The session attempt failure may be indicated by the following observations at the EA:

1. Receipt of a SIP 3xx-, 4xx-, 5xx-, or 6xx-class response to a Session Attempt.
2. The lack of any received SIP response to a Session Attempt within the Establishment Threshold Time (c.f. Section 3.3.2).

Measurement Units:

N/A.

Issues:

None.

See Also:

Session Attempt

3.2. Test Components

3.2.1. Emulated Agent

Definition:

A device in the test topology that initiates/responds to SIP messages as one or more session endpoints and, wherever applicable, sources/receives Associated Media for Established Sessions.

Discussion:

The EA functions in the Signaling and Media Planes. The Tester may act as multiple EAs.

Measurement Units:

N/A

Issues:

None.

See Also:

Media Plane
Signaling Plane
Established Session
Associated Media

3.2.2. Signaling Server

Definition:

Device in the test topology that facilitates the creation of sessions between EAs. This device is the DUT.

Discussion:

The DUT is a RFC3261-capable network intermediary such as a Registrar, Redirect Server, Stateful Proxy, B2BUA or SBC.

Measurement Units:

NA

Issues:

None.

See Also:

Signaling Plane

3.2.3. SIP Transport Protocol

Definition:

The protocol used for transport of the Signaling Plane messages.

Discussion:

Performance benchmarks may vary for the same SIP networking device depending upon whether TCP, UDP, TLS, SCTP, websockets [RFC7118] or any future transport layer protocol is used. For this reason it is necessary to measure the SIP Performance Benchmarks using these various transport protocols. Performance Benchmarks MUST report the SIP Transport Protocol used to obtain the benchmark results.

Measurement Units:

While these are not units of measure, they are attributes that are one of many factors that will contribute to the value of the measurements to be taken. TCP, UDP, SCTP, TLS over TCP, TLS over UDP, TLS over SCTP, and websockets are among the possible values to be recorded as part of the test.

Issues:

None.

See Also:

None.

3.3. Test Setup Parameters**3.3.1. Session Attempt Rate****Definition:**

Configuration of the EA for the number of sessions per second (sps) that the EA attempts to establish using the services of the DUT.

Discussion:

The Session Attempt Rate is the number of sessions per second that the EA sends toward the DUT. Some of the sessions attempted may not result in a session being established.

Measurement Units:

Session attempts per second

Issues:

None.

See Also:

Session
Session Attempt

3.3.2. Establishment Threshold Time**Definition:**

Configuration of the EA that represents the amount of time that an EA client will wait for a response from an EA server before declaring a Session Attempt Failure.

Discussion:

This time duration is test dependent.

It is RECOMMENDED that the Establishment Threshold Time value be set to Timer B or Timer F as specified in RFC 3261, Table 4 [RFC3261].

Measurement Units:

Seconds

Issues:

None.

See Also:

None.

3.3.3. Session Duration**Definition:**

Configuration of the EA that represents the amount of time that the SIP dialog is intended to exist between the two EAs associated with the test.

Discussion:

The time at which the BYE is sent will control the Session Duration.

Measurement Units:

seconds

Issues:

None.

See Also:

None.

3.3.4. Media Packet Size**Definition:**

Configuration on the EA for a fixed number of frames or samples to be sent in each RTP packet of the media stream when the test involves Associated Media.

Discussion:

This document describes a method to measure SIP performance. If the DUT is processing media as well as SIP messages the media processing will potentially slow down the SIP processing and lower the SIP performance metric. The tests with associated media are designed for audio codecs and the assumption was made that larger media packets would require more processor time. This document does not define parameters applicable to video codecs.

For a single benchmark test, media sessions use a defined number of samples or frames per RTP packet. If two SBCs, for example, used the same codec but one puts more frames into the RTP packet, this might cause variation in the performance benchmark results.

Measurement Units:

An integer number of frames or samples, depending on whether hybrid- or sample-based codec are used, respectively.

Issues:

None.

See Also:

None.

3.3.5. Codec Type

Definition:

The name of the codec used to generate the media session.

Discussion

For a single benchmark test, all sessions use the same size packet for media streams. The size of packets can cause a variation in the performance benchmark measurements.

Measurement Units:

This is a textual name (alphanumeric) assigned to uniquely identify the codec.

Issues:

None.

See Also:

None.

3.4. Benchmarks

3.4.1. Session Establishment Rate

Definition:

The maximum value of the Session Attempt Rate that the DUT can handle for an extended, pre-defined, period with zero failures.

Discussion:

This benchmark is obtained with zero failure. The session attempt rate provisioned on the EA is raised and lowered as described in the algorithm in the accompanying methodology document [I-D.ietf-bmwg-sip-bench-meth], until a traffic load over the period of time necessary to attempt N sessions completes without failure, where N is a parameter specified in the algorithm and recorded in the Test Setup Report.

Measurement Units:

sessions per second (sps)

Issues:

None.

See Also:

Invite-Initiated Sessions
Non-Invite-Initiated Sessions
Session Attempt Rate

3.4.2. Registration Rate

Definition:

The maximum value of the Registration Attempt Rate that the DUT can handle for an extended, pre-defined, period with zero failures.

Discussion:

This benchmark is obtained with zero failures. The registration rate provisioned on the Emulated Agent is raised and lowered as described in the algorithm in the companion methodology draft [I-D.ietf-bmwg-sip-bench-meth], until a traffic load consisting of registration attempts at the given attempt rate over the period of time necessary to attempt N registrations completes without failure, where N is a parameter specified in the algorithm and recorded in the Test Setup Report.

This benchmark is described separately from the Session Establishment Rate (Section 3.4.1), although it could be considered a special case of that benchmark, since a REGISTER request is a request for a Non-Invite-Initiated session. It is defined separately because it is a very important benchmark for most SIP installations. An example demonstrating its use is an

avalanche restart, where hundreds of thousands of end points register simultaneously following a power outage. In such a case, an authoritative measurement of the capacity of the device to register endpoints is useful to the network designer. Additionally, in certain controlled networks, there appears to be a difference between the registration rate of new endpoints and the registering rate of existing endpoints (register refreshes). This benchmark can capture these differences as well.

Measurement Units:

registrations per second (rps)

Issues:

None.

See Also:

None.

3.4.3. Registration Attempt Rate

Definition:

Configuration of the EA for the number of registrations per second that the EA attempts to send to the DUT.

Discussion:

The Registration Attempt Rate is the number of registration requests per second that the EA sends toward the DUT.

Measurement Units:

Registrations per second (rps)

Issues:

None.

See Also: Non-Invite-Initiated Session

4. IANA Considerations

This document requires no IANA considerations.

5. Security Considerations

Documents of this type do not directly affect the security of Internet or corporate networks as long as benchmarking is not performed on devices or systems connected to production networks. Security threats and how to counter these in SIP and the media layer

is discussed in RFC3261 [RFC3261], RFC 3550 [RFC3550] and RFC3711 [RFC3711]. This document attempts to formalize a set of common terminology for benchmarking SIP networks. Packets with unintended and/or unauthorized DSCP or IP precedence values may present security issues. Determining the security consequences of such packets is out of scope for this document.

6. Acknowledgments

The authors would like to thank Keith Drage, Cullen Jennings, Daryl Malas, Al Morton, and Henning Schulzrinne for invaluable contributions to this document. Dale Worley provided an extensive review that lead to improvements in the documents. We are grateful to Barry Constantine, William Cervený and Robert Sparks for providing valuable comments during the document's last calls and expert reviews. Al Morton and Sarah Banks have been exemplary working group chairs, we thank them for tracking this work to completion.

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.
- [RFC2544] Bradner, S. and J. McQuaid, "Benchmarking Methodology for Network Interconnect Devices", RFC 2544, March 1999.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", RFC 3261, June 2002.
- [RFC5393] Sparks, R., Lawrence, S., Hawrylyshen, A., and B. Campen, "Addressing an Amplification Vulnerability in Session Initiation Protocol (SIP) Forking Proxies", RFC 5393, December 2008.
- [RFC4320] Sparks, R., "Actions Addressing Identified Issues with the Session Initiation Protocol's (SIP) Non-INVITE Transaction", RFC 4320, January 2006.
- [RFC6026] Sparks, R. and T. Zourzouvillys, "Correct Transaction Handling for 2xx Responses to Session Initiation Protocol (SIP) INVITE Requests", RFC 6026, September 2010.

[I-D.ietf-bmwg-sip-bench-meth]
Davids, C., Gurbani, V., and S. Poretsky, "SIP Performance Benchmarking Methodology",
draft-ietf-bmwg-sip-bench-meth-10 (work in progress),
May 2014.

7.2. Informational References

- [RFC2285] Mandeville, R., "Benchmarking Terminology for LAN Switching Devices", RFC 2285, February 1998.
- [RFC1242] Bradner, S., "Benchmarking terminology for network interconnection devices", RFC 1242, July 1991.
- [RFC3550] Schulzrinne, H., Casner, S., Frederick, R., and V. Jacobson, "RTP: A Transport Protocol for Real-Time Applications", STD 64, RFC 3550, July 2003.
- [RFC3711] Baugher, M., McGrew, D., Naslund, M., Carrara, E., and K. Norrman, "The Secure Real-time Transport Protocol (SRTP)", RFC 3711, March 2004.
- [RFC6357] Hilt, V., Noel, E., Shen, C., and A. Abdelal, "Design Considerations for Session Initiation Protocol (SIP) Overload Control", RFC 6357, August 2011.
- [RFC7118] Baz Castillo, I., Millan Villegas, J., and V. Pascual, "The WebSocket Protocol as a Transport for the Session Initiation Protocol (SIP)", RFC 7118, January 2014.

Authors' Addresses

Carol Davids
Illinois Institute of Technology
201 East Loop Road
Wheaton, IL 60187
USA

Phone: +1 630 682 6024
Email: davids@iit.edu

Vijay K. Gurbani
Bell Laboratories, Alcatel-Lucent
1960 Lucent Lane
Rm 9C-533
Naperville, IL 60566
USA

Phone: +1 630 224 0216
Email: vkg@bell-labs.com

Scott Poretsky
Allot Communications
300 TradeCenter, Suite 4680
Woburn, MA 08101
USA

Phone: +1 508 309 2179
Email: sporetsky@allot.com

