

TRILL Working Group  
Internet Draft  
Intended Status: Standard Track

Expires July 2014

Deepak Kumar  
Samer Salam  
Tissa Senevirathne  
Cisco  
January 15, 2014

TRILL OAM MIB  
draft-ietf-trill-oam-mib-00.txt

#### Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on November 08, 2013.

#### Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

#### Abstract

This document specifies the Management Information Base (MIB) for the IETF TRILL (Transparent Interconnection of Lots of Links) OAM objects.

## Table of Contents

1. Introduction . . . . .	3
2. The Internet-Standard Management Framework . . . . .	3
3. Overview . . . . .	4
4. Conventions . . . . .	4
5. Structure of the MIB module . . . . .	4
5.1. Textual Conventions . . . . .	4
5.2. TRILL-OAM-MIB relationship to IEEE8021-TC-MIB . . . . .	4
5.3. TRILL OAM MIB Tree . . . . .	5
5.3.1. Notifications . . . . .	5
5.3.2. TRILL OAM MIB Per MEP Objects . . . . .	5
5.3.2.1. trillOamMepTable Objects . . . . .	5
5.3.2.2. trillOamMepFlowCfgTable Objects . . . . .	8
5.3.2.3. trillOamPtrTable Objects . . . . .	9
5.3.2.4. trillOamMtrTable Objects . . . . .	10
5.3.2.4. trillOamMepDbTable Objects . . . . .	12
6. Relationship to other MIB module . . . . .	13
6.1. Relationship to IEEE8021-CFM-MIB . . . . .	13
6.2. MIB modules required for IMPORTS . . . . .	13
7. Definition of the TRILL OAM MIB module . . . . .	13
8. Security Considerations . . . . .	47
9. IANA Considerations . . . . .	48
10. References . . . . .	48
10.1. Normative References . . . . .	48
10.2. Informative References . . . . .	49
11. Acknowledgments . . . . .	49

## 1. Introduction

Overall, TRILL OAM is intended to meet the requirements given in [RFC6905]. The general framework for TRILL OAM is specified in [TRILLOAMFRM]. The details of the Fault Management [FM] solution, conforming to that framework, are presented in [TRILLOAMFM]. The solution leverages the message format defined in Ethernet Connectivity Fault Management (CFM) [802.1Q] as the basis for the TRILL OAM message channel.

This document uses the CFM MIB modules defined in [802.1Q] as the basis for TRILL OAM MIB, and augments the existing tables to add new TRILL managed objects required by TRILL. This document further specifies a new table with associated managed objects for TRILL OAM specific capabilities.

## 2. The Internet-Standard Management Framework

For a detailed overview of the Internet-Standard Management Framework, please refer to [RFC3410]. Managed objects are accessed via a virtual information store, termed the Management Information Base or MIB. MIB objects are generally accessed through the Simple Network Management Protocol (SNMP). Objects in the MIB are defined using the Structure of Management Information (SMI) specification. This memo specifies a MIB module that is compliant to SMIV2 [RFC2578], [RFC2579] and [RFC2580].

### 3. Overview

The TRILL-OAM-MIB module is intended to provide an overall framework for managing TRILL OAM. It leverages the IEEE8021-CFM-MIB and IEEE8021-CFM-V2-MIB modules defined in [802.1Q], and augments the Mep and Mep Db entries. It also adds a new table for TRILL OAM specific messages.

### 4. Conventions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in RFC-2119 [RFC2119].

### 5. Structure of the MIB module

Objects in this MIB module are arranged into subtrees. Each subtree is organized as a set of related objects. The various subtrees are shown below, supplemented with the required elements of the IEEE8021-CFM-MIB module.

#### 5.1. Textual Conventions

Textual conventions are defined to represent object types relevant to the TRILL OAM MIB.

#### 5.2. TRILL-OAM-MIB relationship to IEEE8021-TC-MIB

In TRILL, traffic labeling can be done using either a 12-bit VLAN or a 24-bit fine grain label [RFCfg1].

IEEE8021-TC-MIB defines IEEE8021ServiceSelectorType with two values:

- 1 representing a vlanId, and
- 2 representing a 24 bit isid.

We propose to use value 2 for TRILL's fine grain label. As such, TRILL-OAM-MIB will import IEEE8021ServiceSelectorType,

IEEE8021ServiceSelectorValueOrNone, and IEEE8021ServiceSelectorValue from IEEE8021-TC-MIB.

### 5.3. TRILL OAM MIB Tree

TRILL-OAM-MIB

```
|--trillOamNotifications
    |--trillOamFaultAlarm
|--trillOamMibObjects
    |--trillOamMep
        |--trillOamMepTable
        |--trillOamMepFlowCfgTable
        |--trillOamPtrTable
        |--trillOamMtrTable
        |--trillOamMepDbTable
```

#### 5.3.1. Notifications

Notification (fault alarm) is sent to the management entity with the OID of the MEP that has detected the fault.

#### 5.3.2. TRILL OAM MIB Per MEP Objects

The TRILL OAM MIB Per MEP Objects are defined in the trillOamMepTable. The trillOamMepTable augments the dotlagCfmMepEntry (please see section 6.1) defined in IEEE8021-CFM-MIB. It includes objects that are locally defined for an individual MEP and its associated Flow.

##### 5.3.2.1. trillOamMepTable Objects

o trillOamMepRName - This object contains the Rbridge Nickname as defined in [RFC6325] section 3.7.

o trillOamMepPtmTid - indicates the next sequence number/transaction identifier to be sent in a Path Trace message. The sequence number may be zero because it wraps around.

- o trillOamMepNexttMtmTId - indicates the next sequence number/transaction identifier to be sent in a Multi-destination message. The sequence number may be zero because it wraps around.
- o trillOamMepMepPtrIn - indicates the total number of valid, in-order, Path Trace Replies received.
- o trillOamMepPtrInOutOfOrder - indicates the total number of valid, out-of-order, Path Trace Replies received.
- o trillOamMepPtrOut - indicates the total number of valid Path Trace Replies transmitted.
- o trillOamMepMtrIn - indicates the total number of valid, in-order, Multi-destination Replies received.
- o trillOamMepMtrInOutOfOrder - indicates the total number of valid, out-of-order, Multi-destination Replies received.
- o trillOamMepMtrOut - indicates the total number of valid Multi-destination Replies transmitted.
- o trillOamMepTxLbmDestRName - indicates the target destination Rbridge NickName as defined in [RFC6325] section 3.7.
- o trillOamMepTxLbmHC - indicates the hop count field to be transmitted.
- o trillOamMepTxLbmReplyModeOob - True indicates that the Reply Mode of the Loopback message is requested to be out-of-band, and that the "Out of band IP address" TLV is to be transmitted. False indicates that in-band reply is transmitted.
- o trillOamMepTransmitLbmReplyIp - indicates the IP address to be transmitted in the "Out of band IP Address TLV" in the Loopback message.
- o trillOamMepTxLbmFlowEntropy - indicates the 128 bytes Flow entropy to be transmitted, as defined in [TRILLOAMFM].
- o trillOamMepTxPtmDestRName - indicates the target Destination Rbridge Nickname to be transmitted, as defined in [RFC6325] section 3.7.
- o trillOamMepTxPtmHC - indicates the hop count field to be transmitted.

- o trillOamMepTxPtmReplyModeOob - True indicates that the Reply Mode of the Path Trace message is requested to be out-of-band, and that the "Out of band IP address TLV" is to be transmitted. False indicates that in-band reply is transmitted.
- o trillOamMepTransmitPtmReplyIP - indicates the IP address to be transmitted in the "Out of band IP Address TLV" in the Path Trace message.
- o trillOamMepTranmitPtmFlowEntropy - indicates the 128 bytes Flow entropy to be transmitted, as defined in [TRILLOAMFM].
- o trillOamMepTxPtmStatus - A Boolean flag set to True by the MEP Path Trace Initiator State Machine or a MIB manager to indicate that another Path trace message is being transmitted. Reset to false by the MEP Initiator State Machine.
- o trillOamMepTxPtmResultOK - Indicates the result of the operation, True : The Path Trace Message(s) will be (or has been) sent, False: The Path Trace Message(s) will not be sent.
- o trillOamMepTxPtmMessages - The number of Path Trace messages to be transmitted.
- o trillOamMepTxPtmSeqNumber - Indicates the Path Trace Transaction Identifier of the first PTM (to be) sent. The value returned is undefined if trillOamMepTxPtmResultOK is false.
- o trillOamMepTxMtmTree - Indicates the Multi-destination Tree identifier as defined in RFC6325.
- o trillOamMepTxMtmHC - Indicates the hop count field to be transmitted.
- o trillOamMepTxMtmReplyModeOob - True indicates that the Reply of the Multi-destination message is requested to be out-of-band, and that the "Out of band IP address TLV" is to be transmitted. False indicates that in-band reply is transmitted.
- o trillOamMepTransmitMtmReplyIp - the IP address to be transmitted in the "Out of band IP address TLV" in the Multi-destination message.
- o trillOamMepTxMtmFlowEntropy - 128 Byte Flow Entropy to be transmitted, as defined in [TRILL-FM].
- o trillOamMepTxMtmStatus - A Boolean flag set to True by the MEP Multi-Destination Initiator State Machine or a MIB manager

to indicate that another Multicast trace message is being transmitted. Reset to False by the MEP Initiator State Machine.

- o trillOamMepTxMtmResultOK - Indicates the result of the operation: -True The Multi-destination Message(s) will be (or has been) sent. -False The Multi-destination Message(s) will not be sent.

- o trillOamMepTxMtmMessages -The number of Multi-Destination Messages to be transmitted.

- o trillOamMepTxMtmSeqNumber - The Sequence Number of the first Multi-destination message (to be) sent. The value returned is undefined if trillOamMepTxMtmResultOK is false.

- o trillOamMepTxMtmScopeList - The Multi-destination Rbridge Scope list, 2 octets per Rbridge.

#### 5.3.2.2. trillOamMepFlowCfgTable Objects

Each row in this table represents a Flow Configuration Entry for the associated MEP. The table uses four indices. The first three indices are the indices of the Maintenance Domain, MaNet, and MEP tables. The fourth index is the specific Flow Configuration Entry on the selected MEP. Some write-able objects in this table are only applicable in certain cases (as described under each object below), and attempts to write values for them in other cases will be ignored.

- o trillOamMepFlowCfgIndex - an index to the TRILL OAM Mep flow configuration table which indicates the specific Flow for the MEP. The index is never reused for other flow sessions on the same MEP while this session is active. The index value keeps increasing until it wraps to 0. This value can also be used in Flow-identifier TLV.

- o trillOamMepFlowCfgFlowEntropy - This is 96 bytes of flow entropy as described in [TRILL-FM].

- o trillOamMepFlowCfgDestRname - The target Rbridge nickname field to be transmitted as defined in [RFC6325] section 3.7.

- o trillOamMepFlowCfgFlowHC - indicates the time to live field to be transmitted.

- o trillOamMepFlowCfgRowStatus - indicates the status of row. The write-able columns in a row cannot be changed if the row is active. All columns MUST have a valid value before a row can be



activated.

#### 5.3.2.3. trillOamPtrTable Objects

Each row in the table represents a Path Trace Reply Entry for the defined MEP and Transaction. This table uses four indices. The first three indices identify the MEP and the fourth index specifies the Transaction Identifier, and this transaction identifier uniquely identifies the response for a MEP which can have multiple flow.

- o trillOamMepPtrTransactionId - indicates Transaction identifier/sequence number returned by a previous transmit path trace message command, indicating which PTM's response is going to be returned.

- o trillOamPtrHC - indicates hop count field value for a returned PTR.

- o trillOamMepPtrFlag - indicates FCOI field value for a returned PTR.

- o trillOamMepPtrErrorCode - indicates the Return code and Return sub-code value for a returned PTR.

- o trillOamMepPtrTerminalMep - indicates a Boolean value stating whether the forwarded PTM reached a MEP enclosing its MA, as returned in the Terminal MEP flag field.

- o trillOamMepPtrNextEgressIdentifier - An integer field holding the last Egress Identifier returned in the PTR Upstream Rbridge nickname TLV of the PTR. The Last Egress identifies the Upstream Nickname.

- o trillOamMepPtrIngress - The value returned in the Ingress Action field of the PTM. The value ingNoTlv(0) indicates that no Reply Ingress TLV was returned in the PTM.

- o trillOamMepPtrIngressMac - indicates the MAC address returned in the ingress MAC address field.

- o trillOamMepIngressPortIdSubtype - indicates ingress Port ID. The format of this object is determined by the value of the trillOamMepPtrIngressPortIdSubtype object.

- o trillOamMepIngressPortId - indicates the ingress port ID. The format of this object is determined by the value of the trillOamMepPtrIngressPortId object.

o trillOamMepPtrEgressPortIdSubtype - indicates the value returned in the Egress Action field of the PTM. The value ingNoTlv(0) indicates that no Reply Egress TLV was returned in the PTM.

o trillOamMepPtrEgressPortId - indicates the egress port ID. The format of this object is determined by the value of trillOamMepPtrEgressPortId object.

o trillOamMepPtrChassisIdSubtype - This object specifies the format for the Chassis ID returned in the Sender ID TLV of the PTR, if any. This value is ignored if the trillOamMepPtrChassiId has a length of 0.

o trillOamMepPtrChassisId - indicates the chassis ID returned in the Sender ID TLV of the PTR, if any. The format of this object is determined by the value of the trillOamMepPtrChassisIdSubtype object.

o trillOamMepPtrOrganizationSpecificTlv - indicates all Organization specific TLVs returned in the PTR, if any. Includes all octets including and following the TLV length field of each TLV, concatenated together.

o trillOamMepPtrNextHopNicknames - indicates Next hop Rbridge List TLV returned in the PTR, if any. Includes all octets including and following the TLV length concatenated together.

#### 5.3.2.4. trillOamMtrTable Objects

This table includes Multi-destination Reply managed objects. Each row in the table represents a Multi-destination Reply Entry for the defined MEP and Transaction. This table uses five indices: The first three indices are the indices of the Maintenance Domain, MaNet, and MEP tables. The fourth index is the specific Transaction Identifier on the selected MEP. The fifth index is the receive order of Multi-destination replies. Some write-able objects in this table are only applicable in certain cases (as described under each object below), and attempts to write a value for them in other cases will be ignored.

o trillOamMepMtrTransactionId - indicates Transaction identifier/sequence number returned by a previous transmit Multi-destination message command, indicating which MTM's response is going to be returned.

o trillOamMepMtrReceiveOrder - indicates an index to

distinguish among multiple MTR with same same MTR Transaction Identifier field value. `trillOamMepMtrReceiveOrder` are assigned sequentially from 1, in the order that the Multi-destination Tree Initiator received the MTRs.

o `trillOamMepMtrFlag` - indicates FCOI field value for a returned MTR.

o `trillOamMepMtrErrorCode` - indicates return code and return sub code value for a returned MTR.

o `trillOamMepMtrLastEgressIdentifier` - indicates an integer field holding the Last Egress Identifier returned in the MTR Upstream Rbridge Nickname TLV of the MTR. The Last Egress Identifier identifies the Upstream Nickname.

o `trillOamMepMtrIngress` - indicates the value returned in the Ingress Action Field of the MTR. The value `ingNoTlv(0)` indicates that no Reply Ingress TLV was returned in the MTM.

o `trillOamMepMtrIngressMac` - indicates the MAC address returned in the ingress MAC address field.

o `trillOamMepMtrIngressPortIdSubtype` - indicates the ingress Port ID. The format of this object is determined by the value of the `trillOamMepMtrIngressPortIdSubtype` object.

o `trillOamMepMtrIngressPortId` - indicates the ingress Port Id. The format of this object is determined by the value of the `trillOamMepMtrIngressPortId` object.

o `trillOamMepMtrEgress` - indicates the value returned in the Egress Action field of the MTR. The value `ingNoTlv(0)` indicates that no Reply Egress TLV was returned in the MTR.

o `trillOamMepMtrEgressMac` - indicates the MAC address returned in the egress MAC address field.

o `trillOamMepMtrEgressPortIdSubtype` - indicates the egress Port ID. The format of this object is determined by the value of the `trillOamMepMtrEgressPortIdSubtype` object.

o `trillOamMepMtrEgressPortId` - indicates the egress port ID. The format of this object is determined by the value of the `trillOamMepMtrEgressPortId` object.

o `trillOamMepMtrChassisIdSubtype` - indicates the format of the chassis ID returned in the Sender ID TLV of the MTR, if any.

The value is ignored if the `trillOamMepMtrChassisId` has length of 0.

o `trillOamMepMtrChassisId` - indicates the chassis ID returned in the Sender ID TLV of the MTR, if any. The format of this object is determined by the value of the `trillOamMepMtrChassisIdSubtype` object.

o `trillOamMepMtrOrganizationSpecificTlv` - indicates all Organization specific TLVs returned in the MTR, if any. Includes all octets including and following the TLV length field of each TLV, concatenated together.

o `trillOamMepMtrNextHopNicknames` - indicates next hop Rbridge List TLV returned in the PTR, if any. Includes all octets including and following the TLV length field of each TLV, concatenated together.

o `trillOamMepMtrNextHopTotalReceivers` - indicates value indicating that MTR response contains Multicast receiver availability TLV.

o `trillOamMepMtrReceiverCount` - indicates the number of Multicast receivers available on responding Rbridge on the VLAN specified by the diagnostic VLAN.

#### 5.3.2.4. `trillOamMepDbTable` Objects

This table is an augmentation of the `dotlagCfmMepDbTable`, and rows are automatically added or deleted from this table based upon row creation and destruction of the `dotlagCfmMepDbTable`.

o `trillOamMepDbFlowIndex` - This object identifies the Flow. If the Flow Identifier TLV is received then index received can also be used.

o `trillOamMepCfgFlowEntropy` - indicates 96 bytes of Flow entropy.

o `trillOamMepDbFlowState` - indicates the operational state of the remote MEP (flow based) IFF state machines.

o `trillOamMepDbRmepFailedOkTime` - indicates the time (`sysUpTime`) at which the Remote Mep Flow State machine last entered either the `RMEP_FAILED` or `RMEP_OK` state.

o `trillOamMepDbRbridgeName` - indicates Remote MEP Rbridge Nickname.

## 6. Relationship to other MIB module

The IEEE8021-CFM-MIB, IEEE801-CFM-V2-MIB and LLDP-MIB contain objects relevant to TRILL OAM MIB. Management objects contained in these modules are not duplicated here, to reduce overlap to the extent possible.

### 6.1. Relationship to IEEE8021-CFM-MIB

TRILL OAM MIB Imports the following management objects from IEEE8021-CFM-MIB:

- o dotlagCfmMdIndex
- o dotlagCfmMaIndex
- o dotlagCfmMepIdentifier
- o dotlagCfmMepEntry
- o dotlagCfmMepDbEntry
- o DotlagCfmIngressActionFieldValue
- o DotlagCfmEgressActionFieldValue
- o DotlagCfmRemoteMepState

trillOamMepTable Augments dotlagCfmMepEntry. Implementation of IEEE-CFM-MIB is required as we are Augmenting the IEEE-CFM-MIB Table. Objects/Tables that are not applicable to a TRILL implementation have to be handled by the TRILL implementation back end and appropriate values as described in IEEE-CFM-MIB have to be returned.

### 6.2. MIB modules required for IMPORTS

The following MIB module IMPORTS objects from SNMPv2-SMI [RFC2578], SNMPv2-TC [RFC2579], SNMPv2-CONF [RFC2580], IEEE-8021-CFM-MIB, LLDP-MIB.

## 7. Definition of the TRILL OAM MIB module

TRILL-OAM-MIB DEFINITIONS ::= BEGIN

IMPORTS

MODULE-IDENTITY,

```
OBJECT-TYPE,
NOTIFICATION-TYPE,
Counter32,
Unsigned32,
Integer32
    FROM SNMPv2-SMI
RowStatus,
TruthValue,
TimeStamp,
MacAddress
    FROM SNMPv2-TC
OBJECT-GROUP,
NOTIFICATION-GROUP,
MODULE-COMPLIANCE
    FROM SNMPv2-CONF
dotlagCfmMdIndex,
dotlagCfmMaIndex,
dotlagCfmMepIdentifier,
dotlagCfmMepEntry,
dotlagCfmMepDbEntry,
DotlagCfmIngressActionFieldValue,
DotlagCfmEgressActionFieldValue,
DotlagCfmRemoteMepState
    FROM IEEE8021-CFM-MIB
LldpChassisId,
LldpChassisIdSubtype,
LldpPortId
    FROM LLDP-MIB;

trilloamMib MODULE-IDENTITY
    LAST-UPDATED      "201310191200Z"
    ORGANIZATION      "TBD"
    CONTACT-INFO
        "E-mail:   dekuar@cisco.com
        Postal:    510 McCarthy Blvd
                  Milpitas, CA 95035
                  U.S.A.
        Phone:      +1 408 853 9760"
    DESCRIPTION
        "This MIB module contains the management objects for the
        management of Trill Services Operations, Administration
        and Maintenance.
        Initial version. Published as RFC xxxx.
```

-----  
Reference Overview

A number of base documents have been used to create the

Textual Conventions MIB. The following are the abbreviations for the baseline documents:

[CFM] refers to 'Connectivity Fault Management', IEEE 802.1ag-2007, December 2007

[Q.840.1] refers to 'ITU-T Requirements and analysis for NMS-EMS management interface of Ethernet over Transport and Metro Ethernet Network (EoT/MEN)', March 2007

[Y.1731] refers to ITU-T Y.1731 'OAM functions and mechanisms for Ethernet based networks', February 2011

#### Abbreviations Used

Term	Definition
CCM	Continuity Check Message
CFM	Connectivity Fault Management
CoS	Class of Service
IEEE	Institute of Electrical and Electronics Engineers
IETF	Internet Engineering Task Force
ITU-T	International Telecommunication Union - Telecommunicatio

n

#### Standardization Bureau

MAC	Media Access Control
MA	Maintenance Association (equivalent to a MEG)
MD	Maintenance Domain (equivalent to a OAM Domain in MEF 17

)

MD Level	Maintenance Domain Level (equivalent to a MEG level)
ME	Maintenance Entity
MEG	Maintenance Entity Group (equivalent to a MA)
MEG Level	Maintenance Entity Group Level (equivalent to MD Level)
MEP	Maintenance Association End Point or MEG End Point
MIB	Management Information Base
MIP	Maintenance Domain Intermediate Point or MEG Intermediate Point
MP	Maintenance Point. One of either a MEP or a MIP
OAM	Operations, Administration, and Maintenance On-Demand
OAM actions	that are initiated via manual intervention for a limited time to carry out diagnostics. On-Demand OAM can result in singular or periodic OAM actions during the diagnostic time interval
PDU	Protocol Data Unit
RFC	Request for Comment
SNMP	Simple Network Management Protocol
SNMP Agent	An SNMP entity containing one or more command responder and/or notification originator applications (along with their associated SNMP engine). Typically implemented in an NE.
SNMP Manager	An SNMP entity containing one or more command generator

```

        and/or notification receiver applications (along with
        their associated SNMP engine). Typically implemented in
        an EMS or NMS.
    TLV                Type Length Value, a method of encoding Objects
    UTC                Coordinated Universal Time
    UNI                User-to-Network Interface
    VLAN                Virtual LAN"
    REVISION            "201310191200Z"
    DESCRIPTION
        "Initial version. Published as RFC xxxx."
    ::= { mib-2 xxx }

-- RFC Ed.: assigned by IANA, see section 9 for details
--
-- *****
-- Object definitions in the TRILL OAM MIB Module
-- *****

trilloamNotifications OBJECT IDENTIFIER
    ::= { trilloamMib 0 }

trilloamMibObjects OBJECT IDENTIFIER
    ::= { trilloamMib 1 }

trilloamMibConformance OBJECT IDENTIFIER
    ::= { trilloamMib 2 }

-- *****
-- Groups in the TRILL OAM MIB Module
-- *****

trilloamMep OBJECT IDENTIFIER
    ::= { trilloamMibObjects 1 }

-- *****
-- TRILL OAM MEP Configuration
-- *****

trilloamMepTable OBJECT-TYPE
    SYNTAX                SEQUENCE OF TrilloamMepEntry
    MAX-ACCESS            not-accessible
    STATUS                current
    DESCRIPTION
        "This table is an extension of the dotlagCfmMepTable and rows
        are automatically added or deleted from this table based upon
        row creation and destruction of the dotlagCfmMepTable."

```



This table represents the local MEP TRILL OAM configuration table. The primary purpose of this table is provide local parameters for the TRILL OAM function found in [TRILL-FM] and instantiated at a MEP."

REFERENCE "[TRILL-FM]"  
 ::= { trillOamMep 1 }

trillOamMepEntry OBJECT-TYPE  
 SYNTAX TrillOamMepEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION  
 "The conceptual row of trillOamMepTable."  
 AUGMENTS { dotlagCfmMepEntry }  
 ::= { trillOamMepTable 1 }

TrillOamMepEntry ::= SEQUENCE {  
 trillOamMepRName Unsigned32,  
 trillOamMepNextPtmTid Unsigned32,  
 trillOamMepNextMtmTid Unsigned32,  
 trillOamMepPtrIn Counter32,  
 trillOamMepPtrInOutOfOrder Counter32,  
 trillOamMepPtrOut Counter32,  
 trillOamMepMtrIn Counter32,  
 trillOamMepMtrInOutOfOrder Counter32,  
 trillOamMepMtrOut Counter32,  
 trillOamMepTxLbmDestRName Unsigned32,  
 trillOamMepTxLbmHC Unsigned32,  
 trillOamMepTxLbmReplyModeOob TruthValue,  
 trillOamMepTransmitLbmReplyIp OCTET STRING,  
 trillOamMepTxLbmFlowEntropy OCTET STRING,  
 trillOamMepTxPtmDestRName Unsigned32,  
 trillOamMepTxPtmHC Unsigned32,  
 trillOamMepTxPtmReplyModeOob TruthValue,  
 trillOamMepTransmitPtmReplyIp OCTET STRING,  
 trillOamMepTxPtmFlowEntropy OCTET STRING,  
 trillOamMepTxPtmStatus TruthValue,  
 trillOamMepTxPtmResultOK TruthValue,  
 trillOamMepTxPtmMessages Integer32,  
 trillOamMepTxPtmSeqNumber Unsigned32,  
 trillOamMepTxMtmTree Unsigned32,  
 trillOamMepTxMtmHC Unsigned32,  
 trillOamMepTxMtmReplyModeOob TruthValue,  
 trillOamMepTransmitMtmReplyIp OCTET STRING,  
 trillOamMepTxMtmFlowEntropy OCTET STRING,  
 trillOamMepTxMtmStatus TruthValue,  
 trillOamMepTxMtmResultOK TruthValue,  
 trillOamMepTxMtmMessages Integer32,

```
        trillOamMepTxMtmSeqNumber      Unsigned32,
        trillOamMepTxMtmScopeList      OCTET STRING
    }

trillOamMepRName OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65471)
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "This object contains Rbridge NickName of TRILL Rbridge as
        defined in RFC 6325 section 3.7."
    REFERENCE "TRILL-FM and RFC 6325 section 3.7"
    ::= { trillOamMepEntry 1 }

trillOamMepNextPtmTid OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "Next sequence number/transaction identifier to be sent in a
        Path Trace message. This sequence number can be zero because it
        wraps around. Implementation should be unique to identify
        Transaction Id for a MEP with multiple flows."
    REFERENCE "TRILL-FM 11.1.1.1"
    ::= { trillOamMepEntry 2 }

trillOamMepNextMtmTid OBJECT-TYPE
    SYNTAX      Unsigned32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "Next sequence number/transaction identifier to be sent in a
        Multi-destination message. This sequence number can be zero
        because it wraps around. Implementation should be unique to
        identify Transaction Id for a MEP with multiple flows."
    REFERENCE "TRILL-FM 12.2.1"
    ::= { trillOamMepEntry 3 }

trillOamMepPtrIn OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "Total number of valid, in-order Path Trace Replies received."
    REFERENCE "TRILL-FM section 11"
    ::= { trillOamMepEntry 4 }

trillOamMepPtrInOutOfOrder OBJECT-TYPE
```

```
SYNTAX          Counter32
MAX-ACCESS      read-only
STATUS          current
DESCRIPTION
    "Total number of valid, out-of-order Path Trace Replies received."
REFERENCE "TRILL-FM section 11"
 ::= { trillOamMepEntry 5 }

trillOamMepPtrOut OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Total number of valid, Path Trace Replies transmitted."
    REFERENCE "TRILL-FM section 11"
    ::= { trillOamMepEntry 6 }

trillOamMepMtrIn OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Total number of valid, in-order Multi-destination Replies
        received."
    REFERENCE "TRILL-FM section 12"
    ::= { trillOamMepEntry 7 }

trillOamMepMtrInOutOfOrder OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Total number of valid, out-of-order Multi-destination Replies
        received."
    REFERENCE "TRILL-FM section 12"
    ::= { trillOamMepEntry 8 }

trillOamMepMtrOut OBJECT-TYPE
    SYNTAX          Counter32
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Total number of valid, Multi-destination Replies
        transmitted."
    REFERENCE "TRILL-FM section 12"
    ::= { trillOamMepEntry 9 }

trillOamMepTxLbmDestRName OBJECT-TYPE
```

```
SYNTAX          Unsigned32 (0..65471)
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The Target Destination Rbridge NickName Field as
    defined in RFC 6325 section 3.7 to be transmitted."
REFERENCE "TRILL-FM and RFC6325 section 3.7"
 ::= { trillOamMepEntry 10 }

trillOamMepTxLbmHC OBJECT-TYPE
SYNTAX          Unsigned32(1..63)
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The Hop Count to be transmitted.
    "
REFERENCE "TRILL-FM section 3"
 ::= { trillOamMepEntry 11 }

trillOamMepTxLbmReplyModeOob OBJECT-TYPE
SYNTAX          TruthValue
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "True Indicates that Reply of Lbm is out of band and
    out of band IP Address TLV is to be transmitted.
    False indicates that In band reply is transmitted."
REFERENCE "TRILL-FM 10.1.2.1"
 ::= { trillOamMepEntry 12 }

trillOamMepTransmitLbmReplyIp OBJECT-TYPE
SYNTAX          OCTET STRING
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "IP address for out of band IP Address TLV is to be transmitted."
REFERENCE "TRILL-FM 10.1.2.1"
 ::= { trillOamMepEntry 13 }

trillOamMepTxLbmFlowEntropy OBJECT-TYPE
SYNTAX          OCTET STRING
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "128 Byte Flow Entropy as defined in TRILL-FM to be transmitted."
REFERENCE "TRILL-FM section 3"
 ::= { trillOamMepEntry 14 }
```

```
trilloamMepTxPtmDestRName OBJECT-TYPE
    SYNTAX      Unsigned32 (0..65471)
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The Target Destination Rbridge NickName Field
         as defined in RFC 6325 section 3.7 to be transmitted."
    REFERENCE   "TRILL-FM and RFC6325 section 3.7"
    ::= { trilloamMepEntry 15 }

trilloamMepTxPtmHC OBJECT-TYPE
    SYNTAX      Unsigned32 (1..63)
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "The Hop Count field to be transmitted.
         "
    REFERENCE   "TRILL-FM section 3"
    ::= { trilloamMepEntry 16 }

trilloamMepTxPtmReplyModeOob OBJECT-TYPE
    SYNTAX      TruthValue
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "True Indicates that Reply of Ptm is out of band and
         out of band IP Address TLV is to be transmitted.
         False indicates that In band reply is transmitted."
    REFERENCE   "TRILL-FM section 11"
    DEFVAL      { false }
    ::= { trilloamMepEntry 17 }

trilloamMepTransmitPtmReplyIp OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "IP address for out of band IP Address TLV is to be transmitted."
    REFERENCE   "TRILL-FM section 11"
    ::= { trilloamMepEntry 18 }

trilloamMepTxPtmFlowEntropy OBJECT-TYPE
    SYNTAX      OCTET STRING
    MAX-ACCESS   read-create
    STATUS       current
    DESCRIPTION
        "128 Byte Flow Entropy as defined in TRILL-FM to be transmitted."
    REFERENCE   "TRILL-FM section 3"
```

```
::= { trillOamMepEntry 19 }

trillOamMepTxPtmStatus OBJECT-TYPE
    SYNTAX          TruthValue
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "A Boolean flag set to true by the MEP Path Trace Initiator State
        Machine or an MIB manager to indicate that another Ptm is being
        transmitted.
        Reset to false by the MEP Initiator State Machine."
    REFERENCE "TRILL-FM section 11"
    DEFVAL          { false }
    ::= { trillOamMepEntry 20 }

trillOamMepTxPtmResultOK OBJECT-TYPE
    SYNTAX          TruthValue
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "Indicates the result of the operation:
        - true   The Path Trace Message(s) will be (or has been) sent.
        - false  The Path Trace Message(s) will not be sent."
    REFERENCE "TRILL-FM section 11"
    DEFVAL          { true }
    ::= { trillOamMepEntry 21 }

trillOamMepTxPtmMessages OBJECT-TYPE
    SYNTAX          Integer32 (1..1024)
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "The number of Path Trace messages to be transmitted."
    REFERENCE "TRILL-FM section 11"
    ::= { trillOamMepEntry 22 }

trillOamMepTxPtmSeqNumber OBJECT-TYPE
    SYNTAX          Unsigned32
    MAX-ACCESS      read-create
    STATUS          current
    DESCRIPTION
        "The Path Trace Transaction Identifier of the first PTM (to be)
        sent. The value returned is undefined if
        trillOamMepTxPtmResultOK is false."
    REFERENCE "TRILL-FM section 11"
    ::= { trillOamMepEntry 23 }

trillOamMepTxMtmTree OBJECT-TYPE
```

```
SYNTAX          Unsigned32
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The Multi-destination Tree is identifier for tree as defined in
    RFC6325."
 ::= { trillOamMepEntry 24 }

trillOamMepTxMtmHC OBJECT-TYPE
SYNTAX          Unsigned32(1..63)
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The Hop Count field to be transmitted.
    "
REFERENCE "TRILL-FM section 3, RFC 6325 section 3"
 ::= { trillOamMepEntry 25 }

trillOamMepTxMtmReplyModeOob OBJECT-TYPE
SYNTAX          TruthValue
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "True Indicates that Reply of Mtm is out of band and
    out of band IP Address TLV is to be transmitted.
    False indicates that In band reply is transmitted."
REFERENCE "TRILL-FM section 12"
 ::= { trillOamMepEntry 26 }

trillOamMepTransmitMtmReplyIp OBJECT-TYPE
SYNTAX          OCTET STRING
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "IP address for out of band IP Address TLV is to be transmitted."
REFERENCE "TRILL-FM section 12"
 ::= { trillOamMepEntry 27 }

trillOamMepTxMtmFlowEntropy OBJECT-TYPE
SYNTAX          OCTET STRING
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "128 Byte Flow Entropy as defined in TRILL-FM to be transmitted."
REFERENCE "TRILL-FM section 3"
 ::= { trillOamMepEntry 28 }

trillOamMepTxMtmStatus OBJECT-TYPE
```

```

SYNTAX          TruthValue
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "A Boolean flag set to true by the MEP Multi Destination Initiator State
    Machine or an MIB manager to indicate that another Mtm is being
    transmitted.
    Reset to false by the MEP Initiator State Machine."
REFERENCE "TRILL-FM section 12"
DEFVAL         { false }
::= { trilloamMepEntry 29 }

trilloamMepTxMtmResultOK OBJECT-TYPE
SYNTAX          TruthValue
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "Indicates the result of the operation:
    - true  The Multi-destination Message(s) will be (or has been) sent.
    - false The Multi-destination Message(s) will not be sent."
REFERENCE "TRILL-FM section 12"
DEFVAL         { true }
::= { trilloamMepEntry 30 }

trilloamMepTxMtmMessages OBJECT-TYPE
SYNTAX          Integer32 (1..1024)
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The number of Multi Destination messages to be transmitted."
REFERENCE "TRILL-FM section 12"
::= { trilloamMepEntry 31 }

trilloamMepTxMtmSeqNumber OBJECT-TYPE
SYNTAX          Unsigned32
MAX-ACCESS      read-create
STATUS          current
DESCRIPTION
    "The Multi-destination Transaction Identifier of the first MTM (to be
    sent. The value returned is undefined if
    trilloamMepTxMtmResultOK is false."
REFERENCE "TRILL-FM section 12"
::= { trilloamMepEntry 32 }

trilloamMepTxMtmScopeList OBJECT-TYPE
SYNTAX          OCTET STRING
MAX-ACCESS      read-create
STATUS          current

```



## DESCRIPTION

"The Multi-destination Rbridge Scope list, 2 OCTET per Rbridge."

REFERENCE "TRILL-FM section 12"

::= { trillOamMepEntry 33 }

```
-- *****
-- TRILL OAM Tx Measurement Configuration Table
-- *****
```

## trillOamMepFlowCfgTable OBJECT-TYPE

SYNTAX SEQUENCE OF TrillOamMepFlowCfgEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"This table includes configuration objects and operations for the Trill OAM [TRILL-FM]."

Each row in the table represents a Flow configuration Entry for the defined MEP. This table uses four indices. The first three indices are the indices of the Maintenance Domain, MaNet, and MEP tables. The fourth index is the specific Flow configuration Entry on the selected MEP.

Some writable objects in this table are only applicable in certain cases (as described under each object), and attempts to write values for them in other cases will be ignored."

REFERENCE "[TRILL-FM]"

::= { trillOamMep 2 }

## trillOamMepFlowCfgEntry OBJECT-TYPE

SYNTAX TrillOamMepFlowCfgEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The conceptual row of trillOamMepFlowCfgTable."

```
INDEX {
    dotlagCfmMdIndex,
    dotlagCfmMaIndex,
    dotlagCfmMepIdentifier,
    trillOamMepFlowCfgIndex
}
```

::= { trillOamMepFlowCfgTable 1 }

## TrillOamMepFlowCfgEntry ::= SEQUENCE {

```
    trillOamMepFlowCfgIndex      Unsigned32,
    trillOamMepFlowCfgFlowEntropy OCTET STRING,
    trillOamMepFlowCfgDestRName   Unsigned32,
```

```

        trillOamMepFlowCfgFlowHC      Unsigned32,
        trillOamMepFlowCfgRowStatus    RowStatus
    }

```

trillOamMepFlowCfgIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..65535)

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"An index to the Trill OAM Mep Flow Configuration table which indicates the specific Flow for the MEP.

The index is never reused for other flow sessions on the same MEP while this session is active. The index value keeps increasing until it wraps to 0.

This value can also be used in Flow-identifier TLV [TRILL-FM]"

REFERENCE "TRILL-FM"

::= { trillOamMepFlowCfgEntry 1 }

trillOamMepFlowCfgFlowEntropy OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"This is 128 byte of Flow Entropy as described in TRILL OAM [TRILL-FM]."

REFERENCE "TRILL-FM section 3"

::= { trillOamMepFlowCfgEntry 2 }

trillOamMepFlowCfgDestRName OBJECT-TYPE

SYNTAX Unsigned32 (0..65471)

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Target Destination Rbridge NickName Field as defined in RFC 6325 section 3.7 to be transmitted."

REFERENCE "TRILL-FM section 3 and RFC 6325 section 3.7"

::= { trillOamMepFlowCfgEntry 3 }

trillOamMepFlowCfgFlowHC OBJECT-TYPE

SYNTAX Unsigned32

MAX-ACCESS read-create

STATUS current

DESCRIPTION

"The Time to Live field to be transmitted. to be transmitted."

REFERENCE "TRILL-FM section 3 and RFC 6325 section 3.7"

::= { trillOamMepFlowCfgEntry 4 }

## trilloamMepFlowCfgRowStatus OBJECT-TYPE

SYNTAX RowStatus  
 MAX-ACCESS read-create  
 STATUS current  
 DESCRIPTION  
 "The status of the row.

The writable columns in a row cannot be changed if the row is active. All columns MUST have a valid value before a row can be activated."

::= { trilloamMepFlowCfgEntry 5 }

```
-- *****
-- TRILL OAM Path Trace Reply Table
-- *****
```

## trilloamPtrTable OBJECT-TYPE

SYNTAX SEQUENCE OF TrilloamPtrEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"This table includes Path Trace Reply objects and operations for the Trill OAM [TRILL-FM].

Each row in the table represents a Path Trace Reply Entry for the defined MEP and Transaction. This table uses four indices. The first three indices are the indices of the Maintenance Domain, MaNet, and MEP tables. The fourth index is the specific Transaction Identifier on the selected MEP.

Some writable objects in this table are only applicable in certain cases (as described under each object), and attempts to write values for them in other cases will be ignored."

REFERENCE "TRILL-FM"  
 ::= { trilloamMep 3 }

## trilloamPtrEntry OBJECT-TYPE

SYNTAX TrilloamPtrEntry  
 MAX-ACCESS not-accessible  
 STATUS current  
 DESCRIPTION

"The conceptual row of trilloamPtrTable."

INDEX {  
     dotlagCfmMdIndex,  
     dotlagCfmMaIndex,  
     dotlagCfmMepIdentifier,  
     trilloamMepPtrTransactionId

```

    }
    ::= { trillOamPtrTable 1 }

TrillOamPtrEntry ::= SEQUENCE {
    trillOamMepPtrTransactionId      Unsigned32,
    trillOamMepPtrHC                 Unsigned32,
    trillOamMepPtrFlag               Unsigned32,
    trillOamMepPtrErrorCode          Unsigned32,
    trillOamMepPtrTerminalMep        TruthValue,
    trillOamMepPtrLastEgressId       Unsigned32,
    trillOamMepPtrIngress            DotlagCfmIngressActionFieldValu
e,
    trillOamMepPtrIngressMac          MacAddress,
    trillOamMepPtrIngressPortIdSubtype LldpPortId,
    trillOamMepPtrIngressPortId      LldpPortId,
    trillOamMepPtrEgress             DotlagCfmEgressActionFieldValue
,
    trillOamMepPtrEgressMac          MacAddress,
    trillOamMepPtrEgressPortIdSubtype LldpPortId,
    trillOamMepPtrEgressPortId      LldpPortId,
    trillOamMepPtrChassisIdSubtype   LldpChassisIdSubtype,
    trillOamMepPtrChassisId          LldpChassisId,
    trillOamMepPtrOrganizationSpecificTlv OCTET STRING,
    trillOamMepPtrNextHopNicknames   OCTET STRING
}

trillOamMepPtrTransactionId OBJECT-TYPE
    SYNTAX      Unsigned32 (0..4294967295)
    MAX-ACCESS   not-accessible
    STATUS      current
    DESCRIPTION
        "Transaction identifier/sequence number returned by a previous
        transmit path trace message command, indicating which PTM's
        response is going to be returned."
    REFERENCE    "TRILL-FM section 11"
    ::= { trillOamPtrEntry 1 }

trillOamMepPtrHC OBJECT-TYPE
    SYNTAX      Unsigned32 (1..63)
    MAX-ACCESS   read-only
    STATUS      current
    DESCRIPTION
        "Hop Count field value for a returned PTR."
    REFERENCE    "TRILL-FM"
    ::= { trillOamPtrEntry 2 }

trillOamMepPtrFlag OBJECT-TYPE
    SYNTAX      Unsigned32 (0..15)
    MAX-ACCESS   read-only
    STATUS      current

```

DESCRIPTION  
"FCOI (TRILL OAM Message TLV) field value for a  
returned PTR."

REFERENCE "TRILL-FM, 9.4.2.1"  
::= { trillOamPtrEntry 3 }

trillOamMepPtrErrorCode OBJECT-TYPE  
SYNTAX Unsigned32 (0..65535)  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"Return Code and Return Sub code value for a returned PTR."  
REFERENCE "TRILL-FM, 9.4.2.1"  
::= { trillOamPtrEntry 4 }

trillOamMepPtrTerminalMep OBJECT-TYPE  
SYNTAX TruthValue  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"A boolean value stating whether the forwarded PTM reached a  
MEP enclosing its MA, as returned in the Terminal MEP flag of  
the Flags field."  
REFERENCE "TRILL-FM"  
::= { trillOamPtrEntry 5 }

trillOamMepPtrLastEgressId OBJECT-TYPE  
SYNTAX Unsigned32 (0..65535)  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"An Integer field holding the Last Egress Identifier returned  
in the PTR Upstream Rbridge nickname TLV of the PTR.  
The Last Egress Identifier identifies the Upstream Nickname"  
REFERENCE "TRILL-FM 9.4.3.4"  
::= { trillOamPtrEntry 6 }

trillOamMepPtrIngress OBJECT-TYPE  
SYNTAX DotlagCfmIngressActionFieldValue  
MAX-ACCESS read-only  
STATUS current  
DESCRIPTION  
"The value returned in the Ingress Action Field of the PTM.  
The value ingNoTlv(0) indicates that no Reply Ingress TLV was  
returned in the PTM."  
REFERENCE "TRILL-FM 9.4.1"  
::= { trillOamPtrEntry 7 }

```
trilloamMepPtrIngressMac OBJECT-TYPE
    SYNTAX          MacAddress
    MAX-ACCESS       read-only
    STATUS           current
    DESCRIPTION
        "MAC address returned in the ingress MAC address field."
    REFERENCE        "TRILL-FM 9.4.1"
    ::= { trilloamPtrEntry 8 }

trilloamMepPtrIngressPortIdSubtype OBJECT-TYPE
    SYNTAX          LldpPortId
    MAX-ACCESS       read-only
    STATUS           current
    DESCRIPTION
        "Ingress Port ID. The format of this object is determined by
         the value of the trilloamMepPtrIngressPortIdSubtype object."
    REFERENCE        "TRILL-FM 9.4.1"
    ::= { trilloamPtrEntry 9 }

trilloamMepPtrIngressPortId OBJECT-TYPE
    SYNTAX          LldpPortId
    MAX-ACCESS       read-only
    STATUS           current
    DESCRIPTION
        "Ingress Port ID. The format of this object is determined by
         the value of the trilloamMepPtrIngressPortId object."
    REFERENCE        "TRILL-FM 9.4.1"
    ::= { trilloamPtrEntry 10 }

trilloamMepPtrEgress OBJECT-TYPE
    SYNTAX          DotlagCfmEgressActionFieldValue
    MAX-ACCESS       read-only
    STATUS           current
    DESCRIPTION
        "The value returned in the Egress Action Field of the PTM.
         The value ingNoTlv(0) indicates that no Reply Egress TLV was
         returned in the PTM."
    REFERENCE        "TRILL-FM 9.4.1"
    ::= { trilloamPtrEntry 11 }

trilloamMepPtrEgressMac OBJECT-TYPE
    SYNTAX          MacAddress
    MAX-ACCESS       read-only
    STATUS           current
    DESCRIPTION
        "MAC address returned in the egress MAC address field."
    REFERENCE        "TRILL-FM 9.4.1"
    ::= { trilloamPtrEntry 12 }
```

## trilloamMepPtrEgressPortIdSubtype OBJECT-TYPE

SYNTAX               LldpPortId  
MAX-ACCESS       read-only  
STATUS           current  
DESCRIPTION  
    "Egress Port ID. The format of this object is determined by  
    the value of the trilloamMepPtrEgressPortIdSubtype object."  
REFERENCE        "TRILL-FM 9.4.1"  
::= { trilloamPtrEntry 13 }

## trilloamMepPtrEgressPortId OBJECT-TYPE

SYNTAX               LldpPortId  
MAX-ACCESS       read-only  
STATUS           current  
DESCRIPTION  
    "Egress Port ID. The format of this object is determined by  
    the value of the trilloamMepPtrEgressPortId object."  
REFERENCE        "TRILL-FM 9.4.1"  
::= { trilloamPtrEntry 14 }

## trilloamMepPtrChassisIdSubtype OBJECT-TYPE

SYNTAX               LldpChassisIdSubtype  
MAX-ACCESS       read-only  
STATUS           current  
DESCRIPTION  
    "This object specifies the format of the Chassis ID returned  
    in the Sender ID TLV of the PTR, if any. This value is  
    meaningless if the trilloamMepPtrChassisId has a length of 0."  
REFERENCE        "TRILL-FM 9.4.1"  
::= { trilloamPtrEntry 15 }

## trilloamMepPtrChassisId OBJECT-TYPE

SYNTAX               LldpChassisId  
MAX-ACCESS       read-only  
STATUS           current  
DESCRIPTION  
    "The Chassis ID returned in the Sender ID TLV of the PTR, if  
    any. The format of this object is determined by the  
    value of the trilloamMepPtrChassisIdSubtype object."  
REFERENCE        "TRILL-FM 9.4.1"  
::= { trilloamPtrEntry 16 }

## trilloamMepPtrOrganizationSpecificTlv OBJECT-TYPE

SYNTAX               OCTET STRING (SIZE (0..0 | 4..1500))  
MAX-ACCESS       read-only  
STATUS           current  
DESCRIPTION  
    "All Organization specific TLVs returned in the PTR, if

any. Includes all octets including and following the TLV Length field of each TLV, concatenated together."

REFERENCE "TRILL-FM 9.4.1"

::= { trillOamPtrEntry 17 }

trillOamMepPtrNextHopNicknames OBJECT-TYPE

SYNTAX OCTET STRING (SIZE (0..0 | 4..1500))

MAX-ACCESS read-only

STATUS current

DESCRIPTION

"Next hop Rbridge List TLV returned in the PTR, if any. Includes all octets including and following the TLV Length field of each TLV, concatenated together."

REFERENCE "TRILL-FM 9.4.3.5"

::= { trillOamPtrEntry 18 }

-- \*\*\*\*\*

-- TRILL OAM Multi Destination Reply Table

-- \*\*\*\*\*

trillOamMtrTable OBJECT-TYPE

SYNTAX SEQUENCE OF TrillOamMtrEntry

MAX-ACCESS not-accessible

STATUS current

DESCRIPTION

"This table includes Multi-destination Reply objects and operations for the Trill OAM [TRILL-FM].

Each row in the table represents a Multi-destination Reply Entry for the defined MEP and Transaction.

This table uses five indices.

The first three indices are the indices of the Maintenance Domain, MaNet, and MEP tables. The fourth index is the specific Transaction Identifier on the selected MEP.

The fifth index is the receive order of Multi-destination replies.

Some writable objects in this table are only applicable in certain cases (as described under each object), and attempts to write values for them in other cases will be ignored."

REFERENCE "TRILL-FM"

::= { trillOamMep 4 }

trillOamMtrEntry OBJECT-TYPE

SYNTAX TrillOamMtrEntry

MAX-ACCESS not-accessible

STATUS current



## DESCRIPTION

"The conceptual row of trillOamMtrTable."

```

INDEX      {
            dotlagCfmMdIndex,
            dotlagCfmMaIndex,
            dotlagCfmMepIdentifier,
            trillOamMepPtrTransactionId,
            trillOamMepMtrReceiveOrder
          }
 ::= { trillOamMtrTable 1 }

```

```

TrillOamMtrEntry ::= SEQUENCE {
    trillOamMepMtrTransactionId      Unsigned32,
    trillOamMepMtrReceiveOrder      Unsigned32,
    trillOamMepMtrFlag              Unsigned32,
    trillOamMepMtrErrorCode         Unsigned32,
    trillOamMepMtrLastEgressId      Unsigned32,
    trillOamMepMtrIngress          DotlagCfmIngressActionFieldValu
e,
    trillOamMepMtrIngressMac        MacAddress,
    trillOamMepMtrIngressPortIdSubtype LldpPortId,
    trillOamMepMtrIngressPortId     LldpPortId,
    trillOamMepMtrEgress            DotlagCfmEgressActionFieldValue
,
    trillOamMepMtrEgressMac        MacAddress,
    trillOamMepMtrEgressPortIdSubtype LldpPortId,
    trillOamMepMtrEgressPortId     LldpPortId,
    trillOamMepMtrChassisIdSubtype  LldpChassisIdSubtype,
    trillOamMepMtrChassisId        LldpChassisId,
    trillOamMepMtrOrganizationSpecificTlv OCTET STRING,
    trillOamMepMtrNextHopNicknames  OCTET STRING,
    trillOamMepMtrReceiverAvailability TruthValue,
    trillOamMepMtrReceiverCount     TruthValue
}

```

## trillOamMepMtrTransactionId OBJECT-TYPE

```

SYNTAX      Unsigned32 (0..4294967295)
MAX-ACCESS  not-accessible
STATUS      current
DESCRIPTION

```

"Transaction identifier/sequence number returned by a previous transmit Multi-destination message command, indicating which MTM's response is going to be returned."

REFERENCE "TRILL-FM section 12"

```
 ::= { trillOamMtrEntry 1 }
```

## trillOamMepMtrReceiveOrder OBJECT-TYPE

```

SYNTAX      Unsigned32 (1..4294967295)
MAX-ACCESS  not-accessible
STATUS      current

```

## DESCRIPTION

"An index to distinguish among multiple MTR with same MTR Transaction Identifier field value. trilloamMepMtrReceiveOrder are assigned sequentially from 1, in the order that the Multi-destination Tree Initiator received the MTRs."

REFERENCE "TRILL-FM"

::= { trilloamMtrEntry 2 }

## trilloamMepMtrFlag OBJECT-TYPE

SYNTAX Unsigned32 (0..15)

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"FCOI (TRILL OAM Message TLV) field value for a returned MTR."

REFERENCE "TRILL-FM, 9.4.2.1"

::= { trilloamMtrEntry 3 }

## trilloamMepMtrErrorCode OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"Return Code and Return Sub code value for a returned MTR."

REFERENCE "TRILL-FM, 9.4.2.1"

::= { trilloamMtrEntry 4 }

## trilloamMepMtrLastEgressId OBJECT-TYPE

SYNTAX Unsigned32 (0..65535)

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"An Integer field holding the Last Egress Identifier returned in the MTR Upstream Rbridge Nickname TLV of the MTR."

The Last Egress Identifier identifies the Upstream Nickname."

REFERENCE "TRILL-FM 9.4.3.4"

::= { trilloamMtrEntry 5 }

## trilloamMepMtrIngress OBJECT-TYPE

SYNTAX DotlagCfmIngressActionFieldValue

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"The value returned in the Ingress Action Field of the MTR."

The value ingNoTlv(0) indicates that no Reply Ingress TLV was returned in the MTM."

REFERENCE "TRILL-FM 12.2.3"

```
::= { trillOamMtrEntry 6 }

trillOamMepMtrIngressMac OBJECT-TYPE
    SYNTAX          MacAddress
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "MAC address returned in the ingress MAC address field."
    REFERENCE       "TRILL-FM 12.2.3"
    ::= { trillOamMtrEntry 7 }

trillOamMepMtrIngressPortIdSubtype OBJECT-TYPE
    SYNTAX          LldpPortId
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Ingress Port ID. The format of this object is determined by
         the value of the trillOamMepMtrIngressPortIdSubtype object."
    REFERENCE       "TRILL-FM 12.2.3"
    ::= { trillOamMtrEntry 8 }

trillOamMepMtrIngressPortId OBJECT-TYPE
    SYNTAX          LldpPortId
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "Ingress Port ID. The format of this object is determined by
         the value of the trillOamMepMtrIngressPortId object."
    REFERENCE       "TRILL-FM 12.2.3"
    ::= { trillOamMtrEntry 9 }

trillOamMepMtrEgress OBJECT-TYPE
    SYNTAX          DotlagCfmEgressActionFieldValue
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "The value returned in the Egress Action Field of the MTR.
         The value ingNoTlv(0) indicates that no Reply Egress TLV was
         returned in the MTR."
    REFERENCE       "TRILL-FM 12.2.3"
    ::= { trillOamMtrEntry 10 }

trillOamMepMtrEgressMac OBJECT-TYPE
    SYNTAX          MacAddress
    MAX-ACCESS      read-only
    STATUS          current
    DESCRIPTION
        "MAC address returned in the egress MAC address field."
```

```
REFERENCE          "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 11 }

trillOamMepMtrEgressPortIdSubtype OBJECT-TYPE
SYNTAX              LldpPortId
MAX-ACCESS          read-only
STATUS              current
DESCRIPTION
    "Egress Port ID. The format of this object is determined by
    the value of the trillOamMepMtrEgressPortIdSubtype object."
REFERENCE          "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 12 }

trillOamMepMtrEgressPortId OBJECT-TYPE
SYNTAX              LldpPortId
MAX-ACCESS          read-only
STATUS              current
DESCRIPTION
    "Egress Port ID. The format of this object is determined by
    the value of the trillOamMepMtrEgressPortId object."
REFERENCE          "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 13 }

trillOamMepMtrChassisIdSubtype OBJECT-TYPE
SYNTAX              LldpChassisIdSubtype
MAX-ACCESS          read-only
STATUS              current
DESCRIPTION
    "This object specifies the format of the Chassis ID returned
    in the Sender ID TLV of the MTR, if any. This value is
    meaningless if the trillOamMepMtrChassisId has a length of 0."
REFERENCE          "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 14 }

trillOamMepMtrChassisId OBJECT-TYPE
SYNTAX              LldpChassisId
MAX-ACCESS          read-only
STATUS              current
DESCRIPTION
    "The Chassis ID returned in the Sender ID TLV of the MTR, if
    any. The format of this object is determined by the
    value of the trillOamMepMtrChassisIdSubtype object."
REFERENCE          "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 15 }

trillOamMepMtrOrganizationSpecificTlv OBJECT-TYPE
SYNTAX              OCTET STRING (SIZE (0..0 | 4..1500))
MAX-ACCESS          read-only
```

```

STATUS          current
DESCRIPTION
    "All Organization specific TLVs returned in the MTR, if
    any. Includes all octets including and following the TLV
    Length field of each TLV, concatenated together."
REFERENCE        "TRILL-FM 12.2.3"
::= { trillOamMtrEntry 16 }

trillOamMepMtrNextHopNicknames OBJECT-TYPE
SYNTAX           OCTET STRING (SIZE (0..0 | 4..1500))
MAX-ACCESS       read-only
STATUS           current
DESCRIPTION
    "Next hop Rbridge List TLV returned in the PTR, if
    any. Includes all octets including and following the TLV
    Length field of each TLV, concatenated together."
REFERENCE        "TRILL-FM 9.4.3.5"
::= { trillOamMtrEntry 17 }

trillOamMepMtrReceiverAvailability OBJECT-TYPE
SYNTAX           TruthValue
MAX-ACCESS       read-only
STATUS           current
DESCRIPTION
    "True value indicates that MTR response contained
    Multicast receiver availability TLV"
REFERENCE        "TRILL-FM 9.4.3.6"
::= { trillOamMtrEntry 18 }

trillOamMepMtrReceiverCount OBJECT-TYPE
SYNTAX           TruthValue
MAX-ACCESS       read-only
STATUS           current
DESCRIPTION
    "Indicates the number of Multicast receivers available on
    responding RBridge on the VLAN specified by the
    diagnostic VLAN."
REFERENCE        "TRILL-FM 9.4.3.6"
::= { trillOamMtrEntry 19 }

-- *****
-- TRILL OAM MEP Database Table
-- *****

trillOamMepDbTable OBJECT-TYPE
SYNTAX           SEQUENCE OF TrillOamMepDbEntry
MAX-ACCESS       not-accessible
STATUS           current

```

## DESCRIPTION

"This table is an extension of the dotlagCfmMepDbTable and rows are automatically added or deleted from this table based upon row creation and destruction of the dotlagCfmMepDbTable."

## REFERENCE

"[TRILL-FM]"

::= { trillOamMep 5 }

## trillOamMepDbEntry OBJECT-TYPE

SYNTAX TrillOamMepDbEntry

MAX-ACCESS not-accessible

STATUS current

## DESCRIPTION

"The conceptual row of trillOamMepDbTable."

AUGMENTS {  
dotlagCfmMepDbEntry  
}

::= { trillOamMepDbTable 1 }

## TrillOamMepDbEntry ::= SEQUENCE {

trillOamMepDbFlowIndex	Unsigned32,
trillOamMepDbFlowEntropy	OCTET STRING,
trillOamMepDbFlowState	DotlagCfmRemoteMepState,
trillOamMepDbFlowFailedOkTime	TimeStamp,
trillOamMepDbRbridgeName	Unsigned32,
trillOamMepDbLastGoodSeqNum	Counter32

}

## trillOamMepDbFlowIndex OBJECT-TYPE

SYNTAX Unsigned32 (1..65535)

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"This object identifies the Flow. If Flow Identifier TLV is received than index received can also be used."

## REFERENCE "TRILL-FM"

::= {trillOamMepDbEntry 1 }

## trillOamMepDbFlowEntropy OBJECT-TYPE

SYNTAX OCTET STRING

MAX-ACCESS read-only

STATUS current

## DESCRIPTION

"128 byte Flow Entropy."

"

REFERENCE "TRILL-FM section 3."

```

 ::= {trillOamMepDbEntry 2 }

trillOamMepDbFlowState OBJECT-TYPE
    SYNTAX      DotlagCfmRemoteMepState
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The operational state of the remote MEP (flow based)
        IFF State machines. State Machine is running now per
        flow."
    REFERENCE "TRILL-FM"
    ::= {trillOamMepDbEntry 3 }

trillOamMepDbFlowFailedOkTime OBJECT-TYPE
    SYNTAX      TimeStamp
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "The Time (sysUpTime) at which the Remote Mep Flow state
        machine last entered either the RMEP_FAILED or RMEP_OK
        state.
        "
    REFERENCE "TRILL-FM"
    ::= {trillOamMepDbEntry 4 }

trillOamMepDbRbridgeName OBJECT-TYPE
    SYNTAX      Unsigned32(0..65471)
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Remote MEP Rbridge Nickname"
    REFERENCE "TRILL-FM RFC 6325 section 3"
    ::= {trillOamMepDbEntry 5 }

trillOamMepDbLastGoodSeqNum OBJECT-TYPE
    SYNTAX      Counter32
    MAX-ACCESS   read-only
    STATUS       current
    DESCRIPTION
        "Last Sequence Number received."
    REFERENCE "TRILL-FM 13.1"
    ::= {trillOamMepDbEntry 6}

-- *****
***
-- TRILL OAM MIB NOTIFICATIONS (TRAPS)
-- This notification is sent to management entity whenever a MEP loses/restor
es
-- contact with its peer Flow Meps
-- *****
***

```

## trillOamFaultAlarm NOTIFICATION-TYPE

OBJECTS { trillOamMepDbFlowState }

STATUS current

## DESCRIPTION

"A MEP Flow has a persistent defect condition.  
A notification (fault alarm) is sent to the management  
entity with the OID of the Flow that has detected the fault.

The management entity receiving the notification can identify  
the system from the network source address of the  
notification, and can identify the Flow reporting the defect  
by the indices in the OID of the  
trillOamMepFlowIndex, and trillOamFlowDefect  
variable in the notification:

dotlagCfmMdIndex - Also the index of the MEP's  
Maintenance Domain table entry  
(dotlagCfmMdTable).

dotlagCfmMaIndex - Also an index (with the MD table index)  
of the MEP's Maintenance Association  
network table entry  
(dotlagCfmMaNetTable), and (with the MD  
table index and component ID) of the  
MEP's MA component table entry  
(dotlagCfmMaCompTable).

dotlagCfmMepIdentifier - MEP Identifier and final index  
into the MEP table (dotlagCfmMepTable).

trillOamMepFlowCfgIndex - Index identifies  
indicates the specific Flow for the MEP"

REFERENCE "TRILL-FM"

::= { trillOamNotifications 1 }

```
-- *****
***
-- TRILL OAM MIB Module - Conformance Information
-- *****
***
```

## trillOamMibCompliances OBJECT IDENTIFIER

::= { trillOamMibConformance 1 }

## trillOamMibGroups OBJECT IDENTIFIER

::= { trillOamMibConformance 2 }

```
-- *****
-- TRILL OAM MIB Units of conformance
-- *****
```

## trillOamMepMandatoryGroup OBJECT-GROUP



```

OBJECTS      {
    trillOamMepRName,
    trillOamMepNextPtmTid,
    trillOamMepNextMtmTid,
    trillOamMepPtrIn,
    trillOamMepPtrInOutOfOrder,
    trillOamMepPtrOut,
    trillOamMepMtrIn,
    trillOamMepMtrInOutOfOrder,
    trillOamMepMtrOut,
    trillOamMepTxLbmDestRName,
    trillOamMepTxLbmHC,
    trillOamMepTxLbmReplyModeOob,
    trillOamMepTransmitLbmReplyIp,
    trillOamMepTxLbmFlowEntropy,
    trillOamMepTxPtmDestRName,
    trillOamMepTxPtmHC,
    trillOamMepTxPtmReplyModeOob,
    trillOamMepTransmitPtmReplyIp,
    trillOamMepTxPtmFlowEntropy,
    trillOamMepTxPtmStatus,
    trillOamMepTxPtmResultOK,
    trillOamMepTxPtmMessages,
    trillOamMepTxPtmSeqNumber,
    trillOamMepTxMtmTree,
    trillOamMepTxMtmHC,
    trillOamMepTxMtmReplyModeOob,
    trillOamMepTransmitMtmReplyIp,
    trillOamMepTxMtmFlowEntropy,
    trillOamMepTxMtmStatus,
    trillOamMepTxMtmResultOK,
    trillOamMepTxMtmMessages,
    trillOamMepTxMtmSeqNumber,
    trillOamMepTxMtmScopeList
}
STATUS      current
DESCRIPTION
    "Mandatory objects for the TRILL OAM MEP group."
 ::= { trillOamMibGroups 1 }

trillOamMepFlowCfgTableGroup OBJECT-GROUP
    OBJECTS      {
        trillOamMepFlowCfgFlowEntropy,
        trillOamMepFlowCfgDestRName,
        trillOamMepFlowCfgFlowHC,
        trillOamMepFlowCfgRowStatus
    }
    STATUS      current

```

## DESCRIPTION

"Trill OAM MEP Flow Configuration objects group."  
 ::= { trillOamMibGroups 2 }

trillOamPtrTableGroup OBJECT-GROUP

OBJECTS {  
trillOamMepPtrHC,  
trillOamMepPtrFlag,  
trillOamMepPtrErrorCode,  
trillOamMepPtrTerminalMep,  
trillOamMepPtrLastEgressId,  
trillOamMepPtrIngress,  
trillOamMepPtrIngressMac,  
trillOamMepPtrIngressPortIdSubtype,  
trillOamMepPtrIngressPortId,  
trillOamMepPtrEgress,  
trillOamMepPtrEgressMac,  
trillOamMepPtrEgressPortIdSubtype,  
trillOamMepPtrEgressPortId,  
trillOamMepPtrChassisIdSubtype,  
trillOamMepPtrChassisId,  
trillOamMepPtrOrganizationSpecificTlv,  
trillOamMepPtrNextHopNicknames  
}

STATUS current

## DESCRIPTION

"Trill OAM MEP PTR objects group."  
 ::= { trillOamMibGroups 3 }

trillOamMtrTableGroup OBJECT-GROUP

OBJECTS {  
trillOamMepMtrFlag,  
trillOamMepMtrErrorCode,  
trillOamMepMtrLastEgressId,  
trillOamMepMtrIngress,  
trillOamMepMtrIngressMac,  
trillOamMepMtrIngressPortIdSubtype,  
trillOamMepMtrIngressPortId,  
trillOamMepMtrEgress,  
trillOamMepMtrEgressMac,  
trillOamMepMtrEgressPortIdSubtype,  
trillOamMepMtrEgressPortId,  
trillOamMepMtrChassisIdSubtype,  
trillOamMepMtrChassisId,  
trillOamMepMtrOrganizationSpecificTlv,  
trillOamMepMtrNextHopNicknames,  
trillOamMepMtrReceiverAvailability,  
trillOamMepMtrReceiverCount  
}

```

        }
        STATUS          current
        DESCRIPTION
            "Trill OAM MEP MTR objects group."
        ::= { trillOamMibGroups 4 }

trillOamMepDbGroup OBJECT-GROUP
    OBJECTS {
        trillOamMepDbFlowIndex,
        trillOamMepDbFlowEntropy,
        trillOamMepDbFlowState,
        trillOamMepDbFlowFailedOkTime,
        trillOamMepDbRbridgeName,
        trillOamMepDbLastGoodSeqNum
    }

    STATUS          current
    DESCRIPTION
        "Trill OAM MEP DB objects group."
    ::= { trillOamMibGroups 5 }

trillOamNotificationGroup NOTIFICATION-GROUP
    NOTIFICATIONS {
        trillOamFaultAlarm
    }
    STATUS current
    DESCRIPTION
        "Objects for Notification Group"
    ::= { trillOamMibGroups 6 }

-- *****
-- TRILL OAM MIB Module Compliance statements
-- *****

trillOamMibCompliance MODULE-COMPLIANCE
    STATUS          current
    DESCRIPTION
        "The compliance statement for the TRILL OAM MIB."
    MODULE          -- this module
    MANDATORY-GROUPS {
        trillOamMepMandatoryGroup,
        trillOamMepFlowCfgTableGroup,
        trillOamPtrTableGroup,
        trillOamMtrTableGroup,
        trillOamMepDbGroup,
        trillOamNotificationGroup
    }
    ::= { trillOamMibCompliances 1 }

```

```
-- Compliance requirement for read-only implementation.

trillOamMibReadOnlyCompliance MODULE-COMPLIANCE
  STATUS current
  DESCRIPTION
    "Compliance requirement for implementation that only
    provide read-only support for TRILL-OAM-MIB.
    Such devices can be monitored but cannot be configured
    using this MIB module
    "
  MODULE -- this module
  MANDATORY-GROUPS {
    trillOamMepMandatoryGroup,
    trillOamMepFlowCfgTableGroup,
    trillOamPtrTableGroup,
    trillOamMtrTableGroup,
    trillOamMepDbGroup,
    trillOamNotificationGroup
  }
  -- trillOamMepTable

  OBJECT trillOamMepTxLbmDestRName
  MIN-ACCESS read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT trillOamMepTxLbmHC
  MIN-ACCESS read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT trillOamMepTxLbmReplyModeOob
  MIN-ACCESS read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT trillOamMepTransmitLbmReplyIp
  MIN-ACCESS read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT trillOamMepTxLbmFlowEntropy
  MIN-ACCESS read-only
  DESCRIPTION
    "Write access is not required."

  OBJECT trillOamMepTxPtmDestRName
  MIN-ACCESS read-only
```

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmHC

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmReplyModeOob

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTransmitPtmReplyIp

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmFlowEntropy

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmStatus

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmResultOK

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmMessages

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxPtmSeqNumber

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

OBJECT trillOamMepTxMtmTree

MIN-ACCESS read-only

## DESCRIPTION

"Write access is not required."

```
OBJECT trillOamMepTxMtmHC
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmReplyModeOob
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTransmitMtmReplyIp
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmFlowEntropy
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmStatus
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmResultOK
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmMessages
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmSeqNumber
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepTxMtmScopeList
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

-- trillOamMepFlowCfgTable
```

```
OBJECT trillOamMepFlowCfgFlowEntropy
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepFlowCfgDestRName
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepFlowCfgFlowHC
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."

OBJECT trillOamMepFlowCfgRowStatus
MIN-ACCESS read-only
DESCRIPTION
    "Write access is not required."
```

```
::= { trillOamMibCompliances 2 }
```

END

## 8. Security Considerations

This MIB relates to a system that will provide network connectivity and packet forwarding services. As such, improper manipulation of the objects represented by this MIB may result in denial of service to a large number of end-users.

There are number of management objects defined in this MIB module with a MAX-ACCESS clause of read-create. Such objects may be considered sensitive or vulnerable in some network environments. The support for SET operations in a non-secure environment without proper protection can have negative effect on sensitivity/vulnerability are described below.

Some of the readable objects in this MIB module (objects with a MAX-ACCESS other than not-accessible) may be considered sensitive or vulnerable in some network environments. It is thus important to control GET and/or NOTIFY access to these objects and possibly to encrypt the values of these objects when sending them over the network via SNMP.

SNMP version prior to SNMPv3 did not include adequate security. Even

if the network itself is secure, there is no control as to who on the secure network is allowed to access and GET/SET (read/change/create/delete) the objects in this MIB module.

It is RECOMMENDED that implementers consider the security features as provided by the SNMPv3 framework (see [RFC3410], section 8), including full support for the SNMPv3 cryptographic mechanism (for authentication and privacy).

Further, deployment of SNMP version prior to SNMPv3 is NOT RECOMMENDED. Instead, it is RECOMMENDED to deploy SNMPv3 and to enable cryptographic security. It is then a customer/operator responsibility to ensure that the SNMP entity giving access to an instance of this MIB module is properly configured to give access to the objects only to those principals (users) that have legitimate rights to indeed GET or SET (change/create/delete) them.

## 9. IANA Considerations

The MIB module in this document uses the following IANA-assigned OBJECT IDENTIFIER value recorded in the SMI Numbers registry:

Descriptor	OBJECT IDENTIFIER	value
-----		
trillOamMIB	{ mib-2 xxx }	

Editor's Note (to be removed prior to publication): the IANA is requested to assign a value for "xxx" under the 'mib-2' subtree and to record the assignment in the SMI Numbers registry. When the assignment has been made, the RFC Editor is asked to replace "XXX" (here and in the MIB module) with the assigned value and to remove this note.

## 10. References

### 10.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997.

[RFC2578] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Structure of Management Information Version 2 (SMIv2)", STD 58, RFC 2578, April 1999.

[RFC2579] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Textual Conventions for SMIv2", STD



58, RFC 2579, April 1999.

[RFC2580] McCloghrie, K., Ed., Perkins, D., Ed., and J. Schoenwaelder, Ed., "Conformance Statements for SMIPv2", STD 58, RFC 2580, April 1999.

[RFC3410] Case, J., Mundy, R., Partain, D., and B. Stewart, "Introduction and Applicability Statements for Internet-Standard Management Framework", RFC 3410, December 2002.

## 10.2. Informative References

[RFC6905] Senevirathne, T., Bond, D., Aldrin, S., Li, Y., and R. Watve, "Requirements for Operations, Administration, and Maintenance (OAM) in Transparent Interconnection of Lots of Links (TRILL)", RFC 6905, March 2013.

[TRILLOAMFM] Salam, S., et.al., "TRILL OAM Framework", draft-ietf-trill-oam-framework, Work in Progress, November, 2012.

[TRILL-FM] Senevirathne, T., et.al., "TRILL Fault Management", draft-tissa-trill-oam-fm, Work in Progress, February, 2013.

## 11. Acknowledgments

We wish to thank members of the IETF TRILL WG for their comments and suggestions. Detailed comments were provided by Sam Aldrin, and Donald Eastlake.

Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved. Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in Section 4.c of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved. Redistribution and use in source and binary forms, with or without modification, are permitted provided that the following conditions are met:

- o Redistributions of source code must retain the above copyright notice, this list of conditions and the following disclaimer.

- o Redistributions in binary form must reproduce the above copyright notice, this list of conditions and the following disclaimer in the documentation and/or other materials provided with the distribution.

- o Neither the name of Internet Society, IETF or IETF Trust, nor the names of specific contributors, may be used to endorse or promote products derived from this software without specific prior written permission.

THIS SOFTWARE IS PROVIDED BY THE COPYRIGHT HOLDERS AND CONTRIBUTORS "AS IS" AND ANY EXPRESS OR IMPLIED WARRANTIES, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE DISCLAIMED. IN NO EVENT SHALL THE COPYRIGHT OWNER OR CONTRIBUTORS BE LIABLE FOR ANY DIRECT, INDIRECT, INCIDENTAL, SPECIAL, EXEMPLARY, OR CONSEQUENTIAL DAMAGES (INCLUDING, BUT NOT LIMITED TO, PROCUREMENT OF SUBSTITUTE GOODS OR SERVICES; LOSS OF USE, DATA, OR PROFITS; OR BUSINESS INTERRUPTION) HOWEVER CAUSED AND ON ANY THEORY OF LIABILITY, WHETHER IN CONTRACT, STRICT LIABILITY, OR TORT (INCLUDING NEGLIGENCE OR OTHERWISE) ARISING IN ANY WAY OUT OF THE USE OF THIS SOFTWARE, EVEN IF ADVISED OF THE POSSIBILITY OF SUCH DAMAGE.

#### Authors' Addresses

Deepak Kumar  
Cisco  
510 McCarthy Blvd,  
Milpitas, CA 95035, USA  
Phone : +1 408-853-9760  
Email: dekumar@cisco.com

Samer Salam  
Cisco  
595 Burrard St. Suite 2123  
Vancouver, BC V7X 1J1, Canada  
Email: ssalam@cisco.com

Tissa Senevirathne  
Cisco  
375 East Tasman Drive  
San Jose, CA 95134, USA  
Email: tsenevir@cisco.com