

PCE Working Group
Internet-Draft
Intended status: Standards Track
Expires: January 7, 2016

Quintin Zhao
Robin Li
Huawei Technologies
King Ke
Tencent Holdings Ltd.
Luyuan Fang
Microsoft
Chao Zhou
Cisco Systems
Boris Zhang
Telus Communications
July 6, 2015

The Use Cases for Using PCE as the Central Controller(PCECC) of LSPs
draft-zhao-pce-central-controller-user-cases-02

Abstract

In certain networks deployment scenarios, service providers would like to keep all the existing MPLS functionalities in both MPLS and GMPLS network while removing the complexity of existing signaling protocols such as LDP and RSVP-TE. In this document, we propose to use the PCE as a central controller so that LSP can be calculated/signaled/initiated/downloaded/managed through a centralized PCE server to each network devices along the LSP path while leveraging the existing PCE technologies as much as possible.

This draft describes the use cases for using the PCE as the central controller where LSPs are calculated/setup/initiated/downloaded/maintained through extending the current PCE architectures and extending the PCEP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 7, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
1.1. Background	3
1.2. Using the PCE as the Central Controller (PCECC) Approach	4
2. Terminology	7
3. PCEP Requirements	7
4. Use Cases of PCECC for Label Resource Reservations	8
5. Using PCECC for SR without the IGP Extension	9
5.1. Use Cases of PCECC for SR Best Effort(BE) Path	10
5.2. Use Cases of PCECC for SR Traffic Engineering (TE) Path	11
6. Use Cases of PCECC for TE LSP	12
7. Use Cases of PCECC for Multicast LSPs	14
7.1. Using PCECC for P2MP/MP2MP LSPs' Setup	14
7.2. Use Cases of PCECC for the Resiliency of P2MP/MP2MP LSPs	15
7.2.1. PCECC for the End-to-End Protection of the P2MP/MP2MP LSPs	15
7.2.2. PCECC for the Local Protection of the P2MP/MP2MP LSPs	16
8. Use Cases of PCECC for LSP in the Network Migration	17
9. Use Cases of PCECC for L3VPN and PWE3	19
10. The Considerations for PCECC Procedure and PCEP extensions	19
11. IANA Considerations	20
12. Security Considerations	20
13. Acknowledgments	20
14. References	20
14.1. Normative References	20
14.2. Informative References	20

1. Introduction

1.1. Background

In certain network deployment scenarios, service providers would like to have the ability to dynamically adapt to a wide range of customer's requests for the sake of flexible network service delivery, SDN has provides additional flexibility in how the network is operated comparing the traditional network.

The existing networking ecosystem has become awfully complex and highly demanding in terms of robustness, performance, scalability, flexibility, agility, etc. By migrating to the SDN enabled network from the existing network, service providers and network operators must have a solution which they can evolve easily from the existing network into the SDN enabled network while keeping the network services remain scalable, guarantee robustness and availability etc.

Taking the smooth transition between traditional network and the new SDN enabled network into account, especially from a cost impact assessment perspective, using the existing PCE components from the current network to function as the central controller of the SDN network is one choice, which not only achieves the goal of having a centralized controller to provide the functionalities needed for the central controller, but also leverages the existing PCE network components.

The Path Computation Element communication Protocol (PCEP) provides mechanisms for Path Computation Elements (PCEs) to perform route computations in response to Path Computation Clients (PCCs) requests. PCEP Extensions for PCE-initiated LSP Setup in a Stateful PCE Model draft [I-D. draft-ietf-pce- stateful-pce] describes a set of extensions to PCEP to enable active control of MPLS-TE and GMPLS tunnels.

[I-D.crabbe-pce-pce-initiated-lsp] describes the setup and teardown of PCE-initiated LSPs under the active stateful PCE model, without the need for local configuration on the PCC, thus allowing for a dynamic MPLS network that is centrally controlled and deployed.

[I-D.ali-pce-remote-initiated-gmpls-lsp] complements [I-D. draft-crabbe-pce-pce-initiated-lsp] by addressing the requirements for remote-initiated GMPLS LSPs.

SR technology leverages the source routing and tunneling paradigms. A source node can choose a path without relying on hop-by-hop signaling protocols such as LDP or RSVP-TE. Each path is specified as a set of "segments" advertised by link-state routing protocols

(IS-IS or OSPF). [I-D.filsfils-spring-segment-routing] provides an introduction to SR technology. The corresponding IS-IS and OSPF extensions are specified in [I-D.ietf-isis-segment-routing-extensions] and [I-D.psenak-ospf-segment-routing-extensions], respectively.

A Segment Routed path (SR path) can be derived from an IGP Shortest Path Tree (SPT). Segment Routed Traffic Engineering paths (SR-TE paths) may not follow IGP SPT. Such paths may be chosen by a suitable network planning tool and provisioned on the source node of the SR-TE path.

It is possible to use a stateful PCE for computing one or more SR-TE paths taking into account various constraints and objective functions. Once a path is chosen, the stateful PCE can instantiate an SR-TE path on a PCC using PCEP extensions specified in [I-D.crabbe-pce-pce-initiated-lsp] using the SR specific PCEP extensions described in [I-D.sivabalan-pce-segment-routing].

By using the solutions provided from above drafts, LSP in both MPLS and GMPLS network can be setup/delete/maintained/synchronized through a centrally controlled dynamic MPLS network. Since in these solutions, the LSP is need to be signaled through the head end LER to the tail end LER, there are either RSVP-TE signaling protocol need to be deployed in the MPLS/GMPLS network, or extend TGP protocol with node/adjacency segment identifiers signaling capability to be deployed.

The PCECC solution proposed in this document allow for a dynamic MPLS network that is eventually controlled and deployed without the deployment of RSVP-TE protocol or extended IGP protocol with node/adjacency segment identifiers signaling capability while providing all the key MPLS functionalities needed by the service providers. These key MPLS features include MPLS P2P LSP, P2MP/MP2MP LSP, MPLS protection mechanism etc. In the case that one LSP path consists legacy network nodes and the new network nodes which are centrally controlled, the PCECC solution provides a smooth transition step for users.

1.2. Using the PCE as the Central Controller (PCECC) Approach

With PCECC, it not only removes the existing MPLS signaling totally from the control plane without losing any existing MPLS functionalities, but also PCECC achieves this goal through utilizing the existing PCEP without introducing a new protocol into the network.

The following diagram illustrates the PCECC architecture.




Figure 1: PCECC Architecture

Through the draft, we call the combination of the functionality for global label range signaling and the functionality of LSP setup/download/cleanup using the combination of global labels and local labels as PCECC functionality.

Current MPLS label has local meaning. That is, MPLS label allocated locally and signaled through the LDP/RSVP-TE/BGP etc dynamic signaling protocol.

As the SDN(Service-Driven Network) technology develops, MPLS global label has been proposed again for new solutions. [I-D.li-mpls-global-label-usecases] proposes possible usecases of MPLS global label. MPLS global label can be used for identification of the location, the service and the network in different application scenarios. From these usecases we can see that no matter SDN or traditional application scenarios, the new solutions based on MPLS global label can gain advantage over the existing solutions to facilitate service provisions. The solution choices are described in [I-D.li-mpls-global-label-framework].

To ease the label allocation and signaling mechanism, also with the new applications such as concentrated LSP controller is introduced, PCE can be conveniently used as a central controller and MPLS global label range negotiator.

The later section of this draft describes the user cases for PCE server and PCE clients to have the global label range negotiation and local label range negotiation functionality.

To empower networking with centralized controllable modules, there are many choices for downloading the forwarding entries to the data plane, one way is the use of the OpenFlow protocol, which helps devices populate their forwarding tables according to a set of instructions to the data plane. There are other candidate protocols to convey specific configuration information towards devices also. Since the PCEP protocol is already deployed in some of the service network, to leverage the PCEP to populated the MPLS forwarding table is a possible good choice.

For the centralized network, the performance achieved through distributed system can not be easy matched if all of the forwarding path is computed, downloaded and maintained by the centralized controller. The performance can be improved by supporting part of the forwarding path in the PCECC network through the segment routing mechanism except that the adjacency IDs for all the network nodes and links are propagated through the centralized controller instead of using the IGP extension.

The node and link adjacency IDs can be negotiated through the PCECC with each PCECC clients and these IDs can be just taken from the global label range which has been negotiated already.

With the capability of supporting SR within the PCECC architecture, all the p2p forwarding path protection use cases described in the draft [I-D.ietf-spring-resiliency-use-cases] will be supported too within the PCECC network. These protection alternatives include end-to-end path protection, local protection without operator management and local protection with operator management.

With the capability of global label and local label existing at the same time in the PCECC network, PCECC will use compute, setup and maintain the P2MP and MP2MP lsp using the local label range for each network nodes.

With the capability of setting up/maintaining the P2MP/MP2MP LSP within the PCECC network, it is easy to provide the end-end managed path protection service and the local protection with the operation management in the PCECC network for the P2MP/MP2MP LSP, which includes both the RSVP-TE P2MP based LSP and also the mLDP based LSP.

2. Terminology

The following terminology is used in this document.

IGP: Interior Gateway Protocol. Either of the two routing protocols, Open Shortest Path First (OSPF) or Intermediate System to Intermediate System (IS-IS).

PCC: Path Computation Client: any client application requesting a path computation to be performed by a Path Computation Element.

PCE: Path Computation Element. An entity (component, application, or network node) that is capable of computing a network path or route based on a network graph and applying computational constraints.

TE: Traffic Engineering.

3. PCEP Requirements

Following key requirements associated PCECC should be considered when designing the PCECC based solution:

1. Path Computation Element (PCE) clients supporting this draft MUST have the capability to advertise its PCECC capability to the PCECC.
2. Path Computation Element (PCE) supporting this draft MUST have the capability to negotiate a global label range for a group of clients.
3. Path Computation Client (PCC) MUST be able ask for global label range assigned in path request message .
4. PCE are not required to support label reserve service. Therefore, it MUST be possible for a PCE to reject a Path Computation Request message with a reason code that indicates no support for label reserve service.
5. PCEP SHOULD provide a means to return global label range and LSP label assignments of the computed path in the reply message.
6. PCEP SHOULD provide a means to download the MPLS forwarding entry to the PCECC's clients.

4. Use Cases of PCECC for Label Resource Reservations

Example 1 to 2 are based on network configurations illustrated using the following figure:




Figure 2: Using PCECC for Global Label Allocation

Example 1: Shared Global Label Range Reservation

- o PCECC Clients nodes report MPLS label capability to the central controller PCECC.
- o The central controller PCECC collects MPLS label capability of all nodes. Then PCECC can calculate the shared MPLS global label range for all the PCECC client nodes.
- o In the case that the shared global label range need to be negotiated across multiple domains, the central controllers of these domains need to be communicate to negotiate a common global label range.
- o The central controller PCECC notifies the shared global label range to all PCECC client nodes.

Example 2: Global Label Allocation

- o PCECC Client node1 send global label allocation request to the central controller PCECC1.
- o The central controller PCECC1 allocates the global label for FEC1 from the shared global label range and sends the reply to the client node1.
- o The central controller PCECC1 notifies the allocated label for FEC1 to all PCECC client nodes within domain 1.

5. Using PCECC for SR without the IGP Extension

For the centralized network, the performance achieved through distributed system can not be easily matched if all of the forwarding path is computed, downloaded and maintained by the centralized controller. The performance can be improved by supporting part of the forwarding path in the PCECC network through the segment routing mechanism except that node segment IDs and adjacency segment IDs for all the network are allocated dynamically and propagated through the centralized controller instead of using the IGP extension.

When the PCECC is used for the distribution of the node segment ID and adjacency segment ID, the node segment ID is allocated from the global label pool. For the allocation of adjacency segment ID, there are two choices, the first choice is that it is allocated from the local label pool, the second choice is that it is allocated from the global label pool. The advantage for the second choice is that the depth of the label stack for the forwarding path encoding will be reduced since adjacency segment ID can signal the forwarding path without adding the node segment ID in front of it. In this version of the draft, we use the first choice for now. We may update the draft to reflect the use of the second choice.

Same as the SR solutions, when PCECC is used as the central controller, the support of FRR on any topology can be pre-computed and setup without any additional signaling (other than the regular IGP/BGP protocols) including the support of shared risk constraints, support of node and link protection and support of microloop avoidance.

The following example illustrates the use case where the node segment ID and adjacency segment ID are allocated from the global label allocated for SR path.




Figure 3: Using PCECC for SR Path

5.1. Use Cases of PCECC for SR Best Effort(BE) Path

In this mode of the solution, the PCECC just need to allocate the node segment ID and adjacency ID without calculating the explicit path for the SR path. The ingress of the forwarding path just need to encapsulate the destination node segment ID on top of the packet. All the intermediate nodes will forward the packet based on the final destination node segment id. It is similar to the LDP LSP forwarding except that label swapping is using the same global label both for the in segment and out segment in each hop.

The p2p SR BE path examples are explained as bellow:

Note that the node segment id for each node from the shared global labels ranges negotiated already.

Example 1:

R1 may send a packet to R8 simply by pushing an SR header with segment list {1008}. The path can be: R1-R2-R3-R8 or R1-R2-R5-R8

depending on the route calculation on node R2.

Example 2: local link/node protection:

For the packet which has destination of R3 and after that, R2 may preinstalled the backup forwarding entry to protect the R4 node, the pre-installed the backup path can go through either node5 or link1 or link2 between R2 and R3. The backup path calculation is locally decided by R2 and any existing IP FRR algorithms can be used here.

5.2. Use Cases of PCECC for SR Traffic Engineering (TE) Path

In the case of traffic engineering path is needed, the PCECC need to allocate the node segment ID and adjacency ID, and at the same time PCECC calculates the explicit path for the SR path and pass this explicit path represented with a sequence of node segment id and adjacency id. The ingress of the forwarding path need to encapsulate the stack of node segment id and adjacency id on top of the packet. For the case where strict traffic engineering path is needed, all the intermediate nodes and links will be specified through the stack of labels so that the packet is forwarded exactly as it is wanted.

Even though it is similar to TE LSP forwarding where forwarding path is engineered, but the Qos is only guaranteed through the enforce of the bandwidth admission control. As for the RSVP-TE LSP case, Qos is guaranteed through the link bandwidth reservation in each hop of the forwarding path.

The p2p SR traffic engineering path examples are explained as bellow:

Note that the node segment id for each node is allocated from the shared global labels ranges negotiated already and adjacency segment ids for each link are allocated from the local label pool for each node.

Example 1:

R1 may send a packet P1 to R8 simply by pushing an SR header with segment list {1008}. The path should be: R1-R2-R3-R8.

Example 2:

R1 may send a packet P2 to R8 by pushing an SR header with segment list {1002, 9001, 1008}. The path should be: R1-R2-(1)link-R3-R8.

Example 3:

R1 may send a packet P3 to R8 while avoiding the links between R2 and

R3 by pushing an SR header with segment list {1004, 1008}. The path should be : R1-R2-R4-R3-R8

The p2p local protection examples for SR TE path are explained as below:

Example 4: local link protection:

- o R1 may send a packet P4 to R8 by pushing an SR header with segment list {1002, 9001, 1008}. The path should be: R1-R2-(1)link-R3-R8.
- o When node R2 receives the packet from R1 which has the header of R2- (1)link-R3-R8, and also find out there is a link failure of link1, then it will send out the packet with header of R3-R8 through link2.

Example 5: local node protection:

- o R1 may send a packet P5 to R8 by pushing an SR header with segment list {1004, 1008}. The path should be : R1-R2-R4-R3-R8.
- o When node R2 receives the packet from R1 which has the header of {1004, 1008}, and also find out there is a node failure for node4, then it will send out the packet with header of {1005, 1008} to node5 instead of node4.

6. Use Cases of PCECC for TE LSP

In the previous sections, we have discussed the cases where the SR path is setup through the PCECC. Although those cases give the simplicity and scalability, but there are existing functionalities for the traffic engineering path such as the bandwidth guarantee through the full forwarding path and the multicast forwarding path which SR based solution cannot solve. Also there are cases where the depth of the label stack may have been an issue for existing deployment and certain vendors.

So to address these issues, PCECC architecture should also support the TE LSP and multicast LSP functionalities. To achieve this, the existing PCEP can be used to communicate between the PCE server and PCE's client PCC for exchanging the path request and reply information regarding to the TE LSP info. In this case, the TE LSP info is not only the path info itself, but it includes the full forwarding info. Instead of letting the ingress of LSP to initiate the LSP setup through the RSVP-TE signaling protocol, with minor extensions, we can use the PCEP to download the complete TE LSP forwarding entries for each node in the network.




Figure 4: Using PCECC for TE LSP

TE LSP Setup Example

- o Node1 sends a path request message for the setup of TE LSP from R1 to R8.
- o PCECC program each node along the path from R1 to R8 with the primary path: {R1, link1, 6001}, {R2, link3, 7002}, {R4, link0, 9001}, {R3, link1, 3001}, {R8}.
- o For the end to end protection, PCECC program each node along the path from R1 to R8 with the secondary path: {R1, link2, 6002}, {R2, link4, 7001}, {R5, link1, 9002}, {R3, link2, 3002}, {R8}.
- o It is also possible to have a secondary backup path for the local node protection setup by PCECC. For example GBP[not] the primary path is still same as what we have setup so far, then to protect

the node R4 locally, PCECC can program the secondary path like this: {R1, link1, 6001}, {R2, link1, 5001}, {R3, link1, 3001}, {R8}. By doing this, the node R4 is locally protected.

7. Use Cases of PCECC for Multicast LSPs

The current multicast LSPs are setup either using the RSVP-TE P2MP or mLDP protocols. The setup of these LSPs not only need a lot of manual configurations, but also it is also complex when the protection is considered. By using the PCECC solution, the multicast LSP can be computed and setup through centralized controller which has the full picture of the topology and bandwidth usage for each link. It not only reduces the complex configurations comparing the distributed RSVP-TE P2MP or mLDP signal lings, but also it can compute the disjoint primary path and secondary path efficiently.

7.1. Using PCECC for P2MP/MP2MP LSPs' Setup

With the capability of global label and local label existing at the same time in the PCECC network, PCECC will use compute, setup and maintain the P2MP and MP2MP lsp using the local label range for each network nodes.




Figure 5: Using PCECC for P2MP TE LSP

The P2MP examples are explained here:

Step1: R1 may send a packet P1 to R2 simply by pushing an label of 6000 to the packet.

Step2: After R2 receives the packet with label 6000, it will forwarding to R4 by pushing header of 9001 and R5 by pushing header of 9002.

Step3: After R4 receives the packet with label 9001, it will forwarding to R3 by pushing header of 9003. After R5 receives the packet with label 9002, it will forwarding to R5 by pushing header of 9004.

Step3: After R3 receives the packet with label 9003, it will forwarding to R8 by pushing header of 9005

7.2. Use Cases of PCECC for the Resiliency of P2MP/MP2MP LSPs

7.2.1. PCECC for the End-to-End Protection of the P2MP/MP2MP LSPs

In this section we describe the end-end managed path protection service and the local protection with the operation management in the PCECC network for the P2MP/MP2MP LSP, which includes both the RSVP-TE P2MP based LSP and also the mLDP based LSP.

An end-to-end protection (for nodes and links) principle can be applied for computing backup P2MP or MP2MP LSPs. During computation of the primarily multicast trees, PCECC server may also be taken into consideration to compute a secondary tree. A PCE may compute the primary and backup P2MP or MP2MP LSP together or sequentially.




Figure 6: Using PCECC for P2MP TE End-to-End Protection

In the example above, when the PCECC setup the primary multicast tree from the root node R1 to the leafs, which is R1->R2->{R4, R5}, at same time, it can setup the backup tree, which is R11->R3->{R4, R5}. Both the these two primary forwarding tree and secondary forwarding tree will be downloaded to each routers along the primary path and the secondary path. The traffic will be forwarded through the R1->R2->{R4, R5} path normally, and when there is a node in the primary tree, then the root node R1 will switch the flow to the backup tree, which is R11->R3->{R4, R5}. By using the PCECC, the path computation and forwarding path downloading can all be done without the complex signaling used in the P2MP RSVP-TE or mLDP.

7.2.2. PCECC for the Local Protection of the P2MP/MP2MP LSPs

In this section we describe the local protection service in the PCECC network for the P2MP/MP2MP LSP.

While the PCECC sets up the primary multicast tree, it can also build the back LSP among PLR, the protected node, and MPs (the downstream nodes of the protected node). In the cases where the amount of downstream nodes are huge, this mechanism can avoid unnecessary packet duplication on PLR, so that protect the network from traffic congestion risk.




Figure 7: Using PCECC for P2MP TE Local Protection

In the example above, when the PCECC setup the primary multicast path around the PLR node R10 to protect node R20, which is R10->R20->{R40, R50}, at same time, it can setup the backup path R10->R30->{R40, R50}. Both the these two primary forwarding path and secondary forwarding path will be downloaded to each routers along the primary path and the secondary path. The traffic will be forwarded through the R10->R20->{R40, R50} path normally, and when there is a node failure for node R20, then the PLR node R10 will switch the flow to the backup path, which is R10->R30->{R40, R50}. By using the PCECC, the path computation and forwarding path downloading can all be done without the complex signaling used in the P2MP RSVP-TE or mLDP.

8. Use Cases of PCECC for LSP in the Network Migration

One of the main advantages for PCECC solution is that it has backward compatibility naturally since the PCE server itself can function as a proxy node of MPLS network for all the new nodes which don't support the existing MPLS signaling protocol anymore.

As it is illustrated in the following example, the current network will migrate to a total PCECC controlled network gradually by replacing the legacy nodes. During the migration, the legacy nodes still need to signal using the existing MPLS protocol such as LDP and RSVP-TE, and the new nodes setup their portion of the forwarding path through PCECC directly. With the PCECC function as the proxy of these new nodes, MPLS signaling can populate through network as normal.

Example described in this section is based on network configurations illustrated using the following figure:




Figure 8: Using PCECC During Migration

Example: PCECC Initiated LSP Setup In the Network Migration

In this example, there are five nodes for the TE LSP from head end (node1) to the tail end (node5). Where the NodeX is central controlled and other nodes are legacy nodes.

- o Node1 sends a path request message for the setup of LSP destinating to Node5.
- o PCECC sends a reply message for LSP setup with path (node1, if1), (node2, if22), (node-PCECC, if44), (node4, if4), Nnode5.
- o Node1, Node2, Node-PCECC, Node 5 will setup the LSP to Node5 normally using the local label as normal.

- o Then the PCECC will program the outsegment of Node2, the insegment of Node4, and the insegment/outsegment for NodeX.

9. Use Cases of PCECC for L3VPN and PWE3

The existing services using MPLS LSP tunnels based on MPLS signalling mechanism such L3VPN, PWE3 and IPv6 can be simplified by using the PCECC to negotiate the label assignments for the L3VPN, PWE3 and Ipv6.

In the case of L3VPN, VPN labels can be negotiated and distributed through the PCECC PCEP among the PE router instead of using the BGP protocols.




Figure 9: Using PCECC for L3VPN and PWE3

In the case of PWE3, instead of using the LDP signalling protocols, the label and port pairs assigned to each pseudowire can be negotiated through PCECC among the PE routers and the corresponding forwarding entries will be distributed into each PE routers through the extended PCEP protocols.

10. The Considerations for PCECC Procedure and PCEP extensions

The PCECC's procedures and PCEP extensions is defined in [I-D.zhao-pce-pcep-extension-for-pce-controller].

11. IANA Considerations

This document does not require any action from IANA.

12. Security Considerations

TBD.

13. Acknowledgments

We would like to thank Robert Tao, Changjiang Yan, Tieying Huang for their useful comments and suggestions.

14. References

14.1. Normative References

- | | |
|-----------|---|
| [RFC2119] | Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, March 1997. |
| [RFC5440] | Vasseur, JP. and JL. Le Roux, "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, March 2009. |

14.2. Informative References

- | | |
|-----------|---|
| [RFC5441] | Vasseur, JP., Zhang, R., Bitar, N., and JL. Le Roux, "A Backward-Recursive PCE-Based Computation (BRPC) Procedure to Compute Shortest Constrained Inter-Domain Traffic Engineering Label Switched Paths", RFC 5441, |
|-----------|---|

April 2009.

[RFC5541]

Le Roux, J.L.,
Vasseur, J.P., and
Y. Lee, "Encoding
of Objective
Functions in the
Path Computation
Element
Communication
Protocol (PCEP)",
RFC 5541,
June 2009.

[I-D.filsfils-spring-segment-routing]

Filsfils, C.,
Previdi, S.,
Bashandy, A.,
Decraene, B.,
Litkowski, S.,
Horneffer, M.,
Milojevic, I.,
Shakir, R., Ytti,
S., Henderickx, W.,
Tantsura, J., and
E. Crabbe, "Segment
Routing
Architecture", draf
t-filsfils-spring-
segment-routing-04
(work in progress),
July 2014.

[I-D.ietf-pce-stateful-pce]

Crabbe, E., Minei,
I., Medved, J., and
R. Varga, "PCEP
Extensions for
Stateful PCE", draf
t-ietf-pce-
stateful-pce-11
(work in progress),
April 2015.

[I-D.crabbe-pce-pce-initiated-lsp]

Crabbe, E., Minei,
I., Sivabalan, S.,
and R. Varga, "PCEP
Extensions for PCE-
initiated LSP Setup
in a Stateful PCE

Model", draft-crabbe-pce-pce-initiated-lsp-03 (work in progress), October 2013.

[I-D.ali-pce-remote-initiated-gmpls-lsp]

Ali, Z., Sivabalan, S., Filsfils, C., Varga, R., Lopez, V., Dios, O., and X. Zhang, "Path Computation Element Communication Protocol (PCEP) Extensions for remote-initiated GMPLS LSP Setup", draft-ali-pce-remote-initiated-gmpls-lsp-03 (work in progress), February 2014.

[I-D.ietf-isis-segment-routing-extensions]

Previdi, S., Filsfils, C., Bashandy, A., Gredler, H., Litkowski, S., Decraene, B., and J. Tantsura, "IS-IS Extensions for Segment Routing", draft-ietf-isis-segment-routing-extensions-05 (work in progress), June 2015.

[I-D.psenak-ospf-segment-routing-extensions]

Psenak, P., Previdi, S., Filsfils, C., Gredler, H., Shakir, R., Henderickx, W., and J. Tantsura, "OSPF Extensions for Segment Routing", draft-psenak-ospf-

- segment-routing-extensions-05 (work in progress), June 2014.
- [I-D.sivabalan-pce-segment-routing] Sivabalan, S., Medved, J., Filsfils, C., Crabbe, E., Raszuk, R., Lopez, V., and J. Tantsura, "PCEP Extensions for Segment Routing", draft-sivabalan-pce-segment-routing-03 (work in progress), July 2014.
- [I-D.li-mpls-global-label-usecases] Li, Z., Zhao, Q., Yang, T., and R. Raszuk, "Use Cases of MPLS Global Label", draft-li-mpls-global-label-usecases-02 (work in progress), July 2014.
- [I-D.li-mpls-global-label-framework] Li, Z., Zhao, Q., Chen, X., Yang, T., and R. Raszuk, "A Framework of MPLS Global Label", draft-li-mpls-global-label-framework-02 (work in progress), July 2014.
- [I-D.zhao-pce-pcep-extension-for-pce-controller] Zhao, Q., Zhao, K., Li, Z., Dhody, D., Palle, U., and T. Communications, "PCEP Procedures and Protocol Extensions for Using PCE as a Central Controller (PCECC) of LSPs", d

raft-zhao-pce-pcep-
extension-for-pce-
controller-01 (work
in progress),
March 2015.

[I-D.ietf-spring-resiliency-use-cases]

Francois, P.,
Filsfils, C.,
Decraene, B., and
R. Shakir, "Use-
cases for
Resiliency in
SPRING", draft-
ietf-spring-
resiliency-use-
cases-01 (work in
progress),
March 2015.

Authors' Addresses

Quintin Zhao
Huawei Technologies
125 Nagog Technology Park
Acton, MA 01719
US

EMail: quintin.zhao@huawei.com

Robin Li
Huawei Technologies
Huawei Bld., No.156 Beiqing Rd.
Beijing 100095
China

EMail: lizhenbin@huawei.com

King Ke
Tencent Holdings Ltd.
Shenzhen
China

EMail: kinghe@tencent.com

Luyuan Fang
Microsoft

EMail: lufang@microsoft.com

Chao Zhou
Cisco Systems

EMail: chao.zhou@cisco.com

Boris Zhang
Telus Communications
200 Consilium Pl Floor 15
Toronto, ON M1H 3J3
Canada

EMail: Boris.Zhang@telus.com

Katherine Zhao
Huawei Technologies
2330 Central Expressway
Santa Clara, CA 95050
USA

EMail: Katherine.zhao@huawei.com

Richard Li
Huawei Technologies
2330 Central Expressway
Santa Clara, CA 95050
USA

EMail: renwei.li@huawei.com

