

Internet
Internet-Draft
Intended status: Informational
Expires: February 14, 2020

A. Lindem
S. Palani
Cisco Systems
Y. Qu
Futurewei
August 13, 2019

YANG Model for OSPFv3 Extended LSAs
draft-acee-lsr-ospfv3-extended-lsa-yang-06

Abstract

This document defines a YANG data model augmenting the IETF OSPF YANG model to provide support for OSPFv3 Link State Advertisement (LSA) Extensibility as defined in [RFC 8362](#). OSPFv3 Extended LSAs provide extensible TLV-based LSAs for the base LSA types defined in [RFC 5340](#).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 14, 2020.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Overview	2
1.1.	Requirements Language	2
2.	OSPFv3 Extended LSAs	2
3.	OSPFv3 Extended LSA Yang Module	11
4.	Security Considerations	26
5.	IANA Considerations	27
6.	Acknowledgements	28
7.	References	28
7.1.	Normative References	28
7.2.	Informative References	29
	Authors' Addresses	29

[1.](#) Overview

YANG [[RFC6020](#)] [[RFC7950](#)] is a data definition language used to define the contents of a conceptual data store that allows networked devices to be managed using NETCONF [[RFC6241](#)]. YANG is proving relevant beyond its initial confines, as bindings to other interfaces (e.g., ReST) and encodings other than XML (e.g., JSON) are being defined. Furthermore, YANG data models can be used as the basis for implementation of other interfaces, such as CLI and programmatic APIs.

This document defines a YANG data model augmenting the IETF OSPF YANG model [[I-D.ietf-ospf-yang](#)], which itself augments [[RFC8349](#)], to provide support for configuration and operational state for OSPFv3 Extended LSAs as defined in [[RFC8362](#)].

[1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[2.](#) OSPFv3 Extended LSAs

This document defines a model for the OSPFv3 Extended LSA feature. It is an augmentation of the OSPF base model provided support for

OSPFv3 Link State Advertisement (LSA) Extensibility [[RFC8362](#)].
OSPFv3 Extended LSAs provide extensible TLV-based LSAs for the base LSA types defined in [[RFC5340](#)].

The OSPFv3 Extended LSA YANG module requires support for the OSPF base model[I-D.ietf-ospf-yang] which defines basic OSPF configuration and state. The OSPF YANG model augments the ietf-routing YANG model defined in [[RFC8022](#)]. The augmentations defined in the ietf-ospfv3-extended-lsa YANG model will provide global configuration, area configuration, and addition of OSPFv3 Extended LSAs to the Link State Database (LSDB) operational state.

```
module: ietf-ospfv3-extended-lsa
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf:
      +--rw extended-lsa-support?  boolean {extended-lsa-support}?
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area:
      +--rw extended-lsa-support?  boolean {extended-lsa-support}?
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:interfaces/ospf:interface/ospf:database
    /ospf:link-scope-lsa-type/ospf:link-scope-lsas
    /ospf:link-scope-lsa/ospf:version/ospf:ospfv3
    /ospf:ospfv3/ospf:body:
  augment /rt:routing/rt:control-plane-protocols
    /rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area
    /ospf:database/ospf:area-scope-lsa-type
    /ospf:area-scope-lsas/ospf:area-scope-lsa/ospf:version
    /ospf:ospfv3/ospf:ospfv3/ospf:body:
    +--ro e-router
    |   +--ro router-bits
    |   |   +--ro rtr-lsa-bits*  identityref
    |   +--ro lsa-options
    |   |   +--ro lsa-options*  identityref
    |   +--ro e-router-tlvs*
    |   |   +--ro unknown-tlv
    |   |   |   +--ro type?      uint16
    |   |   |   +--ro length?   uint16
    |   |   |   +--ro value?    yang:hex-string
```

```

|      +--ro link-tlv
|      |      +--ro link-tlv-length?          uint16
|      |      +--ro interface-id?             uint32
|      |      +--ro neighbor-interface-id?    uint32
|      |      +--ro neighbor-router-id?       rt-types:router-id
|      |      +--ro type?                     uint8
|      |      +--ro metric?                   uint16
|      |      +--ro sub-tlvs*
|      |      |      +--ro unknown-sub-tlv
|      |      |      |      +--ro type?      uint16
|      |      |      |      +--ro length?    uint16
|      |      |      |      +--ro value?     yang:hex-string

```

```

+--ro e-network
|  +--ro lsa-options
|  |  +--ro lsa-options*  identityref
|  +--ro e-network-tlvs*
|  |  +--ro unknown--tlv
|  |  |  +--ro type?      uint16
|  |  |  +--ro length?    uint16
|  |  |  +--ro value?     yang:hex-string
|  +--ro attached-router-tlv
|  |  +--ro attached-router-tlv-length?    uint16
|  |  +--ro Adjacent-neighbor-router-id?   rt-types:router-id
|  |  +--ro sub-tlvs*
|  |  |  +--ro unknown-sub-tlv
|  |  |  |  +--ro type?      uint16
|  |  |  |  +--ro length?    uint16
|  |  |  |  +--ro value?     yang:hex-string
+--ro e-inter-area-prefix
|  +--ro e-inter-prefix-tlvs*
|  |  +--ro unknown--tlv
|  |  |  +--ro type?      uint16
|  |  |  +--ro length?    uint16
|  |  |  +--ro value?     yang:hex-string
|  +--ro inter-prefix-tlv
|  |  +--ro inter-prefix-tlv-length?    uint16
|  |  +--ro metric?                     rt-types:uint24
|  |  +--ro prefix?                     inet:ip-prefix
|  |  +--ro prefix-options
|  |  |  +--ro prefix-options*  identityref
|  +--ro prefix-length?                uint8

```

```

|         +---ro sub-tlvs*
|           +---ro unknown-sub-tlv
|             +---ro type?      uint16
|             +---ro length?    uint16
|             +---ro value?     yang:hex-string
+---ro e-inter-area-router
|   +---ro e-inter-router-tlvs*
|     +---ro unknown-tlv
|       | +---ro type?      uint16
|       | +---ro length?    uint16
|       | +---ro value?     yang:hex-string
|     +---ro inter-router-tlv
|       +---ro inter-router-tlv-length?  uint16
|       +---ro router-bits
|         | +---ro rtr-lsa-bits*  identityref
|       +---ro lsa-options
|         | +---ro lsa-options*  identityref
|       +---ro metric?          rt-types:uint24
|       +---ro destination-router-id?  rt-types:router-id

```

```

|         +---ro sub-tlvs*
|           +---ro unknown-sub-tlv
|             +---ro type?      uint16
|             +---ro length?    uint16
|             +---ro value?     yang:hex-string
+---ro e-as-external
|   +---ro e-external-tlvs*
|     +---ro unknown-tlv
|       | +---ro type?      uint16
|       | +---ro length?    uint16
|       | +---ro value?     yang:hex-string
|     +---ro external-prefix-tlv
|       +---ro external-prefix-tlv-length?  uint16
|       +---ro flags
|         | +---ro ospfv3-e-external-prefix-bits*  identityref
|       +---ro metric?          rt-types:uint24
|       +---ro prefix?          inet:ip-prefix
|       +---ro prefix-options
|         | +---ro prefix-options*  identityref
|       +---ro prefix-length?      uint8
|       +---ro sub-tlvs*
|         +---ro unknown-sub-tlv

```

```

|         |   +--ro type?      uint16
|         |   +--ro length?   uint16
|         |   +--ro value?    yang:hex-string
|         +--ro ipv6-fwd-addr-sub-tlv
|         |   +--ro ipv6-fwd-addr-sub-tlv-length?  uint16
|         |   +--ro forwarding-address?            inet:ipv6-address
|         +--ro ipv4-fwd-addr-sub-tlv
|         |   +--ro ipv4-fwd-addr-sub-tlv-length?  uint16
|         |   +--ro forwarding-address?            inet:ipv4-address
|         +--ro route-tag-sub-tlv
|         |   +--ro route-tag-sub-tlv-length?      uint16
|         |   +--ro route-tag?                      uint32
+--ro e-nssa
|   +--ro e-external-tlvs*
|     +--ro unknown-tlv
|       |   +--ro type?      uint16
|       |   +--ro length?   uint16
|       |   +--ro value?    yang:hex-string
|       +--ro external-prefix-tlv
|         +--ro external-prefix-tlv-length?  uint16
|         +--ro flags
|         |   +--ro ospfv3-e-external-prefix-bits*  identityref
|         +--ro metric?                             rt-types:uint24
|         +--ro prefix?                             inet:ip-prefix
|         +--ro prefix-options
|         |   +--ro prefix-options*  identityref

```

```

|         +--ro prefix-length?                      uint8
|         +--ro sub-tlvs*
|           +--ro unknown-sub-tlv
|             |   +--ro type?      uint16
|             |   +--ro length?   uint16
|             |   +--ro value?    yang:hex-string
|             +--ro ipv6-fwd-addr-sub-tlv
|               |   +--ro ipv6-fwd-addr-sub-tlv-length?  uint16
|               |   +--ro forwarding-address?            inet:ipv6-address
|             +--ro ipv4-fwd-addr-sub-tlv
|               |   +--ro ipv4-fwd-addr-sub-tlv-length?  uint16
|               |   +--ro forwarding-address?            inet:ipv4-address
|             +--ro route-tag-sub-tlv
|               +--ro route-tag-sub-tlv-length?      uint16
|               +--ro route-tag?                      uint32

```

```

+--ro e-link
|   +--ro rtr-priority?   uint8
|   +--ro lsa-options
|   |   +--ro lsa-options*   identityref
|   +--ro e-link-tlvs*
|   |   +--ro unknown-tlv
|   |   |   +--ro type?       uint16
|   |   |   +--ro length?     uint16
|   |   |   +--ro value?      yang:hex-string
|   |   +--ro intra-prefix-tlv
|   |   |   +--ro intra-prefix-tlv-length?   uint16
|   |   |   +--ro metric?                rt-types:uint24
|   |   |   +--ro prefix?                 inet:ip-prefix
|   |   |   +--ro prefix-options
|   |   |   |   +--ro prefix-options*   identityref
|   |   |   +--ro prefix-length?        uint8
|   |   |   +--ro sub-tlvs*
|   |   |   |   +--ro unknown-sub-tlv
|   |   |   |   |   +--ro type?       uint16
|   |   |   |   |   +--ro length?     uint16
|   |   |   |   |   +--ro value?      yang:hex-string
|   |   +--ro ipv6-link-local-tlv
|   |   |   +--ro ipv6-link-local-tlv-length?   uint16
|   |   |   +--ro link-local-address?           inet:ipv6-address
|   |   |   +--ro sub-tlvs*
|   |   |   |   +--ro unknown-sub-tlv
|   |   |   |   |   +--ro type?       uint16
|   |   |   |   |   +--ro length?     uint16
|   |   |   |   |   +--ro value?      yang:hex-string
|   |   +--ro ipv4-link-local-tlv
|   |   |   +--ro ipv4-link-local-tlv-length?   uint16
|   |   |   +--ro link-local-address?           inet:ipv4-address
|   |   +--ro sub-tlvs*

```

```

|   |   |   +--ro unknown-sub-tlv
|   |   |   |   +--ro type?       uint16
|   |   |   |   +--ro length?     uint16
|   |   |   |   +--ro value?      yang:hex-string
+--ro e-intra-area-prefix
|   +--ro referenced-ls-type?       uint16
|   +--ro referenced-link-state-id? uint32
|   +--ro referenced-adv-router?    rt-types:router-id

```

```

+--ro e-intra-prefix-tlvs*
  +--ro unknown-tlv
  |   +--ro type?      uint16
  |   +--ro length?    uint16
  |   +--ro value?     yang:hex-string
  +--ro intra-prefix-tlv
    +--ro intra-prefix-tlv-length?  uint16
    +--ro metric?                    rt-types:uint24
    +--ro prefix?                    inet:ip-prefix
    +--ro prefix-options
    |   +--ro prefix-options*  identityref
    +--ro prefix-length?      uint8
    +--ro sub-tlvs*
      +--ro unknown-sub-tlv
      |   +--ro type?      uint16
      |   +--ro length?    uint16
      |   +--ro value?     yang:hex-string
augment /rt:routing/rt:control-plane-protocols
  /rt:control-plane-protocol/ospf:ospf/ospf:database
  /ospf:as-scope-lsa-type/ospf:as-scope-lsas
  /ospf:as-scope-lsa/ospf:version/ospf:ospfv3
  /ospf:ospfv3/ospf:body:
+--ro e-router
|   +--ro router-bits
|   |   +--ro rtr-lsa-bits*  identityref
|   +--ro lsa-options
|   |   +--ro lsa-options*  identityref
|   +--ro e-router-tlvs*
|   |   +--ro unknown-tlv
|   |   |   +--ro type?      uint16
|   |   |   +--ro length?    uint16
|   |   |   +--ro value?     yang:hex-string
|   |   +--ro link-tlv
|   |   |   +--ro link-tlv-length?  uint16
|   |   |   +--ro interface-id?      uint32
|   |   |   +--ro neighbor-interface-id?  uint32
|   |   |   +--ro neighbor-router-id?  rt-types:router-id
|   |   |   +--ro type?                uint8
|   |   |   +--ro metric?              uint16
|   |   +--ro sub-tlvs*

```



```

|         +---ro type?      uint16
|         +---ro length?    uint16
|         +---ro value?     yang:hex-string
+---ro e-network
|   +---ro lsa-options
|   |   +---ro lsa-options*  identityref
|   +---ro e-network-tlvs*
|   |   +---ro unknown--tlv
|   |   |   +---ro type?      uint16
|   |   |   +---ro length?    uint16
|   |   |   +---ro value?     yang:hex-string
|   |   +---ro attached-router-tlv
|   |   |   +---ro attached-router-tlv-length?    uint16
|   |   |   +---ro Adjacent-neighbor-router-id?  rt-types:router-id
|   |   +---ro sub-tlvs*
|   |   |   +---ro unknown-sub-tlv
|   |   |   |   +---ro type?      uint16
|   |   |   |   +---ro length?    uint16
|   |   |   |   +---ro value?     yang:hex-string
+---ro e-inter-area-prefix
|   +---ro e-inter-prefix-tlvs*
|   |   +---ro unknown--tlv
|   |   |   +---ro type?      uint16
|   |   |   +---ro length?    uint16
|   |   |   +---ro value?     yang:hex-string
|   |   +---ro inter-prefix-tlv
|   |   |   +---ro inter-prefix-tlv-length?    uint16
|   |   |   +---ro metric?                      rt-types:uint24
|   |   |   +---ro prefix?                      inet:ip-prefix
|   |   |   +---ro prefix-options
|   |   |   |   +---ro prefix-options*  identityref
|   |   |   +---ro prefix-length?        uint8
|   |   +---ro sub-tlvs*
|   |   |   +---ro unknown-sub-tlv
|   |   |   |   +---ro type?      uint16
|   |   |   |   +---ro length?    uint16
|   |   |   |   +---ro value?     yang:hex-string
+---ro e-inter-area-router
|   +---ro e-inter-router-tlvs*
|   |   +---ro unknown-tlv
|   |   |   +---ro type?      uint16
|   |   |   +---ro length?    uint16
|   |   |   +---ro value?     yang:hex-string
|   |   +---ro inter-router-tlv
|   |   |   +---ro inter-router-tlv-length?    uint16
|   |   |   +---ro router-bits
|   |   |   |   +---ro rtr-lsa-bits*  identityref

```

```
|         +---ro lsa-options
|         | +---ro lsa-options*   identityref
|         +---ro metric?          rt-types:uint24
|         +---ro destination-router-id?  rt-types:router-id
|         +---ro sub-tlvs*
|             +---ro unknown-sub-tlv
|                 +---ro type?      uint16
|                 +---ro length?    uint16
|                 +---ro value?     yang:hex-string
+---ro e-as-external
|   +---ro e-external-tlvs*
|       +---ro unknown-tlv
|           | +---ro type?      uint16
|           | +---ro length?    uint16
|           | +---ro value?     yang:hex-string
|       +---ro external-prefix-tlv
|           +---ro external-prefix-tlv-length?  uint16
|           +---ro flags
|               | +---ro ospfv3-e-external-prefix-bits*  identityref
|           +---ro metric?          rt-types:uint24
|           +---ro prefix?          inet:ip-prefix
|           +---ro prefix-options
|               | +---ro prefix-options*  identityref
|           +---ro prefix-length?      uint8
|           +---ro sub-tlvs*
|               +---ro unknown-sub-tlv
|                   | +---ro type?      uint16
|                   | +---ro length?    uint16
|                   | +---ro value?     yang:hex-string
|               +---ro ipv6-fwd-addr-sub-tlv
|                   | +---ro ipv6-fwd-addr-sub-tlv-length?  uint16
|                   | +---ro forwarding-address?            inet:ipv6-address
|               +---ro ipv4-fwd-addr-sub-tlv
|                   | +---ro ipv4-fwd-addr-sub-tlv-length?  uint16
|                   | +---ro forwarding-address?            inet:ipv4-address
|               +---ro route-tag-sub-tlv
|                   +---ro route-tag-sub-tlv-length?  uint16
|                   +---ro route-tag?                uint32
+---ro e-nssa
|   +---ro e-external-tlvs*
|       +---ro unknown-tlv
|           | +---ro type?      uint16
|           | +---ro length?    uint16
|           | +---ro value?     yang:hex-string
|       +---ro external-prefix-tlv
|           +---ro external-prefix-tlv-length?  uint16
```

```

|         +---ro flags
|         | +---ro ospfv3-e-external-prefix-bits*  identityref

```

```

|         +---ro metric?                               rt-types:uint24
|         +---ro prefix?                               inet:ip-prefix
|         +---ro prefix-options
|         | +---ro prefix-options*  identityref
|         +---ro prefix-length?                        uint8
|         +---ro sub-tlvs*
|         | +---ro unknown-sub-tlv
|         | | +---ro type?      uint16
|         | | +---ro length?    uint16
|         | | +---ro value?     yang:hex-string
|         +---ro ipv6-fwd-addr-sub-tlv
|         | +---ro ipv6-fwd-addr-sub-tlv-length?      uint16
|         | +---ro forwarding-address?                inet:ipv6-address
|         +---ro ipv4-fwd-addr-sub-tlv
|         | +---ro ipv4-fwd-addr-sub-tlv-length?      uint16
|         | +---ro forwarding-address?                inet:ipv4-address
|         +---ro route-tag-sub-tlv
|         | +---ro route-tag-sub-tlv-length?          uint16
|         | +---ro route-tag?                          uint32
+---ro e-link
| +---ro rtr-priority?  uint8
| +---ro lsa-options
| | +---ro lsa-options*  identityref
+---ro e-link-tlvs*
| +---ro unknown-tlv
| | +---ro type?      uint16
| | +---ro length?    uint16
| | +---ro value?     yang:hex-string
+---ro intra-prefix-tlv
| +---ro intra-prefix-tlv-length?  uint16
| +---ro metric?                  rt-types:uint24
| +---ro prefix?                  inet:ip-prefix
| +---ro prefix-options
| | +---ro prefix-options*  identityref
| +---ro prefix-length?          uint8
| +---ro sub-tlvs*
| | +---ro unknown-sub-tlv
| | | +---ro type?      uint16
| | | +---ro length?    uint16

```

```

|         +---ro value?      yang:hex-string
| +---ro ipv6-link-local-tlv
|         +---ro ipv6-link-local-tlv-length?  uint16
|         +---ro link-local-address?          inet:ipv6-address
|         +---ro sub-tlvs*
|             +---ro unknown-sub-tlv
|                 +---ro type?      uint16
|                 +---ro length?    uint16
|                 +---ro value?     yang:hex-string

```

```

|         +---ro ipv4-link-local-tlv
|         +---ro ipv4-link-local-tlv-length?  uint16
|         +---ro link-local-address?          inet:ipv4-address
|         +---ro sub-tlvs*
|             +---ro unknown-sub-tlv
|                 +---ro type?      uint16
|                 +---ro length?    uint16
|                 +---ro value?     yang:hex-string
+---ro e-intra-area-prefix
+---ro referenced-ls-type?      uint16
+---ro referenced-link-state-id? uint32
+---ro referenced-adv-router?   rt-types:router-id
+---ro e-intra-prefix-tlvs*
+---ro unknown-tlv
| +---ro type?      uint16
| +---ro length?    uint16
| +---ro value?     yang:hex-string
+---ro intra-prefix-tlv
+---ro intra-prefix-tlv-length? uint16
+---ro metric?                rt-types:uint24
+---ro prefix?                inet:ip-prefix
+---ro prefix-options
| +---ro prefix-options*  identityref
+---ro prefix-length?        uint8
+---ro sub-tlvs*
+---ro unknown-sub-tlv
+---ro type?      uint16
+---ro length?    uint16
+---ro value?     yang:hex-string

```

[3.](#) OSPFv3 Extended LSA Yang Module

```

<CODE BEGINS> file "ietf-ospfv3-extended-lsa@2019-08-13.yang"
module ietf-ospfv3-extended-lsa {
  yang-version 1.1;
  namespace
    "urn:ietf:params:xml:ns:yang:ietf-ospfv3-extended-lsa";

  prefix ospfv3-e-lsa;

  import ietf-routing-types {
    prefix "rt-types";
  }

  import ietf-inet-types {
    prefix "inet";
    reference "RFC 6021 - Common YANG Data Types";
  }

```

Lindem, et al.

Expires February 14, 2020

[Page 11]

Internet-Draft

OSPFv3 Extended LSAs YANG

August 2019

```

import ietf-routing {
  prefix "rt";
  reference "RFC 8349 - A YANG Data Model for Routing
    Management (NMDA Version)";
}

import ietf-ospf {
  prefix "ospf";
  reference "RFC XXXX - A YANG Data Model for OSPF
    Protocol";
}

organization
  "IETF LSR - Link State Routing Working Group";

contact
  "WG Web:  <http://tools.ietf.org/wg/lsr/>
   WG List: <mailto:lsr@ietf.org>

   Author:  Acee Lindem
            <mailto:acee@cisco.com>
   Author:  Sharmila Palani
            <mailto:shpalani@cisco.com>
   Author:  Yingzhen Qu
            <mailto:yingzhen.qu@futurewei.com>";

```

description

"This YANG module defines the configuration and operational state for OSPFv3 Extended LSAs, which is common across all of the vendor implementations.

Copyright (c) 2019 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of RFC XXXX; see the RFC itself for full legal notices.";

reference "RFC XXXX";
revision 2019-08-13 {
 description
 "Initial revision.";

Lindem, et al.

Expires February 14, 2020

[Page 12]

Internet-Draft

OSPFv3 Extended LSAs YANG

August 2019

```
  reference
    "RFC XXXX: A YANG Data Model for OSPFv3 Extended LSAs.";
}

feature extended-lsa-support {
  description
    "Support for OSPFv3 Extended LSAs";
  reference
    "RFC 8362 - OSPFv3 Link State Advertisement (LSA)
      Extensibility";
}

/*
 * OSPFv3 Extend LSA Type Identities
 */
identity ospfv3-e-router-lsa {
  base ospf:ospfv3-lsa-type;
  description
```

```

        "OSPFv3 Extended Router LSA - Type 0xA021";
    }

    identity ospfv3-e-network-lsa {
        base ospf:ospfv3-lsa-type;
        description
            "OSPFv3 Extended Network LSA - Type 0xA022";
    }

    identity ospfv3-e-summary-lsa-type {
        base ospf:ospfv3-lsa-type;
        description
            "OSPFv3 Extended Summary LSA types";
    }

    identity ospfv3-e-inter-area-prefix-lsa {
        base ospfv3-e-summary-lsa-type;
        description
            "OSPFv3 Extended Inter-area Prefix LSA - Type 0xA023";
    }

    identity ospfv3-e-inter-area-router-lsa {
        base ospfv3-e-summary-lsa-type;
        description
            "OSPFv3 Extended Inter-area Router LSA - Type 0xA024";
    }

    identity ospfv3-e-external-lsa-type {
        base ospf:ospfv3-lsa-type;
        description

```

```

        "OSPFv3 Extended External LSA types";
    }

    identity ospfv3-e-as-external-lsa {
        base ospfv3-e-external-lsa-type;
        description
            "OSPFv3 Extended AS-External LSA - Type 0xC025";
    }

    identity ospfv3-e-nssa-lsa {
        base ospfv3-e-external-lsa-type;

```

```

    description
      "OSPFv3 Extended Not-So-Stubby-Area (NSSA) LSA -
        Type 0xA027";
  }

  identity ospfv3-e-link-lsa {
    base ospf:ospfv3-lsa-type;
    description
      "OSPFv3 Extended Link LSA - Type 0x8028";
  }

  identity ospfv3-e-intra-area-prefix-lsa {
    base ospf:ospfv3-lsa-type;
    description
      "OSPFv3 Extended Intra-area Prefix LSA - Type 0xA029";
  }

  identity ospfv3-e-prefix-option {
    description
      "Base identity for OSPFv3 Prefix Options.";
  }

  identity nu-bit {
    base ospfv3-e-prefix-option;
    description
      "When set, the prefix should be excluded
        from IPv6 unicast calculations.";
  }

  identity la-bit {
    base ospfv3-e-prefix-option;
    description
      "When set, the prefix is actually an IPv6 interface
        address of the Advertising Router.";
  }

  identity p-bit {

```

```

    base ospfv3-e-prefix-option;
    description
      "When set, the NSSA area prefix should be
        translated to an AS External LSA and advertised

```



```

        by the translating NSSA Border Router.";
    }

    identity dn-bit {
        base ospfv3-e-prefix-option;
        description
            "When set, the inter-area-prefix LSA or
            AS-external LSA prefix has been advertised as an
            L3VPN prefix.";
    }

    identity ospfv3-e-external-prefix-option {
        description
            "Base identity for OSPFv3 External Prefix Options.";
    }

    identity e-bit {
        base ospfv3-e-external-prefix-option;
        description
            "When set, the metric specified is a Type 2
            external metric.";
    }

    grouping unknown-sub-tlv {
        description
            "Unknown TLV grouping";
        container unknown-sub-tlv {
            uses ospf:tlv;
            description "Unknown External TLV Sub-TLV";
        }
    }

    grouping ospfv3-lsa-prefix {
        description
            "OSPFv3 LSA prefix";

        leaf prefix {
            type inet:ip-prefix;
            description
                "LSA Prefix";
        }
        container prefix-options {
            leaf-list prefix-options {
                type identityref {

```

```
        base ospfv3-e-prefix-option;
    }
    description
        "OSPFv3 prefix option flag list. This list will
        contain the identities for the OSPFv3 options
        that are set for the OSPFv3 prefix.";
    }
    description "Prefix options.";
}

leaf prefix-length {
    type uint8 {
        range "0..128";
    }
    description "Prefix length.";
}

grouping ipv6-fwd-addr-sub-tlv {
    container ipv6-fwd-addr-sub-tlv {
        description
            "IPv6 Forwarding Address Sub-TLV";
        leaf ipv6-fwd-addr-sub-tlv-length {
            type uint16;
            description
                "IPv6 Forwarding Addrss Sub-TLV Length - 16
                for IPv6 address";
        }
        leaf forwarding-address {
            type inet:ipv6-address;
            description
                "Forwarding address";
        }
    }
    description
        "IPv6 Forwarding Address Sub-TLV grouping";
}

grouping ipv4-fwd-addr-sub-tlv {
    container ipv4-fwd-addr-sub-tlv {
        description
            "IPv4 Forwarding Address Sub-TLV";
        leaf ipv4-fwd-addr-sub-tlv-length {
            type uint16;
            description
                "IPv4 Forwarding Addrss Sub-TLV Length - 4
                for IPv4 address";
        }
    }
}
```

```
}
```

```
    leaf forwarding-address {
      type inet:ipv4-address;
      description
        "Forwarding address";
    }
  }
  description
    "IPv4 Forwarding Address Sub-TLV grouping";
}

grouping route-tag-sub-tlv {
  container route-tag-sub-tlv {
    description
      "Route Tag Sub-TLV";
    leaf route-tag-sub-tlv-length {
      type uint16;
      description
        "Route Tag Sub-TLV Length - 4 for 32-bit tag";
    }
    leaf route-tag {
      type uint32;
      description
        "Route Tag";
    }
  }
}
description
  "Route Tag Sub-TLV grouping";
}

grouping external-prefix-tlv {
  container external-prefix-tlv {
    description "External Prefix LSA TLV";
    leaf external-prefix-tlv-length {
      type uint16;
      description
        "External Prefix TLV Length - Variable dependent
          on sub-TLVs";
    }
  }
  container flags {
    leaf-list ospfv3-e-external-prefix-bits {
```

```

        type identityref {
            base ospfv3-e-external-prefix-option;
        }
        description "OSPFv3 external-prefix TLV bits list.";
    }
    description "External Prefix Flags";
}
leaf metric {

```

```

        type rt-types:uint24;
        description "External Prefix Metric";
    }
    uses ospfv3-lsa-prefix;
    list sub-tlvs {
        description "External Prefix TLV Sub-TLVs";
        uses unknown-sub-tlv;
        uses ipv6-fwd-addr-sub-tlv;
        uses ipv4-fwd-addr-sub-tlv;
        uses route-tag-sub-tlv;
    }
}
description "External Prefix TLV Grouping";
}

grouping intra-area-prefix-tlv {
    container intra-prefix-tlv {
        description "Intra-Area Prefix LSA TLV";
        leaf intra-prefix-tlv-length {
            type uint16;
            description
                "Intra-Area Prefix TLV Length - Variable dependent
                on sub-TLVs";
        }
    }
    leaf metric {
        type rt-types:uint24;
        description "Intra-Area Prefix Metric";
    }
}
uses ospfv3-lsa-prefix;
list sub-tlvs {
    description "Intra-Area Prefix TLV Sub-TLVs";
    uses unknown-sub-tlv;
}

```

```

    }
    description "Intra-Area Prefix TLV Grouping";
}

grouping ipv6-link-local-tlv {
    container ipv6-link-local-tlv {
        description "IPv6 Link-Local LSA TLV";
        leaf ipv6-link-local-tlv-length {
            type uint16;
            description
                "IPv6 Link-Local TLV Length - Variable dependent
                on sub-TLVs";
        }
        leaf link-local-address {
            type inet:ipv6-address;
        }
    }
}

```

```

        description
            "IPv6 Link Local address";
    }
    list sub-tlvs {
        description "IPv6 Link Local TLV Sub-TLVs";
        uses unknown-sub-tlv;
    }
}
description "IPv6 Link-Local TLV Grouping";
}

grouping ipv4-link-local-tlv {
    container ipv4-link-local-tlv {
        description "IPv6 Link-Local LSA TLV";
        leaf ipv4-link-local-tlv-length {
            type uint16;
            description
                "IPv4 Link-Local TLV Length - Variable dependent
                on sub-TLVs";
        }
        leaf link-local-address {
            type inet:ipv4-address;
            description
                "IPv4 Link Local address";
        }
    }
    list sub-tlvs {

```

```

        description "IPv4 Link Local TLV Sub-TLVs";
        uses unknown-sub-tlv;
    }
}
description "IPv4 Link-Local TLV Grouping";
}

grouping ospfv3-e-lsa-body {
    description "OSPFv3 Extended LSA body.";
    container e-router {
        when "derived-from(../../ospf:header/ospf:type, "
            + "'ospfv3-e-router-lsa')" {
            description "Only valid for OSPFv3 Extended-Router LSAs";
        }
        description "OSPFv3 Extended Router LSA";
        uses ospf:ospf-router-lsa-bits;
        uses ospf:ospfv3-lsa-options;

        list e-router-tlvs {
            description "E-Router LSA TLVs";
            container unknown-tlv {
                uses ospf:tlv;
            }
        }
    }
}

```

```

        description "Unknown E-Router TLV";
    }
    container link-tlv {
        description "E-Router LSA TLV";
        leaf link-tlv-length {
            type uint16;
            description
                "Link TLV Length - Variable dependent on sub-TLVs";
        }
        leaf interface-id {
            type uint32;
            description "Interface ID for link";
        }
        leaf neighbor-interface-id {
            type uint32;
            description "Neighbor's Interface ID for link";
        }
        leaf neighbor-router-id {
            type rt-types:router-id;
        }
    }
}

```

```

        description "Neighbor's Router ID for link";
    }
    leaf type {
        type uint8;
        description "Link type: 1 - Point-to-Point Link
                    2 - Transit Network Link
                    3 - Stub Network Link Link
                    4 - Virtual Link";
    }
    leaf metric {
        type uint16;
        description "Link Metric";
    }
    list sub-tlvs {
        description "Link TLV Sub-TLVs";
        uses unknown-sub-tlv;
    }
}
}
}

container e-network {
    when "derived-from(..../ospf:header/ospf:type, "
        + "'ospfv3-e-network-lsa')\" {
        description
            "Only applies to E-Network LSAs.";
    }
    description "Extended Network LSA";
    uses ospf:ospfv3-lsa-options;
}

```

```

list e-network-tlvs {
    description "E-Network LSA TLVs";
    container unknown--tlv {
        uses ospf:tlv;
        description "Unknown E-Network TLV";
    }
    container attached-router-tlv {
        description "Attached Router TLV";
        leaf attached-router-tlv-length {
            type uint16;
            description
                "Attached Router TLV Length - Variable dependent

```

```

        on sub-TLVs";
    }
    leaf Adjacent-neighbor-router-id {
        type rt-types:router-id;
        description "Adjacent Neighbor's Router ID";
    }
    list sub-tlvs {
        description "Attached Router TLV Sub-TLVs";
        uses unknown-sub-tlv;
    }
}

container e-inter-area-prefix {
    when "derived-from(..../ospf:header/ospf:type, "
        + "'ospfv3-e-inter-area-prefix-lsa')\" {
        description
            "Only applies to E-Inter-Area-Prefix LSAs.";
    }
    description "Extended Inter-Area Prefix LSA";
    list e-inter-prefix-tlvs {
        description "E-Inter-Area-Prefix LSA TLVs";
        container unknown--tlv {
            uses ospf:tlv;
            description "Unknown E-Inter-Area-Prefix TLV";
        }
        container inter-prefix-tlv {
            description "Unknown E-Inter-Area-Prefix LSA TLV";
            leaf inter-prefix-tlv-length {
                type uint16;
                description
                    "Inter-Area-Prefix TLV Length - Variable dependent
                     on sub-TLVs";
            }
        }
        leaf metric {

```

```

        type rt-types:uint24;
        description "Inter-Area Prefix Metric";
    }
    uses ospfv3-lsa-prefix;
    list sub-tlvs {

```



```

        description "Inter-Area Prefix TLV Sub-TLVs";
        uses unknown-sub-tlv;
    }
}
}
}

container e-inter-area-router {
    when "derived-from(..../ospf:header/ospf:type, "
        + "'ospfv3-e-inter-area-router-lsa')" {
        description
            "Only applies to E-Inter-Area-Router LSAs.";
    }
    description "Extended Inter-Area Router LSA";
    list e-inter-router-tlvs {
        description "E-Inter-Area-Router LSA TLVs";
        container unknown-tlv {
            uses ospf:tlv;
            description "Unknown E-Inter-Area-Router TLV";
        }
        container inter-router-tlv {
            description "Unknown E-Inter-Area-Router LSA TLV";
            leaf inter-router-tlv-length {
                type uint16;
                description
                    "Inter-Area-Router TLV Length - Variable dependent
                     on sub-TLVs";
            }
            uses ospf:ospf-router-lsa-bits;
            uses ospf:ospfv3-lsa-options;
            leaf metric {
                type rt-types:uint24;
                description "Inter-Area Router Metric";
            }
            leaf destination-router-id {
                type rt-types:router-id;
                description "Destination Router ID";
            }
        }
        list sub-tlvs {
            description "Inter-Area Router TLV Sub-TLVs";
            uses unknown-sub-tlv;
        }
    }
}

```

```

    }
}

container e-as-external {
    when "derived-from-or-self(..../ospf:header/ospf:type, "
        + "'ospfv3-e-as-external-lsa')" {
        description
            "Only applies to E-AS-external LSAs.";
    }
    list e-external-tlvs {
        description "E-External LSA TLVs";
        container unknown-tlv {
            uses ospf:tlv;
            description "Unknown E-External TLV";
        }
        uses external-prefix-tlv;
    }
    description "E-AS-External LSA.";
}

container e-nssa {
    when "derived-from-or-self(..../ospf:header/ospf:type, "
        + "'ospfv3-e-nssa-lsa')" {
        description
            "Only applies to E-NSSA LSAs.";
    }
    list e-external-tlvs {
        description "E-NSSA LSA TLVs";
        container unknown-tlv {
            uses ospf:tlv;
            description "Unknown E-External TLV";
        }
        uses external-prefix-tlv;
    }
    description "E-NSSA LSA.";
}

container e-link {
    when "derived-from-or-self(..../ospf:header/ospf:type, "
        + "'ospfv3-e-link-lsa')" {
        description
            "Only applies to Extended Link LSAs.";
    }
    description "E-Link LSA";
    leaf rtr-priority {
        type uint8;
        description "Router Priority for the interface.";
    }
}

```

```
    uses ospf:ospfv3-lsa-options;
    list e-link-tlvs {
      description "E-Link LSA TLVs";
      container unknown-tlv {
        uses ospf:tlv;
        description "Unknown E-Link TLV";
      }
      uses intra-area-prefix-tlv;
      uses ipv6-link-local-tlv;
      uses ipv4-link-local-tlv;
    }
  }

  container e-intra-area-prefix {
    when "derived-from-or-self(..../ospf:header/ospf:type, "
      + "'ospfv3-e-intra-area-prefix-lsa')" {
      description
        "Only applies to E-Intra-Area-Prefix LSAs.";
    }
    description "E-Intra-Area-Prefix LSA";
    leaf referenced-ls-type {
      type uint16;
      description "Referenced Link State type";
    }
    leaf referenced-link-state-id {
      type uint32;
      description
        "Referenced Link State ID";
    }
    leaf referenced-adv-router {
      type rt-types:router-id;
      description
        "Referenced Advertising Router";
    }
    list e-intra-prefix-tlvs {
      description "E-Intra-Area-Prefix LSA TLVs";
      container unknown-tlv {
        uses ospf:tlv;
        description "Unknown E-Intra-Area-Prefix TLV";
      }
      uses intra-area-prefix-tlv;
    }
  }
```

```

    }
}

/* Configuration */
augment "/rt:routing/rt:control-plane-protocols"
    + "/rt:control-plane-protocol/ospf:ospf" {

```

```

    when "/rt:routing/rt:control-plane-protocols"
        + "/rt:control-plane-protocol/rt:type = 'ospf:ospfv3'" {
        description
            "This augments the OSPFv3 routing protocol when used.";
    }
description
    "This augments the OSPFv3 protocol configuration
    with segment routing.";
leaf extended-lsa-support {
    if-feature extended-lsa-support;
    type boolean;
    default false;
    description
        "Enable OSPFv3 Extended LSA Support for the OSPFv3
        domain";
}
}

augment "/rt:routing/rt:control-plane-protocols/"
    + "rt:control-plane-protocol/ospf:ospf/ospf:areas/ospf:area" {
    when "'ospf:.../.../.../.../rt:type' = 'ospf:ospfv3'" {
        description
            "This augments the OSPFv3 area configuration
            when used.";
    }
description
    "This augments the OSPFv3 protocol area
    configuration with Extend LSA support";
leaf extended-lsa-support {
    if-feature extended-lsa-support;
    type boolean;
    default false;
    description
        "Enable OSPFv3 Extended LSA Support for the OSPFv3 area";
}
}

```

```

}

/*
 * Link State Database (LSDB) Augmentations
 */
augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:areas/ospf:area/"
+ "ospf:interfaces/ospf:interface/ospf:database/"
+ "ospf:link-scope-lsa-type/ospf:link-scope-lsas/"
+ "ospf:link-scope-lsa/ospf:version/ospf:ospfv3/"
+ "ospf:ospfv3/ospf:body" {
  when "/rt:routing/rt:control-plane-protocols"

```

```

+ "/rt:control-plane-protocol/rt:type = 'ospf:ospfv3'" {
  description
    "This augmentation is only valid for OSPFv3.";
}
description
  "OSPFv3 Link-Scoped Extended LSAs";
}

augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:areas/ospf:area/ospf:database/"
+ "ospf:area-scope-lsa-type/ospf:area-scope-lsas/"
+ "ospf:area-scope-lsa/ospf:version/ospf:ospfv3/"
+ "ospf:ospfv3/ospf:body" {
  when "../..../..../..../..../..../..../"
  + "rt:type = 'ospf:ospfv3'" {
    description
      "This augmentation is only valid for OSPFv3
      E-Router LSAs";
  }
  uses ospfv3-e-lsa-body;
  description
    "OSPFv3 Area-Scoped Extended LSAs";
}
augment "/rt:routing/"
+ "rt:control-plane-protocols/rt:control-plane-protocol/"
+ "ospf:ospf/ospf:database/"
+ "ospf:as-scope-lsa-type/ospf:as-scope-lsas/"

```

```

+ "ospf:as-scope-lsa/ospf:version/ospf:ospfv3/"
+ "ospf:ospfv3/ospf:body" {
when "'ospf:../../../../../../../../../../'"
+ "rt:type" = 'ospf:ospfv3' {
description
    "This augmentation is only valid for OSPFv3.";
}
uses ospfv3-e-lsa-body;
description
    "OSPFv3 AS-Scoped Extended LSAs";
}
}
<CODE ENDS>

```

4. Security Considerations

The YANG modules specified in this document define a schema for data that is designed to be accessed via network management protocols such as NETCONF [\[RFC6241\]](#) or RESTCONF [\[RFC8040\]](#). The lowest NETCONF layer is the secure transport layer, and the mandatory-to-implement secure

transport is Secure Shell (SSH) [\[RFC6242\]](#). The lowest RESTCONF layer is HTTPS, and the mandatory-to-implement secure transport is TLS [\[RFC5246\]](#).

The NETCONF access control model [\[RFC6536\]](#) provides the means to restrict access for particular NETCONF or RESTCONF users to a pre-configured subset of all available NETCONF or RESTCONF protocol operations and content.

There are a number of data nodes defined in `ietf-ospfv3-extended-lsa.yang` module that are writable/creatable/deletable (i.e., `config true`, which is the default). These data nodes may be considered sensitive or vulnerable in some network environments. Write operations (e.g., `edit-config`) to these data nodes without proper protection can have a negative effect on network operations. For OSPFv3 Extended LSAs, the ability to disable OSPFv3 Extended LSA support result in a denial of service.

Some of the readable data nodes in the `ietf-ospfv3-extended-lsa.yang` module may be considered sensitive or vulnerable in some network environments. It is thus important to control read access (e.g., via

get, get-config, or notification) to these data nodes. The exposure of the Link State Database (LSDB) will expose the detailed topology of the network. This may be undesirable since both due to the fact that exposure may facilitate other attacks. Additionally, network operators may consider their topologies to be sensitive confidential data.

[5.](#) IANA Considerations

This document registers a URI in the IETF XML registry [[RFC3688](#)]. Following the format in [[RFC3688](#)], the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-ospfv3-extended-lsa
Registrant Contact: The IESG.
XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[RFC6020](#)].

name: ietf-ospfv3-extended-lsa
namespace: urn:ietf:params:xml:ns:yang:ietf-ospfv3-extended-lsa
prefix: ospfv3-e-lsa
reference: RFC XXXX

Lindem, et al.	Expires February 14, 2020	[Page 27]
----------------	---------------------------	-----------

Internet-Draft	OSPFv3 Extended LSAs YANG	August 2019
----------------	---------------------------	-------------

[6.](#) Acknowledgements

This document was produced using Marshall Rose's xml2rfc tool.

The YANG model was developed using the suite of YANG tools written and maintained by numerous authors.

[7.](#) References

[7.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997,

<<https://www.rfc-editor.org/info/rfc2119>>.

- [RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), DOI 10.17487/RFC3688, January 2004, <<https://www.rfc-editor.org/info/rfc3688>>.
- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/info/rfc5246>>.
- [RFC5340] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF for IPv6", [RFC 5340](#), DOI 10.17487/RFC5340, July 2008, <<https://www.rfc-editor.org/info/rfc5340>>.
- [RFC6020] Bjorklund, M., Ed., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), DOI 10.17487/RFC6020, October 2010, <<https://www.rfc-editor.org/info/rfc6020>>.
- [RFC6241] Enns, R., Ed., Bjorklund, M., Ed., Schoenwaelder, J., Ed., and A. Bierman, Ed., "Network Configuration Protocol (NETCONF)", [RFC 6241](#), DOI 10.17487/RFC6241, June 2011, <<https://www.rfc-editor.org/info/rfc6241>>.
- [RFC6242] Wasserman, M., "Using the NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), DOI 10.17487/RFC6242, June 2011, <<https://www.rfc-editor.org/info/rfc6242>>.
- [RFC6536] Bierman, A. and M. Bjorklund, "Network Configuration Protocol (NETCONF) Access Control Model", [RFC 6536](#), DOI 10.17487/RFC6536, March 2012, <<https://www.rfc-editor.org/info/rfc6536>>.

Lindem, et al.

Expires February 14, 2020

[Page 28]

Internet-Draft

OSPFv3 Extended LSAs YANG

August 2019

- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.
- [RFC8022] Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [RFC 8022](#), DOI 10.17487/RFC8022, November 2016, <<https://www.rfc-editor.org/info/rfc8022>>.

- [RFC8040] Bierman, A., Bjorklund, M., and K. Watsen, "RESTCONF Protocol", [RFC 8040](#), DOI 10.17487/RFC8040, January 2017, <<https://www.rfc-editor.org/info/rfc8040>>.
- [RFC8349] Lhotka, L., Lindem, A., and Y. Qu, "A YANG Data Model for Routing Management (NMDA Version)", [RFC 8349](#), DOI 10.17487/RFC8349, March 2018, <<https://www.rfc-editor.org/info/rfc8349>>.
- [RFC8362] Lindem, A., Roy, A., Goethals, D., Reddy Vallem, V., and F. Baker, "OSPFv3 Link State Advertisement (LSA) Extensibility", [RFC 8362](#), DOI 10.17487/RFC8362, April 2018, <<https://www.rfc-editor.org/info/rfc8362>>.

[7.2.](#) Informative References

- [I-D.ietf-ospf-yang]
Yeung, D., Qu, Y., Zhang, Z., Chen, I., and A. Lindem,
"YANG Data Model for OSPF Protocol", [draft-ietf-ospf-yang-26](#) (work in progress), August 2019.

Authors' Addresses

Acee Lindem
Cisco Systems
301 Midenhall Way
Cary, NC 27513

EMail: acee@cisco.com

Sharmila Palani
Cisco Systems
170 West Tasman Drive
San Jose, CA 95134

EMail: shpalani@cisco.com

Yingzhen Qu
Futurewei
2330 Central Expressway
Santa Clara, CA 95050
USA

EMail: yingzhen.qu@futurewei.com

