

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: October 17, 2015

A. Lindem, Ed.
Y. Qu
D. Yeung
Cisco Systems
I. Chen
Ericsson
J. Zhang
Juniper Networks
Y. Yang
Cisco Systems
April 15, 2015

Key Chain YANG Data Model
draft-acee-rtg-yang-key-chain-04.txt

Abstract

This document describes the key chain YANG data model. A key chain is a list of elements each containing a key, send lifetime, accept lifetime, and algorithm. By properly overlapping the send and accept lifetimes of multiple key chain elements, keys and algorithms may be gracefully updated. By representing them in a YANG data model, key distribution can be automated. Key chains are commonly used for routing protocol authentication and other applications. In some applications, the protocols do not use the key chain element key directly, but rather a key derivation function is used to derive a short-lived key from the key chain element key.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 17, 2015.

Internet-Draft

YANG Key Chain

April 2015

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Notation	3
2.	Problem Statement	3
2.1.	Graceful Key Rollover using Key Chains	3
3.	Design of the Key Chain Model	4
3.1.	Key Chain Operational State	4
3.2.	Key Chain Model Tree	5
4.	Key Chain YANG Model	7
5.	Security Considerations	14
6.	IANA Considerations	14
7.	References	15
7.1.	Normative References	15
7.2.	Informative References	15
Appendix A.	Acknowledgments	16
	Authors' Addresses	16

[1.](#) Introduction

This document describes the key chain YANG data model. A key chain is a list of elements each containing a key, send lifetime, accept lifetime, and algorithm. By properly overlapping the send and accept lifetimes of multiple key chain elements, keys and algorithms may be gracefully updated. By representing them in a YANG data model, key distribution can be automated. Key chains are commonly used for routing protocol authentication and other applications. In some applications, the protocols do not use the key chain element key

directly, but rather a key derivation function is used to derive a short-lived key from the key chain element key.

[1.1.](#) Requirements Notation

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC-KEYWORDS](#)].

[2.](#) Problem Statement

This document describes a YANG [[YANG](#)] data model for key chains. Key chains have been implemented and deployed by a large percentage of network equipment vendors. Providing a standard YANG model will facilitate automated key distribution and non-disruptive key rollover. This will aid in tightening the security of the core routing infrastructure as recommended in [[IAB-REPORT](#)].

A key chain is a list of containing one or more elements containing a Key ID, key, send/accept lifetimes, and the associated authentication or encryption algorithm. A conceptual representation of a crypto key table is described in [[CRYPTO-KEYTABLE](#)]. The key chain model presented herein represents a practical implementation of the crypto key table. However, the key selection is left to the applications requiring authentication or encryption. This is more inline with the current operational model.

[2.1.](#) Graceful Key Rollover using Key Chains

Key chains may be used to gracefully update the key and/or algorithm used by an application for authentication or encryption. This MAY be accomplished by accepting all the keys that have a valid accept lifetime and sending the key with the most recent send lifetime. One scenario for facilitating key rollover is to:

1. Distribute a key chain with a new key to all the routers or other network devices in the domain of that key chain. The new key's accept lifetime should be such that it is accepted during the key rollover period. The send lifetime should be a time in the

future when it can be assured that all the routers in the domain of that key are upgraded. This will have no immediate impact on the keys used for transmission.

2. Assure that all the network devices have been updated with the updated key chain and that their system times are roughly synchronized. The system times of devices within an administrative domain are commonly synchronized (e.g., using Network Time Protocol (NTP) [[NTP-PROTO](#)]). This also may be automated.

3. When the send lifetime of the new key becomes valid, the network devices within the domain of key chain will start sending the new key.
4. At some point in the future, a new key chain with the old key removed may be distributed to the network devices within the domain of the key chain. However, this may be deferred until the next key rollover. If this is done, the key chain will always include two keys; either the current and future key (during key rollovers) or the current and previous keys (between key rollovers).

[3.](#) Design of the Key Chain Model

The ietf-keychain module contains a list of one or more keys indexed by a Key ID. For some applications (e.g., OSPFv3 [[OSPFV3-AUTH](#)]), the Key-Id is used to identify the key chain entry to be used. In addition to the Key-ID, each key chain entry includes a key-string and a cryptographic algorithm. Optionally, the key chain entries include send/accept lifetimes. If the send/accept lifetime is unspecified, the key is always considered valid.

Note that asymmetric keys, i.e., a different key value used for transmission versus acceptance, may be supported with multiple key chain elements where the accept-lifetime or send-lifetime is not valid (e.g., has an end-time equal to the start-time).

Due to the differences in key chain implementations across various vendors, some of the data elements are optional. Additionally, the

key-chain is made a grouping so that an implementation could support scoping other than at the global level. Finally, the crypto-algorithm-types grouping is provided for reuse when configuring legacy authentication and encryption not using key-chains.

A key-chain is identified by a unique name within the scope of the network device. The "key-chain-ref" typedef SHOULD be used by other YANG modules when they need to reference a configured key-chain.

[3.1.](#) Key Chain Operational State

The key chain operational state is maintained in a separate tree. In addition the configuration state, it includes an indication of whether or not a key chain entry is valid for sending or acceptance.

[3.2.](#) Key Chain Model Tree

```
+--rw key-chains
|  +--rw key-chain-list* [name]
|    +--rw name                string
|    +--rw accept-tolerance {accept-tolerance}?
|    |  +--rw duration?      uint32
|    +--rw key-chain-entry* [key-id]
|      +--rw key-id           uint64
|      +--rw key-string
|        +--rw (key-string-style)?
|        |  +--:(keystring)
|        |    +--rw keystring?      string
|        |    +--:(hexadecimal) {hex-key-string}?
|        |      +--rw hexadecimal-string?  yang:hex-string
|      +--rw lifetime
|        +--rw (lifetime)?
|        |  +--:(send-and-accept-lifetime)
|        |    +--rw send-accept-lifetime
|        |      +--rw (lifetime)?
|        |      |  +--:(always)
|        |      |    +--rw always?      empty
```

```

        +---:(start-end-time)
        +---rw start-date-time? yang:date-and-time
        +---rw (end-time)?
        +---:(infinite)
        | +---rw no-end-time?          empty
        +---:(duration)
        | +---rw duration?             uint32
        +---:(end-date-time)
        +---rw end-date-time?
        yang:date-and-time
+---:(independent-send-accept-lifetime)
| {independent-send-accept-lifetime}?
+---rw send-lifetime
| +---rw (lifetime)?
+---:(always)
| +---rw always?                      empty
+---:(start-end-time)
+---rw start-date-time? yang:date-and-time
+---rw (end-time)?
+---:(infinite)
| +---rw no-end-time?          empty
+---:(duration)
| +---rw duration?             uint32
+---:(end-date-time)
+---rw end-date-time?
yang:date-and-time

```

```

+---rw accept-lifetime
+---rw (lifetime)?
+---:(always)
| +---rw always?                      empty
+---:(start-end-time)
+---rw start-date-time? yang:date-and-time
+---rw (end-time)?
+---:(infinite)
| +---rw no-end-time?          empty
+---:(duration)
| +---rw duration?             uint32
+---:(end-date-time)
+---rw end-date-time?
yang:date-and-time
+---rw crypto-algorithm

```

```

|         +---rw (algorithm)?
|         |   +---:(hmac-sha-1-12) {crypto-hmac-sha-1-12}?
|         |   |   +---rw hmac-sha1-12?    empty
|         +---:(md5)
|         |   +---rw md5?                    empty
|         +---:(sha-1)
|         |   +---rw sha-1?                  empty
|         +---:(hmac-sha-1)
|         |   +---rw hmac-sha-1?            empty
|         +---:(hmac-sha-256)
|         |   +---rw hmac-sha-256?          empty
|         +---:(hmac-sha-384)
|         |   +---rw hmac-sha-384?          empty
|         +---:(hmac-sha-512)
|         |   +---rw hmac-sha-512?          empty
+---ro key-chains-state
+---ro key-chain-list-state*
+---ro name-state?                        string
+---ro accept-tolerance-state
| +---ro duration?    uint32
+---ro key-chain-entry* [key-id]
|   +---ro key-id                        uint64
|   +---ro lifetime-state
|   |   +---ro send-lifetime
|   |   |   +---ro (lifetime)?
|   |   |   |   +---:(always)
|   |   |   |   |   +---ro always?                empty
|   |   |   |   +---:(start-end-time)
|   |   |   |   |   +---ro start-date-time?        yang:date-and-time
|   |   |   |   |   +---ro (end-time)?
|   |   |   |   |   |   +---:(infinite)
|   |   |   |   |   |   |   +---ro no-end-time?    empty
|   |   |   |   |   |   |   +---:(duration)

```

```

|   |   |   |   +---ro duration?                uint32
|   |   |   |   +---:(end-date-time)
|   |   |   |   +---ro end-date-time?        yang:date-and-time
|   +---ro send-valid?                boolean
|   +---ro accept-lifetime
|   |   +---ro (lifetime)?
|   |   |   +---:(always)
|   |   |   |   +---ro always?                empty

```

```

| |      +---:(start-end-time)
| |      +---ro start-date-time?   yang:date-and-time
| |      +---ro (end-time)?
| |      +---:(infinite)
| |      | +---ro no-end-time?      empty
| |      +---:(duration)
| |      | +---ro duration?         uint32
| |      +---:(end-date-time)
| |      +---ro end-date-time?     yang:date-and-time
| +---ro accept-valid?            boolean
+---ro crypto-algorithm-state
  +---ro (algorithm)?
    +---:(hmac-sha-1-12) {crypto-hmac-sha-1-12}?
    | +---ro hmac-sha1-12?         empty
    +---:(md5)
    | +---ro md5?                  empty
    +---:(sha-1)
    | +---ro sha-1?                empty
    +---:(hmac-sha-1)
    | +---ro hmac-sha-1?           empty
    +---:(hmac-sha-256)
    | +---ro hmac-sha-256?         empty
    +---:(hmac-sha-384)
    | +---ro hmac-sha-384?         empty
    +---:(hmac-sha-512)
    +---ro hmac-sha-512?          empty

```

4. Key Chain YANG Model

```

<CODE BEGINS>
module ietf-key-chain {
  namespace "urn:ietf:params:xml:ns:yang:ietf-key-chain";
  // replace with IANA namespace when assigned
  prefix "key-chain";

  import ietf-yang-types {
    prefix "yang";
  }
}

```

```

    "Cisco Systems
      170 West Tasman Drive
      San Jose, CA 95134-1706
      USA";
  contact
    "Acee Lindem - acee@cisco.com";

  description
    "This YANG module defines the generic configuration
      data for key-chain. It is intended that the module
      will be extended by vendors to define vendor-specific
      key-chain configuration parameters.
    ";

  revision 2015-02-24 {
    description
      "Initial revision.";
    reference
      "RFC XXXX: A YANG Data Model for key-chain";
  }

  typedef key-chain-ref {
    type leafref {
      path "/key-chain:key-chains/key-chain-list/key-chain:name";
    }
    description
      "This type is used by data models that need to reference
        configured key-chains.";
  }

  feature hex-key-string {
    description
      "Support hexadecimal key string.";
  }

  feature accept-tolerance {
    description
      "To specify the tolerance or acceptance limit.";
  }

  feature independent-send-accept-lifetime {
    description
      "Support for independent send and accept key lifetimes.";
  }

  feature crypto-hmac-sha-1-12 {
    description

```

```
    "Support for TCP HMAC-SHA-1 12 byte digest hack.";
}

grouping lifetime {
  description
    "Key lifetime specification.";
  choice lifetime {
    default always;
    description
      "Options for specifying key accept or send lifetimes";
    case always {
      leaf always {
        type empty;
        description
          "Indicates key lifetime is always valid.";
      }
    }
    case start-end-time {
      leaf start-date-time {
        type yang:date-and-time;
        description "Start time.";
      }
      choice end-time {
        default infinite;
        description
          "End-time setting.";
        case infinite {
          leaf no-end-time {
            type empty;
            description
              "Indicates key lifetime end-time in infinite.";
          }
        }
      }
    }
    case duration {
      leaf duration {
        type uint32 {
          range "1..2147483646";
        }
        units seconds;
        description "Key lifetime duration, in seconds";
      }
    }
    case end-date-time {
      leaf end-date-time {
        type yang:date-and-time;
        description "End time.";
      }
    }
  }
}
```

```
    }  
  }
```

Internet-Draft

YANG Key Chain

April 2015

```
    }  
  }  
}
```

```
grouping crypto-algorithm-types {  
  description "Cryptographic algorithm types.";   
  choice algorithm {  
    description  
      "Options for cryptographic algorithm specification.";   
    case hmac-sha-1-12 {  
      if-feature crypto-hmac-sha-1-12;  
      leaf hmac-sha1-12 {  
        type empty;  
        description "The HMAC-SHA-1-12 algorithm.";   
      }  
    }  
    case md5 {  
      leaf md5 {  
        type empty;  
        description "The MD5 algorithm.";   
      }  
    }  
    case sha-1 {  
      leaf sha-1 {  
        type empty;  
        description "The SHA-1 algorithm.";   
      }  
    }  
    case hmac-sha-1 {  
      leaf hmac-sha-1 {  
        type empty;  
        description "HMAC-SHA-1 authentication algorithm.";   
      }  
    }  
    case hmac-sha-256 {  
      leaf hmac-sha-256 {  
        type empty;  
        description "HMAC-SHA-256 authentication algorithm.";   
      }  
    }  
  }  
}
```

```

    }
  }
  case hmac-sha-384 {
    leaf hmac-sha-384 {
      type empty;
      description "HMAC-SHA-384 authentication algorithm.";
    }
  }
  case hmac-sha-512 {

```

```

    leaf hmac-sha-512 {
      type empty;
      description "HMAC-SHA-512 authentication algorithm.";
    }
  }
}

grouping key-chain {
  description
    "key-chain specification grouping.";
  leaf name {
    type string;
    description "Name of the key-chain.";
  }

  container accept-tolerance {
    if-feature accept-tolerance;
    description
      "Tolerance for key lifetime acceptance (seconds).";
    leaf duration {
      type uint32;
      units seconds;
      default "0";
      description
        "Tolerance range, in seconds.";
    }
  }

  list key-chain-entry {
    key "key-id";
    description "One key.";
  }
}

```

```

leaf key-id {
    type uint64;
    description "Key id.";
}
container key-string {
    description "The key string.";
    choice key-string-style {
        description
            "Key string styles";
        case keystring {
            leaf keystring {
                type string;
                description "Key string in ASCII format.";
            }
        }
        case hexadecimal {

```

```

        if-feature hex-key-string;
        leaf hexadecimal-string {
            type yang:hex-string;
            description
                "Key in hexadecimal string format.";
        }
    }
}
}
container lifetime {
    description "Specify a key's lifetime.";
    choice lifetime {
        description
            "Options for specification of send and accept
            lifetimes.";
        case send-and-accept-lifetime {
            description
                "Send and accept key have the same lifetime.";
            container send-accept-lifetime {
                uses lifetime;
                description
                    "Single lifetime specification for both send and
                    accept lifetimes.";
            }
        }
    }
}

```

```

    case independent-send-accept-lifetime {
        if-feature independent-send-accept-lifetime;
        description
            "Independent send and accept key lifetimes.";
        container send-lifetime {
            uses lifetime;
            description
                "Separate lifetime specification for send
                 lifetime.";
        }
        container accept-lifetime {
            uses lifetime;
            description
                "Separate lifetime specification for accept
                 lifetime.";
        }
    }
}
}
}
container crypto-algorithm {
    uses crypto-algorithm-types;
    description "Cryptographic algorithm associated with key.";
}

```

```

    }
}
container key-chains {
    list key-chain-list {
        key "name";
        description
            "List of key-chains.";
        uses key-chain;
    }
    description "All configured key-chains for the device.";
}

container key-chains-state {
    config "false";
    description "All configured key-chains state.";
    list key-chain-list-state {
        description "One key-chain state.";
        leaf name-state {

```

```

    type string;
    description "Configured name of the key-chain.";
}

container accept-tolerance-state {
    description
        "Configured tolerance for key lifetime
        acceptance (seconds).";
    leaf duration {
        type uint32;
        description
            "Configured tolerance range, in seconds.";
    }
}

list key-chain-entry {
    key "key-id";
    description "One key.";
    leaf key-id {
        type uint64;
        description "Configured key id.";
    }
    container lifetime-state {
        description "Configured key's lifetime.";
        container send-lifetime {
            uses lifetime;
            description
                "Configured send-lifetime.";
        }
        leaf send-valid {

```

```

    type boolean;
    description
        "Status of send-lifetime.";
}
container accept-lifetime {
    uses lifetime;
    description
        "Configured accept-lifetime.";
}
leaf accept-valid {
    type boolean;

```

```

        description
            "Status of accept-lifetime.";
    }
}
container crypto-algorithm-state {
    uses crypto-algorithm-types;
    description "Configured cryptographic algorithm.";
}
}
}
}
}
<CODE ENDS>

```

5. Security Considerations

This document enables the automated distribution of industry standard key chains using the NETCONF [[NETCONF](#)] protocol. As such, the security considerations for the NETCONF protocol are applicable. Given that the key chains themselves are sensitive data, it is RECOMMENDED that the NETCONF communication channel be encrypted. One way to do accomplish this would be to invoke and run NETCONF over SSH as described in [[NETCONF-SSH](#)].

6. IANA Considerations

This document registers a URI in the IETF XML registry [[XML-REGISTRY](#)]. Following the format in [RFC 3688](#), the following registration is requested to be made:

URI: urn:ietf:params:xml:ns:yang:ietf-key-chain

Registrant Contact: The IESG.

XML: N/A, the requested URI is an XML namespace.

This document registers a YANG module in the YANG Module Names registry [[YANG](#)].

name: ietf-acl namespace: urn:ietf:params:xml:ns:yang:ietf-key-

chain prefix: ietf-key-chain reference: RFC XXXX

[7.](#) References

[7.1.](#) Normative References

[NETCONF] Enns, R., Bjorklund, M., Schoenwaelder, J., and A. Bierman, "Network Configuration Protocol (NETCONF)", [RFC 6241](#), June 2011.

[NETCONF-SSH] Wasserman, M., "Using NETCONF Protocol over Secure Shell (SSH)", [RFC 6242](#), June 2011.

[RFC-KEYWORDS] Bradner, S., "Key words for use in RFC's to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[XML-REGISTRY] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

[YANG] Bjorklund, M., "YANG - A Data Modeling Language for the Network Configuration Protocol (NETCONF)", [RFC 6020](#), October 2010.

[7.2.](#) Informative References

[CRYPTO-KEYTABLE] Housley, R., Polk, T., Hartman, S., and D. Zhang, "Table of Cryptographic Keys", [RFC 7210](#), April 2014.

[IAB-REPORT] Andersson, L., Davies, E., and L. Zhang, "Report from the IAB workshop on Unwanted Traffic March 9-10, 2006", [RFC 4948](#), August 2007.

[NTP-PROTO] Mills, D., Martin, J., Burbank, J., and W. Kasch, "Network Time Protocol Version 4: Protocol and Algorithms Specification", [RFC 5905](#), June 2010.

[OSPFV3-AUTH]

Bhatia, M., Manral, V., and A. Lindem, "Supporting Authentication Trailer for OSPFv3", [RFC 7166](#), March 2014.

[Appendix A](#). Acknowledgments

The RFC text was produced using Marshall Rose's `xml2rfc` tool.

Authors' Addresses

Acee Lindem (editor)
Cisco Systems
301 Midenhall Way
Cary, NC 27513
USA

Email: acee@cisco.com

Yingzhen Qu
Cisco Systems
170 West Tasman Drive
San Jose, CA 95134
USA

Email: yiqu@cisco.com

Derek Yeung
Cisco Systems
170 West Tasman Drive
San Jose, CA 95134
USA

Email: myeung@cisco.com

Ing-Wher Chen
Ericsson

Email: ing-wher.chen@ericsson.com

Internet-Draft

YANG Key Chain

April 2015

Jeffrey Zhang
Juniper Networks
10 Technology Park Drive
Westford, MA 01886
USA

Email: zzhang@juniper.net

Yi Yang
Cisco Systems
7025 Kit Creek Road
Research Triangle Park, NC 27709
USA

Email: yiya@cisco.com

Lindem, et al.

Expires October 17, 2015

[Page 17]