

Network Working Group
Internet-Draft
Intended status: Informational
Expires: January 10, 2013

J. Arkko
Ericsson
C. Jennings
Cisco
Z. Shelby
Sensinode
July 9, 2012

Uniform Resource Names for Device Identifiers
draft-arkko-core-dev-urn-03

Abstract

This memo describes a new Uniform Resource Name (URN) namespace for hardware device identifiers. A general representation of device identity can be useful in many applications, such as in sensor data streams and storage, or equipment inventories. A URN-based representation can be easily passed along in any application that needs the information.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 10, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	Requirements language	4
3.	DEV URN Definition	4
4.	DEV URN Subtypes	5
4.1.	MAC Addresses	6
4.2.	1-Wire Device Identifiers	6
5.	Examples	6
6.	Security Considerations	7
7.	IANA Considerations	7
8.	References	7
8.1.	Normative References	7
8.2.	Informative References	8
Appendix A.	Changes from Previous Version	10
Appendix B.	Acknowledgments	10
	Authors' Addresses	10

1. Introduction

This memo describes a new Uniform Resource Name (URN) [[RFC2141](#)] [[RFC3406](#)] namespace for hardware device identifiers. A general representation of device identity can be useful in many applications, such as in sensor data streams and storage, or equipment inventories [[I-D.ietf-core-coap](#)], [[I-D.jennings-senml](#)], [[I-D.arkko-core-sleepy-sensors](#)] [[I-D.arkko-core-security-arch](#)]. A URN-based representation can be easily passed along in any application that needs the information, as it fits in protocols mechanisms that are designed to carry URNs [[RFC2616](#)], [[RFC3261](#)], [[I-D.ietf-core-coap](#)]. Finally, URNs can also be easily carried and stored in formats such as XML [[W3C.REC-xml-19980210](#)] or JSON [[I-D.jennings-senml](#)] [[RFC4627](#)]. Using URNs in these formats is often preferable as they are universally recognized, self-describing, and therefore avoid the need for agreeing to interpret an octet string as a specific form of a MAC address, for instance.

This memo defines identity URN types for situations where no such convenient type already exist. For instance, [[I-D.farrell-decade-ni](#)] defines cryptographic identifiers, [[I-D.montemurro-gsma-imei-urn](#)] defines International Mobile station Equipment Identity (IMEI) identifiers for use with 3GPP cellular systems, and [[I-D.atarius-dispatch-meid-urn](#)] defines Mobile Equipment Identity (MEID) identifiers for use with 3GPP2 cellular systems. Those URN types should be employed when such identities are transported; this memo does not redefine these identifiers in any way.

Universally Unique IDentifier (UUID) URNs [[RFC4122](#)] are another alternative way for representing device identifiers, and already support MAC addresses as one of type of an identifier. However, UUIDs can be inconvenient in environments where it is important that the identifiers are as simple as possible and where additional requirements on stable storage, real-time clocks, and identifier length can be prohibitive. UUID-based identifiers are recommended for all general purpose uses when MAC addresses are available as identifiers. The device URN defined in this memo is recommended for constrained environments.

Future device identifier types can extend the device device URN type defined here, or define their own URNs.

The rest of this memo is organized as follows. [Section 3](#) defines the "DEV" URN type, and [Section 4](#) defines subtypes for IEEE MAC-48, EUI-48 and EUI-64 addresses and 1-wire device identifiers. [Section 5](#) gives examples. [Section 6](#) discusses the security considerations of the new URN type. Finally, [Section 7](#) specifies the IANA registration for the new URN type and sets requirements for subtype allocations

within this type.

2. Requirements language

In this document, the key words "MAY", "MUST", "MUST NOT", "OPTIONAL", "RECOMMENDED", "SHOULD", and "SHOULD NOT", are to be interpreted as described in [\[RFC2119\]](#).

3. DEV URN Definition

Namespace ID: "dev" requested

Registration Information: This is the first registration of this namespace, 2011-08-27.

Registration version number: 1

Registration date: 2011-08-27

Declared registrant of the namespace: IETF and the CORE working group. Should the working group cease to exist, discussion should be directed to the general IETF discussion forums or the IESG.

Declaration of syntactic structure: The identifier is expressed in ASCII (UTF-8) characters and has a hierarchical structure as follows:

```
devurn = "urn:dev:" body componentpart
body = macbody / owbody / otherbody
macbody = "mac:" hexstring
owbody = "ow:" hexstring
otherbody = subtype ":" identifier
subtype = ALPHA *(DIGIT / ALPHA)
identifier = 1*unreserved
componentpart = [ ";" component [ componentpart ] ]
component = *1(DIGIT / ALPHA)
hexstring = hexbyte /
             hexbyte hexstring
hexbyte = hexdigit hexdigit
hexdigit = DIGIT / hexletter
hexletter = "a" / "b" / "c" / "d" / "e" / "f"
```

The above Augmented Backus-Naur Form (ABNF) uses the DIGIT and ALPHA rules defined in [\[RFC5234\]](#), which are not repeated here. The rule for unreserved is defined in [Section 2.3 of \[RFC3986\]](#).

The device identity namespace includes three subtypes, and more may

be defined in the future as specified in [Section 7](#).

The optional components following the hexstring are strings depicting individual aspects of a device. The specific strings and their semantics are up to the designers of the device, but could be used to refer to specific interfaces or functions within the device.

Relevant ancillary documentation: See [Section 4](#).

Identifier uniqueness considerations: Device identifiers are generally expected to be unique, barring the accidental issue of multiple devices with the same identifiers.

Identifier persistence considerations: This URN type SHOULD only be used for persistent identifiers, such as hardware-based identifiers or cryptographic identifiers based on keys intended for long-term usage.

Process of identifier assignment: The process for identifier assignment is dependent on the used subtype, and documented in the specific subsection under [Section 4](#).

Process for identifier resolution: The device identities are not expected to be globally resolvable. No identity resolution system is expected. Systems may perform local matching of identities to previously seen identities or configured information, however.

Rules for Lexical Equivalence: The lexical equivalence of the DEV URN is defined as an exact and case sensitive string match. Note that the two subtypes defined in this document use only lower case letters, however. Future types might use identifiers that require other encodings that require a more full-blown character set (such as BASE64), however.

Conformance with URN Syntax: The string representation of the device identity URN and of the MEID sub namespace is fully compatible with the URN syntax.

Validation Mechanism: Specific subtypes may be validated through mechanisms discussed in [Section 4](#).

Scope: DEV URN is global in scope.

[4.](#) DEV URN Subtypes

4.1. MAC Addresses

DEV URNs of the "mac" subtype are based on the EUI-64 identifier [[IEEE.EUI64](#)] derived from a device with a built-in 64-bit EUI-64. The EUI-64 is formed from 24 or 36 bits of organization identifier followed by 40 or 28 bits of device-specific extension identifier assigned by that organization.

In the DEV URN "mac" subtype the hexstring is simply the full EUI-64 identifier represented as a hexadecimal string. It is always exactly 16 characters long.

MAC-48 and EUI-48 identifiers are also supported by the same DEV URN subtype. To convert a MAC-48 address to an EUI-64 identifier, The OUI of the Ethernet address (the first three octets) becomes the organization identifier of the EUI-64 (the first three octets). The fourth and fifth octets of the EUI are set to the fixed value FFFF hexadecimal. The last three octets of the Ethernet address become the last three octets of the EUI-64. The same process is used to convert an EUI-48 identifier, but the fixed value FFFE is used instead.

Identifier assignment for all of these identifiers rests within the IEEE.

4.2. 1-Wire Device Identifiers

The 1-Wire* system is a device communications bus system designed by Dallas Semiconductor Corporation. 1-Wire devices are identified by a 64-bit identifier that consists of 8 byte family code, 48 bit identifier unique within a family, and 8 bit CRC code [[OW](#)].

*) 1-Wire is a registered trademark.

In DEV URNs with the "ow" subtype the hexstring is a representation of the full 64 bit identifier as a hexadecimal string. It is always exactly 16 characters long. Note that the last two characters represent the 8-bit CRC code. Implementations MAY check the validity of this code.

Family code and identifier assignment for all 1-wire devices rests with the manufacturers.

5. Examples

The following three examples provide examples of MAC-based, 1-Wire, and Cryptographic identifiers:


```
urn:dev:mac:0024beffffe804ff1      # The MAC address of
                                     # Jari's laptop

urn:dev:ow:10e2073a01080063         # The 1-Wire temperature
                                     # sensor in Jari's
                                     # kitchen

urn:dev:ow:264437f50000000ed;humidity # The laundry sensor's
                                     # humidity part

urn:dev:ow:264437f50000000ed;temperature # The laundry sensor's
                                     # temperature part
```

6. Security Considerations

On most devices, the user can display device identifiers. Depending on circumstances, device identifiers may or may not be modified or tampered by the user. An implementation of the DEV URN MUST NOT change these properties from what they were intended. In particular, a device identifier that is intended to be immutable should not become mutable as a part of implementing the DEV URN type. More generally, nothing in this memo should be construed to override what the relevant device specifications have already said about the identifiers.

Other devices in the same network may or may not be able to identify the device. For instance, on Ethernet network, the MAC address of a device is visible to all other devices.

7. IANA Considerations

Additional subtypes for DEV URNs can be defined through IETF Review or IESG Approval [[RFC5226](#)].

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2141] Moats, R., "URN Syntax", [RFC 2141](#), May 1997.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom,

"Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.

[RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.

[RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

[RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

[IEEE.EUI64]
IEEE, "Guidelines For 64-bit Global Identifier (EUI-64)",
IEEE ,
<<http://standards.ieee.org/db/oui/tutorials/EUI64.html>>.

[OW] IEEE, "Overview of 1-Wire(R) Technology and Its Use",
MAXIM
<http://www.maxim-ic.com/app-notes/index.mvp/id/1796>,
<<http://www.maxim-ic.com/app-notes/index.mvp/id/1796>>.

8.2. Informative References

[RFC2616] Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.

[RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.

[RFC3971] Arkko, J., Kempf, J., Zill, B., and P. Nikander, "SEcure Neighbor Discovery (SEND)", [RFC 3971](#), March 2005.

[RFC3972] Aura, T., "Cryptographically Generated Addresses (CGA)", [RFC 3972](#), March 2005.

[RFC4122] Leach, P., Mealling, M., and R. Salz, "A Universally Unique IDentifier (UUID) URN Namespace", [RFC 4122](#), July 2005.

[RFC4627] Crockford, D., "The application/json Media Type for JavaScript Object Notation (JSON)", [RFC 4627](#), July 2006.

[W3C.REC-xml-19980210]

Sperberg-McQueen, C., Bray, T., and J. Paoli, "XML 1.0 Recommendation", World Wide Web Consortium FirstEdition REC-xml-19980210, February 1998, <<http://www.w3.org/TR/1998/REC-xml-19980210>>.

[I-D.ietf-core-coap]

Shelby, Z., Hartke, K., Bormann, C., and B. Frank, "Constrained Application Protocol (CoAP)", [draft-ietf-core-coap-06](#) (work in progress), May 2011.

[I-D.jennings-senml]

Jennings, C., "Media Type for Sensor Markup Language (SENML)", [draft-jennings-senml-05](#) (work in progress), March 2011.

[I-D.farrell-decade-ni]

Farrell, S., Kutscher, D., Dannewitz, C., Ohlman, B., Keranen, A., and P. Hallam-Baker, "Naming Things with Hashes", [draft-farrell-decade-ni-09](#) (work in progress), July 2012.

[I-D.arkko-core-sleepy-sensors]

Arkko, J., Rissanen, H., Loreto, S., Turanyi, Z., and O. Novo, "Implementing Tiny COAP Sensors", [draft-arkko-core-sleepy-sensors-01](#) (work in progress), July 2011.

[I-D.arkko-core-security-arch]

Arkko, J. and A. Keranen, "CoAP Security Architecture", [draft-arkko-core-security-arch-00](#) (work in progress), July 2011.

[I-D.montemurro-gsma-imei-urn]

Montemurro, M., "A Uniform Resource Name Namespace For The GSM Association (GSMA) and the International Mobile station Equipment Identity(IMEI)", [draft-montemurro-gsma-imei-urn-01](#) (work in progress), February 2007.

[I-D.atarius-dispatch-meid-urn]

Atarius, R., "A Uniform Resource Name Namespace for the Device Identity and the Mobile Equipment Identity (MEID)", [draft-atarius-dispatch-meid-urn-01](#) (work in progress), August 2011.

[Appendix A.](#) Changes from Previous Version

Version -02 introduced several changes. The biggest change is that with the NI URNs [[I-D.farrell-decade-ni](#)], it was no longer necessary to define cryptographic identifiers in this specification. Another change was that we incorporated a more generic syntax for future extensions; non-hexstring identifiers can now also be supported, if some future device identifiers for some reason would, for instance, use BASE64. As a part of this change, we also changed the component part separator character from '-' to ';' so that the general format of the rest of the URN can employ the unreserved characters [[RFC3986](#)].

[Appendix B.](#) Acknowledgments

The authors would like to thank Ari Keranen, Stephen Farrell, Christer Holmberg, Peter Saint-Andre, Wouter Cloetens, and Ahmad Muhanna for interesting discussions in this problem space. We would also like to note prior documents that focused on specific device identifiers, such as [[I-D.montemurro-gsma-imei-urn](#)] or [[I-D.atarius-dispatch-meid-urn](#)].

Authors' Addresses

Jari Arkko
Ericsson
Jorvas 02420
Finland

Email: jari.arkko@piuha.net

Cullen Jennings
Cisco
170 West Tasman Drive
San Jose, CA 95134
USA

Phone: +1 408 421-9990
Email: fluffy@cisco.com

Zach Shelby
Sensinode
Kidekuja 2
Vuokatti 88600
FINLAND

Phone: +358407796297

Email: zach@sensinode.com