

**IPv6 Source/Destination Routing using IS-IS
draft-baker-ipv6-isis-dst-src-routing-00**

Abstract

This note describes the changes necessary for IS-IS to route classes of IPv6 traffic that are defined by a source prefix and a destination prefix. This implies not routing "to a destination", but "traffic matching a classification tuple". The obvious application is egress routing - routing traffic using a given prefix to an upstream network that will not drop traffic using that prefix using [BCP 38](#) filters.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 21, 2013.

Copyright Notice

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	3
2.	Theory of Routing	3
2.1.	Dealing with ambiguity	3
3.	Extensions necessary for IS-IS/IPv6	4
3.1.	Source Prefix sub-TLV	4
4.	IANA Considerations	5
5.	Security Considerations	5
6.	Privacy Considerations	5
7.	Acknowledgements	5
8.	Change Log	5
9.	References	5
9.1.	Normative References	5
9.2.	Informative References	5
Appendix A.	Use case: Egress Routing	6
Appendix B.	FIB Design	7
B.1.	Linux Source-Address Forwarding	7
B.1.1.	One FIB per source prefix	7
B.1.2.	One FIB per source prefix plus a general FIB	8
B.2.	PATRICIA	9
B.2.1.	Virtual Bit String	9
B.2.2.	Tree Construction	9
B.2.3.	Tree Lookup	10
	Author's Address	10

[1.](#) Introduction

This specification builds on the extensible TLV defined in [[RFC5308](#)]. It adds to the existing Reachability TLV the (obviously optional) sub-TLV for an IPv6 Source Prefix, to define routes defined by a source and a destination prefix. Note that `::/0`, "any IPv6 Address", is a prefix, so this may be used for default routes as well as more specific routes.

IS-IS TLVs that specify only a destination prefix remain legal. They may be understood as identifying a route to a destination prefix from

Baker

Expires August 21, 2013

[Page 2]

"any" source, which is a very useful class of traffic to compactly represent.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

2. Theory of Routing

Both IS-IS and OSPF perform their calculations by building a lattice of routers and routes from the router performing the calculation to each router, and then use those routes to get to destinations that those routes advertise connectivity to. Following the SPF algorithm, calculation starts by selecting a starting point (typically the router doing the calculation), and successively adding {link, router} pairs until one has calculated a route to every router in the network. As each router is added, including the original router, destinations that it is directly connected to are turned into routes in the route table: "to get to 2001:db8::/32, route traffic to {interface, list of next hop routers}". For immediate neighbors to the originating router, of course, there is no next hop router; traffic is handled locally.

IS-IS [[ISO.10589.1992](#)] represents those destinations as a type-length-value field that identifies an address. For CLNS, it was designed to the ISO NSAP; by various extensions, it also handles IPv4 and IPv6 prefixes and their counterparts for other protocols. Adding a new class of traffic to route is as simple as adding a new tuple type and the supporting method routines for that class of traffic.

2.1. Dealing with ambiguity

In any routing protocol, there is the possibility of ambiguity. An area border router might, for example, summarize the routes to other areas into a small set of relatively short prefixes, which have more specific routes within the area. Traditionally, we have dealt with that using a "longest match first" rule. If the same datagram matches more than one destination prefix advertised within the area, we follow the route to the longest matching prefix.

When routing a class of traffic, we follow an analogous "most specific match" rule; we follow the route for the most specific matching tuple. In cases of simple overlap, such as routing to 2001:db8::/32 or 2001:db8:1::/48, that is exactly analogous; we choose one of the two routes.

It is possible, however, to construct an ambiguous case in which neither class subsumes the other. For example, presume that

- o A is a prefix,
- o B is a more-specific prefix within A,
- o C is a different prefix, and
- o D is a more-specific prefix of C.

The two classes {A, D, *, *} and {B, C, *, *} are ambiguous: a datagram within {B, D, *, *} matches both classes, and it is not clear in the data plane what decision to make. Solving this requires the addition of a third route in the FIB corresponding to the class {B, D, *, *}, which is more-specific than either of the first two, and can be given routing guidance based on metrics or other policy in the usual way.

3. Extensions necessary for IS-IS/IPv6

[Section 2 of \[RFC5308\]](#) defines the "IPv6 Reachability TLV", and carries in it destination prefix advertisements. It has the capability of extension, using sub-TLVs. The extension needed is to add a sub-TLV for each additional item in the tuple. We interpret the lack of a given sub-TLV as "any"; by definition, S=0 implies any source address, any DSCP, and any flow label. If S=1, there will be one or more additional sub-TLVs following the sub-TLV format specified there.

3.1. Source Prefix sub-TLV

```

0                               1                               2                               3
0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      |Prefix Length |      Prefix
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

Source Prefix Sub-TLV

Source Prefix Type: assigned by IANA

TLV Length: Length of the sub-TLV in octets

Prefix Length: Length of the prefix in bits

Prefix: (source prefix length +7)/8 octets of prefix

4. IANA Considerations

This section will request an identifying value for the TLV defined.
This is deferred to the -01 version of the draft.

5. Security Considerations

To be considered.

6. Privacy Considerations

To be considered.

7. Acknowledgements

8. Change Log

Initial Version: February 2013

9. References

9.1. Normative References

- [ISO.10589.1992]
International Organization for Standardization,
"Intermediate system to intermediate system intra-domain-
routing routine information exchange protocol for use in
conjunction with the protocol for providing the
connectionless-mode Network Service (ISO 8473)", ISO
Standard 10589, 1992.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2328] Moy, J., "OSPF Version 2", STD 54, [RFC 2328](#), April 1998.
- [RFC5308] Hopps, C., "Routing IPv6 with IS-IS", [RFC 5308](#), October
2008.
- [RFC5340] Coltun, R., Ferguson, D., Moy, J., and A. Lindem, "OSPF
for IPv6", [RFC 5340](#), July 2008.

9.2. Informative References

- [I-D.baker-fun-routing-class]
Baker, F., "Routing a Traffic Class", [draft-baker-fun-
routing-class-00](#) (work in progress), July 2011.

[PATRICIA]

Morrison, D.R., "Practical Algorithm to Retrieve Information Coded in Alphanumeric", Journal of the ACM 15(4) pp514-534, October 1968.

[RFC0791] Postel, J., "Internet Protocol", STD 5, [RFC 791](#), September 1981.

[RFC1195] Callon, R., "Use of OSI IS-IS for routing in TCP/IP and dual environments", [RFC 1195](#), December 1990.

[RFC1247] Moy, J., "OSPF Version 2", [RFC 1247](#), July 1991.

[RFC1349] Almquist, P., "Type of Service in the Internet Protocol Suite", [RFC 1349](#), July 1992.

[RFC2460] Deering, S.E. and R.M. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.

[RFC2597] Heinanen, J., Baker, F., Weiss, W., and J. Wroclawski, "Assured Forwarding PHB Group", [RFC 2597](#), June 1999.

[RFC2827] Ferguson, P. and D. Senie, "Network Ingress Filtering: Defeating Denial of Service Attacks which employ IP Source Address Spoofing", [BCP 38](#), [RFC 2827](#), May 2000.

Appendix A. Use case: Egress Routing

Using this technology for egress routing is straightforward. Presume a multihomed edge (residential or enterprise) network with multiple egress points to the various ISPs. These ISPs allocate PA prefixes to the network. Due to [BCP 38](#) [[RFC2827](#)], the network must presume that its upstream ISPs will filter out any traffic presented to them that does not use their PA prefix.

Within the network, presume that a /64 prefix from each of those PA prefixes is allocated on each LAN, and that hosts generate and use multiple addresses on each interface.

Within the network, we permit any host to communicate with any other. Hence, routing advertisements within the network use traditional destination routing, which is understood to be advertising the traffic class

{destination, ::/0}.

From the egresses, the firewall or its neighboring router injects a default route for traffic "from" its PA prefix:

{::/0, PA prefix}.

Routing is calculated as normal, with the exception that traffic following a default route will select that route based on the source address. Traffic will never be lost to [BCP 38](#) filters, because by definition the only traffic sent to the ISP is using the PA prefix assigned by the ISP. In addition, while hosts can use spoofed addresses outside of their PA prefixes to attack each other, they cannot send traffic using spoofed addresses to their upstream networks; such traffic has no route.

[Appendix B](#). FIB Design

While the design of the Forwarding Information Base is not a matter for standardization, as it only has to work correctly, not interoperate with something else, the design of a FIB for this type of lookup may differ from approaches used in destination routing. We describe one possible approach that is known to work, from the perspective of a proof of concept.

[B.1](#). Linux Source-Address Forwarding

The University of Waikato has added to the Linux Advanced Routing & Traffic Control facility the ability to maintain multiple FIBs, one for each of a set of prefixes. Implementing source/destination routing using this mechanism is not difficult.

The router must know what source prefixes might be used in its domain. This may be by configuration or, at least in concept, learned from the routing protocols themselves. In whichever way that is done, one can imagine two fundamental FIB structures to serve N source prefixes; N FIBs, one per prefix, or N+1 FIBs, one per prefix plus one for destinations for which the source prefix is unspecified.

[B.1.1](#). One FIB per source prefix

In an implementation with one FIB per source prefix, the routing algorithm has two possibilities.

- o If it calculates a route to a prefix (such as a default route) associated with a given source prefix, it stores the route in the FIB for the relevant source prefix.
- o If it calculates a route for which the source prefix is unspecified, it stores that route in all N FIBs.

When forwarding a datagram, the IP forwarder looks at the source address of the datagram to determine which FIB it should use. If it

is from an address for which there is no FIB, the forwarder discards the datagram as containing a forged source address. If it is from an address within one of the relevant prefixes, it looks up the destination in the indicated FIB and forwards it in the usual way.

The argument for this approach is simplicity: there is one place to look in making a forwarding decision for any given datagram. The argument against it is memory space; it is likely that the FIBs will be similar, but every destination route not associated with a source prefix is duplicated in each FIB. In addition, since it automatically removes traffic whose source address is not among the configured list, it limits the possibility of user software using improper addresses.

B.1.2. One FIB per source prefix plus a general FIB

In an implementation with N+1 FIBs, the algorithm is slightly more complex.

- o If it calculates a route to a prefix (such as a default route) associated with a given source prefix, it stores the route in the FIB for the relevant source prefix.
- o If it calculates a route for which the source prefix is unspecified, it stores that route in the FIB that is not associated with a source prefix.

When forwarding a datagram, the IP forwarder looks at the source address of the datagram to determine which FIB it should use. If it is from one of the configured prefixes, it looks the destination up in the indicated FIB. In any event it also looks the destination up in the "unspecified source address" FIB. If the destination is found in only one of the two, the indicated route is followed. If the destination is found in both, the more specific route is followed.

The argument for this approach is memory space; if a large percentage of routes are only in the general FIB, such as when egress routing is used for the default route and all other routes are internal, the other FIBs are likely to be very small - perhaps only a single default route. The argument against this approach is complexity: most lookups if not all will be done in a prefix-specific FIB and in the general FIB.

B.2. PATRICIA

One approach is a [[PATRICIA](#)] Tree. This is a relative of a Trie, but unlike a Trie, need not use every bit in classification, and does not need the bits used to be contiguous. It depends on treating the bit string as a set of slices of some size, potentially of different sizes. Slice width is an implementation detail; since the algorithm is most easily described using a slice of a single bit, that will be presumed in this description.

B.2.1. Virtual Bit String

It is quite possible to view the fields in a datagram header incorporated into the classification tuple as a virtual bit string such as is shown in Figure 1. This bit string has various regions within it. Some vary and are therefore useful in a radix tree lookup. Some may be essentially constant - all global IPv6 addresses at this writing are within 2000::/3, for example, so while it must be tested to assure a match, incorporating it into the radix tree may not be very helpful in classification. Others are ignored; if the destination is a remote /64, we really don't care what the EID is. In addition, due to variation in prefix length and other details, the widths of those fields vary among themselves. The algorithm the FIB implements, therefore, must efficiently deal with the fact of a discontinuous lookup key.

```
+-----+-----+-----+-----+
|Destination Prefix  |Source Prefix          |DSCP | Flow Label|
+-----+-----+-----+-----+
Common|Varying|Ignored|Common|Varying|Ignored|Varying or ignored
```

Figure 1: Treating a traffic class as a virtual bit string

B.2.2. Tree Construction

The tree is constructed by recursive slice-wise decomposition. At each stage, the input is a set of classes to be classified. At each stage, the result is the addition of a lookup node in the tree that identifies the location of its slice in the virtual bit string (which might be a bit number), the width of the slice to be inspected, and an enumerated set of results. Each result is a similar set of classes, and is analyzed in a similar manner.

The analysis is performed by enumerating which bits that have not already been considered are best suited to classification. For a slice of N bits, one wants to select a slide that most evenly divides the set of classes into 2^N subsets. If one or more bits in the slice is ignored in some of the classes, those classes must be

included in every subset, as the actual classification of them will depend on other bits.

```
Input:{2001:db8::/32, ::/0, *, *}
      {2001:db8:1::/48, ::/0, AF41, *}
      {2001:db8:1::/48, ::/0, AF42, *}
      {2001:db8:1::/48, ::/0, AF43, *}
```

Common parts: Destination prefix 2001:dba, source prefix, and label

Varying parts: DSCP and the third set of sixteen bits in the destination prefix

One possible decomposition:

(1) slice = DSCP

enumerated cases:

```
(a) { {2001:db8::/32, ::/0, *, *}, {2001:db8:1::/48, ::/0, AF41, *} }
(b) { {2001:db8::/32, ::/0, *, *}, {2001:db8:1::/48, ::/0, AF42, *} }
(c) { {2001:db8::/32, ::/0, *, *}, {2001:db8:1::/48, ::/0, AF43, *} }
```

(2) slice = third sixteen bit field in destination

This divides each enumerated case into those containing 0001 and "everything else", which would imply 2001:db8::/32

(1) DSCP




Figure 2: Example PATRICIA Tree

B.2.3. Tree Lookup

To look something up in a PATRICIA Tree, one starts at the root of the tree and performs the indicated comparisons recursively walking down the tree until one reaches a terminal node. When the enumerated subset is empty or contains only a single class, classification stops. Either classification has failed (there was no matching class, or one has presumably found the indicated class. At that point, every bit in the virtual bit string must be compared to the classifier; classification is accepted on a perfect match.

In the example in Figure 2, if a packet {2001:db8:1:2:3:4:5:6, 2001:db8:2:3:4:5:6:7, AF41, 0} arrives, we start at the root. Since it is an AF41 packet, we deduce that case (1a) applies, and since the destination has 0001 in the third sixteen bit field of the destination address, we are comparing to {2001:db8:1::/48, ::/0, AF41, *}. Since the destination address is within 2001:db8:1::/48, classification as that succeeds.

Author's Address

Fred Baker
Cisco Systems
Santa Barbara, California 93117
USA

Email: fred@cisco.com