

Transport Area Working Group

Internet-Draft

Obsoletes: [3540](#) (if approved)

Updates: [3168](#), [4341](#), [4342](#), [5622](#), [6679](#)
(if approved)

Intended status: Standards Track

Expires: May 1, 2017

D. Black

Dell EMC

October 28, 2016

Explicit Congestion Notification (ECN) Experimentation
draft-black-tsvwg-ecn-experimentation-02

Abstract

Multiple protocol experiments have been proposed that involve changes to Explicit Congestion Notification (ECN) as specified in [RFC 3168](#). This memo summarizes the proposed areas of experimentation to provide an overview to the Internet community and updates [RFC 3168](#), a Proposed Standard RFC, to allow the experiments to proceed without requiring a standards process exception for each Experimental RFC to update [RFC 3168](#). Each experiment is still required to be documented in an Experimental RFC. In addition, this memo makes related updates to the ECN specifications for RTP in [RFC 6679](#) and to the ECN specifications for DCCP in [RFC 4341](#), [RFC 4342](#) and [RFC 5622](#). This memo also records the conclusion of the ECN Nonce experiment in [RFC 3540](#), obsoletes [RFC 3540](#) and reclassifies it as Historic to enable new experimental use of the ECT(1) codepoint.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on May 1, 2017.

Internet-Draft

ECN Experimentation

October 2016

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
1.1.	Requirements Language	3
2.	Scope of ECN Experiments	3
3.	ECN Nonce and RFC 3540	4
4.	Updates to RFC 3168	5
4.1.	Alternative Backoff	5
4.2.	ECT Differences	5
4.3.	Generalized ECN	6
4.4.	Effective Congestion Control is Required	7
5.	ECN for RTP Updates to RFC 6679	7
6.	ECN for DCCP Updates to RFCs 4341, 4342 and 5622	8
7.	Acknowledgements	9
8.	IANA Considerations	9
9.	Security Considerations	9
10.	References	10
10.1.	Normative References	10
10.2.	Informative References	11
	Author's Address	12

[1.](#) Introduction

Multiple protocol experiments have been proposed that involve changes to Explicit Congestion Notification (ECN) as specified in [RFC 3168](#) [[RFC3168](#)]. This memo summarizes the proposed areas of experimentation to provide an overview to the Internet community and updates [RFC 3168](#) to allow the experiments to proceed without

requiring a standards process exception for each Experimental RFC to update [RFC 3168](#), a Proposed Standard RFC. This memo also makes related updates to the ECN specification for RTP in [RFC 6679](#) [[RFC6679](#)] for the same reason. Each experiment is still required to be documented in one or more separate RFCs, but use of Experimental

Black

Expires May 1, 2017

[Page 2]

Internet-Draft

ECN Experimentation

October 2016

RFCs for this purpose does not require a process exception to modify [RFC 3168](#) or [RFC 6679](#) when the modification falls within the bounds established by this memo.

One of these areas of experimentation involves use of the ECT(1) codepoint that was dedicated to the ECN Nonce experiment as described in [RFC 3540](#) [[RFC3540](#)]. This memo records the conclusion of the ECN Nonce experiment, obsoletes [RFC 3540](#) and reclassifies it as Historic.

1.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

2. Scope of ECN Experiments

Three areas of ECN experimentation are covered by this memo; the cited Internet-Drafts should be consulted for the goals and rationale of each proposed experiment:

Alternative Backoff: For congestion indicated by ECN, use a different IETF-approved TCP sender response (e.g., reduce the response so that the sender backs off by a smaller amount) by comparison to congestion indicated by loss, e.g., as proposed in [[I-D.khademi-tcpm-alternativebackoff-ecn](#)] and [[I-D.briscoe-tsvwg-ecn-l4s-id](#)] - the experiment in the latter draft couples the backoff change to ECT Differences functionality (next bullet). This is at variance with [RFC 3168](#)'s requirement that a TCP sender's congestion control response to ECN congestion indications be the same as to drops.

ECT Differences: Use ECT(1) to request ECN congestion marking behavior in the network that differs from ECT(0) counterbalanced by a changed response to each mark at the sender, e.g., as

proposed in [[I-D.briscoe-tsvwg-ecn-l4s-id](#)]. This is at variance with [RFC 3168](#)'s requirement that ECT(0)-marked traffic and ECT(1)-marked traffic not receive different treatment in the network.

Generalized ECN: Use ECN for TCP control packets (i.e., send control packets such as SYN with ECT marking) and for retransmitted packets, e.g., as proposed in [[I-D.bagnulo-tsvwg-generalized-ecn](#)]. This is at variance with [RFC 3168](#)'s prohibition of use of ECN for TCP control packets and retransmitted packets

The scope of this memo is limited to these three areas of experimentation. This memo neither prejudices the outcomes of the

Black

Expires May 1, 2017

[Page 3]

Internet-Draft

ECN Experimentation

October 2016

proposed experiments nor specifies the experiments in detail. The purpose of this memo is to remove constraints in standards track RFCs that serve to prohibit these areas of experimentation.

3. ECN Nonce and [RFC 3540](#)

As specified in [RFC 3168](#), ECN uses two ECN Capable Transport (ECT) codepoints to indicate that a packet supports ECN, ECT(0) and ECT(1), with the second codepoint used to support ECN nonce functionality to discourage receivers from exploiting ECN to improve their throughput at the expense of other network users, as specified in experimental [RFC 3540](#) [[RFC3540](#)].

While the ECN Nonce works as specified, and has been deployed in limited environments, widespread usage in the Internet has not materialized. A study of the ECN behaviour of the Alexa top 1M web servers using 2014 data [[Trammell15](#)] found that after ECN was negotiated, none of the 581,711 IPv4 servers tested were using both ECT codepoints, which would have been a possible sign of ECN Nonce usage. Of the 17,028 IPv6 servers tested, 4 set both ECT(0) and ECT(1) on data packets. This might have been evidence of use of the ECN Nonce by these 4 servers, but equally it might have been due to re-marking of the ECN field by an erroneous middlebox or router.

With the emergence of new experimental functionality that depends on use of the ECT(1) codepoint for other purposes, continuing to reserve that codepoint for the ECN Nonce experiment is no longer justified. In addition, alternative approaches to discouraging receivers from exploiting ECN have emerged, see [Appendix B.1](#) of

[[I-D.briscoe-tsvwg-ecn-l4s-id](#)]. Therefore, in support of ECN experimentation with the ECT(1) codepoint, this memo:

- o Declares that the ECN Nonce experiment [[RFC3540](#)] has concluded, and notes the absence of widespread deployment.
- o Obsoletes [RFC 3540](#) in order to facilitate experimental use of the ECT(1) codepoint.
- o Reclassifies [RFC 3540](#) as Historic to document the ECN Nonce experiment and discourage further implementation of the ECN Nonce.
- o Updates [RFC 3168](#) [[RFC3168](#)] to remove discussion of the ECN Nonce and use of ECT(1) for that Nonce. The specific text updates are omitted for brevity.

The following guidance on ECT codepoint usage in Section 5 of [RFC 3168](#) is relevant when the ECN Nonce is not implemented:

Black

Expires May 1, 2017

[Page 4]

Internet-Draft

ECN Experimentation

October 2016

Protocols and senders that only require a single ECT codepoint SHOULD use ECT(0).

OPEN ISSUE: Change the above requirement in [RFC 3168](#) from SHOULD to MUST towards reserving ECT(1) for experimentation?

[4.](#) Updates to [RFC 3168](#)

[RFC 3168](#) can only be updated directly by another standards track RFC unless a standards process exception is approved by the IESG. In support of the above areas of experimentation, and specifically to avoid multiple uncoordinated requests to the IESG for process exceptions, this memo updates [RFC 3168](#) [[RFC3168](#)] to allow changes in the following areas, provided that the changes are documented by an Experimental RFC. It is also possible to change [RFC 3168](#) via publication of another standards track RFC.

[4.1.](#) Alternative Backoff

[Section 5 of RFC 3168](#) specifies that:

"Upon the receipt by an ECN-Capable transport of a single CE

packet, the congestion control algorithms followed at the end-systems MUST be essentially the same as the congestion control response to a *single* dropped packet."

In support of Alternative Backoff experimentation, this memo updates [RFC 3168](#) to allow the congestion control response (including the TCP Sender's congestion control response) to a CE-marked packet to differ from the response to a dropped packet, provided that the changes from [RFC 3168](#) are documented in an Experimental RFC. The specific change to [RFC 3168](#) is to insert the words "unless otherwise specified by an Experimental RFC" at the end of the sentence quoted above.

[RFC 4774](#) [[RFC4774](#)] quotes the above text from [RFC 3168](#) as background, but does not impose requirements based on that text. Therefore no update to [RFC 4774](#) is required to enable this area of experimentation.

[4.2.](#) ECT Differences

[Section 5 of RFC 3168](#) specifies that:

"Routers treat the ECT(0) and ECT(1) codepoints as equivalent. Senders are free to use either the ECT(0) or the ECT(1) codepoint to indicate ECT, on a packet-by-packet basis."

Black

Expires May 1, 2017

[Page 5]

Internet-Draft

ECN Experimentation

October 2016

In support of ECT Differences experimentation, this memo updates [RFC 3168](#) to allow routers to treat the ECT(0) and ECT(1) codepoints differently, and allow requirements to be imposed on sender usage of ECT(0) and ECT(1), provided that the changes from [RFC 3168](#) are documented in an Experimental RFC. That change makes the second sentence quoted above misleading, so [RFC 3168](#) is also updated to remove that sentence. The specific change to [RFC 3168](#) is to insert the words "unless otherwise specified by an Experimental RFC" at the end of the first sentence, and remove the second sentence with this result:

"Routers treat the ECT(0) and ECT(1) codepoints as equivalent unless otherwise specified by an Experimental RFC."

As ECT(0) was the original codepoint used to signal ECN capability,

ECT Differences experiments SHOULD modify the network behavior for ECT(1) rather than ECT(0) if network behavior for only one ECT codepoint is modified.

In support of ECT Differences experimentation, this memo also updates [RFC 3168](#) to remove discussion of the ECN Nonce, as noted in [Section 3](#) above.

[4.3.](#) Generalized ECN

[RFC 3168](#) prohibits use of ECN for TCP control packets and retransmitted packets in a number of places:

- o "To ensure the reliable delivery of the congestion indication of the CE codepoint, an ECT codepoint MUST NOT be set in a packet unless the loss of that packet in the network would be detected by the end nodes and interpreted as an indication of congestion." ([Section 5.2](#))
- o "A host MUST NOT set ECT on SYN or SYN-ACK packets." ([Section 6.1.1](#))
- o "pure acknowledgement packets (e.g., packets that do not contain any accompanying data) MUST be sent with the not-ECT codepoint." ([Section 6.1.4](#))
- o "This document specifies ECN-capable TCP implementations MUST NOT set either ECT codepoint (ECT(0) or ECT(1)) in the IP header for retransmitted data packets, and that the TCP data receiver SHOULD ignore the ECN field on arriving data packets that are outside of the receiver's current window." ([Section 6.1.5](#))

- o "the TCP data sender MUST NOT set either an ECT codepoint or the CWR bit on window probe packets." ([Section 6.1.6](#))

In support of Generalized ECN experimentation, this memo updates [RFC 3168](#) to allow the use of ECT codepoints on SYN and SYN-ACK packets, pure acknowledgement packets, window probe packets and retransmissions of packets that were originally sent with an ECT codepoint, provided that the changes from [RFC 3168](#) are documented in

an Experimental RFC. The specific change to [RFC 3168](#) is to insert the words "unless otherwise specified by an Experimental RFC" at the end of each sentence quoted above.

[4.4.](#) Effective Congestion Control is Required

Congestion control remains an important aspect of the Internet architecture [[RFC2914](#)]. Any Experimental RFC that takes advantage of this memo's updates to [RFC 3168](#) or [RFC 6679](#) is required to discuss the congestion control implications of the experiment(s) in order to provide assurance that deployment of the experiment(s) does not pose a congestion-based threat to the operation of the Internet.

[5.](#) ECN for RTP Updates to [RFC 6679](#)

[RFC 6679](#) [[RFC6679](#)] specifies use of ECN for RTP traffic; it allows use of both the ECT(0) and ECT(1) codepoints, and provides the following guidance on use of these codepoints in [section 7.3.1](#) :

The sender SHOULD mark packets as ECT(0) unless the receiver expresses a preference for ECT(1) or for a random ECT value using the "ect" parameter in the "a=ecn-capable-rtp:" attribute.

The ECT Differences area of experimentation increases the potential consequences of using ECT(1) instead of ECT(0), and hence the above guidance is updated by adding the following two sentences:

Use of random ECT values is NOT RECOMMENDED, as that may expose RTP to differences in network treatment of traffic marked with ECT(1) and ECT(0) and differences in associated endpoint congestion responses, e.g., as proposed in [[I-D.briscoe-tsvwg-ecn-l4s-id](#)]. ECT(0) SHOULD be used unless there is a need for more than one ECT codepoint or unless otherwise specified in an Experimental RFC.

[Section 7.3.3 of RFC 6679](#) specifies RTP's response to receipt of CE marked packets as being identical to the response to dropped packets:

The reception of RTP packets with ECN-CE marks in the IP header is a notification that congestion is being experienced. The default

to provide the congestion control algorithm with a congestion notification that triggers the algorithm to react as if packet loss had occurred. There should be no difference in congestion response if ECN-CE marks or packet drops are detected.

In support of Alternative Backoff experimentation, this memo updates this text in a fashion similar to [RFC 3168](#) to allow the RTP congestion control response to a CE-marked packet to differ from the response to a dropped packet, provided that the changes from [RFC 6679](#) are documented in an Experimental RFC. The specific change to [RFC 6679](#) is to insert the words "Unless otherwise specified by an Experimental RFC" and reformat the last two sentences to be subject to that condition, i.e.:

The reception of RTP packets with ECN-CE marks in the IP header is a notification that congestion is being experienced. Unless otherwise specified by an Experimental RFC:

- * The default reaction on the reception of these ECN-CE-marked packets MUST be to provide the congestion control algorithm with a congestion notification that triggers the algorithm to react as if packet loss had occurred.
- * There should be no difference in congestion response if ECN-CE marks or packet drops are detected.

The second sentence of the immediately following paragraph in [RFC 6679](#) requires a related update:

Other reactions to ECN-CE may be specified in the future, following IETF Review. Detailed designs of such alternative reactions MUST be specified in a Standards Track RFC and be reviewed to ensure they are safe for deployment under any restrictions specified.

The update is to change "Standards Track RFC" to "Standards Track RFC or Experimental RFC" for consistency with the first update.

[6.](#) ECN for DCCP Updates to RFCs 4341, 4342 and 5622

The specifications of the three DCCP Congestion Control IDs (CCIDs) 2 [[RFC4341](#)], 3 [[RFC4342](#)] and 4 [[RFC5622](#)] contain broadly the same wording as follows:

each DCCP-Data and DCCP-DataAck packet is sent as ECN Capable with either the ECT(0) or the ECT(1) codepoint set.

This memo updates these sentences in each of the three RFCs as follows:

each DCCP-Data and DCCP-DataAck packet is sent as ECN Capable. Unless otherwise specified by an Experimental RFC, such DCCP senders SHOULD set the ECT(0) codepoint.

In support of ECT Differences experimentation (as noted in [Section 3](#)), this memo also updates all three of these RFCs to remove discussion of the ECN Nonce. The specific text updates are omitted for brevity.

[7.](#) Acknowledgements

The content of this draft, including the specific portions of [RFC 3168](#) that are updated draws heavily from [\[I-D.khademi-tsvwg-ecn-response\]](#), whose authors are gratefully acknowledged. The authors of the Internet Drafts describing the experiments have motivated the production of this memo - their interest in innovation is welcome and heartily acknowledged. Colin Perkins suggested updating [RFC 6679](#) on RTP and provided guidance on where to make the updates.

The draft has been improved as a result of comments from a number of reviewers, including Spencer Dawkins, Gorry Fairhurst, Ingemar Johansson, Naeem Khademi, Mirja Kuehlewind and Michael Welzl. Bob Briscoe's thorough review of an early version of this draft resulted in numerous improvements including addition of the updates to the DCCP RFCs.

[8.](#) IANA Considerations

This memo includes no request to IANA.

[9.](#) Security Considerations

As a process memo that makes no changes to existing protocols, there are no protocol security considerations.

However, effective congestion control is crucial to the continued operation of the Internet, and hence this memo places the responsibility for not breaking Internet congestion control on the experiments and the experimenters who propose them, as specified in [Section 4.4](#).

Security considerations for the proposed experiments are discussed in

the Internet-Drafts that propose them.

Black

Expires May 1, 2017

[Page 9]

Internet-Draft

ECN Experimentation

October 2016

See [Appendix B.1](#) of [[I-D.briscoe-tsvwg-ecn-l4s-id](#)] for discussion of alternatives to the ECN Nonce.

[10.](#) References

[10.1.](#) Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.
- [RFC2914] Floyd, S., "Congestion Control Principles", [BCP 41](#), [RFC 2914](#), DOI 10.17487/RFC2914, September 2000, <<http://www.rfc-editor.org/info/rfc2914>>.
- [RFC3168] Ramakrishnan, K., Floyd, S., and D. Black, "The Addition of Explicit Congestion Notification (ECN) to IP", [RFC 3168](#), DOI 10.17487/RFC3168, September 2001, <<http://www.rfc-editor.org/info/rfc3168>>.
- [RFC3540] Spring, N., Wetherall, D., and D. Ely, "Robust Explicit Congestion Notification (ECN) Signaling with Nonces", [RFC 3540](#), DOI 10.17487/RFC3540, June 2003, <<http://www.rfc-editor.org/info/rfc3540>>.
- [RFC4341] Floyd, S. and E. Kohler, "Profile for Datagram Congestion Control Protocol (DCCP) Congestion Control ID 2: TCP-like Congestion Control", [RFC 4341](#), DOI 10.17487/RFC4341, March 2006, <<http://www.rfc-editor.org/info/rfc4341>>.
- [RFC4342] Floyd, S., Kohler, E., and J. Padhye, "Profile for Datagram Congestion Control Protocol (DCCP) Congestion Control ID 3: TCP-Friendly Rate Control (TFRC)", [RFC 4342](#), DOI 10.17487/RFC4342, March 2006, <<http://www.rfc-editor.org/info/rfc4342>>.
- [RFC5622] Floyd, S. and E. Kohler, "Profile for Datagram Congestion Control Protocol (DCCP) Congestion ID 4: TCP-Friendly Rate

Control for Small Packets (TFRC-SP)", [RFC 5622](#), DOI 10.17487/RFC5622, August 2009, <<http://www.rfc-editor.org/info/rfc5622>>.

[RFC6679] Westerlund, M., Johansson, I., Perkins, C., O'Hanlon, P., and K. Carlberg, "Explicit Congestion Notification (ECN) for RTP over UDP", [RFC 6679](#), DOI 10.17487/RFC6679, August 2012, <<http://www.rfc-editor.org/info/rfc6679>>.

Black

Expires May 1, 2017

[Page 10]

Internet-Draft

ECN Experimentation

October 2016

[10.2.](#) Informative References

[I-D.bagnulo-tsvwg-generalized-ecn]

Bagnulo, M. and B. Briscoe, "Adding Explicit Congestion Notification (ECN) to TCP control packets", [draft-bagnulo-tsvwg-generalized-ecn-01](#) (work in progress), July 2016.

[I-D.briscoe-tsvwg-ecn-l4s-id]

Schepper, K., Briscoe, B., and I. Tsang, "Identifying Modified Explicit Congestion Notification (ECN) Semantics for Ultra-Low Queuing Delay", [draft-briscoe-tsvwg-ecn-l4s-id-01](#) (work in progress), March 2016.

[I-D.khademi-tcpm-alternativebackoff-ecn]

Khademi, N., Welzl, M., Armitage, G., and G. Fairhurst, "TCP Alternative Backoff with ECN (ABE)", [draft-khademi-tcpm-alternativebackoff-ecn-00](#) (work in progress), May 2016.

[I-D.khademi-tsvwg-ecn-response]

Khademi, N., Welzl, M., Armitage, G., and G. Fairhurst, "Updating the Explicit Congestion Notification (ECN) Specification to Allow IETF Experimentation", [draft-khademi-tsvwg-ecn-response-01](#) (work in progress), July 2016.

[RFC4774] Floyd, S., "Specifying Alternate Semantics for the Explicit Congestion Notification (ECN) Field", [BCP 124](#), [RFC 4774](#), DOI 10.17487/RFC4774, November 2006, <<http://www.rfc-editor.org/info/rfc4774>>.

[Trammell15]

Trammell, B., Kuehlewind, M., Boppart, D., Learmonth, I., Fairhurst, G., and R. Scheffenegger, "Enabling Internet-Wide Deployment of Explicit Congestion Notification".

In Proc Passive & Active Measurement (PAM'15) Conference (2015)

[Appendix A](#). Change History

[To be removed before RFC publication.]

Changes from [draft-black-tsvwg-ecn-experimentation-00](#) to -01

- o [Section 4.2](#) - also update [RFC 3168](#) to remove sentence indicating that senders are free to use both ECT codepoints. Add a SHOULD for ECT Differences experiments to use ECT(1).

Black

Expires May 1, 2017

[Page 11]

Internet-Draft

ECN Experimentation

October 2016

- o [Section 5](#) - only discourage use of random ECT values, but use NOT RECOMMENDED to do so. Consistent use of ECT(1) without using ECT(0) is ok. Mention possible changes in endpoint response.
- o Add more Acknowledgements and Change History
- o Additional editorial changes.

Changes from [draft-black-tsvwg-ecn-experimentation-01](#) to -02

- o Add DCCP RFC updates and one missing [RFC 3168](#) update (probe packets).
- o Discourage RTP usage of ECT(1).
- o Strengthen text on lack of ECN Nonce deployment.
- o Cross-reference the L4S draft appendix that discusses ECN Nonce alternatives.
- o Additional editorial changes.

Author's Address

David Black

Dell EMC
176 South Street
Hopkinton, MA 01748
USA

Email: david.black@dell.com

Black

Expires May 1, 2017

[Page 12]