

MPLS Working Group

M.

Bocci

Internet-Draft

Nokia

Intended status: Informational

S.

Bryant

Expires: October 13, 2022

University of Surrey

5GIC

April 11,

2022

Requirements for MPLS Network Action Indicators and MPLS Ancillary Data
[draft-bocci-mpls-miad-adi-requirements-04](#)

Abstract

This draft specifies requirements for indicators in the MPLS label stack to support ancillary data in the packet and high level requirements on that ancillary data. This work is the product of the

IETF MPLS Open Design Team. Requirements are derived from a number of new proposals for additions to the MPLS label stack to allow forwarding or other processing decisions to be made, either by a transit or terminating LSR (i.e. the LER), based on application data that may be in or below the bottom of the label stack.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months

and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 13, 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect

Bocci & Bryant
1]

Expires October 13, 2022

[Page

to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

[1](#). Introduction

[2](#)

[1.1](#). Terminology

[2](#)

[1.2](#). Background

[3](#)

[2](#). Requirements Language

[5](#)

[3](#). MPLS Network Action Indicator Requirements

[5](#)

[3.1](#). General Requirements

[5](#)

[3.2](#). Requirements on Network Action Indicators

[6](#)

[3.3](#). Requirements on Ancillary Data

[7](#)

[4](#). IANA Considerations

[8](#)

[5](#). Security Considerations

[8](#)

[6](#). Acknowledgements

[8](#)

[7](#). References

[9](#)

[7.1](#). Normative References

[9](#)

[7.2](#). Informative References

[9](#)

Authors' Addresses

[10](#)

[1](#). Introduction

There is significant interest in developing the MPLS data plane to address the requirements of new applications [[I-D.saad-mpls-miad-usecases](#)]. These applications typically require the inclusion of ancillary data in the MPLS packet. This data may be encoded either in the label stack or below the bottom of the label stack. This data is then either intercepted and processed, or some other forwarding decision is taken by routers processing the packet. The ancillary data is added by the ingress LSR, and is then processed using mechanisms implemented by intermediate and/or egress LSRs that comply with the MPLS base architecture and potentially its

extensions, including (but not limited to) [[RFC3031](#)], [[RFC3032](#)], [[RFC6790](#)].

This draft specifies requirements for indicators in the MPLS label stack to support these applications, as well as the encoding and use of the ancillary data.

1.1. Terminology

- o Ancillary Data (AD): Data relating to the MPLS packet that may be used to affect the forwarding or other processing of that packet, either at an Label Edge Router (LER) [[RFC4221](#)] or Label Switching Router (LSR). This data may be encoded within a network action

sub-stack (see below) (in-stack data), and/or after the bottom of the label stack (post-stack data).

- o Network Action: An operation to be performed on a packet. A network action may affect router state, packet forwarding, or it may affect the packet in some other way. A network action is said to be present if there is an indicator in the packet that invokes the action.
- o Network Action Indication (NAI): An indication in the packet that a certain network action is to be performed. There may be associated ancillary data in the packet.
- o Network Action Sub-Stack (NAS): A set of related, contiguous Label Stack Entries (LSEs). The first LSE contains the NAI. The TC and TTL values in the sub-stack may be redefined. The label field in the second and following LSE may be redefined. Solutions MUST NOT redefine the S bit. See [Section 3.1](#) through [Section 3.5](#).
- o In-Stack Data: Any data within the MPLS label stack including the outer LSE and the bottom of stack (the LSE with the S-bit set).
- o Post-Stack Data: Any data beyond the LSE with the S-Bit set, but before the first octet of the user payload. This document does not prescribe whether post-stack data precedes or follows any other protocol structure such as a control word or associated channel header (ACH).
- o Scope: The set of nodes that should perform a given action.

1.2. Background

The MPLS architecture is specified in [[RFC3031](#)] and provides a mechanism for forwarding packets through a network without requiring any analysis of the packet payload's network layer header by intermediate nodes (Label Switching Routers - LSRs). Formally, inspection may only occur at network ingress (the Label edge router

- LER) where the packet is assigned to a forwarding equivalence class (FEC).

MPLS uses switching based on a label pushed on the packet to achieve efficient forwarding and traffic engineering of flows associated with the FEC. While originally used for IP traffic, MPLS has been extended to support point-to-point, point-to-multipoint and multipoint-to-multipoint layer 2 and layer 3 services. An overview

Bocci & Bryant
3]

Expires October 13, 2022

[Page

of the development of MPLS is provided in [\[I-D.bryant-mpls-dev-primer\]](#).

A number of applications have emerged which require LSRs to make forwarding or other processing decisions based on inspection of the network layer header, or some other ancillary information in the protocol stack encapsulated deeper in the packet. An early example of this was generation of a hash of the payload header to be used for

load balancing over Equal Cost Multipath (ECMP) or Link Aggregation Group (LAG) next hops. This is based on an assumption that the network layer protocol is IP. MPLS was extended to avoid the need for LSRs to perform this operation if load balancing was needed based

on the payload and instead use only the MPLS label stack, using the Entropy Label / Entropy Label Indicator [\[RFC6790\]](#) which are inserted at the LER. Other applications where the intermediate LSRs may need to inspect and process a packet on an LSP include OAM, which can make

use of mechanisms such the Router Alert Label [\[RFC3032\]](#) or the Generic Associated Channel Label (GAL) [\[RFC5586\]](#) to indicate that an intercepted packet should be processed locally. See [\[I-D.bryant-mpls-dev-primer\]](#) for detailed list of such applications.

There have been a number of new proposals for how ancillary data is carried in MPLS and how its presence is indicated to the LSR or egress LER, for example In-situ OAM and Service Function Chaining (SFC). A summary of these proposals is contained in [\[I-D.bryant-mpls-dev-primer\]](#), an overview of use cases is provided in

[\[I-D.saad-mpls-miad-usecases\]](#). [\[I-D.song-mpls-extension-header\]](#) summarises some of the issues with existing solutions to address these new applications (note that this document draws on the requirements and issues without endorsing a specific solution from [\[I-D.song-mpls-extension-header\]](#)):

These solutions rely on either the built-in next-protocol indicator in the header or the knowledge of the format and size of the header to access the following packet data. The node is required to be able to parse the new header, which is unrealistic in an incremental deployment environment.

A piecemeal solution often assumes the new header is the only extra header and its location in the packet is fixed by default. It is impossible or difficult to support multiple new headers in one packet due to the conflicted assumption. An example of this is that the GAL/G-ACH mechanism assumes that if the GAL is present, only a single G-ACH header follows.

New applications therefore require the definition of extensions to the MPLS architecture and label stack operations that can be used

Bocci & Bryant
4]

Expires October 13, 2022

[Page

across these applications in order to minimise implementation complexity and promote interoperability and extensibility.

2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in

BCP

[14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

3. MPLS Network Action Indicator Requirements

This document specifies requirements of MPLS Network Action Indicators, and the associated Ancillary Data. The requirements are for the behavior of the protocol mechanisms and procedures that constitute building blocks out of which indicators for network actions and associated ancillary data are constructed.

It does not specify the detailed actions and processing that may be required by an application for any ancillary data by an LSR or LER. The requirements in this document do not describe what functions an implementation must support. The purpose of this document is to identify the toolkit and any new protocol work that is required. This new protocol work MUST be based on the existing MPLS architecture.

3.1. General Requirements

1. MPLS combines extensibility, flexibility and efficiency by using control plane context combined with a simple data plane mechanism to allow the network to make forwarding decisions about a packet.
Any solution MUST maintain these properties of MPLS.
2. Any solutions to these requirements MUST NOT restrict the generality of MPLS architecture [[RFC3031](#)], [[RFC3032](#)].
3. If extensions to the MPLS data plane are required, they MUST NOT be inconsistent with the MPLS architecture [[RFC3031](#)], [[RFC3032](#)].
4. Solutions meeting the requirements set out in this document MUST be able to coexist with and MUST NOT obsolete existing MPLS mechanisms.
5. The design of any mechanism SHOULD be such that an LSR is able to efficiently parse the label stack.
6. Mechanisms MUST NOT increase the size of the MPLS label stack more than is necessary.

Bocci & Bryant
5]

Expires October 13, 2022

[Page

7. The design of solutions MUST NOT expose confidential information [[RFC6973](#)] [[RFC3552](#)] to the LSRs.
8. Solution specifications MUST document any changes to the existing MPLS data plane security model that they introduce.

3.2. Requirements on Network Action Indicators

1. When an MPLS Network Action is required, an indicator is REQUIRED in the label stack.
2. An MPLS Network Action MUST specify whether ancillary data is required in the label stack and/or post-stack data.
3. Any solution MUST respect the principle that Special Purpose Labels are the mechanism of last resort and therefore must minimise the number of new SPLs that are allocated.
4. Insertion, parsing, processing and disposition of Network Action Indicators SHOULD make use of existing MPLS data plane operations.
5. An NAI MUST NOT be delivered to a node that is not capable of processing in the way in a way that is acceptable to the imposing LER.
6. NAI MUST NOT become top of stack at a node that does not understand how to perform a disposition operation on it. Disposition includes both processing and ignoring.
7. The NAI design MUST support scoping of network actions.
8. A given NAI specification MUST specify if the scope is end-to-end, hop-by-hop, or directed at one or more selected nodes.
9. If a design allows more than one scope, a mechanism MUST be provided to specify the precedence of the scopes.
10. A mechanism is REQUIRED to enable an LER inserting NAIs to determine if the far-end LER can accept and process a packet containing a given NAI.
11. NAIs SHOULD be supported for both P2P and P2MP paths, but any specific NAI may only be supported for one or the other.
12. Data plane mechanisms for NAIs MUST be consistent across different control plane protocol types.

13. A mechanism MUST be defined for control / management planes in use to determine the ability of downstream LSRs/LEs to accept/process a given NAI.
14. A mechanism is REQUIRED to enable an LSR to determine if an NAI is present in a packet.
15. NAIs can only be inserted at LEs, but MAY be processed at LSRs and LEs. If it is required to insert an NAI at a transit LSR on an LSP, then a new label stack MUST be pushed.
16. It SHOULD be possible to include indicators for multiple network actions in the same packet.
17. The solution MUST allow NAI-carrying and non-NAI-carrying packets to coexist on the same LSP.
18. The solution MUST support the processing of a subset of the NAIs on a packet.
19. Any specification of a solution that inserts or modifies the NAI MUST discuss the possible ECMP consequences.

3.3. Requirements on Ancillary Data

1. Solutions for in-stack ancillary data MUST be able to coexist with and MUST NOT obsolete existing MPLS mechanisms.
2. A common preamble for ancillary data MUST be defined so that a node receiving the ancillary data can determine whether to process, ignore, skip over or discard it according to network or local policies.
3. Any specification of a mechanism MUST describe whether it can coexist with existing post-stack data mechanisms e.g. control words and G-ACH, and if so how this coexistence operates.
4. A mechanism MUST be defined for an LE inserting ancillary data to determine that each node that needs to process the ancillary data can read the required distance into the packet at that node, for example [[RFC9088](#)].
5. Ancillary data MAY be associated with control or maintenance information for traffic carried by an LSP, and/or it MAY be associated with the user traffic itself.
6. For scoped ancillary data, a mechanism is REQUIRED to enable an LE inserting NAIs whose network actions make use of that

Bocci & Bryant
7]

Expires October 13, 2022

[Page

ancillary data, to determine if the NAI and ancillary data will be processed by LSRs within the scope along the path. Such a mechanism MAY need to determine if LSRs along the path can process a specific type of AD implied by the NAI at the depth in the stack that it will be presented to the LSR.

7. Network action specifications MUST specify if the ancillary data needs to be processed as a part of the immediate forwarding operation and whether packet mis-ordering is allowed to occur as a result of the time taken to process the ancillary data.
8. In order to prevent unnecessary scanning of the packet, care needs to be taken in the location of post stack ancillary data, for example it SHOULD be located as close to the bottom of the label stack as possible.
9. A solution MUST be provided to verify the authenticity of ancillary data processed to LSRs [[RFC3552](#)].
10. The design of the ancillary data MUST NOT expose confidential information [[RFC6973](#)] [[RFC3552](#)] to the LSRs.

4. IANA Considerations

This document makes no request of IANA.

Note to RFC Editor: this section may be removed on publication as an RFC.

5. Security Considerations

The mechanisms required by this document introduce new security considerations to MPLS. Individual solution specifications meeting these requirements MUST address any security considerations.

6. Acknowledgements

The authors gratefully acknowledge the contributions from Greg Mirsky, Yingzhen Qu, Haoyu Song, Tarek Saad, Loa Andersson, Tony Li, John Drake and Bruno Decraene.

The authors also gratefully acknowledge the input of the members of the MPLS Open Design Team.

Bocci & Bryant
8]

Expires October 13, 2022

[Page

7. References

7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

7.2. Informative References

- [I-D.bryant-mpls-dev-primer]
Bryant, S., "A Primer on the Development of MPLS", [draft-bryant-mpls-dev-primer-01](#) (work in progress), December 2021.
- [I-D.saad-mpls-miad-usecases]
Saad, T., Makhijani, K., Song, H., and G. Mirsky, "Use Cases for MPLS Function Indicators and Ancillary Data", [draft-saad-mpls-miad-usecases-01](#) (work in progress),
March 2022.
- [I-D.song-mpls-extension-header]
Song, H., Li, Z., Zhou, T., Andersson, L., and Z. Zhang, "MPLS Extension Header", [draft-song-mpls-extension-header-06](#) (work in progress), January 2022.
- [RFC3031] Rosen, E., Viswanathan, A., and R. Callon, "Multiprotocol Label Switching Architecture", [RFC 3031](#), DOI 10.17487/RFC3031, January 2001, <<https://www.rfc-editor.org/info/rfc3031>>.
- [RFC3032] Rosen, E., Tappan, D., Fedorkow, G., Rekhter, Y., Farinacci, D., Li, T., and A. Conta, "MPLS Label Stack Encoding", [RFC 3032](#), DOI 10.17487/RFC3032, January 2001, <<https://www.rfc-editor.org/info/rfc3032>>.
- [RFC3552] Rescorla, E. and B. Korver, "Guidelines for Writing RFC Text on Security Considerations", [BCP 72](#), [RFC 3552](#), DOI 10.17487/RFC3552, July 2003, <<https://www.rfc-editor.org/info/rfc3552>>.

- [RFC4221] Nadeau, T., Srinivasan, C., and A. Farrel, "Multiprotocol Label Switching (MPLS) Management Overview", [RFC 4221](#), DOI 10.17487/RFC4221, November 2005, <<https://www.rfc-editor.org/info/rfc4221>>.
- [RFC5586] Bocci, M., Ed., Vigoureux, M., Ed., and S. Bryant, Ed., "MPLS Generic Associated Channel", [RFC 5586](#), DOI 10.17487/RFC5586, June 2009, <<https://www.rfc-editor.org/info/rfc5586>>.
- [RFC6790] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", [RFC 6790](#), DOI 10.17487/RFC6790, November 2012, <<https://www.rfc-editor.org/info/rfc6790>>.
- [RFC6973] Cooper, A., Tschofenig, H., Aboba, B., Peterson, J., Morris, J., Hansen, M., and R. Smith, "Privacy Considerations for Internet Protocols", [RFC 6973](#), DOI 10.17487/RFC6973, July 2013, <<https://www.rfc-editor.org/info/rfc6973>>.
- [RFC9088] Xu, X., Kini, S., Psenak, P., Filsfils, C., Litkowski, S., and M. Bocci, "Signaling Entropy Label Capability and Entropy Readable Label Depth Using IS-IS", [RFC 9088](#), DOI 10.17487/RFC9088, August 2021, <<https://www.rfc-editor.org/info/rfc9088>>.

Authors' Addresses

Matthew Bocci
Nokia

Email: matthew.bocci@nokia.com

Stewart Bryant
University of Surrey 5GIC

Email: sb@stewartbryant.com

