

6man WG  
Internet-Draft  
Intended status: Standards Track  
Expires: 14 April 2022

X. Li  
C. Bao  
CERNET Center/Tsinghua University  
E. Ruan  
Fungible Inc.  
R. Bonica  
Juniper Networks  
11 October 2021

Compressed Routing Header (CRH) Helper Option  
draft-bonica-6man-crh-helper-opt-04

Abstract

This document defines the IPv6 Compressed Routing Header (CRH) Helper option. When a source node sends a packet with a CRH, it can use the CRH Helper option to provide additional information to downstream nodes.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 14 April 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

CRH Helper Option

October 2021

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Option Format . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Option Processing . . . . .	<a href="#">4</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">5</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">5</a>
<a href="#">7.</a>	Acknowledgements . . . . .	<a href="#">5</a>
<a href="#">8.</a>	Normative References . . . . .	<a href="#">5</a>
	Authors' Addresses . . . . .	<a href="#">6</a>

[1.](#) Introduction

IPv6 [[RFC8200](#)] source nodes use the Compressed Routing Header (CRH) [[I-D.bonica-6man-comp-rtg-hdr](#)] to steer packets along a delivery path to their destination. Two CRH versions have been defined. The CRH-16 encodes segment endpoints in 16 bits, while CRH-32, encodes segment endpoints in 32 bits.

Both CRH versions contain the following fields:

- \* Next Header - Identifies the header immediately following the CRH.
- \* Hdr Ext Len - Length of the CRH.
- \* Routing Type - Identifies the Routing header variant (i.e., CRH-16 or CRH-32).
- \* Segments Left - The number of segments still to be traversed before reaching the packet's ultimate destination.
- \* Segment Identifier (SID) List - Represents the delivery path as an ordered list of Segment Identifiers (SID). SIDs are listed in

reverse order, with SID[0] representing the final segment, SID[1] representing the penultimate segment, and so forth. SIDs are listed in reverse order so that Segments Left can be used as an index to the SID List. The SID indexed by Segments Left is called the current SID.

As per [[RFC8200](#)], when an IPv6 node receives a packet, it examines the packet's destination address. If the destination address represents an interface belonging to the node, the node processes the next header. If the next header is a CRH, it is processed as follows:

- \* If Segments Left equals 0, skip over the CRH and process the next header in the packet.
- \* Decrement Segments Left.
- \* Query a local data structure, called the CRH Forwarding Information Base (CRH-FIB), searching for an entry that is indexed by the current SID.
- \* If the above-mentioned query returns a CRH-FIB entry, update the packet's IPv6 Destination Address and forward the packet.

In a typical CRH deployment, every segment ingress node maintains a complete CRH-FIB and the above-mentioned query returns a CRH-FIB entry. However, in some CRH deployments, some segment ingress nodes maintain a complete CRH-FIB while others do not. For example, a node that does not participate in a control plane or communicate with a controller may not maintain a CRH-FIB.

This document defines the IPv6 CRH Helper option. When a source node sends a packet with a CRH, it can use the IPv6 CRH Helper option to provide CRH-FIB information to downstream nodes that do not maintain a complete CRH-FIB.

If a segment ingress node queries its CRH-FIB, searching for an entry that is indexed by the current SID, and that query returns nothing, the segment ingress node can obtain the required CRH-FIB information from the IPv6 CRH Helper option. If the segment ingress node cannot obtain the required CRH-FIB information from either source, it discards the packet and sends an ICMPv6 [[RFC4443](#)] Parameter Problem

message to the source node.

## 2. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## 3. Option Format

The CRH Helper option contains the following fields:

- \* Option Type - (8-bits) CRH Helper option. Value TBD by IANA. (Suggested value: 0x11). See Note below.
- \* Opt Data Len - (8-bits) Length of the option, in octets, excluding the Option Type and Option Length fields.
- \* Helper List - (Variable length) A list of Helpers.

Each Helper contains the following fields:

- \* Helper Length - (8-bits) Length of the Helper, in octets, excluding Helper Length. Value MUST be greater than 2 and less than 19.
- \* Low SID - (8-bits) Index to the CRH SID List. References the first member of the SID List to which this Helper applies.
- \* High SID - (8-bits) Index to the CRH SID List. References the last member of the SID List to which this Helper applies.
- \* Prefix field (variable length): An IPv6 Prefix.

NOTE : The highest-order two bits of the Option Type (i.e., the "act" bits) are 00. These bits specify the action taken by a destination node that does not recognize the option. The required action is to

skip over this option and continue processing the header.

The third highest-order bit of the Option Type (i.e., the "chg" bit) is 0. This indicates that Option Data cannot be modified along the path between the packet's source and its destination.

#### 4. Option Processing

When a segment endpoint node processes a CRH, it attempts to resolve the SID using information contained by its CRH-FIB. If it cannot resolve the SID using CRH-FIB, it attempts to resolve the SID using information received in an applicable Helper. If no Helper applies to the current SID, the processing node discards the packet and sends an ICMPv6 Parameter Problem message to the source node.

When the processing node uses a Helper to resolve a SID, it executes the following procedure:

- \* Set the IPv6 Destination Address to 0::

- \* Overwrite the low order bits of the IPv6 Destination Address with the current SID found in the CRH
- \* Overwrite the high order bits of the IPv6 Destination Address with the prefix found in the applicable Helper

If the prefix found in the applicable Helper is 16 bytes long, it overwrites the entire IPv6 Destination Address.

The CRH Helper option MAY occur in a Destination Options header that precedes a CRH. It SHOULD NOT occur in a Hop-by-hop options header or in a Destination Options header that precedes an upper-layer header.

When a segment ingress node resolves a SID using information obtained from the CRH helper option, it forwards the packet through the least-cost path to its new destination.

Information obtained from the CRH Helper option is transient. It is discarded as soon as the packet that carried it has been processed.

#### 5. Security Considerations

When a segment endpoint node processes a CRH, it attempts to resolve the SID using information contained by its CRH-FIB. If it can resolve the SID using CRH-FIB, it MUST ignore the CRH Helper option, even if it contains an applicable Helper.

## 6. IANA Considerations

IANA is requested to allocate a code point from the Destination Options and Hop-by-hop Options registry (<https://www.iana.org/assignments/ipv6-parameters/ipv6-parameters.xhtml#ipv6-parameters-2>). This option is called "CRH Helper Option". The "act" bits are 00 and the "chg" bit is 0. (Suggested value: 0x11).

## 7. Acknowledgements

Thanks to TBD for their careful review of this document.

## 8. Normative References

### [I-D.bonica-6man-comp-rtg-hdr]

Bonica, R., Kamite, Y., Alston, A., Henriques, D., and L. Jalil, "The IPv6 Compact Routing Header (CRH)", Work in Progress, Internet-Draft, [draft-bonica-6man-comp-rtg-hdr-26](https://www.ietf.org/archive/id/draft-bonica-6man-comp-rtg-hdr-26), 25 May 2021, <<https://www.ietf.org/archive/id/draft-bonica-6man-comp-rtg-hdr-26.txt>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC4443] Conta, A., Deering, S., and M. Gupta, Ed., "Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification", STD 89,

[RFC 4443](#), DOI 10.17487/RFC4443, March 2006,  
<<https://www.rfc-editor.org/info/rfc4443>>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

[RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, [RFC 8200](#), DOI 10.17487/RFC8200, July 2017, <<https://www.rfc-editor.org/info/rfc8200>>.

#### Authors' Addresses

Xing Li  
CERNET Center/Tsinghua University  
Room 225, Main Building, Tsinghua University  
Beijing  
100084  
People's Republic of China

Email: [xing@cernet.edu.cn](mailto:xing@cernet.edu.cn)

Congxiao Bao  
CERNET Center/Tsinghua University  
Room 225, Main Building, Tsinghua University  
Beijing  
100084  
People's Republic of China

Email: [congxiao@cernet.edu](mailto:congxiao@cernet.edu)

Li, et al.

Expires 14 April 2022

[Page 6]

---

Internet-Draft

CRH Helper Option

October 2021

Eddie Ruan  
Fungible Inc.  
3201 Scott Blvd  
Santa Clara, California 95054  
United States of America

Email: [eddie.ruan@fungible.com](mailto:eddie.ruan@fungible.com)

Ron Bonica  
Juniper Networks  
2251 Corporate Park Drive  
Herndon, Virginia 20171  
United States of America

Email: [rbonica@juniper.net](mailto:rbonica@juniper.net)