

CoRE Roadmap and Implementation Guide
draft-bormann-core-roadmap-03

Abstract

The CoRE set of protocols, in particular the CoAP protocol, is defined in [draft-ietf-core-coap](#) in conjunction with a number of specifications that are currently nearing completion. There are also several dozen more individual Internet-Drafts in various states of development, with various levels of WG review and interest.

Today, this is simply a bewildering array of documents. Beyond the main four documents, it is hard to find relevant information and assess the status of proposals. At the level of Internet-Drafts, the IETF has only adoption as a WG document to assign status - too crude an instrument to assess the level of development and standing for anyone who does not follow the daily proceedings of the WG.

With a more long-term perspective, as additional drafts mature and existing specifications enter various levels of spec maintenance, the entirety of these specifications may become harder to understand, pose specific implementation problems, or be simply inconsistent.

The present guide aims to provide a roadmap to these documents as well as provide specific advice how to use these specifications in combination. In certain cases, it may provide clarifications or even corrections to the specifications referenced.

This guide is intended as a continued work-in-progress, i.e. a long-lived Internet-Draft, to be updated whenever new information becomes available and new consensus on how to handle issues is formed. Similar to the ROHC implementation guide, [RFC 4815](#), it might be published as an RFC at some future time later in the acceptance curve of the specifications.

This document does not describe a new protocol or attempt to set a new standard of any kind - it mostly describes good practice in using the existing specifications, but it may also document emerging consensus where a correction needs to be made.

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 25, 2013.

Copyright Notice

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	4
1.1.	Terminology	4
2.	The Main Four	5
2.1.	The CoAP protocol	5
2.2.	Discovery	6
2.3.	Further reading	7
3.	Informational Drafts	8
3.1.	Implementation	8
3.2.	Multicast and Group Communication	8
3.3.	Security	9
3.4.	Intermediaries	9
3.5.	Congestion Control	10
4.	CoAP over X	11
5.	Optional components of CoRE	12
5.1.	CoAP-misc	12
5.2.	Generalizing Media Types	12
5.3.	Patience, Leisure, Pledge, or: Timing extensions	13
5.4.	Extending Observe	13
5.5.	Service discovery	13
5.6.	Server discovery, Naming, etc.	14
5.7.	More support for sleepy nodes	14
6.	Replaced drafts	17
7.	IANA Considerations	18
8.	Security Considerations	19
9.	Acknowledgements	20
10.	References	21
10.1.	Normative References	21
10.2.	Informative References	21
	Author's Address	27

1. Introduction

(To be written - for now please see the Abstract.)

1.1. Terminology

This document is a guide. However, it might evolve to make specific recommendations on how to use standards-track specifications. Therefore: The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#). They indicate requirement levels for compliant CoRE implementations [[RFC2119](#)]. Note that these keywords are not only used where a correction or clarification is intended; the latter are explicitly identified as such.

The term "byte" is used in its now customary sense as a synonym for "octet".

2. The Main Four

The main component of the CoRE architecture is the Constrained Application Protocol (CoAP). It aims to provide a RESTful transfer service, not unlike HTTP, but radically simplified for the use on constrained devices on constrained networks. REST is the architectural style that informed the design of HTTP [[REST](#)]. The terms "constrained device" and "constrained network" refer to limited-capability devices such as sensors operating on networks such as the IEEE 802.15.4 based 6LoWPAN [[RFC4919](#)]. [[I-D.ietf-lwig-guidance](#)] provides a more detailed discussion of what we mean by these terms.

2.1. The CoAP protocol

The CoAP protocol is defined in three specifications:

- o [[I-D.ietf-core-coap](#)]
- o [[I-D.ietf-core-block](#)]
- o [[I-D.ietf-core-observe](#)]

The first specification, [[I-D.ietf-core-coap](#)], provides the core transfer protocol, including the means to provide communication security using the DTLS protocol [[RFC6347](#)] (compare this to the way [[RFC2616](#)] and [[RFC2818](#)] define HTTP and HTTPS). The protocol is structured into a message layer, which provides duplicate detection and optional message reliability on top of UDP, and a request/response layer, which provides the usual REST operations GET, PUT, POST, and DELETE. A highly efficient protocol encoding carries the 4-byte base header, a sequence of `_Options_`, and the payload (body) of a message. The main extension points of CoAP are its Options, similar to the way new header fields are used to extend HTTP.

Since CoAP is a very simple protocol based on UDP, it is limited in its transfer size by the datagram sizes provided by UDP. As a further constraint, many constrained networks do not provide good reliability of delivery once their small frame sizes are exceeded and the adaptation layer is forced to fragment [[WEI](#)]. This may lead to a practical limitation to payload sizes as small as 64 bytes. [[I-D.ietf-core-block](#)] extends the base CoAP protocol with three options that enable `_blockwise_` transfer, i.e., splitting up a larger transfer into a sequence of smaller transactions, as well as the early determination of the overall size of the resource representation.

In HTTP, transactions are always client initiated, and it is the

responsibility of the client to perform GET operations again and again (polling) if it wants to stay up to date about the status of a resource. This "pull model" becomes expensive in an environment with limited power, limited network resources, and nodes that sleep most of the time. Some more or less savory workarounds have been developed for HTTP [[RFC6202](#)], but, as a new protocol, CoAP can do better. [[I-D.ietf-core-observe](#)] extends the base CoAP protocol with an option that a client can use to indicate its interest in further updates from a resource. If the server accepts this option, the client becomes an `_Observer_` of this resource and receives an asynchronous notification message each time it changes. Each such notification message is identical in structure to the response to the initial GET request.

While the "Block" and "Observe" specifications are optional additions to the CoAP protocol (just as the core specification already defines 14 options most of which will not need to be used in every message), they together form what is now generally considered to be the CoAP protocol. All three CoAP specifications are, at the time of this writing, in the process of being updated based on the comments to the first Working-Group Last-Call [[RFC2418](#)], a prerequisite to submitting them to the IESG for publication as a Standards-Track RFC. The specifications, together with link-format (below), have been widely implemented in highly interoperable implementations: an ETSI "plugtest" event in March 2012 was attended by 15 organizations with 20 implementations; in over 3000 tests performed only about 6 % failed.

[2.2.](#) Discovery

The fourth specification in the main set now nearing completion does not extend the CoAP protocol but addresses a different problem.

In the Web, a number of methods for discovery of resources are common. Initially, Web discovery was just performed by humans based on an entry resource to a server (e.g., `/index.html`). This resource then includes links that directly or indirectly allow a human to reach the other Web resources that make up the Web site.

Web discovery can be performed by machines if standardized interfaces and resource descriptions are available. Among the component mechanisms for Web discovery that are standardized in the IETF are the well-known resource path `"/.well-known/..."` [[RFC5785](#)] and the HTTP link header [[RFC5988](#)]. Several related techniques are in common use today.

Clearly, in the machine-to-machine environments that will be typical of CoAP applications, it is important to enable devices to discover

each other and their resources. Autonomous devices and embedded systems necessitate uniform, interoperable resource discovery.

A basic component for this is provided by a standardized description format for the resources a server provides, the `_link-format_`. Unless other methods of discovery are available, CoAP servers should provide such a description via the well-known URI `"/.well-known/core"`, available for access via a GET request on that URI. (More advanced resource discovery schemes might make the same description available by other means, e.g. by posting it to a resource directory.)

The description format has been adapted from the format used in the HTTP link header [[RFC5988](#)], which is simple and easy to parse. In contrast to the HTTP specification, link-format is specified as an Internet media type (what used to be called "MIME type") and intended to be carried around in the payload [[RFC6690](#)].

[RFC6690] is the first RFC of the CoRE working group.

[2.3.](#) Further reading

A recent article provides a more detailed overview over the CoRE documents nearing completion [[SB](#)].

While the specification documents themselves have to go into meticulous details on every aspect of their protocols, they are the ultimate reference source and are the recommended reading if this basic overview is not sufficient.

3. Informational Drafts

3.1. Implementation

In the IETF, a separate working group is working on informational documents concerning guidance in lightweight implementation of protocols, the LWIG working group. LWIG has several drafts pertinent here:

[I-D.ietf-lwig-guidance] is the main working document of the WG. It contains some discussion about CoAP implementation in its [section 3.4.2](#), including the efficient representation of managing duplicate detection state. [I-D.kovatsch-lwig-class1-coap] contains additional considerations that, over time, might move into [I-D.ietf-lwig-guidance].

[I-D.castellani-lwig-coap-separate-responses] contains some examples for message exchanges, focusing on elaborating exchanges involving separate responses.

Two drafts show how to build minimal implementations of security protocols relevant for CoAP: [I-D.tschofenig-lwig-tls-minimal] for TLS, which is relevant for CoAP's use of DTLS; and [I-D.kivinen-ipsecme-ikev2-minimal] for IKEv2, the protocol for setting up IPsec security associations. See also the discussion of [I-D.hartke-core-codtls] in [Section 3.3](#).

3.2. Multicast and Group Communication

As it is based on UDP, CoAP easily supports the use of IP multicast to confer messages. However, there are difficult issues around making the desirable multicast applications actually work well.

This led to an additional milestone on the CoRE charter:

Nov 2012: Using CoAP for group communications to IESG as Informational

The informational WG draft [I-D.ietf-core-groupcomm] discusses fundamentals and use cases for group communication with CoAP. In parts, it is still in an explorative mode and will require additional investigation before conclusive results become available.

[I-D.dijk-core-groupcomm-misc] gives some additional considerations, listing requirements, providing some taxonomy, proposing deployment guidelines, and discussing approaches that are not (yet?) in the focus of the WG. Its [section 5](#) can serve as an overview over the status of multicast in constrained node/networks.

3.3. Security

Several individual drafts analyze the issues around the security of constrained devices in constrained networks.

draft-garcia-core-security		2012-03-26
draft-sarikaya-core-sbootstrapping	-05	2012-07-10
draft-jennings-core-transitive-trust-enrollment	-01	2012-10-13

Figure 1

[I-D.garcia-core-security] in particular describes the "Thing Lifecycle" and discusses resulting architectural considerations. [I-D.jennings-core-transitive-trust-enrollment] demonstrates a specific approach to securing the Thing Lifecycle based on defined roles of security players, including a Manufacturer, an Introducer, and a Transfer Agent.

Further work around Thing Lifecycles is also expected to occur in the SOLACE initiative (Smart Object Lifecycle Architecture for Constrained Environments), with its early mailing list at solace@ietf.org -- developed after the model of the COMAN initiative (Management for Constrained Management Networks and Devices, coman@ietf.org, [I-D.ersue-constrained-mgmt]).

[I-D.hartke-core-codtls] looks specifically into the use of DTLS in constrained networks. It raises issues that pertain both to the LWIG and CoRE working groups of the IETF.

Other drafts in this space:

draft-wang-core-profile-secflag-options	-02	2012-10-12
---	-----	------------

Figure 2

3.4. Intermediaries

[I-D.castellani-core-http-mapping] discusses some ideas about what HTTP/CoAP intermediaries could do beyond the basic mapping defined in [I-D.ietf-core-coap]. In the IETF83 WG meeting, it was discussed to evolve this draft into one document describing best practices for mapping between HTTP and CoAP (beyond what is already described in [I-D.ietf-core-coap]), and one document that describes usages that serve as additional useful examples for more advanced forms of mapping, a first draft is available in [I-D.castellani-core-advanced-http-mapping].

3.5. Congestion Control

[I-D.ietf-core-coap] only defines a very basic congestion control scheme that is focused on being safe in a wide variety of applications. Additional documents will define more advanced congestion control schemes that can provide more optimized performance in exchange for more implementation complexity and/or a narrower field of application.

Several drafts are contributing to this active subject of discussion in the WG:

draft-bormann-core-congestion-control	-02 2012-08-01
draft-bormann-core-cocoa	-00 2012-08-13

Figure 3

[I-D.greevenbosch-core-minimum-request-interval] proposes adding an option that allows a server to indicate its desire for some pacing of the requests sent to it by one client; enabling a form of server load control.

4. CoAP over X

[I-D.becker-core-coap-sms-gprs] shows how to run CoAP over cellular SMS and in mixed SMS/GPRS environments. This draft optionally makes use of an SMS-oriented encoding for CoAP that is described in [\[I-D.bormann-coap-misc\]](#).

[I-D.li-core-coap-payload-length-option] defines a way to indicate the length of the payload in case the underlying transport does not provide a suitable definite length indication.

5. Optional components of CoRE

Additional sub-protocols are being discussed in the IETF that may become optional protocols in CoREs.

The present document will track these sub-protocols and be amended once the sub-protocols reach formal status in the IETF.

Since the WG is cautious in adopting additional work while the main specifications near completion, none of the additional protocols proposed have become WG documents yet.

5.1. CoAP-misc

One draft is a little different from the other drafts in this category: [[I-D.bormann-coap-misc](#)] is a running document capturing CoAP extensions that are in various states of being cooked.

Some of these extensions may finally be adopted for the WG documents and then vanish from CoAP-misc. For other extensions, we may decide that they are not very good ideas. Instead of deleting them from CoAP-misc, they are moved to an appendix. This documents the approach, the best implementation of that approach that was reached, and the reasons why it was not adopted. This documentation should spare the WG and its contributors from the continuous reinvention of bad ideas.

As of the time of writing, the main body of CoAP-misc is almost empty, as most urgent developments have found their way into the WG documents, and many other ideas wait in the "nursery" section of the document.

5.2. Generalizing Media Types

CoAP defines a registry for combinations of an Internet Media Type ("MIME type") and a Content Encoding (e.g. some form of compression), enabling its compact encoding of this information in one or two bytes. Each entry in the registry defines a single, fixed set of media type parameters (as in ";charset=utf-8"), if any. This does not work well with media types that rely on more complex combinations of parameter settings. [[I-D.doi-core-parameter-option](#)] proposes to add an option to carry parameters for media types.

[[I-D.fossati-core-multipart-ct](#)] defines a new media type that can carry multiple embedded representations employing different media types using a binary type-length-value format.

5.3. Patience, Leisure, Pledge, or: Timing extensions

Several proposals intend to extend the amount of information available during an exchange about the timing requirements of the participants.

| [draft-li-core-coap-patience-option](#) | -01 | 2012-10-22 |

Figure 4

Another discussion is in [Appendix B.4](#) of [\[I-D.bormann-coap-misc\]](#).

The question of whether some of this functionality should be introduced into the main WG documents now is currently also the subject of an active issue tracker ticket [\[CoRE204\]](#).

5.4. Extending Observe

5.5. Service discovery

Basic service discovery is defined in [\[RFC6690\]](#). A JSON representation of the same information is defined in [\[I-D.bormann-core-links-json\]](#). The intention is to make this information available in an equivalent format that is more accessible to classic Web servers, both as a file format (Internet media type) and as a format that can be used in e.g. a JavaScript API.

[\[I-D.arkko-core-dev-urn\]](#) defines a new Uniform Resource Name (URN) namespace that can be used to provide hardware device identifiers in resource descriptions.

[\[I-D.shelby-core-interfaces\]](#) provides additional semantics that can be used to make resource descriptions more directly machine-interpretable. This ties in to a more general discussion about CoRE profiles that has only just begun.

[\[I-D.greevenbosch-core-profile-description\]](#) ties into this and defines a basic JSON format for indicating what CoAP Options and what Content-Formats (still called media-types there) are available for a resource.

[\[I-D.fossati-core-fp-link-format-attribute\]](#) defines a link-format attribute that indicates a certain resource is best reached via a specific proxy.

Other drafts in this space:

draft-wang-core-profile-secflag-options	-01 2012-07-16
---	------------------

Figure 5

5.6. Server discovery, Naming, etc.

On the boundary between service and server discovery, resource directory servers provide a way to collect resource descriptions from multiple servers into one accessible location.

[I-D.bormann-core-simple-server-discovery] provided a basic way to discover such servers in a constrained node/network without necessarily having to resort to multicast. It has been merged into [I-D.shelby-core-resource-directory], which defines protocol elements that can be used for setting up such a resource directory.

Additional drafts include:

draft-he-core-energy-aware-pd	-01 2012-07-16
draft-cao-core-pd	-02 2012-07-16

Figure 6

An attempt to merge mDNS/DNS-SD-based discovery (colloquially known as zeroconf or Bonjour), including recent approaches to extend these for constrained networks, into the picture is documented in [I-D.vanderstok-core-dna].

5.7. More support for sleepy nodes

The basic communication model of CoAP was imported from the Web. This applies well to some communication requirements in constrained node/networks, but leaves some other requirements open.

The assumption underlying the current set of WG documents is that the communication layers below the application provide support functions for sleeping nodes. Adding support at the application layer might be able to further reduce the power requirements of "sleepy nodes" that can sleep most of the time.

[I-D.rahman-core-sleepy-problem-statement] summarizes the overall problem statement for sleepy nodes without getting into any specific solution.

A number of drafts aim to extend the CoAP communication model towards more support for sleepy nodes.

The base CoAP spec [I-D.ietf-core-coap] already provides some

rudimentary support of sleepy nodes by supporting caching in intermediaries: resources from a sleepy node may be available from a caching proxy (if previously retrieved) even though the node is asleep. [[I-D.ietf-core-observe](#)] enhances this support by enabling sleepy nodes to update caching intermediaries on their own schedule.

A number of drafts more extensively extend the concept of an intermediary by introducing an additional kind of server that is hosting the resources of the sleepy node:

The approach of [[I-D.vial-core-mirror-server](#)] is to store the actual resource representations in a special type of Resource Directory called the Mirror Server. Communicating devices can then fetch the resource from the Mirror Server regardless of the state of the sleepy server. ([[I-D.vial-core-mirror-proxy](#)] simply appears to be a previous version of this draft.)

Similar to the above, the approach of [[I-D.fossati-core-publish-option](#)] is to temporarily delegate authority of its resources (when it is sleeping) to a proxy server that is always on.

Also, the approach of [[I-D.giacomin-core-sleepy-option](#)] is to define a proxy that acts as a store-and-forward agent for a sleepy node.

Other drafts introduce a variety of signaling based approaches to facilitate communicating with sleepy nodes: The approach of [[I-D.castellani-core-alive](#)] is to define a new CoAP message type (called "Alive") which the sleepy node multicasts to all interested devices when it wakes up. The approach of [[I-D.rahman-core-sleepy](#)] is to introduce storing of sleep characteristics in the Resource Directory. Communicating devices can then query the RD to learn the sleep status of the sleepy node before attempting communications.

Finally, some drafts build on the concept of the Observe mechanism to help keep track of the sleepy node information. The approach of [[I-D.fossati-core-monitor-option](#)] is to extend the Observe pattern to handle the scenario when both server and clients are sleepy nodes. Note that some of the other drafts (e.g., [[I-D.vial-core-mirror-server](#)], [[I-D.rahman-core-sleepy](#)]) include using/extending the Observe mechanism as part of their overall approach.

Support for sleepy nodes is currently a very active subject of discussion in the WG; it is clear that there is a high level of interest in the WG in addressing application-level support for sleepy nodes in future specifications.

[I-D.arkko-core-cellular] provides a well-founded discussion of methods for power conservation in CoAP nodes connected via cellular networks.

6. Replaced drafts

Internet-Drafts often get replaced by merged drafts or get promoted to WG drafts. As the relationships between drafts are not always accurately captured by the secretariat tools, this table provides a mapping from current drafts to any previous drafts they are replacing:

current draft	replaced draft
[I-D.ietf-core-coap]	draft-shelby-core-coap
[I-D.ietf-core-block]	draft-bormann-core-coap-block
	draft-li-core-coap-size-option
[I-D.ietf-core-observe]	draft-hartke-coap-observe
[RFC6690]	draft-shelby-core-link-format
[I-D.ietf-core-groupcomm]	draft-rahman-core-groupcomm
[I-D.becker-core-coap-sms-gprs]	draft-li-core-coap-over-sms
[I-D.vanderstok-core-dna]	draft-vanderstok-core-bc
[I-D.shelby-core-resource-directory]	draft-bormann-core-simple-server-discovery
[I-D.greevenbosch-core-minimum-request-interval]	draft-greevenbosch-core-block-minimum-time

Note that [draft-scim-core-schema](#) is just named against the naming conventions and actually unrelated to the CoRE working group.

7. IANA Considerations

This document has no actions for IANA.

8. Security Considerations

(None so far; this section will certainly grow as additional security considerations beyond those listed in the base specifications become known.)

9. Acknowledgements

(The concept for this document is borrowed from [[RFC4815](#)], which was invented by Lars-Erik Jonsson. Thanks!)

Akbar Rahman contributed text to this roadmap.

10. References

10.1. Normative References

- [I-D.ietf-core-block]
Bormann, C. and Z. Shelby, "Blockwise transfers in CoAP",
[draft-ietf-core-block-10](#) (work in progress), October 2012.
- [I-D.ietf-core-coap]
Shelby, Z., Hartke, K., Bormann, C., and B. Frank,
"Constrained Application Protocol (CoAP)",
[draft-ietf-core-coap-12](#) (work in progress), October 2012.
- [I-D.ietf-core-observe]
Hartke, K., "Observing Resources in CoAP",
[draft-ietf-core-observe-06](#) (work in progress),
September 2012.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC5785] Nottingham, M. and E. Hammer-Lahav, "Defining Well-Known
Uniform Resource Identifiers (URIs)", [RFC 5785](#),
April 2010.
- [RFC6347] Rescorla, E. and N. Modadugu, "Datagram Transport Layer
Security Version 1.2", [RFC 6347](#), January 2012.
- [RFC6690] Shelby, Z., "Constrained RESTful Environments (CoRE) Link
Format", [RFC 6690](#), August 2012.

10.2. Informative References

- [CoRE204] "Introduce a minimal version of Pledge", CoRE ticket #204,
<<http://trac.tools.ietf.org/wg/core/trac/ticket/204>>.
- [I-D.arkko-core-cellular]
Arkko, J., Eriksson, A., and A. Keranen, "Building Power-
Efficient CoAP Devices for Cellular Networks",
[draft-arkko-core-cellular-00](#) (work in progress),
July 2012.
- [I-D.arkko-core-dev-urn]
Arkko, J., Jennings, C., and Z. Shelby, "Uniform Resource
Names for Device Identifiers", [draft-arkko-core-dev-urn-03](#)
(work in progress), July 2012.
- [I-D.becker-core-coap-sms-gprs]

Becker, M., Li, K., Kuladinithi, K., and T. Poetsch,
"Transport of CoAP over SMS, USSD and GPRS",
[draft-becker-core-coap-sms-gprs-02](#) (work in progress),
July 2012.

[I-D.bormann-coap-misc]

Bormann, C. and K. Hartke, "Miscellaneous additions to
CoAP", [draft-bormann-coap-misc-21](#) (work in progress),
October 2012.

[I-D.bormann-core-links-json]

Bormann, C., "Representing CoRE Link Collections in JSON",
[draft-bormann-core-links-json-01](#) (work in progress),
July 2012.

[I-D.bormann-core-simple-server-discovery]

Bormann, C., "CoRE Simple Server Discovery",
[draft-bormann-core-simple-server-discovery-01](#) (work in
progress), March 2012.

[I-D.castellani-core-advanced-http-mapping]

Castellani, A., Loreto, S., Rahman, A., Fossati, T., and
E. Dijk, "Best Practices for HTTP-CoAP Mapping
Implementation",
[draft-castellani-core-advanced-http-mapping-00](#) (work in
progress), July 2012.

[I-D.castellani-core-alive]

Castellani, A. and S. Loreto, "CoAP Alive Message",
[draft-castellani-core-alive-00](#) (work in progress),
March 2012.

[I-D.castellani-core-http-mapping]

Castellani, A., Loreto, S., Rahman, A., Fossati, T., and
E. Dijk, "Best Practices for HTTP-CoAP Mapping
Implementation", [draft-castellani-core-http-mapping-05](#)
(work in progress), July 2012.

[I-D.castellani-lwig-coap-separate-responses]

Castellani, A., "Learning CoAP separate responses by
examples",
[draft-castellani-lwig-coap-separate-responses-00](#) (work in
progress), March 2012.

[I-D.dijk-core-groupcomm-misc]

Dijk, E. and A. Rahman, "Miscellaneous CoAP Group
Communication Topics", [draft-dijk-core-groupcomm-misc-02](#)
(work in progress), October 2012.

[I-D.doi-core-parameter-option]

Doi, Y. and K. Lynn, "CoAP Content-Type Parameter Option", [draft-doi-core-parameter-option-01](#) (work in progress), October 2012.

[I-D.ersue-constrained-mgmt]

Ersue, M., Romascanu, D., and J. Schoenwaelder, "Management of Networks with Constrained Devices: Use Cases and Requirements", [draft-ersue-constrained-mgmt-02](#) (work in progress), October 2012.

[I-D.fossati-core-fp-link-format-attribute]

Fossati, T. and S. Loreto, "Resource Discovery through Proxies", [draft-fossati-core-fp-link-format-attribute-00](#) (work in progress), July 2012.

[I-D.fossati-core-monitor-option]

Fossati, T., Giacomini, P., and S. Loreto, "Monitor Option for CoAP", [draft-fossati-core-monitor-option-00](#) (work in progress), July 2012.

[I-D.fossati-core-multipart-ct]

Fossati, T., "Multipart Content Format Encoding for CoAP", [draft-fossati-core-multipart-ct-01](#) (work in progress), October 2012.

[I-D.fossati-core-publish-option]

Fossati, T., Giacomini, P., and S. Loreto, "Publish Option for CoAP", [draft-fossati-core-publish-option-00](#) (work in progress), July 2012.

[I-D.garcia-core-security]

Garcia-Morchon, O., Keoh, S., Kumar, S., Hummen, R., and R. Struik, "Security Considerations in the IP-based Internet of Things", [draft-garcia-core-security-04](#) (work in progress), March 2012.

[I-D.giacomini-core-sleepy-option]

Fossati, T., Giacomini, P., Loreto, S., and M. Rossini, "Sleepy Option for CoAP", [draft-giacomini-core-sleepy-option-00](#) (work in progress), February 2012.

[I-D.greevenbosch-core-minimum-request-interval]

Greevenbosch, B., "CoAP Minimum Request Interval", [draft-greevenbosch-core-minimum-request-interval-00](#) (work in progress), September 2012.

[I-D.greevenbosch-core-profile-description]

Greevenbosch, B., Hoebeke, J., and I. Ishaq, "CoAP Profile Description Format",

[draft-greevenbosch-core-profile-description-01](#) (work in progress), October 2012.

[I-D.hartke-core-codtls]

Hartke, K. and O. Bergmann, "Datagram Transport Layer Security in Constrained Environments",

[draft-hartke-core-codtls-02](#) (work in progress), July 2012.

[I-D.ietf-core-groupcomm]

Rahman, A. and E. Dijk, "Group Communication for CoAP",

[draft-ietf-core-groupcomm-03](#) (work in progress), October 2012.

[I-D.ietf-lwig-guidance]

Bormann, C., "Guidance for Light-Weight Implementations of the Internet Protocol Suite", [draft-ietf-lwig-guidance-02](#) (work in progress), August 2012.

[I-D.jennings-core-transitive-trust-enrollment]

Jennings, C., "Transitive Trust Enrollment for Constrained Devices",

[draft-jennings-core-transitive-trust-enrollment-01](#) (work in progress), October 2012.

[I-D.kivinen-ipsecme-ikev2-minimal]

Kivinen, T., "Minimal IKEv2",

[draft-kivinen-ipsecme-ikev2-minimal-01](#) (work in progress), October 2012.

[I-D.kovatsch-lwig-class1-coap]

Kovatsch, M., "Implementing CoAP for Class 1 Devices",

[draft-kovatsch-lwig-class1-coap-00](#) (work in progress), October 2012.

[I-D.li-core-coap-payload-length-option]

Li, K. and X. Sun, "CoAP Payload-Length Option Extension",

[draft-li-core-coap-payload-length-option-00](#) (work in progress), May 2012.

[I-D.rahman-core-sleepy]

Rahman, A., "Enhanced Sleepy Node Support for CoAP",

[draft-rahman-core-sleepy-01](#) (work in progress), October 2012.

[I-D.rahman-core-sleepy-problem-statement]

Rahman, A., Fossati, T., Loreto, S., and M. Vial, "Sleepy Devices in CoAP - Problem Statement", [draft-rahman-core-sleepy-problem-statement-01](#) (work in progress), October 2012.

[I-D.shelby-core-interfaces]

Shelby, Z. and M. Vial, "CoRE Interfaces", [draft-shelby-core-interfaces-03](#) (work in progress), July 2012.

[I-D.shelby-core-resource-directory]

Shelby, Z., Krco, S., and C. Bormann, "CoRE Resource Directory", [draft-shelby-core-resource-directory-04](#) (work in progress), July 2012.

[I-D.tschofenig-lwig-tls-minimal]

Tschofenig, H. and J. Gilger, "A Minimal (Datagram) Transport Layer Security Implementation", [draft-tschofenig-lwig-tls-minimal-01](#) (work in progress), October 2012.

[I-D.vanderstok-core-dna]

Stok, P., Lynn, K., and A. Brandt, "CoRE Discovery, Naming, and Addressing", [draft-vanderstok-core-dna-02](#) (work in progress), July 2012.

[I-D.vial-core-mirror-proxy]

Vial, M., "CoRE Mirror Server", [draft-vial-core-mirror-proxy-01](#) (work in progress), July 2012.

[I-D.vial-core-mirror-server]

Vial, M., "CoRE Mirror Server", [draft-vial-core-mirror-server-00](#) (work in progress), October 2012.

[REST]

Fielding, R., "Architectural Styles and the Design of Network-based Software Architectures", Ph.D. Dissertation, University of California, Irvine, 2000, <http://www.ics.uci.edu/~fielding/pubs/dissertation/fielding_dissertation.pdf>.

[RFC2418]

Bradner, S., "IETF Working Group Guidelines and Procedures", [BCP 25](#), [RFC 2418](#), September 1998.

[RFC2616]

Fielding, R., Gettys, J., Mogul, J., Frystyk, H., Masinter, L., Leach, P., and T. Berners-Lee, "Hypertext Transfer Protocol -- HTTP/1.1", [RFC 2616](#), June 1999.

- [RFC2818] Rescorla, E., "HTTP Over TLS", [RFC 2818](#), May 2000.
- [RFC4815] Jonsson, L-E., Sandlund, K., Pelletier, G., and P. Kremer, "RObust Header Compression (ROHC): Corrections and Clarifications to [RFC 3095](#)", [RFC 4815](#), February 2007.
- [RFC4919] Kushalnagar, N., Montenegro, G., and C. Schumacher, "IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs): Overview, Assumptions, Problem Statement, and Goals", [RFC 4919](#), August 2007.
- [RFC5988] Nottingham, M., "Web Linking", [RFC 5988](#), October 2010.
- [RFC6202] Loreto, S., Saint-Andre, P., Salsano, S., and G. Wilkins, "Known Issues and Best Practices for the Use of Long Polling and Streaming in Bidirectional HTTP", [RFC 6202](#), April 2011.
- [SB] Bormann, C., Castellani, A., and Z. Shelby, "CoAP: An Application Protocol for Billions of Tiny Internet Nodes", DOI 10.1109/MIC.2012.29, 2012.
- [WEI] Shelby, Z. and C. Bormann, "6LoWPAN: the Wireless Embedded Internet", ISBN 9780470747995, 2009.

Author's Address

Carsten Bormann
Universitaet Bremen TZI
Postfach 330440
Bremen D-28359
Germany

Phone: +49-421-218-63921

Email: cabo@tzi.org