

Routing Area Working Group  
Internet-Draft  
Intended status: Informational  
Expires: January 4, 2016

C. Bowers  
Juniper Networks  
J. Farkas  
Ericsson  
July 3, 2015

Applicability of Maximally Redundant Trees to IEEE 802.1Qca Path Control  
and Reservation  
[draft-bowers-rtgwg-mrt-applicability-to-8021qca-01](#)

Abstract

IEEE 802.1Qca Path Control and Reservation (PCR) [[IEEE8021Qca](#)] uses the algorithm specified in [[I-D.ietf-rtgwg-mrt-frr-algorithm](#)] to compute Maximally Redundant Trees (MRTs) to be used for the protection of data traffic in bridged networks. This document discusses the applicability of the MRT algorithm to 802.1Qca.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 4, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">2.</a>	<a href="#">How 802.1Qca uses the MRT algorithm</a>	<a href="#">3</a>
<a href="#">2.1.</a>	<a href="#">MRT Explicit Trees in 802.1Qca</a>	<a href="#">3</a>
<a href="#">2.2.</a>	<a href="#">'MRT with GADAG' Explicit Trees in 802.1Qca</a>	<a href="#">3</a>
<a href="#">2.3.</a>	<a href="#">MRT Explicit Trees as Strict Trees</a>	<a href="#">4</a>
<a href="#">3.</a>	<a href="#">Other considerations</a>	<a href="#">4</a>
<a href="#">3.1.</a>	<a href="#">Unequal link metrics</a>	<a href="#">4</a>
<a href="#">3.2.</a>	<a href="#">Computation of MRT-Blue and MRT-Red next-hops from the point of view of other nodes</a>	<a href="#">5</a>
<a href="#">3.3.</a>	<a href="#">Recalculation of MRTs</a>	<a href="#">5</a>
<a href="#">4.</a>	<a href="#">IANA Considerations</a>	<a href="#">6</a>
<a href="#">5.</a>	<a href="#">Security Considerations</a>	<a href="#">6</a>
<a href="#">6.</a>	<a href="#">Acknowledgements</a>	<a href="#">6</a>
<a href="#">7.</a>	<a href="#">Informative References</a>	<a href="#">6</a>
	<a href="#">Authors' Addresses</a>	<a href="#">7</a>

## [1.](#) Introduction

IEEE 802.1Qaq Shortest Path Bridging (SPB) [[IEEE8021aq](#)] is an amendment to IEEE Std 802.1Q that allows bridged frames to travel on the shortest path between their source and destination(s), as opposed to traveling along paths determined by shared spanning trees. [[IEEE8021aq](#)] and [[RFC6329](#)] specify extensions to IS-IS that allow bridges to share the topology information needed to construct shortest path trees. These extensions are referred to here as ISIS-SPB. [[IEEE8021aq](#)] has been already incorporated in [[IEEE8021Q](#)].

[[IEEE8021Qca](#)] is an amendment to [[IEEE8021Q](#)] that specifies explicit path control, bandwidth assignment, and protection mechanisms for data flows for bridged networks. [[IEEE8021Qca](#)] is an extension to IS-IS that builds upon the ISIS-SPB extensions and extends them further as described in [[I-D.ietf-isis-pcr](#)]. These extensions (referred to here as ISIS-PCR) allow bridges to share the information needed to construct explicit trees.

[[IEEE8021Qca](#)] specifies five different methods for the construction of explicit trees as well as how to share the information needed to construct these trees. These five different methods of explicit trees are referred to as Strict Tree, Loose Tree, Loose Tree Set, MRT, and MRT with GADAG. This document is concerned with the MRT and 'MRT with GAGAG' explicit tree methods (algorithms). Both methods produce Maximally Redundant Trees (MRTs) [[I-D.ietf-rtgwg-mrt-frr-architecture](#)].



This document is intended to explain the relationship between [IEEE8021Qca] and [I-D.ietf-rtgwg-mrt-frr-algorithm]. The text should not be interpreted as normative with respect to either.

## **2. How 802.1Qca uses the MRT algorithm**

The algorithm for computing Maximally Redundant Trees in [I-D.ietf-rtgwg-mrt-frr-algorithm] has been specified with a focus on supporting fast-reroute for the protection of unicast IP and LDP traffic, as described in [I-D.ietf-rtgwg-mrt-frr-architecture]. The computation described in [I-D.ietf-rtgwg-mrt-frr-algorithm] starts with the topology of an IGP area, prunes it to form an MRT Island topology, constructs a GADAG, and then uses that GADAG to construct a complete set of destination-based MRT-Blue and MRT-Red trees rooted at each node in the MRT Island, where each tree spans all nodes in the MRT Island. [IEEE8021Qca] supports this mode of operation, but it also supports other modes of operation as described below.

### **2.1. MRT Explicit Trees in 802.1Qca**

In [IEEE8021Qca], the flooding of an SPB Instance sub-TLV ([RFC6329]) with the MRT ECT Algorithm value in the absence of a Topology sub-TLV ([I-D.ietf-isis-pcr]) results in the creation of an MRT-Blue and an MRT-Red tree rooted at each node in the domain, and each tree spans all nodes in the domain. This is equivalent to the behavior described in [I-D.ietf-rtgwg-mrt-frr-algorithm].

In addition, [IEEE8021Qca] allows one to affect both the number and structure of the MRT-Blue and Red trees by including the Topology sub-TLV in the MT-Capability TLV (type 144 [RFC6329]). In the context of the MRT ECT Algorithm, Hop sub-TLVs in the Topology sub-TLV specify nodes with flags that can indicate Root, Exclude, or Edge Bridge. In the context of the MRT algorithm, all nodes with the Exclude flag set are excluded from the MRT Island. The GADAG is then computed for the MRT Island. For each node with the Root flag set, an MRT-Blue and an MRT-Red tree rooted at that node is constructed.

Note that the Edge Bridge flag does not affect the construction of the MRTs. It is used to determine which filtering database (FDB) entries to install once the trees have been determined.

### **2.2. 'MRT with GADAG' Explicit Trees in 802.1Qca**

In the previous section, each node will compute the same GADAG based on the same topology information using the algorithm steps in sections 5.4 and 5.5 of [I-D.ietf-rtgwg-mrt-frr-algorithm]. Each node then applies the algorithm steps in [section 5.6.5](#) of



[I-D.ietf-rtgwg-mrt-frr-algorithm] to that GADAG, in order to compute the MRT-Blue and MRT-Red next-hops for the trees of interest.

[IEEE8021Qca] can operate in a mode where each node is supplied with a common GADAG (communicated via ISIS-PCR), from which each node then determines the MRT-Blue and MRT-Red next-hops for the trees of interest. That is, this mode of operation bypasses the algorithm steps in [section 5.4](#) and 5.5 of [I-D.ietf-rtgwg-mrt-frr-algorithm] and only applies the algorithm steps in [section 5.6.5](#) to the GADAG communicated directly via ISIS-PCR.

This behavior is controlled in [IEEE8021Qca] by flooding an SPB Instance sub-TLV with the 'MRT with GADAG' ECT Algorithm value as well as a Topology sub-TLV. Hop sub-TLVs in this Topology sub-TLV are used to describe the common GADAG using an ear decomposition. The first Hop sub-TLV is the GADAG root followed by a sequence of Hop sub-TLVs describing an ordered ear that terminates on the GADAG root. Subsequent ears are described as sequences of Hop sub-TLVs. Setting the Root flag for a given Hop sub-TLV indicates that MRT-Blue and Red trees rooted at that node should be constructed.

### **2.3. MRT Explicit Trees as Strict Trees**

A Path Computation Element can also implement each computation step of [I-D.ietf-rtgwg-mrt-frr-algorithm] and compute the MRTs. The MRTs can be then specified by Topology sub-TLVs, one for each. The SPB Instance sub-TLV then conveys the ST ECT Algorithm value.

## **3. Other considerations**

### **3.1. Unequal link metrics**

[IEEE8021aq] specifies that if two SPB Link Metrics are different at each end of a link, the maximum of the two values is used in SPB calculations. In order to provide symmetry and maintain consistency with [IEEE8021aq], [IEEE8021Qca] places the same requirement on the Link Metrics for the topology graph that is used in the MRT algorithm. In order to accomplish this, [IEEE8021Qca] makes the same modification to link metrics before applying the MRT algorithm. This change of metric values can affect the ordering of interfaces on a given node through the Interface\_Compare function in section 5 of [I-D.ietf-rtgwg-mrt-frr-algorithm], which in turn can affect the GADAG computed. The change of metric values can also affect the results of the SPF\_No\_Traverse\_Root function used in determining MRT next-hops, since the SPF traversal depends on metric values.

This modification of link metrics applies ONLY to [IEEE8021Qca]. When the MRT lowpoint inheritance algorithm in



[[I-D.ietf-rtgwg-mrt-frr-algorithm](#)] is applied to IP/LDP FRR, the topology graph with the link metrics advertised by the IGP are used without modification by the MRT algorithm.

### **3.2. Computation of MRT-Blue and MRT-Red next-hops from the point of view of other nodes**

In the algorithm described in [[I-D.ietf-rtgwg-mrt-frr-algorithm](#)] a given node computes and installs its own MRT-Blue and MRT-Red next-hops for all destinations. This computation is all that is required for the IP/LDP FRR application to function properly. An individual node does not need to compute the MRT-Blue and MRT-Red next-hops used by other nodes. Instead the complete MRT tree structure is created in the network as the result of each node computing and installing the appropriate MRT next-hops. This is analogous to the way that shortest path trees are instantiated in shortest path routing, with each node needing to compute and install only its own shortest path next-hops.

In some scenarios, a bridge using [[IEEE8021Qca](#)] may need to know more than just its own MRT-Blue and MRT-Red next-hops. This can be accomplished by having a bridge perform the MRT next-hop computation specified in section 5.6.5 of [[I-D.ietf-rtgwg-mrt-frr-algorithm](#)] from the point of view of one or more other bridges. The result of computing an MRT next-hop from the point of view of another bridge is the normative result. An implementation may use another method to compute MRT next-hops from the point of view of remote bridges as long as it produces the same result.

This does not modify the MRT algorithm with respect to its use for the IP/LDP FRR application as described in [[I-D.ietf-rtgwg-mrt-frr-architecture](#)].

### **3.3. Recalculation of MRTs**

MRTs can be used for the protection of SPTs in a bridged network similarly to IP/LDP FRR application of MRTs. A pair of MRT-Blue and MRT-Red then protect the SPT rooted at the MRT Root. The MRTs are only used for protection, i.e. MRTs do not carry traffic during normal operation, similarly to IP/LDP FRR operations. The Point of Local Repair (PLR) is responsible for redirecting traffic from SPTs to MRTs upon detection of a failure event.

In 802.1Qca, recalculation of MRTs after a topology change follows the general method specified in Section 12.2 of [[I-D.ietf-rtgwg-mrt-frr-architecture](#)], with an additional requirement. Immediately after a failure, the PLR or PLRs redirect some traffic onto MRTs. In the meantime, all nodes receive





notification of the failure, recompute SPTs, and install them in their FIBs. The PLRs take the traffic off of the MRTs, and put the traffic on the new SPTs. Based on [\[I-D.ietf-rtgwg-mrt-frr-architecture\]](#), at this point it is safe to recompute and install the new MRTs corresponding to the new topology.

802.1Qca places an additional requirement on when it is safe to install the new MRTs. The new MRTs should not be recomputed and installed if there is any reason to suspect that the nodes of the domain do not share a common view on the network topology. This is in order to prevent loops in the MRT paths that may be used by PLRs at the next failure event. The loop prevention method to be used for MRTs in 802.1Qca is the Agreement Protocol, which is specified in [\[IEEE8021aq\]](#) and also described in [\[AP\]](#).

Note that while 802.1Qca requires that the Agreement Protocol be used to avoid loops on MRTs, it does not mandate the use of the Agreement Protocol for the shortest path trees, where other loop mitigation techniques can be used.

#### [4.](#)    IANA Considerations

This document introduces no new IANA Considerations.

#### [5.](#)    Security Considerations

The ISIS-PCR extensions for the use of the MRT algorithm are not believed to introduce new security concerns.

#### [6.](#)    Acknowledgements

The authors would like to thank Alvaro Retana for his suggestions and review.

#### [7.](#)    Informative References

[AP]        Seaman, M., "Agreement Protocol", September 7, 2010, <<http://www.ieee802.org/1/files/public/docs2010/aq-seaman-agreement-protocol-0910-v2.pdf>>.

[I-D.ietf-isis-pcr]        Farkas, J., Bragg, N., Unbehagen, P., Parsons, G., Ashwood-Smith, P., and C. Bowers, "IS-IS Path Computation and Reservation", [draft-ietf-isis-pcr-00](#) (work in progress), April 2015.



[I-D.ietf-rtgwg-mrt-frr-algorithm]

Envedi, G., Csaszar, A., Atlas, A., Bowers, C., and A. Gopalan, "Algorithms for computing Maximally Redundant Trees for IP/LDP Fast- Reroute", [draft-ietf-rtgwg-mrt-frr-algorithm-02](#) (work in progress), January 2015.

[I-D.ietf-rtgwg-mrt-frr-architecture]

Atlas, A., Kebler, R., Bowers, C., Envedi, G., Csaszar, A., Tantsura, J., and R. White, "An Architecture for IP/LDP Fast-Reroute Using Maximally Redundant Trees", [draft-ietf-rtgwg-mrt-frr-architecture-05](#) (work in progress), January 2015.

[IEEE8021aq]

IEEE 802.1, "IEEE 802.1aq: IEEE Standard for Local and metropolitan area networks - Media Access Control (MAC) Bridges and Virtual Bridged Local Area Networks - Amendment 20: Shortest Path Bridging", 2012, <<http://standards.ieee.org/getieee802/download/802.1aq-2012.pdf>>.

[IEEE8021Q]

IEEE 802.1, "IEEE 802.1Q-2014: IEEE Standard for Local and metropolitan area networks - Bridges and Bridged Networks", 2014, <<http://standards.ieee.org/findstds/standard/802.1Q-2014.html>>.

[IEEE8021Qca]

IEEE 802.1, "IEEE 802.1Qca Bridges and Bridged Networks - Amendment: Path Control and Reservation - Draft 2.1", (work in progress), June 23, 2015, <<http://www.ieee802.org/1/pages/802.1ca.html>>.

[RFC6329] Fedyk, D., Ashwood-Smith, P., Allan, D., Bragg, A., and P. Unbehagen, "IS-IS Extensions Supporting IEEE 802.1aq Shortest Path Bridging", [RFC 6329](#), April 2012.

Authors' Addresses

Chris Bowers  
Juniper Networks  
1194 N. Mathilda Ave.  
Sunnyvale, CA 94089  
US

Email: [cbowers@juniper.net](mailto:cbowers@juniper.net)



Janos Farkas  
Ericsson  
Konyves Kalman krt. 11/B  
Budapest 1097  
Hungary

Email: [janos.farkas@ericsson.com](mailto:janos.farkas@ericsson.com)