

Independent  
Internet-Draft  
Intended status: Informational  
Expires: February 6, 2015

H. Butler  
Hobu Inc.  
M. Daly  
Cadcorp  
A. Doyle  
MIT  
S. Gillies  
Mapbox Inc.  
T. Schaub  
OpenGeo  
S. Drees

August 5, 2014

The GeoJSON Format  
draft-butler-geojson-04

## Abstract

GeoJSON is a geospatial data interchange format based on JavaScript Object Notation (JSON). It defines several types of JSON objects and the manner in which they are combined to represent data about geographic features, their properties, and their spatial extents. This document recommends a single coordinate reference system based on WGS 84. Other coordinate reference systems are not recommended.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on February 6, 2015.

Internet-Draft

GeoJSON

August 2014

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">1.1.</a>	Requirements Language . . . . .	<a href="#">3</a>
<a href="#">1.2.</a>	Conventions Used in This Document . . . . .	<a href="#">4</a>
<a href="#">1.3.</a>	Specification of GeoJSON . . . . .	<a href="#">4</a>
<a href="#">1.4.</a>	Definitions . . . . .	<a href="#">4</a>
<a href="#">1.5.</a>	Example . . . . .	<a href="#">4</a>
<a href="#">2.</a>	GeoJSON Object . . . . .	<a href="#">6</a>
<a href="#">2.1.</a>	Geometry Object . . . . .	<a href="#">6</a>
<a href="#">2.1.1.</a>	Position . . . . .	<a href="#">6</a>
<a href="#">2.1.2.</a>	Point . . . . .	<a href="#">7</a>
<a href="#">2.1.3.</a>	MultiPoint . . . . .	<a href="#">7</a>
<a href="#">2.1.4.</a>	LineString . . . . .	<a href="#">7</a>
<a href="#">2.1.5.</a>	MultiLineString . . . . .	<a href="#">7</a>
<a href="#">2.1.6.</a>	Polygon . . . . .	<a href="#">7</a>
<a href="#">2.1.7.</a>	MultiPolygon . . . . .	<a href="#">8</a>
<a href="#">2.1.8.</a>	Geometry Collection . . . . .	<a href="#">8</a>
<a href="#">2.2.</a>	Feature Object . . . . .	<a href="#">8</a>
<a href="#">2.3.</a>	Feature Collection Object . . . . .	<a href="#">8</a>
<a href="#">3.</a>	Coordinate Reference System . . . . .	<a href="#">8</a>
<a href="#">4.</a>	Bounding Box . . . . .	<a href="#">9</a>
<a href="#">5.</a>	Security Considerations . . . . .	<a href="#">10</a>
<a href="#">6.</a>	Interoperability Considerations . . . . .	<a href="#">10</a>
<a href="#">7.</a>	IANA Considerations . . . . .	<a href="#">11</a>
<a href="#">8.</a>	References . . . . .	<a href="#">12</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">12</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">12</a>

<a href="#">Appendix A.</a>	Geometry Examples . . . . .	<a href="#">12</a>
<a href="#">A.1.</a>	Points . . . . .	<a href="#">12</a>
<a href="#">A.2.</a>	LineStrings . . . . .	<a href="#">13</a>
<a href="#">A.3.</a>	Polygons . . . . .	<a href="#">13</a>
<a href="#">A.4.</a>	MultiPoints . . . . .	<a href="#">14</a>

<a href="#">A.5.</a>	MultiLineStrings . . . . .	<a href="#">14</a>
<a href="#">A.6.</a>	MultiPolygons . . . . .	<a href="#">15</a>
<a href="#">A.7.</a>	GeometryCollections . . . . .	<a href="#">16</a>
<a href="#">Appendix B.</a>	Contributors . . . . .	<a href="#">17</a>
	Authors' Addresses . . . . .	<a href="#">17</a>

## [1.](#) Introduction

GeoJSON is a format for encoding data about geographic features using JavaScript Object Notation (JSON) [[RFC7159](#)]. The format is concerned with features in the broadest sense; any thing with qualities that are bounded in geographical space may be a feature whether it is a physical structure or not. The concepts in GeoJSON are not new; they are derived from pre-existing open geographic information system standards (for COM, SQL, and XML) and have been streamlined to better suit web application development using JSON.

GeoJSON comprises the seven concrete geometry types defined in the OpenGIS Simple Features Implementation Specification for SQL [[SFSQL](#)]: 0-dimensional Point and MultiPoint; 1-dimensional curve LineString and MultiLineString; 2-dimensional surface Polygon and MultiPolygon; and the heterogeneous GeometryCollection. GeoJSON representations of instances of these geometry types are analogous to the well-known binary (WKB) and text (WKT) representations described in that same specification.

GeoJSON also comprises the types Feature and FeatureCollection. Feature objects in GeoJSON contain a geometry object with one of the above geometry types and additional properties. A FeatureCollection object contains an array of feature objects. This structure is analogous to that of the Web Feature Service (WFS) response to GetFeatures requests specified in [[WFSv1](#)] or to a KML Folder of Placemarks [[KMLv2.2](#)]. Some implementations of the WFS specification also provide GeoJSON formatted responses to GetFeature requests, but there is no particular service model or feature type ontology implied in the GeoJSON format specification.

Since its initial publication in 2008 [[GJ2008](#)], the GeoJSON format specification has steadily grown in popularity. It is widely used in JavaScript web mapping libraries, JSON-based document databases, and web APIs.

### [1.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

### [1.2.](#) Conventions Used in This Document

The ordering of the members of any JSON object defined in this document MUST be considered irrelevant, as specified by [[RFC7159](#)].

Some examples use the combination of a JavaScript single line comment (//) followed by an ellipsis (...) as placeholder notation for content deemed irrelevant by the authors. These placeholders must of course be deleted or otherwise replaced, before attempting to validate the corresponding JSON code example.

Whitespace is used in the examples inside this document to help illustrate the data structures, but is not required. Unquoted whitespace is not significant in JSON.

### [1.3.](#) Specification of GeoJSON

This document updates the original GeoJSON format specification [[GJ2008](#)].

### [1.4.](#) Definitions

- o JavaScript Object Notation (JSON), and the terms object, name, value, array, number, true, false, and null are to be interpreted as defined in [[RFC7159](#)].
- o Inside this document the term "geometry type" refers to the seven case-sensitive strings: "Point", "MultiPoint", "LineString", "MultiLineString", "Polygon", "MultiPolygon", and

"GeometryCollection".

- o As another shorthand notation, the term "GeoJSON types" refers to the nine case-sensitive strings "Feature", "FeatureCollection" and the geometry types listed above.

### [1.5.](#) Example

A GeoJSON feature collection:

```
{
  "type": "FeatureCollection",
  "features": [{
    "type": "Feature",
    "geometry": {
      "type": "Point",
      "coordinates": [102.0, 0.5]
    },
    "properties": {
      "prop0": "value0"
    }
  }, {
    "type": "Feature",
    "geometry": {
      "type": "LineString",
      "coordinates": [
        [102.0, 0.0],
        [103.0, 1.0],
        [104.0, 0.0],
        [105.0, 1.0]
      ]
    }
  }
], {
```

```

    "properties": {
      "prop0": "value0",
      "prop1": 0.0
    }
  }, {
    "type": "Feature",
    "geometry": {
      "type": "Polygon",
      "coordinates": [
        [
          [100.0, 0.0],
          [101.0, 0.0],
          [101.0, 1.0],
          [100.0, 1.0],
          [100.0, 0.0]
        ]
      ]
    },
    "properties": {
      "prop0": "value0",
      "prop1": {
        "this": "that"
      }
    }
  }
]
}

```

## [2. GeoJSON Object](#)

GeoJSON always consists of a single object. This object (referred to as the GeoJSON object below) represents a geometry, feature, or collection of features.

- o The GeoJSON object **MUST** have a member with the name "type". The value of the member **MUST** be one of the GeoJSON types.
- o The GeoJSON object **MAY** have any number of other members.
- o A GeoJSON object **MAY** have a "bbox" member, the value of which **MUST** be a bounding box array (see 4. Bounding Boxes).

### [2.1. Geometry Object](#)

A geometry object is a GeoJSON object where the "type" value is one of the geometry types. A GeoJSON geometry object of any type other than "GeometryCollection" MUST have a member with the name "coordinates". The value of the coordinates member is always an array. The structure of the elements in this array is determined by the type of geometry. GeoJSON processors MAY interpret geometry objects with empty coordinates arrays as null objects.

#### [2.1.1.](#) Position

A position is the fundamental geometry construct. The "coordinates" member of a geometry object is composed of either:

- o one position (in the case of a Point geometry),
- o an array of positions (LineString or MultiPoint geometries),
- o an array of arrays of positions (Polygons, MultiLineStrings),
- o or a multidimensional array of positions (MultiPolygon).

A position is represented by an array of numbers. There MUST be two or more elements. The first two elements will be longitude and latitude, or easting and northing, precisely in that order and using decimal numbers. Altitude or elevation MAY be included as an optional third element.

Additional position elements MAY be included but MUST follow the three specified above and MAY be ignored by software. Interpretation and meaning of additional elements is beyond the scope of this specification.

Examples of positions and geometries are provided in "Appendix A. Geometry Examples".

#### [2.1.2.](#) Point

For type "Point", the "coordinates" member MUST be a single position.

#### [2.1.3.](#) MultiPoint

For type "MultiPoint", the "coordinates" member MUST be an array of positions.

#### [2.1.4.](#) LineString

For type "LineString", the "coordinates" member MUST be an array of two or more positions.

#### [2.1.5.](#) MultiLineString

For type "MultiLineString", the "coordinates" member MUST be an array of LineString coordinate arrays.

#### [2.1.6.](#) Polygon

To specify a constraint specific to polygons, it is useful to introduce the concept of a linear ring:

- o A linear ring is a closed LineString with 4 or more positions.
- o The first and last positions are equivalent (they represent equivalent points).
- o A linear ring is the boundary of a surface or the boundary of a hole in a surface.

Though a linear ring is not explicitly represented as a GeoJSON geometry type, it leads to a canonical formulation of the Polygon geometry type definition as follows:

- o For type "Polygon", the "coordinates" member MUST be an array of linear ring coordinate arrays.
- o For Polygons with more than one of these rings, the first MUST be the exterior ring and any others MUST be interior rings. The exterior ring bounds the surface and the interior rings (if present) bound holes within the surface.

#### [2.1.7.](#) MultiPolygon



For type "MultiPolygon", the "coordinates" member MUST be an array of Polygon coordinate arrays.

#### [2.1.8.](#) Geometry Collection

A GeoJSON object with type "GeometryCollection" is a geometry object which represents a collection of geometry objects. A geometry collection MUST have a member with the name "geometries". The value corresponding to "geometries" is an array. Each element in this array is a GeoJSON geometry object.

#### [2.2.](#) Feature Object

A GeoJSON object with the type "Feature" is a feature object.

- o A feature object MUST have a member with the name "geometry". The value of the geometry member SHALL be either a geometry object as defined above or, in the the case that the feature is unlocated, a JSON null value.
- o A feature object MUST have a member with the name "properties". The value of the properties member is an object (any JSON object or a JSON null value).
- o If a feature has a commonly used identifier, that identifier SHOULD be included as a member of the feature object with the name "id" and the value of this member is either a JSON string or number.

#### [2.3.](#) Feature Collection Object

A GeoJSON object with the type "FeatureCollection" is a feature collection object. An object of type "FeatureCollection" MUST have a member with the name "features". The value corresponding to "features" is an array. Each element in the array is a feature object as defined above.

### [3.](#) Coordinate Reference System

The default reference system for all GeoJSON coordinates SHALL be a geographic coordinate reference system, using the [\[WGS84\]](#) datum, and with longitude and latitude units of decimal degrees. This coordinate reference system is equivalent to the OGC's "<http://www.opengis.net/def/crs/OGC/1.3/CRS84>" [\[OGCURL\]](#). An OPTIONAL third position element SHALL be the height in meters above the WGS 84

reference ellipsoid. For widest interoperability, GeoJSON data SHOULD use this default coordinate reference system.

Other coordinate reference systems, including ones described by CRS objects of the kind defined in [GJ2008] are NOT RECOMMENDED. GeoJSON processing software SHALL NOT be expected to have access to coordinate reference systems databases. Applications requiring CRS other than the default MUST assume all responsibility for reference system and coordinate accuracy. Furthermore, GeoJSON coordinates MUST NOT under any circumstances use latitude, longitude order. See [Section 6](#), Interoperability Considerations, for guidance in processing GeoJSON documents that do contain such a CRS object.

#### 4. Bounding Box

A GeoJSON object MAY have a member named "bbox" to include information on the coordinate range for its geometries, features, or feature collections. The value of the bbox member MUST be an array of length  $2 \times n$  where  $n$  is the number of dimensions represented in the contained geometries, with the lowest values for all axes followed by the highest values. The axes order of a bbox follows the axes order of geometries.

Example of a bbox member on a feature:

```
{
  "type": "Feature",
  "bbox": [-180.0, -90.0, 180.0, 90.0],
  "geometry": {
    "type": "Polygon",
    "coordinates": [
      [
        [-180.0, 10.0],
        [20.0, 90.0],
        [180.0, -5.0],
        [-30.0, -90.0]
      ]
    ]
  }
  //...
}
```

Example of a bbox member on a feature collection:

```
{
  "type": "FeatureCollection",
  "bbox": [100.0, 0.0, 105.0, 1.0],
  "features": [
    //...
  ]
}
```

## 5. Security Considerations

GeoJSON shares security issues common to all JSON content types. See [\[RFC7159\] Section 12](#) for additional information. GeoJSON does not provide executable content.

As with other geographic data formats, e.g., [\[KMLv2.2\]](#), providing details about the locations of sensitive persons, animals, habitats, and facilities can expose them to unauthorized tracking or injury. GeoJSON does not provide privacy or integrity services; if sensitive data requires privacy or integrity protection the service must be provided externally.

## 6. Interoperability Considerations

There are differences among geographic data formats over whether latitude or longitude come first in a pair of numbers. Longitude comes first in GeoJSON coordinates as it does in [\[KMLv2.2\]](#).

The original GeoJSON format specification [\[GJ2008\]](#) included descriptions of coordinate reference system (CRS) objects. These are NOT RECOMMENDED but may be found in existing documents. When such a CRS is encountered in GeoJSON, the document should be processed with caution. The coordinate values may be projected, i.e., easting and northing instead of longitude and latitude.

On encountering a named CRS object with a value of "urn:ogc:def:crs:OGC:1.3:CRS84" or "http://www.opengis.net/def/crs/OGC/1.3/CRS84", processors SHOULD interpret the coordinates exactly as in [Section 2.1.1](#); these CRS are equivalent to the default coordinate reference system.

Due to a history of changing and vernacular usage, extra caution is required when processing GeoJSON that has a named CRS object with the value "EPSG:4326." Heuristics may be necessary to interpret the coordinates properly; they may not be in the required longitude, latitude order.

When serving GeoJSON, use of CRS objects is NOT RECOMMENDED. If an application requires coordinates in a reference system other than the

Butler, et al.

Expires February 6, 2015

[Page 10]

---

Internet-Draft

GeoJSON

August 2014

default, it MUST assume all responsibility for communicating this to clients.

Regardless, GeoJSON coordinates MUST NOT under any circumstances use latitude, longitude order.

## [7.](#) IANA Considerations

The MIME media type for GeoJSON text is application/vnd.geo+json.

Type name: application

Subtype name: vnd.geo+json

Required parameters: n/a

Optional parameters: n/a

Encoding considerations: binary

Security considerations: See [section 5](#) above

Interoperability considerations: See [section 6](#) above

Published specification: [draft-butler-geojson](#)

Applications that use this media type: various

Additional information:

Magic number(s) : n/a

File extension(s) : .json, .geojson

Macintosh file type code : TEXT

Object Identifiers: n/a

Person to contact for further information:

Sean Gillies

sean.gillies@gmail.com

Intended usage: COMMON

Restrictions on usage: none

Butler, et al.

Expires February 6, 2015

[Page 11]

---

Internet-Draft

GeoJSON

August 2014

## [8.](#) References

### [8.1.](#) Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC7159] Bray, T., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), March 2014.

### [8.2.](#) Informative References

[GJ2008] Butler, H., Daly, M., Doyle, A., Gillies, S., Schaub, T., and C. Schmidt, "The GeoJSON Format Specification", June 2008.

[KMLv2.2] Wilson, T., "OGC KML", OGC 07-147r2, April 2008.

[OGCURL] Cox, S., "OGC-NA Name type specification - definitions: Part 1 - basic name", OGC 09-048r3, March 2010.

[SFSQL] OpenGIS Consortium, Inc., "OpenGIS Simple Features Specification For SQL Revision 1.1", OGC 99-049, May 1999.

[WFSv1] Vretanos, P., "Web Feature Service Implementation

Specification", OGC 02-058, May 2002.

[WGS84] National Imagery and Mapping Agency, "Department of Defense World Geodetic System 1984, Third Edition", 1984.

## [Appendix A](#). Geometry Examples

Each of the examples below represents a valid and complete GeoJSON object.

### [A.1](#). Points

Point coordinates are in x, y order (easting, northing for projected coordinates, longitude, latitude for geographic coordinates):

```
{
  "type": "Point",
  "coordinates": [100.0, 0.0]
}
```

Butler, et al.

Expires February 6, 2015

[Page 12]

---

Internet-Draft

GeoJSON

August 2014

### [A.2](#). LineStrings

Coordinates of LineString are an array of positions (see "2.1.1. Position"):

```
{
  "type": "LineString",
  "coordinates": [
    [100.0, 0.0],
    [101.0, 1.0]
  ]
}
```

### [A.3](#). Polygons

Coordinates of a Polygon are an array of LinearRing (cf. "2.1.6 Polygon") coordinate arrays. The first element in the array represents the exterior ring. Any subsequent elements represent

interior rings (or holes).

No holes:

```
{
  "type": "Polygon",
  "coordinates": [
    [
      [100.0, 0.0],
      [101.0, 0.0],
      [101.0, 1.0],
      [100.0, 1.0],
      [100.0, 0.0]
    ]
  ]
}
```

With holes:

```
{
  "type": "Polygon",
  "coordinates": [
    [
      [100.0, 0.0],
      [101.0, 0.0],
      [101.0, 1.0],
      [100.0, 1.0],
      [100.0, 0.0]
    ],
    [
```

```
        [100.2, 0.2],
        [100.8, 0.2],
        [100.8, 0.8],
        [100.2, 0.8],
        [100.2, 0.2]
    ]
}
}
```

#### [A.4.](#) MultiPoints

Coordinates of a MultiPoint are an array of positions::

```
{
  "type": "MultiPoint",
  "coordinates": [
    [100.0, 0.0],
    [101.0, 1.0]
  ]
}
```

#### [A.5.](#) MultiLineStrings

Coordinates of a MultiLineString are an array of LineString coordinate arrays:

```
{
  "type": "MultiLineString",
  "coordinates": [
    [
```



```
        [100.0, 0.0],
        [101.0, 1.0]
    ],
    [
        [102.0, 2.0],
        [103.0, 3.0]
    ]
]
}
```

#### [A.6.](#) MultiPolygons

Coordinates of a MultiPolygon are an array of Polygon coordinate arrays:

```
{
  "type": "MultiPolygon",
  "coordinates": [
    [
      [
        [102.0, 2.0],
        [103.0, 2.0],
        [103.0, 3.0],
        [102.0, 3.0],
        [102.0, 2.0]
      ]
    ],
    [
      [
        [100.0, 0.0],
        [101.0, 0.0],
        [101.0, 1.0],
        [100.0, 1.0],
        [100.0, 0.0]
      ],
      [
        [100.2, 0.2],
        [100.8, 0.2],
        [100.8, 0.8],
        [100.2, 0.8],
        [100.2, 0.2]
      ]
    ]
  ]
}
```

#### [A.7.](#) GeometryCollections

Each element in the geometries array of a GeometryCollection is one of the geometry objects described above:

Internet-Draft

GeoJSON

August 2014

```
{
  "type": "GeometryCollection",
  "geometries": [{
    "type": "Point",
    "coordinates": [100.0, 0.0]
  }, {
    "type": "LineString",
    "coordinates": [
      [101.0, 0.0],
      [102.0, 1.0]
    ]
  }
]
```

## [Appendix B](#). Contributors

The GeoJSON format is the product of discussion on the GeoJSON mailing list: <http://lists.geojson.org/listinfo.cgi/geojson-geojson.org>.

Comments are solicited and should be addressed to the GeoJSON mailing list at [geojson@lists.geojson.org](mailto:geojson@lists.geojson.org) or to the GeoJSON issue tracker at <https://github.com/geojson/draft-geojson/issues>.

## Authors' Addresses

H. Butler  
Hobu Inc.

M. Daly  
Cadcorp

A. Doyle  
MIT

S. Gillies  
Mapbox Inc.

Email: sean.gillies@gmail.com

URI: <http://sgillies.net>

T. Schaub

OpenGeo

Butler, et al.

Expires February 6, 2015

[Page 17]

---

Internet-Draft

GeoJSON

August 2014

S. Drees

Rheinaustr. 62

Bonn 53225

DE

Email: stefan@drees.name

URI: <http://sdre.es/>

