

NFSv4  
Internet-Draft  
Intended status: Standards Track  
Expires: July 19, 2014

C. Lever  
Oracle  
January 15, 2014

**Federated Filesystem Security Addendum**  
**draft-cel-nfsv4-federated-fs-security-addendum-00**

Abstract

This document addresses critical security-related items that are missing from existing FedFS proposed standards.

## Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 19, 2014.

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Lever

Expires July 19, 2014

[Page 2]

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">4</a>
<a href="#">1.1.</a>	Problem Statement: GSSAPI service name for ADMIN . . . . .	<a href="#">4</a>
<a href="#">1.2.</a>	Problem Statement: Compromised NSDBs . . . . .	<a href="#">4</a>
<a href="#">1.3.</a>	Scope Of This Document . . . . .	<a href="#">6</a>
<a href="#">2.</a>	GSSAPI Service Name for the FedFS ADMIN protocol . . . . .	<a href="#">7</a>
<a href="#">3.</a>	Fencing Compromised NSDBs . . . . .	<a href="#">8</a>
<a href="#">4.</a>	Security Considerations . . . . .	<a href="#">9</a>
<a href="#">5.</a>	IANA Considerations . . . . .	<a href="#">10</a>
<a href="#">6.</a>	Acknowledgements . . . . .	<a href="#">11</a>
<a href="#">7.</a>	References . . . . .	<a href="#">12</a>
<a href="#">7.1.</a>	Normative References . . . . .	<a href="#">12</a>
<a href="#">7.2.</a>	Informative References . . . . .	<a href="#">12</a>
	Author's Address . . . . .	<a href="#">13</a>

Lever

Expires July 19, 2014

[Page 3]

## **1. Introduction**

Requirements for federated filesystems are described in [\[RFC5716\]](#). Specification of the protocol used by administrators to configure file servers and construct namespaces is provided in [\[FEDFS-ADMIN\]](#). Specification of the protocol allowing file servers to store namespace information is provided in [\[FEDFS-NSDB\]](#).

These documents are now immutable. However, some security-related concerns have arisen that should be addressed immediately rather than waiting for another version of these protocols to be ratified.

### **1.1. Problem Statement: GSSAPI service name for ADMIN**

After IESG review, the Security Considerations chapter of [\[FEDFS-ADMIN\]](#) now specifically requires that implementations of this protocol support GSSAPI security mechanisms.

ADMIN protocol clients must use a service principal to establish a GSS context shared with an ADMIN server. To construct the service principal, clients need to know a priori the protocol's GSSAPI service name. The form of that service name is described in [section 4.1 of \[RFC2743\]](#).

Also according to the final paragraph of [section 4.1](#), requesting an addition to the "GSSAPI/Kerberos/SASL Service Names" registry requires a specification. Because [\[FEDFS-ADMIN\]](#) cannot be changed, a new specification must be provided.

### **1.2. Problem Statement: Compromised NSDBs**

The FedFS ADMIN RPC protocol provides a mechanism for provisioning NSDBs on remote file servers. The operations it provides are `FEDFS_SET_NSDB_PARAMS`, `FEDFS_GET_NSDB_PARAMS`, and `FEDFS_GET_LIMITED_NSDB_PARAMS`.

`FEDFS_SET_NSDB_PARAMS` specifies the name of an NSDB and the security mode to use when connecting to this NSDB. The file server connects to an NSDB in order to resolve a FedFS junction. The ADMIN protocol specification further says:

On success, this operation returns `FEDFS_OK`. When the operation returns, the new connection parameters SHOULD be used for all subsequent LDAP connections to the given NSDB. Existing connections MAY be terminated and re-established using the new connection parameters. The connection parameters SHOULD be durable across file server reboots.

Lever

Expires July 19, 2014

[Page 4]

There are two security modes defined in the protocol specification: `FEDFS_SEC_NONE`, which does not authenticate the LDAP server; and `FEDFS_SEC_TLS`, which uses `START_TLS` ([RFC 4513](#)) to authenticate the LDAP server.

When `FEDFS_SEC_TLS` is specified with the `FEDFS_SET_NSDB_PARAMS` operation, an x.509v3 certificate chain is also provided to the fileserver. The fileserver uses the provided certificate to authenticate subsequent connections to this NSDB. The `FEDFS_SET_NSDB_PARAMS` operation can change the connection security used by a fileserver to connect to a particular NSDB from `NONE` to `TLS` or `TLS` to `NONE`.

Over time, domain administrators add NSDB connection parameters to each of their fileservers to enable FedFS junction resolution. The specified NSDB may be the domain's own, or it might be an NSDB in a foreign domain.

Many junctions on multiple fileservers can be created that use a particular NSDB. There is no way to find such junctions without an exhaustive search. Since filesystem namespace topology can evolve arbitrarily over time, a recorded pathname of any junction is almost guaranteed to become stale.

Now suppose we have two FedFS domains: `example.net` and `university.edu`. Suppose `university.edu` fileservers have a number of junctions that refer to locations maintained by `example.net`, and thus `university.net`'s fileservers are configured to resolve junctions on `example.net`'s NSDB.

One day Mallory compromises `example.net`'s NSDB, but the domain administrator there is on a long vacation. The administrator at `university.net` discovers the compromise immediately, but has no control over the foreign NSDB and cannot create a fresh x.509 certificate or verify that the contents of the NSDB are unmolested. The only choice is to find and remove every junction in the `university.edu` domain that contains the compromised NSDB.

If `university.edu` is using a good implementation of FedFS, the administrative tools it provides might allow an administrator to simply visit each of its fileservers and mark the `example.net` NSDB as compromised. Any junction resolution that attempts to use that NSDB would fail, but all junctions remain in place. When `example.net`'s administrator gets back from holiday and cleans up the mess, the `university.edu` administrator can then update each of her fileservers with fresh connection parameters for that NSDB.

However, none of this can be done remotely using the FedFS ADMIN



Lever

Expires July 19, 2014

[Page 5]

protocol. It does not have a mechanism for removing NSDB connection parameters or for fencing a compromised NSDB.

### **1.3. Scope Of This Document**

This document specifies additional requirements for the FedFS ADMIN protocol specified in [[FEDFS-ADMIN](#)], which is a standards track specification.

## **2. GSSAPI Service Name for the FedFS ADMIN protocol**

Section 6 of [[FEDFS-ADMIN](#)] requires a FedFS ADMIN server to support the RPCSEC\_GSS framework [[RFC2203](#)]. The present document specifies the GSSAPI service name, as described in [Section 4.1 of \[RFC2743\]](#), to be used for the FedFS ADMIN protocol.

Regardless of what security mechanism under RPCSEC\_GSS is in use, a FedFS ADMIN server MUST identify itself in GSSAPI via a GSS\_C\_NT\_HOSTBASED\_SERVICE name type. GSS\_C\_NT\_HOSTBASED\_SERVICE names are of the form:

`service@hostname`

For the ADMIN protocol, the "service" element is

`fedfs-admin`

Implementations of security mechanisms will convert `fedfs-admin@hostname` to various different forms. For Kerberos V5, the following form is RECOMMENDED:

`fedfs-admin/hostname`

This service name SHOULD NOT be used to authenticate other GSSAPI services.

Lever

Expires July 19, 2014

[Page 7]

### **3. Fencing Compromised NSDBs**

An NSDB is considered "foreign" relative to a particular FedFS domain if that domain's administrator has no administrative access to that NSDB.

When a FedFS domain administrator is faced with a foreign NSDB that is compromised or otherwise unusable, and in the absence of an implementation-provided mechanism for fencing an NSDB, the administrator can fence that NSDB using the following technique.

1. The administrator locally generates a new certificate for the compromised foreign NSDB. The certificate can be self-signed, or signed by the administrator's local certificate authority.
2. The administrator distributes this certificate to all of her domain's file servers using the FedFS ADMIN protocol or some other secure means. The connection security for the foreign NSDB is set to FEDFS\_SEC\_TLS on each of the local domain's file servers.
3. The administrator requests fresh certificate material from the administrator of the foreign NSDB.
4. When the threat has passed and the foreign NSDB is safe to use again, the administrator can distribute the new valid certificate material to her domain's file servers.

No change to the ADMIN protocol as specified in [[FEDFS-ADMIN](#)] is required to fence a compromised NSDB. Step 2 guarantees that, on file servers in the administrator's local FedFS domain, resolving a junction that references the compromised foreign NSDB will fail until updated certificate material is provided.



#### **4. Security Considerations**

When deploying FedFS, the use of security mechanisms that maintain the confidentiality of all network communications is recommended. This includes the use of any pseudoflavor that supports the `rpc_gss_svc_privacy` service for the FedFS ADMIN protocol, and the use of TLS message encryption for the NSDB protocol.

When creating x.509 certificates for authenticating NSDBs, implementations should utilize keys that are as large as practical, especially if certificate lifetimes are long.

Operational security is further enhanced by ensuring that all hardware entropy sources are verified for cryptographic use. This recommendation applies to the creation of x.509 certificate material, random-variant UUIDs, and handshake keys used to secure transports, for example.

Information stored in `fedfsDescr` and `fedfsAnnotation` attributes are readable by any unauthenticated user of an NSDB, and therefore should contain no sensitive information.

Lever

Expires July 19, 2014

[Page 9]



## **5. IANA Considerations**

In accordance with [Section 4.1 of \[RFC2743\]](#), the service name "fedfs-admin" will be registered in the GSSAPI Service Name registry at [http://www.iana.org/assignments/gssapi-service-names/](http://www.iana.org/assignments/gssapi-service-names/gssapi-service-names.xml) gssapi-service-names.xml

The new entry should reference the present document as the specification.

## **6. Acknowledgements**

The author of this document gratefully acknowledges the contributions of Nico Williams, Robert Thurlow, Spencer Shepler, Tom Haynes, and David Noveck.

## **7. References**

### **7.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC2203] Eisler, M., Chiu, A., and L. Ling, "RPCSEC\_GSS Protocol Specification", [RFC 2203](#), September 1997.
- [RFC2743] Linn, J., "Generic Security Service Application Program Interface Version 2, Update 1", [RFC 2743](#), January 2000.

### **7.2. Informative References**

- [FEDFS-ADMIN]  
Lentini, J., Everhart, C., Ellard, D., Tewari, R., and M. Naik, "Administration Protocol for Federated Filesystems", [draft-ietf-nfsv4-federated-fs-admin](#) (Work In Progress), 2010.
- [FEDFS-NSDB]  
Lentini, J., Everhart, C., Ellard, D., Tewari, R., and M. Naik, "NSDB Protocol for Federated Filesystems", [draft-ietf-nfsv4-federated-fs-protocol](#) (Work In Progress), 2010.
- [RFC5716] Lentini, J., Everhart, C., Ellard, D., Tewari, R., and M. Naik, "Requirements for Federated File Systems", [RFC 5716](#), January 2010.

Lever

Expires July 19, 2014

[Page 12]

Author's Address

Charles Lever  
Oracle Corporation  
1015 Granger Avenue  
Ann Arbor, MI 48104  
US

Phone: +1 734 274 2396

Email: [chuck.lever@oracle.com](mailto:chuck.lever@oracle.com)