Workgroup: Network Working Group

Internet-Draft: draft-chen-lsr-adv-lkno-01

Published: 12 January 2023

Intended Status: Standards Track

Expires: 16 July 2023

Authors: H. Chen D. Eastlake A. Wang

Futurewei Futurewei China Telecom

G. Mishra Y. Liu Y. Fan L. Liu Verizon Inc. China Mobile Casa Systems Fujitsu

X. Liu

IBM Corporation

IGP Extensions for Advertising Link Numbers

Abstract

This document describes OSPF and IS-IS extensions for distributing the link numbers assigned to the links originating at a node.

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 16 July 2023.

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents

(https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- 1. Introduction
 - 1.1. <u>Terminology</u>
- 2. Extensions to OSPFv2
- 3. Extensions to OSPFv3
- 4. Extensions to IS-IS
- 5. Security Considerations
- 6. IANA Considerations
- Acknowledgements
- 8. References
 - 8.1. Normative References
 - 8.2. Informative References

Authors' Addresses

1. Introduction

When the links originating at each node in a network are numbered from 1 to the number of the such links for that node, an efficient stateless multicast along an explicit P2MP path can be achieved through using the link numbers of the links on the path to represent the path.

This document proposes OSPF and IS-IS extensions for distributing the link numbers assigned to the links originating at a node which will support such multicast. After a controller such as PCE as a controller has the link numbers of the links originating at every node, for an explicit P2MP path, the controller can send the ingress the path represented by the link numbers of the links on the path.

1.1. Terminology

LSA: Link State Advertisement.

OSPF: Open Shortest Path First.

LSP: Link State Protocol data unit.

IS-IS: Intermediate System to Intermediate System.

MT: Multi-Topology.

TE:

Traffic Engineering.

2. Extensions to OSPFv2

This section describes extensions to OSPFv2 for distributing the link numbers assigned to the links of a node.

[RFC7684] defines the OSPFv2 Extended Link TLV to advertise the information about a link. Multiple Link TLVs for the links of a router are included in the OSPFv2 Extended Link Opaque LSA of the router. The OSPFv2 Extended Link TLV has the following format:

0	1		2	3
0 1 2 3 4 5	6 7 8 9 0 1 2	3 4 5 6 7 8	9 0 1 2 3 4 5	6 7 8 9 0 1
+-+-+-+-+-+	-+-+-+-+-+-	+-+-+-	+-+-+-+-+-	+-+-+-+-+-+
1	Type (1)	1	Length (Varia	ıble)
+-+-+-+-+	-+-+-+-+-+-+	+-+-+-+-	+-+-+-+-+-	+-+-+-+-+
Link Type	· [R	eserved	I
+-+-+-+-+	-+-+-+-+-+-+	+-+-+-	+-+-+-+-+-	+-+-+-+-+-+
1		Link ID		1
+-+-+-+-+	-+-+-+-+-+-	-+-+-+-	+-+-+-+-+-	+-+-+-+-+-+
1		Link Data	L	1
+-+-+-+-+-+	-+-+-+-+-+-+	+-+-+-	+-+-+-+-+-	+-+-+-+-+-+
1	Sub	-TLVs (vari	able)	1
~				~
+-+-+-+-+-+	-+-+-+-+-+-	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-+

Figure 1: OSPFv2 Extended Link TLV

Type: 1.

Length: Variable, dependent on Sub-TLVs.

Link Type, Link ID and Link Data: They are defined in Section A.4.2 of [RFC2328].

Reserved: MUST be set to 0 on transmission and MUST be ignored on reception.

Under the OSPFv2 Extended Link TLV for a link, a Link Number Sub-TLV is defined for distributing the link number assigned to the link by the router originating the LSA. A Link Number Sub-TLV is included in the Link TLV for a link of Link Type Point-to-Point, Broadcast (i.e., link to LAN or Transit Network), or stub (i.e., link to stub network). The Link Number Sub-TLV has the following format:

Figure 2: Link Number Sub-TLV

Type: TBD1. (Note this is the Sub-TLV Type, not the Link Type.)

Length: 2.

Link Number: A 2-octet field carrying the link number assigned to
 the link when the Link Type of the link in the OSPFv2 Extended
 Link TLV containing this Sub-TLV is 1 (i.e., Point-to-Point
 connection to another router), 2 (i.e., connection to a Transit
 Network or LAN), or 3 (i.e., connection to a stub network).

3. Extensions to OSPFv3

This section describes extensions to OSPFv3 for distributing the link numbers assigned to the links of a node.

[RFC8362] defines the OSPFv3 Extended Router LSA, which may include multiple Router-Link TLVs.

0	=	1		2		3
0 1 2	2 3 4 5 6 7 8 9 0	9 1 2 3 4	5 6 7 8	9 0 1 2	3 4 5 6 7	8 9 0 1
+-+-+	-+-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
	LS Age	I	1 0 1		0x21	1
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
		Link S	State ID			1
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
		Advertis	ing Rout	er		1
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
		LS Seque	ence Numb	er		1
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
	LS Checksum			Ler	igth	1
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
0	N x V E B		Opti	ons		
+-+-+	-+-+-+-+-+-	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+
			TLVs			1
:						:
+-+-+	-+-+-+-+-+-+	-+-+-+-+	+-+-+	-+-+-+	-+-+-+-	+-+-+-+

Figure 3: Extended Router-LSA

A Router-Link TLV defines a single router link.

Θ	1	2		3					
0 1 2 3 4 5 6 7	8 9 0 1 2 3 4	5 6 7 8 9 0 1	2 3 4 5 6 7 8 9	0 1					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-+-	-+-+-+					
Type (1 - Rou	ter-Link)	Leng	th (Variable)	- 1					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-	-+-+-+					
Link Type	0		Metric	- 1					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-	-+-+-+					
	Inter	face ID		1					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-	-+-+-+					
	Neighbor	Interface ID		- 1					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-+-	-+-+-+					
	Neighbo	r Router ID		- 1					
+-									
	Sub	-TLVs		- 1					
:				:					
+-+-+-+-+-+-+	-+-+-+-+-	+-+-+-+-+-	+-+-+-+-+-+-	-+-+-+					

Figure 4: Router-Link TV

Under the Router-Link TLV for a link, a Link Number Sub-TLV is defined. This Sub-TLV has the same format as the Link Number Sub-TLV defined above for the OSPFv2 Extended Link TLV.

The Router-Link TLV for a link may include a Link Number Sub-TLV for distributing the link number assigned to the link by the router originating the LSA.

4. Extensions to IS-IS

This section describes extensions to IS-IS for distributing the link numbers assigned to the links of a node.

The Extended IS Reachability TLV (Type 22) defined in [RFC5305] may contain Sub-TLVs (such as those for TE (Traffic Engineering)) that apply to a link/interface to a neighbor. To encode multiple links or interfaces to neighbors, the structure inside TLV is repeated.

The Multi-Topology (MT) Intermediate Systems TLV (Type 222) defined in [RFC5120] may contain Sub-TLVs (such as those for TE) that apply to a link/interface. It is aligned with the Extended IS Reachability TLV (Type 22) but has an additional two bytes in front at the beginning of the TLV for MT-ID.

A Link Number Sub-TLV is defined and used in the Extended IS Reachability TLV (Type 22) and/or MT Intermediate Systems TLV (Type 222) to advertise the link numbers assigned to the links of a node.

The Link Number Sub-TLV has the following format:

(9										1										2										3	
(9	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1	2	3	4	5	6	7	8	9	0	1
+	- +	-+	+	-	+ - •	+-	+ -	+	+	+	+	+	 	+	+	+	+	+	+	+	- -	+	 	+	+	+	+	 	+	+	- - +	- +
		Ту	γре	9	(TI	BD	3)				L	enç	gtŀ	า			l				I	_ir	٦k	Nι	uml	oeı	r					
+	- +	- +	+	-	+	+-	+ -	+	+	+	+	+	 	+ - +	+	+	+	+	 	+	- -	+	+ - +	 	+	+	+	 	 	+	H - H	+ - +

Figure 5: IS-IS Link Number Sub-TLV

Type: TBD3.

Length: 2.

Link Number: A 2-octet field carrying the link number assigned to the link.

5. Security Considerations

TBD.

6. IANA Considerations

Under "OSPFv2 Extended Link TLV Sub-TLVs registry" as defined in [RFC7684], IANA is requested to assign a registry value for Link Number Sub-TLV as follows:

+=	========	=+=	==========	+===:	===========	+
'	Value	•	Description	 	reference	
+=	========	=+=	==========	+===:		+
	TBD1		Link Number		This document	
+-		-+-		+		+

Under "OSPFv3 Extended-LSA Sub-TLVs registry" as defined in $[\mbox{RFC8362}]$, IANA is requested to assign a registry value for Link Number Sub-TLV as follows:

+=		+=:	======================================	+===:	=======================================	+
•	Value	'	Description		reference	
+=	=========	+=	==============	+===:	=======================================	+
'		'	Link Number	'	This document	

Under "Sub-TLVs for TLVs 22, 23, 25, 141, 222, and 223" for IS-IS TLV Codepoints, IANA is requested to assign a codepoint for Link Number Sub-TLV as follows:

+========	+==============	===	+==	+==	+==	=+	===	+===	+====	======+
Sub-TLV Type	Sub-TLV Name	22	23	25	14	1	222	223	3 refe	rence
+========	+=============	=+==	+==	+==	+==	=+	===	+===	+====	=====+
	Link Number				•		-	•	•	document
+	+	-+	+	+	+	-+		+	+	+

7. Acknowledgements

TBD.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
 Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/
 RFC2119, March 1997, https://www.rfc-editor.org/info/rfc2119.

- [RFC5305] Li, T. and H. Smit, "IS-IS Extensions for Traffic Engineering", RFC 5305, DOI 10.17487/RFC5305, October 2008, https://www.rfc-editor.org/info/rfc5305>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC
 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174,
 May 2017, https://www.rfc-editor.org/info/rfc8174>.
- [RFC8362] Lindem, A., Roy, A., Goethals, D., Reddy Vallem, V., and
 F. Baker, "OSPFv3 Link State Advertisement (LSA)

Extensibility", RFC 8362, DOI 10.17487/RFC8362, April 2018, https://www.rfc-editor.org/info/rfc8362>.

8.2. Informative References

Authors' Addresses

Huaimo Chen Futurewei Boston, MA, United States of America

Email: Huaimo.chen@futurewei.com

Donald E. Eastlake 3rd Futurewei 2386 Panoramic Circle Apopka, FL, 32703 United States of America

Phone: <u>+1-508-333-2270</u> Email: <u>d3e3e3@gmail.com</u>

Aijun Wang China Telecom Beiqijia Town, Changping District Beijing 102209 China

Email: wangaj3@chinatelecom.cn

Gyan S. Mishra
Verizon Inc.
13101 Columbia Pike
Silver Spring, MD 20904
United States of America

Phone: <u>301 502-1347</u>

Email: gyan.s.mishra@verizon.com

Yisong Liu China Mobile

Email: liuyisong@chinamobile.com

Yanhe Fan Casa Systems United States of America

Email: yfan@casa-systems.com

Lei Liu Fujitsu

United States of America

Email: liulei.kddi@gmail.com

Xufeng Liu
IBM Corporation

United States of America

Email: xufeng.liu.ietf@gmail.com