

Network Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: September 3, 2019

C. Hopps  
LabN Consulting, L.L.C.  
March 2, 2019

**YANG Geo Location**  
**draft-chopps-netmod-geo-location-01**

Abstract

This document defines a generic geographical location object YANG grouping. The geographical location grouping is intended to be used in YANG models for specifying a location on or in reference to the Earth or any other astronomical object.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on September 3, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	The Geo Location Object . . . . .	<a href="#">3</a>
<a href="#">2.1.</a>	Frame of Reference . . . . .	<a href="#">3</a>
<a href="#">2.2.</a>	Location . . . . .	<a href="#">4</a>
<a href="#">2.3.</a>	Motion . . . . .	<a href="#">4</a>
<a href="#">2.4.</a>	Nested Locations . . . . .	<a href="#">5</a>
<a href="#">2.5.</a>	Non-location Attributes . . . . .	<a href="#">5</a>
<a href="#">2.6.</a>	Tree . . . . .	<a href="#">5</a>
<a href="#">3.</a>	YANG Module . . . . .	<a href="#">6</a>
<a href="#">4.</a>	ISO 6709:2008 Conformance . . . . .	<a href="#">11</a>
<a href="#">5.</a>	Usability . . . . .	<a href="#">12</a>
<a href="#">5.1.</a>	Portability . . . . .	<a href="#">12</a>
<a href="#">5.1.1.</a>	IETF URI Value . . . . .	<a href="#">12</a>
<a href="#">5.1.2.</a>	W3C . . . . .	<a href="#">12</a>
<a href="#">5.1.3.</a>	Geography Markup Language (GML) . . . . .	<a href="#">14</a>
<a href="#">5.1.4.</a>	KML . . . . .	<a href="#">15</a>
<a href="#">6.</a>	IANA Considerations . . . . .	<a href="#">16</a>
<a href="#">6.1.</a>	Geodetic System Value Registry . . . . .	<a href="#">16</a>
<a href="#">7.</a>	Security Considerations . . . . .	<a href="#">17</a>
<a href="#">8.</a>	References . . . . .	<a href="#">17</a>
<a href="#">8.1.</a>	Normative References . . . . .	<a href="#">17</a>
<a href="#">8.2.</a>	Informative References . . . . .	<a href="#">18</a>
<a href="#">Appendix A.</a>	Examples . . . . .	<a href="#">19</a>
<a href="#">Appendix B.</a>	Acknowledgements . . . . .	<a href="#">22</a>
	Author's Address . . . . .	<a href="#">22</a>

**[1.](#) Introduction**

In many applications we would like to specify the location of something geographically. Some examples of locations in networking might be the location of data center, a rack in an internet exchange point, a router, a firewall, a port on some device, or it could be the endpoints of a fiber, or perhaps the failure point along a fiber.

Additionally, while this location is typically relative to The Earth, it does not need to be. Indeed it is easy to imagine a network or device located on The Moon, on Mars, on Enceladus (the moon of Saturn) or even a comet (e.g., 67p/churyumov-gerasimenko).

Finally, one can imagine defining locations using different frames of reference or even alternate systems (e.g., simulations or virtual realities).

This document defines a "geo-location" YANG grouping that allows for all of the above data to be captured.

Hopps

Expires September 3, 2019

[Page 2]

This specification conforms to [[ISO.6709.2008](#)].

The YANG data model described in this document conforms to the Network Management Datastore Architecture defined in [[RFC8342](#)].

## **1.1. Terminology**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## **2. The Geo Location Object**

### **2.1. Frame of Reference**

The frame of reference ("reference-frame") defines what the location values refer to and their meaning. The referred to object can be any astronomical body. It could be a planet such as The Earth or Mars, a moon such as Enceladus, an asteroid such as Ceres, or even a comet such as 1P/Halley. This value is specified in "astronomical-body" and is defined by the International Astronomical Union (<<http://www.iau.org>>), The default "astronomical-body" value is "earth".

In addition to identifying the astronomical body we also need to define the meaning of the coordinates (e.g., latitude and longitude) and the definition of 0-height. This is done with a "geodetic-datum" value. The default value for "geodetic-datum" is "wgs-84" (i.e., the World Geodetic System, [[WGS84](#)]), which is used by the Global Positioning System (GPS) among many others. We define an IANA registry for specifying standard values for the "geodetic-datum".

In addition to the "geodetic-datum" value we allow refining the coordinate and height accuracy using "coord-accuracy" and "height-accuracy" respectively. When specified these values override the defaults implied by the "geodetic-datum" value.

Finally, we define an optional feature which allows for changing the system for which the above values are defined. This optional feature adds an "alternate-system" value to the reference frame. This value is normally not present which implies the natural universe is the system. The use of this value is intended to allow for creating virtual realities or perhaps alternate coordinate systems. The definition of alternate systems is outside the scope of this document.



## 2.2. Location

This is the location on or relative to the astronomical object. It is specified using 2 or 3 coordinates values. These values are given either as "latitude", "longitude", and an optional "height", or as Cartesian coordinates of "x", "y" and an optional "z". For the standard location choice "latitude" and "longitude" are specified as fractions of decimal degrees, and the "height" value is in fractions of meters. For the Cartesian choice "x", "y" and "z" are in fractions of meters. In both choices the exact meanings of all of the values are defined by the "geodetic-datum" value in the [Section 2.1](#).

## 2.3. Motion

Support is added for objects in relatively stable motion. For objects in relatively stable motion the grouping provides a 3-dimensional vector value. The components of the vector are "v-north", "v-east" and "v-up" which are all given in fractional meters per second. The values "v-north" and "v-east" are relative to true-north as defined by the reference frame for the astronomical body, "v-up" is perpendicular to the plane defined by "v-north" and "v-east", and is pointed away from the center of mass.

To derive the 2-dimensional heading and speed one would use the following formulas:

$$\text{speed} = \sqrt{v_{\text{north}}^2 + v_{\text{east}}^2}$$

$$\text{heading} = \arctan(v_{\text{east}} / v_{\text{north}})$$

For some applications that demand high accuracy, and where the data is infrequently updated this velocity vector can track very slow movement such as continental drift.

Tracking more complex forms of motion is outside the scope of this work. The intent of the grouping being defined here is to identify where something is located, and generally this is expected to be somewhere on or relative to the Earth (or another astronomical body). At least two options are available to YANG models that wish to use this grouping with objects that are changing location frequently in non-simple ways, they can add additional motion data to their model directly, or if the application allows it can require more frequent queries to keep the location data current.



## 2.4. Nested Locations

When locations are nested (e.g., a building may have a location which houses routers that also have locations) the module using this grouping is free to indicate in its definition that the "reference-frame" is inherited from the containing object so that the "reference-frame" need not be repeated in every instance of location data.

## 2.5. Non-location Attributes

During the development of this module, the question of whether it would support data such as orientation arose. These types of attributes are outside the scope of this grouping because they do not deal with a location but rather describe something more about the object that is at the location. Module authors are free to add these non-location attributes along with their use of this location grouping.

## 2.6. Tree

The following is the YANG tree diagram [RFC8340] for the geo-location grouping.

```
module: geo-location
  +-- geo-location
    +-- reference-frame
      |  +-- alternate-system?    string {alternate-systems}?
      |  +-- astronomical-body?  string
      |  +-- geodetic-system
      |    +-- geodetic-datum?    string
      |    +-- coord-accuracy?    decimal64
      |    +-- height-accuracy?   decimal64
    +-- (location)
      |  +--:(ellipsoid)
      |    |  +-- latitude        degrees
      |    |  +-- longitude       degrees
      |    |  +-- height?         decimal64
      |  +--:(cartesian)
      |    +-- x                  decimal64
      |    +-- y                  decimal64
      |    +-- z?                 decimal64
    +-- velocity
      |  +-- v-north?             decimal64
      |  +-- v-east?             decimal64
      |  +-- v-up?               decimal64
    +-- timestamp?               types:date-and-time
```





### 3. YANG Module

```
<CODE BEGINS> file "ietf-geo-location@2019-02-17.yang"
module ietf-geo-location {
  namespace "urn:ietf:params:xml:ns:yang:ietf-geo-location";
  prefix geo;
  import ietf-yang-types { prefix types; }

  organization
    "IETF NETMOD Working Group (NETMOD)";
  contact
    "Christian Hopps <chopps@chopps.org>";

  // RFC Ed.: replace XXXX with actual RFC number and
  // remove this note.

  description
    "This module defines a grouping of a container object for
    specifying a location on or around an astronomical object (e.g.,
    The Earth).

    Copyright (c) 2018 IETF Trust and the persons identified as
    authors of the code. All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject to
    the license terms contained in, the Simplified BSD License set
    forth in Section 4.c of the IETF Trust's Legal Provisions
    Relating to IETF Documents
    (https://trustee.ietf.org/license-info).

    The key words 'MUST', 'MUST NOT', 'REQUIRED', 'SHALL', 'SHALL
    NOT', 'SHOULD', 'SHOULD NOT', 'RECOMMENDED', 'NOT RECOMMENDED',
    'MAY', and 'OPTIONAL' in this document are to be interpreted as
    described in BCP 14 [RFC2119] [RFC8174] when, and only when,
    they appear in all capitals, as shown here.

    This version of this YANG module is part of RFC XXXX
    (https://tools.ietf.org/html/rfcXXXX); see the RFC itself for
    full legal notices.";

  // RFC Ed.: replace XXXX with actual RFC number and
  // remove this note.

  revision 2019-02-17 {
    description "Initial Revision";
    reference "RFC XXXX: YANG Geo Location";
  }
}
```



```
typedef degrees {
  type decimal64 {
    fraction-digits 16;
  }
  units "decimal degrees";
  description "Coordinate value.";
}

feature alternate-systems {
  description
    "This feature means the device supports specifying locations
    using alternate systems for reference frames.";
}

grouping geo-location {
  description
    "Grouping to identify a location on an astronomical object.";

  container geo-location {
    description
      "A location on an astronomical body (e.g., The Earth)
      somewhere in a universe.";

    container reference-frame {
      description
        "The Frame of Reference for the location values.";

      leaf alternate-system {
        if-feature alternate-systems;
        type string;
        description
          "The system in which the astronomical body and
          geodetic-datum is defined. Normally, this value is not
          present and the system is the natural universe; however,
          when present this value allows for specifying alternate
          systems (e.g., virtual realities). An alternate-system
          modifies the definition (but not the type) of the other
          values in the reference frame.";
      }

      leaf astronomical-body {
        type string {
          pattern
            '[-0-9a-z #x22#x23#x5B#x5D' +
            '!$%&()*+,\.\/:;<=>?@\^_`{|}~]+';
        }
        default "earth";
        description
          "An astronomical body as named by the International
```



```

    Astronomical Union (IAU) or according to the alternate
    system if specified. Examples include 'sun' (our star),
    'earth' (our planet), 'moon' (our moon), 'enceladus' (a
    moon of Saturn), 'ceres' (an asteroid),
    '67p/churyumov-gerasimenko' (a comet). The value should
    be comprised of all lower case ASCII characters not
    including control characters (i.e., values 32..64, and
    91..126)";
}
container geodetic-system {
  description
    "The geodetic system of the location data.";
  leaf geodetic-datum {
    type string {
      pattern
        '[-0-9a-z#x22#x23#x5B#x5D' +
        '!$%&()*+,\.\/:;<=>?@\^_`{|}~]+';
    }
    default "wgs-84";
    description
      "A geodetic-datum defining the meaning of latitude,
      longitude and height. The default is 'wgs-84' which is
      used by the Global Positioning System (GPS)";
  }
  leaf coord-accuracy {
    type decimal64 {
      fraction-digits 6;
    }
    description
      "The accuracy of the latitude longitude pair. When
      coord-accuracy is specified it overrides the
      geodetic-datum implied accuracy. If Cartesian
      coordinates are in use this accuracy corresponds to
      the X and Y components";
  }
  leaf height-accuracy {
    type decimal64 {
      fraction-digits 6;
    }
    units "meters";
    description
      "The accuracy of height value. When specified it
      overrides the geodetic-datum implied default. If
      Cartesian coordinates are in use this accuracy
      corresponds to the Z component.";
  }
}
// May wish to allow for height to be relative.
// If so need to decide if we have a boolean (to ground)

```



```
    // or an enumeration (e.g., local ground, sea-floor,
    // ground floor, containing object, ...) or even allow
    // for a string for most generic but least portable
    // comparable
    // leaf height-relative {
    // }
  }
}
choice location {
  mandatory true;
  description
    "The location data either in lat/long or Cartesian values";
  case ellipsoid {
    leaf latitude {
      type degrees;
      mandatory true;
      description
        "The latitude value on the astronomical body. The
        definition and precision of this measurement is
        indicated by the reference-frame value.";
    }
    leaf longitude {
      type degrees;
      mandatory true;
      description
        "The longitude value on the astronomical body. The
        definition and precision of this measurement is
        indicated by the reference-frame.";
    }
  }
  leaf height {
    type decimal64 {
      fraction-digits 6;
    }
    units "meters";
    description
      "Height from a reference 0 value. The precision and '0'
      value is defined by the reference-frame.";
  }
}
case cartesian {
  leaf x {
    type decimal64 {
      fraction-digits 6;
    }
    mandatory true;
    description
      "The X value as defined by the reference-frame.";
  }
}
```





```
    leaf y {
      type decimal64 {
        fraction-digits 6;
      }
      mandatory true;
      description
        "The Y value as defined by the reference-frame.";
    }
    leaf z {
      type decimal64 {
        fraction-digits 6;
      }
      units "meters";
      description
        "The Z value as defined by the reference-frame.";
    }
  }
}

container velocity {
  description
    "If the object is in motion the velocity vector describes
    this motion at the the time given by the timestamp.";

  leaf v-north {
    type decimal64 {
      fraction-digits 12;
    }
    units "meters per second";
    description
      "v-north is the rate of change (i.e., speed) towards
      truth north as defined by the ~geodetic-system~.";
  }

  leaf v-east {
    type decimal64 {
      fraction-digits 12;
    }
    units "meters per second";
    description
      "v-east is the rate of change (i.e., speed) perpendicular
      to truth-north as defined by the ~geodetic-system~.";
  }

  leaf v-up {
    type decimal64 {
      fraction-digits 12;
    }
    units "meters per second";
  }
}
```



```

        description
          "v-up is the rate of change (i.e., speed) away from the
            center of mass.";
      }
    }
    leaf timestamp {
      type types:date-and-time;
      description "Reference time when location was recorded.";
    }
  }
}
<CODE ENDS>

```

#### 4. ISO 6709:2008 Conformance

[ISO.6709.2008] provides an appendix with a set of tests for conformance to the standard. The tests and results are given in the following table along with an explanation of non-applicable tests.

Test	Description	Pass Explanation
A.1.2.1	elements reqd. for a geo. point location	CRS is always indicated
A.1.2.2	Description of a CRS from a register	CRS register is defined
A.1.2.3	definition of CRS	N/A - Don't define CRS
A.1.2.4	representation of horizontal position	lat/long values conform
A.1.2.5	representation of vertical position	height value conforms
A.1.2.6	text string representation	N/A - No string format

#### Conformance Test Results

For test "A.1.2.1" the YANG geo location object either includes a CRS ("reference-frame") or has a default defined ([[WGS84](#)]).



For "A.1.2.3" we do not define our own CRS, and doing so is not required for conformance.

For "A.1.2.6" we do not define a text string representation, which is also not required for conformance.

## **5. Usability**

The geo-location object defined in this document and YANG module have been designed to be usable in a very broad set of applications. This includes the ability to locate things on astronomical bodies other than The Earth, and to utilize entirely different coordinate systems and realities.

Many systems make use of geo-location data, and so it's important to be able describe this data using this geo-location object defined in this document.

### **5.1. Portability**

In order to verify portability while developing this module the following standards and standard APIs and were considered.

#### **5.1.1. IETF URI Value**

[RFC5870] defines a standard URI value for geographic location data. It includes the ability to specify the "geodetic-value" (it calls this "crs") with the default being "wgs-84" [WGS84]. For the location data it allows 2 to 3 coordinates defined by the "crs" value. For accuracy it has a single "u" parameter for specifying uncertainty. The "u" value is in fractions of meters and applies to all the location values. As the URI is a string, all values are specified as strings and so are capable of as much precision as required.

URI values can be mapped to and from the YANG grouping, with the caveat that some loss of precision (in the extremes) may occur due to the YANG grouping using decimal64 values rather than strings.

#### **5.1.2. W3C**

See <<https://w3c.github.io/geolocation-api/#dom-geolocationposition>>.

W3C Defines a geo-location API in [W3CGEO]. We show a snippet of code below which defines the geo-location data for this API. This is used by many application (e.g., Google Maps API).



```

interface GeolocationPosition {
  readonly attribute GeolocationCoordinates coords;
  readonly attribute DOMTimeStamp timestamp;
};

interface GeolocationCoordinates {
  readonly attribute double latitude;
  readonly attribute double longitude;
  readonly attribute double? altitude;
  readonly attribute double accuracy;
  readonly attribute double? altitudeAccuracy;

  readonly attribute double? speed;
};

```

#### **5.1.2.1. Compare with YANG Model**

Field	Type	YANG	Type
accuracy	double	coord-accuracy	dec64 fr 6
altitude	double	height	dec64 fr 6
altitudeAccuracy	double	height-accuracy	dec64 fr 6
heading	double	heading	dec64 fr 16
latitude	double	latitude	dec64 fr 16
longitude	double	longitude	dec64 fr 16
speed	double	speed	dec64 fr 12
timestamp	DOMTimeStamp	timestamp	string

accuracy (double): Accuracy of "latitude" and "longitude" values in meters.

altitude (double): Optional height in meters above the [\[WGS84\]](#) ellipsoid.

altitudeAccuracy (double): Optional accuracy of "altitude" value in meters.

heading (double): Optional Direction in decimal deg from true north increasing clock-wise.





latitude, longitude (double): Standard lat/long values in decimal degrees.

speed (double): Speed along heading in meters per second.

timestamp (DOMTimeStamp): Specifies milliseconds since the Unix EPOCH in 64 bit unsigned integer. The YANG model defines the timestamp with arbitrarily large precision by using a string which encompasses all representable values of this timestamp value.

W3C API values can be mapped to the YANG grouping, with the caveat that some loss of precision (in the extremes) may occur due to the YANG grouping using decimal64 values rather than doubles.

Conversely, only YANG values for The Earth using the default "wgs-84" [[WGS84](#)] as the "geodetic-datum", can be directly mapped to the W3C values, as W3C does not provide the extra features necessary to map the broader set of values supported by the YANG grouping.

### **5.1.3. Geography Markup Language (GML)**

ISO adopted the Geography Markup Language (GML) defined by OGC 07-036 as [[ISO.19136.2007](#)]. GML defines, among many other things, a position type "gml:pos" which is a sequence of "double" values. This sequence of values represent coordinates in a given CRS. The CRS is either inherited from containing elements or directly specified as attributes "srsName" and optionally "srsDimension" on the "gml:pos".

GML defines an Abstract CRS type which Concrete CRS types derive from. This allows for many types of CRS definitions. We are concerned with the Geodetic CRS type which can have either ellipsoidal or Cartesian coordinates. We believe that other non-Earth based CRS as well as virtual CRS should also be representable by the GML CRS types as well.

Thus GML "gml:pos" values can be mapped directly to the YANG grouping, with the caveat that some loss of precision (in the extremes) may occur due to the YANG grouping using decimal64 values rather than doubles.

Conversely, YANG grouping values can be mapped to GML as directly as the GML CRS available definitions allow with a minimum of Earth-based geodetic systems fully supported.

GML also defines an observation value in "gml:Observation" which includes a timestamp value "gml:validTime" in addition to other components such as "gml:using" "gml:target" and "gml:resultOf". Only the timestamp is mappable to and from the YANG grouping. Furthermore



"gml:validTime" can either be an Instantaneous measure ("gml:TimeInstant") or a time period ("gml:TimePeriod"). Only the instantaneous "gml:TimeInstant" is mappable to and from the YANG grouping.

#### **5.1.4. KML**

KML 2.2 [[KML22](#)] (formerly Keyhole Markup Language) was submitted by Google to Open Geospatial Consortium (OGC) <https://www.opengeospatial.org/> and was adopted. The latest version as of this writing is KML 2.3 [[KML23](#)]. This schema includes geographic location data in some of its objects (e.g., <kml:Point or <kml:Camera> objects). This data is provided in string format and corresponds to the [[W3CGEO](#)] values. The timestamp value is also specified as a string as in our YANG grouping.

KML has some special handling for the height value useful for visualization software, "kml:altitudeMode". These values for "kml:altitudeMode" include indicating the height is ignored ("clampToGround"), in relation to the locations ground level ("relativeToGround"), or in relation to the geodetic datum ("absolute"). The YANG grouping can directly map the ignored and absolute cases, but not the relative to ground case.

In addition to the "kml:altitudeMode" KML also defines two seafloor height values using "kml:seaFloorAltitudeMode". One value is to ignore the height value ("clampToSeaFloor") and the other is relative ("relativeToSeaFloor"). As with the "kml:altitudeMode" value, the YANG grouping supports the ignore case but not the relative case.

The KML location values use a geodetic datum defined in Annex A by the GML Coordinate Reference System (CRS) [[ISO.19136.2007](#)] with identifier "LonLat84\_5773". The altitude value for KML absolute height mode is measured from the vertical datum specified by [[WGS84](#)].

Thus the YANG grouping and KML values can be directly mapped in both directions (when using a supported altitude mode) with the caveat that some loss of precision (in the extremes) may occur due to the YANG grouping using decimal64 values rather than strings. For the relative height cases the application doing the transformation is expected to have the data available to transform the relative height into an absolute height which can then be expressed using the YANG grouping.



## **6. IANA Considerations**

### **6.1. Geodetic System Value Registry**

This registry allocates names for standard geodetic systems. Often these values are referred to using multiple names (e.g., full names or multiple acronyms values). The intent of this registry is to provide a single standard value for any given geodetic system.

The values SHOULD use an acronym when available, they MUST be converted to lower case, and spaces MUST be changed to dashes "-".

Each entry should be sufficient to define the 3 coordinate values (2 if height is not required). So for example the "wgs-84" is defined as WGS-84 with the geoid updated by at least [\[EGM96\]](#) for height values. Specific entries for [\[EGM96\]](#) and [\[EGM08\]](#) are present if a more precise definition of the data is required.

It should be noted that [\[RFC5870\]](#) also creates a registry for Geodetic Systems (it calls CRS); however, this registry has a very strict modification policy. The authors of [\[RFC5870\]](#) have the stated goal of making CRS registration hard to avoid proliferation of CRS values. As our module defines alternate systems and has a broader (beyond earth) scope, the registry defined below is meant to be more easily modified.

TODO: Open question, should we create a new registry here or attempt to modify the one created by [\[RFC5870\]](#). It's worth noting that we include the ability to specify any geodetic system including ones designed for astronomical bodies other than the earth, as well as ones based on alternate systems. These requirements may be too broad for adapting the existing [\[RFC5870\]](#) registry.

TODO: Open question, is FCFS too easy, perhaps expert review would strike a good balance. If expert review is acceptable, would it also be acceptable to update the policy on [\[RFC5870\]](#) and use it instead?

The allocation policy for this registry is First Come First Served, [\[RFC8126\]](#) as the intent is simply to avoid duplicate values.

The initial values for this registry are as follows.



Name	Description
me	Mean Earth/Polar Axis (Moon)
mola-vik-1	MOLA Height, IAU Viking-1 PM (Mars)
wgs-84-96	World Geodetic System 1984 [ <a href="#">WGS84</a> ] w/ EGM96
wgs-84-08	World Geodetic System 1984 [ <a href="#">WGS84</a> ] w/ [ <a href="#">EGM08</a> ]
wgs-84	World Geodetic System 1984 [ <a href="#">WGS84</a> ] (EGM96 or better)

## 7. Security Considerations

This document defines a common geo location grouping using the YANG data modeling language. The grouping itself has no security or privacy impact on the Internet, but the usage of the grouping in concrete YANG modules might have. The security considerations spelled out in the YANG 1.1 specification [[RFC7950](#)] apply for this document as well.

## 8. References

### 8.1. Normative References

- [EGM08] Pavlis, N., Holmes, S., Kenyon, S., and J. Factor, "An Earth Gravitational Model to Degree 2160: EGM08.", 2008, <[http://earth-info.nga.mil/GandG/wgs84/gravitymod/egm2008/egm08\\_wgs84.html](http://earth-info.nga.mil/GandG/wgs84/gravitymod/egm2008/egm08_wgs84.html)>.
- [EGM96] Lemoine, F., Kenyon, S., Factor, J., Trimmer, R., Pavlis, N., Chinn, D., Cox, C., Klosko, S., Luthcke, S., Torrence, M., Wang, Y., Williamson, R., Pavlis, E., Rapp, R., and T. Olson, "The Development of the Joint NASA GSFC and the National Imagery and Mapping Agency (NIMA) Geopotential Model EGM96.", 1998, <<https://cddis.nasa.gov/926/egm96/egm96.html>>.
- [ISO.6709.2008] International Organization for Standardization, "ISO 6709:2008 Standard representation of geographic point location by coordinates.", 2008.





- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8342] Bjorklund, M., Schoenwaelder, J., Shafer, P., Watsen, K., and R. Wilton, "Network Management Datastore Architecture (NMDA)", [RFC 8342](#), DOI 10.17487/RFC8342, March 2018, <<https://www.rfc-editor.org/info/rfc8342>>.
- [WGS84] National Imagery and Mapping Agency., "National Imagery and Mapping Agency Technical Report 8350.2, Third Edition.", 1 2000, <<http://earth-info.nga.mil/GandG/publications/tr8350.2/wgs84fin.pdf>>.

## 8.2. Informative References

- [ISO.19136.2007] International Organization for Standardization, "ISO 19136:2007 Geographic information -- Geography Markup Language (GML)".
- [KML22] Wilson, T., Ed., "OGC KML (Version 2.2)", 4 2008, <[http://portal.opengeospatial.org/files/?artifact\\_id=27810](http://portal.opengeospatial.org/files/?artifact_id=27810)>.
- [KML23] Burggraf, D., Ed., "OGC KML 2.3", 8 2015, <<http://docs.opengeospatial.org/is/12-007r2/12-007r2.html>>.
- [RFC5870] Mayrhofer, A. and C. Spanring, "A Uniform Resource Identifier for Geographic Locations ('geo' URI)", [RFC 5870](#), DOI 10.17487/RFC5870, June 2010, <<https://www.rfc-editor.org/info/rfc5870>>.
- [RFC7950] Bjorklund, M., Ed., "The YANG 1.1 Data Modeling Language", [RFC 7950](#), DOI 10.17487/RFC7950, August 2016, <<https://www.rfc-editor.org/info/rfc7950>>.



- [RFC8340] Bjorklund, M. and L. Berger, Ed., "YANG Tree Diagrams", [BCP 215](#), [RFC 8340](#), DOI 10.17487/RFC8340, March 2018, <<https://www.rfc-editor.org/info/rfc8340>>.
- [W3CGEO] Popescu, A., "Geolocation API Specification", 11 2016, <<https://www.w3.org/TR/2016/REC-geolocation-API-20161108/>>.

## [Appendix A](#). Examples

Below is a fictitious module that uses the geo-location grouping.

```
<CODE BEGINS> file "ietf-uses-geo-location@2019-02-02.yang"
module ietf-uses-geo-location {
  namespace
    "urn:ietf:params:xml:ns:yang:ietf-uses-geo-location";
  prefix ugeo;
  import geo-location { prefix geo; }
  organization "Empty Org";
  contact "Example Author <eauthor@example.com>";
  description "Example use of geo-location";
  revision 2019-02-02 { reference "None"; }
  container locatable-items {
    description "container of locatable items";
    list locatable-item {
      key name;
      description "A of locatable item";
      leaf name {
        type string;
        description "name of locatable item";
      }
      uses geo:geo-location;
    }
  }
}
<CODE ENDS>
```

Below is a the YANG tree for the fictitious module that uses the geo-location grouping.



```
module: ietf-uses-geo-location
  +--rw locatable-items
    +--rw locatable-item* [name]
      +--rw name          string
      +--rw geo-location
        +--rw reference-frame
          | +--rw alternate-system?  string {alternate-systems}?
          | +--rw astronomical-body? string
          | +--rw geodetic-system
          |   +--rw geodetic-datum?  string
          |   +--rw coord-accuracy?  decimal64
          |   +--rw height-accuracy? decimal64
        +--rw (location)
          | +--:(ellipsoid)
          | | +--rw latitude    degrees
          | | +--rw longitude   degrees
          | | +--rw height?     decimal64
          | +--:(cartesian)
          |   +--rw x           decimal64
          |   +--rw y           decimal64
          |   +--rw z?          decimal64
        +--rw velocity
          | +--rw v-north?      decimal64
          | +--rw v-east?       decimal64
          | +--rw v-up?         decimal64
        +--rw timestamp?       types:date-and-time
```

Below is some example YANG XML data for the fictitious module that uses the geo-location grouping.



```
<ns0:config xmlns:ns0="urn:ietf:params:xml:ns:netconf:base:1.0">
  <locatable-items
    xmlns="urn:ietf:params:xml:ns:yang:ietf-uses-geo-location">
    <locatable-item>
      <name>Gaetana's</name>
      <geo-location>
        <latitude>40.73297</latitude>
        <longitude>-74.007696</longitude>
      </geo-location>
    </locatable-item>
    <locatable-item>
      <name>Pont des Arts</name>
      <geo-location>
        <timestamp>2012-03-31T16:00:00Z</timestamp>
        <latitude>48.8583424</latitude>
        <longitude>2.3375084</longitude>
        <height>35</height>
      </geo-location>
    </locatable-item>
    <locatable-item>
      <name>Saint Louis Cathedral</name>
      <geo-location>
        <timestamp>2013-10-12T15:00:00-06:00</timestamp>
        <latitude>29.9579735</latitude>
        <longitude>-90.0637281</longitude>
      </geo-location>
    </locatable-item>
    <locatable-item>
      <name>Apollo 11 Landing Site</name>
      <geo-location>
        <timestamp>1969-07-21T02:56:15Z</timestamp>
        <reference-frame>
          <astronomical-body>moon</astronomical-body>
          <geodetic-system>
            <geodetic-datum>me</geodetic-datum>
          </geodetic-system>
        </reference-frame>
        <latitude>0.67409</latitude>
        <longitude>23.47298</longitude>
      </geo-location>
    </locatable-item>
  </locatable-items>
</ns0:config>
```





## [Appendix B](#). Acknowledgements

We would like to thank Peter Lothberg for the motivation as well as help in defining a more broadly useful geographic location object.

We would also like to thank Acee Lindem and Qin Wu for their work on a geographic location object that led to this documents creation.

### Author's Address

Christian Hopps  
LabN Consulting, L.L.C.

Email: chopps@chopps.org