

Network Working Group S.  
Leontiev  
Internet-Draft P.  
Smirnov  
Intended status: Informational A.  
Chelpanov  
Expires: August 1, 2009 CRYPTO-  
PRO  
January 28,  
2009

**Using GOST 28147-89, GOST R 34.10-2001, and GOST R 34.11-94 Algorithms  
for XML Security  
draft-chudov-cryptopro-cpxmlsig-05**

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on August 1, 2009.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.



Abstract

This document specifies how to use Russian national cryptographic standards GOST 28147-89, GOST R 34.10-2001 and GOST R 34.11-94 with XML Signatures, XML Encryption, WS-SecureConversation, WS-SecurityPolicy and WS-Trust. A number of Uniform Resource Identifiers (URIs) and XML elements are defined.

Table of Contents

- [1.](#) Introduction . . . . . 4
- [2.](#) GOST Cryptographic Algorithms . . . . . 4
- [3.](#) Version and Namespaces . . . . . 4
- [4.](#) XML Schema Preamble and DTD Replacement . . . . . 5
  - [4.1.](#) XML Schema Preamble . . . . . 6
  - [4.2.](#) DTD Replacement . . . . . 6
- [5.](#) Object Identifiers Representation . . . . . 6
- [6.](#) Specifying GOST within XML Signature and XML Encryption . . . 6
  - [6.1.](#) GOST R 34.11-94 Algorithm in DigestMethod . . . . . 7
  - [6.2.](#) GOST R 34.11-94 HMAC Algorithm in SignatureMethod . . . . . 7
  - [6.3.](#) GOST R 34.10-2001 Algorithm in SignatureMethod . . . . . 8
  - [6.4.](#) GOST R 34.10-2001 Public Key in KeyValue . . . . . 8
    - [6.4.1.](#) Key Value Root Element . . . . . 8
    - [6.4.2.](#) Public Key Parameters . . . . . 9
  - [6.5.](#) GOST R 34.10-2001-based Key Agreement Algorithm in AgreementMethod . . . . . 10
  - [6.6.](#) GOST R 34.10-2001-based Key Transport Algorithm in EncryptionMethod . . . . . 11
  - [6.7.](#) GOST 28147-89 Algorithm in EncryptionMethod . . . . . 11
  - [6.8.](#) Symmetric Key Wrap . . . . . 12
    - [6.8.1.](#) GOST 28147-89 Key Wrap in EncryptionMethod . . . . . 12
    - [6.8.2.](#) CryptoPro Key Wrap in EncryptionMethod . . . . .

<a href="#">14</a>	<a href="#">7.</a>	Specifying GOST within WS-* . . . . .
<a href="#">16</a>	<a href="#">7.1.</a>	GOST Algorithm Suite for WS-SecurityPolicy . . . . .
<a href="#">16</a>	<a href="#">7.2.</a>	GOST Key Derivation Algorithm for WS-SecureConversation . . . . .
<a href="#">17</a>	<a href="#">7.3.</a>	GOST Computed Key Mechanism for WS-Trust . . . . .
<a href="#">17</a>	<a href="#">7.4.</a>	Using WS-Trust for TLS Handshake with GOST Algorithm Suite . . . . .
<a href="#">18</a>	<a href="#">8.</a>	Security Considerations . . . . .
<a href="#">19</a>	<a href="#">9.</a>	IANA Considerations . . . . .
<a href="#">19</a>	<a href="#">9.1.</a>	URN Sub-Namespace Registration for urn:ietf:params:xml:ns:cpxmlsec . . . . .
<a href="#">19</a>	<a href="#">9.2.</a>	Schema Registration . . . . .
<a href="#">20</a>	<a href="#">10.</a>	References . . . . .
<a href="#">20</a>	<a href="#">10.1.</a>	Normative references . . . . .
<a href="#">20</a>	<a href="#">10.2.</a>	Informative references . . . . .
<a href="#">23</a>	<a href="#">Appendix A.</a>	Aggregate XML Schema . . . . .
<a href="#">23</a>		

<a href="#">Appendix B</a>	Aggregate DTD . . . . .	
<a href="#">25</a>		
<a href="#">Appendix C</a>	Examples . . . . .	
<a href="#">25</a>		
<a href="#">C.1</a>	Signed document . . . . .	
<a href="#">25</a>		
<a href="#">Appendix D</a>	Acknowledgments . . . . .	
<a href="#">26</a>		
	Authors' Addresses . . . . .	
<a href="#">27</a>		



## **1. Introduction**

This document specifies how to use GOST R 34.10-2001 digital signatures and public keys, GOST R 34.11-94 hash, GOST 28147-89 encryption algorithms with XML Signatures [[XMLDSIG](#)], XML Encryption [[XMLENC-CORE](#)], WS-SecureConversation [[WS-SECURECONVERSATION](#)], WS-SecurityPolicy [[WS-SECURITYPOLICY](#)] and WS-Trust [[WS-TRUST](#)].

This document uses both XML Schemas ([\[XML-SCHEMA-1\]](#), [\[XML-SCHEMA-2\]](#)) (normative) and DTDs [[XML](#)] (informational) to specify the corresponding XML structures.

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[KEYWORDS](#)].

## **2. GOST Cryptographic Algorithms**

Algorithms GOST R 34.10-2001, GOST R 34.11-94 and GOST 28147-89 have been developed by Russian Federal Agency of Governmental Communication and Information (FAGCI) and "All-Russian Scientific and

Research Institute of Standardization". They are described in [[GOSTR341001](#)], [[GOSTR341194](#)] ([\[GOST3431004\]](#) and [\[GOST3431195\]](#)) and [[GOST28147](#)]. RECOMMENDED parameters for those algorithms are described in [[CPALGS](#)].

## **3. Version and Namespaces**

This specification makes no provision for an explicit version number in the syntax. If a future version is needed, it will use a different namespace.

The XML namespace [[XML-NS](#)] URI [[RFC3986](#)] that MUST be used by implementations of this (dated) specification is:

urn:ietf:params:xml:ns:cpxmlsec

The following external XML namespaces are used in this specification (without line breaks; the choice of any namespace prefix is arbitrary and not semantically significant):

<http://www.w3.org/2000/09/xmlsig#>

Prefix:  
dsig





Specification:

[\[XMLDSIG\]](#)

<http://www.w3.org/2001/04/xmlenc#>

Prefix:

xenc

Specification:

[\[XMLENC-CORE\]](#)

<http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702>

Prefix:

sp

Specification:

[\[WS-SECURITYPOLICY\]](#)

<http://www.w3.org/ns/ws-policy>

Prefix:

wsp

Specification:

[\[WS-POLICY\]](#)

<http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512>

Prefix:

wsc

Specification:

[\[WS-SECURECONVERSATION\]](#)

[http://docs.oasis-open.org/wss/2004/01/  
oasis-200401-wss-wssecurity-secext-1.0.xsd](http://docs.oasis-open.org/wss/2004/01/oasis-200401-wss-wssecurity-secext-1.0.xsd)

Prefix:

wsse

Specification:

[\[WS-SECURITY\]](#)

<http://docs.oasis-open.org/ws-sx/ws-trust/200512/>

Prefix:

wst

Specification:

[\[WS-TRUST\]](#)

In the remaining sections of this document elements in the external namespaces are marked as such by using the namespace prefixes defined above.

#### **4. XML Schema Preamble and DTD Replacement**



#### **4.1. XML Schema Preamble**

The subsequent preamble is to be used with the XML Schema definitions given in the remaining sections of this document.

```
<xs:schema
  xmlns:cpxmlsec="urn:ietf:params:xml:ns:cpxmlsec"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:sp=
    "http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702"
  targetNamespace="urn:ietf:params:xml:ns:cpxmlsec"
  elementFormDefault="qualified"
  version="0.4">
```

#### **4.2. DTD Replacement**

In order to include GOST XML-signature syntax, the following definition of the entity Key.ANY SHOULD replace the one in [\[XMLDSIG\]](#):

```
<!ENTITY % KeyValue.ANY '| cpxmlsec:GOSTKeyValue'>
```

### **5. Object Identifiers Representation**

Object Identifiers (OIDs) are included in XML by the corresponding URN value as defined in [\[URN\\_OID\]](#).

The subsequent type is to be used to define algorithm parameters by OIDs:

```
<xs:simpleType name="ObjectIdentifierType">
  <xs:restriction base="xs:anyURI">
    <xs:pattern value=
      "urn:oid:(([0-1]\.[1-3]?\d)|(2\.\d+))(\.\d+)*" />
    </xs:restriction>
  </xs:simpleType>
```

### **6. Specifying GOST within XML Signature and XML Encryption**

This section specifies the details of how to use GOST algorithms with

XML Signature Syntax and Processing [\[XMLDSIG\]](#) and XML Encryption Syntax and Processing [\[XMLENC-CORE\]](#). It relies heavily on syntaxes and namespaces defined in [\[XMLDSIG\]](#) and [\[XMLENC-CORE\]](#).



### **6.1. GOST R 34.11-94 Algorithm in DigestMethod**

The identifier for the GOST R 34.11-94 digest algorithm is:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr3411
```

The dsig:DigestMethod node may contain a child node cpxmlsec:ParametersR3411 specifying parameters for GOST R 34.11-94 algorithm. cpxmlsec:ParametersR3411 node contains one OID specified in [section 8.2 \[CPALGS\]](#). If cpxmlsec:ParametersR3411 node is missing, the application should infer algorithm parameters from other sources.

If the application omits cpxmlsec:ParametersR3411 node, it SHOULD use parameters defined by id-GostR3411-94-CryptoProParamSet (see [Section 11.2 of \[CPALGS\]](#)).

Schema Definition:

```
<xs:element name="ParametersR3411"
            type="cpxmlsec:ObjectIdentifierType"/>
```

DTD Definition:

```
<!ELEMENT ParametersR3411 (#PCDATA) >
```

An example of a GOST R 34.11-94 dsig:DigestMethod node is:

```
<dsig:DigestMethod dsig:Algorithm=
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr3411">
  <!-- id-GostR3411-94-CryptoProParamSet -->
  <cpxmlsec:ParametersR3411>urn:oid:1.2.643.2.2.30.1<
  /cpxmlsec:ParametersR3411>
</dsig:DigestMethod>
```

A GOST R 34.11-94 digest is a 256-bit string. The content of the dsig:DigestValue element shall be the base64 [\[RFC4648\]](#) encoding of this bit string viewed as a 32-octet octet stream.

### **6.2. GOST R 34.11-94 HMAC Algorithm in SignatureMethod**

GOST R 34.11-94 can also be used in HMAC [\[HMAC\]](#) as described in section 6.3.1 of [\[XMLDSIG\]](#). Identifier:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:hmac-gostr3411
```

The dsig:SignatureMethod node may contain a child node cpxmlsec:ParametersR3411 specifying parameters for GOST R 34.11-94 algorithm. cpxmlsec:ParametersR3411 node syntax and processing in this case are



equivalent to the ones in dsig:DigestMethod case.

An example of a GOST R 34.11-94 HMAC dsig:SignatureMethod node is:

```
<dsig:SignatureMethod dsig:Algorithm=
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:hmac-gostr3411">
  <!-- id-GostR3411-94-CryptoProParamSet -->
  <cpxmlsec:ParametersR3411>urn:oid:1.2.643.2.2.30.1<
  /cpxmlsec:ParametersR3411>
</dsig:SignatureMethod>
```

The output of the GOST R 34.11-94 HMAC algorithm is ultimately the output of the GOST R 34.11-94 digest algorithm. This value shall be base64 [[RFC4648](#)] encoded for the dsig:SignatureValue in the same straightforward fashion as the output of the digest algorithm.

### **6.3. GOST R 34.10-2001 Algorithm in SignatureMethod**

The input to the GOST R 34.10-2001 algorithm is the canonicalized representation of the dsig:SignedInfo element as specified in [Section 3](#) of [[XMLDSIG](#)].

The identifier for the GOST R 34.10-2001 signature algorithm is (without line break):

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr34102001-
gostr3411
```

An example of a GOST R 34.10-2001 dsig:SignatureMethod node is (without line break in attribute value):

```
<dsig:SignatureMethod dsig:Algorithm=
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr34102001-
  gostr3411" />
```

GOST R 34.10-2001 signature is a 64-octet value as described in section 2.2 of [[CPPK](#)]. The content of the dsig:SignatureValue element shall be the base64 [[RFC4648](#)] encoding of this value.

### **6.4. GOST R 34.10-2001 Public Key in KeyValue**

#### **6.4.1. Key Value Root Element**

GOST R 34.10-2001 public key can be transmitted in cpxmlsec:GOSTKeyValue node. It is included in dsig:KeyValue node just like dsig:RSAKeyValue or xenc:DHKeyValue.

cpxmlsec:GOSTKeyValue node consists of an optional child node cpxmlsec:PublicKeyParameters and a mandatory child node cpxmlsec:





PublicKey. If cpxmlsec:PublicKeyParameters node is missing, the application should infer parameters from other sources.

Schema Definition:

```
<xs:element name="GOSTKeyValue"
            type="cpxmlsec:KeyValue" />

<xs:complexType name="KeyValue" >
  <xs:sequence >
    <xs:element name="PublicKeyParameters"
                type="cpxmlsec:PublicKeyParameters"
                minOccurs="0" />
    <xs:element name="PublicKey" type="xs:base64Binary" />
  </xs:sequence >
</xs:complexType >
```

DTD Definition:

```
<!ELEMENT GOSTKeyValue (
    PublicKeyParameters?, PublicKey) >
<!ELEMENT PublicKey (#PCDATA) >
```

If the application omits cpxmlsec:PublicKeyParameters node, it SHOULD use parameters identified by DefaultPublicKeyParameters.

DefaultPublicKeyParameters:

```
<cpxmlsec:PublicKeyParameters>
  <!-- id-GostR3410-2001-CryptoPro-A-ParamSet -->
  <cpxmlsec:publicKeyParamSet>urn:oid:1.2.643.2.2.35.1</cpxmlsec:publicKeyParamSet>
  <!-- id-GostR3411-94-CryptoProParamSet -->
  <cpxmlsec:digestParamSet>urn:oid:1.2.643.2.2.30.1</cpxmlsec:digestParamSet>
  <!-- id-Gost28147-89-CryptoPro-A-ParamSet -->
  <cpxmlsec:encryptionParamSet>urn:oid:1.2.643.2.2.31.1</cpxmlsec:encryptionParamSet>
</cpxmlsec:PublicKeyParameters>
```

#### **6.4.2. Public Key Parameters**

cpxmlsec:PublicKeyParameters node contains three OIDs: cpxmlsec:publicKeyParamSet, cpxmlsec:digestParamSet and optional cpxmlsec:encryptionParamSet. Parameter values corresponding to these OIDs can be found in [[CPALGS](#)].



Schema Definition:

```
<xs:complexType name="PublicKeyParametersType">
  <xs:sequence>
    <xs:element name="publicKeyParamSet"
      type="cpxmlsec:ObjectIdentifierType"/>
    <xs:element name="digestParamSet"
      type="cpxmlsec:ObjectIdentifierType"/>
    <xs:element name="encryptionParamSet"
      type="cpxmlsec:ObjectIdentifierType"
      minOccurs="0"/>
  </xs:sequence>
</xs:complexType>
```

DTD Definition:

```
<!ELEMENT PublicKeyParameters (
  publicKeyParamSet, digestParamSet,
  encryptionParamSet?) >
<!ELEMENT publicKeyParamSet (#PCDATA) >
<!ELEMENT digestParamSet (#PCDATA) >
<!ELEMENT encryptionParamSet (#PCDATA) >
```

#### **6.5. GOST R 34.10-2001-based Key Agreement Algorithm in AgreementMethod**

Key agreement algorithm based on GOST R 34.10-2001 public keys (see Section 5 of [CPALGS]) involves the derivation of shared secret information using keys from the sender and recipient.

The identifier for the key agreement algorithm based on GOST R 34.10-2001 is:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:agree-gost2001
```

An example of a GOST R 34.10-2001-based key agreement AgreementMethod node is:

```
<xenc:AgreementMethod xenc:Algorithm=
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:agree-gost2001">
  <xenc:KA-Nonce>...</xenc:KA-Nonce>
  <xenc:OriginatorKeyInfo>
    <dsig:X509Data><dsig:X509Certificate>
      ...
    </dsig:X509Certificate></dsig:X509Data>
  </xenc:OriginatorKeyInfo>
  <xenc:RecipientKeyInfo><dsig:KeyValue>
    ...
  </dsig:KeyValue></xenc:RecipientKeyInfo>
```



</xenc:AgreementMethod>

The shared keying material for algorithm based on GOST R 34.10-2001 needed will be calculated as a result of function VKO GOST R 34.10-2001 (see Section 5.2 of [CPALGS]), which generates GOST KEK using two GOST R 34.10-2001 keypairs and UKM. xenc:KA-Nonce node of xenc:AgreementMethod contains base64 encoded 64-bits value of UKM, if UKM is used.

#### **6.6. GOST R 34.10-2001-based Key Transport Algorithm in EncryptionMethod**

The key transport algorithm based on VKO GOST R 34.10-2001, specified in [CPALGS], is public key encryption algorithms, that MUST be used for key encryption/decryption only.

The identifier for the key transport algorithm based on VKO GOST R 34.10-2001 is:

urn:ietf:params:xml:ns:cpxmlsec:algorithms:transport-gost2001

An example of a VKO GOST R 34.10-2001-based key transport EncryptedKey node is:

```
<xenc:EncryptedKey>
  <xenc:EncryptionMethod xenc:Algorithm=
"urn:ietf:params:xml:ns:cpxmlsec:algorithms:transport-gost2001" />
  <dsig:KeyInfo>
    <dsig:X509Data><dsig:X509Certificate>
      ...
    </dsig:X509Certificate></dsig:X509Data>
  </dsig:KeyInfo>
  <xenc:CipherData>
    <xenc:CipherValue>...</xenc:CipherValue>
  </xenc:CipherData>
</xenc:EncryptedKey>
```

The CipherValue for such encrypted key is the base64 encoding of the [X.208-88] DER encoding of a GostR3410-KeyTransport structure (see section 4.2.1 of [CPCMS]).

#### **6.7. GOST 28147-89 Algorithm in EncryptionMethod**

The identifier for the GOST 28147-89 symmetric encryption algorithm is:



urn:ietf:params:xml:ns:cpxmlsec:algorithms:gost28147

The xenc:EncryptionMethod node may contain a child node cpxmlsec:Parameters28147 specifying parameters for GOST 28147-89 algorithm. cpxmlsec:Parameters28147 specifies the set of corresponding Gost28147-89-ParamSetParameters (see Section 8.1 of [CPALGS]). Encryption mode is specified by mode parameter of Gost28147-89-ParamSetParameters structure. CFB and CNT modes are RECOMMENDED to use. If cpxmlsec:Parameters28147 node is missing, the application should infer algorithm parameters from other sources.

If the application omits cpxmlsec:Parameters28147 node, it SHOULD use parameters defined by id-Gost28147-89-CryptoPro-A-ParamSet (see Section of 10.2 [CPALGS]).

Schema Definition:

```
<xs:element name="Parameters28147"
            type="cpxmlsec:ObjectIdentifierType" />
```

DTD Definition:

```
<!ELEMENT Parameters28147 (#PCDATA) >
```

An example of a GOST 28147-89 xenc:EncryptionMethod node is:

```
<xenc:EncryptionMethod dsig:Algorithm=
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:gost28147">
  <!-- id-Gost28147-89-CryptoPro-A-ParamSet -->
  <cpxmlsec:Parameters28147>urn:oid:1.2.643.2.2.31.1<
  /cpxmlsec:Parameters28147>
</xenc:EncryptionMethod>
```

256-bit key, 64-bit Initialization Vector (IV), and optional parameters are used in GOST 28147-89 encryption algorithm. The resulting cipher text is prefixed by the IV. If included in XML output, it is then base64 encoded.

## **6.8. Symmetric Key Wrap**

Symmetric Key Wrap algorithms considered in this section are shared secret key encryption algorithms that MUST be used for symmetric keys encryption/decryption only.

### **6.8.1. GOST 28147-89 Key Wrap in EncryptionMethod**

The GOST 28147-89 Key Wrap algorithm wraps (encrypts) a key (the wrapped key, WK) under a GOST 28147-89 Key Wrap (specified in





sections [6.1](#), [6.2](#) of [[CPALGS](#)]).

Note: This algorithm MUST NOT be used without key agreement algorithm, because such WK is constant for every wrapping-encrypting pair. Encrypting many different keys with the same constant WK may reveal that WK. The only key agreement algorithm possible to use with GOST 28147-89 Key Wrap defined by this specification is a GOST R 34.10-2001-based key agreement (see [Section 6.5](#)).

The identifier for the GOST 28147-89 Key Wrap algorithm is:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:kw-gost
```

The CipherValue for such wrapped key is the base64 encoding of the [[X.208-88](#)] DER encoding of a GostR3410-KeyWrap structure.

ASN.1 structure:

```
GostR3410-KeyWrap ::=
  SEQUENCE {
    encryptedKey Gost28147-89-EncryptedKey,
    encryptedParameters Gost28147-89-KeyWrapParameters
  }
```



An example of a GOST 28147-89 Key Wrap EncryptedData node is:

```
<xenc:EncryptedData>
  <xenc:EncryptionMethod dsig:Algorithm=
    "urn:ietf:params:xml:ns:cpxmlsec:algorithms:gost28147" />
  <dsig:KeyInfo>
    <xenc:EncryptedKey>
      <xenc:EncryptionMethod xenc:Algorithm=
        "urn:ietf:params:xml:ns:cpxmlsec:algorithms:kw-gost" />
      <dsig:KeyInfo>
        <xenc:AgreementMethod xenc:Algorithm=
          "urn:ietf:params:xml:ns:cpxmlsec:algorithms:agree-gost2001">
          <xenc:KA-Nonce>...</xenc:KA-Nonce>
          <xenc:OriginatorKeyInfo>
            <dsig:X509Data><dsig:X509Certificate>
              ...
            </dsig:X509Certificate></dsig:X509Data>
          </xenc:OriginatorKeyInfo>
          <xenc:RecipientKeyInfo><dsig:KeyValue>
            ...
          </dsig:KeyValue></xenc:RecipientKeyInfo>
        </xenc:AgreementMethod>
      </dsig:KeyInfo>
    <xenc:CipherData>
      <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
  </xenc:EncryptedKey>
</dsig:KeyInfo>
<xenc:CipherData>
  <xenc:CipherValue>...</xenc:CipherValue>
</xenc:CipherData>
</xend:EncryptedData>
```

Gost28147-89-KeyWrapParameters is described in section 4.1.1 of [\[CPCMS\]](#). The xenc:KA-Nonce node value of the xenc:AgreementMethod node MUST be used as ukm.

The resulting wrapped key (WK) is placed in the Gost28147-89-EncryptedKey encryptedKey field, its mac (CEK\_MAC) is placed in the Gost28147-89-EncryptedKey macKey field. ukm field of Gost28147-89-KeyWrapParameters MUST be absent.

### **6.8.2. CryptoPro Key Wrap in EncryptionMethod**

The CryptoPro Key Wrap algorithm wraps (encrypts) a key (wrapped key,

WK) under a CryptoPro Key Wrap (specified in sections [6.3](#), [6.4](#) of [\[CPALGS\]](#)).



The identifier for the CryptoPro Key Wrap algorithms is:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:kw-cp
```

The CipherValue for such wrapped key is the base64 encoding of the [X.208-88] DER encoding of a GostR3410-KeyWrap structure (see [Section 6.8.1](#)).

An example of a CryptoPro Key Wrap EncryptedData node is:

```
<xenc:EncryptedData>
  <xenc:EncryptionMethod dsig:Algorithm=
    "urn:ietf:params:xml:ns:cpxmlsec:algorithms:gost28147" />
  <dsig:KeyInfo>
    <xenc:EncryptedKey>
      <xenc:EncryptionMethod xenc:Algorithm=
        "urn:ietf:params:xml:ns:cpxmlsec:algorithms:kw-cp" />
      <dsig:KeyInfo>
        <dsig:KeyName>John Smith</dsig:KeyName>
      </dsig:KeyInfo>
    <xenc:CipherData>
      <xenc:CipherValue>...</xenc:CipherValue>
    </xenc:CipherData>
    </xenc:EncryptedKey>
  </dsig:KeyInfo>
  <xenc:CipherData>
    <xenc:CipherValue>...</xenc:CipherValue>
  </xenc:CipherData>
</xenc:EncryptedData>
```

The resulting wrapped key (WK) is placed in the Gost28147-89-EncryptedKey encryptedKey field, its mac (CEK\_MAC) is placed in the Gost28147-89-EncryptedKey macKey field.

If CryptoPro Key Wrap algorithm is combined with Key Agreement Algorithm, the xenc:KA-Nonce node value of the xenc:AgreementMethod node MUST be used as ukm. ukm field of Gost28147-89-KeyWrapParameters type must be absent.

Note: The only key agreement algorithm possible to use with CryptoPro Key Wrap defined by this specification is a GOST R 34.10-2001-based key agreement (see [Section 6.5](#)).

If CryptoPro Key Wrap algorithm is not combined with Key Agreement Algorithm, ukm field of Gost28147-89-KeyWrapParameters type MUST be present.



## 7. Specifying GOST within WS-\*

This section specifies the details of how to use GOST algorithms with

WS-SecureConversation [[WS-SECURECONVERSATION](#)], WS-SecurityPolicy [[WS-SECURITYPOLICY](#)] and WS-Trust [[WS-TRUST](#)].

### 7.1. GOST Algorithm Suite for WS-SecurityPolicy

This specification defines a new possible value for an [Algorithm Suite] property of a Security Binding (see section 6.1 of [[WS-SECURITYPOLICY](#)]). The new value is BasicGost.

BasicGost Algorithm Suite defines the following values for operations

and properties (without line breaks in URIs):

- [Sym Sig]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:hmac-gostr3411
- [Asym Sig]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr34102001-gostr3411
- [Dig]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:gostr3411
- [Enc]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:gost28147
- [Sym KW]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:kw-cp
- [Asym KW]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:transport-gost2001
- [Comp Key]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:dk-p-gostr3411
- [Enc KD]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:dk-p-gostr3411
- [Sig KD]  
urn:ietf:params:xml:ns:cpxmlsec:algorithms:dk-p-gostr3411
- [Min SKL]  
256
- [Max SKL]  
256
- [Min AKL]  
512
- [Max AKL]  
512

Note: For definition of [Comp Key], [Enc KD] and [Sig KD] algorithm see [Section 7.2](#)

To indicate a requirement to use GOST Algorithm Suite defined above conforming implementations MUST place cpxmlsec:BasicGost node in sp:AlgorithmSuite Assertion (see section 7.1 of [[WS-SECURITYPOLICY](#)]).





Schema Definition:

```
<xs:element name="BasicGost"  
            type="sp:QNameAssertionType"/>
```

DTD Definition:

```
<!ELEMENT BasicGost EMPTY >
```

An example of a GOST Algorithm Suite in sp:AlgorithmSuite Assertion is:

```
<sp:AlgorithmSuite>  
  <wsp:Policy>  
    <cpxmlsec:BasicGost/>  
  </wsp:Policy>  
</sp:AlgorithmSuite>
```

## **7.2. GOST Key Derivation Algorithm for WS-SecureConversation**

This specification defines a new possible value for an Algorithm attribute of a wsc:DerivedKeyToken node (see section 7 of [\[WS-SECURECONVERSATION\]](#)).

The new key derivation algorithm identifier is:

```
urn:ietf:params:xml:ns:cpxmlsec:algorithms:dk-p-gostr3411
```

An example of a GOST Key Derivation Algorithm in wsc:DerivedKeyToken node is:

```
<wsc:DerivedKeyToken Algorithm=  
  "urn:ietf:params:xml:ns:cpxmlsec:algorithms:dk-p-gostr3411">  
  <wsse:SecurityTokenReference>...</wsse:SecurityTokenReference>  
  <wsc:Nonce>...</wsc:Nonce>  
</wsc:DerivedKeyToken>
```

GOST Key Derivation Algorithm uses a pseudorandom function P\_GOSTR3411 (see section 4 of [\[CPALGS\]](#)) to derive keys just like a P\_SHA-1 function is used in [\[WS-SECURECONVERSATION\]](#) (see [section 7](#)).

## **7.3. GOST Computed Key Mechanism for WS-Trust**

This specification defines a new possible value for a wst:ComputedKey node (see section 4.4.4 of [\[WS-TRUST\]](#)).

The new computed key mechanism identifier is:



urn:ietf:params:xml:ns:cpxmlsec:algorithms:ck-p-gostr3411

An example of a GOST Computed Key Mechanism in wst:ComputedKey node (without line breaks) is:

```
<wst:ComputedKey>  
  urn:ietf:params:xml:ns:cpxmlsec:algorithms:ck-p-gostr3411  
</wst:ComputedKey>
```

GOST Computed Key Mechanism uses a pseudorandom function P\_GOSTR3411 (see section 4 of [CPALGS]) to compute a key just like a P\_SHA-1 function is used in [WS-TRUST] (see section 4.4.4). It is REQUIRED that EntREQ and EntRES are strings of length 256 bits.

#### **7.4. Using WS-Trust for TLS Handshake with GOST Algorithm Suite**

This specification defines how to use WS-Trust ([WS-TRUST]) to perform TLS Handshake (see [TLS]) and establish secure session for GOST Algorithm Suite.

WS-Trust can be used to do TLS Handshake as specified in [WS-TRUST-TLS]. The outcome of the protocol under discussion is a new session key issued using a secure session established by TLS Handshake. Issued session key is intended to secure further communication by means of WS-Security ([WS-SECURITY]).

If application is required to use GOST Algorithm Suite after performing TLS Handshake by WS-Trust it MUST use one of GOST  
28147-89

Cipher Suites for TLS (see [draft.CPTLS]).

The main flow of TLS Negotiation over WS-Trust defined in this specification complies with [WS-TRUST-TLS], but there are a few differences specified below that MUST be obeyed.

The paragraph R4305 (see section 4.3 of [WS-TRUST-TLS]) MUST be replaced with the following text:

The responder is responsible for issuing the key associated with the TLSNego session. If the initiator requested properties for the generated key (e.g. key size) in the initial RST message, the generated key SHOULD match those requirements. The issued key MUST be communicated back to the initiator using the wst:RequestedProofToken element and MUST be protected using CryptoPro Key Wrap algorithm (see section 6.3 of [CPALGS]) where server\_write\_key (see section 6.3 of [TLS]) is a wrapping key. Wrapped key is contained in the <xenc:CipherData><xenc:CipherValue>...</xenc:CipherValue></xenc:CipherData> elements of the xenc:EncryptedKey.



GOST R 34.11-94 and P\_GOSTR3411 algorithms MUST be used instead of SHA1 and PSHA1 algorithms correspondingly to compute authenticator (see section 4.9 of [[WS-TRUST-TLS](#)]).

## **8. Security Considerations**

Conforming applications MUST use unique values for ukm and iv. Recipients MAY verify that ukm and iv specified by the sender are unique.

Applications SHOULD verify signature values, subject public keys and algorithm parameters to conform to [[GOSTR341001](#)], standard before using them.

Cryptographic algorithm parameters affect algorithm strength. Using parameters not listed in [[CPALGS](#)] is NOT RECOMMENDED (see the Security Considerations section of [[CPALGS](#)]).

Using the same key for signature and key derivation is NOT RECOMMENDED.

It is NOT RECOMMENDED to use XML encryption without XML signature or HMAC.

## **9. IANA Considerations**

This document uses URNs to describe XML namespaces and XML schemas conforming to a registry mechanism described in [[RFC3688](#)]. IANA has registered two URI assignments.

### **9.1. URN Sub-Namespace Registration for urn:ietf:params:xml:ns:cpxmlsec**

URI: urn:ietf:params:xml:ns:cpxmlsec

Registrant Contact:

Mikhail V. Pavlov  
CRYPTO-PRO, Ltd.  
16/5, Sushevskij val  
Moscow, 127018  
Russia  
Phone: +7 (495) 780 4820  
Fax: +7 (495) 660 2330  
Email: pav@CryptoPro.ru  
URI: <http://www.CryptoPro.ru>

XML: None. Namespace URIs do not represent an XML specification.



## **9.2. Schema Registration**

URI: urn:ietf:params:xml:schema:cpxmlsec

Registrant Contact:

Mikhail V. Pavlov  
CRYPTO-PRO, Ltd.  
16/5, Sushevskij val  
Moscow, 127018  
Russia  
Phone: +7 (495) 780 4820  
Fax: +7 (495) 660 2330  
Email: pav@CryptoPro.ru  
URI: <http://www.CryptoPro.ru>

XML: The XML can be found in [Appendix A](#).

## **10. References**

### **10.1. Normative references**

- [CPALGS] Popov, V., Kurepkin, I., and S. Leontiev, "Additional Cryptographic Algorithms for Use with GOST 28147-89, GOST R 34.10-94, GOST R 34.10-2001, and GOST R 34.11-94 Algorithms", [RFC 4357](#), January 2006.
- [CPCMS] Leontiev, S. and G. Chudov, "Using the GOST 28147-89, GOST R 34.11-94, GOST R 34.10-94, and GOST R 34.10-2001 Algorithms with Cryptographic Message Syntax (CMS)", [RFC 4490](#), May 2006.
- [CPPK] Leontiev, S. and D. Shefanovski, "Using the GOST R 34.10-94, GOST R 34.10-2001, and GOST R 34.11-94 Algorithms with the Internet X.509 Public Key Infrastructure Certificate and CRL Profile", [RFC 4491](#), May 2006.
- [GOST28147] Government Committee of the USSR for Standards, "Cryptographic Protection for Data Processing System, Gosudarstvennyi Standard of USSR (In Russian)", GOST 28147-89, 1989.
- [GOST3431004] Council for Standardization, Metrology and Certification of the Commonwealth of Independence States (EASC), Minsk, "Information technology. Cryptographic Data Security.





Formation and verification processes of (electronic) digital signature based on Asymmetric Cryptographic Algorithm (In Russian)", GOST 34.310-2004, 2004.

[GOST3431195]

Council for Standardization, Metrology and Certification of the Commonwealth of Independence States (EASC), Minsk, "Information technology. Cryptographic Data Security. Cashing function (In Russian)", GOST 34.311-95, 1995.

[GOSTR341001]

Government Committee of the Russia for Standards, "Information technology. Cryptographic Data Security. Signature and verification processes of [electronic] digital signature, Gosudarstvennyi Standard of Russian Federation (In Russian)", GOST R 34.10-2001, 2001.

[GOSTR341194]

Government Committee of the Russia for Standards, "Information technology. Cryptographic Data Security. Hashing function, Gosudarstvennyi Standard of Russian Federation (In Russian)", GOST R 34.11-94, 1994.

[HMAC]

Krawczyk, H., Bellare, M., and R. Canetti, "HMAC: Keyed-Hashing for Message Authentication", [RFC 2104](#), February 1997.

[KEYWORDS]

Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.

[RFC3688]

Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

[RFC3986]

Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), January 2005.

[RFC4648]

Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), October 2006.

[TLS]

Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", [RFC 5246](#), August 2008.

[WS-POLICY]

Vedamuthu, A., Orchard, D., Hirsch, F., Hondo, M., Yendluri, P., Boubez, T., and Ue. Yalcinalp, "Web



Policy 1.5 - Framework", W3C REC-ws-policy,  
September 2007, <<http://www.w3.org/TR/ws-policy/>>.

[WS-SECURECONVERSATION]

Lawrence, K. and C. Kaler, "WS-SecureConversation 1.3",  
OASIS Standard ws-secureconversation-1.3-os, March 2007,

<

[http://docs.oasis-open.org/ws-sx/ws-secureconversation/  
200512/ws-secureconversation-1.3-os.html](http://docs.oasis-open.org/ws-sx/ws-secureconversation/200512/ws-secureconversation-1.3-os.html)>.

[WS-SECURITY]

Lawrence, K. and C. Kaler, "Web Services Security: SOAP  
Message Security 1.1 (WS-Security 2004)", OASIS  
Standard wss-v1.1-spec-os-SOAPMessageSecurity,  
February 2006, <[http://docs.oasis-open.org/wss/v1.1/  
wss-v1.1-spec-os-SOAPMessageSecurity.pdf](http://docs.oasis-open.org/wss/v1.1/wss-v1.1-spec-os-SOAPMessageSecurity.pdf)>.

[WS-SECURITYPOLICY]

Lawrence, K. and C. Kaler, "WS-SecurityPolicy 1.2", OASIS  
Standard ws-securitypolicy-1.2-spec-os, July 2007,

<http://

[/docs.oasis-open.org/ws-sx/ws-securitypolicy/200702/  
ws-securitypolicy-1.2-spec-os.html](http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702/ws-securitypolicy-1.2-spec-os.html)>.

[WS-TRUST]

Lawrence, K. and C. Kaler, "WS-Trust 1.3", OASIS  
Standard ws-trust-1.3-os, March 2007, <[http://  
docs.oasis-open.org/ws-sx/ws-trust/200512/  
ws-trust-1.3-os.html](http://docs.oasis-open.org/ws-sx/ws-trust/200512/ws-trust-1.3-os.html)>.

[WS-TRUST-TLS]

Alexander, J., Della-Libera, G., Gajjala, V., Gavrylyuk,  
K., Kaler, C., McIntosh, M., Nadalin, A., Rich, B., and

T.

Vishwanath, "Application Note: Using WS-Trust for TLS  
Handshake", September 2007, <[http://  
download.boulder.ibm.com/ibmdl/pub/software/dw/specs/  
ws-trust/WSTrustForTLS-final.pdf](http://download.boulder.ibm.com/ibmdl/pub/software/dw/specs/ws-trust/WSTrustForTLS-final.pdf)>.

[X.208-88]

International International Telephone and Telegraph  
Consultative Committee, "Specification of Abstract Syntax  
Notation One (ASN.1)", CCITT Recommendation X.208,  
November 1988.

[XML-NS]

Bray, T., Hollander, D., Layman, A., and R. Tobin,  
"Namespaces in XML (Second Edition)", W3C REC-xml-names,  
August 2006,  
<<http://www.w3.org/TR/REC-xml-names-20060816>>.

[XML-SCHEMA-1]



Thompson, H., Beech, D., Maloney, M., and N. Mendelsohn,  
"XML Schema Part 1: Structures Second Edition", W3C REC-  
xmlschema-1, October 2004,  
<<http://www.w3.org/TR/2004/REC-xmlschema-1-20041028/>>.

[XML-SCHEMA-2]

Biron, P. and A. Malhotra, "XML Schema Part 2: Datatypes  
Second Edition", W3C REC-xmlschema-2, October 2004,  
<<http://www.w3.org/TR/2004/REC-xmlschema-2-20041028/>>.

[XMLDSIG]  
Markup

Eastlake, D., Reagle, J., and D. Solo, "(Extensible  
Language) XML-Signature Syntax and Processing", [RFC  
3275](#),  
March 2002.

[XMLENC-CORE]

Eastlake, D. and J. Reagle, "XML Encryption Syntax and  
Processing", W3C Candidate Recommendation xmlenc-core,  
August 2002, <<http://www.w3.org/TR/xmlenc-core/>>.

[draft.CPTLS]

Afanasiev, A., Nikishin, N., Izotov, B., Minaeva, E.,  
Murugov, S., Ustinov, I., Erkin, A., Chudov, G., and S.  
Leontiev, "GOST 28147-89 Cipher Suites for Transport  
Layer  
Security (TLS)", [draft-chudov-cryptopro-cptls-04](#) (work in  
progress), December 2008.

## [10.2.](#) Informative references

[RFC4134] Hoffman, P., "Examples of S/MIME Messages", [RFC 4134](#),  
July 2005.

[URNOID] Mealling, M., "A URN Namespace of Object Identifiers",  
[RFC 3061](#), February 2001.

[XML] Bray, T., Paoli, J., Sperberg-McQueen, C., Maler, E., and  
F. Yergeau, "Extensible Markup Language (XML) 1.0 (Fourth  
Edition)", W3C REC-xml, August 2006,  
<<http://www.w3.org/TR/2006/REC-xml-20060816/>>.

## [Appendix A.](#) Aggregate XML Schema

```
<?xml version="1.0" encoding="UTF-8"?>
```

```
<!-- Declare helper entity to avoid overrunning right margin of RFC  
text while importing WS-SecurityPolicy schema.-->
```

```
<!DOCTYPE schema [
```



```
<!ENTITY ws-securitypolicyuri
  "http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702">
]>

<xs:schema
  xmlns:cpxmlsec="urn:ietf:params:xml:ns:cpxmlsec"
  xmlns:xs="http://www.w3.org/2001/XMLSchema"
  xmlns:sp=
    "http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702"
  targetNamespace="urn:ietf:params:xml:ns:cpxmlsec"
  elementFormDefault="qualified"
  version="0.4">

  <xs:import namespace=
    "http://docs.oasis-open.org/ws-sx/ws-securitypolicy/200702"
    schemaLocation=
    "&ws-securitypolicyuri;/ws-securitypolicy-1.2.xsd" />

  <xs:simpleType name="ObjectIdentifierType">
    <xs:restriction base="xs:anyURI">
      <xs:pattern
        value="urn:oid:(([0-1]\.[1-3]?\d)|(2\.\d+))(\.\d+)*" />
    </xs:restriction>
  </xs:simpleType>

  <xs:element name="ParametersR3411"
    type="cpxmlsec:ObjectIdentifierType" />

  <xs:element name="GOSTKeyValue" type="cpxmlsec:KeyValue" />

  <xs:complexType name="KeyValue">
    <xs:sequence>
      <xs:element name="PublicKeyParameters"
        type="cpxmlsec:PublicKeyParametersType"
        minOccurs="0"/>
      <xs:element name="PublicKey" type="xs:base64Binary" />
    </xs:sequence>
  </xs:complexType>

  <xs:complexType name="PublicKeyParametersType">
    <xs:sequence>
      <xs:element name="publicKeyParamSet"
        type="cpxmlsec:ObjectIdentifierType" />
      <xs:element name="digestParamSet"
        type="cpxmlsec:ObjectIdentifierType" />
      <xs:element name="encryptionParamSet"
        type="cpxmlsec:ObjectIdentifierType"
        minOccurs="0" />
    </xs:sequence>
  </xs:complexType>

```





```
        </xs:sequence>
    </xs:complexType>

    <xs:element name="Parameters28147"
                type="cpxmlsec:ObjectIdentifierType" />

    <xs:element name="BasicGost"
                type="sp:QNameAssertionType"/>

</xs:schema>
```

## [Appendix B.](#) Aggregate DTD

```
<!ELEMENT GOSTKeyValue (
    PublicKeyParameters?, PublicKey) >
<!ELEMENT PublicKey (#PCDATA) >
<!ELEMENT PublicKeyParameters (
    publicKeyParamSet, digestParamSet,
    encryptionParamSet?) >
<!ELEMENT publicKeyParamSet (#PCDATA) >
<!ELEMENT digestParamSet (#PCDATA) >
<!ELEMENT encryptionParamSet (#PCDATA) >
<!ELEMENT Parameters28147 (#PCDATA) >
<!ELEMENT ParametersR3411 (#PCDATA) >
<!ELEMENT BasicGost EMPTY >
```

## [Appendix C.](#) Examples

Examples here are stored in the same format as the examples in [\[RFC4134\]](#) and can be extracted using the same program.

If you want to extract without the program, copy all the lines between the ">" and "<" markers, remove any page breaks, and remove the "|" in the first column of each line. The result is a valid Base64 blob that can be processed by any Base64 decoder.

### [C.1.](#) Signed document

This sample contain the signed XML document using the sample certificate from Section 4.2 of [\[CPPK\]](#).



|>XmlDocSigned2001.xml
|PD94bwwgdmVyc2l1vbj0iMS4wIiB1bmNvZGluZz0idXRmLTgiPz48Q3J5cHRvUHJv
|WE1MIFNpZ25lZD0idHJ1ZSI+SGVvZSBpcyBzb21lIGRhdGEgdG8gc2l1nbi48U2ln
|bmF0dXJlIHhtbG5zPSJodHRwOi8vd3d3LnczLm9yZy8yMDAwLzA5L3htbGRzaWcj
|Ij48U2lnbmVksW5mbz48Q2Fub25pY2FsaXphdGlvbk1ldGhvZCBBbGdvcml0aG09
|Imh0dHA6Ly93d3cudzMub3JnL1RSLzIwMDEvUkVDLXhtbC1jMTRuLTIwMDEwMzE1
|IiAvPjxTaWduYXR1cmVNZXRob2QgQWxnb3JpdGhtPSJodHRwOi8vd3d3LnczLm9y
|Zy8yMDAwLzA0L3htbGRzaWctbW9yZSNnb3N0c3RyMzQxMSIg
|Lz48U2lnbmVksW5mbz48Q2Fub25pY2FsaXphdGlvbk1ldGhvZCBBbGdvcml0aG09
|aXR0bT0iaHR0cDovL3d3dy53My5vcmcvMjAwMDEwMzE1L2VudmVsb3B1
|ZC1zaWduYXR1cmUiIC8+PC9UcmFuc2ZvcmlzPjxEaWdlc3RNZXRob2QgQWxnb3Jp
|dGhtPSJodHRwOi8vd3d3LnczLm9yZy8yMDAwLzA0L3htbGRzaWctbW9yZSNnb3N0
|c3RyMzQxMSIgPERpZ2VzdFZhbnHV1Pi9Kd3RRc3Z5NWsvUjBwZUx6ZG0ySWlqUEJ0
|U0o1cEpSalQ5R1VRSEV5VGc9PC9EaWdlc3RwYXN1ZT48L1JlZmVyaW5jZT48L1Np
|Z25lZEluZm8+PFNpZ25hdHVyZVZhbnHV1PkZjYjNwNGlCdmRmZ11vN245NudhUUN1
|ZDkxWVA3dzhvVjAzUjZ6a1JEZGxjK0RuQ2Mwcj1Nc0E1YS9iaFlDeVdQC9jRVU4
|K3FZRnJ5SmJjaXJ5d0hBPT08L1NpZ25hdHVyZVZhbnHV1PjxLZX1JbmZvPjxYNTA5
|RGF0YT48WDUwOUNlcnRpZmljYXRlPjx1JSUIwRENDQVg4Q0VDDjF4aDdDRWIwWHg5
|e1VZbWETG1Fd0NBWUdLb1VEQWdJRE1HMHhIekFkQmd0VkJBTU1Ga2R2YzNSU016
|UXhNQzB5TURBeE1HVjRZVzF3YkdVeEVqQVFCZ05WQkFvTUNVTn11WEIwYjFCeWJ6
|RUxNQWtHQTFVRUJoTUNVbFV4S1RBbkJna3Foa21HOXcwQkNRRVdHa2R2YzNSU016
|UXhNQzB5TURBeFFHVjRZVzF3YkdVdVkyOXRNqjRyRFRBMU1EZ3hOakUwTVRneU1G
|b1hEVEUxTURneE5qRTBNVGD5TUZvd2JURWZnQjBHQTFVRUF3d1dSMj16ZEZJek5E
|RXdmVE13TURFZ1pYaGhiWEJzW1RFU01CQUdBMVVFQ2d3S1EzSjVjSFJ2VUHKdk1R
|c3dDUV1EV1FRR0V3S1NWVEVwTUNjR0NTcUdTSWIZRFFFskFSWwFSMj16ZEZJek5E
|RXdmVE13TURGQVpYaGhiWEJzW1M1amIyMHdZekFjQmdZcWhRTUNBaE13RwdZSEtV
|VURBZ01rQUFZSEtVURBZ011QVFOREFBukFoSlZvZFdBQ0drQjFDTTBUakRHSkxQ
|M2xCUU42UTF6MGJtc1A1MDh5Zmx1UDY4d1d1WldJQTlDYWZJV3VEK1NONnFhN2Zs
|Ykh5N0RmRDJhOH11b2FZREFJQmdZcWhRTUNBZ01EUVFBOEw4a0pSTGNucWV5bjF1
|bjdVMjNTdzZwa2ZFUxUzdTB4RmtWUHZGUS8zY0hlRjI2TkcreHh0W1B6M1RhVFZY
|ZG9pwWtYwW1EMDJyRXgxY1VjTTk3aTwvWUwOUNlcnRpZmljYXRlPjxwWUwOURh
|dGE+PC9LZX1JbmZvPjxwWU2lnbmF0dXJlPjxwWUwOURhZG9pWtYwW1EMDJyRXgxY1VjTTk3aTwvWUwOUNlcnRpZmljYXRlPjxwWUwOURh
|<XmlDocSigned2001.xml

Appendix D. Acknowledgments

The authors wish to thank:

Microsoft Corporation Russia for provided information about company products and solutions, and also for technical consulting in PKI.

Our colleague Grigorij S. Chudov for writing the first version of this document.



Authors' Addresses

Serguei E. Leontiev  
CRYPTO-PRO, Ltd.  
16/5, Sushevskij val  
Moscow 127018  
Russia

Phone: +7 (495) 780 4820  
Fax: +7 (495) 660 2330  
Email: lse@CryptoPro.ru  
URI: <http://www.CryptoPro.ru>

Pavel V. Smirnov  
CRYPTO-PRO, Ltd.  
16/5, Sushevskij val  
Moscow 127018  
Russia

Phone: +7 (495) 780 4820  
Fax: +7 (495) 660 2330  
Email: spv@CryptoPro.ru  
URI: <http://www.CryptoPro.ru>

Aleksandr V. Chelpanov  
CRYPTO-PRO, Ltd.  
16/5, Sushevskij val  
Moscow 127018  
Russia

Phone: +7 (495) 780 4820  
Fax: +7 (495) 660 2330  
Email: cav@CryptoPro.ru  
URI: <http://www.CryptoPro.ru>

