SPRING Working Group
Internet-Draft
Intended status: Standards Track
Expires: November 21, 2020

W. Cheng
China Mobile
Z. Li
C. Li
Huawei Technologies
F. Clad
Cisco Systems, Inc
A. Liu
ZTE Corporation
C. Xie
China Telecom
Y. Liu
China Mobile
S. Zadok
Broadcom
May 20, 2020

Generalized SRv6 Network Programming for SRv6 Compression
draft-cl-spring-generalized-srv6-for-cmpr-01

Abstract

This document proposes Generalized Segment Routing over IPv6 (G-SRv6) Networking Programming for SRv6 compression.

G-SRv6 can reduce the overhead of SRv6 by encoding the Generalized SIDs(G-SID) in SID list, and it also supports to program SRv6 SIDs and G-SIDs in a single SRH to support incremental deployment and smooth upgrade.

G-SRv6 is fully compatible with SRv6 with no modification of SRH, no new address consumption, no new route creation, and even no modification of control plane.

G-SRv6 for Compression is designed based on the Compressed SRv6 Segment List Encoding in SRH [I-D.filsfilscheng-spring-srv6-srh-comp-sl-enc] framework.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at https://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 21, 2020.

Copyright Notice

Copyright (c) 2020 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (https://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction 3
2. Terminology 3
  2.1. Requirements Language 4
3. Concepts of G-SRv6 4
  3.1. G-SID 4
  3.2. G-SID Container 5
  3.3. G-SID Index 6
  3.4. COC Flavor 6
4. G-SRH 6
5. Packet Processing 9
6. Illustration 10
7. Benefits 12
8. Protocol Extensions Requirements 13
  8.1. Data Plane 13
  8.2. Control Plane 14
9. IANA Considerations 14
10. Security Considerations 15
11. Contributors 15
12. Acknowledgements 15
13. References 15
  13.1. Normative References 15
  13.2. Informative References 16
Authors' Addresses 17

1. Introduction

Segment routing (SR) [RFC8402] is a source routing paradigm that explicitly indicates the forwarding path for packets at the ingress node by inserting an ordered list of instructions, called segments.

When segment routing is deployed on the IPv6 data plane, it is called SRv6 [RFC8754]. For support of SR, a new routing header called Segment Routing Header (SRH), which contains a list of SIDs and other information, has been defined in [RFC8754]. In use cases like Traffic Engineering, an ordered SID List with multiple SIDs is inserted into the SRH to steer packets along an explicit path.

However, the size of SIDs (16 bytes per SID) in SRH proposes challenges for packet processing and payload efficiency [I-D.cheng-spring-shorter-srv6-sid-requirement]. In order to solve this problem, this document proposes Generalized Segment Routing over IPv6 (G-SRv6) Networking Programming for SRv6 compression.

G-SRv6 supports to encode multiple types of Segments in an SRH, called Generalized SRH (G-SRH). In SRv6 Compression, the G-SRH can carry multiple SRv6 SID and G-SID(Generalized Segment Identifier) containers in the SID list. A G-SID container may include an SRv6 SID or multiple G-SIDs and optional padding. A G-SID can be a 32-bits value of the original SRv6 SID, which contains the node ID and function ID. By carrying G-SIDs instead of 128 bits SRv6 SID, the problem of SRv6 header size can be solved, and the solution is compatible with SRv6.

2. Terminology

This document makes use of the terms defined in [RFC8754], [RFC8402] and [RFC8200], and the reader is assumed to be familiar with that terminology. This document introduces the following terms:

Compressible SRv6 SID: It is the 128-bit SRv6 SID whose format can be compressed. It is composed by Common Prefix and Generalized Segment Identifier (G-SID) and optional arguments and padding.

Common Prefix: It is the same prefix shared by multiple SIDs.

G-SRv6: Generalized SRv6 Network Programming

G-SRH: Generalized Segment Routing Header. It keeps the same format and code point with original SRH, which can carry multiple G-SIDs and original SIDs.

G-SID: Generalized Segment Identifier.It is a Compressed SID(C-SID) [I-D.filsfilscheng-spring-srv6-srh-comp-sl-enc].

G-SID Container: Generalized Segment Identifier Container.It is a C-SID container [I-D.filsfilscheng-spring-srv6-srh-comp-sl-enc].

2.1. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. Concepts of G-SRv6

This section describes the concepts of G-SRv6.

3.1. G-SID

In an SRv6 domain, the SIDs are allocated from an address block, called SID space. Therefore, the SIDs allocated from the same SID space share the common prefix. Also, if the length of the SID is less than 128 bits, then padding is required. In an SID List, the common prefix and padding are redundant. Reducing the redundant information can reduce the overhead of SRv6.

This document defines a Generalized SID (G-SID) to carry the different part of the original SRv6 SID in the SRH to reduce the size of the SRH. The G-SID can be a 32-bits value following the common prefix in the original SRv6 SID. An SRv6 SID with this format is called compressible SRv6 SID. The format of a compressible SRv6 SID with 32-bits G-SID is shown in Figure 1.

```
0          Variable Length          32 bits                128 bits
+-----------------------------------------------------------------+
|             Common Prefix    |     G-SID     | Args/padding  |
+-----------------------------------------------------------------+
|<-------- Locator ----------------->|
```

Figure 1. 32 bits G-SID in SRv6 SID

In order to indicate the format of the SRv6 SID is compressible, control plane extension may be considered. This is out of scope of this document, and can be described in other documents.

3.2. G-SID Container

In order to align with 128 bits, a 128 bit G-SID Container is defined. A G-SID Container is a 128 bits value, and it may contain different type of SIDs:

- o an SRv6 SID: A G-SID Container contains a single SRv6 SID.

- o A Micro SID Carrier: A G-SID Container contains a Micro SID carrier [I-D.filsfils-spring-net-pgm-extension-srv6-usid].

- o Multiple G-SIDs: A G-SID Container contains multiple G-SIDs and optional padding. When G-SID is a 32-bits value, a G-SID Container can consist of 4 G-SIDs. If the length of G-SIDs in a G-SID Container is less than 128 bits, then padding is required.

```
 0                   1                   2                   3
 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 0                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 1                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 2                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 3                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
                                (a)

 0                   1                   2                   3
 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            Padding                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            Padding                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 0                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            G-SID 1                            |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
                                (b)
```

Figure 2. G-SID Container for Compression

3.3. G-SID Index

In order to locate the G-SID within the G-SID Container, this section defines Generalized SID Index (SI) to indicate the location of the G-SID within the current G-SID Container.

SI is a location argument of the G-SID, which is the least bits in the argument part. When G-SID is a 32 bits value, the SI is the least 2 bits in Argument.

```
 0         Variable Length            32 bits                128 bits
 +-------------------------------------------------------------+
 |             Common Prefix   |  G-SID         |SI|  Padding   |
 +-------------------------------------------------------------+
```

Figure 4. SI in the IPv6 DA

3.4. COC Flavor

In order to indicate the SRv6 compression processing, updating the next 32-bits G-SID to the IPv6 DA, this section defines COC(Continue of Compression) Flavor.

When a node receives an SID with COC Flavor, it indicates to update the G-SID part in IPv6 DA with the next 32 bits G-SID.

When a node receives an SID without COC Flavor, the node processes the packet as a normal SRv6 packet [I-D.ietf-spring-srv6-network-programming], for example, update the IPv6 DA with the next 128 bits SID if SL >0.

Therefore, if the behavior of the last G-SID in the G-SID list has no COC Flavor, then the next 128 bits SID will be updated to the DA, so it indicates the end of the compression sub-path.

When COC Flavor applies to END, END.X and END.T, the SIDs can be advertised via the IS-IS [I-D.ietf-lsr-isis-srv6-extensions], and the SRv6 SID Structure Sub-Sub-TLV MUST be carried to indicate the format of the SRv6 SID. The Locator.Block length indicates the length of the common prefix, and the G-SID is the following 32-bits value after the Block, which contains the Node ID and Function ID.

4. G-SRH

G-SRH supports to encode different types of segment in a single SRH without modifying the encapsulation format of SRH.

When an SRv6 path travels normal SRv6 nodes and compressed SRv6 nodes, the SRv6 SID and G-SIDs can be encoded in a single G-SRH.

For easier understanding, this document assumes that the Compressible SRv6 SID consists of 64 bits common prefix and 32 bits G-SID. The encoding can be shown as follows.

```
     0                   1                   2                   3
     0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    | Next Header   |  Hdr Ext Len  |  Routing Type  | Segments Left|
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |  Last Entry   |    Flag       |               Tag             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                      Other G-SID Container                    |
    .                             ...                               .
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
---
    |                       Optional Padding                        |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           G-SID 0                             |  G-SID
Container 0
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    .                            ...                                .        ...
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           G-SID 3                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
---
    |                           G-SID 0                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           G-SID 1                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           G-SID 2                             |  G-SID
Container j
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           G-SID 3                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
---
    |                        Common Prefix                          |
    |                                                               |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+  G-SID
Container k
    |                           G-SID 0                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                           Padding                             |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
---
    |                             ...                               |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    |                                                               |
    |             Generalized Segment List[n] (128 bits SRv6 SID)   |
    |                                                               |
    |                                                               |
    +-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
    //         Optional Type Length Value objects (variable)       //
```

```
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
```

Figure 3. G-SRH for SRv6 Compression

Where:

- o Common Prefix: the common prefix shared by the Compressible SRv6 SIDs in the current compression sub-path. Usually, it is the prefix of the SID space, called Locator Block in control plane [I-D.ietf-spring-srv6-network-programming]. Operators are free to configure the length and the value of the common prefix based on the address planning of their networking.

- o G-SID: 32-bits Generalized SID.

- o Padding: Must be zero. When the length of G-SIDs within the G-SID Container is less than 128 bits, then padding is needed.

5. Packet Processing

This section describes the pseudo code of COC Flavor, and it replaces the S13 and S14 of End, End.X, and End.T's pseudo code [I-D.ietf-spring-srv6-network-programming]. The pseudo code is shown below.

When N receives a packet whose IPv6 DA is S and S is a local SID with COC Flavor, N does:

```
If (DA.SI != 0) {                                    //ref1
    Decrement DA.SI by 1.
} Else {
    Decrement Segments Left by 1.
    Set DA.SI to 3 in the IPv6 Destination Address
}
Copy Segment List[Segments Left][DA.SI] into the bits  //ref2
  [B..B+31] of the IPv6 Destination Address.
```

- o Ref1: an SID with COC flavor indicates the SRv6 compression processing that the node needs to update the next 32 bits G-SID to the IPv6 DA.

  - * When the SI is greater than 0, the next G-SID is the next G-SID in the current G-SID Container.

  - * Otherwise, the next G-SID is the first G-SID in the next G-SID Container.

- o Ref2: B is the length of the Locator Block [I-D.ietf-spring-srv6-network-programming].

An SID without COC Flavor will be processed following the SRv6 processing. The node will update the next 128 bit SID to the IPv6 DA if the SL > 0.

6. Illustration

This section describes a simple example of G-SRv6 for compression.

The reference topology is shown below.

```
                      *--------------------*
                      *    SRv6 Domain     *
                      *                    *
        Tenant10 CE1--0-1-2-3-4-5-6-7-8-9-10--CE2  Tenant10
                      *                    *
                      *--------------------*
```

Figure 5. Reference topology

Nodes 0 - 10 are G-SRv6 enabled nodes within the SRv6 domain, and node 0 is the ingress node of the G-SRv6 path while the node 10 is the egress node.

Nodes CE1 and CE2 are tenants of VPN 10, and they are outside of the SRv6 domain.

In order to ease the reading of the example, this section introduces a simplified SID allocation schema.

- o 2001:db8::/64 is dedicated to the internal SRv6 SID space, which is the common prefix for the SIDs as well.

- o Node k has 2001:db8:0:0:k::/80 for its local SID space. Its SIDs will be explicitly allocated from that block.

- o 2001:db8:0:0:k:1:: represents the End.X SID with COC allocated by node K, and it is associated with interface N of node K. For instance, 2001:db8:0:0:1:1:: represents the End.X with COC flavor allocated by node 1.

- o 2001:db8:0:0:k:2:: represents the End.X SID without COC allocated by node K, and it is associated with interface N of node K. For instance, 2001:db8:0:0:1:2:: represents the End.X without COC flavor allocated by node 1.

- o 2001:db8:0:0:10:10:: is an END.DT4 SID initiated by node 10, which is associated with the VRF10.

Therefore, the SID 2001:db8:0:0:1:1::, 2001:db8:0:0:2:1::, 2001:db8:0:0:3:1::, 2001:db8:0:0:4:1::, 2001:db8:0:0:5:1::, 2001:db8:0:0:6:1::, 2001:db8:0:0:7:1::, 2001:db8:0:0:8:1:: are SRv6

End.X SIDs with COC Flavor, and 2001:db8:0:0:9:2:: is a Compressible SRv6 End.X SID.

The SID list [2001:db8:0:0:1:1::, 2001:db8:0:0:2:1::, 2001:db8:0:0:3:1::, 2001:db8:0:0:4:1::, 2001:db8:0:0:5:1::, 2001:db8:0:0:6:1::, 2001:db8:0:0:7:1::, 2001:db8:0:0:8:1::, 2001:db8:0:0:9:2::, 2001:db8:0:0:10:10::] is calculated for a strict TE path from Node 1 to Node 10 for the VPN traffic of tenant 10.

In G-SRv6, the SID list can be encoded as [2:1, 3:1, 4:1, 5:1, 6:1, 7:1, 8:1, 9:2, 2001:db8:0:0:10:10::] in reduced mode. The G-SID Container encoding is shown below.

```
 0                   1                   2                   3
 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+    ----
|                                                               |
|                     2001:db8:0:0:10:10::                      |   G-SID
Container 0
|                                                               |
|                                                               |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+    ----
|                            9:2                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            8:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+   G-SID
Container 1
|                            7:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            6:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+    ----
|                            5:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            4:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+   G-SID
Container 2
|                            3:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+
|                            2:1                                |
+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+-+    ----
```

Figure 6. G-SID Container Encoding for G-SRv6

The packets forwarding procedures:

o Node 0 sends the SRv6 packet with G-SRH to the node 1.The SL is 3. The Active SID in IPv6 DA is 2001:db8:0:0:1:1::.

- When node 1 receives the packet, the IPv6 DA is 2001:db8:0:0:1:1::, which is a Local End.X with COC Flavor SID.

The SRH.SL is 3, and DA.SI is 0. The node processes the packet: SL = SL-1,DA.SI =3, pointing to the next G-SID 2:1, and updates SRH[SL=2][DA.SI=3] to the IPv6 DA[CP:CP+31], where CP is the length of the common prefix. The packet is forwarded with the new IPv6 DA 2001:db8:0:0:2:1:C::, to the node 2.

- o When node 2 receives the packet, the IPv6 DA is 2001:db8:0:0:2:1:C::, which is a Local End.X with COC Flavor SID. The SRH.SL is 2, and DA.SI is 3. The node processes the packet: DA.SI --, pointing to the next G-SID 3:1, and updates SRH[SL=2][DA.SI=2] to the IPv6 DA[CP:CP+31]. The packet is forwarded with the new IPv6 DA 2001:db8:0:0:3:1:8::, to the node 3.

- o Similar to node 1 and 2, the node 3,4,5,6,7,8 process the packet and forward with the new IPv6 DA.

- o When node 9 receives the packet, the IPv6 DA is 2001:db8:0:0:9:2::, which is a Local End.X SID. The SRH.SL is 1. The node updates the next SID 2001:db8:0:0:10:10:: to the IPv6 DA and forwards the packet to the node 10.

- o Node 10 receives the packet, and the IPv6 DA is an VPN SID allocated by itself, the node processes the SRv6 VPN SID.

This illustration shows that 70 % overhead of SID list is removed in G-SRv6(10 x 16 Bytes to 3 x 16 Bytes), also, it shows the capabilities of encoding G-SIDs and SRv6 SIDs in a single G-SRH.

7. Benefits

- o G-SRv6 is fully compatible with SRv6

  - * No SRH encapsulation modification.

  - * No new address consumption: Compressible SRv6 SIDs can be allocated from the Locator allocated to the node.

  - * No new route advertisements: Compressible SRv6 SIDs can share the same locator with the normal SRv6 SID.

  - * No security policy modification: when reusing the Locator with SRv6 SIDs, no security policy need to be updated.

  - * No control plane modification: Controller can install the SR policy with 128-bits G-SID Containers, and the ingress treats the G-SID Container as an opaque 128-bits SID without understanding the structure of it. G-SRv6 capable nodes

understand the COC flavor behaviors, while Compression disable SRv6 nodes are unaware of Compression.

- o G-SRv6 reduces the SRv6 encapsulation size.
  - * 128 bits to 32 bits, up to 75 % overhead is reduced. More overhead is reduced when the G-SID is a 16-bits value.
- o G-SRv6 has efficient address consumption and easy to deploy
  - * Operators are free to allocate an SID space from their address space.
  - * No affect of networking(i.e. routes and ACL security policies) by using the existing Locator to allocate compressible SRv6 SIDs.
- o G-SRv6 is hardware friendly
  - * Same SRv6 processing flow with a new IPv6 DA update method
  - * Leverages the mature hardware capabilities (DA update, DA longest match)
  - * Avoids extra lookup in indexed mapping table
- o G-SRv6 supports incremental deployments, which can be deployed on demand.

8. Protocol Extensions Requirements

This section describes the protocol extension requirements.

8.1. Data Plane

REQ1-01: An SRv6 compression path can be represented as a G-SID Container list consists of a compressible SRv6 SID and G-SID Containers.

REQ1-02: A G-SID Container consists of at most 4 (32-bits) G-SIDs, if the number of G-SID is less than 4, then padding is required to align with 128 bits.

REQ1-03: If the first Compressible SRv6 SID is copied to the IPv6 DA, then following G-SIDs should be updated to the IPv6 DA by the nodes along the SRv6 compression sub-path accordingly.

REQ1-04: The last G-SID in the G-SID Container for the SRv6 compression sub-path is the a G-SID without COC flavor.

REQ1-05: When process the G-SID with COC flavor in the IPv6 DA, the next G-SID is updated to the IPv6 DA.

8.2. Control Plane

REQ1-11: ISIS/OSPF/BGP-LS/PCEP extensions for advertising the capabilities of supporting G-SRv6 for SRv6 compression.

REQ1-12: ISIS/OSPF/BGP-LS/BGP extensions for advertising Compressible SRv6 SIDs.

REQ1-13: ISIS/OSPF/BGP-LS/BGP extensions for advertising the Continue-of-compression(COC) flavor SID.

REQ1-21: BGP SR Policy extensions for programming a G-SRv6 path combining with Compressible SRv6 SIDs and SRv6 SIDs.

REQ1-31: PCEP SR Policy extensions for programming a G-SRv6 path combining with G-SIDs and SRv6 SIDs.

REQ1-32: PCEP extensions for programming a G-SRv6 path combining with G-SIDs and SRv6 SIDs.

9. IANA Considerations

This document requests IANA to allocate the following codepoints for COC flavor behaviors within the "SRv6 Endpoint Behaviors" sub-registry under the top-level "Segment Routing Parameters" registry.

Value	Hex	Endpoint behavior	Reference
101	0x0065	End with COC	[This.ID]
102	0x0066	End with PSP&COC	[This.ID]
104	0x0068	End with PSP&USP&COC	[This.ID]
105	0x0069	End.X with COC	[This.ID]
106	0x006A	End.X with PSP&COC	[This.ID]
108	0x006C	End.X with PSP&USP&COC	[This.ID]
109	0x006D	End.T with COC	[This.ID]
110	0x006E	End.T with PSP&COC	[This.ID]
112	0x0070	End.T with PSP&USP&COC	[This.ID]
130	0x0082	End with PSP&USD&COC	[This.ID]
131	0x0083	End with PSP&USP&USD&COC	[This.ID]
133	0x0085	End.X with PSP&USD&COC	[This.ID]
135	0x0087	End.X with PSP&USP&USD&COC	[This.ID]
137	0x0089	End.T with PSP&USD&COC	[This.ID]
139	0x008B	End.T with PSP&USP&USD&COC	[This.ID]

Table 1: IETF - SRv6 Endpoint Behaviors

10. Security Considerations

The security considerations described in [RFC8754], and [RFC8402] are applicable to this specification. No additional security measure is required.

11. Contributors

TBD

12. Acknowledgements

TBD

13. References

13.1. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <https://www.rfc-editor.org/info/rfc2119>.

[RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <https://www.rfc-editor.org/info/rfc8174>.

[RFC8200] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", STD 86, RFC 8200, DOI 10.17487/RFC8200, July 2017, <https://www.rfc-editor.org/info/rfc8200>.

[RFC8754] Filsfils, C., Ed., Dukes, D., Ed., Previdi, S., Leddy, J., Matsushima, S., and D. Voyer, "IPv6 Segment Routing Header (SRH)", RFC 8754, DOI 10.17487/RFC8754, March 2020, <https://www.rfc-editor.org/info/rfc8754>.

[RFC8402] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", RFC 8402, DOI 10.17487/RFC8402, July 2018, <https://www.rfc-editor.org/info/rfc8402>.

[I-D.ietf-spring-srv6-network-programming] Filsfils, C., Camarillo, P., Leddy, J., Voyer, D., Matsushima, S., and Z. Li, "SRv6 Network Programming", draft-ietf-spring-srv6-network-programming-15 (work in progress), March 2020.

[I-D.filsfilscheng-spring-srv6-srh-comp-sl-enc] Cheng, W., Filsfils, C., Li, Z., Cai, D., Voyer, D., Clad, F., Shay, S., Guichard, J., and L. Aihua, "Compressed SRv6 Segment List Encoding in SRH", draft-filsfilscheng-spring-srv6-srh-comp-sl-enc-01 (work in progress), May 2020.

13.2. Informative References

[I-D.filsfils-spring-net-pgm-extension-srv6-usid] Filsfils, C., Camarillo, P., Cai, D., Voyer, D., Meilik, I., Patel, K., Henderickx, W., Jonnalagadda, P., Melman, D., Liu, Y., and J. Guichard, "Network Programming extension: SRv6 uSID instruction", draft-filsfils-spring-net-pgm-extension-srv6-usid-07 (work in progress), May 2020.

[I-D.cheng-spring-shorter-srv6-sid-requirement] Cheng, W., Xie, C., Pang, R., Li, Z., Chen, R., Lijun, L., Duan, X., and G. Mirsky, "Shorter SRv6 SID Requirements", draft-cheng-spring-shorter-srv6-sid-requirement-01 (work in progress), March 2020.

[I-D.ietf-lsr-isis-srv6-extensions] Psenak, P., Filsfils, C., Bashandy, A., Decraene, B., and Z. Hu, "IS-IS Extension to Support Segment Routing over IPv6 Dataplane", draft-ietf-lsr-isis-srv6-extensions-08 (work in progress), April 2020.

Authors' Addresses

Weiqiang Cheng(editor)
China Mobile
No.32 Xuanwumen west street
Beijing 100053
China

Email: chengweiqiang@chinamobile.com

Zhenbin Li
Huawei Technologies
Huawei Campus, No. 156 Beiqing Rd.
Beijing 100095
China

Email: lizhenbin@huawei.com

Cheng Li(editor)
Huawei Technologies
Huawei Campus, No. 156 Beiqing Rd.
Beijing 100095
China

Email: c.l@huawei.com

Francois Clad
Cisco Systems, Inc
France

Email: fclad@cisco.com

Aihua Liu
ZTE Corporation
Shenzhen
China

Email: liu.aihua@zte.com.cn

Chongfeng Xie
China Telecom
Technology Innovation park, Changping District
Beijing
China

Email: xiechf.bri@chinatelecom.cn

Yisong Liu
China Mobile
No.32 Xuanwumen west street
Beijing

Email: liuyisong@chinamobile.com

Shay Zadok
Broadcom
Israel

Email: shay.zadok@broadcom.com