

Internet Engineering Task Force  
INTERNET-DRAFT  
Expires: Apr 27, 2003

Craig Metz  
Extreme Networks  
Jun-ichiro itojun Hagino  
Research Lab, IIJ  
Oct 27, 2002

**IPv4-Mapped Address API Considered Harmful**  
**draft-cmetz-v6ops-v4mapped-api-harmful-00.txt**

Status of this Memo

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

To view the list Internet-Draft Shadow Directories, see <http://www.ietf.org/shadow.html>.

Distribution of this memo is unlimited.

The internet-draft will expire in 6 months. The date of expiration will be Apr 27, 2003.

## Abstract

The IPv6 Addressing Architecture [Hinden, 1998] defines the "IPv4-mapped IPv6 address." This representation is used in the IPv6 basic API [Gilligan, 1999] to denote IPv4 addresses using AF\_INET6 sockets. The use of IPv4-mapped addresses on AF\_INET6 sockets degrades portability, complicates IPv6 systems, and is likely to create security problems. This document discusses each issue in turn. Finally, it proposes to resolve these problems by recommending deprecation of this mechanism.

## **1. Drawbacks due to IPv4 mapped address support**

### **1.1. Degraded portability**

[RFC2553 section 3.7](#) specifies the behavior of IPv4-mapped addresses with an AF\_INET6 socket. However, the description fails to specify important details that are necessary for good portability. Specifically, the



specification needs to define:

- (1) The interaction between multiple `bind(2)` attempts to the same port, with different addresses. What happens when an application does and does not call `setsockopt(..., SO_REUSEPORT, ...)` in order to `bind(2)` to the same port on `AF_INET` and `AF_INET6`? What happens when an application calls `bind(2)` on `AF_INET` socket, and an application calls `bind(2)` on an `AF_INET6` socket with IPv4-mapped address? Note that there are many more issues here that need specification.
- (2) The selection/interaction of port numbers between `AF_INET` and `AF_INET6` sockets on `bind(2)` and/or `connect(2)` system calls. This is related to (1).
- (3) The treatment of socket options (`setsockopt(2)` and `getsockopt(2)`) with IPv4-mapped addresses on `AF_INET6` sockets. What happens when an application calls `setsockopt(2)` for IPv4 options or IPv6 options on an `AF_INET6` socket that is not yet bound (and, therefore, the host does not know if IPv4 or IPv6 communication will be used)? What happens when an application calls `setsockopt(2)` for IPv4 options or IPv6 options on an `AF_INET6` socket that is bound to IPv4-mapped addresses?
- (4) The delivery of multicast packets to `AF_INET` and `AF_INET6` sockets. What happens when an application binds to the IPv6 unspecified address (:::) with a certain port -- does it receive IPv4 multicast traffic as well? What will be the relationship between `IP_MULTICAST_IF` and `IPV6_MULTICAST_IF` socket options? What happens when an application calls `sendto(2)` to an IPv4-mapped address for an IPv4 multicast address? How will the source address will be selected?

Due to these ambiguities, developers of applications that use IPv4-mapped addresses on `AF_INET6` sockets might encounter portability problems.

### **1.2. Increased implementation complexity**

Implementation of IPv4-mapped addresses has a real and significant cost, both in the system software (e.g., network stack, kernel, and system libraries) and in the application software (ALL of which must now correctly handle IPv4-mapped addresses). The combined man-time for developers, testers, document writers, and support staff is a real and potentially tangible added cost of this particular feature. Because applications are affected, the number of implementations for which this cost will apply has the potential to be huge.

Implementation of IPv4-mapped addresses increases the complexity of all IPv6 implementations, both in the system software and in the application

software. Increased complexity is bad for software engineering reasons beyond the scope of this document. Technology market forces and Internet history have demonstrated that simpler protocols and simpler

systems have a tendency to be more successful than complex alternatives.

If the community wishes to see IPv6 achieve successful deployment, it is important that the resource costs and complexity costs associated with IPv6 be as low as possible. Where opportunities exist to decrease these costs, the community should seriously consider doing so in order to nurture deployment.

### **1.3. Access control complexity**

[RFC2553 section 3.7](#) adds extra complexity to address-based access controls. It is likely that there will be many errors introduced by of this.

Due to [RFC2553 section 3.7](#), AF\_INET6 sockets will accept IPv4 packets. On an IPv4/v6 dual stack node, if there is no AF\_INET listening socket, most users would believe that there will be no access from IPv4 peers. However, if an AF\_INET6 listening socket is present, IPv4 peers will be able to access the service. This is likely to confuse users and result in configuration errors that can be exploited by malicious parties. (It is violating the security principle of least surprise)

AF\_INET6 sockets will accept IPv4 packets even (and especially) if the application is not expecting them. Every application that uses AF\_INET6 sockets MUST correctly handle reception of IPv4 packets. Failure of a developer to consider every relevant case might lead to a security problem. This is likely to be overlooked by developers -- especially those new to IPv6 development (as most are). This is likely to result in applications with flaws that can be exploited by malicious parties. (Again, this is violating the security principle of least surprise)

Systems that support IPv4 communications on AF\_INET6 sockets using IPv4-mapped addresses have a greater potential to have security problems than they would if they did not have this feature.

## **2. Recommended solution**

- o Deprecate [RFC2553 section 3.7](#). By doing so, IPv6 implementations will be greatly simplified, both in the system software and in all IPv6 application software.

## **3. Alternative solution**

- o Expand [RFC2553 section 3.7](#) to fully define the behavior of AF\_INET6 sockets using IPv4-mapped addresses.
- o Change the default value for IPV6\_V6ONLY socket option defined in [Gilligan, 2002] to "on." With this approach, systems must still

implement the complex interactions between AF\_INET and AF\_INET6  
socket, which can lead to security problems. Also, once a application

turns the socket option off, it MUST correctly handle all cases where an IPv4-mapped address might be used or it may have security problems.

#### **4. Implementation tips to application developers**

- o In EVERY application, check for IPv4-mapped addresses wherever addresses enter code paths under your control (i.e., are returned from system calls, or from library calls, or are input from the user or a file), and handle them in an appropriate manner. This approach is difficult in reality, and there is no way to determine whether it has been followed fully.
- o Do not intentionally use [RFC2553 section 3.7](#) (IPv4 traffic on AF\_INET6 socket). Implement server applications by using separate AF\_INET and AF\_INET6 listening sockets. Explicitly set the IPV6\_V6ONLY socket option to on, whenever the socket option is available on the system.

NOTE: Due to the lack of standard behavior in bind(2) semantics, this may not be possible on some systems. Some IPv6 stack does not permit bind(2) to 0.0.0.0, after bind(2) to ::. Also, there is no standard on how IPv4 traffic will be routed when both 0.0.0.0 and :: listening sockets are available on the same port.

- o Implement programs in a protocol-independent manner using getaddrinfo(3) and getnameinfo(3), instead of hard-coding AF\_INET6. [RFC2553 section 3.7](#) leads people to port IPv4 application to IPv6 by replacing AF\_INET into AF\_INET6. However, by hard-coding AF\_INET6 into the program, developers are failing to correct their dependencies on particular protocol families. As a consequence, any future protocol support will again require the application to be modified. Applications that hard-code AF\_INET6 require IPv6-capable systems and will fail on a system that only has IPv4 support. It is critical to implement programs in a protocol-independent manner if you want to ship a single program (binary/source) that runs on IPv4-only, IPv6-only, as well as IPv4/v6 dual stack systems.

#### **5. Security considerations**

This document discusses security issues with the use of IPv4-mapped address. A recommended and alternate solution is provided.

#### **6. Change History**

None yet.





## References

Hinden, 1998.

**R. Hinden and S. Deering**, "IP Version 6 Addressing Architecture" in [RFC2373](http://ftp.isi.edu/in-notes/rfc2373.txt) (July 1998). [ftp://ftp.isi.edu/in-notes/rfc2373.txt](http://ftp.isi.edu/in-notes/rfc2373.txt).

Gilligan, 1999.

**R. Gilligan, S. Thomson, J. Bound, and W. Stevens**, "Basic Socket Interface Extensions for IPv6" in [RFC2553](http://ftp.isi.edu/in-notes/rfc2553.txt) (March 1999). [ftp://ftp.isi.edu/in-notes/rfc2553.txt](http://ftp.isi.edu/in-notes/rfc2553.txt).

Gilligan, 2002.

**R. Gilligan, S. Thomson, J. Bound, J. McCann, and W. R. Stevens**, "Basic Socket Interface Extensions for IPv6" in [draft-ietf-ipngwg-rfc2553bis-06.txt](#) (July 2002). work in progress material.

## Author's address

Craig Metz  
Extreme Networks  
220 Spring Street, Suite 100  
Herndon, VA 20170-5209, USA  
Tel: +1 703 885 6721  
email: cmetz@inner.net

Jun-ichiro itojun Hagino  
Research Laboratory, Internet Initiative Japan Inc.  
Takebashi Yasuda Bldg.,  
3-13 Kanda Nishiki-cho,  
Chiyoda-ku, Tokyo 101-0054, JAPAN  
Tel: +81-3-5259-6350  
Fax: +81-3-5259-6351  
email: itojun@iijlab.net

