

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: December 11, 2014

D. Cridland
Surevine Limited
June 9, 2014

Here Lies Extensible Messaging and Presence Protocol (XMPP) Session
Establishment
draft-cridland-xmpp-session-00

Abstract

The Extensible Messaging and Presence Protocol (XMPP) historically had a Session Establishment request defined in [RFC 3921](#) which clients were required to perform at the beginning of a session. [RFC 6121](#) dropped this entirely. This specification reinstates it as an optional no-op to aid backwards compability, matching commonly deployed workarounds.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 11, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

Internet-Draft

XMPP Session

June 2014

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	The Session Establishment Tombstone	3
2.1.	Feature Advertisement	3
2.2.	Session Establishment Request	3
3.	Security Considerations	4
4.	IANA Considerations	4
4.1.	XML Namespace Name for Session Data	4
5.	Acknowledgements	4
6.	References	4
6.1.	Normative References	4
6.2.	Informative References	4
	Author's Address	5

[1.](#) Introduction

Within this specification, we refer to "Old" clients and servers meaning those conforming to the [\[RFC3921\]](#) particularly with respect to its [Section 3](#) (Session Establishment). We refer to "New" clients and servers meaning those conforming to the newer definition of Session Establishment within this document.

While [\[RFC6121\]](#) removed Session Establishment entirely from XMPP, there exist deployed clients which expect the feature to be advertised, and will refuse to proceed if it is not. Similarly, where the feature is advertised, clients were advised to use it, as deployed Old servers may require it.

This has led to a situation where although deprecated by [RFC 6121](#), the status quo is unchanged.

A number of servers advertise it with a discussed (but not standardized) <optional/> subelement to the feature, which clients can use as a hint that they may elide Session Establishment without penalty.

This document formalizes this and acts as the tombstone for Session Establishment, deprecating it in a manner where one can see where it used to be.

[2.](#) The Session Establishment Tombstone

This specification formalizes the `<optional/>` marker and explicitly defines the Session Establishment request itself as a no-op.

[2.1.](#) Feature Advertisement

Session Establishment SHALL be advertised within the Stream Features element as an element of local name "session", qualified by the "urn:iETF:params:xml:ns:xmpp-session" XML namespace. This element MUST contain a child element within the same namespace with local name "optional", known as the `<optional/>` marker. Clients SHALL ignore such advertisements.

If a client sees an advertisement which does not contain the `<optional/>` marker, however, this indicates an Old server, and it MUST perform Session Establishment as detailed in the next section.

Also, note that Old Clients will also perform the protocol despite the existence of the `<optional/>` marker.

[2.2.](#) Session Establishment Request

A Old client connecting to a New server, or a New client against a Old server, issues a Session Establishment request. This consists of an IQ stanza of type "set" containing an empty `<session/>` child element qualified by the "urn:iETF:params:xml:ns:xmpp-session" namespace:

Step 1: Client requests session with server:

```
<iq to='example.com' type='set' id='sess_1'>
  <session xmlns='urn:iETF:params:xml:ns:xmpp-session' />
</iq>
```

A New server MUST treat this as a no-op; that is, it MUST NOT perform any special processing which has any effect on the session. The only behaviour allowed and required by this specification is the empty result:

Step 2: Server informs client of success:

```
<iq from='example.com' type='result' id='sess_1'/>
```

Note that this specification does not allow any error to be generated at this point in response to a syntactically valid request.

[3.](#) Security Considerations

This document defines, in effect, a no-op, and therefore it is thought not to have any security impact.

[4.](#) IANA Considerations

This document supercedes the original definition of the XML namespace defined in [RFC 3921](#), therefore the IANA is requested to update the registry as follows:

[4.1.](#) XML Namespace Name for Session Data

A URN sub-namespace for session-related data in the Extensible Messaging and Presence Protocol (XMPP) is defined as follows. (This namespace name adheres to the format defined in The IETF XML Registry [[RFC3688](#)].)

URI: urn:ietf:params:xml:ns:xmpp-session

Specification: This document

Description: Here lies the XML namespace name for session-related data in the Extensible Messaging and Presence Protocol (XMPP), as defined in "this document".

Registrant Contact: IETF, XMPP Working Group, <xmpp@ietf.org>

[5.](#) Acknowledgements

The examples and some of the text were lifted from [RFC 3921](#) by Peter Saint-Andre. The optional marker was proposed some time ago and was

implemented by Curtis King and Waqas Hussein amongst others.

[6.](#) References

[6.1.](#) Normative References

[RFC6121] Saint-Andre, P., "Extensible Messaging and Presence Protocol (XMPP): Instant Messaging and Presence", [RFC 6121](#), March 2011.

[6.2.](#) Informative References

[RFC3921] Saint-Andre, P., Ed., "Extensible Messaging and Presence Protocol (XMPP): Instant Messaging and Presence", [RFC 3921](#), October 2004.

[RFC3688] Mealling, M., "The IETF XML Registry", [BCP 81](#), [RFC 3688](#), January 2004.

Cridland

Expires December 11, 2014

[Page 4]

Internet-Draft

XMPP Session

June 2014

Author's Address

Dave Cridland
Surevine Limited
PO Box 1136
Guildford, Surrey GU1 9ND
UK

Email: dave.cridland@surevine.com

