

Network Working Group	D. Crocker
Internet-Draft	Brandenburg InternetWorking
Intended status: Best Current Practice	October 14, 2011
Expires: April 16, 2012	

DNS Scoped Data Through Attribute Leaves
draft-crocker-dns-attrleaf-06

[Abstract](#)

Historically, any DNS RR may occur for any domain name. Recent additions have defined DNS leaf nodes that contain a reserved node name, beginning with an underscore. The underscore construct is used to define a semantic scope for DNS records associated with the parent domain. This note explores the nature of this DNS usage and defines the "underscore names" registry with IANA.

[Status of this Memo](#)

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 16, 2012.

[Copyright Notice](#)

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

[Table of Contents](#)

- *1. [Introduction](#)

- *2. [Scaling Benefits and TXT and SRV Resource Records](#)
- *3. [Underscore DNS Registry Function](#)
- *4. [DNS Underscore Registry Definition](#)
- *5. [IANA Considerations](#)
- *6. [Related Registries](#)
- *7. [Security Considerations](#)
- *8. [References](#)
 - *8.1. [Normative References](#)
 - *8.2. [References -- Informative](#)
- *Appendix A. [Acknowledgements](#)
- *[Author's Address](#)

1. Introduction

The core DNS technical specifications assign no semantics to domain names or their parts, and no constraints upon which resource records (RRs) may be associated with particular names. Over time, some leaf node names, such as "www" and "ftp" have come to imply support for particular services, but this is a matter of operational convention, rather than defined protocol semantics. This freedom in the basic technology has permitted a wide range of administrative and semantic policies to be used -- in parallel. Data semantics have been limited to the specification of particular resource records, on the expectation that new ones would be added as needed.

Some recent service enhancements have defined a restricted scope for the occurrence of particular resource records. That scope is a leaf node, within which the uses of specific resource records can be formally defined and constrained. The leaf has a distinguished naming convention: It uses a reserved DNS node name that begins with an underscore. Because host names are not allowed to use the underscore character, this distinguishes the name from all legal host name. Effectively, this convention creates a space for attributes that are associated with the parent domain, one level up.

An established example is the SRV record [\[RFC2782\]](#) which generalizes concepts long-used for email routing by the MX record [\[RFC0974\]](#) [\[RFC2821\]](#). The use of special DNS names has significant benefits and detriments. Some of these are explored in [\[RFC5507\]](#).

[Comment]: The terms "resolution context" and "scoping rules" have been suggested, in place of "semantic scope". In order to avoid

concern for matters of semantics, this specification uses the term "scoping rules", to create a focus on the mechanics being defined, rather than nuances of interpretation for the mechanism.

The scoping feature is particularly useful when generalized resource records are used -- notably TXT and SRV. It provides efficient separation of one use of them from another. Absent this separation, an undifferentiated mass of these RRs are returned to the client which then must parse through the internals of the records in the hope of finding ones that are relevant. With underscore-based scoping, only the relevant RRs are returned.

This specification discusses the underscore "attribute" enhancement, provides an explicit definition of it, and establishes an IANA registry for the reserved names that begin with underscore.

Discussion Venue: Discussion about this draft is directed to the dnsop@lists.uoregon.edu mailing list of the [IETF DNSOP Working Group](#).

2. Scaling Benefits and TXT and SRV Resource Records

Some resource records are generic and support a variety of uses. Each additional use defines its own rules and, possibly, its own internal syntax and node-naming conventions to distinguish among particular types. The TXT and SRV records are the notable examples. Used freely, some of these approaches scale poorly, particularly when the same RR can be present in the same leaf node, but with different uses. An increasingly-popular approach, with excellent scaling properties, uses an underscore-based name to define a place in the DNS that is constrained to particular uses for particular RRs. This means that a direct lookup produces only the desired records, at no greater cost than a typical lookup.

In the case of TXT records, different uses have developed largely without coordination. One side-effect is that there is no consistently distinguishable internal syntax for the record; even internal inspection might not be a reliable means of distinguishing among the different uses. Underscore-based names therefore provide an administrative way of separating TXT records that might have different uses, but otherwise would have no syntactic markers for distinguishing among them.

In the case of the SRV RR distinguishing among different types of use was part of the design. [\[RFC2782\]](#) The SRV specification serves as a template, defining an RR that may only be used for specific applications when there is an additional specification. The template definition includes reference to tables of names from which underscore-names should be drawn. The set of <service> names is defined in terms of other IANA tables, namely any table with symbolic names. The other SRV naming field is <proto>, although its pool of names is not explicitly defined.

3. Underscore DNS Registry Function

This specification defines a registry for DNS nodes names, used to define scope of use for specific resource records (RR). A given name defines a specific, constrained context for the use of such records. This does not constrain the use of other resource records that are not specified. The purpose of the registry is to avoid collisions resulting from the use of the same underscore name, for different applications. Structurally, the registry is defined as a single, flat table of names that begin with underscore. In some cases, such as for SRV, an underscore name might be multi-part, as a sequence of names. Semantically, this is a hierarchical model, thereby making a flat registry unexpected.

The registry requires such hierarchies to be registered as a combinatorial case analysis set, with each entry being a full sequence of underscore names. Given a scheme that is actually structured, this flat design is inelegant. However it has the benefit of being extremely simple, with the added advantage of being easier for readers to understand, as long as these cases are small and few.

NAME
_service1
_service2._protoB
_service3._protoC
_service3._protoC
_service4._protoD._useX
_protoE._region._authority

Example of Underscore Names

The flat registry design:

- *provides significantly simpler administration than is needed for hierarchical tables, simples, and

- *is significantly simpler for readers to understand and is likely to produce fewer programming or administration errors.

4. DNS Underscore Registry Definition

A registry entry MUST contain:

- *Name:** Specifies a textual name for a scoped portion of the DNS. The name will usually be taken from the specification cited in the "Purpose" column and is intended for use in discussions about the entry.

- DNS Label(s):** Specifies a sequence of one or more underscore names that define a single name reservation.

Constraints:

Specifies any restrictions on use of the name.

RR(s): Lists the RRs that are defined for use within this scope.

References Lists specifications that define the records and their use under this Name.

Purpose: Specifies the particular purpose/use for specific RR(s), defined for use within the scope of the registered underscore name.

5. IANA Considerations

Per [\[RFC2434\]](#), IANA is requested to establish a DNS Underscore Name Registry, for DNS node names that begin with the underscore character (_) and have been specified in any published RFC, or are documented by a specification published by another standards organization. The contents of each entry are defined in [Section 4](#).

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
SRV TCP	_srv._tcp		SRV	[RFC2782]	SRV template
SRV UDP	_srv._udp		SRV	[RFC2782]	SRV template
LDAP SRV	_ldap._tcp		SRV	[RFC2782]	LDAP server
SIP TCP	_sip._tcp		NAPTR	[RFC3263] , [RFC6011]	Locating SIP Servers and UA configuration
SIPS TCP	_sips._tcp		NAPTR	[RFC3263] , [RFC6011]	Locating SIP Servers and UA configuration
SIP UDP	_sip._udp		SRV	[RFC3263] , [RFC6011]	Locating SIP servers and UA configuration
SPF	_spf		TXT	[RFC4408]	Authorized IP addresses for sending mail
DKIM	_domainkey		TXT	[RFC4871]	Public key for verifying DKIM signature.
ADSP	_adsp._domainkey		TXT	[RFC5617]	Published DKIM usage practices

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
PKI LDAP	_PKIXREP._ldap		SRV	[RFC4386]	LDAP PKI Repository
PKI HTTP	_PKIXREP._http		SRV	[RFC4386]	HTTP PKI Repository
PKI OCSP	_PKIXREP._ocsp		SRV	[RFC4386]	OCSP PKI Repository
VBR	_vouch		TXT	[RFC5518]	Vouch-by-reference domain assertion
DDDS	--unknown!--		SRV	[RFC3404]	Mapping DDDS query to DNS records
SOAP BEEP	_soap-beep._tcp		SRV	[RFC4227]	SOAP over BEEP lookup, when no port specified
XMLRPC BEEP	_xmlrpc-beep._tcp		SRV	[RFC3529]	Resolve url for XML-RPC using BEEP
Diameter SCTP	_diameter._sctp		SRV	[RFC3588]	Diameter rendezvous over SCTP
Diameter TCP	_diameter._tcp		SRV	[RFC3588]	Diameter rendezvous over TCP
Tunnel	_tunnel._tcp		SRV	[RFC3620]	Finding the appropriate address for tunneling into a particular domain
SLP TCP	_slpda._tcp		SRV	[RFC3832]	Discovering desired services in given DNS domains
SLP UDP	_slpda._udp		SRV	[RFC3832]	Discovering desired services in given DNS domains

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
IM	_im		SRV	[RFC3861]	Instant Messaging address resolution
Pres	_pres		SRV	[RFC3861]	Presence address resolution
Msg Track	_mtqp._tcp		SRV	[RFC3887]	Assist in determining the path that a particular message has taken through a messaging system
XMPP Client	_xmpp-client._tcp		SRV	[RFC6120]	XMPP client lookup of server
XMPP Server	_xmpp-server._tcp		SRV	[RFC6120]	XMPP server-server lookup
DDDS SRV	_???	(unable to discern details. / dcrocker)	SRV (and NAPTR?)	[RFC3958]	Map domain name, application service name, and application protocol dynamically to target server and port
Kerberos TCP	_kerberos._tcp		SRV	[RFC4120]	purpose
Kerberos UDP	_kerberos._udp		SRV	[RFC4120]	purpose
PKI LDAP	_pkixrep._ldap		SRV	[RFC4386]	Enables certificate-using systems to locate PKI repositories
PKI HTTP	_pkixrep._http		SRV	[RFC4386]	Enables certificate-using systems to locate PKI repositories

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
PKI OCSP	_pkixrep._ocsp		SRV	[RFC4386]	Enables certificate-using systems to locate PKI repositories
Cert Store	_certificates._tcp		SRV	[RFC4387]	Obtain certificates and certificate revocation lists (CRLs) from PKI repositories
Cert Revocation Store	_crls._tcp		SRV	[RFC4387]	Obtain certificates and certificate revocation lists (CRLs) from PKI repositories
PGP Key Store	pgpkeys._tcp		SRV	[RFC4387]	Obtain certificates and certificate revocation lists (CRLs) from PKI repositories
MSRP Relay Locator	_msrp._tcp		SRV	[RFC4976]	purpose
Mobile IPv6 Bootstrap	_mip6._ipv6		SRV	[RFC5026] , [RFC5555]	Bootstrap Mobile IPv6 Home Agent information from non-topological information
Digital Video Broadcasting TCP	_dvbservdsc._tcp		SRV	[RFC5328]	Discover non-default DVB entry points addresses
Digital Video	_dvbservdsc._udp		SRV	[RFC5328]	Discover non-default DVB

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
Broadcasting UDP					entry points addresses
CAPWAP AC	_capwap-control._udp		rrs	[RFC5415]	Discover the CAPWAP AC address(es)
IM SIP	_im._sip		SRV	[RFC5509]	For resolving Instant Messaging and Presence services with SIP
Pres SIP	_pres._sip		SRV	[RFC5509]	For resolving Instant Messaging and Presence services with SIP
IEEE 802.21 Mobility TCP	_mihis._tcp		NAPTR, SRV	[RFC5679]	Discovering servers that provide IEEE 802.21-defined Mobility Services
IEEE 802.21 Mobility UDP	_mihis._udp		NAPTR, SRV	[RFC5679]	Discovering servers that provide IEEE 802.21-defined Mobility Services
STUN Client/Server TCP	_stun._.tcp		SRV	[RFC5389]	Find a STUN server
STUN Client/Server UDP	_stun._.udp		SRV	[RFC5389]	Find a STUN server
STUN Client/Server TLS	_stuns._.tcp		SRV	[RFC5389]	Find a STUN server
TURN TCP	_turn._tcp		SRV	[RFC5766] , [RFC5928]	Control the operation of a relay to bypass NAT
TURN UDP	_turn._udp		SRV	[RFC5766] , [RFC5928]	Control the operation of

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
					a relay to bypass NAT
TURN TLS	_turns._tcp		SRV	[RFC5766] , [RFC5928]	Control the operation of a relay to bypass NAT
STUN NAT Behavior Discovery TCP	_stun-behavior._tcp		SRV	[RFC5780]	Discover the presence and current behavior of NATs and firewalls between the STUN client and the STUN server
STUN NAT Behavior Discovery UDP	_stun-behavior._udp		SRV	[RFC5780]	Discover the presence and current behavior of NATs and firewalls between the STUN client and the STUN server
STUN NAT Behavior Discovery TLS	_stun-behaviors._tcp		SRV	[RFC5780]	Discover the presence and current behavior of NATs and firewalls between the STUN client and the STUN server
Sieve Management	_sieve._tcp		SRV	[RFC5804]	Manage Sieve scripts on a remote server
AFS VLDB	_afs3-vlserver._udp		SRV	[RFC5864]	Locate services for the AFS distributed file system
AFS PTS			SRV	[RFC5864]	

NAME	DNS LABEL	CONSTRAINTS	RR(s)	REFERENCES	PURPOSE
	_afs3-prserver._udp				Locate services for the AFS distributed file system
Mail MSA Submission	_submission._tcp		SRV	[RFC6186]	Locate email services
IMAP	_imap._tcp		SRV	[RFC6186]	Locate email services
IMAP TLS	_imaps._tcp		SRV	[RFC6186]	Locate email services
POP	_pop3._tcp		SRV	[RFC6186]	Locate email services
POP TLS	_pop3s._tcp		SRV	[RFC6186]	Locate email services

DNS Underscore SCOPE Name Registry (with initial values)

[6. Related Registries](#)

Numerous specifications have defined their own, independent registries for use of underscore names. It is likely that adoption of the proposed, integrated registry should render these piecemeal registries obsolete

Registries that are candidates for replacement include:

- *Instant Messaging SRV Protocol Label Registry
- *Public Key Infrastructure using X.509 (PKIX) Parameters
- *Presence SRV Protocol Label Registry

[7. Security Considerations](#)

This memo raises no security issues.

[8. References](#)

[8.1. Normative References](#)

[RFC2434]	Narten, T. and H. Alvestrand, " Guidelines for Writing an IANA Considerations Section in RFCs ", RFC 2434, October 1998.
---------------------------	--

[8.2. References -- Informative](#)

, "

[RFC2821]	Klensin, J., " Simple Mail Transfer Protocol ", RFC 2821, April 2001.
[RFC0974]	Partridge, C., " Mail routing and the domain system ", RFC 974, January 1986.
[RFC2782]	Gulbrandsen, A. , Vixie, P. and L. Esibov , " A DNS RR for specifying the location of services (DNS SRV) ", RFC 2782, February 2000.
[RFC3263]	Rosenberg, J. and H. Schulzrinne, " Session Initiation Protocol (SIP): Locating SIP Servers ", RFC 3263, June 2002.
[RFC3404]	MMealling, M., " Dynamic Delegation Discovery System (DDDS) Part Four: The Uniform Resource Identifiers (URI) Resolution Application ", RFC 3404, October 2002.
[RFC3529]	Harold, W., " Using Extensible Markup Language-Remote Procedure Calling (XML-RPC) in Blocks Extensible Exchange Protocol (BEEP) ", RFC 3529, April 2003.
[RFC3588]	Calhoun, P., Loughney, J., Guttman, E., Zorn, G. and J. Arkko, "Diameter Base Protocol ", September 2003.
[RFC3620]	New, D., " The TUNNEL Profile ", RFC 3620, October 2003.
[RFC3861]	Peterson, J., " Address Resolution for Instant Messaging and Presence ", RFC 3861, August 2004.
[RFC3832]	, , , , , , , and , "Remote Service Discovery in the Service Location Protocol (SLP) via DNS SRV", July 2004.
[RFC3887]	Message Tracking Query Protocol", September 2007.
[RFC3958]	Daigle, L. and A. Newton, " Domain-Based Application Service Location Using SRV RRs and the Dynamic Delegation Discovery Service (DDDS) ", RFC 3958, January 2005.
[RFC4120]	, , , , , and , " The Kerberos Network Authentication Service (V5) ", RFC 4120, July 2005.
[RFC4227]	O'Tuathail, E. and M. Rose, " Using the Simple Object Access Protocol (SOAP) in Blocks Extensible Exchange Protocol (BEEP) ", RFC 4227, January 2006.
[RFC4386]	Boeyen, S. and P. Hallam-Baker, "Internet X.509 Public Key Infrastructure: Repository Locator Service", February 2006.
[RFC4387]	Gutmann, P., " Internet X.509 Public Key Infrastructure Operational Protocols: Certificate Store Access via HTTP ", RFC 4387, February 2006.
[RFC4408]	Wong, M. and W. Schlitt, " Sender Policy Framework (SPF) for Authorizing Use of Domains in E-Mail, Version 1 ", RFC 4408, April 2006.
[RFC5617]	, , , , , and , "DomainKeys Identified Mail (DKIM) Author Domain Signing Practices (ADSP)", August 2009.
[RFC4871]	Allman, E., Callas, J., Delany, M., Libbey, M., Fenton, J. and M. Thomas, " DomainKeys Identified Mail (DKIM) Signatures ", RFC 4871, May 2007.

[RFC4976]	Jennings, C., Mahy, R. and Roach, " Relay Extensions for the Message Session Relay Protocol (MSRP) ", RFC 4976, September 2007.
[RFC5026]	Giaretta, G., Kempf, J. and V. Devarapalli, " Mobile IPv6 Bootstrapping in Split Scenario ", RFC 5026, October 2007.
[RFC5328]	Adolf, A. and P. MacAvock, " A Uniform Resource Name (URN) Namespace for the Digital Video Broadcasting Project (DVB) ", RFC 5328, September 2008.
[RFC5389]	Rosenberg, , Mahy, , Matthews, and Wing, " Session Traversal Utilities for NAT (STUN) ", RFC 5389, October 2008.
[RFC5507]	Faltstrom, P. and R. Austein, "", RFC 5507, April 2009.
[RFC5415]	Calhoun, P., Montemurro, M. and D. Stanley, " Control And Provisioning of Wireless Access Points (CAPWAP) Protocol Specification ", RFC 5415, March 2009.
[RFC5509]	Loreto, S., " Internet Assigned Numbers Authority (IANA) Registration of Instant Messaging and Presence DNS SRV RRs for the Session Initiation Protocol (SIP) ", RFC 5509, April 2009.
[RFC5518]	Hoffman, P., Levine, J. and A. Hathcock, "Vouch By Reference", RFC5 5518, April 2009.
[RFC5555]	Soliman, H., " Mobile IPv6 Support for Dual Stack Hosts and Routers ", RFC 5555, June 2009.
[RFC5679]	Bajko, G., " Locating IEEE 802.21 Mobility Services Using DNS ", RFC 5679, December 2009.
[RFC5766]	Mahy, R., Matthews, P. and J. Rosenberg, " Traversal Using Relays around NAT (TURN): Relay Extensions to Session Traversal Utilities for NAT (STUN) ", RFC 5766, April 2010.
[RFC5780]	MacDonald, D. and B. Lowekamp, " NAT Behavior Discovery Using Session Traversal Utilities for NAT (STUN) ", RFC 5780, May 2010.
[RFC5804]	Melnikov, A. and T. Martin, " A Protocol for Remotely Managing Sieve Scripts ", RFC 5804, July 2010.
[RFC5864]	Allbery, R., " NS SRV Resource Records for AFS ", RFC 5864, April 2010.
[RFC5928]	Petit-Huguenin, M., " Traversal Using Relays around NAT (TURN) Resolution Mechanism ", RFC 5928, August 2010.
[RFC6011]	Lawrence, S. and J. Elwell, " Session Initiation Protocol (SIP) User Agent Configuration ", RFC 6011, October 2010.
[RFC6120]	Saint-Andre, P., " Extensible Messaging and Presence Protocol (XMPP): Core ", RFC 6120, March 2011.
[RFC6186]	Daboo, C., " Use of SRV Records for Locating Email Submission/Access Services ", RFC 6186, March 2011.

Appendix A. Acknowledgements

Thanks go to Bill Fenner, Tony Hansen, Peter Koch, Olaf Kolkman, and Andrew Sullivan for diligent review of the earlier drafts.

Author's Address

Dave Crocker Crocker Brandenburg InternetWorking 675 Spruce Dr.
Sunnyvale, CA 94086 USA Phone: +1.408.246.8253 EMail:
dcrocker@bbiw.net URI: <http://bbiw.net/>