

|                                  |              |  |
|----------------------------------|--------------|--|
| Network Working Group            | C. Daboo     |  |
| Internet-Draft                   | Apple, Inc.  |  |
| Intended status: Standards Track | M. Douglass  |  |
| Expires: November 27, 2010       | RPI          |  |
|                                  | S. Lees      |  |
|                                  | Microsoft    |  |
|                                  | May 26, 2010 |  |

[TOC](#)

## **xCal: The XML format for iCalendar draft-daboo-et-al-icalendar-in-xml-04**

### **Abstract**

This specification defines "xCal", an XML format for iCalendar data.

### **Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on November 27, 2010.

### **Copyright Notice**

Copyright (c) 2010 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

---

## Table of Contents

|                             |                                                               |  |
|-----------------------------|---------------------------------------------------------------|--|
| <a href="#">1.</a>          | Introduction                                                  |  |
| <a href="#">2.</a>          | Conventions Used in This Document                             |  |
| <a href="#">3.</a>          | Converting from iCalendar to xCal                             |  |
| <a href="#">3.1.</a>        | Pre-processing                                                |  |
| <a href="#">3.2.</a>        | iCalendar stream (RFC5545 section 3.4)                        |  |
| <a href="#">3.3.</a>        | Components (RFC5545 section 3.6)                              |  |
| <a href="#">3.4.</a>        | Properties (RFC5545 section 3.7 and 3.8)                      |  |
| <a href="#">3.4.1.</a>      | Special Cases for Properties                                  |  |
| <a href="#">3.4.1.1.</a>    | Multi-valued Properties                                       |  |
| <a href="#">3.4.1.2.</a>    | GEO Property                                                  |  |
| <a href="#">3.4.1.3.</a>    | REQUEST-STATUS Property                                       |  |
| <a href="#">3.5.</a>        | Parameters (RFC5545 section 3.2)                              |  |
| <a href="#">3.5.1.</a>      | VALUE parameter                                               |  |
| <a href="#">3.6.</a>        | Values (RFC5545 section 3.3)                                  |  |
| <a href="#">3.6.1.</a>      | Binary (RFC5545 section 3.3.1)                                |  |
| <a href="#">3.6.2.</a>      | Boolean (RFC5545 section 3.3.2)                               |  |
| <a href="#">3.6.3.</a>      | Calendar User Address (RFC5545 section 3.3.3)                 |  |
| <a href="#">3.6.4.</a>      | Date (RFC5545 section 3.3.4)                                  |  |
| <a href="#">3.6.5.</a>      | Date-Time (RFC5545 section 3.3.5)                             |  |
| <a href="#">3.6.6.</a>      | Duration (RFC5545 section 3.3.6)                              |  |
| <a href="#">3.6.7.</a>      | Float (RFC5545 section 3.3.7)                                 |  |
| <a href="#">3.6.8.</a>      | Integer (RFC5545 section 3.3.8)                               |  |
| <a href="#">3.6.9.</a>      | Period of Time (RFC5545 section 3.3.9)                        |  |
| <a href="#">3.6.10.</a>     | Recurrence Rule (RFC5545 section 3.3.10)                      |  |
| <a href="#">3.6.11.</a>     | Text (RFC5545 section 3.3.11)                                 |  |
| <a href="#">3.6.12.</a>     | Time (RFC5545 section 3.3.12)                                 |  |
| <a href="#">3.6.13.</a>     | URI (RFC5545 section 3.3.13)                                  |  |
| <a href="#">3.6.14.</a>     | UTC Offset (RFC5545 section 3.3.14)                           |  |
| <a href="#">3.7.</a>        | Extensions                                                    |  |
| <a href="#">4.</a>          | Converting from XML into iCalendar                            |  |
| <a href="#">4.1.</a>        | Converting XML Extensions into iCalendar                      |  |
| <a href="#">4.2.</a>        | The XML property for iCalendar                                |  |
| <a href="#">5.</a>          | Security Considerations                                       |  |
| <a href="#">6.</a>          | IANA Considerations                                           |  |
| <a href="#">6.1.</a>        | Namespace Registration                                        |  |
| <a href="#">6.2.</a>        | Media Type                                                    |  |
| <a href="#">7.</a>          | Acknowledgments                                               |  |
| <a href="#">8.</a>          | References                                                    |  |
| <a href="#">8.1.</a>        | Normative References                                          |  |
| <a href="#">8.2.</a>        | Informative References                                        |  |
| <a href="#">Appendix A.</a> | Relax NG Schema                                               |  |
| <a href="#">Appendix B.</a> | XML Stylesheet for conversion to iCalendar                    |  |
| <a href="#">Appendix C.</a> | Example                                                       |  |
| <a href="#">C.1.</a>        | iCalendar Data                                                |  |
| <a href="#">C.2.</a>        | XML Data                                                      |  |
| <a href="#">Appendix D.</a> | Change History (to be removed prior to publication as an RFC) |  |

---

## 1. Introduction

[TOC](#)

The iCalendar data format [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)," September 2009.\)](#) is a widely deployed interchange format for calendaring and scheduling data. While many applications and services consume and generate calendar data, iCalendar is a specialized format that requires its own parser/generator. In contrast, XML-based formats are widely used for interoperability between applications, and the many tools that generate, parse, and manipulate XML make it easier to work with than iCalendar.

The purpose of this specification is to define "xCal", an XML format for iCalendar data. xCal is defined so that iCalendar data to be converted to XML, and then back to iCalendar, without losing any semantic meaning in the data. Anyone creating XML calendar data according to this specification will know that their data can be converted to a valid iCalendar representation as well.

Two key design considerations are:

Round-tripping (converting an iCalendar instance to XML and back) will give the same result as the starting point.

Preserve the semantics of the iCalendar data. While a simple consumer can easily browse the calendar data in XML, a full understanding of iCalendar is still required in order to modify and/or fully comprehend the calendar data.

---

## 2. Conventions Used in This Document

[TOC](#)

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\] \(Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels," March 1997.\)](#).

When XML element types in the namespace

"urn:ietf:params:xml:ns:icalendar-2.0" are referenced in this document outside of the context of an XML fragment, the string "ICAL:" will be prefixed to the element types.

Some examples in this document contain "partial" XML documents used for illustrative purposes. In these examples, three periods "..." are used

to indicate a portion of the document that has been removed for compactness.

---

### 3. Converting from iCalendar to xCal

[TOC](#)

This section describes how iCalendar data is converted to XML using a simple mapping between the iCalendar data model and XML elements.

---

#### 3.1. Pre-processing

[TOC](#)

iCalendar uses a line folding mechanism to limit lines of data to a maximum line length (typically 72 characters) to ensure maximum likelihood of preserving data integrity as it is transported via various means (e.g., email) - see Section 3.1 of [\[RFC5545\]](#) (Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification (iCalendar)," September 2009.). Prior to converting iCalendar data into XML all folded lines MUST be unfolded. iCalendar data uses an "escape" character sequence for text values and parameter values. When such text elements are converted into XML the escaping MUST be removed. iCalendar uses a base64 encoding for binary data. The base64 encoding MUST remain when converted to XML.

---

#### 3.2. iCalendar stream (RFC5545 section 3.4)

[TOC](#)

At the top level of the iCalendar object model is an "iCalendar stream". This object encompasses multiple "iCalendar objects". In XML, the entire stream is contained in the root ICAL:icalendar XML element. An iCalendar stream can contain one or more iCalendar objects. Each iCalendar object, delimited by BEGIN:VCALENDAR and END:VCALENDAR, is enclosed by the ICAL:vcalendar XML element. Example:

```
<?xml version="1.0" encoding="utf-8"?>
<icalendar xmlns="urn:ietf:params:xml:ns:icalendar-2.0">
  <vcalendar>
    ...
  </vcalendar>
</icalendar>
```

iCalendar objects are comprised of a set of "components", "properties", "parameters" and "values". A "component" can contain other "components" or "properties". A "property" has a value and optionally a set of "parameters".

In xCal, "components" are contained within an ICAL:components XML element. With that element, another ICAL:components element could appear (representing components nested within components) or the ICAL:properties XML element could appear. ICAL:properties is used to encapsulate iCalendar properties.

Each iCalendar property will be mapped to its own XML element as described below. Within each of these elements there is an optional ICAL:parameters XML element used to encapsulate any iCalendar parameters. Additionally there will be one or more XML elements representing the value of the iCalendar property.

Example:

```
<?xml version="1.0" encoding="utf-8"?>
<icalendar xmlns="urn:ietf:params:xml:ns:icalendar-2.0">
  <vcalendar>
    <properties>
      ...
    </properties>
    <components>
      ...
    </components>
  </vcalendar>
</icalendar>
```

| Item             | XML element    | XML Definition                                     |
|------------------|----------------|----------------------------------------------------|
| iCalendar Stream | ICAL:icalendar | <a href="#">Appendix A (Relax NG Schema)</a> # 3.4 |
| VCALENDAR        | ICAL:vcalendar | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6 |

---

### 3.3. Components (RFC5545 section 3.6)

[TOC](#)

Each calendar component in the VCALENDAR object, delimited by BEGIN and END, will be converted to an enclosing XML element with the same name, but in lowercase:

| Component | XML element   | XML Definition                                       |
|-----------|---------------|------------------------------------------------------|
| VEVENT    | ICAL:vevent   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.1 |
| VTODO     | ICAL:vtodo    | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.2 |
| VJOURNAL  | ICAL:vjournal | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.3 |

|           |                 |                                                      |
|-----------|-----------------|------------------------------------------------------|
| VFREEBUSY | ICAL:vfreesbusy | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.4 |
| VTIMEZONE | ICAL:vtimezone  | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.5 |
| STANDARD  | ICAL:standard   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.5 |
| DAYLIGHT  | ICAL:daylight   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.5 |
| VALARM    | ICAL:valarm     | <a href="#">Appendix A (Relax NG Schema)</a> # 3.6.6 |

### 3.4. Properties (RFC5545 section 3.7 and 3.8)

[TOC](#)

iCalendar properties , whether they apply to the VCALENDAR object or to a component, are handled in a consistent way in the xCal format. iCalendar properties are enclosed in the XML element ICAL:properties. Each individual iCalendar property is represented in XML by an element of the same name as the iCalendar property, but in lowercase. For example, the CALSCALE property is represented in XML by the ICAL:calscale element.

Example:

```
<?xml version="1.0" encoding="utf-8"?>
<icalendar xmlns="urn:ietf:params:xml:ns:icalendar-2.0">
  <vcalendar>
    <properties>
      <calscale>...</calscale>
      <version>...</version>
      <prodid>...</prodid>
    </properties>
    <components>
      ...
    </components>
  </vcalendar>
</icalendar>
```

Each property can contain an ICAL:parameters XML element encapsulating any iCalendar parameters associated with the iCalendar property. Each property will contain one or more "value" XML elements as described below representing the value of the iCalendar property.

| Property | XML element   | XML Definition                                       |
|----------|---------------|------------------------------------------------------|
| CALSCALE | ICAL:calscale | <a href="#">Appendix A (Relax NG Schema)</a> # 3.7.1 |
| METHOD   | ICAL:method   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.7.2 |
| PRODID   | ICAL:prodid   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.7.3 |

|                  |                       |                                                            |
|------------------|-----------------------|------------------------------------------------------------|
| VERSION          | ICAL:version          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.7.4    |
| ATTACH           | ICAL:attach           | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.1  |
| CATEGORIES       | ICAL:categories       | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.2  |
| CLASS            | ICAL:class            | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.3  |
| COMMENT          | ICAL:comment          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.4  |
| DESCRIPTION      | ICAL:description      | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.5  |
| GEO              | ICAL:geo              | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.6  |
| LOCATION         | ICAL:location         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.7  |
| PERCENT-COMPLETE | ICAL:percent-complete | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.8  |
| PRIORITY         | ICAL:priority         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.9  |
| RESOURCES        | ICAL:resources        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.10 |
| STATUS           | ICAL:status           | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.11 |
| SUMMARY          | ICAL:summary          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.1.12 |
| COMPLETED        | ICAL:completed        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.1  |
| DTEND            | ICAL:dtend            | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.2  |
| DUE              | ICAL:due              | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.3  |
| DTSTART          | ICAL:dtstart          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.4  |
| DURATION         | ICAL:duration         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.5  |
| FREEBUSY         | ICAL:freebusy         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.6  |
| TRANSP           | ICAL:transp           | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.2.7  |
| TZID             | ICAL:tzid             | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.3.1  |
| TZNAME           | ICAL:tzname           |                                                            |

|                |                     |                                                           |
|----------------|---------------------|-----------------------------------------------------------|
|                |                     | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.3.2 |
| TZOFFSETFROM   | ICAL:tzoffsetfrom   | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.3.3 |
| TZOFFSETTO     | ICAL:tzoffsetto     | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.3.4 |
| TZURL          | ICAL:tzurl          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.3.5 |
| ATTENDEE       | ICAL:attendee       | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.1 |
| CONTACT        | ICAL:contact        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.2 |
| ORGANIZER      | ICAL:organizer      | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.3 |
| RECURRENCE-ID  | ICAL:recurrence-id  | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.4 |
| RELATED-TO     | ICAL:related-to     | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.5 |
| URL            | ICAL:url            | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.6 |
| UID            | ICAL:uid            | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.4.7 |
| EXDATE         | ICAL:exdate         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.5.1 |
| RDATE          | ICAL:rdate          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.5.2 |
| RRULE          | ICAL:rrule          | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.5.3 |
| ACTION         | ICAL:action         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.6.1 |
| REPEAT         | ICAL:repeat         | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.6.2 |
| TRIGGER        | ICAL:trigger        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.6.3 |
| CREATED        | ICAL:created        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.7.1 |
| DTSTAMP        | ICAL:dtstamp        | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.7.2 |
| LAST-MODIFIED  | ICAL:last-modified  | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.7.3 |
| SEQUENCE       | ICAL:sequence       | <a href="#">Appendix A (Relax NG Schema)</a> #<br>3.8.7.4 |
| REQUEST-STATUS | ICAL:request-status |                                                           |

---

### 3.4.1. Special Cases for Properties

[TOC](#)

Some properties in iCalendar can contain "structured" value data. This includes lists of "standard" value types, as well as values with specific "fields". In xCal, these "structured" values are represented as separate XML elements in various ways for ease of processing using standard XML tools.

---

#### 3.4.1.1. Multi-valued Properties

[TOC](#)

The following iCalendar properties can have values that consist of a list of "standard" iCalendar values separated by a specific delimiter. In XML these properties are represented by an XML element that contains multiple "value" elements ([Section 3.6 \(Values \(RFC5545 section 3.3\)\)](#)).

| Property   | XML element     | XML Definition                                          |
|------------|-----------------|---------------------------------------------------------|
| CATEGORIES | ICAL:categories | <a href="#">Appendix A (Relax NG Schema)</a> # 3.8.1.2  |
| RESOURCES  | ICAL:resources  | <a href="#">Appendix A (Relax NG Schema)</a> # 3.8.1.10 |
| FREEBUSY   | ICAL:freebusy   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.8.2.6  |
| EXDATE     | ICAL:exdate     | <a href="#">Appendix A (Relax NG Schema)</a> # 3.8.5.1  |
| RDATE      | ICAL:rdate      | <a href="#">Appendix A (Relax NG Schema)</a> # 3.8.5.2  |

---

#### 3.4.1.2. GEO Property

[TOC](#)

In iCalendar, the GEO property value is defined as a semi-colon separated list of two FLOAT values, the first representing latitude and the second longitude.

In xCal, the value for the ICAL:geo element is represented by an ICAL:value element containing an ICAL:latitude element and an ICAL:longitude element, each of which contain text values representing the FLOAT values. See [Appendix A \(Relax NG Schema\)](#) # 3.8.1.6.

---

[TOC](#)

### 3.4.1.3. REQUEST-STATUS Property

In iCalendar, the REQUEST-STATUS property value is defined as a semi-colon separated list of two or three TEXT values. The first represents a code, the second a description, and the third (optional) additional data.

In xCal, the value for the ICAL:request-status element is represented by an ICAL:value element containing an ICAL:code element, and iCAL:description element, and optionally and ICAL:data element, each of which contain the corresponding TEXT values. See [Appendix A \(Relax NG Schema\)](#) # 3.8.8.3.

---

## 3.5. Parameters (RFC5545 section 3.2)

[TOC](#)

iCalendar parameters are enclosed in the XML element ICAL:parameters which optionally occurs once in each property XML element. Each individual iCalendar parameter is represented in xCal by an element of the same name as the iCalendar parameter, but in lowercase. For example, the PARTSTAT parameter is represented in XML by the ICAL:partstat element.

Example:

```
<?xml version="1.0" encoding="utf-8"?>
<icalendar xmlns="urn:ietf:params:xml:ns:icalendar-2.0">
  <vcalendar>
    ...
    <components>
      ...
      <attendee>
        <parameters>
          <partstat>NEEDS-ACTION</partstat>
        </parameters>
      ...
    </components>
  </vcalendar>
</icalendar>
```

Each parameter contains either text, or one or more child XML elements representing iCalendar value types.

| Parameter | XML element | XML Definition                                       |
|-----------|-------------|------------------------------------------------------|
| ALTREP    | ICAL:altrep | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.1 |
| CN        | ICAL:cn     | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.2 |
| CUTYPE    | ICAL:cutype | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.3 |
|           |             | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.4 |

|                |                     |                                                       |
|----------------|---------------------|-------------------------------------------------------|
| DELEGATED-FROM | ICAL:delegated-from |                                                       |
| DELEGATED-TO   | ICAL:delegated-to   | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.5  |
| DIR            | ICAL:dir            | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.6  |
| ENCODING       | ICAL:encoding       | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.7  |
| FMTTYPE        | ICAL:fmttype        | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.8  |
| FBTYP          | ICAL:fbtype         | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.9  |
| LANGUAGE       | ICAL:language       | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.10 |
| MEMBER         | ICAL:member         | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.11 |
| PARTSTAT       | ICAL:partstat       | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.12 |
| RANGE          | ICAL:range          | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.13 |
| RELATED        | ICAL:related        | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.14 |
| RELTYPE        | ICAL:reltype        | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.15 |
| ROLE           | ICAL:role           | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.16 |
| RSVP           | ICAL:rsvp           | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.17 |
| SENT-BY        | ICAL:sent-by        | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.18 |
| TZID           | ICAL:tzid           | <a href="#">Appendix A (Relax NG Schema)</a> # 3.2.19 |

### 3.5.1. VALUE parameter

[TOC](#)

iCalendar defines a VALUE parameter (Section 3.2.20 of [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)," September 2009.\)](#)). This parameter is not mapped to an xCal XML element. Instead, the value type is handled by having different XML elements for each value, and these appear inside of ICAL:property elements. Thus, when converting from iCalendar to XML, any VALUE parameters are skipped. When converting from XML into iCalendar, the appropriate VALUE parameter MUST be included in the iCalendar property if the value type is not the default value type for that property.

---

### 3.6. Values (RFC5545 section 3.3)

[TOC](#)

iCalendar value types are mapped into XML elements with a matching name in all lowercase. In some cases, iCalendar defines "structured" values and these are mapped into separate child elements in each value element, as described by the simple DTD definitions below. Some properties allow for multiple values and these are represented by separate matching value XML elements.

---

#### 3.6.1. Binary (RFC5545 section 3.3.1)

[TOC](#)

**Description:** iCalendar BINARY property values are represented by the ICAL:binary XML element. The content of the element is base64 encoded data. Whitespace MAY be inserted into the data at any point to "wrap" the data to reasonable line lengths. When converting back to iCalendar the whitespace MUST first be removed.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.1

---

#### 3.6.2. Boolean (RFC5545 section 3.3.2)

[TOC](#)

**Description:** iCalendar BOOLEAN property values are represented by the ICAL:boolean XML element. The content of the element is text containing either of "TRUE" or "FALSE".

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.2

---

#### 3.6.3. Calendar User Address (RFC5545 section 3.3.3)

[TOC](#)

**Description:** iCalendar CAL-ADDRESS property values are represented by the ICAL:cal-address XML element. The content of the element is a URI.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.3

---

#### 3.6.4. Date (RFC5545 section 3.3.4)

[TOC](#)

**Description:** iCalendar DATE property values are represented by the ICAL:date XML element. The content of the element is the same date value specified by RFC5545.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.4

---

#### 3.6.5. Date-Time (RFC5545 section 3.3.5)

[TOC](#)

**Description:** iCalendar DATE-TIME property values are represented by the ICAL:date-time XML element. The content of the element is the same date-time value specified by RFC5545.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.5

---

#### 3.6.6. Duration (RFC5545 section 3.3.6)

[TOC](#)

**Description:** iCalendar DURATION property values are represented by the ICAL:duration XML element. The content of the element is the same duration value specified by RFC5545.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.6

---

#### 3.6.7. Float (RFC5545 section 3.3.7)

[TOC](#)

**Description:** iCalendar FLOAT property values are represented by the ICAL:float XML element. The content of the element is a text representation of a floating point number.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.7

---

#### 3.6.8. Integer (RFC5545 section 3.3.8)

[TOC](#)

**Description:**

iCalendar INTEGER property values are represented by the ICAL:integer XML element. The content of the element is a text representation of an integer number.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.8

---

#### 3.6.9. Period of Time (RFC5545 section 3.3.9)

[TOC](#)

**Description:** iCalendar PERIOD property values are represented by the ICAL:period XML element. The content of the element is the same period value specified by RFC5545.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.9

---

#### 3.6.10. Recurrence Rule (RFC5545 section 3.3.10)

[TOC](#)

**Description:** iCalendar RECUR property values are represented by the ICAL:recur XML element. The content of the element is child elements representing the various components of a recurrence rule.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.10

---

#### 3.6.11. Text (RFC5545 section 3.3.11)

[TOC](#)

**Description:** iCalendar TEXT property values are represented by the ICAL:text XML element. The content of the element is simple text.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.11

---

#### 3.6.12. Time (RFC5545 section 3.3.12)

[TOC](#)

**Description:** iCalendar TIME property values are represented by the ICAL:time XML element. The content of the element is the same time value specified by RFC5545.

**XML Definition:**

[Appendix A \(Relax NG Schema\)](#) # 3.3.12

---

**3.6.13. URI (RFC5545 section 3.3.13)**

[TOC](#)

**Description:** iCalendar URI property values are represented by the ICAL:uri XML element. The content of the element is a URI.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.13

---

**3.6.14. UTC Offset (RFC5545 section 3.3.14)**

[TOC](#)

**Description:** iCalendar UTC-OFFSET property values are represented by the ICAL:utc-offset XML element. The content of the element is the same UTC offset value specified by RFC5545.

**XML Definition:** [Appendix A \(Relax NG Schema\)](#) # 3.3.14

---

**3.7. Extensions**

[TOC](#)

iCalendar extension properties and parameters (those with an "X-" prefix in their name) are handled in the same way as other properties and parameters: the property or parameter is represented by an XML element with the same name, but in lowercase. e.g., the "X-FOO" property in iCalendar turns into the ICAL:x-foo element in XML.

---

**4. Converting from XML into iCalendar**

[TOC](#)

When converting component, property and parameter values, the names SHOULD be converted to uppercase. Although iCalendar names are case insensitive, common practice is to keep them all uppercase following the actual definitions in [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)," September 2009.\)](#).

Backslash escaping and line folding MUST be applied to the resulting iCalendar data as required by [\[RFC5545\] \(Desruisseaux, B., "Internet](#)

#### 4.1. Converting XML Extensions into iCalendar

[TOC](#)

XML extensions are converted back to iCalendar in one of two ways, depending on whether the extensions are in the iCalendar XML namespace, or in an external namespace.

Extensions that are part of the iCalendar XML namespace MUST have element names that begin with "x-", and will be converted back to the equivalent extension property in iCalendar. For example, the "x-foo" element will convert to the "X-FOO" iCalendar property.

Extensions that are in a namespace other than the iCalendar XML namespace SHOULD be preserved in the iCalendar representation using the XML iCalendar property described in [Section 4.2 \(The XML property for iCalendar\)](#).

---

#### 4.2. The XML property for iCalendar

[TOC](#)

This section describes an extension property for iCalendar, as covered in section 8.2.3 of [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)," September 2009.\)\).](#)

Property name: XML

Purpose: To embed XML-encoded calendar data in the iCalendar format.

Value type: A single text value.

Property parameters: None allowed.

Conformance: The property can appear on any iCalendar component.

Description: The value of this property is an XML element. The XML property MUST NOT be used to contain properties that are already defined in iCalendar, or properties that use the "X-" iCalendar extension property syntax. Since all elements in the urn:ietf:params:xml:ns:icalendar-2.0 namespace convert to a well-defined iCalendar object, the elements in this property MUST NOT be in the urn:ietf:params:xml:ns:icalendar-2.0 namespace. The XML element which is the value of this property MUST have an XML namespace declaration.

There can be more than one XML property present for a given iCalendar object. The ordering of XML properties is not preserved in the conversion between XML and iCalendar.

Format definition: This property is defined by the following notation:

xml = "XML:" text CRLF

Example: The following is an example of an iCalendar event with a location embedded in KML markup inside the XML property.

```
BEGIN:VCALENDAR
CALSCALE:GREGORIAN
PRODID:-//Example Inc.//Example Calendar//EN
VERSION:2.0
BEGIN:VEVENT
DTSTAMP:20080205T191224Z
DTSTART:20081006
SUMMARY:Planning meeting
UID:4088E990AD89CB3DBB484909
XML:<kml xmlns="http://www.opengis.net/kml/2.2">...</kml>
END:VEVENT
END:VCALENDAR
```

---

## 5. Security Considerations

[TOC](#)

This extension does not introduce any new security concerns than those already described in iCalendar.

---

## 6. IANA Considerations

[TOC](#)

This document defines a new URN to identify a new XML namespace for iCalendar data. The URN conforms to a registry mechanism described in [\[RFC3688\]](#) (Mealling, M., "The IETF XML Registry," January 2004.).

This document defines a new media type. The registration is in [Section 6.2 \(Media Type\)](#).

This document defines a new property for iCalendar. The registration is in [Section 4.2 \(The XML property for iCalendar\)](#).

---

### 6.1. Namespace Registration

[TOC](#)

Registration request for the iCalendar namespace:

URI: urn:ietf:params:xml:ns:icalendar-2.0

Registrant Contact: See the "Authors' Addresses" section of this document.

XML: None. Namespace URIs do not represent an XML specification.

---

[TOC](#)

## 6.2. Media Type

This section defines the MIME media type for use with iCalendar in XML data.

**To:** ietf-types@iana.org

**Subject:** Registration of media type application/xml+calendar

**Type name:** application

**Subtype name:** calendar+xml

**Required parameters:** none

**Optional parameters:** charset, method, component and optinfo as defined for the text/calendar media type

**Encoding considerations:** iCalendar data is typically UTF-8 and thus the XML representation will follow that. As a result, for 7-bit transports, data in UTF-8 MUST be encoded in quoted-printable or base64.

**Security considerations:** See [Section 5 \(Security Considerations\)](#).

**Interoperability considerations:** This media type provides an alternative syntax to iCalendar data based on XML.

**Published specification:** This specification.

**Applications which use this media type:** Applications that currently make use of the text/calendar media type can use this as an alternative.

**Additional information:**

**Magic number(s):** None

**File extension(s):** XML data should use "xml" as the file extension.

**Macintosh file type code(s):** None specified.

**Person & email address to contact for further information:** See the "Author's Address" section of this document.

**Intended usage:** COMMON

**Restrictions on usage:** There are no restrictions on where this media type can be used.

**Author:**

See the "Author's Address" section of this document.

**Change controller:** IETF

---

## 7. Acknowledgments

[TOC](#)

This specification originated from the work of the XML technical committee of the Calendaring and Scheduling Consortium.

---

## 8. References

[TOC](#)

### 8.1. Normative References

[TOC](#)

|                        |                                                                                                                                                                                                                                                  |
|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| [RFC2119]              | <a href="#">Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels,"</a> BCP 14, RFC 2119, March 1997 ( <a href="#">TXT</a> , <a href="#">HTML</a> , <a href="#">XML</a> ).                                                      |
| [RFC3688]              | Mealling, M., " <a href="#">The IETF XML Registry</a> ," BCP 81, RFC 3688, January 2004 ( <a href="#">TXT</a> ).                                                                                                                                 |
| [RFC5545]              | Desruisseaux, B., " <a href="#">Internet Calendaring and Scheduling Core Object Specification (iCalendar)</a> ," RFC 5545, September 2009 ( <a href="#">TXT</a> ).                                                                               |
| [W3C.REC-xml-20040204] | Bray, T., Maler, E., Paoli, J., Yergeau, F., and C. Sperberg-McQueen, " <a href="#">Extensible Markup Language (XML) 1.0 (Third Edition)</a> ," World Wide Web Consortium FirstEdition REC-xml-20040204, February 2004 ( <a href="#">HTML</a> ). |

---

### 8.2. Informative References

[TOC](#)

## Appendix A. Relax NG Schema

[TOC](#)

Below is a Relax NG schema for iCalendar in XML. This schema uses the compact notation of Relax NG. The numeric section numbers given in the comments refer to section in [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\),"](#)

[September 2009.](#)). The ordering of elements follows the section ordering of [\[RFC5545\] \(Desruisseaux, B., "Internet Calendaring and Scheduling Core Object Specification \(iCalendar\)," September 2009.\)](#).

The Relax NG compact notation "?" operator is used to indicate an unordered list of items. However, that operator, as defined, allows "mixing" each element that it operates on at any depth within the other elements, rather than just allowing "mixing" of siblings only. As a result, the schema provided allows certain constructs that are not allowed in iCalendar. Given that there is no sibling-only unordered list operator in RelaxNG, this is the best representation that can be given.

```
# Relax NG Schema for iCalendar in XML

default namespace = "urn:ietf:params:xml:ns:icalendar-2.0"

# 3.2 Property Parameters

# 3.2.1 Alternate Text Representation

altrepparam = element altrep { value-uri }

# 3.2.2 Common Name

cnparam = element cn { text }

# 3.2.3 Calendar User Type

cutypeparam = element cutype {
    "INDIVIDUAL" |
    "GROUP" |
    "RESOURCE" |
    "ROOM" |
    "UNKNOWN"
}

# 3.2.4 Delegators

delfromparam = element delegated-from { value-cal-address+ }

# 3.2.5 Delegates

deltoparam = element delegated-to { value-cal-address+ }

# 3.2.6 Directory Entry Reference

dirparam = element dir { value-uri }

# 3.2.7 Inline Encoding

encodingparam = element encoding {
    "8BIT" |
    "BASE64"
}

# 3.2.8 Format Type

fmttypeparam = element fmttype { text }

# 3.2.9 Free/Busy Time Type
```

```

fbtypeparam = element fbtype {
    "FREE" |
    "BUSY" |
    "BUSY-UNAVAILABLE" |
    "BUSY-TENTATIVE"
}

# 3.2.10 Language

languageparam = element language { text }

# 3.2.11 Group or List Membership

memberparam = element member { value-cal-address+ }

# 3.2.12 Participation Status

partstatparam = element partstat {
    type-partstat-event |
    type-partstat-todo |
    type-partstat-jour
}

type-partstat-event = (
    "NEEDS-ACTION" |
    "ACCEPTED" |
    "DECLINED" |
    "TENTATIVE" |
    "DELEGATED"
)

type-partstat-todo = (
    "NEEDS-ACTION" |
    "ACCEPTED" |
    "DECLINED" |
    "TENTATIVE" |
    "DELEGATED" |
    "COMPLETED" |
    "IN-PROCESS"
)

type-partstat-jour = (
    "NEEDS-ACTION" |
    "ACCEPTED" |
    "DECLINED"
)

# 3.2.13 Recurrence Identifier Range

rangeparam = element range {

```

```

        "THISANDFUTURE"
    }

# 3.2.14 Alarm Trigger Relationship

trigrelparam = element related {
    "START" |
    "END"
}

# 3.2.15 Relationship Type

reltypeparam = element reltype {
    "PARENT" |
    "CHILD" |
    "SIBLING"
}

# 3.2.16 Participation Role

roleparam = element role {
    "CHAIR" |
    "REQ-PARTICIPANT" |
    "OPT-PARTICIPANT" |
    "NON-PARTICIPANT"
}

# 3.2.17 RSVP Expectation

rsvpparam = element rsvp {
    "TRUE" |
    "FALSE"
}

# 3.2.18 Sent By

sentbyparam = element sent-by { value-cal-address }

# 3.2.19 Time Zone Identifier

tzidparam = element tzid { text }

# 3.3 Property Value Data Types

# 3.3.1 BINARY

value-binary = element binary { text }

# 3.3.2 BOOLEAN

```

```
value-boolean = element boolean {
    ("TRUE" | "FALSE")
}

# 3.3.3 CAL-ADDRESS

value-cal-address = element cal-address { text }

# 3.3.4 DATE

value-date = element date {
    text
}

# 3.3.5 DATE-TIME

value-date-time = element date-time {
    text
}

# 3.3.6 DURATION

value-duration = element duration {
    text
}

# 3.3.7 FLOAT

value-float = element float { text }

# 3.3.8 INTEGER

value-integer = element integer { text }

# 3.3.9 PERIOD

value-period = element period {
    text
}

# 3.3.10 RECUR

value-recur = element recur {
    type-freq,
    (type-until | type-count)?,
    element interval { text }?,
    element bysecond { text }*,
    element byminute { text }*,
    element byhour { text }*,
    type-byday*,

```

```

        type-bymonthday*,
        type-byyearday*,
        type-byweekno*,
        element bymonth { text }*,
        type-bysetpos*,
        element wkst { type-weekday }?
    }

type-freq = element freq {
    "SECONDLY" |
    "MINUTELY" |
    "HOURLY" |
    "DAILY" |
    "WEEKLY" |
    "MONTHLY" |
    "YEARLY"
}

type-until = element until {
    type-date |
    type-date-time
}

type-count = element count { text }

type-weekday = (
    "SU" |
    "MO" |
    "TU" |
    "WE" |
    "TH" |
    "FR" |
    "SA"
)

type-byday = element byday {
    element ordwk {
        text
    }?,
    element weekday { type-weekday }
}

type-bymonthday = element bymonthday {
    text
}

type-byyearday = element byyearday {
    text
}

```

```

type-byweekno = element byweekno {
    text
}

type-bysetpos = element bysetpos {
    text
}

# 3.3.11 TEXT

value-text = element text { text }

# 3.3.12 TIME

value-time = element time { text }

# 3.3.13 URI

value-uri = element uri { text }

# 3.3.14 UTC-OFFSET

value-utc-offset = element utc-offset { text }


# 3.4 iCalendar Stream

start = element icalendar { vcalendar+ }


# 3.6 Calendar Components

vcalendar = element vcalendar {
    type-calprops,
    type-component
}

type-calprops = element properties {
    property-prodid &
    property-version &
    property-calscale? &
    property-method?
}

type-component = element components {
    (
        component-vevent |
        component-vtodo |
        component-vjournal |
        component-vfreebusy |
        component-vtimezone
    )
}

```

```
    )*  
}
```

### # 3.6.1 Event Component

```
component-vevent = element vevent {  
    type-eventprop,  
    element components {  
        component-valarm+  
    }?  
}
```

```
type-eventprop = element properties {  
    property-dtstamp &  
    property-dtstart &  
    property-uid &  
  
    property-class? &  
    property-created? &  
    property-description? &  
    property-geo? &  
    property-last-mod? &  
    property-location? &  
    property-organizer? &  
    property-priority? &  
    property-seq? &  
    property-status-event? &  
    property-summary? &  
    property-transp? &  
    property-url? &  
    property-recurid? &  
  
    property-rrule? &  
  
    (property-dtend | property-duration)? &  
  
    property-attach* &  
    property-attendee* &  
    property-categories* &  
    property-comment* &  
    property-contact* &  
    property-exdate* &  
    property-rstatus* &  
    property-related* &  
    property-resources* &  
    property-rdate*  
}
```

### # 3.6.2 To-do Component

```

component-vtodo = element vtodo {
    type-todoprop,
    element components {
        component-valarm+
    }?
}

type-todoprop = element properties {
    property-dtstamp &
    property-uid &

    property-class? &
    property-completed? &
    property-created? &
    property-description? &
    property-geo? &
    property-last-mod? &
    property-location? &
    property-organizer? &
    property-percent? &
    property-priority? &
    property-recurid? &
    property-seq? &
    property-status-todo? &
    property-summary? &
    property-url? &

    property-rrule? &

    (
        (property-dtstart?, property-dtend? ) |
        (property-dtstart, property-duration)?
    ) &

    property-attach* &
    property-attendee* &
    property-categories* &
    property-comment* &
    property-contact* &
    property-exdate* &
    property-rstatus* &
    property-related* &
    property-resources* &
    property-rdate*
}

```

### # 3.6.3 Journal Component

```

component-vjournal = element vjournal {

```

```

    type-jourprop
}

type-jourprop = element properties {
    property-dtstamp &
    property-uid &

    property-class? &
    property-created? &
    property-dtstart? &
    property-last-mod? &
    property-organizer? &
    property-recurid? &
    property-seq? &
    property-status-jour? &
    property-summary? &
    property-url? &

    property-rrule? &

    property-attach* &
    property-attendee* &
    property-categories* &
    property-comment* &
    property-contact* &
    property-description? &
    property-exdate* &
    property-related* &
    property-rdate* &
    property-rstatus*
}

```

#### # 3.6.4 Free/Busy Component

```

component-vfreebusy = element vfreebusy {
    type-fbprop
}

```

```

type-fbprop = element properties {
    property-dtstamp &
    property-uid &

    property-contact? &
    property-dtstart? &
    property-dtend? &
    property-duration? &
    property-organizer? &
    property-url? &

    property-attendee* &

```

```
    property-comment* &
    property-freebusy* &
    property-rstatus*
}
```

#### # 3.6.5 Time Zone Component

```
component-vtimezone = element vtimezone {
    element properties {
        property-tzid &

        property-last-mod? &
        property-tzurl?
    },
    element components {
        (component-standard | component-daylight) &
        component-standard* &
        component-daylight*
    }
}
```

```
component-standard = element standard {
    type-tzprop
}
```

```
component-daylight = element daylight {
    type-tzprop
}
```

```
type-tzprop = element properties {
    property-dtstart &
    property-tzoffsetto &
    property-tzoffsetfrom &

    property-rrule? &

    property-comment* &
    property-rdate* &
    property-tzname*
}
```

#### # 3.6.6 Alarm Component

```
component-valarm = element valarm {
    audioprop | dispprop | emailprop
}
```

```
type-audioprop = element properties {
    property-action &
    property-trigger &
```

```

        (property-duration, property-repeat)? &
        property-attach?
    }

```

```

type-dispprop = element properties {
    property-action &
    property-description &
    property-trigger &
    property-summary &

    property-attendee+ &

    (property-duration, property-repeat)? &
    property-attach*
}

```

```

type-emailprop = element properties {
    property-action &
    property-description &
    property-trigger &

    (property-duration, property-repeat)?
}

```

### # 3.7 Calendar Properties

#### # 3.7.1 Calendar Scale

```

property-calscale = element calscale {

    element parameters { empty }?,

    element text { "GREGORIAN" }
}

```

#### # 3.7.2 Method

```

property-method = element method {

    element parameters { empty }?,

    value-text
}

```

#### # 3.7.3 Product Identifier

```

property-prodid = element prodid {

```

```
    element parameters { empty }?,  
    value-text  
}
```

#### # 3.7.4 Version

```
property-version = element version {  
    element parameters { empty }?,  
    value-text  
}
```

### # 3.8 Component Properties

#### # 3.8.1 Descriptive Component Properties

##### # 3.8.1.1 Attachment

```
property-attach = element attach {  
    element parameters {  
        fmttypeparam? &  
        encodingparam?  
    }?,  
    value-uri | value-binary  
}
```

##### # 3.8.1.2 Categories

```
property-categories = element categories {  
    element parameters {  
        languageparam? &  
    }?,  
    value-text+  
}
```

##### # 3.8.1.3 Classification

```
property-class = element class {  
    element parameters { empty }?,  
    element text {  
        "PUBLIC" |  
        "PRIVATE" |
```

```

        "CONFIDENTIAL"
    }
}

# 3.8.1.4 Comment

property-comment = element comment {

    element parameters {
        altrepparam? &
        languageparam?
    }?,

    value-text
}

# 3.8.1.5 Description

property-description = element description {

    element parameters {
        altrepparam? &
        languageparam?
    }?,

    value-text
}

# 3.8.1.6 Geographic Position

property-geo = element geo {

    element parameters { empty }?,

    element value {
        element latitude { text },
        element longitude { text }
    }
}

# 3.8.1.7 Location

property-location = element location {

    element parameters {
        altrepparam? &
        languageparam?
    }?,

    value-text
}

```

```
}
```

```
# 3.8.1.8 Percent Complete
```

```
property-percent = element percent-complete {
```

```
    element parameters { empty }?,
```

```
    value-integer
```

```
}
```

```
# 3.8.1.9 Priority
```

```
property-priority = element priority {
```

```
    element parameters { empty }?,
```

```
    value-integer
```

```
}
```

```
# 3.8.1.10 Resources
```

```
property-resources = element resources {
```

```
    element parameters {  
        altrepparam? &  
        languageparam?  
    }?,
```

```
    value-text+
```

```
}
```

```
# 3.8.1.11 Status
```

```
property-status-event = element status {
```

```
    element parameters { empty }?,
```

```
    element text {  
        "TENTATIVE" |  
        "CONFIRMED" |  
        "CANCELLED"  
    }  
}
```

```
}
```

```
property-status-todo = element status {
```

```
    element parameters { empty }?,
```

```
    element text {
```

```

        "NEEDS-ACTION" |
        "COMPLETED" |
        "IN-PROCESS" |
        "CANCELLED"
    }
}

property-status-jour = element status {

    element parameters { empty }?,

    element text {
        "DRAFT" |
        "FINAL" |
        "CANCELLED"
    }
}

```

#### # 3.8.1.12 Summary

```

property-summary = element summary {

    element parameters {
        altrepparam? &
        languageparam?
    }?,

    value-text
}

```

#### # 3.8.2 Date and Time Component Properties

##### # 3.8.2.1 Date/Time Completed

```

property-completed = element completed {

    element parameters { empty }?,

    value-date-time
}

```

##### # 3.8.2.2 Date/Time End

```

property-dtend = element dtend {

    element parameters {
        tzidparam?
    }?,

    value-date-time |

```

```
    value-date
}
```

#### # 3.8.2.3 Date/Time Due

```
property-due = element due {

    element parameters {
        tzidparam?
    }?,

    value-date-time |
    value-date
}
```

#### # 3.8.2.4 Date/Time Start

```
property-dtstart = element dtstart {

    element parameters {
        tzidparam?
    }?,

    value-date-time |
    value-date
}
```

#### # 3.8.2.5 Duration

```
property-duration = element duration {

    element parameters { empty }?,

    value-duration
}
```

#### # 3.8.2.6 Free/Busy Time

```
property-freebusy = element freebusy {

    element parameters {
        fbtypeparam?
    }?,

    value-period+
}
```

#### # 3.8.2.7 Time Transparency

```
property-transp = element transp {  
    element parameters { empty }?,  
    element text {  
        "OPAQUE" |  
        "TRANSPARENT"  
    }  
}
```

### # 3.8.3 Time Zone Component Properties

#### # 3.8.3.1 Time Zone Identifier

```
property-tzid = element tzid {  
    element parameters { empty }?,  
    value-text  
}
```

#### # 3.8.3.2 Time Zone Name

```
property-tzname = element tzname {  
    element parameters {  
        languageparam?  
    }?,  
    value-text  
}
```

#### # 3.8.3.3 Time Zone Offset From

```
property-tzoffsetfrom = element tzoffsetfrom {  
    element parameters { empty }?,  
    value-utc-offset  
}
```

#### # 3.8.3.4 Time Zone Offset To

```
property-tzoffsetto = element tzoffsetto {  
    element parameters { empty }?,  
    value-utc-offset  
}
```

#### # 3.8.3.5 Time Zone URL

```
property-tzurl = element tzurl {  
    element parameters { empty }?,  
    value-uri  
}
```

#### # 3.8.4 Relationship Component Properties

##### # 3.8.4.1 Attendee

```
property-attendee = element attendee {  
    element parameters {  
        cutypeparam? &  
        memberparam? &  
        roleparam? &  
        partstatparam? &  
        rsvpparam? &  
        deltoparam? &  
        delfromparam? &  
        sentbyparam? &  
        cnparam? &  
        dirparam? &  
        languageparam?  
    }?,  
    value-cal-address  
}
```

##### # 3.8.4.2 Contact

```
property-contact = element contact {  
    element parameters {  
        altrepparam? &  
        languageparam?  
    }?,  
    value-text  
}
```

##### # 3.8.4.3 Organizer

```
property-organizer = element organizer {  
    element parameters {  
        cnparam? &  
        dirparam? &
```

```

        sentbyparam? &
        languageparam?
    }?,

    value-cal-address
}

# 3.8.4.4 Recurrence ID

property-recurid = element recurrence-id {

    element parameters {
        tzidparam? &
        rangeparam?
    }?,

    value-date-time |
    value-date
}

# 3.8.4.5 Related-To

property-related = element related-to {

    element parameters {
        reltypeparam?
    }?,

    value-text
}

# 3.8.4.6 Uniform Resource Locator

property-url = element url {

    element parameters { empty }?,

    value-uri
}

# 3.8.4.7 Unique Identifier

property-uid = element uid {

    element parameters { empty }?,

    value-text
}

# 3.8.5 Recurrence Component Properties

```

#### # 3.8.5.1 Exception Date/Times

```
property-exdate = element exdate {  
  
    element parameters {  
        tzidparam?  
    }?,  
  
    value-date-time+ |  
    value-date+  
}
```

#### # 3.8.5.2 Recurrence Date/Times

```
property-rdate = element rdate {  
  
    element parameters {  
        tzidparam?  
    }?,  
  
    value-date-time+ |  
    value-date+ |  
    value-period+  
}
```

#### # 3.8.5.3 Recurrence Rule

```
property-rrule = element rrule {  
  
    element parameters { empty }?,  
  
    value-recur  
}
```

#### # 3.8.6 Alarm Component Properties

##### # 3.8.6.1 Action

```
property-action = element action {  
  
    element parameters { empty }?,  
  
    element text {  
        "AUDIO" |  
        "DISPLAY" |  
        "EMAIL"  
    }  
}
```

#### # 3.8.6.2 Repeat Count

```
property-repeat = element repeat {  
    element parameters { empty }?,  
    value-integer  
}
```

#### # 3.8.6.3 Trigger

```
property-repeat = element repeat {  
    (  
        element parameters {  
            trigretparam?  
        }?,  
        value-duration  
    ) |  
    (  
        element parameters { empty }?,  
        value-date-time  
    )  
}
```

#### # 3.8.7 Change Management Component Properties

##### # 3.8.7.1 Date/Time Created

```
property-created = element created {  
    element parameters { empty }?,  
    value-date-time  
}
```

##### # 3.8.7.2 Date/Time Stamp

```
property-dtstamp = element dtstamp {  
    element parameters { empty }?,  
    value-date-time  
}
```

##### # 3.8.7.3 Last Modified

```
property-last-mod = element last-modified {
```

```

        element parameters { empty }?,

        value-date-time
    }

# 3.8.7.4 Sequence Number

property-seq = element sequence {

    element parameters { empty }?,

    value-integer
}

# 3.8.8 Miscellaneous Component Properties

# 3.8.8.3 Request Status

property-rstatus = element request-status {

    element parameters {
        languageparam?
    }?,

    element value {
        element code { text },
        element description { text },
        element data { text }?
    }
}

```

---

## Appendix B. XML Stylesheet for conversion to iCalendar

[TOC](#)

TO DO

---

## Appendix C. Example

[TOC](#)

Below is some example iCalendar data and its representation in XML as defined by this specification.

---

[TOC](#)

## C.1. iCalendar Data

```
BEGIN:VCALENDAR
CALSCALE:GREGORIAN
PRODID:-//Example Inc.//Example Calendar//EN
VERSION:2.0
BEGIN:VEVENT
DTSTAMP:20080205T191224Z
DTSTART:20081006
SUMMARY:Planning meeting
UID:4088E990AD89CB3DBB484909
END:VEVENT
END:VCALENDAR
```

---

## C.2. XML Data

[TOC](#)

```
<?xml version="1.0" encoding="utf-8"?>
<icalendar xmlns="urn:ietf:params:xml:ns:icalendar-2.0">
  <vcalendar>
    <properties>
      <calscale><text>GREGORIAN</text></calscale>
      <prodid>
        <text>-//Example Inc.//Example Calendar//EN</text>
      </prodid>
      <version><text>2.0</text></version>
    </properties>
    <components>
      <vevent>
        <properties>
          <dtstamp><date-time>20080205T191224Z</date-time></dtstamp>
          <dtstart><date>20081006</date></dtstart>
          <summary>
            <text>Planning meeting</text>
          </summary>
          <uid>
            <text>4088E990AD89CB3DBB484909</text>
          </uid>
        </properties>
      </vevent>
    </components>
  </vcalendar>
</icalendar>
```

---

## Appendix D. Change History (to be removed prior to publication as an RFC)

[TOC](#)

Changes from -03:

1. Changed the proposed MIME type from xml+calendar to calendar+xml.
2. Fixed several references to sections of RFC5545.
3. Updated example in Appendix C.
4. Corrected the definition and grammar for TIME and UTC-OFFSET properties.

Changes from -02:

1. Removed the LINK extension and related sections. The concept will be addressed in a separate specification.
2. Various minor edits for clarity and consistency.

Changes from -01:

1. Added LINK extension to iCalendar and section discussing links in XML format.
2. Adopted "xCal" as the short name for the specification.

Changes from -00:

1. Changed 2445bis references to RFC5545.
2. Added a version number to the XML namespace for iCalendar.
3. Changed the values for the date, date-time, period, and duration elements to exactly match the values specified in RFC5545. Previously these were broken out into separate elements for day, month, year, etc.
4. Added specification for XML property in iCalendar.

---

## Authors' Addresses

[TOC](#)

|  |             |
|--|-------------|
|  | Cyrus Daboo |
|  | Apple Inc.  |

|         |                                                                          |
|---------|--------------------------------------------------------------------------|
|         | 1 Infinite Loop                                                          |
|         | Cupertino, CA 95014                                                      |
|         | USA                                                                      |
| E-Mail: | <a href="mailto:cyrus@daboo.name">cyrus@daboo.name</a>                   |
| URI:    | <a href="http://www.apple.com/">http://www.apple.com/</a>                |
|         |                                                                          |
|         | Mike Douglass                                                            |
|         | Rensselaer Polytechnic Institute                                         |
|         | 110 8th Street                                                           |
|         | Troy, NY 12180                                                           |
|         | USA                                                                      |
| E-Mail: | <a href="mailto:doug1m@rpi.edu">doug1m@rpi.edu</a>                       |
| URI:    | <a href="http://www.rpi.edu/">http://www.rpi.edu/</a>                    |
|         |                                                                          |
|         | Steven Lees                                                              |
|         | Microsoft Corporation                                                    |
|         | One Microsoft Way                                                        |
|         | Redmond, WA 98052                                                        |
|         | USA                                                                      |
| E-Mail: | <a href="mailto:steven.lees@microsoft.com">steven.lees@microsoft.com</a> |
| URI:    | <a href="http://www.microsoft.com/">http://www.microsoft.com/</a>        |