

Workgroup: MPLS
Internet-Draft:
draft-decraene-mpls-slid-encoded-entropy-
label-id-02
Updates: [6790](#) (if approved)
Published: 6 August 2021
Intended Status: Standards Track
Expires: 7 February 2022
Authors: B. Decraene, Ed. C. Filsfils
Orange Cisco Systems, Inc.
W. Henderickx T. Saad V. Beeram
Nokia Juniper Networks Juniper Networks
L. Jalil
Verizon

Using Entropy Label for Network Slice Identification in MPLS networks.

Abstract

This document defines a solution to encode a slice identifier in MPLS in order to distinguish packets that belong to different slices, to allow enforcing per network slice policies (.e.g, Qos).

The slice identification is independent of the topology. It allows for QoS/DiffServ policy on a per slice basis in addition to the per packet QoS/DiffServ policy provided by the MPLS Traffic Class field.

In order to minimize the size of the MPLS stack and to ease incremental deployment the slice identifier is encoded as part of the Entropy Label.

This document also extends the use of the TTL field of the Entropy Label in order to provide a flexible set of flags called the Entropy Label Control field.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 7 February 2022.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Entropy Label Control field](#)
- [3. Slice Identifier](#)
 - [3.1. Ingress LSR](#)
 - [3.2. Transit LSR](#)
 - [3.3. Bandwidth-Allocation Slice](#)
 - [3.4. Backward Compatibility](#)
 - [3.5. Benefits](#)
- [4. End to end absolute loss measurements](#)
- [5. Programmed sampling of packets](#)
- [6. Changes / Authors Notes](#)
- [7. References](#)
 - [7.1. Normative References](#)
 - [7.2. Informative References](#)
- [Authors' Addresses](#)

1. Introduction

Segment Routing (SR) [[RFC8402](#)] leverages the source-routing paradigm. A node steers a packet through a controlled set of instructions, called segments, by prepending the packet with an SR header. In the SR-MPLS data plane [[RFC8660](#)] , the SR header is instantiated through a label stack.

This document defines a solution to encode a slice identifier in MPLS in order to provide QoS on a per slice basis. It allows for QoS/DiffServ policy on a per slice basis in addition to the per packet QoS/DiffServ policy provided by the MPLS Traffic Class field. The slice identification is independent of the topology and the QoS of the network, thus enabling scalable network slicing.

This document encodes the slice identifier in a portion of the MPLS Entropy Label (EL) defined in [[RFC6790](#)]. This has advantages in SR-MPLS networks as it avoids the use of additional label which would increase the size of the label stack. This also reuses the data plane processing of the Entropy Label on the egress LSR, the signaling of the Entropy Label capability from the egress to the ingress [[I-D.ietf-isis-mpls-elic](#)] [[I-D.ietf-ospf-mpls-elic](#)], and the signaling capability of transit routers to read this label [[RFC8491](#)] which allows for an easier and faster incremental deployment.

2. Entropy Label Control field

[[RFC6790](#)] defines the MPLS Entropy Label. [[RFC6790](#)] section 4.2 defines the use of the Entropy Label Indicator (ELI) followed by the Entropy Label (EL) and the MPLS header fields (Label, TC, S, TTL) in each. [[RFC6790](#)] also specifies that the TTL field of the EL must be set to zero by the ingress LSR.

Following the procedures of [[RFC6790](#)] EL is never used for forwarding and its TTL is never looked at nor decremented:

*An EL capable Egress LSR performs a lookup on the ELI and as a result pop two labels: ELI and EL.

*An EL non-capable Egress LSR performs a lookup on the ELI and as a result must drop the packet as specified in [[RFC3031](#)] for the handling of an invalid incoming label.

Hence essentially the TTL field of the EL behaves as a reserved field which must be set to zero when sent and ignored when received.

This document extends the TTL field of the EL and calls it the Entropy Label Control (ELC) field. The ELC is a set of eight flags: ELC0 for bit 0, ELC1 for bit 1, ..., ELC7 for bit 7.

Given that the MPLS header is very compact (32 bits) with no reserved bits and that MPLS is used within a trusted administrative domain, the semantic of these bits is not standardized but defined on a per administrative domain basis. This allows for increased reuse and flexibility of this scarce resource. As a consequence, an application using one of those bits MUST allow the choice of the bit by configuration by the network operator.

3. Slice Identifier

Each network slice in an MPLS domain is uniquely identified by a Slice Identifier (SLID) [[I-D.bestbar-teas-ns-packet](#)]. This section encodes the SLID in a portion of the MPLS Entropy Label defined in [[RFC6790](#)].

The number of bits to be used for encoding the SLID in the EL is governed by a local policy and uniform within a network slice policy domain.

3.1. Ingress LSR

When an ingress LSR classifies that a packet belongs to the slice and that the egress has indicated via signaling that it can process EL for the tunnel, the ingress LSR pushes an Entropy Label with the:

- *SLID encoded in the most significant bits of the Entropy Label.

- *the entropy information encoded in the remaining lower bits of the Entropy Label as described in section 4.2 of [[RFC6790](#)] .

- *SPI bit (SLID Presence Indicator) set in one bit of the ELC field.

The choice of the ELC field used for SPI, and the number of bits to be used for encoding the SLID MUST be configurable by the network operator.

The slice classification method is outside the scope of this document.

The encoding of the Slide ID in the Entropy Label is in line with the specification of the Flow Label as the slide identification `_is_` a property of the flow:

- *For a given flow it is constant in all packets.

- *It's a property specific to the flow so would typically be used to determine the Entropy Label.

3.2. Transit LSR

Any router within the SR domain that forwards a packet with the SPI bit set MUST use the SLID to select a slice and apply per-slice policies.

There are many different policies that could define a slice for a particular application or service. The most basic of these is bandwidth-allocation, an implementation complying with this specification SHOULD support the bandwidth-allocation slice as defined in the next section.

3.3. Bandwidth-Allocation Slice

A per-slice policy is configured at each interface of each router in the SR domain, with one traffic shaper per SLID. The bit rate of

each shaper is configured to reflect the bandwidth allocation of the per-slice policy.

If shapers are not available, or desirable, an implementation MAY configure one scheduling queue per SLID with a guaranteed bandwidth equal to the bandwidth-allocation for the slice. This option allows a slice to consume more bandwidth than its allocation when available.

Per-slice shapers or queues effectively provides a virtual port per slice. This solution MAY be complemented with a per-virtual-port hierarchical DiffServ policy. Within the context of one specific slice, packets are further classified into children DiffServ queues which hang from the virtual port. The Traffic Class value in the MPLS header SHOULD be used for queue selection.

3.4. Backward Compatibility

The Entropy Label usage described in this document is consistent with [\[RFC6790\]](#) as ingress LSRs freely chooses the EL of a given flow, and transit LSRs treat the EL as an opaque set of bits.

As per [\[RFC6790\]](#) an ingress LSR that does not support this extension has the SPI bit cleared, and thus does not enable the SLID semantic of the Entropy bits. Hence, SLID-aware transit LSRs will not classify these packets into a slice.

3.5. Benefits

From a Segment Routing architecture perspective, this network slice identifier for SR-MPLS is inline with the network slice identifier for SRv6 proposed in [\[I-D.filsfils-spring-srv6-stateless-slice-id\]](#) .

From an SR-MPLS perspective, using the EL to carry the network slice identifier has multiple benefits:

- *This limits the number of labels pushed on the MPLS stack compared to using a pair of labels (ELI+EL) for flow entropy plus two or three labels for the slice indicator and the slice identifier. This is beneficial for the ingress LSR which may have limitations with regards to the number of labels pushed, for the transit LSR which may have limitations with regards to the label stack depth to be examined during transit in order to read both the entropy and the SLID. This presents additional benefit to network operators by reducing the packet overhead for traffic carried through the network;

- *This avoids defining new extensions for the signaling of the egress capability to support the slice indicator and the slice identifier;

*This improves incremental deployment as all egress LSRs supporting EL can be sent the slice identifier from day one, allowing slice classification on transit LSRs.

4. End to end absolute loss measurements

This section describes the usage of a ELC flag to enable packet loss measurements, as described in section 3.1 of [[RFC8321](#)] , for SR-MPLS networks.

TBD

5. Programmed sampling of packets

This section describes the usage of a ELC flag to detect end to end packet loss.

TBD

6. Changes / Authors Notes

[RFC Editor: Please remove this section before publication]

00: Initial version.

01: New co-author

02: editorial precision that the slice ID is a component of flow entropy hence inline with the use of entropy label.

7. References

7.1. Normative References

[[RFC6790](#)] Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", RFC 6790, DOI 10.17487/RFC6790, November 2012, <<https://www.rfc-editor.org/info/rfc6790>>.

[[RFC8402](#)] Filsfils, C., Ed., Previdi, S., Ed., Ginsberg, L., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing Architecture", RFC 8402, DOI 10.17487/RFC8402, July 2018, <<https://www.rfc-editor.org/info/rfc8402>>.

[[RFC8660](#)] Bashandy, A., Ed., Filsfils, C., Ed., Previdi, S., Decraene, B., Litkowski, S., and R. Shakir, "Segment Routing with the MPLS Data Plane", RFC 8660, DOI 10.17487/RFC8660, December 2019, <<https://www.rfc-editor.org/info/rfc8660>>.

7.2. Informative References

[I-D.bestbar-teas-ns-packet]

Saad, T., Beeram, V. P., Wen, B., Ceccarelli, D., Halpern, J., Peng, S., Chen, R., Liu, X., Contreras, L. M., and R. Rokui, "Realizing Network Slices in IP/MPLS Networks", Work in Progress, Internet-Draft, draft-bestbar-teas-ns-packet-03, 11 July 2021, <<https://www.ietf.org/archive/id/draft-bestbar-teas-ns-packet-03.txt>>.

[I-D.filsfils-spring-srv6-stateless-slice-id]

Filsfils, C., Clad, F., Camarillo, P., Raza, K., Voyer, D., and R. Rokui, "Stateless and Scalable Network Slice Identification for SRv6", Work in Progress, Internet-Draft, draft-filsfils-spring-srv6-stateless-slice-id-04, 30 July 2021, <<https://www.ietf.org/archive/id/draft-filsfils-spring-srv6-stateless-slice-id-04.txt>>.

[I-D.ietf-isis-mpls-elc] Xu, X., Kini, S., Psenak, P., Filsfils, C., Litkowski, S., and M. Bocci, "Signaling Entropy Label Capability and Entropy Readable Label Depth Using IS-IS", Work in Progress, Internet-Draft, draft-ietf-isis-mpls-elc-13, 28 May 2020, <<https://www.ietf.org/archive/id/draft-ietf-isis-mpls-elc-13.txt>>.

[I-D.ietf-ospf-mpls-elc] Xu, X., Kini, S., Psenak, P., Filsfils, C., Litkowski, S., and M. Bocci, "Signaling Entropy Label Capability and Entropy Readable Label Depth Using OSPF", Work in Progress, Internet-Draft, draft-ietf-ospf-mpls-elc-15, 1 June 2020, <<https://www.ietf.org/archive/id/draft-ietf-ospf-mpls-elc-15.txt>>.

[RFC3031] Rosen, E., Viswanathan, A., and R. Callon, "Multiprotocol Label Switching Architecture", RFC 3031, DOI 10.17487/RFC3031, January 2001, <<https://www.rfc-editor.org/info/rfc3031>>.

[RFC8321]

Fioccola, G., Ed., Capello, A., Cociglio, M., Castaldelli, L., Chen, M., Zheng, L., Mirsky, G., and T. Mizrahi, "Alternate-Marking Method for Passive and Hybrid Performance Monitoring", RFC 8321, DOI 10.17487/RFC8321, January 2018, <<https://www.rfc-editor.org/info/rfc8321>>.

[RFC8491]

Tantsura, J., Chunduri, U., Aldrin, S., and L. Ginsberg, "Signaling Maximum SID Depth (MSD) Using IS-IS", RFC 8491, DOI 10.17487/RFC8491, November 2018, <<https://www.rfc-editor.org/info/rfc8491>>.

Authors' Addresses

Bruno Decraene (editor)
Orange

Email: bruno.decraene@orange.com

Clarence Filsfils
Cisco Systems, Inc.
Belgium

Email: cf@cisco.com

Wim Henderickx
Nokia
Copernicuslaan 50
95134 Antwerp 2018
Belgium

Email: wim.henderickx@nokia.com

Tarek Saad
Juniper Networks

Email: tsaad@juniper.net

Vishnu Pavan Beeram
Juniper Networks

Email: vbeeram@juniper.net

Luay Jalil
Verizon

Email: luay.jalil@verizon.com