PCE Working Group Internet-Draft Updates: <u>5440</u> (if approved) Intended status: Standards Track Expires: April 24, 2015

# Update to Include Route Object (IRO) specification in Path Computation Element communication Protocol (PCEP) draft-dhody-pce-iro-update-00

#### Abstract

During discussions of a document to provide a standard representation and encoding of Domain-Sequence within the Path Computation Element (PCE) communication Protocol (PCEP) for communications between a Path Computation Client (PCC) and a PCE, or between two PCEs. It was determined that there was a need for clarification with respect to the ordered nature of the Include Route Object (IRO).

An informal survey was conducted to determine the state of current and planned implementation with respect to IRO ordering and handling of Loose bit.

This document updates the IRO specification based on the survey conclusion and recommendation.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 24, 2015.

Expires April 24, 2015

[Page 1]

IR0-UPDATE

## Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<u>1</u> .	Introduction	<u>2</u>
<u>1</u>	<u>.1</u> . Requirements Language	<u>3</u>
<u>2</u> .	Update in IRO specification	<u>3</u>
<u>3</u> .	Other Considerations	<u>4</u>
<u>4</u> .	Security Considerations	<u>4</u>
<u>5</u> .	IANA Considerations	<u>4</u>
<u>6</u> .	Acknowledgments	<u>4</u>
<u>7</u> .	References	<u>4</u>
7	<u>.1</u> . Normative References	<u>4</u>
7	<u>.2</u> . Informative References	<u>4</u>
Appe	endix A. Details of IRO survey	<u>6</u>

#### **<u>1</u>**. Introduction

The Path Computation Element Communication Protocol (PCEP) provides mechanisms for Path Computation Elements (PCEs) to perform path computations in response to Path Computation Clients (PCCs) requests.

[RFC5440] defines the Include Route Object (IRO) to specify that the computed path must traverse a set of specified network elements. The specification did not mention if IRO is an ordered or un-ordered list of sub-objects. It mentioned that the L bit (loose) has no meaning within an IRO.

[RFC5441] suggested the use of IRO to indicate the sequence of domains to be traversed during inter-domain path computation.

During discussion of [<u>I-D.ietf-pce-pcep-domain-sequence</u>] it was proposed to have a new IRO type with ordered nature, as well as handling of L bit.

[Page 2]

In order to discover the current state of affairs amongst implementations a survey of the existing and planned implementations was conducted. This survey [<u>I-D.dhody-pce-iro-survey</u>] was informal and conducted via email. Responses were collected and anonymized by the PCE working group chair.

This document updates the IRO specifications in [<u>RFC5440</u>] as per the conclusion and action points presented in [<u>I-D.dhody-pce-iro-survey</u>].

#### **<u>1.1</u>**. Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [<u>RFC2119</u>].

#### 2. Update in IRO specification

[RFC5440] describes IRO as an optional object used to specify that the computed path MUST traverse a set of specified network elements. It further state that the L bit of such sub-object has no meaning within an IRO. It did not mention if IRO is an ordered or un-ordered list of sub-objects.

A survey of the existing and planned implementations was conducted in order to discover the current state of affairs amongst implementations. [I-D.dhody-pce-iro-survey] describe the questionnaire, results and presents some conclusions and proposed action items. More details in Appendix A.

The survey suggest that most implementations construct or interpret IRO in an ordered fashion and consider it to be an ordered list. More than half of implementation under survey consider the IRO subobjects as strict hops, others consider loose or support both. The results shown in this survey seems to suggest that most implementations would be fine with updating [RFC5440] to specify IRO as an ordered list as well as to enable support for loose bit (L-bit) such that both strict and loose hops could be supported in the IRO.

This document thus updates [<u>RFC5440</u>] regarding the IRO specification making IRO as an ordered list as well as support for loose bit (L-bit).

The content of an IRO object is an ordered list of subobjects representing a series of abstract nodes. An abstract node may just be a simple abstract node comprising one node or a group of nodes for example an AS (comprising of multiple hops within the AS) (refer [<u>RFC3209</u>] for details). Further each subobject has an attribute

[Page 3]

called 'L-bit', which is set if the subobject represents a loose hop. If the bit is not set, the subobject represents a strict hop.

#### **<u>3</u>**. Other Considerations

Based on the survey, it should be noted that most implementation already support the update in the IRO specification as per this document. The other implementation are expected to make an update to the IRO procedures.

## **<u>4</u>**. Security Considerations

This update in IRO specification does not introduce any new security considerations, apart from those mentioned in [<u>RFC5440</u>]. Clarification in the supported IRO ordering or Loose bit handling will not have any negative security impact.

It is worth noting that PCEP operates over TCP. An analysis of the security issues for routing protocols that use TCP (including PCEP) is provided in [<u>RFC6952</u>] while [<u>I-D.ietf-pce-pceps</u>] discusses an experimental approach to provide secure transport for PCEP.

## 5. IANA Considerations

This informational document makes no requests to IANA for action.

### 6. Acknowledgments

A special thanks to PCE chairs for guidance regarding this work.

## 7. References

## 7.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", <u>BCP 14</u>, <u>RFC 2119</u>, March 1997.
- [RFC5440] Vasseur, JP. and JL. Le Roux, "Path Computation Element (PCE) Communication Protocol (PCEP)", <u>RFC 5440</u>, March 2009.

## 7.2. Informative References

[RFC3209] Awduche, D., Berger, L., Gan, D., Li, T., Srinivasan, V., and G. Swallow, "RSVP-TE: Extensions to RSVP for LSP Tunnels", <u>RFC 3209</u>, December 2001.

Expires April 24, 2015 [Page 4]

- [RFC5441] Vasseur, JP., Zhang, R., Bitar, N., and JL. Le Roux, "A Backward-Recursive PCE-Based Computation (BRPC) Procedure to Compute Shortest Constrained Inter-Domain Traffic Engineering Label Switched Paths", <u>RFC 5441</u>, April 2009.
- [RFC6952] Jethanandani, M., Patel, K., and L. Zheng, "Analysis of BGP, LDP, PCEP, and MSDP Issues According to the Keying and Authentication for Routing Protocols (KARP) Design Guide", RFC 6952, May 2013.
- [I-D.ietf-pce-pcep-domain-sequence]

Dhody, D., Palle, U., and R. Casellas, "Standard Representation Of Domain-Sequence", <u>draft-ietf-pce-pcep-</u> <u>domain-sequence-05</u> (work in progress), July 2014.

[I-D.ietf-pce-pceps]

Lopez, D., Dios, O., Wu, W., and D. Dhody, "Secure Transport for PCEP", <u>draft-ietf-pce-pceps-02</u> (work in progress), October 2014.

[I-D.dhody-pce-iro-survey]

Dhody, D., "Informal Survey into Include Route Object (IRO) Implementations in Path Computation Element communication Protocol (PCEP)", <u>draft-dhody-pce-iro-</u><u>survey-00</u> (work in progress), October 2014.

Expires April 24, 2015 [Page 5]

IR0-UPDATE

## Appendix A. Details of IRO survey

During discussions of this document to provide a standard representation and encoding of Domain-Sequence within PCEP. It was determined that there was a need for clarification with respect to the ordered nature of the IRO.

Since there was a proposal to have a new IRO type with ordering, as well as handling of Loose bit, in an earlier version of this document (refer - <u>draft-ietf-pce-pcep-domain-sequence-05</u>), it was deemed necessary to conduct a survey of the existing and planned implementations. An informal survey was conducted via email. Responses were collected and anonymized by the PCE working group chairs.

[I-D.dhody-pce-iro-survey] summarizes the survey questions and captures the results. It further list some conclusions and action points.

This document was considered as one possible venue to handle the proposed action points.

Author's Address

Dhruv Dhody Huawei Technologies Leela Palace Bangalore, Karnataka 560008 INDIA

EMail: dhruv.ietf@gmail.com

Expires April 24, 2015 [Page 6]