PCE Working Group Internet-Draft

Intended status: Standards Track

Expires: June 11, 2017

D. Dhody
Huawei Technologies
D. King
Lancaster University
December 8, 2016

Experimental Codepoint Allocation for Path Computation Element communication Protocol (PCEP) draft-dhody-pce-pcep-exp-codepoints-02

Abstract

IANA assigns values to the Path Computation Element (PCE) communication Protocol (PCEP) parameters (messages, objects, TLVs). IANA established a new top-level registry to contain all PCEP codepoints and sub-registries. The allocation policy for each new registry is by IETF Consensus.

This document seeks to mark some codepoints for experimental usage of PCEP.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of $\frac{BCP}{78}$ and $\frac{BCP}{79}$.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at http://datatracker.ietf.org/drafts/current/.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on June 11, 2017.

Copyright Notice

Copyright (c) 2016 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (http://trustee.ietf.org/license-info) in effect on the date of publication of this document. Please review these documents

Internet-Draft EXP-CODEPOINT December 2016

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

<u>1</u> .	Intr	oduc	ction																<u>2</u>
<u>2</u> .	PCEP	Mes	ssages	s.															<u>3</u>
<u>3</u> .	PCEP	0bj	jects																<u>3</u>
<u>4</u> .	PCEP	TLV	/s .																<u>3</u>
<u>5</u> .	IANA	Cor	nsiden	rat	ior	าร													<u>3</u>
5.	<u>.1</u> .	New	PCEP	Ме	SS	age	es												<u>3</u>
<u>5</u> .	<u>. 2</u> .	New	PCEP	0b	jed	cts	6												<u>3</u>
<u>5</u> .	<u>. 3</u> .	New	PCEP	TL	Vs														<u>4</u>
<u>6</u> .	Allo	cati	ion Po	oli	су														<u>4</u>
<u>7</u> .	Secu	rity	/ Cons	sid	era	ati	Lor	าร											<u>4</u>
<u>8</u> .	Ackn	owle	edgmer	nts															<u>4</u>
<u>9</u> .	Refe	renc	ces																<u>4</u>
9	<u>.1</u> .	Norm	native	e R	efe	ere	enc	ces	3										<u>5</u>
9	<u>. 2</u> .	Info	ormati	ive	Re	efe	ere	end	ces	3									<u>5</u>
Appe	<u>endix</u>	Α.	Othe	er	Cod	dep	iod	int	S										<u>6</u>
Auth	nors'	Add	dresse	es															6

1. Introduction

The Path Computation Element communication Protocol (PCEP) provides mechanisms for Path Computation Elements (PCEs) to perform path computations in response to Path Computation Clients (PCCs) requests.

In <u>section 9 of [RFC5440]</u>, IANA assigns values to the PCEP protocol parameters (messages, objects, TLVs). IANA established a new top-level registry to contain all PCEP codepoints and sub-registries. The allocation policy for each new registry is by IETF Consensus as described in [RFC5226]. Specifically, new assignments are made via RFCs approved by the IESG. Typically, the IESG will seek input on prospective assignments from appropriate persons (e.g., a relevant Working Group if one exists). Early allocation [RFC7120] provides some latitude for allocation of these code points, but is reserved for features that are considered appropriately stable.

With some recent advancement, there is an enhanced need to experiment with PCEP. It is often necessary to use some sort of number or constant in order to actually test or experiment with the new function, even when testing in a closed environment. In order to run experiment, it is important that the value won't collide not only with existing codepoints but any future allocation.

This document thus set apart some codepoints in PCEP registry and subregistries for experimental usage.

2. PCEP Messages

Some codepoints are requested to be set aside for experimentation with new PCEP messages. The suggested range is 246-255.

3. PCEP Objects

Some codepoints are requested to be set aside for experimentation with new PCEP objects. The suggested range is 224-255.

4. PCEP TLVs

Some codepoints are requested to be set aside for experimentation with new PCEP TLVs. The suggested range is 65280-65535.

[Editor's Note - There have been suggestions to increase this range a little bit more, perhaps to 65024-65535]

5. IANA Considerations

IANA maintains the "Path Computation Element Protocol (PCEP) Numbers" at http://www.iana.org/assignments/pcep>.

5.1. New PCEP Messages

Within this registry IANA maintains a sub-registry for PCEP Messages (see PCEP Messages at http://www.iana.org/assignments/pcep).

Upon approval of this document, IANA is requested to make the following allocations:

İ	Туре	Description	Ì	Allocation Policy	Ī
İ	246-255	Unassigned	Ì	Experimental Use	Ì

5.2. New PCEP Objects

Within this registry IANA maintains a sub-registry for PCEP Objects (see PCEP Objects at http://www.iana.org/assignments/pcep).

Upon approval of this document, IANA is requested to make the following allocations:

Type Description Allocation Policy ++	+		++
224-255 Unassigned Experimental Use			
++	224-255	Unassigned	Experimental Use

5.3. New PCEP TLVs

Within this registry IANA maintains a sub-registry for PCEP TLVs (see PCEP TLV Type Indicators at http://www.iana.org/assignments/pcep).

Upon approval of this document, IANA is requested to make the following allocations:

+	 + -		+-		-+
•	 •	•	•	Allocation Policy	
	•		•	Experimental Use	•
+	 +-		+-		-+

6. Allocation Policy

The allocation policy for the IANA request in $\frac{\text{Section 5}}{\text{Section 5}}$ is "Experimental". As per [RFC5226], IANA does not record specific assignments for any particular use for this policy.

As the experiment/standard progress and an early IANA allocation or RFC publication happens, the IANA defined codepoints are used and experimental code points are freed up.

7. Security Considerations

This document does not introduce any new security considerations to the existing protocol. Refer to $[{\tt RFC5440}]$ for further details of the specific security measures.

8. Acknowledgments

The authors would like to thank Ramon Casellas, Jeff Tantsura, Adrian Farrel, Jonathan Hardwick, Julien Mueric, Lou Berger, and Michael Shroff for their feedback and suggestions.

9. References

Internet-Draft EXP-CODEPOINT December 2016

9.1. Normative References

9.2. Informative References

- [RFC7120] Cotton, M., "Early IANA Allocation of Standards Track Code Points", <u>BCP 100</u>, <u>RFC 7120</u>, DOI 10.17487/RFC7120, January 2014, http://www.rfc-editor.org/info/rfc7120.

<u>Appendix A</u>. Other Codepoints

Based on the feedback from the WG, it was decided to focus only on the essentials in the scope of this documents. For others, Experiments can use a new experimental TLV/Object instead.

Authors' Addresses

Dhruv Dhody Huawei Technologies Divyashree Techno Park, Whitefield Bangalore, Karnataka 560066 India

EMail: dhruv.ietf@gmail.com

Daniel King Lancaster University UK

EMail: d.king@lancaster.ac.uk