

Workgroup: PCE
Internet-Draft: draft-dhody-pce-pceps-tls13-02
Updates: [8253](#) (if approved)
Published: 13 March 2023
Intended Status: Standards Track
Expires: 14 September 2023
Authors: D. Dhody S. Turner R. Housley
 Huawei Technologies sn3rd Vigil Security

Updates for PCEPS

Abstract

RFC 8253 defines how to protect PCEP messages with TLS 1.2. This document updates RFC 8253 to address support requirements for TLS 1.2 and TLS 1.3 and the use of TLS 1.3's early data.

Discussion Venues

This note is to be removed before publishing as an RFC.

Discussion of this document takes place on the Path Computation Element Working Group mailing list (pce@ietf.org), which is archived at <https://mailarchive.ietf.org/arch/browse/pce/>.

Source for this draft and an issue tracker can be found at <https://github.com/dhruvdhody/draft-dhody-pce-pceps-tls13>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 14 September 2023.

Copyright Notice

Copyright (c) 2023 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Conventions and Definitions](#)
- [3. Early Data](#)
- [4. Cipher Suites](#)
- [5. Security Considerations](#)
- [6. IANA Considerations](#)
- [7. References](#)
 - [7.1. Normative References](#)
 - [7.2. Informative References](#)
- [Acknowledgments](#)
- [Authors' Addresses](#)

1. Introduction

[RFC8253] defines how to protect PCEP messages [RFC5440] with TLS 1.2 [RFC5246]. This document updates [RFC8253] to address support requirements for TLS 1.2 [RFC5246] and TLS 1.3 [I-D.ietf-tls-rfc8446bis] and the use of TLS 1.3's early data, which is also known as 0-RTT data. All other provisions set forth in [RFC8253] are unchanged, including connection initiation, message framing, connection closure, certificate validation, peer identity, and failure handling.

Editor's Note: The reference to [I-D.ietf-tls-rfc8446bis] could be changed to RFC 8446 incase the progress of the bis draft is slower than the progression of this document.

2. Conventions and Definitions

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in BCP 14 [RFC2119] [RFC8174] when, and only when, they appear in all capitals, as shown here.

3. Early Data

Early data (aka 0-RTT data) is a mechanism defined in TLS 1.3 [[I-D.ietf-tls-rfc8446bis](#)] that allows a client to send data ("early data") as part of the first flight of messages to a server. Note that TLS 1.3 can be used without early data as per [Appendix F.5](#) of [[I-D.ietf-tls-rfc8446bis](#)]. In fact, early data is permitted by TLS 1.3 only when the client and server share a Pre-Shared Key (PSK), either obtained externally or via a previous handshake. The client uses the PSK to authenticate the server and to encrypt the early data.

As noted in [Section 2.3](#) of [[I-D.ietf-tls-rfc8446bis](#)], the security properties for early data are weaker than those for subsequent TLS-protected data. In particular, early data is not forward secret, and there is no protection against the replay of early data between connections. [Appendix E.5](#) of [[I-D.ietf-tls-rfc8446bis](#)] requires applications not use early data without a profile that defines its use. This document specifies that PCEPS implementations that support TLS 1.3 **MUST NOT** use early data.

4. Cipher Suites

Implementations **MUST** support TLS 1.2 [[RFC5246](#)] and are **REQUIRED** to support the TLS_ECDHE_RSA_WITH_AES_128_GCM_SHA256 cipher suite [[RFC9325](#)].

Implementations **MAY** implement additional TLS 1.2 cipher suites that provide mutual authentication and confidentiality as required by PCEP.

Implementations **SHOULD** support TLS 1.3 [[I-D.ietf-tls-rfc8446bis](#)] and, if implemented, **MUST** prefer to negotiate TLS 1.3 over earlier versions of TLS.

Implementations that support TLS 1.3 [[I-D.ietf-tls-rfc8446bis](#)] are **REQUIRED** to support the mandatory-to-implement cipher suites listed in [Section 9.1](#) of [[I-D.ietf-tls-rfc8446bis](#)].

Implementations that support TLS 1.3 **MAY** implement additional TLS 1.3 cipher suites that provide mutual authentication and confidentiality as required by PCEP.

PCEPS Implementations **SHOULD** follow the recommendations given in [[RFC9325](#)].

5. Security Considerations

The Security Considerations of PCEP [[RFC5440](#)], [[RFC8231](#)], [[RFC8281](#)], and [[RFC8283](#)]; TLS 1.2 [[RFC5246](#)]; TLS 1.3 [[I-D.ietf-tls-rfc8446bis](#)], and; [[RFC9325](#)] apply here as well.

The Path Computation Element (PCE) defined in [[RFC4655](#)] is an entity that is capable of computing a network path or route based on a network graph, and applying computational constraints. A Path Computation Client (PCC) may make requests to a PCE for paths to be computed. PCEP is the communication protocol between a PCC and PCE and is defined in [[RFC5440](#)]. Stateful PCE [[RFC8231](#)] specifies a set of extensions to PCEP to enable control of TE-LSPs by a PCE that retains the state of the LSPs provisioned in the network (a stateful PCE). [[RFC8281](#)] describes the setup, maintenance, and teardown of LSPs initiated by a stateful PCE without the need for local configuration on the PCC, thus allowing for a dynamic network that is centrally controlled. [[RFC8283](#)] introduces the architecture for PCE as a central controller

TLS mutual authentication is used to ensure that only authorized users and systems are able to send and receive PCEP messages. To this end, neither the PCC nor the PCE should establish a PCEPS with TLS connection with an unknown, unexpected, or incorrectly identified peer; see [Section 3.5](#) of [[RFC5440](#)]. If deployments make use of a trusted list of Certification Authority (CA) certificates [[RFC5280](#)], then the listed CAs should only issue certificates to parties that are authorized to access the PCE. Doing otherwise will allow certificates that were issued for other purposes to be inappropriately accepted by a PCE.

6. IANA Considerations

There are no IANA considerations.

7. References

7.1. Normative References

[[I-D.ietf-tls-rfc8446bis](#)]

Rescorla, E., "The Transport Layer Security (TLS) Protocol Version 1.3", Work in Progress, Internet-Draft, draft-ietf-tls-rfc8446bis-05, 24 October 2022, <<https://datatracker.ietf.org/doc/html/draft-ietf-tls-rfc8446bis-05>>.

[[RFC2119](#)] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/rfc/rfc2119>>.

- [RFC5246] Dierks, T. and E. Rescorla, "The Transport Layer Security (TLS) Protocol Version 1.2", RFC 5246, DOI 10.17487/RFC5246, August 2008, <<https://www.rfc-editor.org/rfc/rfc5246>>.
- [RFC5280] Cooper, D., Santesson, S., Farrell, S., Boeyen, S., Housley, R., and W. Polk, "Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile", RFC 5280, DOI 10.17487/RFC5280, May 2008, <<https://www.rfc-editor.org/rfc/rfc5280>>.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", RFC 5440, DOI 10.17487/RFC5440, March 2009, <<https://www.rfc-editor.org/rfc/rfc5440>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/rfc/rfc8174>>.
- [RFC8253] Lopez, D., Gonzalez de Dios, O., Wu, Q., and D. Dhody, "PCEPS: Usage of TLS to Provide a Secure Transport for the Path Computation Element Communication Protocol (PCEP)", RFC 8253, DOI 10.17487/RFC8253, October 2017, <<https://www.rfc-editor.org/rfc/rfc8253>>.
- [RFC9325] Sheffer, Y., Saint-Andre, P., and T. Fossati, "Recommendations for Secure Use of Transport Layer Security (TLS) and Datagram Transport Layer Security (DTLS)", BCP 195, RFC 9325, DOI 10.17487/RFC9325, November 2022, <<https://www.rfc-editor.org/rfc/rfc9325>>.

7.2. Informative References

- [RFC4655] Farrell, A., Vasseur, J.-P., and J. Ash, "A Path Computation Element (PCE)-Based Architecture", RFC 4655, DOI 10.17487/RFC4655, August 2006, <<https://www.rfc-editor.org/rfc/rfc4655>>.
- [RFC8231] Crabbe, E., Minei, I., Medved, J., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for Stateful PCE", RFC 8231, DOI 10.17487/RFC8231, September 2017, <<https://www.rfc-editor.org/rfc/rfc8231>>.
- [RFC8281] Crabbe, E., Minei, I., Sivabalan, S., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for PCE-Initiated LSP Setup in a Stateful PCE

Model", RFC 8281, DOI 10.17487/RFC8281, December 2017, <<https://www.rfc-editor.org/rfc/rfc8281>>.

[RFC8283] Farrel, A., Ed., Zhao, Q., Ed., Li, Z., and C. Zhou, "An Architecture for Use of PCE and the PCE Communication Protocol (PCEP) in a Network with Central Control", RFC 8283, DOI 10.17487/RFC8283, December 2017, <<https://www.rfc-editor.org/rfc/rfc8283>>.

Acknowledgments

We would like to thank Adrian Farrel for their review.

Authors' Addresses

Dhruv Dhody
Huawei Technologies

Email: dhruv.ietf@gmail.com

Sean Turner
sn3rd

Email: sean@sn3rd.com

Russ Housley
Vigil Security, LLC
516 Dranesville Road
Herndon, VA, 20170
United States of America

Email: housley@vigilsec.com