

PCE Working Group  
Internet-Draft  
Intended status: Standards Track  
Expires: April 25, 2019

D. Dhody  
F. Zhang  
X. Zhang  
M. Negi  
Huawei Technologies  
V. Lopez  
O. Gonzalez de Dios  
Telefonica I+D  
October 22, 2018

**PCEP Extensions for Receiving SRLG Information**  
**draft-dhody-pce-recv-srlg-07**

**Abstract**

The Path Computation Element (PCE) provides functions of path computation in support of traffic engineering (TE) in networks controlled by Multi-Protocol Label Switching (MPLS) and Generalized MPLS (GMPLS).

This document provides extensions for the Path Computation Element Protocol (PCEP) to receive Shared Risk Link Group (SRLG) information during path computation via encoding this information in the path computation reply message.

**Status of This Memo**

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 25, 2019.

**Copyright Notice**

Copyright (c) 2018 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">2</a>
<a href="#">1.1.</a>	<a href="#">Requirements Language</a>	<a href="#">3</a>
<a href="#">2.</a>	<a href="#">Terminology</a>	<a href="#">3</a>
<a href="#">3.</a>	<a href="#">Usage of SRLG</a>	<a href="#">4</a>
<a href="#">4.</a>	<a href="#">PCEP Requirements</a>	<a href="#">4</a>
<a href="#">5.</a>	<a href="#">Extension to PCEP</a>	<a href="#">5</a>
<a href="#">5.1.</a>	<a href="#">SRLG Information TLV</a>	<a href="#">5</a>
<a href="#">5.2.</a>	<a href="#">SRLG Subobject in ERO</a>	<a href="#">6</a>
<a href="#">6.</a>	<a href="#">Other Considerations</a>	<a href="#">6</a>
<a href="#">6.1.</a>	<a href="#">Other Path Setup Types</a>	<a href="#">6</a>
<a href="#">6.2.</a>	<a href="#">Backward Compatibility</a>	<a href="#">7</a>
<a href="#">6.3.</a>	<a href="#">Confidentiality via PathKey</a>	<a href="#">7</a>
<a href="#">6.4.</a>	<a href="#">Coherent SRLG IDs</a>	<a href="#">7</a>
<a href="#">7.</a>	<a href="#">Security Considerations</a>	<a href="#">7</a>
<a href="#">8.</a>	<a href="#">Manageability Considerations</a>	<a href="#">8</a>
<a href="#">8.1.</a>	<a href="#">Control of Function and Policy</a>	<a href="#">8</a>
<a href="#">8.2.</a>	<a href="#">Information and Data Models</a>	<a href="#">8</a>
<a href="#">8.3.</a>	<a href="#">Liveness Detection and Monitoring</a>	<a href="#">8</a>
<a href="#">8.4.</a>	<a href="#">Verify Correct Operations</a>	<a href="#">8</a>
<a href="#">8.5.</a>	<a href="#">Requirements On Other Protocols</a>	<a href="#">8</a>
<a href="#">8.6.</a>	<a href="#">Impact On Network Operations</a>	<a href="#">8</a>
<a href="#">9.</a>	<a href="#">IANA Considerations</a>	<a href="#">9</a>
<a href="#">9.1.</a>	<a href="#">New TLV</a>	<a href="#">9</a>
<a href="#">9.2.</a>	<a href="#">New Subobjects for the ERO Object</a>	<a href="#">9</a>
<a href="#">10.</a>	<a href="#">Acknowledgments</a>	<a href="#">10</a>
<a href="#">11.</a>	<a href="#">References</a>	<a href="#">10</a>
<a href="#">11.1.</a>	<a href="#">Normative References</a>	<a href="#">10</a>
<a href="#">11.2.</a>	<a href="#">Informative References</a>	<a href="#">11</a>
<a href="#">Appendix A.</a>	<a href="#">Contributor Addresses</a>	<a href="#">14</a>
	<a href="#">Authors' Addresses</a>	<a href="#">14</a>

## [1.](#) Introduction

As per [[RFC4655](#)], PCE based path computation model is deployed in large, multi-domain, multi-region, or multi-layer networks. In such



case PCEs may cooperate with each other to provide end to end optimal path.

It is important to understand which TE links in the network might be at risk from the same failures. In this sense, a set of links can constitute a 'shared risk link group' (SRLG) if they share a resource whose failure can affect all links in the set [[RFC4202](#)]. H-LSP (Hierarchical LSP) or S-LSP (Stitched LSP) can be used for carrying one or more other LSPs as described in [[RFC4206](#)] and [[RFC6107](#)]. H-LSP and S-LSP may be computed by PCE(s) and further form as a TE link. The SRLG information of such LSPs can be obtained during path computation itself and encoded in the PCEP Path Computation Reply (PCRep) message. [[I-D.zhang-ccamp-gmpls-uni-app](#)] describes the use of a PCE for end to end User-Network Interface (UNI) path computation.

Note that [[RFC8001](#)] specifies an extension to Resource ReserVation Protocol-Traffic Engineering (RSVP-TE) where SRLG information is collected at the time of signaling. But in case a PCE or cooperating PCEs are used for path computation it is recommended that SRLG information is provided by the PCE(s) during the path computation itself to the ingress (PCC) rather than receiving this information during signaling.

Further, for other path setup types (PST), (such as segment routing (SR), PCE as central controller (PCECC)) using a PCEP based approach for SRLG information is useful.

[RFC7926] describes a scaling problem with SRLGs in multi-layer environment and introduces a concept of Macro SRLG (MSRLG). Lower layer SRLG are abstracted at the time of path computation and can be the basis to generate such a Macro SRLG at the PCE.

### **1.1. Requirements Language**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#) [[RFC2119](#)] [[RFC8174](#)] when, and only when, they appear in all capitals, as shown here.

## **2. Terminology**

The following terminology is used in this document.

CPS: Confidential Path Segment. A segment of a path that contains nodes and links that the policy requires not to be disclosed outside the domain.



PCE: Path Computation Element. An entity (component, application, or network node) that is capable of computing a network path or route based on a network graph and applying computational constraints.

SRLG: Shared Risk Link Group.

UNI: User-Network Interface.

### **3. Usage of SRLG**

[RFC4202] states that a set of links can constitute a 'shared risk link group' (SRLG) if they share a resource whose failure can affect all links in the set. For example, two fibers in the same conduit would be in the same SRLG. If an LSR is required to have multiple diversely routed LSPs to another LSR, the path computation should attempt to route the paths so that they do not have any links in common, and such that the path SRLGs are disjoint.

In case a PCE or cooperating PCEs are used for path computation, the SRLG information is provided by the PCE(s). For example, disjoint paths for inter-domain or inter-layer LSPs. In order to achieve path computation for a secondary (backup) path, a PCC may request the PCE for a route that must be SRLG disjoint from the primary (working) path. The Exclude Route Object (XRO) [RFC5521] is used to specify SRLG information to be explicitly excluded.

### **4. PCEP Requirements**

Following key requirements are identified for PCEP to receive SRLG information during path computation:

SRLG Indication: The PCEP speaker SHOULD be capable of indicating whether the SRLG information of the path is to be received during the path computation procedure to PCE.

SRLG: If requested, the SRLG information SHOULD be received during the path computation and encoded in the PCEP message from PCE.

Cooperating PCEs [RFC4655] with inter-PCE communication work together to provide the end to end optimal path as well as the SRLG information of this path. During inter-domain or inter-layer path computation, the aggregating PCE (Parent PCE [RFC6805] or Ingress PCE(1) [RFC5441] or Higher-Layer PCE [RFC5623]) should receive the SRLG information of path segments from other PCEs and provide the end to end SRLG information of the optimal path to the Path Computation Client (PCC).



S (SRLG - 1 bit): when set, in a PCReq message, this indicates that the SRLG information of the path SHOULD be provided in the PCRep message. Otherwise, when cleared, this indicates that the SRLG information SHOULD NOT be included in the PCRep message. In a PCRep message, when the S bit is set this indicates that the returned path in ERO also carry the SRLG information; otherwise (when the S bit is cleared), the returned path does not carry SRLG information. Further incase of PCRpt [[RFC8231](#)] message for delegated LSP the flag indicates that when PCE computes the path, it SHOULD provide the SRLG information in PCUpd [[RFC8231](#)] message. Incase of PCUpd and PCInitiate [[RFC8281](#)] message, the flag indicates that the ERO also carry the SRLG information.





## 5.2. SRLG Subobject in ERO

As per [RFC5440], ERO is used to encode the path and is carried within a PCRep message to provide the computed path when computation was successful. Further as per [RFC8231] and [RFC8281], the ERO is also encoded in PCUpd and PCInitiate message for stateful operations.

The SRLG of a path is the union of the SRLGs of the links in the path [RFC4202]. The SRLG subobject is defined in [RFC8001] for ROUTE\_RECORD object (RRO). The same subobject format (reproduced below) can be used by the ERO object in the PCEP messages.

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|      Type      |      Length      |D|      Reserved      |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                  SRLG ID 1 (4 octets)                  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
~                      .....                      ~
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+
|                  SRLG ID n (4 octets)                  |
+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+---+

```

The meaning and description of Type, Length, D-Bit and SRLG ID can be found in [RFC8001]. Reserved field MUST be set to zero on transmission and MUST be ignored on receipt.

The SRLG subobject should be encoded inside the ERO object in the PCEP messages by the PCE when the S-Bit is set in the SRLG-INFO TLV (inside LSPA object). Incase no SRLG information is present for the path, an empty SRLG subobject with Length as 4 (and no SRLG-IDs) is included.

## 6. Other Considerations

### 6.1. Other Path Setup Types

Initially PCEP was used for LSPs that are set up using the RSVP-TE signaling protocol. However, other TE path setup methods are possible within the PCE architecture such as SR [I-D.ietf-pce-segment-routing].

[RFC8001] describes SRLG information collection via RSVP-TE extension, which can not be used for Segment Routing (SR), making PCE the best source for the SRLG information for SR.



## **6.2. Backward Compatibility**

If a PCE receives a PCEP message and the PCE does not understand the new TLV in the LSPA object, then as per [\[RFC5440\]](#), it would ignore the TLV. In which case, the PCC will receive ERO with no SRLG subobject and can determine that the PCE does not support the PCEP extension as defined in this document.

If PCEP speaker receives a PCEP message with SRLG subobject that it does not support or recognize, it would act according to the existing processing rules of the ERO as per [\[RFC5440\]](#).

## **6.3. Confidentiality via PathKey**

[\[RFC5520\]](#) defines a mechanism to hide the contents of a segment of a path, called the Confidential Path Segment (CPS). The CPS may be replaced by a path-key that can be conveyed in the PCEP and signaled within in a RSVP-TE ERO.

When path-key confidentiality is used, encoding SRLG information in PCRep along with the path-key could be useful to compute a SRLG disjoint backup path at the later instance.

The path segment that needs to be hidden (that is, CPS) MAY be replaced in the ERO with a PKS. The PCE MAY use the SRLG Sub-objects in the ERO along with the PKS sub-object.

## **6.4. Coherent SRLG IDs**

In a multi-layer multi-domain scenario, SRLG ids may be configured by different management entities in each layer/domain. In such scenarios, maintaining a coherent set of SRLG IDs is a key requirement in order to be able to use the SRLG information properly. Thus, SRLG IDs must be unique. Note that current procedure is targeted towards a scenario where the different layers and domains belong to the same operator, or to several coordinated administrative groups. Ensuring the aforementioned coherence of SRLG IDs is beyond the scope of this document. Further scenarios, where coherence in the SRLG IDs cannot be guaranteed are out of the scope of the present document and are left for further study.

## **7. Security Considerations**

The procedures defined in this document permit the transfer of SRLG data between layers or domains during the path computation of LSPs, subject to policy at the PCE. It is recommended that PCE policies take the implications of releasing SRLG information into consideration and behave accordingly during path computation. Other



security concerns are discussed in [\[RFC5440\]](#). An analysis of the security issues for routing protocols that use TCP (including PCEP) is provided in [\[RFC6952\]](#), while [\[RFC8253\]](#) discusses a TLS based approach to provide secure transport for PCEP.

## **[8.](#) Manageability Considerations**

### **[8.1.](#) Control of Function and Policy**

A PCE involved in inter-domain or inter-layer path computation should be capable of being configured with a SRLG processing policy to specify if the SRLG IDs of the domain or specific layer network can be exposed to the PCEP peer outside the domain or layer network, or whether they should be summarized, mapped to values that are comprehensible to PCC outside the domain or layer network, or removed entirely.

### **[8.2.](#) Information and Data Models**

[\[RFC7420\]](#) describes the PCEP MIB and [\[I-D.ietf-pce-pcep-yang\]](#) specify PCEP YANG, there are no new MIB Objects or YANG changes for this document.

### **[8.3.](#) Liveness Detection and Monitoring**

Mechanisms defined in this document do not imply any new liveness detection and monitoring requirements in addition to those already listed in [\[RFC5440\]](#).

### **[8.4.](#) Verify Correct Operations**

Mechanisms defined in this document do not imply any new operation verification requirements in addition to those already listed in [\[RFC5440\]](#) and [\[RFC8231\]](#).

### **[8.5.](#) Requirements On Other Protocols**

Mechanisms defined in this document do not imply any new requirements on other protocols. Note that, [\[RFC8001\]](#) provide similar requirements for signaling protocol.

### **[8.6.](#) Impact On Network Operations**

Mechanisms defined in this document do not have any impact on network operations in addition to those already listed in [\[RFC5440\]](#) and [\[RFC8231\]](#).



## 9. IANA Considerations

IANA assigns values to PCEP parameters in registries defined in [RFC5440]. IANA is requested to make the following additional assignments.

### 9.1. New TLV

IANA maintains the "Path Computation Element Protocol (PCEP) Numbers" registry and the "PCEP TLV Type Indicators" sub-registry. IANA is requested to allocate a codepoint for -

Type	Meaning	Reference
TBD	SRLG-INFO	This document

This document requests that a new sub-registry, named "SRLG-INFO TLV Flag Field", is created within the "Path Computation Element Protocol (PCEP) Numbers" registry to manage the Flag field of the this TLV. New values are to be assigned by Standards Action [RFC8126]. Each bit should be tracked with the following qualities:

- o Bit number (counting from bit 0 as the most significant bit)
- o Capability description
- o Defining RFC

The following values are defined in this document:

Bit	Description	Reference
31	SRLG (S-bit)	This document

### 9.2. New Subobjects for the ERO Object

PCEP uses the ERO registry maintained for RSVP at <http://www.iana.org/assignments/rsvp-parameters/rsvp-parameters.xhtml>. Within this registry IANA maintains sub-registry for ERO subobject at <http://www.iana.org/assignments/rsvp-parameters/rsvp-parameters.xhtml#rsvp-parameters-25>

Upon approval of this document, IANA is requested to make identical additions to the registry as follows (which is un-assigned right now):

Subobject Type	Reference
34 SRLG sub-object	[This I.D.]





Note that, an allocation for SRLG sub-object for RRO in RSVP-TE is made for [[RFC8001](#)].

## **10. Acknowledgments**

Special thanks to the authors of [[RFC8001](#)]. This document borrows some of text from it.

## **11. References**

### **11.1. Normative References**

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC5440] Vasseur, JP., Ed. and JL. Le Roux, Ed., "Path Computation Element (PCE) Communication Protocol (PCEP)", [RFC 5440](#), DOI 10.17487/RFC5440, March 2009, <<https://www.rfc-editor.org/info/rfc5440>>.
- [RFC8001] Zhang, F., Ed., Gonzalez de Dios, O., Ed., Margaria, C., Hartley, M., and Z. Ali, "RSVP-TE Extensions for Collecting Shared Risk Link Group (SRLG) Information", [RFC 8001](#), DOI 10.17487/RFC8001, January 2017, <<https://www.rfc-editor.org/info/rfc8001>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.
- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.
- [RFC8231] Crabbe, E., Minei, I., Medved, J., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for Stateful PCE", [RFC 8231](#), DOI 10.17487/RFC8231, September 2017, <<https://www.rfc-editor.org/info/rfc8231>>.
- [RFC8281] Crabbe, E., Minei, I., Sivabalan, S., and R. Varga, "Path Computation Element Communication Protocol (PCEP) Extensions for PCE-Initiated LSP Setup in a Stateful PCE Model", [RFC 8281](#), DOI 10.17487/RFC8281, December 2017, <<https://www.rfc-editor.org/info/rfc8281>>.



## **11.2. Informative References**

- [RFC4202] Kompella, K., Ed. and Y. Rekhter, Ed., "Routing Extensions in Support of Generalized Multi-Protocol Label Switching (GMPLS)", [RFC 4202](#), DOI 10.17487/RFC4202, October 2005, <<https://www.rfc-editor.org/info/rfc4202>>.
- [RFC4206] Kompella, K. and Y. Rekhter, "Label Switched Paths (LSP) Hierarchy with Generalized Multi-Protocol Label Switching (GMPLS) Traffic Engineering (TE)", [RFC 4206](#), DOI 10.17487/RFC4206, October 2005, <<https://www.rfc-editor.org/info/rfc4206>>.
- [RFC4655] Farrel, A., Vasseur, J., and J. Ash, "A Path Computation Element (PCE)-Based Architecture", [RFC 4655](#), DOI 10.17487/RFC4655, August 2006, <<https://www.rfc-editor.org/info/rfc4655>>.
- [RFC5441] Vasseur, JP., Ed., Zhang, R., Bitar, N., and JL. Le Roux, "A Backward-Recursive PCE-Based Computation (BRPC) Procedure to Compute Shortest Constrained Inter-Domain Traffic Engineering Label Switched Paths", [RFC 5441](#), DOI 10.17487/RFC5441, April 2009, <<https://www.rfc-editor.org/info/rfc5441>>.
- [RFC5520] Bradford, R., Ed., Vasseur, JP., and A. Farrel, "Preserving Topology Confidentiality in Inter-Domain Path Computation Using a Path-Key-Based Mechanism", [RFC 5520](#), DOI 10.17487/RFC5520, April 2009, <<https://www.rfc-editor.org/info/rfc5520>>.
- [RFC5521] Oki, E., Takeda, T., and A. Farrel, "Extensions to the Path Computation Element Communication Protocol (PCEP) for Route Exclusions", [RFC 5521](#), DOI 10.17487/RFC5521, April 2009, <<https://www.rfc-editor.org/info/rfc5521>>.
- [RFC5623] Oki, E., Takeda, T., Le Roux, JL., and A. Farrel, "Framework for PCE-Based Inter-Layer MPLS and GMPLS Traffic Engineering", [RFC 5623](#), DOI 10.17487/RFC5623, September 2009, <<https://www.rfc-editor.org/info/rfc5623>>.
- [RFC6107] Shiomoto, K., Ed. and A. Farrel, Ed., "Procedures for Dynamically Signaled Hierarchical Label Switched Paths", [RFC 6107](#), DOI 10.17487/RFC6107, February 2011, <<https://www.rfc-editor.org/info/rfc6107>>.



- [RFC6805] King, D., Ed. and A. Farrel, Ed., "The Application of the Path Computation Element Architecture to the Determination of a Sequence of Domains in MPLS and GMPLS", [RFC 6805](#), DOI 10.17487/RFC6805, November 2012, <<https://www.rfc-editor.org/info/rfc6805>>.
- [RFC6952] Jethanandani, M., Patel, K., and L. Zheng, "Analysis of BGP, LDP, PCEP, and MSDP Issues According to the Keying and Authentication for Routing Protocols (KARP) Design Guide", [RFC 6952](#), DOI 10.17487/RFC6952, May 2013, <<https://www.rfc-editor.org/info/rfc6952>>.
- [RFC7420] Koushik, A., Stephan, E., Zhao, Q., King, D., and J. Hardwick, "Path Computation Element Communication Protocol (PCEP) Management Information Base (MIB) Module", [RFC 7420](#), DOI 10.17487/RFC7420, December 2014, <<https://www.rfc-editor.org/info/rfc7420>>.
- [RFC7926] Farrel, A., Ed., Drake, J., Bitar, N., Swallow, G., Ceccarelli, D., and X. Zhang, "Problem Statement and Architecture for Information Exchange between Interconnected Traffic-Engineered Networks", [BCP 206](#), [RFC 7926](#), DOI 10.17487/RFC7926, July 2016, <<https://www.rfc-editor.org/info/rfc7926>>.
- [RFC8253] Lopez, D., Gonzalez de Dios, O., Wu, Q., and D. Dhody, "PCEPS: Usage of TLS to Provide a Secure Transport for the Path Computation Element Communication Protocol (PCEP)", [RFC 8253](#), DOI 10.17487/RFC8253, October 2017, <<https://www.rfc-editor.org/info/rfc8253>>.
- [I-D.ietf-pce-segment-routing]  
Sivabalan, S., Filsfils, C., Tantsura, J., Henderickx, W., and J. Hardwick, "PCEP Extensions for Segment Routing", [draft-ietf-pce-segment-routing-14](#) (work in progress), October 2018.
- [I-D.ietf-pce-pcep-yang]  
Dhody, D., Hardwick, J., Beeram, V., and J. Tantsura, "A YANG Data Model for Path Computation Element Communications Protocol (PCEP)", [draft-ietf-pce-pcep-yang-09](#) (work in progress), October 2018.



[I-D.zhang-ccamp-gmpls-uni-app]

Zhang, F., Dios, O., Farrel, A., Zhang, X., and D. Ceccarelli, "Applicability of Generalized Multiprotocol Label Switching (GMPLS) User-Network Interface (UNI)", [draft-zhang-ccamp-gmpls-uni-app-05](#) (work in progress), February 2014.



## **Appendix A. Contributor Addresses**

Udayasree Palle

E-Mail: udayasreereddy@gmail.com

Avantika  
India

E-Mail: s.avantika.avantika@gmail.com

### **Authors' Addresses**

Dhruv Dhody  
Huawei Technologies  
Divyashree Techno Park, Whitefield  
Bangalore, Karnataka 560066  
India

E-Mail: dhruv.ietf@gmail.com

Fatai Zhang  
Huawei Technologies  
Bantian, Longgang District  
Shenzhen, Guangdong 518129  
P.R.China

E-Mail: zhangfatai@huawei.com

Xian Zhang  
Huawei Technologies  
Bantian, Longgang District  
Shenzhen, Guangdong 518129  
P.R.China

E-Mail: zhang.xian@huawei.com

Mahendra Singh Negi  
Huawei Technologies  
Divyashree Techno Park, Whitefield  
Bangalore, Karnataka 560066  
India

E-Mail: mahend.ietf@gmail.com



Victor Lopez  
Telefonica I+D  
Distrito Telefonica  
Edificio Sur 3, 3rd floor  
Madrid 28050  
Spain

E-Mail: victor.lopezalvarez@telefonica.com

Oscar Gonzalez de Dios  
Telefonica I+D  
Distrito Telefonica  
Edificio Sur 3, 3rd floor  
Madrid 28050  
Spain

E-Mail: oscar.gonzalezdedios@telefonica.com

