

Network Working Group  
Internet-Draft  
Intended status: Informational  
Expires: September 26, 2009

K. Drage  
Alcatel-Lucent  
March 25, 2009

A Session Initiation Protocol (SIP) Extension for the Identification of  
Services

[draft-drage-sipping-service-identification-03](#)

Status of this Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on September 26, 2009.

Copyright Notice

Copyright (c) 2009 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents in effect on the date of publication of this document (<http://trustee.ietf.org/license-info>). Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

This document may contain material from IETF Documents or IETF Contributions published or made publicly available before November 10, 2008. The person(s) controlling the copyright in some of this material may not have granted the IETF Trust the right to allow modifications of such material outside the IETF Standards Process. Without obtaining an adequate license from the person(s) controlling the copyright in such materials, this document may not be modified outside the IETF Standards Process, and derivative works of it may not be created outside the IETF Standards Process, except to format it for publication as an RFC or to translate it into languages other than English.



## Abstract

This document describes private extensions to the Session Initiation Protocol (SIP) that enable a network of trusted SIP servers to assert the service of authenticated users. The use of these extensions is only applicable inside an administrative domain with previously agreed-upon policies for generation, transport and usage of such information. This document does NOT offer a general service identification model suitable for use between different trust domains, or use in the Internet at large.

The document also defines a URN to identify both services and UA applications. This URN can be used within the SIP header fields defined in this document to identify services, and also within the framework defined for caller preferences and callee capabilities to identify usage of both services and applications between end UAs.



## 1. Introduction

This document describes private extensions to the Session Initiation Protocol (SIP) that enable a network of trusted SIP servers to assert the service possibly subject to the user being entitled to that service. The use of these extensions is only applicable inside an administrative domain with previously agreed-upon policies for generation, transport and usage of such information. This document does NOT offer a general service model suitable for use between different trust domains, or use in the Internet at large.

The concept of "service" within SIP has no hard and fast rules.

[draft-ietf-sipping-service-identification](#)

[[I-D.ietf-sipping-service-identification](#)] provides general guidance on what constitutes a service within SIP and what does not.

This document also makes use of the terms "derived service identification" and "declarative service identification" as defined in [draft-ietf-sipping-service-identification](#) [[I-D.ietf-sipping-service-identification](#)].

During a session setup proxies may need to understand what service the request is related to in order to know what application server to contact or other service logic to invoke. The SIP INVITE request contains all of the information necessary to determine the service. However, the calculation of the service may be computational and database intensive. For example, a given trust domain's definition of a service might include request authorization. Moreover the analysis may require examination of the SDP.

For example, an INVITE request with video SDP directed to a video-on-demand Request-URI could be marked as an IPTV session. An INVITE request with push-to-talk over cellular (PoC) routes could be marked as a PoC session. An INVITE request with a Require header field containing an option tag of "foogame" could be marked as a foogame session.

NOTE: If the information contained within the SIP INVITE request is not sufficient to uniquely identify a service, the remedy is to extend the SIP signalling to capture the missing element.

[draft-ietf-sipping-service-identification](#)

[[I-D.ietf-sipping-service-identification](#)] provides further explanation.

By providing a mechanism to compute and store the results of the domain specific service calculation, i.e. the derived service identification, this optimization allows a single trusted proxy to perform an analysis of the request and authorize the requestor's

Drage

Expires September 26, 2009

[Page 4]

permission to request such a service. The proxy may then include a service identifier that relieves other trusted proxies and trusted UAs from performing further duplicate analysis of the request for their service identification purposes. In addition, this extension allows user agent clients outside the trust domain to provide a hint of the requested service.

This extension does not provide for the dialog or transaction to be rejected if the service is not supported end-to-end. SIP provides other mechanisms, such as the option-tag and use of the Require and Proxy-Require header fields, where such functionality is required. No explicitly signalled service identification exists and the session proceeds for each nodes definition of the service in use, on the basis of information contained in SDP and in other SIP header fields.

This mechanism is specifically a mechanism to manage the information needs of intermediate routing devices between the calling user and the user represented by the Request-URI. In support of this mechanism, a URN is defined to identify the services. This URN has wider applicability to additionally identify services and terminal applications. Between end users, caller preferences and callee capabilities as specified in [RFC 3840](#) [[RFC3840](#)] and [RFC 3841](#) [[RFC3841](#)] provide an appropriate mechanism for indicating such service and application identification. These mechanisms have been extended by [draft-rosenberg-sip-app-media-tag](#) [[I-D.rosenberg-sip-app-media-tag](#)] to provide further capabilities in this area.

The mechanism proposed in this document relies on a new header field called 'P-Asserted-Service' that contains a URN. This is supported by a further new header field called 'P-Preferred-Service' that also contains a URN, and which allows the UA to express a preferences to the decisions made on service within the trust domain.

P-Asserted-Service: urn:urn-7:3gpp-service.exampletelephony.version1

A proxy server which handles a request can, after authenticating the originating user in some way (for example: Digest authentication), to ensure that the user is entitled to that service, insert such a P-Asserted-Service header field into the request and forward it to other trusted proxies. A proxy that is about to forward a request to a proxy server or UA that it does not trust removes all the P-Asserted-Service header field values.

This document labels services by means of an informal URN. This provides a hierarchical structure for defining services and subservices, and provides an address that can be resolvable for various purposes outside the scope of this document, e.g. to obtain



Drage

Expires September 26, 2009

[Page 5]

information about the service so described.

## **2. Applicability Statement**

This document describes private extensions to SIP (see [RFC 3261](#) [[RFC3261](#)]) that enable a network of trusted SIP servers to assert the service of end users or end systems. The use of these extensions is only applicable inside a 'Trust Domain' as defined in Short term requirements for Network Asserted Identity (see [RFC 3324](#) [[RFC3324](#)]). Nodes in such a Trust Domain are explicitly trusted by its users and end-systems to publicly assert the service of each party, and that they have common and agreed upon definitions of services and homogeneous service offerings. The means by which the network determines the service to assert is outside the scope of this document (though it commonly entails some form of authentication).

The mechanism for defining a trust domain is to provide a certain set of specifications known as 'Spec(T)', and they specify compliance to that set of specifications. Spec(T) MUST specify behavior as documented in [RFC 3324](#) [[RFC3324](#)].

This document does NOT offer a general service model suitable for inter-domain use or use in the Internet at large. Its assumptions about the trust relationship between the user and the network may not apply in many applications. For example, these extensions do not accommodate a model whereby end users can independently assert their service by use of the extensions defined here. End users assert their service by including the SIP and SDP parameters that correspond to the service they require. Furthermore, since the asserted services are not cryptographically certified, they are subject to forgery, replay, and falsification in any architecture that does not meet the requirements of [RFC 3324](#) [[RFC3324](#)].

The asserted services also lack an indication of who specifically is asserting the service, and so it must be assumed that a member of the Trust Domain is asserting the service. Therefore, the information is only meaningful when securely received from a node known to be a member of the Trust Domain.

Despite these limitations, there are sufficiently useful specialized deployments that meet the assumptions described above, and can accept the limitations that result, to warrant informational publication of this mechanism.



### **3. Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14](#), [RFC 2119](#) [[RFC2119](#)].

Throughout this document requirements for or references to proxy servers or proxy behavior apply similarly to other intermediaries within a Trust Domain (ex: B2BUAs).

The term Trust Domain in this document has the meaning as defined in [RFC 3324](#) [[RFC3324](#)].



## 4. Syntax of the Header Fields

The following syntax specification uses the augmented Backus-Naur Form (BNF) as described in [RFC 4234](#) [[RFC5234](#)].

### 4.1. The P-Asserted-Service Header

The P-Asserted-Service header field is used among trusted SIP entities (typically intermediaries) to carry the service information of the user sending a SIP message.

The P-Asserted-Service header field carries information that is derived service identification. While a declarative service identification can assist in deriving the value transferred in this header, this should be in the form of streamlining the correct derived service identification.

```
PAssertedService = "P-Asserted-Service"
                   HCOLON PAssertedService-value
PAssertedService-value = Service-ID *(COMMA Service-ID)
```

See [Section 4.4](#) for the definition of Service-ID in ABNF.

Proxies can (and will) add and remove this header field.

Table 1 extends the headers defined in this document to Table 2 in SIP [[RFC3261](#)], [Section 7.1](#) of the SIP-specific event notification [[RFC3265](#)], tables 1 and 2 in the SIP INFO method [[RFC2976](#)], tables 1 and 2 in Reliability of provisional responses in SIP [[RFC3262](#)], tables 1 and 2 in the SIP UPDATE method [[RFC3311](#)], tables 1 and 2 in the SIP extension for Instant Messaging [[RFC3428](#)], table 1 in the SIP REFER method [[RFC3515](#)] and tables 2 and 3 in the SIP PUBLISH method [[RFC3903](#)]:

Header field	where	proxy	ACK	BYE	CAN	INV	OPT	REG	SUB
P-Asserted-Service	R	admr	-	-	-	0	0	-	0
Header field	NOT PRA INF UPD MSG REF PUB								
P-Asserted-Service			-	-	-	-	0	0	0

Table 1

There may be multiple P-Asserted-Service header fields. The semantics of multiple P-Asserted-Service header fields appearing in the same request is not defined.





#### 4.2. The P-Preferred-Service Header

The P-Preferred-Service header field is used by a user agent sending the SIP request to provide a hint to a trusted proxy of the preferred service that the user wishes to be used for the P-Asserted-Service field value that the trusted element will insert.

The P-Preferred-Service header field carries information that is declarative service identification. Such information should only be used to assist in deriving a derived service identification at the recipient entity.

```

PPreferredService = "P-Preferred-Service"
                    HCOLON PPreferredService-value
PPreferredService-value = Service-ID *(COMMA Service-ID)

```

See [Section 4.4](#) for the definition of Service-ID in ABNF.

Table 2 extends the headers defined in this document to Table 2 in SIP [\[RFC3261\]](#), [Section 7.1](#) of the SIP-specific event notification [\[RFC3265\]](#), tables 1 and 2 in the SIP INFO method [\[RFC2976\]](#), tables 1 and 2 in Reliability of provisional responses in SIP [\[RFC3262\]](#), tables 1 and 2 in the SIP UPDATE method [\[RFC3311\]](#), tables 1 and 2 in the SIP extension for Instant Messaging [\[RFC3428\]](#), table 1 in the SIP REFER method [\[RFC3515\]](#) and tables 2 and 3 in the SIP PUBLISH method [\[RFC3903\]](#):

Header field	where	proxy	ACK	BYE	CAN	INV	OPT	REG	SUB
P-Preferred-Service	R	dr	-	-	-	0	0	-	0
Header field	NOT PRA INF UPD MSG REF PUB								
P-Preferred-Service			-	-	-	-	0	0	0

Table 2

There may be multiple P-Preferred-Service header fields. The semantics of multiple P-Preferred-Service header fields appearing in the same request is not defined.

#### 4.3. Service and Application Definition

Definition of services and their characteristics is outside the scope of this document. Other standards organizations, vendors and operators may define their own services and register them.

A hierarchical structure is defined consisting of service identifiers



or application identifiers, subservice identifiers.

The service and subservice identifiers identify the service as described in [Section 1](#). The URN may also be used to identify a service or an application between end users for use within the context of [RFC 3841](#) [[RFC3841](#)] and [RFC 3840](#) [[RFC3840](#)].

IANA maintains a registry of service identifier values that have been assigned. This registry is created by the actions of [Section 8.2](#) of this document.

Subservice identifiers are not managed by IANA. It is the responsibility of the organisation that registered the service to manage the subservices.

#### **[4.4.](#) Registration Template**

Below, we include the registration template for the URN scheme according to [RFC 3406](#) [[RFC3406](#)]. The URN scheme is defined as an informal NID.

Namespace ID: urn-7

Registration Information: Registration version: 1; registration date: 2009-03-22

Declared registrant of the namespace: TBD

Declaration of syntactic structure: The URN consists of a hierarchical service identifier or application identifier, with a sequence of labels separated by periods. The left-most label is the most significant one and is called 'top-level service identifier', while names to the right are called 'sub-services' or 'sub-applications'. The set of allowable characters is the same as that for domain names (see [RFC 1123](#) [[RFC1123](#)]) and a subset of the labels allowed in [RFC 3958](#) [[RFC3958](#)]. Labels are case-insensitive and MUST be specified in all lower-case. For any given service identifier, labels can be removed right-to-left and the resulting URN is still valid, referring a more generic service, with the exception of the top-level service identifier and possibly the first sub-service or sub-application identifier. Labels cannot be removed beyond a defined basic service, for example, the label w.x may define a service, but the label w may only define an assignment authority for assigning subsequent values and not define a service in its own right. In other words, if a service identifier 'w.x.y.z' exists, the URNs 'w.x' and 'w.x.y' are also valid service identifiers, but w may not be a valid service identifier if it merely defines who is responsible



for defining x.

```
Service-ID      = "urn:urn-7:" urn-service-id
urn-service-id  = top-level *("." sub-service-id)
top-level       = let-dig [ *26let-dig ]
sub-service-id  = let-dig [ *let-dig ]
let-dig         = ALPHA / DIGIT / "-"
```

While the naming convention above uses the term "service" all the constructs are equally applicable to identifying applications within the UA.

Note to RFC editor: the value above has been preassigned by IANA.

Relevant ancillary documentation: None

Identifier uniqueness considerations: A service identifier identifies a service, and an application identifier an application indicated in the service or application registration (see IANA Considerations ([Section 8](#))). Uniqueness is guaranteed by the IANA registration.

Identifier persistence considerations: The service or application identifier for the same service is or application expected to be persistent, although there naturally cannot be a guarantee that a particular service will continue to be available globally or at all times.

Process of identifier assignment: The process of identifier assignment is described in the IANA Considerations ([Section 8](#)).

Process for identifier resolution: There is no single global resolution service for service identifiers or application identifiers.

Rules for Lexical Equivalence: 'service' identifiers are compared according to case-insensitive string equality.

Conformance with URN Syntax: The BNF in the 'Declaration of syntactic structure' above constrains the syntax for this URN scheme.

Validation mechanism: Validation determines whether a given string is currently a validly-assigned URN (see [RFC 3406](#) [[RFC3406](#)]). Due to the distributed nature of usage and since not all services are available everywhere, validation in this sense is not possible



Scope: The scope for this URN can be local to a single domain, or may be more widely used.

## **5. Usage of the P-Preferred-Service and P-Asserted-Service header fields**

### **5.1. Usage of the P-Preferred-Service and P-Asserted-Service header fields in Requests**

#### **5.1.1. Procedures at User Agent Clients (UAC)**

The UAC MAY insert a P-Preferred-Service in a request that creates a dialog, or a request outside of a dialog. This information can assist the proxies in identifying appropriate service capabilities to apply to the call. This information MUST NOT conflict with other SIP or SDP information included in the request. Furthermore, the SIP or SDP information needed to signal functionality of this service MUST be present. Thus if a service requires a video component, then the SDP has to include the media line associated with that video component; it cannot be assumed from the P-Preferred-Service header field value. Similarly if the service requires particular SIP functionality for which a SIP extension and a Require header field value is defined, then the request has to include that SIP signalling as well as the P-Preferred-Service header field value.

A UAC that is within the same trust domain as the proxy it sends a request to, (e.g a media gateway or application server) MAY insert a P-Asserted-Service header field in a request that creates a dialog, or a request outside of a dialog. This information MUST NOT conflict with other SIP or SDP information included in the request. Furthermore, the SIP or SDP information needed to signal functionality of this service MUST be present.

#### **5.1.2. Procedures at Intermediate Proxies**

A proxy in a Trust Domain can receive a request from a node that it trusts, or a node that it does not trust. When a proxy receives a request from a node it does not trust and it wishes to add a P-Asserted-Service header field, the proxy MUST identify the service appropriate to the capabilities (e.g. SDP) in the request, MAY authenticate the originator of the request (in order to determine whether the user is subscribed for that service), and use the identity which results from this checking and authentication to insert a P-Asserted-Service header field into the request.

When a proxy receives a request containing a P-Preferred-Service header field the Proxy MAY use the contents of that header field to assist in determining the service to be included in a P-Asserted-Service header field, (for instance to prioritize the order of comparison of filter criteria for potential services that the request could match). The proxy MUST NOT use the contents of the





P-Preferred-Service header field to identify the service without first checking against the capabilities (e.g. SDP) contained in the request. If the proxy inserts a P-Asserted-Service header field in the request the proxy **MUST** remove the P-Preferred-Service header field before forwarding the request, otherwise the Proxy **SHOULD** include the P-Preferred-Service header field when forwarding the request.

If the proxy receives a request from a node that it trusts, it can use the information in the P-Asserted-Service header field, if any, as if it had authenticated the user itself.

If there is no P-Asserted-Service header field present, or it is not possible to match the request to a specific service as identified by the service identifier, a proxy **MAY** add one containing it using its own analysis of the information contained in the SIP request. If the proxy received the request from an element that it does not trust and there is a P-Asserted-Service header present, the proxy **MUST** replace that header field contents with a new analysis or remove this header field.

The analysis performed to identify such service identifiers is outside the scope of this document. However, it is perfectly valid as a result of the analysis to not include any service identifier in the forwarded request, and thus not include a P-Asserted-Service header.

If a proxy forwards a request to a node outside the proxy's trust domain, there **MUST NOT** be a P-Asserted-Service header field in the forwarded request.

#### **5.1.3. Procedures at User Agent Servers (UAS)**

For a UAS outside the trust domain, the P-Asserted-Service header is removed before it reaches this entity, therefore there are no procedures for such a device.

However, if a User Agent Server receives a request from a previous element that it does not trust, it **MUST NOT** use the P-Asserted-Service header field in any way.

If a UA is part of the Trust Domain from which it received a request containing a P-Asserted-Service header field, then it can use the value freely but it **MUST** ensure that it does not forward the information to any element that is not part of the Trust Domain.



## **5.2. Usage of the P-Preferred-Service and P-Asserted-Service header fields in Responses**

There is no usage of these header field in responses.

## 6. Examples of Usage

In this example, proxy.example.com creates a P-Asserted-Service header field from the user identity it discovered from SIP Digest authentication, and the list of services appropriate to that user, and the services that correspond to the SDP information included in the request. Note that F1 and F2 are about identifying the user and do not directly form part of the capability provided in this document. It forwards this information to a trusted proxy which forwards it to a trusted gateway. Note that these examples consist of partial SIP messages that illustrate only those headers relevant to the authenticated identity problem.

\* F1 useragent.example.com -> proxy.example.com

```
INVITE sip:+14085551212@example.com SIP/2.0
Via: SIP/2.0/TCP useragent.example.com;branch=z9hG4bK-123
To: <sip:+14085551212@example.com>
From: "Anonymous" <sip:anonymous@anonymous.invalid>;tag=9802748
Call-ID: 245780247857024504
CSeq: 1 INVITE
Max-Forwards: 70
```

```
v=0
o=- 2987933615 2987933615 IN IP6 5555::aaa:bbb:ccc:ddd
s=-
c=IN IP6 5555::aaa:bbb:ccc:ddd
t=0 0
m=audio 3456 RTP/AVPF 97 96
b=AS:25.4
a=curr:qos local sendrecv
a=curr:qos remote none
a=des:qos mandatory local sendrecv
a=des:qos mandatory remote sendrecv
a=sendrecv
a=rtpmap:97 AMR
a=fmtp:97 mode-set=0,2,5,7; maxframes
```

\* F2 proxy.example.com -> useragent.example.com

```
SIP/2.0 407 Proxy Authorization
Via: SIP/2.0/TCP useragent.example.com;branch=z9hG4bK-123
To: <sip:+14085551212@example.com>;tag=123456
From: "Anonymous" <sip:anonymous@anonymous.invalid>;tag=9802748
Call-ID: 245780247857024504
CSeq: 1 INVITE
Proxy-Authenticate: .... realm="sip.example.com"
```



\* F3 useragent.example.com -> proxy.example.com

INVITE sip:+14085551212@example.com SIP/2.0  
Via: SIP/2.0/TCP useragent.example.com;branch=z9hG4bK-124  
To: <sip:+14085551212@example.com>  
From: "Anonymous" <sip:anonymous@anonymous.invalid>;tag=9802748  
Call-ID: 245780247857024504  
CSeq: 2 INVITE  
Max-Forwards: 70  
Proxy-Authorization: realm="sip.example.com" user="fluffy"

v=0

o=- 2987933615 2987933615 IN IP6 5555::aaa:bbb:ccc:ddd

s=-

c=IN IP6 5555::aaa:bbb:ccc:ddd

t=0 0

m=audio 3456 RTP/AVPF 97 96

b=AS:25.4

a=curr:qos local sendrecv

a=curr:qos remote none

a=des:qos mandatory local sendrecv

a=des:qos mandatory remote sendrecv

a=sendrecv

a=rtpmap:97 AMR

a=fmtp:97 mode-set=0,2,5,7; maxframes





\* F4 proxy.example.com -> proxy.pstn.example (trusted)

INVITE sip:+14085551212@proxy.pstn.example SIP/2.0  
Via: SIP/2.0/TCP useragent.example.com;branch=z9hG4bK-124  
Via: SIP/2.0/TCP proxy.example.com;branch=z9hG4bK-abc  
To: <sip:+14085551212@example.com>  
From: "Anonymous" <sip:anonymous@anonymous.invalid>;tag=9802748  
Call-ID: 245780247857024504  
CSeq: 2 INVITE  
Max-Forwards: 69  
P-Asserted-Service: urn:urn-7:3gpp-service.exampletelephony.version1

v=0  
o=- 2987933615 2987933615 IN IP6 5555::aaa:bbb:ccc:ddd  
s=-  
c=IN IP6 5555::aaa:bbb:ccc:ddd  
t=0 0  
m=audio 3456 RTP/AVPF 97 96  
b=AS:25.4  
a=curr:qos local sendrecv  
a=curr:qos remote none  
a=des:qos mandatory local sendrecv  
a=des:qos mandatory remote sendrecv  
a=sendrecv  
a=rtpmap:97 AMR  
a=fmtp:97 mode-set=0,2,5,7; maxframes



\* F5 proxy.pstn.example -> gw.pstn.example (trusted)

INVITE sip:+14085551212@gw.pstn.example SIP/2.0  
Via: SIP/2.0/TCP useragent.example.com;branch=z9hG4bK-124  
Via: SIP/2.0/TCP proxy.example.com;branch=z9hG4bK-abc  
Via: SIP/2.0/TCP proxy.pstn.example;branch=z9hG4bK-a1b2  
To: <sip:+14085551212@example.com>  
From: "Anonymous" <sip:anonymous@anonymous.invalid>;tag=9802748  
Call-ID: 245780247857024504  
CSeq: 2 INVITE  
Max-Forwards: 68  
P-Asserted-Service: urn:urn-7:3gpp-service.exampletelephony.version1

v=0  
o=- 2987933615 2987933615 IN IP6 5555::aaa:bbb:ccc:ddd  
s=-  
c=IN IP6 5555::aaa:bbb:ccc:ddd  
t=0 0  
m=audio 3456 RTP/AVPF 97 96  
b=AS:25.4  
a=curr:qos local sendrecv  
a=curr:qos remote none  
a=des:qos mandatory local sendrecv  
a=des:qos mandatory remote sendrecv  
a=sendrecv  
a=rtpmap:97 AMR  
a=fmtp:97 mode-set=0,2,5,7; maxframes



## **7. Security considerations**

The mechanism provided in this document is a partial consideration of the problem of service identification in SIP. For example, these mechanisms provide no means by which end users can securely share service information end-to-end without a trusted service provider. This information is secured by transitive trust, which is only as reliable as the weakest link in the chain of trust.

The trust domain provides a set of servers where the characteristics of the service are agreed for that service identifier value, and that the calling user is entitled to use that service.

[draft-ietf-sipping-service-identification](#)

[[I-D.ietf-sipping-service-identification](#)] identifies the impact of allowing such service identifier values to "leak" outside of the trust domain, including implications on fraud, interoperability and stifling of service innovation.



## **8. IANA considerations**

### **8.1. P-Asserted-Service and P-Preferred-Service header fields**

This document specifies two new SIP headers: P-Asserted-Service and P-Preferred-Service. Their syntax is given in [Section 3](#). These headers are defined by the following information, which has been added to the header sub-registry under <http://www.iana.org/assignments/sip-parameters>.

Header Name	compact	Reference
-----	-----	-----
P-Asserted-Service		[RFCxxxx]
P-Preferred-Service		[RFCxxxx]

Note to the RFC editor: substitute xxxx with the RFC number of this document.

### **8.2. Definition of Service-ID values**

top-level identifiers are identified by labels managed by IANA, according to the processes outlined in [RFC 5226](#) [[RFC5226](#)] in a new registry called "Service-ID/Application-ID Labels". Thus, creating a new service at the top-level requires IANA action. The policy for adding service labels is 'specification required'. The following two identifiers are initially defined:

3gpp-service

3gpp-application

Subservice identifiers are not managed by IANA. It is the responsibility of the organisation that registered the service to manage the subservices.

Application identifiers are not managed by IANA. It is the responsibility of the organisation that registered the service to manage the applicable applications.

Entries in the registration table have the following format:





Service/Application	Reference	Description
-----		
3gpp-service	RFCxxxx	Communication services defined by 3GPP for use by the IM CN subsystem and its attached UAs. This value in itself does not define a service and requires subsequent labels to define the service.
3gpp-application	RFCxxxx	Applications defined by 3GPP for use by UAs attached to the IM CN subsystem. This value in itself does not define a service and requires subsequent labels to define the service.

Note to the RFC editor: substitute xxxx with the RFC number of this document.



## **9. APPENDIX: Changes history**

Note to RFC Editor: Please remove this entire appendix before publication

### **9.1. Changes between version -01 and version -02**

1. Incorporation of terms "derived service identification" and "declarative service identification" from [draft-ietf-sipping-service-identification](#).
2. Correction of the URN syntax in examples.
3. Appropriate introduction to table 1 and table 2 placing these in a normative context to those in other tables in other RFCs.
4. Addition to security considerations section to clarify trust domain concept.
5. References to [RFC 3325](#) changed to [RFC 3324](#) for definition of trust domain.
6. Reference to [RFC 2234](#) updated to [RFC 5234](#) because the later revision applies. No consequential technical change.
7. Reference to [RFC 2434](#) updated to [RFC 5226](#) because the later revision applies. No consequential technical change.
8. References updated to symbolic. Remove of reference identifiers from abstract.
9. Numerous editorial changes and minor clarifications.

### **9.2. Changes between version -02 and version -03**

1. The URN value has been preassigned by IANA. This value substituted into document.
2. service-id is extended to include "urn:" within the expansion to conform to usage.
3. Procedures inserted where the UAS is inside the trust domain, e.g. gateway.
4. Procedures inserted for the proxy handling of a P-Preferred-Service header field.



5. A number of editorial corrections.

## **10. References**

### **10.1. Normative References**

- [RFC1123] Braden, R., "Requirements for Internet Hosts - Application and Support", STD 3, [RFC 1123](#), October 1989.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC3261] Rosenberg, J., Schulzrinne, H., Camarillo, G., Johnston, A., Peterson, J., Sparks, R., Handley, M., and E. Schooler, "SIP: Session Initiation Protocol", [RFC 3261](#), June 2002.
- [RFC3324] Watson, M., "Short Term Requirements for Network Asserted Identity", [RFC 3324](#), November 2002.
- [RFC3406] Daigle, L., van Gulik, D., Iannella, R., and P. Faltstrom, "Uniform Resource Names (URN) Namespace Definition Mechanisms", [BCP 66](#), [RFC 3406](#), October 2002.
- [RFC3958] Daigle, L. and A. Newton, "Domain-Based Application Service Location Using SRV RRs and the Dynamic Delegation Discovery Service (DDDS)", [RFC 3958](#), January 2005.
- [RFC5226] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.
- [RFC5234] Crocker, D. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), January 2008.

### **10.2. Informative References**

- [RFC2976] Donovan, S., "The SIP INFO Method", [RFC 2976](#), October 2000.
- [RFC3262] Rosenberg, J. and H. Schulzrinne, "Reliability of Provisional Responses in Session Initiation Protocol (SIP)", [RFC 3262](#), June 2002.
- [RFC3265] Roach, A., "Session Initiation Protocol (SIP)-Specific Event Notification", [RFC 3265](#), June 2002.
- [RFC3311] Rosenberg, J., "The Session Initiation Protocol (SIP) UPDATE Method", [RFC 3311](#), October 2002.



- [RFC3428] Campbell, B., Rosenberg, J., Schulzrinne, H., Huitema, C., and D. Gurle, "Session Initiation Protocol (SIP) Extension for Instant Messaging", [RFC 3428](#), December 2002.
- [RFC3515] Sparks, R., "The Session Initiation Protocol (SIP) Refer Method", [RFC 3515](#), April 2003.
- [RFC3840] Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Indicating User Agent Capabilities in the Session Initiation Protocol (SIP)", [RFC 3840](#), August 2004.
- [RFC3841] Rosenberg, J., Schulzrinne, H., and P. Kyzivat, "Caller Preferences for the Session Initiation Protocol (SIP)", [RFC 3841](#), August 2004.
- [RFC3903] Niemi, A., "Session Initiation Protocol (SIP) Extension for Event State Publication", [RFC 3903](#), October 2004.
- [I-D.ietf-sipping-service-identification]  
Rosenberg, J., "Identification of Communications Services in the Session Initiation Protocol (SIP)",  
[draft-ietf-sipping-service-identification-03](#) (work in progress), August 2008.
- [I-D.rosenberg-sip-app-media-tag]  
Rosenberg, J., "A Session Initiation Protocol (SIP) Media Feature Tag for MIME Application Sub-Types",  
[draft-rosenberg-sip-app-media-tag-02](#) (work in progress), November 2007.





Author's Address

Keith Drage  
Alcatel-Lucent  
Quadrant, Stonehill Green, Westlea  
Swindon, Wilts  
UK

Email: [drage@alcatel-lucent.com](mailto:drage@alcatel-lucent.com)