

6TiSCH  
Internet-Draft  
Intended status: Informational  
Expires: July 8, 2015

D. Dujovne, Ed.  
Universidad Diego Portales  
LA. Grieco  
Politecnico di Bari  
MR. Palattella  
University of Luxembourg  
N. Accettura  
University of California Berkeley  
January 4, 2015

6TiSCH On-the-Fly Scheduling  
[draft-dujovne-6tisch-on-the-fly-04](#)

## Abstract

This document describes the environment, problem statement, and goals of On-The-Fly (OTF) scheduling, a Layer-3 mechanism for 6TiSCH networks. The purpose of OTF is to dynamically adapt the aggregate bandwidth, i.e., the number of reserved soft cells between neighbor nodes, based on the specific application constraints to be satisfied. When using OTF, softcell and bundle reservation is distributed: through the 6top interface, neighbor nodes negotiate the cell(s) to be (re)allocated/deleted, with no intervention needed of a centralized entity. This document aims at defining a module which uses the functionalities provided by the 6top sublayer to (i) extract statistics and (ii) determine when to reserve/delete soft cells in the schedule. The exact reservation and deletion algorithm, and the number and type of statistics to be used in the algorithm are out of scope. OTF deals only with the number of softcells to be reserved/deleted; it is up to 6top to select the specific soft cells within the TSCH schedule.

## Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 8, 2015.

## Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">2</a>
<a href="#">2.</a>	Allocation policy . . . . .	<a href="#">3</a>
<a href="#">3.</a>	Allocation methods . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Cell and Bundle Reservation/Deletion . . . . .	<a href="#">5</a>
5.	Getting statistics and other information about cells through 6top . . . . .	<a href="#">6</a>
<a href="#">6.</a>	Events triggering algorithms in OTF . . . . .	<a href="#">7</a>
<a href="#">7.</a>	Bandwidth Estimation Algorithms . . . . .	<a href="#">8</a>
<a href="#">8.</a>	OTF external CoAP interface . . . . .	<a href="#">9</a>
<a href="#">9.</a>	Acknowledgments . . . . .	<a href="#">10</a>
<a href="#">10.</a>	References . . . . .	<a href="#">11</a>
<a href="#">10.1.</a>	Informative References . . . . .	<a href="#">11</a>
<a href="#">10.2.</a>	External Informative References . . . . .	<a href="#">11</a>
	Authors' Addresses . . . . .	<a href="#">11</a>

## [1.](#) Introduction

The IEEE802.15.4e standard [[IEEE802154e](#)] was published in 2012 as an amendment to the Medium Access Control (MAC) protocol defined by the IEEE802.15.4-2011 [[IEEE802154](#)] standard. The Timeslotted Channel Hopping (TSCH) mode of IEEE802.15.4e is the object of this document.

On-The-Fly (OTF) scheduling is a 1-hop protocol with which a node negotiates the number of soft cells scheduled with its neighbors, without requiring any intervention of a centralized entity (e.g., a PCE). This document describes the OTF allocation policies and methods used by two neighbors to allocate one or more softcells in a distribution fashion. It also proposes an algorithm for estimating the required bandwidth (BW). This document defines the interface



between OTF and the 6top sublayer ([[I-D.wang-6tisch-6top](#)]), to collect and retrieve statistics, or allocate/delete cells and bundles. This document defines a framework; the algorithm and statistics used are out of scope. This draft follows the terminology defined in [[I-D.ietf-6tisch-terminology](#)] and addresses the open issue related to the scheduling mechanisms raised in [[I-D.ietf-6tisch-ts](#)].

## 2. Allocation policy

OTF is a distributed scheduling protocol which increases/decreases the bandwidth between two neighbor nodes (i.e., adding/deleting soft cells) by interacting with the 6top sublayer. It retrieves statistics from 6top, and uses that information to trigger 6top to add/delete softcells to a particular neighbor. The algorithm which decides when to add/delete softcells is out of scope. For example, 6top might decide to add a cell if some queue of outbound frames is overflowing. Similarly, OTF can delete cells when the queue has been empty for some time. OTF only triggers 6top to add/delete the soft cells, it is the responsibility of the 6top sublayer to determine the exact slotOffset/channelOffset of those cells. In this document, the term "cell" and "soft cell" are used interchangeably.

All the soft cells allocated are part of best effort track, i.e. with TrackID=00, as defined in [[I-D.wang-6tisch-6top](#)]. These cells can be used for forwarding any packet in the queue, regardless of the specific track it belongs to. OTF manages the global bandwidth requirements between two neighbor nodes; per-track management is currently out of scope.

OTF is prone to schedule collisions. Nodes might not be aware of the cells allocated by other pairs of nodes. A schedule collision occurs when the same cell is allocated by different pairs in the same interference space. The probability of having allocation collision may be kept low by grouping cells into chunks (see [[I-D.ietf-6tisch-terminology](#)] and [[I-D.ietf-6tisch-architecture](#)] for more details). The use of chunks is outside the scope of this current version of the OTF draft.

The "allocation policy" is the algorithm used by OTF to decide when to increase/decrease the bandwidth allocated between two neighbor nodes in order to satisfy the traffic requirements. These requirements can be expressed in terms of throughput, latency or other constraints.

This document introduces the following parameters for describing the behavior of the OTF allocation policy:



**SCHEDULEDCELLS:** The amount of soft cells scheduled in a bundle on the best effort track between two neighbors.

**REQUIREDCELLS:** Number of cells requested by OTF to 6top, a non-negative value. How this is computed is out of the scope. It MAY be an instantaneous request, or a value averaged on several measurements.

**OTFTHRESH:** Threshold parameter introducing cell over-provisioning in the allocation policy. It is a non-negative value expressed as number of cells. Which value to use is application-specific and out of scope.

The OTF allocation policy compares the number of required cells against the number of scheduled ones, using the OTF threshold for bounding the signaling overhead due to negotiations of new cells. In details:

1. If **REQUIREDCELLS** is greater than **SCHEDULEDCELLS**, OTF asks 6top to add one or more soft cells to the bundle on the best effort track.
2. If **REQUIREDCELLS** is greater or equal than **SCHEDULEDCELLS-OTFTHRESH**, and it is lower than or equal to **SCHEDULEDCELLS**, OTF does not perform any bundle resizing, since the scheduled cells are sufficient for managing the current traffic conditions.
3. If **REQUIREDCELLS** is lower than **SCHEDULEDCELLS-OTFTHRESH**, OTF asks 6top to delete one or more soft cells from the bundle on the best-effort track.

When **OTFTHRESH=0**, any discrepancy between **REQUIREDCELLS** and **SCHEDULEDCELLS** triggers a 6top negotiation of soft cells. Other values for the **OTFTHRESH** over-provision the scheduled number of cells, reducing the number of triggered 6top negotiations.

The number of soft cells to be scheduled/deleted for bundle resizing is out of the scope of this document and implementation-dependant.

### **3. Allocation methods**

Beyond the allocation policies that describe the approach used by OTF for fulfilling the node bandwidth requests, the OTF framework also includes Allocation Methods that specify how OTF issues commands to the 6top sublayer. In other words, the allocation methods represent the mechanisms that are used by the allocation policies.



In detail, OTF includes two distinct allocation methods: soft cell and bundle allocation methods. Each Allocation Policy can use either one or both allocation methods. As specified in [\[I-D.wang-6tisch-6top\]](#), 6top provides a set of commands that allows OTF to allocate/delete soft cells. The same set of commands can be used for reserving bundles.

With the soft cell allocation method, OTF has 6top reserve a single soft cell on the best effort track, for allowing a given node to exchange traffic with a specific neighbor. The 6top layer allocates and maintains this cell. If a bundle is already reserved between the same pair of neighbors, on the same track, this request translates into a bundle resize request. The newly allocated cell increases the size of the already existing bundle. Similarly, when OTF realizes there is a reduction of traffic exchanged between the two neighbors, it may ask 6top to delete a softcell from the best effort track, i.e. to decrease the size of the bundle on the best effort track. If no bundle with TrackID=00 exists, the 6top softcell create command generates a new bundle of size 1.

With the bundle allocation method, OTF sends bundle allocation requests to the 6top sublayer, specifying the bundle size (the number of soft cells) and the TrackID=00. Scheduling N softcells is equivalent to asking for a bundle of size N. The cells within the bundle are allocated by 6top (and thus, used for traffic exchange) only afterwards, according to the nodes bandwidth need.

#### **4. Cell and Bundle Reservation/Deletion**

In order to reserve/delete softcells, OTF interacts with 6top sublayer. To this aim OTF uses the following set of commands offered by 6top: CREATE.softcell, and DELETE.softcell. When creating (deleting) a softcell, OTF specifies the track the cell belongs to (i.e., best effort track, TrackID=00), but not its slotOffset nor the channelOffset. If at least one cell on the best effort track already exists, the CREATE.softcell and DELETE.softcell, translate into INCREASE and DECREASE the bundle size, respectively. 6top is responsible for picking the specific cell to be added/deleted within the bundle. Before being able to do so, source and destination nodes go through a cell negotiation process. This process is out of scope of 6top and OTF. In order to reserve a best effort bundle, OTF uses the CREATE.softcell command, set TrackID=00, but asks 6top for multiple softcells. Following OTF request, 6top either (i) creates a new bundle, if no cells were reserved already on the best effort track, or (ii) increases the bundle size of the already existing best-effort bundle. By using the DELETE.softcell command, and asking for deleting multiple softcells, OTF has 6top delete the entire best effort bundle.





OTF provides a policy for 6top to generate CREATE/DELETE.softcells commands, policy that is out of 6top scope [[I-D.wang-6tisch-6top](#)]. Such policy is not the only one that can be used by 6top. Others may be defined in the future.

## **5. Getting statistics and other information about cells through 6top**

Statistics are kept in 4 data structures of 6top MIB: CellList, MonitoringStatusList, NeighborList, and QueueList.

CellList provides per-cell statistics. From this list, an upper layer can get per-bundle statistics. OTF may have access to the CellList, by using the CoAP-YANG Model, but actually cell-specific statistics are not significant to OTF, since softcells can be re-allocated in time by 6top itself, based on network conditions.

MonitoringStatusList provides per-neighbor and slotframe statistics. From it an upper layer (e.g., OTF) can get per bundle overview of scheduling and its performance. Such list contains information about the number of hard and soft cells reserved to a given node with a specific neighbor, and the QoS (that can be expressed in form of different metrics: PDR, ETX, RSSI, LQI) on the actual bandwidth, and the over-provisioned bandwidth (which includes the over-provisioned cells). 6top can use such list to operate 6top Monitoring Functions, such as re-allocating cells (by changing their slotOffset and/or channelOffset) when it finds out that the link quality of some softcell is much lower than average. Unlike 6top, OTF does not operate any re-allocation of cells. In fact, OTF can ask for more/less bandwidth, but cannot move any cell within the schedule. Thus, the 6top Monitoring function is useful to OTF, because it can provide better cells for a given bandwidth requirement, specified by OTF. For instance, OTF may require some additional bandwidth (e.g. 2 cells in a specific slotframe) with PDR = 75%; then, 6top will reserve 3 slots in the slotframe to meet the bandwidth requirement. In addition, when the link quality drops to 50%, 6top will reserve 4 slots to keep meeting the bandwidth requirement. Given that OTF operates on the global bandwidth between two neighbor nodes, it does not need to be informed from 6top about cells' re-allocation.

NeighborList provides per-neighbor statistics. From it, an upper layer can understand the connectivity of a pair of nodes. Based on the quality of the link, e.g., LQI under threshold, OTF may ask 6top to delete some cells, in order to reserve them for better-connected links.

QueueList provides per-Queue statistics. From it, an upper layer can know the traffic load. OTF, based on such queue statistics (e.g., average length of the queue, average age of the packet in queue,



etc.) may trigger a 6top CREATE.softcell (DELETESoftcell) command for increasing (decreasing) the bandwidth and be able to better serve the packets in the queue.

## 6. Events triggering algorithms in OTF

The Algorithms running within OTF MUST be event-oriented. As a consequence, OTF requires to connect the algorithms with external events to trigger their execution. The algorithm also generates one or more events when it is executed, such as a new softcell allocation. Both type of events, the one which triggers the algorithm and the ones which are generated by the execution of the algorithm are called OTF events.

The following notation is used on the definition of OTF events:

$BW \leftarrow BWA(B, T, S(B, T))$  where:

BWA: Bandwidth allocation algorithm

BW: Bandwidth

T: Best Effort Track

B: Bundle

$S(B, T)$  Statistics for bundle B on track T

$M(B, T)$ : Actual bundle size for bundle B on track T

The OTF events are defined as:

Event A: A new bundle B on track T is created. The OTF events generated by the algorithm are:

1. Add a new entry in the storage M for bundle B on track T.
2. Ask 6top for  $S(B, T)$ .
3.  $BW \leftarrow BWA(B, T, S(B, T))$ .
4. Ask 6top to allocate a bundle of size BW.
5.  $M(B, T) \leftarrow BW$ .

Event B: A packet is waiting to be transmitted on any track, but no cell is available (i.e., saturation). The OTF events generated by the algorithm are:



1. Collect stats  $S(B,T)$  from 6top.
2.  $BW \leftarrow BWA(B,T,S(B,T))$ .
3. Ask 6top to increase the bundle size up to  $BW$ .
4. If (allocation successful) then  $M(B,T) \leftarrow BW$ .

Event C: The usage of a bundle  $B$  on track  $T$  is too low, below a pre-established threshold. The OTF events generated by the algorithm are:

1. Collect stats  $S(B,T)$  from 6top.
2.  $BW \leftarrow BWA(B,T,S(B,T))$ .
3. Ask 6top to decrease the bundle size to  $BW$ .
4. If (allocation successful) then  $M(B,T) \leftarrow BW$ .

Event D: The usage of a bundle  $B$  on track  $T$  is too high, above a pre-established threshold. The OTF events generated by the algorithm are:

1. Collect stats  $S(B,T)$  from 6top.
2.  $BW \leftarrow BWA(B,T,S(B,T))$ .
3. Ask 6top to increase the bundle size to  $BW$ .
4. If (allocation successful) then  $M(B,T) \leftarrow BW$ .

Event E: Bundle  $B$  on track  $T$  is deleted. The OTF events generated by the algorithm are:

1. purge  $M(B,T)$ .

## **7. Bandwidth Estimation Algorithms**

OTF supports different bandwidth estimation algorithms that can be used by a node in a 6TiSCH network for checking the current traffic conditions and thus the actual bandwidth usage. By doing so, one can adapt (increase or decrease) the number of scheduled cells/bundles for a given pair of neighbors (e.g., parent node and its child), according to their needs. OTF supports several bandwidth estimation algorithms numbered 0 to 255 in the OTF implementation. The first algorithm (0) is reserved to the default algorithm that is described below. By using SET and GET commands, one can set the specific



algorithm to be used, and get information about which algorithm is implemented.

Steps of the default bandwidth estimation algorithm, running over a parent node:

Step 1: Collect the bandwidth requests from child nodes (incoming traffic).

Step 2: Collect the node bandwidth requirement from the application (self/local traffic).

Step 3: Collect the current outgoing scheduled bandwidth (outgoing traffic).

Step 4: If (outgoing < incoming + self) then SCHEDULE soft cells/bundles to satisfy bandwidth requirements.

Step 5: If (outgoing > incoming + self) then DELETE the soft cells that are not used.

Step 6: Return to step 1.

The default bandwidth estimation algorithm introduced in this document adopts a reactive allocation policy, i.e., it uses OTFTHRESH=0. In this case, at Step 4, new soft cells will be scheduled, using the cell allocation method, only if there are no free cells in the bundle that can satisfy the current request of soft cells. The node asks 6top for increasing the bundle size by using the bundle allocation method.

## **8. OTF external CoAP interface**

In order to select the current OTF algorithm and provide functional parameters from outside OTF, this module uses CoAP with YANG as the data model. The algorithm number and the parameters MUST be invoked in different CoAP calls.

The path to select the algorithm is '6t/e/otf/alg' with A as the algorithm number.





```

+-----+
Header  | POST                                     |
+-----+
Uri-Path| /6t/e/otf/alg                               |
+-----+
Options | CBOR( {AlgNo: 123} )                         |
+-----+

```

Figure 1: Algorithm number POST message

To obtain the current algorithm number:

```

+-----+
Header  | GET                                     |
+-----+
Uri-Path| /6t/e/otf/alg                               |
+-----+
Options | Accept: application/cbor                     |
+-----+

```

Figure 2: Algorithm number GET message

An example is: 'coap://[aaaa::1]/6t/e/otf/alg'

The current algorithm parameter path is '6t/e/otf/alg/par'.

```

+-----+
Header  | POST                                     |
+-----+
Uri-Path| /6t/e/otf/alg/par                           |
+-----+
Options | CBOR( {Par: 0x1234} )                       |
+-----+

```

Figure 3: Algorithm number POST message

An example follows: 'coap://[aaaa::1]/6t/e/otf/alg/par'

## 9. Acknowledgments

Special thanks to Prof. Kris Pister for his valuable contribution in designing the default Bandwidth Estimation Algorithm, and to Prof. Qin Wang for her support in defining the interaction between OTF and 6top sublayer.

Thanks to the Fondecyt 1121475 Project, to INRIA Chile "Network Design" group and to the IoT6 European Project (STREP) of the 7th Framework Program (Grant 288445).



## **10. References**

### **10.1. Informative References**

[I-D.ietf-6tisch-terminology]

Palattella, M., Thubert, P., Watteyne, T., and Q. Wang, "Terminology in IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-terminology-02](#) (work in progress), July 2014.

[I-D.ietf-6tisch-architecture]

Thubert, P., Watteyne, T., and R. Assimiti, "An Architecture for IPv6 over the TSCH mode of IEEE 802.15.4e", [draft-ietf-6tisch-architecture-04](#) (work in progress), October 2014.

[I-D.ietf-6tisch-tsch]

Watteyne, T., Palattella, M., and L. Grieco, "Using IEEE802.15.4e TSCH in an IoT context: Overview, Problem Statement and Goals", [draft-ietf-6tisch-tsch-04](#) (work in progress), December 2014.

[I-D.wang-6tisch-6top]

Wang, Q., Vilajosana, X., and T. Watteyne, "6TiSCH Operation Sublayer (6top)", [draft-wang-6tisch-6top-00](#) (work in progress), October 2013.

### **10.2. External Informative References**

[IEEE802154e]

IEEE standard for Information Technology, "IEEE std. 802.15.4e, Part. 15.4: Low-Rate Wireless Personal Area Networks (LR-WPANs) Amendment 1: MAC sublayer", April 2012.

[IEEE802154]

IEEE standard for Information Technology, "IEEE std. 802.15.4, Part. 15.4: Wireless Medium Access Control (MAC) and Physical Layer (PHY) Specifications for Low-Rate Wireless Personal Area Networks", June 2011.

Authors' Addresses



Diego Dujovne (editor)  
Universidad Diego Portales  
Escuela de Informatica y Telecomunicaciones  
Av. Ejercito 441  
Santiago, Region Metropolitana  
Chile

Phone: +56 (2) 676-8121  
Email: [diego.dujovne@mail.udp.cl](mailto:diego.dujovne@mail.udp.cl)

Luigi Alfredo Grieco  
Politecnico di Bari  
Department of Electrical and Information Engineering  
Via Orabona 4  
Bari 70125  
Italy

Phone: 00390805963911  
Email: [a.grieco@poliba.it](mailto:a.grieco@poliba.it)

Maria Rita Palattella  
University of Luxembourg  
Interdisciplinary Centre for Security, Reliability and Trust  
4, rue Alphonse Weicker  
Luxembourg L-2721  
LUXEMBOURG

Phone: (+352) 46 66 44 5841  
Email: [maria-rita.palattella@uni.lu](mailto:maria-rita.palattella@uni.lu)

Nicola Accettura  
University of California Berkeley  
Berkeley Sensor & Actuator Center  
490 Cory Hall  
Berkeley, California 94720  
USA

Email: [nicola.accettura@eecs.berkeley.edu](mailto:nicola.accettura@eecs.berkeley.edu)

