

INTERNET-DRAFT
Obsoletes: [6195](#)
Updates: [1183](#), [3597](#)
Intended status: Best Current Practice
Expires: September 9, 2012

Donald Eastlake 3rd
Huawei

March 10, 2012

Domain Name System (DNS) IANA Considerations
<[draft-eastlake-dnsex-6195bis-01.txt](#)>

Abstract

This document specifies Internet Assigned Number Authority (IANA) parameter assignment considerations are specified for the allocation of Domain Name System (DNS) resource record types, CLASSES, operation codes, error codes, DNS protocol message header bits, and AFSDB resource record subtypes. It obsoletes [RFC 6195](#).

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Distribution of this draft is unlimited. It is intended to become the new [BCP 42](#) obsoleting [RFC 6195](#). Comments should be sent to the DNS Extensions Working Group mailing list <dnsex@ietf.org>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

Table of Contents

- [1. Introduction.....3](#)
- [1.1. Terminology.....3](#)

- [2. DNS Query/Response Headers.....4](#)
- [2.1. One Spare Bit?.....4](#)
- [2.2. OpCode Assignment.....5](#)
- [2.3. RCODE Assignment.....5](#)

- [3. DNS Resource Records.....7](#)
- [3.1. RRTYPE IANA Considerations.....8](#)
- [3.1.1. DNS RRTYPE Allocation Policy.....9](#)
- [3.1.2. DNS RRTYPE Expert Guidelines.....10](#)
- [3.1.3. Special Note on the OPT RR.....10](#)
- [3.1.4. The AFSDB RR Subtype Field.....10](#)
- [3.2. RR CLASS IANA Considerations.....11](#)
- [3.3. Label Considerations.....13](#)
- [3.3.1. Label Types.....13](#)
- [3.3.2. Label Contents and Use.....13](#)

- [4. Security Considerations.....14](#)
- [5. IANA Considerations.....14](#)

- [Appendix A: RRTYPE Allocation Template.....15](#)
- [Appendix B: Changes From \[RFC 6195\]\(#\).....16](#)
- [Normative References.....17](#)
- [Informative References.....18](#)

1. Introduction

The Domain Name System (DNS) provides replicated distributed secure hierarchical databases that store "resource records" (RRs) under domain names. DNS data is structured into CLASSES and zones that can be independently maintained. Familiarity with [[RFC1034](#)], [[RFC1035](#)], [[RFC2136](#)], [[RFC2181](#)], and [[RFC4033](#)] is assumed.

This document provides, either directly or by reference, the general IANA parameter assignment considerations that apply across DNS query and response headers and all RRs. There may be additional IANA considerations that apply to only a particular RRTYPE or query/response OpCode. See the specific RFC defining that RRTYPE or query/response OpCode for such considerations if they have been defined, except for AFSDB RR considerations [[RFC1183](#)], which are included herein. This RFC obsoletes [[RFC6195](#)]; however, the only significant changes are the changes to the RRTYPE IANA allocation process.


IANA currently maintains a web page of DNS parameters available from <http://www.iana.org>.

1.1. Terminology

"Standards Action", "IETF Review", "Specification Required", and "Private Use" are as defined in [[RFC5226](#)].

2. DNS Query/Response Headers

The header for DNS queries and responses contains field/bits in the following diagram taken from [\[RFC2136\]](#) and [\[RFC6195\]](#):



The ID field identifies the query and is echoed in the response so they can be matched.

The QR bit indicates whether the header is for a query or a response.

The AA, TC, RD, RA, AD, and CD bits are each theoretically meaningful only in queries or only in responses, depending on the bit. However, some DNS implementations copy the query header as the initial value of the response header without clearing bits. Thus, any attempt to use a "query" bit with a different meaning in a response or to define a query meaning for a "response" bit is dangerous, given existing implementation. Such meanings may only be assigned by a Standards Action.

The unsigned integer fields query count (QDCOUNT), answer count (ANCOUNT), authority count (NSCOUNT), and additional information count (ARCOUNT) express the number of records in each section for all OpCodes except Update [\[RFC2136\]](#). These fields have the same structure and data type for Update but are instead the counts for the zone (ZOCOUNT), prerequisite (PRCOUNT), update (UPCOUNT), and additional information (ARCOUNT) sections.

2.1. One Spare Bit?

There have been ancient DNS implementations for which the Z bit being on in a query meant that only a response from the primary server for

a zone is acceptable. It is believed that current DNS implementations

D. Eastlake 3rd

[Page 4]

ignore this bit.

Assigning a meaning to the Z bit requires a Standards Action.

2.2. OpCode Assignment

Currently, DNS OpCodes are assigned as follows:

OpCode	Name	Reference
0	Query	[RFC1035]
1	IQuery (Inverse Query, Obsolete)	[RFC3425]
2	Status	[RFC1035]
3	available for assignment	
4	Notify	[RFC1996]
5	Update	[RFC2136]
6-15	available for assignment	

New OpCode assignments require a Standards Action as modified by [RFC4020].

2.3. RCODE Assignment

It would appear from the DNS header above that only four bits of RCODE, or response/error code, are available. However, RCODEs can appear not only at the top level of a DNS response but also inside OPT RRs [RFC2671bis], TSIG RRs [RFC2845], and TKEY RRs [RFC2930]. The OPT RR provides an 8-bit extension resulting in a 12-bit RCODE field, and the TSIG and TKEY RRs have a 16-bit RCODE field.


Error codes appearing in the DNS header and in these three RR types all refer to the same error code space with the single exception of error code 16, which has a different meaning in the OPT RR than in other contexts. This duplicate assignment was accidental. See table below.

RCODE	Name	Description	Reference
Decimal			
Hexadecimal			
0	NoError	No Error	[RFC1035]
1	FormErr	Format Error	[RFC1035]
2	ServFail	Server Failure	[RFC1035]
3	NXDomain	Non-Existent Domain	[RFC1035]
4	NotImp	Not Implemented	[RFC1035]
5	Refused	Query Refused	[RFC1035]
6	YXDomain	Name Exists when it should not	[RFC2136]
7	YXRRSet	RR Set Exists when it should not	[RFC2136]
8	NXRRSet	RR Set that should exist does not	[RFC2136]
9	NotAuth	Server Not Authoritative for zone	[RFC2136]
10	NotZone	Name not contained in zone	[RFC2136]
11 - 15			
0xB - 0xF		Available for assignment	
16	BADVERS	Bad OPT Version	[RFC2671bis]
16	BADSIG	TSIG Signature Failure	[RFC2845]
17	BADKEY	Key not recognized	[RFC2845]
18	BADTIME	Signature out of time window	[RFC2845]
19	BADMODE	Bad TKEY Mode	[RFC2930]
20	BADNAME	Duplicate key name	[RFC2930]
21	BADALG	Algorithm not supported	[RFC2930]
22	BADTRUC	Bad Truncation	[RFC4635]
23 - 3,840			
0x0017 - 0x0F00		Available for assignment	
3,841 - 4,095			
0x0F01 - 0x0FFF		Private Use	
4,096 - 65,534			
0x1000 - 0xFFFFE		Available for assignment	
65,535			
0xFFFF		Reserved, can only be allocated by a Standards Action.	

Since it is important that RCODEs be understood for interoperability, assignment of a new RCODE in the ranges listed above as "Available for assignment" requires an IETF Review.

3. DNS Resource Records

All RRs have the same top-level format, shown in the figure below taken from [RFC1035].



NAME is an owner name, i.e., the name of the node to which this resource record pertains. NAMES are specific to a CLASS as described in Section 3.2. NAMES consist of an ordered sequence of one or more labels, each of which has a label type [RFC1035] [RFC2671bis].

TYPE is a 2-octet unsigned integer containing one of the RRTYPE codes. See Section 3.1.

CLASS is a 2-octet unsigned integer containing one of the RR CLASS codes. See Section 3.2.

TTL is a 4-octet (32-bit) unsigned integer that specifies, for data TYPES, the number of seconds that the resource record may be cached before the source of the information should again be consulted. Zero is interpreted to mean that the RR can only be used for the transaction in progress.

RDLENGTH is an unsigned 16-bit integer that specifies the length in octets of the RDATA field.

RDATA is a variable-length string of octets that constitutes the resource. The format of this information varies according to the TYPE and, in some cases, the CLASS of the resource record.

3.1. RRTYPE IANA Considerations

There are three subcategories of RRTYPE numbers: data TYPES, QTYPES, and Meta-TYPES.

Data TYPES are the means of storing data. QTYPES can only be used in queries. Meta-TYPES designate transient data associated with a particular DNS message and, in some cases, can also be used in queries. Thus far, data TYPES have been assigned from 1 upward, plus the block from 100 through 103, and from 32,768 upward, while Q and Meta-TYPES have been assigned from 255 downward except for the OPT Meta-RR, which is assigned TYPE 41. There have been DNS implementations that made caching decisions based on the top bit of the bottom byte of the RRTYPE.

There are currently three Meta-TYPES assigned: OPT [[RFC2671bis](#)], TSIG [[RFC2845](#)], and TKEY [[RFC2930](#)]. There are currently five QTYPES assigned: * (ALL), MAILA, MAILB, AXFR, and IXFR.

RRTYPES have mnemonics that must be completely disjoint from the mnemonics used for CLASSES and that must match the following regular expression:

$$[A-Z][A-Z0-9\-\-]*[A-Z0-9]$$

Considerations for the allocation of new RRTYPES are as follows:

Decimal
Hexadecimal

- 0
0x0000 - RRTYPE zero is used as a special indicator for the SIG (0) RR [[RFC2931](#)] [[RFC4034](#)] and in other circumstances, and it must never be allocated for ordinary use.
- 1 - 127
0x0001 - 0x007F - Remaining RRTYPES in this range are assigned for data TYPES by the DNS RRTYPE Allocation Policy as specified in [Section 3.1.1](#).
- 128 - 255
0x0080 - 0x00FF - Remaining RRTYPES in this range are assigned for Q and Meta-TYPES by the DNS RRTYPE Allocation Policy as specified in [Section 3.1.1](#).
- 256 - 61,439
0x0100 - 0xEFFF - Remaining RRTYPES in this range are assigned for data RRTYPES by the DNS RRTYPE Allocation Policy as specified in [Section 3.1.1](#). (32,768 and 32,769 (0x8000 and

0x8001) have been assigned.)

D. Eastlake 3rd

[Page 8]

61,440 - 65,279

0xF000 - 0xFEFF - Reserved for future use. IETF Review required to define use.

65,280 - 65,534

0xFF00 - 0xFFFE - Private Use.

65,535

0xFFFF - Reserved, can only be assigned by a Standards Action.

3.1.1. DNS RRTYPE Allocation Policy

Parameter values specified in [Section 3.1](#) above, as assigned based on DNS RRTYPE Allocation Policy, are allocated by Expert Review if they meet the two requirements listed below. There will be a pool of a small number of Experts appointed by the IESG. Each application will be judged by an Expert selected by IANA. In any case where the selected Expert is unavailable or states they have a conflict of interest, IANA may select another Expert from the pool.

Some guidelines for the Experts are given in [Section 3.1.2](#). RRTYPES that do not meet the requirements below may nonetheless be allocated by a Standards Action as modified by [\[RFC4020\]](#).

1. A complete template as specified in [Appendix A](#) has been posted for two weeks to the dnsex@ietf.org mailing list before the Expert Review decision.

Note that partially completed or draft templates may be posted directly by the applicant for comment and discussion, but the formal posting to start the two week period is made by the Expert.

2. The RR for which an RRTYPE code is being requested is either (a) a data TYPE that can be handled as an Unknown RR as described in [\[RFC3597\]](#) or (b) a Meta-TYPE whose processing is optional, i.e., it is safe to simply discard RRs with that Meta-TYPE in queries or responses.

Note that such RRs may include additional section processing, provided such processing is optional.

After the applicant submits their formal application using the template specified in [Appendix A](#), IANA appoints an Expert and the template is sent to the Expert. No more than two weeks after receiving the application the Expert shall explicitly approve or reject the application, informing IANA and the applicant. The Expert may consult with other technical expert as necessary. If the Expert does not approve the application within this period, it is considered rejected. IANA should report non-responsive Experts to the IESG.

IANA shall maintain a public archive of approved templates.

3.1.2. DNS RRTYPE Expert Guidelines

The Expert should normally reject any RRTYPE allocation request that meets one or more of the following criteria:

1. Was documented in a manner that was not sufficiently clear or complete to evaluate or implement. (Additional documentation can be provided during the public comment period or by the Expert.)
2. The proposed RRTYPE or RRTYPEs affect DNS processing and do not meet the criteria in point 2 of [Section 3.1.1](#) above.
3. Application use as documented makes incorrect assumptions about DNS protocol behavior, such as wild cards, CNAME, DNAME, etc.
4. An excessive number of RRTYPE values is being requested when the purpose could be met with a smaller number or with Private Use values.

3.1.3. Special Note on the OPT RR

The OPT (OPTion) RR (RRTYPE 41) and its IANA considerations are specified in [[RFC2671bis](#)]. Its primary purpose is to extend the effective field size of various DNS fields including RCODE, label type, OpCode, flag bits, and RDATA size. In particular, for resolvers and servers that recognize it, it extends the RCODE field from 4 to 12 bits.

3.1.4. The AFSDB RR Subtype Field

The AFSDB RR [[RFC1183](#)] is a CLASS-insensitive RR that has the same RDATA field structure as the MX RR [[RFC1035](#)], but the 16-bit unsigned integer field at the beginning of the RDATA is interpreted as a subtype as follows:

Decimal
Hexadecimal

0
0x0000 - Reserved; allocation requires a Standards Action.

0x0001 - Andrews File Service v3.0 Location Service [[RFC1183](#)].

2

0x0002 - DCE/NCA root cell directory node [[RFC1183](#)].

3 - 65,279

0x0003 - 0xFEFF - Allocation by IETF Review.

65,280 - 65,534

0xFF00 - 0xFFFE - Private Use.

65,535

0xFFFF - Reserved; allocation requires a Standards Action.

[3.2. RR CLASS IANA Considerations](#)

There are currently two subcategories of DNS CLASSES: normal, data-containing classes and QCLASSES that are only meaningful in queries or updates.

DNS CLASSES have been little used but constitute another dimension of the DNS distributed database. In particular, there is no necessary relationship between the name space or root servers for one data CLASS and those for another data CLASS. The same DNS NAME can have completely different meanings in different CLASSES. The label types are the same, and the null label is usable only as root in every CLASS. As global networking and DNS have evolved, the IN, or Internet, CLASS has dominated DNS use.

As yet, there has not been a requirement for "meta-CLASSES". That would be a CLASS to designate transient data associated with a particular DNS message, which might be usable in queries. However, it is possible that there might be a future requirement for one or more "meta-CLASSES".

CLASSES have mnemonics that must be completely disjoint from the mnemonics used for RRTYPES and that must match the following regular expression:

```
[A-Z][A-Z0-9\-]*[A-Z0-9]
```

The current CLASS assignments and considerations for future assignments are as follows:

Decimal
Hexadecimal

0
0x0000 - Reserved; assignment requires a Standards Action.

1
0x0001 - Internet (IN).

2
0x0002 - Available for assignment by IETF Review as a data CLASS.

3
0x0003 - Chaos (CH) [[Moon1981](#)].

4
0x0004 - Hesiod (HS) [[Dyer1987](#)].

5 - 127
0x0005 - 0x007F - Available for assignment by IETF Review for data CLASSES only.

128 - 253
0x0080 - 0x00FD - Available for assignment by IETF Review for QCLASSES and meta-CLASSES only.

254
0x00FE - QCLASS NONE [[RFC2136](#)].

255
0x00FF - QCLASS * (ANY) [[RFC1035](#)].

256 - 32,767
0x0100 - 0x7FFF - Assigned by IETF Review.

32,768 - 57,343
0x8000 - 0xDFFF - Assigned for data CLASSES only, based on Specification Required as defined in [[RFC5226](#)].

57,344 - 65,279
0xE000 - 0xFEFF - Assigned for QCLASSES and meta-CLASSES only, based on Specification Required as defined in [[RFC5226](#)].

65,280 - 65,534
0xFF00 - 0xFFFE - Private Use.

65,535
0xFFFF - Reserved; can only be assigned by a Standards Action.

[3.3.](#) Label Considerations

DNS NAMEs are sequences of labels [[RFC1035](#)].

[3.3.1.](#) Label Types

At the present time, there are two categories of label types: data labels and compression labels. Compression labels are pointers to data labels elsewhere within an RR or DNS message and are intended to shorten the wire encoding of NAMEs.

The two existing data label types are sometimes referred to as Text and Binary. Text labels can, in fact, include any octet value including zero-value octets, but many current uses involve only printing ASCII characters [[RFC20](#)]. For retrieval, Text labels are defined to treat ASCII upper and lower case letter codes as matching [[RFC4343](#)]. Binary labels are bit sequences [[RFC2673](#)]. The Binary label type is Historic [[RFC2671bis](#)].

[3.3.2.](#) Label Contents and Use

The last label in each NAME is "ROOT", which is the zero-length label. By definition, the null or ROOT label cannot be used for any other NAME purpose.

NAMEs are local to a CLASS. The Hesiod [[Dyer1987](#)] and Chaos [[Moon1981](#)] CLASSES are for essentially local use. The IN, or Internet, CLASS is thus the only DNS CLASS in global use on the Internet at this time.

A somewhat out-of-date description of name allocation in the IN Class is given in [[RFC1591](#)]. Some information on reserved top-level domain names is in [BCP 32](#) [[RFC2606](#)].

4. Security Considerations

This document addresses IANA considerations in the allocation of general DNS parameters, not security. See [[RFC4033](#)], [[RFC4034](#)], and [[RFC4035](#)] for secure DNS considerations.

5. IANA Considerations

This document consists entirely of DNS IANA Considerations.

IANA has established a process for accepting [Appendix A](#) templates and selecting an Expert from those appointed to review such template form applications. IANA archives and makes available all approved RRTYPE allocation templates. It is the duty of the applicant to post the formal application template to the dns-rrtype-applications@ietf.org mailing list, which IANA will monitor. The dnsext@ietf.org mailing list is for community discussion and comment. See [Section 3.1](#) and [Appendix A](#) for more details.

Appendix A: RRTYPE Allocation Template

DNS RRTYPE PARAMETER ALLOCATION TEMPLATE

When ready for formal consideration, this template is to be submitted to IANA for processing by emailing the template to `dns-rrtype-applications@ietf.org`.

A. Submission Date:

B. Submission Type:

New RRTYPE

Modification to existing RRTYPE

C. Contact Information for submitter (will be publicly posted):

Name:

Email Address:

International telephone number:

Other contact handles:

D. Motivation for the new RRTYPE application.

Please keep this part at a high level to inform the Expert and reviewers about uses of the RRTYPE. Most reviewers will be DNS experts that may have limited knowledge of your application space.

E. Description of the proposed RR type.

This description can be provided in-line in the template, as an attachment, or with a publicly available URL.

F. What existing RRTYPE or RRTYPES come closest to filling that need and why are they unsatisfactory?

G. What mnemonic is requested for the new RRTYPE (optional)?

Note: this can be left blank and the mnemonic decided after the template is accepted.

H. Does the requested RRTYPE make use of any existing IANA registry or require the creation of a new IANA sub-registry in DNS Parameters? If so, please indicate which registry is to be used or created. If a new sub-registry is needed, specify the allocation policy for it and its initial contents. Also include what the modification procedures will be.

I. Does the proposal require/expect any changes in DNS servers/resolvers that prevent the new type from being processed as an unknown RRTYPE (see [[RFC3597](#)])?

J. Comments:

Appendix B: Changes From [RFC 6195](#)

Drop description of changes from [RFC 5395](#) to [RFC 6195](#) since those changes have already happened and we don't need to do them again.

Cut back RRTYPE Expert review period to two weeks and eliminate the dnsex@ietf.org comment period.

Update references for revised versions.

A number of minor editorial and typos fixes.

Normative References

- [RFC1034] - Mockapetris, P., "Domain names - concepts and facilities", STD 13, [RFC 1034](#), November 1987.
- [RFC1035] - Mockapetris, P., "Domain names - implementation and specification", STD 13, [RFC 1035](#), November 1987.
- [RFC1996] - Vixie, P., "A Mechanism for Prompt Notification of Zone Changes (DNS NOTIFY)", [RFC 1996](#), August 1996.
- [RFC2136] - Vixie, P., Ed., Thomson, S., Rekhter, Y., and J. Bound, "Dynamic Updates in the Domain Name System (DNS UPDATE)", [RFC 2136](#), April 1997.
- [RFC2181] - Elz, R. and R. Bush, "Clarifications to the DNS Specification", [RFC 2181](#), July 1997.
- [RFC2845] - Vixie, P., Gudmundsson, O., Eastlake 3rd, D., and B. Wellington, "Secret Key Transaction Authentication for DNS (TSIG)", [RFC 2845](#), May 2000.
- [RFC2930] - Eastlake 3rd, D., "Secret Key Establishment for DNS (TKEY RR)", [RFC 2930](#), September 2000.
- [RFC3425] - Lawrence, D., "Obsoleting IQUERY", [RFC 3425](#), November 2002.
- [RFC3597] - Gustafsson, A., "Handling of Unknown DNS Resource Record (RR) Types", [RFC 3597](#), September 2003.
- [RFC4020] - Kompella, K. and A. Zinin, "Early IANA Allocation of Standards Track Code Points", [BCP 100](#), [RFC 4020](#), February 2005.
- [RFC4033] - Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "DNS Security Introduction and Requirements", [RFC 4033](#), March 2005.
- [RFC4034] - Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Resource Records for the DNS Security Extensions", [RFC 4034](#), March 2005.
- [RFC4035] - Arends, R., Austein, R., Larson, M., Massey, D., and S. Rose, "Protocol Modifications for the DNS Security Extensions", [RFC 4035](#), March 2005.
- [RFC4635] - Eastlake 3rd, D., "HMAC SHA (Hashed Message Authentication Code, Secure Hash Algorithm) TSIG Algorithm Identifiers", [RFC 4635](#), August 2006.

[RFC5226] - Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 5226](#), May 2008.

[RFC2671bis] - Damas, J., Graff, M., and Vixie, P., "Extension Mechanisms for DNS (EDNS0)", [draft-ietf-dnsext-rfc2671bis-edns0](#), work in progress.

Informative References

[Dyer1987] - Dyer, S., and F. Hsu, "Hesiod", Project Athena Technical Plan - Name Service, April 1987.

[Moon1981] - Moon, D., "Chaosnet", A.I. Memo 628, Massachusetts Institute of Technology Artificial Intelligence Laboratory, June 1981.

[RFC20] - Cerf, V., "ASCII format for network interchange", [RFC 20](#), October 1969.

[RFC1183] - Everhart, C., Mamakos, L., Ullmann, R., and P. Mockapetris, "New DNS RR Definitions", [RFC 1183](#), October 1990.

[RFC1591] - Postel, J., "Domain Name System Structure and Delegation", [RFC 1591](#), March 1994.

[RFC2606] - Eastlake 3rd, D. and A. Panitz, "Reserved Top Level DNS Names", [BCP 32](#), [RFC 2606](#), June 1999.

[RFC2673] - Crawford, M., "Binary Labels in the Domain Name System", [RFC 2673](#), August 1999.

[RFC2931] - Eastlake 3rd, D., "DNS Request and Transaction Signatures (SIG(0)s)", [RFC 2931](#), September 2000.

[RFC4343] - Eastlake 3rd, D., "Domain Name System (DNS) Case Insensitivity Clarification", [RFC 4343](#), January 2006.

[RFC6195] - Eastlake 3rd, D., "Domain Name System (DNS) IANA Considerations", [RFC 6195](#), March 2011.

Author's Address

Donald E. Eastlake 3rd
Huawei R&D USA
155 Beaver Street
Milford, MA 01757 USA

Telephone: +1-508-333-2270
email: d3e3e3@gmail.com

Copyright and IPR Provisions

Copyright (c) 2012 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License. The definitive version of an IETF Document is that published by, or under the auspices of, the IETF. Versions of IETF Documents that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of IETF Documents. The definitive version of these Legal Provisions is that published by, or under the auspices of, the IETF. Versions of these Legal Provisions that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of these Legal Provisions. For the avoidance of doubt, each Contributor to the IETF Standards Process licenses each Contribution that he or she makes as part of the IETF Standards Process to the IETF Trust pursuant to the provisions of [RFC 5378](#). No language to the contrary, or terms, conditions or rights that differ from or are inconsistent with the rights and licenses granted under [RFC 5378](#), shall have any effect and shall be null and void, whether published or posted by such Contributor, or included with or in such Contribution.

