

INTERNET-DRAFT
Intended status: Proposed Standard

Donald Eastlake
Yizhou Li
Huawei
Radia Perlman
Intel

Expires: March 15, 2014

September 16, 2013

TRILL: Interface Addresses APPsub-TLV
<[draft-eastlake-trill-ia-appsubtlv-01.txt](#)>

Abstract

This document specifies a TRILL (Transparent Interconnection of Lots of Links) IS-IS application sub-TLV that enables the reporting by a TRILL switch of sets of addresses such that all of the addresses in each set designate the same interface (port). For example, an EUI-48 MAC (Extended Unique Identifier 48-bit, Media Access Control) address, IPv4 address, and IPv6 address can be reported as all corresponding to the same interface. Such information could be use in some cases to synthesize responses to or by-pass the need for the Address Resolution Protocol (ARP), the IPv6 Neighbor Discovery (ND) protocol, or the flooding of unknown MAC addresses.

Status of This Memo

This Internet-Draft is submitted to IETF in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Distribution of this document is unlimited. Comments should be sent to the TRILL working group mailing list.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/1id-abstracts.html>. The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

Table of Contents

1. Introduction.....	3
1.1 Conventions Used in This Document.....	3
2. Format of the Interface Addresses APPsub-TLV.....	4
3. IA APPsub-TLV sub-sub-TLVs.....	8
3.1 AFN Size sub-sub-TLV.....	8
3.2 Fixed Address sub-sub-TLV.....	9
3.3 Data Label sub-sub-TLV.....	9
3.4 Topology sub-sub-TLV.....	10
4. Security Considerations.....	11
5. IANA Considerations.....	12
5.1 Additional AFN Number Allocation.....	12
5.2 IA APPsub-TLV Sub-Sub-TLVs SubRegistry.....	13
Acknowledgments.....	14
Appendix A: Examples.....	15
A.1 Simple Example.....	15
A.2 Complex Example.....	15
Normative References.....	18
Informational References.....	18
Authors' Addresses.....	20

1. Introduction

This document specifies a TRILL (Transparent Interconnection of Lots of Links) [[RFC6325](#)] IS-IS application sub-TLV (APPsub-TLV [[RFC6823](#)]) that enables the convenient representation of sets of addresses such that all of the addresses in each set designate the same interface (port). For example, an EUI-48 MAC (Extended Unique Identifier 48-bit, Media Access Control [[RFC5342bis](#)]) address, IPv4 address, and IPv6 address can be reported as all three designating the same interface. In addition, a Data Label (VLAN or Fine Grained Label (FGL [[RFCfgl](#)])) is specified for the interface along with the TRILL switch and, optional the TRILL switch port, from which the interface is reachable.

This APPsub-TLV appears inside the TRILL GENINFO TLV specified in [[ESADI](#)] but may also occur in other application contexts. Directory Assisted TRILL Edge services [[DirectoryFramework](#)] [[DirectoryScheme](#)] are expected to make use of this APPsub-TLV.

Although, in some IETF protocols, address field types are represented by Ethertype [[RFC5342bis](#)] or Hardware Type [[RFC5494](#)] only Address Family Number (AFN) is used in this APPsub-TLV to represent address field type.

1.1 Conventions Used in This Document

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

The terminology and acronyms of [[RFC6325](#)] are used herein along with the following additional acronyms and terms:

AFN: Address Family Number

APPsub-TLV: Application sub-TLV [[RFC6823](#)].

Data Label: VLAN or FGL.

FGL: Fine Grained Label [[RFCfgl](#)].

IA: Interface Addresses.

RBridge: An alternative name for a TRILL switch.

TRILL switch: A device the implements the TRILL protocol.

2. Format of the Interface Addresses APPsub-TLV

The Interface Addresses (IA) APPsub-TLV is used to advertise that a set of addresses indicate the same interface (port) within a Data Label (VLAN or FGL) and to associate that interface with the TRILL switch, and optionally the TRILL switch port, by which the interface is reachable. These addresses can be in different address families. For example, it can be used to declare that a particular interface with specified IPv4, IPv6, and EUI-48 MAC addresses in some particular Data Label is reachable from a particular TRILL switch.

The Template field indicates the exact format of each Address Set in an Interface Addresses APPsub-TLV. Certain well-known sets of addresses are represented by special values. Other sets of addresses are specified by a list of AFNs. The Template format that uses a list of AFNs provides an explicit pattern for the type and order of addresses in each Address Set in an IA APPsub-TLV.

A device or application making use of IA APPsub-TLV data is not required to make use of all IA data. For example, a device or application that was only interested in MAC and IPv6 addresses could ignore any IPv4 or other types of address information that was present.

[illegible]

+--+--+--+--+--+--+--+--+--+--+...

Figure 1. The Interface Addresses APPsub-TLV

- o Type: Interface Addresses TRILL APPsub-TLV type, set to TBD[#2 suggested] (IA-SUBTLV).
- o Length: Variable, minimum 6, maximum 250 when inside a TRILL GENINFO TLV [[ESADI](#)], maximum 255 in unconstrained contexts. If length is 5 or less or if the APPsub-TLV extends beyond an encompassing TRILL GENINFO TLV, the APPsub-TLV MUST be ignored.
- o Nickname: The nickname of the TRILL switch by which the address sets are reachable. If zero, the address sets are reachable from the TRILL switch originating the message containing the APPsub-TLV (for example, an [[ESADI](#)] message).
- o Flags: A byte of flags as follows:

```

  0 1 2 3 4 5 6 7
+---+---+---+---+
|D|L|   RESV   |
+---+---+---+---+

```

D: If D is one, the APPsub-TLV contains Push Directory information.

L: If L is one, the APPsub-TLV contains information learned locally by observing ingressed frames. (Both D and L can one in the same IA APPsub-TLV.)

RESV: Additional reserved flag bits that MUST be sent as zero and ignored on receipt.

- o Confidence: This 8-bit unsigned quantity in the range 0 to 254 indicates the confidence level in the addresses being transported [[RFC6325](#)]. A value of 255 is treated as if it was 254.
- o Addr Sets End: The unsigned offset of the byte, within the IA APPsub-TLV value part, of the last byte of the last Address Set. This will be the byte just before the first sub-sub-TLV if any sub-sub-TLVs are present (see [Section 3](#)). If this is equal to Size, there are no sub-sub-TLVs. If this is less than Size, the IA APPsub-TLV is corrupt and MUST be discarded.
- o Template: The initial byte of this field is the unsigned integer K. If K has a value from 1 to 32, it indicates that this initial byte is followed by a list of K AFNs (Address Family Numbers) that specify the exact structure and order of each Address Set occurring later in the APPsub-TLV. K can be 1, which is the minimum valid value. If K is zero, the APPsub-TLV is ignored. If K

is 33 to 254, it indicates that the exact structure of each

Address Set corresponds to a specific well known Template as described below.

If the Template uses explicit AFNs, it looks like the following.

```

+-+--+--+--+--+--+
|  K              | (1 byte)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  AFN 1          | (2 bytes)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  AFN 2          | (2 bytes)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  ...
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  AFN K          | (2 bytes)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

For K in the 33 to 254 range, some values indicate combinations of a specific number of 48-bit MAC addresses, IPv4 addresses, IPv6 addresses, and TRILL switch port IDs in that order. the value of K is

$$K = 32 + M + 2*v4 + 6*v6 + 30*P$$

where M is the number of 48-bit MAC addresses (limited to 1 or 2), v4 is the number of IPv4 addresses (limited to 0, 1, or 2) and v6 is the number of IPv6 addresses (limited to 0 through 4 inclusive), and P is the number of TRILL switch port IDs (limited to 0 or 1). That equation specifies values of K from 32 through 91. Values from 92 through 254 are available for assignment by Expert Review (see [Section 5](#)). 255 is reserved. If a Template K value of 255 or an unknown template value in the range 33 to 254 is received, the IA APPsub-TLV MUST be ignored.

- o AFN: A two-byte Address Family Number. The number of AFNs present is given in first byte of the Template field if that value is less than 33. There are no AFNs if it is in the range 33 through 255. This sequence specifies the structure of the Address Sets occurring later in the TLV. For example, if Template Size is 2 and the two AFNs present are the AFNs for EUI-48 and IPv4, in that order, then each Address set present will consist of a 6-byte MAC address followed by a 4-byte IPv4 address. If any AFNs are present that are unknown to the receiving IS and the length of the corresponding address is not provided by a sub-sub-TLV as specified below, the receiving IS will be unable to parse the Address Sets and MUST ignore the IA APPsub-TLV.
- o Address Set: Each address set in the APPsub-TLV consists of

exactly the same sequence of addresses of the types specified by the Template earlier in the APPsub-TLV. No alignment, other than

to a byte boundary, is guaranteed. The addresses in each Address Set are contiguous with no unused bytes between them and the Address Sets are contiguous with no unused bytes between successive Address Sets. The Address Sets must fit within the TLV. If the product of the size of an Address Set and the number of Address Sets is so large that this is not true, the IA APPsub-TLV is ignored.

- o sub-sub-TLVs: If the Address Sets indicated by Addr Sets End do not completely fill the Length of the APPsub-TLV, the remaining bytes are parsed as sub-sub-TLVs [[RFC5305](#)]. Any such sub-sub-TLVs that are not known to the receiving RBridge are ignored. Should this parsing not be possible, for example there is only one remaining byte or an apparent sub-sub-TLV extends beyond the end of the TLV, the containing IA APPsub-TLV is considered corrupt and is ignored. (Several sub-sub-TLV types are specified in [Section 3](#).)

Different IA APPsub-TLVs within the same or different LSPs or other data structures may have different Templates. The same AFN may occur more than once in a Template and the same address may occur in different address sets. For example, an EUI-48 MAC address interface might have three different IPv6 addresses. This could be represented by an IA APPsub-TLV whose Template specifically provided for one EUI-48 address and three IPv6 addresses, which might be an efficient format if there were multiple interfaces with that pattern. Alternatively, a Template with one EUI-48 and one IPv6 address could be used in an IA APPsub-TLV with three address sets each having the same EUI-48 address but different IPv6 addresses, which might be the most efficient format if only one interface had multiple IPv6 addresses and other interfaces had only one IPv6 address.

In order to be able to parse the Address Sets, a receiving RBridge must know at least the size of the address each AFN the Template specifies; however, the presence of the Addr Set End field means that the sub-sub-TLVs, if any, can always be located by a receiver. An RBridge can be assumed to know the size of the AFNs list in [Section 5](#). Should an RBridge wish to include an AFN that some receiving RBridge in the campus may not know, it SHOULD include an AFN-Size sub-sub-TLV as described below. If an IA APPsub-TLV is received with one or more AFNs in its template for which the receiving RBridge does not know the length and for which an AFN-Size sub-sub-TLV is not present, that IA APPsub-TLV MUST be ignored.

3. IA APPsub-TLV sub-sub-TLVs

IA APPsub-TLVs can have trailing sub-sub-TLVs [[RFC5305](#)] as specified below. These sub-sub-TLVs occur after the Address Sets and the amount of space available for sub-sub-TLVs is determined from the overall IA APPsub-TLV length and the value of the Addr Set End byte.

There is no ordering restriction on sub-sub-TLVs. Unless otherwise specified each sub-sub-TLV type can occur zero, one, or many times in an IA APPsub-TLV.

3.1 AFN Size sub-sub-TLV

Using this sub-TLV, the originating RBridge can specify the size of an address type. This is useful under two circumstances as follows:

1. One or more AFNs that are unknown to the receiving RBridge appears in the template. If an AFN Size sub-sub-TLV is present for each such AFN, then at least the IA APPsub-TLV can be parsed and possibly other addresses in each address set can still be used.
2. If an AFN occurs in the Template that represents a variable length address, this sub-sub-TLV gives its size for all occurrences in that IA APPsub-TLV. (It is believed that the addresses specified by all currently assigned AFNs are fixed length.)

```

+-+--+--+--+--+--+--+
| Type = AFNsz      |           (1 byte)
+-+--+--+--+--+--+--+
| Length            |           (1 byte)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| AFN Size Record(s)                                | (3 bytes)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

Where each AFN Size Record is structured as follows:

```

+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  AFN                                | (2 bytes)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|  AdrSize                            | (1 byte)
+-+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

- o Type: AFN-Size sub-sub-TLV type, set to 1 (AFNsz).
- o Length: 3*n where n is the number of AFN Size Records present. If n is not a multiple of 3, the sub-sub-TLV MUST be ignored.

- o AFN Size Record(s): Zero or more 3-byte records, each giving the

size of an address type identified by an AFN,

- o AFN: The AFN whose length is being specified by the AFN Size Record.
- o AdrSize: The length of the address specified by the AFN field as an unsigned integer byte.

An AFN Size sub-sub-TLV for any AFN known to the receiving RBridge is compared with the size known to the RBridge and if they differ, the IA APPsub-TLV is assumed to be corrupt and MUST be ignored.

3.2 Fixed Address sub-sub-TLV

There may be cases where, in an Interface Addresses APP-subTLV, the same address would appear across every address set in the APP-subTLV. To avoid wasted space, this sub-sub-TLV can be used to indicate such a fixed address. The address or addresses incorporated into the sets by this sub-sub-TLV are NOT mentioned in the IA APPsub-TLV Template.

```

+---+---+---+---+
|Type=FIXEDADR |           (1 byte)
+---+---+---+---+
| Length       |           (1 byte)
+---+---+---+---+
| AFN          |           (2 bytes)
+---+---+---+---+---+---+---+...
| Fixed Address |           (variable)
+---+---+---+---+---+---+---+...
```

- o Type: Data Label sub-sub-TLV type, set to 2 (FIXEDADR).
- o Length: variable, minimum 3. If Length is 2 or less, the sub-sub-TLV MUST be ignored.
- o AFN: Address Family Number of the Fixed Address.
- o Fixed Address: The address of the type indicated by the preceding AFN field that is considered to be part of every Address Set in the IA APPsub-TLV.

3.3 Data Label sub-sub-TLV

This sub-sub-TLV indicates the Data Label within which the interfaces listed in the IA APPsub-TLV are reachable. It is useful if the IA

APPsub-TLV occurs outside of the context of an [[ESADI](#)] or other type

of message specifying the Data Label or if it is desired to override that specification. Multiple occurrences of this sub-sub-TLV indicate that the interface is reachable in all of the Data Labels given.

```

+---+---+---+---+
|Type=DATALEN   |                (1 byte)
+---+---+---+---+
| Length        |                (1 byte)
+---+---+---+---+---+---+---+---+...
| Data Label    |                (variable)
+---+---+---+---+---+---+---+---+...

```

- o Type: Data Label sub-TLV type, set to 3 (LABEL).
- o Length: 2 or 3
- o Data Label: If length is 2, the bottom 12 bits of the Data Label are a VLAN ID and the top 4 bits are reserved (MUST be sent as zero and ignored on receipt). If the length is 3, the three Data Label bytes contain an FGL [[RFCfg1](#)].

3.4 Topology sub-sub-TLV

The presence of this sub-sub-TLV indicates that the interfaces given in the IA APPsub-TLV are reachable in the topology give. It is useful if the IA APPsub-TLV occurs outside of the context of an [[ESADI](#)] or other type of message specifying the topology or if it is desired to override that specification. If it occurs multiple times, then the Address Sets are in all of the topologies given.

```

+---+---+---+---+
|Type=DATALEN   |                (1 byte)
+---+---+---+---+
| Length        |                (1 byte)
+---+---+---+---+---+---+---+---+---+
| RESV |         Topology         | (2 bytes)
+---+---+---+---+---+---+---+---+---+

```

- o Type: Topology sub-TLV type, set to 4 (TOPOLOGY).
- o Length: 2.

RESV: Four reserved bits. MUST be sent as zero and ignored on receipt.

- o Topology: The 12-bit topology number [[RFC5120](#)].

4. Security Considerations

The integrity of address mapping information and the correctness of Data Labels (VLANs or FLGs [[RFCfg1](#)]) are very important. Forged, altered, or incorrect address mapping or Data Labeling can lead to delivery of packets to the incorrect party, violating security policy. However, this document merely describes a data format and does not provide any explicit mechanisms for securing that data, other than a few trivial consistency checks that might detect some corrupted data. Security on the wire, or in storage, for this data is to be providing by the transport or storage used. For example, when transported with [[ESADI](#)], [[ESADI](#)] security mechanisms can be used.

The address mapping data, if known to be complete and correct, can be used to detect some cases of forged packet source addresses [[DirectoryFramework](#)]. In particular, if a native frame is received by a TRILL switch that would otherwise accept it but authoritative data indicates the source address should not be reachable from the receiving TRILL switch, that frame should be discarded. The data format specified in this document may optionally include RBridge Port ID number so that this forged address filtering can be optionally applied with port granularity.

See [[RFC6325](#)] for general TRILL Security Considerations.

5. IANA Considerations

As discussed below, IANA will allocate some new AFN numbers and create the TRILL IS-APPsub-TLV sub-sub-TLV subregistry.

5.1 Additional AFN Number Allocation

IANA is requested to allocate four new AFN numbers as follows:

Number	Description	References
-----	-----	-----
TBD	OUI	[RFC5342bis]
TBD	MAC/24	This document.
TBD	MAC/40	This document.
TBD	IPv6/64	This document.
TBD	RBridge Port ID	[RFC6325]

The OUI AFN is provided so that MAC addresses can be abbreviated if they have the same upper 24 bits. In particular, if there is an OUI provided as a Fixed Address sub-sub-TLV (see [Section 5.2.2](#)) then, whenever a MAC/24 or MAC/40 address appears within an Address Set (as indicated by the Template), the OUI is used as the first 24 bits of the actual MAC address for the Address Set. An OUI provided by a Fixed Address sub-sub-TLV is ignored if the IA APPsub-TLV has no MAC/24 or MAC/40 in its template.

MAC/24 is a 24-bit suffix intended to be pre-fixed by an OUI as in the previous paragraph. In the absence of an OUI specified as a Fixed Address in the same APPsub-TLV, an Address Set containing an MAC/24 address cannot be used.

MAC/40 is a suffix as specified above except that it is 40-bit so the result of combining it with an OUI is a 64-bit MAC address.

IPv6/64 is an 8-byte quantity that is the first 64 bits of an IPv6 address. If present, there will normally be an EUI-48 or EUI-64 address in the address set to provide the lower 64 bits of the IPv6 address. For this purpose, an EUI-48 is expanded to 64 bits as described in [[RFC5342bis](#)].

Other AFNs can be found at <http://www.iana.org/assignments/address-family-numbers>

The following AFN values may be particularly useful for IA APPsub-TLVs:

Hex	Decimal	Description	References
-----	-----	-----	-----
0001	1	IPv4	
0002	2	IPv6	
4005	16,389	48-bit MAC	[RFC5342bis]
4006	16,390	64-bit MAC	[RFC5342bis]

5.2 IA APPsub-TLV Sub-Sub-TLVs SubRegistry

IANA is requested to establish a new subregistry for sub-sub-TLVs of the Interface Addresses APPsub-TLV with initial contents as shown below.

Name: Interface Addresses APPsub-TLV Sub-Sub-TLVs

Procedure: Expert Review

Reference: This document

Type	Description	Reference
----	-----	-----
0	Reserved	
1	AFN Size	This document
2	Fixed Address	This document
3	Data Label	This document
4	Topology	This document
5-254	Available	
255	Reserved	

Acknowledgments

The authors gratefully acknowledge the contributions and review by the following:

Linda Dunbar

The document was prepared in raw nroff. All macros used were defined within the source file.

Appendix A: Examples

Below are example IA APPsub-TLVs.

A.1 Simple Example

Below is an annotated IA APPsub-TLV carrying two simple pairs of EUI-48 MAC addresses and IPv4 addresses from a Push Directory [[DirectoryFramework](#)]. No sub-sub-TLVs are included.

```

0x02(TBD)      Type: Interface Addresses
26             Size: 26 (=0x1A)
0x1234         RBridge Nickname from which reachable
0b10000000     Flags: Push Directory data
0xE3          Confidence
26            Address Sets End: 26 (=0x1A)
36            Template: 36(=0x24) = 32 + 1(MAC48) + 2*1(IPv4)

```

Address Set One

```

0x00005E0053A9  48-bitMAC address
198.51.100.23   IPv4 address

```

Address Set Two

```

0x00005E00536B  48-bit MAC address
203.0.113.201   IPv4 address

```

Size includes 6 for the fixed fields though and including the one byte template, plus 2 times the Address Set size. Each Address Set is 10 bytes, 6 for the 48-bit MAC address plus 4 for the IPv4 address. So total size is $6 + 2*10 = 26$.

See [Section 2](#) for more information on Template.

A.2 Complex Example

Below is an annotated IA APPsub-TLV carrying three sets of addresses, each consisting of an EUI-48 MAC address, an IPv4 addresses, an IPv6 address, and an RBridge Port ID, all from a Push Directory [[DirectoryFramework](#)]. The IPv6 address for each address set is synthesized from the MAC address given in that set and the IPv6/64 64-bit prefix provided through a Fixed Address sub-sub-TLV. In addition, a sub-sub-TLV is included that provides an FGL which overrides whatever Data Label may be provided by the envelope (for example [[ESADI](#)]) within which this IA APPsub-TLV occurs.

0x02(TBD)	Type: Interface Addresses
59	Size: 59 (=0x3B)
0x4321	RBridge Nickname from which reachable
0b10000000	Flags: Push Directory data
0xD3	Confidence
42	Address Sets End: 42 (=0x2A)
65	Template: $65(0x41)=32+1(\text{MAC}48)+2*1(\text{IPv}4)+30*1(\text{P})$

Address Set One

0x00005E0053DE	48-bit MAC address
198.51.100.105	IPv4 address
0x1DE3	RBridge Port ID

Address Set Two

0x00005E0053E3	48-bit MAC address
203.0.113.89	IPv4 address
0x1DEE	RBridge Port ID

Address Set Three

0x00005E0053D3	48-bit MAC address
192.0.2.139	IPv4 address
0x01DE	RBridge Port ID

sub-sub-TLV One

0x03	Type: Data Label
0x03	Length: implies FGL
0xD3E3E3	Fine Grained Label

sub-sub-TLV Two

0x02	Type: Fixed Address
0x0A	Size: $0x0A = 10$
0xTBDx	AFN: IPv6/64
0x0x20010DB800000000	IPv6 Prefix: 2001:DB8::

See [Section 2](#) for more information on Template.

The Fixed Address sub-sub-TLV causes the IPv6/64 value given to be treated as if it occurred as a 4th entry inside each of the three Address Sets. When there is an IPv6/64 entry and a 48-bit MAC entry, the MAC value is expanded by inserting 0xFFFE immediately after the OUI and the resulting 64-bit value is used as the lower 64 bits of the resulting IPv6 address [[RFC5342bis](#)]. As a result, a receiving TRILL would treat the three Address Sets shown as if they had an IPv6 address in them as follows:

Address Set One

0x20010DB800000000000005EFFFFE0053DE IPv6 Address

Address Set Two

0x20010DB800000000000005EFFFFE0053E3 IPv6 Address

Address Set Three

0x20010DB800000000000005EFFFFE0053D3 IPv6 Address

As an alternative to the compact "well know value" Template encoding used in this example above, the less compact explicit AFN encoding could have been used. In that case, the IA APPsub-TLV would have started as follows:

0x02(TBD)	Type: Interface Addresses
65	Size: 65 (=0x41)
0x4321	RBridge Nickname from which reachable
0b10000000	Flags: Push Directory data
0xD3	Confidence
48	Address Sets End: 48 (=0x30)
0x3	Template: 3 AFNs
0x4005	AFN: 48-bit MAC
0x0001	AFN: IPv4
0xTBDz	AFN: RBridge Port ID

As a final point, since the 48-bit MAC addresses in these three Address Sets all have the same OUI (the IANA OUI [[RFC5342bis](#)]), it would have been possible to just have a MAC/24 value giving the lower 24 bits of the MAC in each Address Set. The OUI would then be supplied by a second Fixed Address sub-sub-TLV proving the OUI. With N Address Sets, this would have saved 3*N or 9 bytes in this case at the cost of 7 bytes (1 each for the type and length of the sub-sub-TLV, 2 for the OUI AFN number, and 3 for the OUI). So, even with just three Address Sets, there would be a small net saving. The savings would grow with a larger number of Address Sets.

Normative References

- [RFC2119] - Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997
- [RFC5120] - Przygienda, T., Shen, N., and N. Sheth, "M-ISIS: Multi Topology (MT) Routing in Intermediate System to Intermediate Systems (IS-ISs)", [RFC 5120](#), February 2008.
- [RFC5305] - Li, T. and H. Smit, "IS-IS Extensions for Traffic Engineering", [RFC 5305](#), October 2008.
- [RFC5342bis] - Eastlake 3rd, D., "IANA Considerations and IETF Protocol Usage for IEEE 802 Parameters", [BCP 141](#), [RFC 5342](#), September 2008.
- [RFC6325] - Perlman, R., Eastlake 3rd, D., Dutt, D., Gai, S., and A. Ghanwani, "Routing Bridges (RBridges): Base Protocol Specification", [RFC 6325](#), July 2011.
- [RFC6823] - Ginsberg, L., Previdi, S., and M. Shand, "Advertising Generic Information in IS-IS", [RFC 6823](#), December 2012.
- [RFCfgl] - D. Eastlake, M. Zhang, P. Agarwal, R. Perlman, D. Dutt, "TRILL: Fine-Grained Labeling", [draft-ietf-trill-fine-labeling-07.txt](#), in RFC Editor's queue.

Informational References

- [ARP reduction] - Shah, et. al., "ARP Broadcast Reduction for Large Data Centers", Oct 2010.
- [DirectoryFramework] - Dunbar, L., D. Eastlake, R. Perlman, I. Gashinsky, "TRILL Edge Directory Assistance Framework", [draft-ietf-trill-directory-framework-07.txt](#), in RFC Editor's queue.
- [DirectoryScheme] - Dunbar, L., D. Eastlake, R. Perlman, I. Gashinsky, Y. Li, "TRILL: Directory Assistance Mechanisms", [draft-dunbar-trill-scheme-for-directory-assist](#), work in progress.
- [ESADI] - Zhai, H., F. Hu, R. Perlman, D. Eastlake, O. Stokes, "TRILL (Transparent Interconnection of Lots of Links): The ESADI (End Station Address Distribution Information) Protocol", [draft-ietf-trill-esadi-03.txt](#), work in progress.
- [RFC5494] - Arkko, J. and C. Pignataro, "IANA Allocation Guidelines

for the Address Resolution Protocol (ARP)", [RFC 5494](#), April

D. Eastlake, et al

[Page 18]

INTERNET-DRAFT

TRILL: IA APPsub-TLV

2009.

Authors' Addresses

Donald Eastlake
Huawei Technologies
155 Beaver Street
Milford, MA 01757 USA

Phone: +1-508-333-2270
Email: d3e3e3@gmail.com

Yizhou Li
Huawei Technologies
101 Software Avenue,
Nanjing 210012 China

Phone: +86-25-56622310
Email: liyizhou@huawei.com

Radia Perlman
Intel Labs
2200 Mission College Blvd.
Santa Clara, CA 95054-1549 USA

Phone: +1-408-765-8080
Email: Radia@alum.mit.edu

Copyright, Disclaimer, and Additional IPR Provisions

Copyright (c) 2013 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License. The definitive version of an IETF Document is that published by, or under the auspices of, the IETF. Versions of IETF Documents that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of IETF Documents. The definitive version of these Legal Provisions is that published by, or under the auspices of, the IETF. Versions of these Legal Provisions that are published by third parties, including those that are translated into other languages, should not be considered to be definitive versions of these Legal Provisions. For the avoidance of doubt, each Contributor to the IETF Standards Process licenses each Contribution that he or she makes as part of the IETF Standards Process to the IETF Trust pursuant to the provisions of [RFC 5378](#). No language to the contrary, or terms, conditions or rights that differ from or are inconsistent with the rights and licenses granted under [RFC 5378](#), shall have any effect and shall be null and void, whether published or posted by such Contributor, or included with or in such Contribution.

