

Network Working Group
Internet-Draft
Intended status: Standards Track
Expires: 28 September 2022

K. Inamdar
Unaffiliated
S. Narayanan
D. Engi
G. Salgueiro
Cisco
March 2022

The 'sipTrunkingCapability' Link Relation Type
draft-engi-siptrunkingcapability-link-00

Abstract

This specification defines the 'sipTrunkingCapabilities' link relation type that may be used for the retrieval of capabilities and configuration requirements from Internet Telephony Service Providers (ITSPs). A Session Initiation Protocol (SIP) trunking capability set is defined to allow the transfer of technical requirements needed for seamless peering between SIP-based enterprise telephony networks and ITSPs where an exchange of parameters and configuration information is required.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 2 September 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document.

Internet-Draft

"sipTrunkingCapability" Link Type

March 2022

Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Revised BSD License text as described in Section 4.e of the [Trust Legal Provisions](#) and are provided without warranty as described in the Revised BSD License.

Table of Contents

1.	Introduction	2
2.	Terminology	2
3.	The 'sipTrunkingCapability' Link Relation Type	3
4.	Example Usage	3
5.	IANA Considerations	4
6.	Security Considerations	4
7.	Acknowledgements	4
8.	References	4
8.1.	Normative References	4
8.2.	Informative Reference	5
	Authors' Addresses	5

[1.](#) Introduction

[RFC 8288](#) [[RFC8288](#)] defined a way of indicating relationships between resources on the Web. This document specifies the 'sipTrunkingCapability' link relation type according to the rules of [RFC 8288](#) [[RFC8288](#)]. Links with this relationship type can be used to exchange capability information between potential peer devices. In the event that systems require additional parameters and configuration to negotiate communication, a well-known URI can be utilized to deliver information to potential peers including machine-readable instructions and parameters needed for peering.

The 'sipTrunkingCapability' link relation type may be used on web resources hosted by Internet Telephony Service Providers (ITSPs) to provide a structured and detailed capability set document. The capability set document encapsulates a set of characteristics of an ITSP, which when retrieved by enterprise telephony network devices allows for automated establishment of Session Initiation Protocol (SIP) trunking between the two telephony networks.

[2.](#) Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT",

"SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

[3.](#) The 'sipTrunkingCapability' Link Relation Type

A capability set document is hosted via web resources by the ITSP. The document describes the configuration parameters required to successfully establish SIP trunking between an enterprise and service provider SIP telephony network. The capability set document SHOULD be comprised of structured and machine-readable parameters that could be easily converted into configuration data to meet the communication requirements of the service provider.

[4.](#) Example Usage

This section provides an example of possible use of the 'sipTrunkingCapability' relation type. The need for an enterprise telephony network to obtain a capability set document from an Internet Telephony Service Provider (ITSP) is documented in Automatic Peering for SIP Trunks [[I-D.ietf-asap-sip-auto-peer](#)]. The 'sipTrunkingCapability' link relation type allows an enterprise telephony network to specifically request the capability set document from a web server hosted in the ITSP network.

The enterprise network device solicits the location of the capability document from the well-known URI hosted by the SIP service provider using the WebFinger protocol [[RFC7033](#)].

```
GET /.well-known/webfinger?  
    resource=http%3A%2F%2Fssp1.example.com  
    rel=sipTrunkingCapability  
HTTP/1.1  
Host: ssp1.example.com
```

The capability set location is returned to the source device referencing the URI that contains parameters for peering.

```
HTTP/1.1 200 OK
```

```
Access-Control-Allow-Origin: *
Content-Type: application/jrd+json
{
  "subject" : "http://ssp1.example.com",
  "links" :
  [
    {
      "rel" : "sipTrunkingCapability",
      "href" : "https://capserver.ssp1.com/capserver/capdoc.json"
    },
  ]
}
```

The ITSP may use an authentication framework such as OAuth2 to determine the identity of the enterprise telephony network and provide the appropriate capability set document.

[5.](#) IANA Considerations

IANA has registered the sipTrunkingCapability link relation under the "Link Relation Types" Registry, with a reference to this document, using the following template:

Relation Name: sipTrunkingCapability

Description: A capability document that defines parameters or configuration requirements for automated peering and communication channel negotiation of the Session Initiation Protocol (SIP).

Reference: RFCXXXX

[[NOTE TO RFC EDITOR: Please change XXXX to the number assigned to this specification, and remove this paragraph on publication.]]

[6.](#) Security Considerations

The 'sipTrunkingCapability' relation type is not known to introduce any new security issues not already discussed in [RFC 8288](#) [RFC8288] for generic use of web linking mechanisms. However, it is recommended to exercise caution when publishing potentially sensitive capability information over unencrypted or unauthenticated channels.

7. Acknowledgements

This document resulted from the discussions in the ASAP working group, especially the detailed and thoughtful comments of Cullen Jennings, Jonathan Rosenberg, Jon Peterson and Chris Wendt.

8. References

8.1. Normative References

- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC8288] Nottingham, M., "Web Linking", [RFC 8288](#), DOI 10.17487/RFC8288, October 2017, <<https://www.rfc-editor.org/info/rfc8288>>.

Inamdar, et al.

Expires 28 September 2022

[Page 4]

Internet-Draft

"sipTrunkingCapability" Link Type

March 2022

8.2. Informative Reference

- [I-D.ietf-asap-sip-auto-peer]
Inamdar, K., Narayanan, S., and C. Jennings, "Automatic Peering for SIP Trunks", October 2021, <<https://datatracker.ietf.org/doc/html/draft-ietf-asap-sip-auto-peer-04>>.
- [RFC7033] Jones, P., Salgueiro, G., Jones, M., and J. Smarr, "WebFinger", [RFC 7033](#), DOI 10.17487/RFC7033, September 2013, <<https://www.rfc-editor.org/info/rfc7033>>.

Authors' Addresses

Kaustubh Inamdar
Unaffiliated
Email: kaustubh.ietf@gmail.com

Sreekanth Narayanan
Cisco
Email: sreenara@cisco.com

Derek Engi
Cisco
Ann Arbor, MI
US
Phone: +1 919 392 7966
Email: deengi@cisco.com

Gonzalo Salgueiro
Cisco
7200-12 Kit Creek Rd.
Research Triangle Park, NC 27709
US
Phone: +1 919 392 3266
Email: gsalguei@cisco.com