

LISP Working Group
Internet-Draft
Intended status: Experimental
Expires: January 7, 2016

V. Ermagan
Cisco Systems
A. Rodriguez-Natal
F. Coras
Technical University of Catalonia
C. Moberg
Cisco Systems
A. Cabellos-Aparicio
Technical University of Catalonia
F. Maino
Cisco Systems
July 6, 2015

LISP Configuration YANG Model
draft-ermagan-lisp-yang-01

Abstract

This document describes a YANG data model to use with the Locator/ID Separation Protocol (LISP).

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 7, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents

carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	2
2. LISP Module	3
2.1. Module Structure	3
2.2. Module Definition	3
3. LISP-ITR Module	9
3.1. Module Structure	9
3.2. Module Definition	22
4. LISP ETR Module	26
4.1. Module Structure	26
4.2. Module Definition	30
5. LISP Map Server Module	32
5.1. Module Structure	33
5.2. Module Definition	43
6. LISP Map Resolver Module	47
6.1. Module Structure	47
6.2. Module Definition	48
7. LISP Proxy ITR Module	49
7.1. Module Structure	50
7.2. Module Definition	59
8. LISP Proxy ETR Module	62
8.1. Module Structure	62
8.2. Module Definition	64
9. LISP Address Types	66
9.1. Module Definition	66
10. Acknowledgments	78
11. IANA Considerations	78
12. Security Considerations	78
13. Normative References	78
Authors' Addresses	79

[1. Introduction](#)

The Locator/ID Separation Protocol (LISP) defines several network elements subject to be configured. This document presents the YANG data models required for basic configuration of all major LISP [RFC6830]elements. The models also capture some essential operational data elements as well.

Ermagan, et al.

Expires January 7, 2016

[Page 2]

2. LISP Module

This module is the base LISP module that is augmented in multiple models to represent various LISP device roles.

2.1. Module Structure

```
module: ietf-lisp
  +-rw lisp
  |  +-rw devices
  |    +-rw device* [type id]
  |      +-rw type      device-ref
  |      +-rw id       string
  |      +-rw enabled? boolean
  +-ro lisp-state
    +-ro devices
      +-ro device* [type id]
        +-ro type      device-ref
        +-ro id       string
```

2.2. Module Definition

```
module ietf-lisp {
  namespace "urn:ietf:params:xml:ns:yang:ietf-lisp";
  prefix lisp;
  import ietf-interfaces {
    prefix if;
  }
  import lisp-address-types {
    prefix lcaf;
  }
  organization
    "IETF LISP (Locator/ID Separation Protocol) Working Group";
  contact
    "lisp@ietf.org";
  description
    "This YANG module defines the generic configuration
     and operational data for LISP. The module can be extended by
     vendors to define vendor-specific LISP configuration
     parameters and policies."
```

Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions

Ermagan, et al.

Expires January 7, 2016

[Page 3]

Relating to IETF Documents
(<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see
the RFC itself for full legal notices.

";

```
revision 2014-12-19 {
    description
        "Initial revision.";
    reference
        "https://tools.ietf.org/html/rfc6830";
}
identity lisp-device {
    description
        "LISP network device.";
}
typedef device-ref {
    type identityref {
        base lisp-device;
    }
    description
        "LISP device reference";
}
typedef map-reply-action {
    type enumeration {
        enum no-action {
            value 0;
            description
                "Mapping is kept alive and no encapsulation occurs.";
        }
        enum natively-forward {
            value 1;
            description
                "Matching packets are not encapsulated or dropped but
                 natively forwarded.";
        }
        enum send-map-request {
            value 2;
            description
                "Matching packets invoke Map-Requests.";
        }
        enum drop {
            value 3;
            description
                "Matching packets are dropped.";
        }
    }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 4]

```
description
  "Defines the lisp map-cache ACT type";
reference "https://tools.ietf.org/html/rfc6830#section-6.1.4";
}
typedef eid-id {
  type string;
  description
    "Type encoding of lisp-addresses to be generally used in EID
     keyed lists.";
}
typedef auth-key-type {
  type enumeration {
    enum none {
      value 0;
      description
        "No authentication.";
    }
    enum hmac-sha-1-96 {
      value 1;
      description
        "HMAC-SHA-1-96 (RFC2404) authentication is used.";
    }
    enum hmac-sha-256-128 {
      value 2;
      description
        "HMAC-SHA-256-128 (RFC4868) authentication is used.";
    }
  }
  description
    "Enumeration of the authentication mechanisms supported by
     LISP.";
  reference
    "https://tools.ietf.org/html/rfc6830#section-6.1.6";
}
grouping locators {
  description
    "Group that defines a list of LISP locators.";
  list rloc {
    key "id";
    description
      "List of routing locators";
    leaf id {
      type string;
      description
        "Locator id";
    }
    // FC need to be sure we don't use interface-name in itr
    // cached mappings
  }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 5]

```
choice address-type {
    description
        "The address type of the locator";
    case interface-name {
        leaf interface {
            type if:interface-state-ref;
            description
                "The name of the interface supporting the locator.";
        }
    }
    case address {
        container locator-address {
            uses lcaf:lisp-address;
            description
                "The locator address provided in LISP canonincal
                 address format.";
        }
    }
    leaf priority {
        type uint8;
        description
            "Locator priority.";
    }
    leaf weight {
        type uint8;
        description
            "Locator weight.";
    }
    leaf multicast-priority {
        type uint8;
        description
            "Locator's multicast priority";
    }
    leaf multicast-weight {
        type uint8;
        description
            "Locator's multicast weight";
    }
}
grouping mappings {
    description
        "Group that defines a list of LISP mappings.";
    list mapping {
        key "id";
        description
            "List of EID to RLOCs mappings.";
```

Ermagan, et al.

Expires January 7, 2016

[Page 6]

```
leaf id {
    type eid-id;
    description
        "Id that uniquely identifies a mapping.";
}
container eid {
    uses lcaf:lisp-address;
    description
        "End-host Identifier (EID) to be mapped to a list of
        locators";
}
leaf ttl {
    type uint32;
    description
        "Mapping validity period.";
}
leaf authoritative {
    type bits {
        bit A {
            description
                "Authoritative bit.";
        }
    }
    description
        "Bit that indicates if mapping comes from an
        authoritative source.";
}
choice locator-list {
    case negative-mapping {
        leaf map-reply-action {
            type map-reply-action;
            description
                "Forwarding action for a negative mapping.";
        }
    }
    case positive-mapping {
        container rlocs {
            uses locators;
            description
                "List of locators for a positive mapping.";
        }
    }
    default "positive-mapping";
    description
        "Choice of locator list based on type of mapping.";
}
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 7]

```
/* Configuration Data */
container lisp {
    description
        "Configuration parameters for LISP subsystem.";
    container devices {
        description
            "Configuration of LISP devices.";
        list device {
            key "type id";
            description
                "Each entry contains configuration of a lisp-device.";
            leaf type {
                type device-ref;
                description
                    "The type of LISP device - identity derived from the
                     'lisp-device' base identity.";
            }
            leaf id {
                type string;
                description
                    "Arbitrary device name.";
            }
            leaf enabled {
                type boolean;
                default "true";
                description
                    "Enable/disable the lisp-device.";
            }
        }
    }
}

/* Operational state data */
container lisp-state {
    config false;
    description
        "Operational state of the LISP subsystem.";
    container devices {
        description
            "Operational state of lisp-devices.";
        list device {
            key "type id";
            description
                "Each entry contains operational data of a lisp-device.";
            leaf type {
                type device-ref;
                description
                    "Type of LISP device.";
            }
        }
    }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 8]

```

    }
    leaf id {
      type string;
      description
        "Name of LISP device.";
    }
  }
}

}

```

[3.](#) LISP-ITR Module

This module captures the configuration data model of a LISP ITR. The model also captures some operational data elements.

[3.1.](#) Module Structure

```

module: lisp-itr
augment /lisp:lisp/devices/lisp:device:
  +-rw itr-cfg!
  +-rw rloc-probing!
    | +-rw interval?          uint16
    | +-rw retries?           uint8
    | +-rw retries-interval? uint16
  +-rw itr-rlocs
    | +-rw itr-rloc* [id]
    |   +-rw id              string
    |   +-rw address
    |     +-rw afi            lisp-address-family-ref
    |     +-rw instance-id?    instance-id-type
    |     +-rw (address)?
    |       +-:(ipv4)
    |         | +-rw ipv4?      inet:ipv4-address
    |       +-:(ipv6)
    |         | +-rw ipv6?      inet:ipv6-address
    |       +-:(mac)
    |         | +-rw mac?       yang:mac-address
    |       +-:(distinguished-name)
    |         | +-rw distinguished-name?  distinguished-name
    |       +-:(lcaf)
    |         +-rw lcaf
    |           +-rw lcaf-type      lcaf-ref
    |           +-rw (address)?
    |             +-:(null-address)
    |               | +-rw null-address
    |               |   +-rw address?  empty

```

Ermagan, et al.

Expires January 7, 2016

[Page 9]

```
+--:(afi-list)
|   +-rw afi-list
|     +-rw address-list*    simple-address
+--:(instance-id)
|   +-rw instance-id
|     +-rw instance-id?    instance-id-type
|     +-rw mask-length?   uint8
|     +-rw address?       simple-address
+--:(as-number)
|   +-rw as-number
|     +-rw as?            inet:as-number
|     +-rw address?      simple-address
+--:(application-data)
|   +-rw application-data
|     +-rw address?      simple-address
|     +-rw protocol?    uint8
|     +-rw ip-tos?      int32
|     +-rw local-port-low?  inet:port-number
|     +-rw local-port-high?  inet:port-number
|     +-rw remote-port-low?  inet:port-number
|     +-rw remote-port-high?  inet:port-number
+--:(geo-coordinates)
|   +-rw geo-coordinates
|     +-rw latitude?      bits
|     +-rw latitude-degrees?  uint8
|     +-rw latitude-minutes?  uint8
|     +-rw latitude-seconds?  uint8
|     +-rw longitude?      bits
|     +-rw longitude-degrees?  uint16
|     +-rw longitude-minutes?  uint8
|     +-rw longitude-seconds?  uint8
|     +-rw altitude?       int32
|     +-rw address?       simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|     +-rw ms-udp-port?   uint16
|     +-rw etr-udp-port?   uint16
|     +-rw global-etr-rloc?  simple-address
|     +-rw ms-rloc?       simple-address
|     +-rw private-etr-rloc?  simple-address
|     +-rw rtr-rlocs*     simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|     +-rw hop* [address]
|       +-rw address      simple-address
|       +-rw lrs-bits?    bits
+--:(sourc-dest-key)
|   +-rw sourc-dest-key
```

Ermagan, et al.

Expires January 7, 2016

[Page 10]

```
|          +-+rw source?    inet:ip-prefix
|          +-+rw dest?      inet:ip-prefix
+-+rw local-eids
|  +-+rw local-eid* [id]
|    +-+rw id            lisp:eid-id
|    +-+rw eid-address
|      +-+rw afi           lisp-address-family-ref
|      +-+rw instance-id?   instance-id-type
|      +-+rw (address)?
|        +-:(ipv4)
|          +-+rw ipv4?        inet:ipv4-address
|        +-:(ipv6)
|          +-+rw ipv6?        inet:ipv6-address
|        +-:(mac)
|          +-+rw mac?         yang:mac-address
|        +-:(distinguished-name)
|          +-+rw distinguished-name?  distinguished-name
|        +-:(lcaf)
|          +-+rw lcaf
|            +-+rw lcaf-type       lcaf-ref
|            +-+rw (address)?
|              +-:(null-address)
|                +-+rw null-address
|                +-+rw address?    empty
|              +-:(afi-list)
|                +-+rw afi-list
|                  +-+rw address-list*  simple-address
|              +-:(instance-id)
|                +-+rw instance-id
|                  +-+rw instance-id?  instance-id-type
|                  +-+rw mask-length? uint8
|                  +-+rw address?    simple-address
|              +-:(as-number)
|                +-+rw as-number
|                  +-+rw as?          inet:as-number
|                  +-+rw address?    simple-address
|              +-:(application-data)
|                +-+rw application-data
|                  +-+rw address?    simple-address
|                  +-+rw protocol?   uint8
|                  +-+rw ip-tos?     int32
|                  +-+rw local-port-low?  inet:port-number
|                  +-+rw local-port-high?  inet:port-number
|                  +-+rw remote-port-low?  inet:port-number
|                  +-+rw remote-port-high?  inet:port-number
|              +-:(geo-coordinates)
|                +-+rw geo-coordinates
|                  +-+rw latitude?    bits
```

Ermagan, et al.

Expires January 7, 2016

[Page 11]

Ermagan, et al.

Expires January 7, 2016

[Page 12]

```
+--:(afi-list)
|   +-rw afi-list
|     +-rw address-list*    simple-address
+--:(instance-id)
|   +-rw instance-id
|     +-rw instance-id?    instance-id-type
|     +-rw mask-length?   uint8
|     +-rw address?       simple-address
+--:(as-number)
|   +-rw as-number
|     +-rw as?            inet:as-number
|     +-rw address?      simple-address
+--:(application-data)
|   +-rw application-data
|     +-rw address?      simple-address
|     +-rw protocol?    uint8
|     +-rw ip-tos?      int32
|     +-rw local-port-low?  inet:port-number
|     +-rw local-port-high?  inet:port-number
|     +-rw remote-port-low?  inet:port-number
|     +-rw remote-port-high?  inet:port-number
+--:(geo-coordinates)
|   +-rw geo-coordinates
|     +-rw latitude?      bits
|     +-rw latitude-degrees?  uint8
|     +-rw latitude-minutes?  uint8
|     +-rw latitude-seconds?  uint8
|     +-rw longitude?      bits
|     +-rw longitude-degrees?  uint16
|     +-rw longitude-minutes?  uint8
|     +-rw longitude-seconds?  uint8
|     +-rw altitude?       int32
|     +-rw address?       simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|     +-rw ms-udp-port?   uint16
|     +-rw etr-udp-port?   uint16
|     +-rw global-etr-rloc?  simple-address
|     +-rw ms-rloc?       simple-address
|     +-rw private-etr-rloc?  simple-address
|     +-rw rtr-rlocs*     simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|     +-rw hop* [address]
|       +-rw address      simple-address
|       +-rw lrs-bits?    bits
+--:(sourc-dest-key)
|   +-rw sourc-dest-key
```

Ermagan, et al.

Expires January 7, 2016

[Page 13]

```
|      |          +-+rw source?    inet:ip-prefix
|      |          +-+rw dest?     inet:ip-prefix
|      +-+rw map-resolver-address*  inet:ip-address
+-+rw proxy-etr
|  +-+rw proxy-etr* [id]
|  +-+rw id                  lisp:eid-id
|  +-+rw eid-address
|    |  +-+rw afi           lisp:address-family-ref
|    |  +-+rw instance-id?   instance-id-type
|    |  +-+rw (address)?
|    |    +-:(ipv4)
|    |      |  +-+rw ipv4?       inet:ipv4-address
|    |    +-:(ipv6)
|    |      |  +-+rw ipv6?       inet:ipv6-address
|    |    +-:(mac)
|    |      |  +-+rw mac?        yang:mac-address
|    |    +-:(distinguished-name)
|    |      |  +-+rw distinguished-name?  distinguished-name
|    |    +-:(lcaf)
|    |      +-+rw lcaf
|    |        +-+rw lcaf-type      lcaf-ref
|    |        +-+rw (address)?
|    |          +-:(null-address)
|    |            |  +-+rw null-address
|    |            |  +-+rw address?   empty
|    |          +-:(afi-list)
|    |            |  +-+rw afi-list
|    |            |  +-+rw address-list*  simple-address
|    |          +-:(instance-id)
|    |            |  +-+rw instance-id
|    |            |  +-+rw instance-id?  instance-id-type
|    |            |  +-+rw mask-length?  uint8
|    |            |  +-+rw address?    simple-address
|    |          +-:(as-number )
|    |            |  +-+rw as-number
|    |            |  +-+rw as?         inet:as-number
|    |            |  +-+rw address?    simple-address
|    |          +-:(application-data)
|    |            |  +-+rw application-data
|    |            |  +-+rw address?    simple-address
|    |            |  +-+rw protocol?   uint8
|    |            |  +-+rw ip-tos?    int32
|    |            |  +-+rw local-port-low?  inet:port-number
|    |            |  +-+rw local-port-high?  inet:port-number
|    |            |  +-+rw remote-port-low?  inet:port-number
|    |            |  +-+rw remote-port-high?  inet:port-number
|    |          +-:(geo-coordinates)
|    |            |  +-+rw geo-coordinates
```



```
|           |   +-+rw latitude?          bits
|           |   +-+rw latitude-degrees? uint8
|           |   +-+rw latitude-minutes? uint8
|           |   +-+rw latitude-seconds? uint8
|           |   +-+rw longitude?        bits
|           |   +-+rw longitude-degrees? uint16
|           |   +-+rw longitude-minutes? uint8
|           |   +-+rw longitude-seconds? uint8
|           |   +-+rw altitude?         int32
|           |   +-+rw address?          simple-address
|           +-+:nat-traversal
|               +-+rw nat-traversal
|                   +-+rw ms-udp-port?    uint16
|                   +-+rw etr-udp-port?  uint16
|                   +-+rw global-etr-rloc? simple-address
|                   +-+rw ms-rloc?      simple-address
|                   +-+rw private-etr-rloc? simple-address
|                   +-+rw rtr-rlocs*    simple-address
|           +-+:explicit-locator-path
|               +-+rw explicit-locator-path
|                   +-+rw hop* [address]
|                       +-+rw address      simple-address
|                       +-+rw lrs-bits?   bits
|           +-+:sourc-dest-key
|               +-+rw sourc-dest-key
|                   +-+rw source?     inet:ip-prefix
|                   +-+rw dest?       inet:ip-prefix
|           +-+rw proxy-etr-address*  inet:ip-address
+-+rw static-mappings
    +-+rw mapping* [id]
        +-+rw id                  eid-id
        +-+rw eid
            |   +-+rw afi          lisp-address-family-ref
            |   +-+rw instance-id?  instance-id-type
            |   +-+rw (address)?
                +-+:ipv4
                    |   +-+rw ipv4?      inet:ipv4-address
                +-+:ipv6
                    |   +-+rw ipv6?      inet:ipv6-address
                +-+:mac
                    |   +-+rw mac?      yang:mac-address
                +-+:distinguished-name
                    |   +-+rw distinguished-name? distinguished-name
                +-+:lcaf
                    +-+rw lcaf
                        +-+rw lcaf-type      lcaf-ref
                        +-+rw (address)?
                            +-+:null-address
```

Ermagan, et al.

Expires January 7, 2016

[Page 15]

```
|   +-rw null-address
|     +-rw address?    empty
+--:(afi-list)
|   +-rw afi-list
|     +-rw address-list*  simple-address
+--:(instance-id)
|   +-rw instance-id
|     +-rw instance-id?  instance-id-type
|     +-rw mask-length?  uint8
|     +-rw address?      simple-address
+--:(as-number)
|   +-rw as-number
|     +-rw as?          inet:as-number
|     +-rw address?      simple-address
+--:(application-data)
|   +-rw application-data
|     +-rw address?      simple-address
|     +-rw protocol?    uint8
|     +-rw ip-tos?       int32
|     +-rw local-port-low?  inet:port-number
|     +-rw local-port-high?  inet:port-number
|     +-rw remote-port-low?  inet:port-number
|     +-rw remote-port-high?  inet:port-number
+--:(geo-coordinates)
|   +-rw geo-coordinates
|     +-rw latitude?      bits
|     +-rw latitude-degrees?  uint8
|     +-rw latitude-minutes?  uint8
|     +-rw latitude-seconds?  uint8
|     +-rw longitude?      bits
|     +-rw longitude-degrees?  uint16
|     +-rw longitude-minutes?  uint8
|     +-rw longitude-seconds?  uint8
|     +-rw altitude?       int32
|     +-rw address?        simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|     +-rw ms-udp-port?    uint16
|     +-rw etr-udp-port?    uint16
|     +-rw global-etr-rloc?  simple-address
|     +-rw ms-rloc?        simple-address
|     +-rw private-etr-rloc?  simple-address
|     +-rw rtr-rlocs*      simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|     +-rw hop* [address]
|       +-rw address      simple-address
|       +-rw lrs-bits?    bits
```

Ermagan, et al.

Expires January 7, 2016

[Page 16]

```

|           +-:(sourc-dest-key)
|           +-rw sourc-dest-key
|               +-rw source?    inet:ip-prefix
|               +-rw dest?     inet:ip-prefix
+-rw ttl?          uint32
+-rw authoritative?   bits
+-rw (locator-list)?
|           +-:(negative-mapping)
|           | +-rw map-reply-action?  map-reply-action
|           +-:(positive-mapping)
|               +-rw rlocs
|                   +-rw rloc* [id]
|                       +-rw id                  string
|                       +-rw (address-type)?
|                           +-:(interface-name)
|                               | +-rw interface?      if:interface-state-
ref
|           +-:(address)
|               +-rw locator-address
|                   +-rw afi             lisp-address-
family-ref
|           +-rw instance-id?      instance-id-type
|           +-rw (address)?
|               +-:(ipv4)
|                   | +-rw ipv4?        inet:ipv4-
address
|               +-:(ipv6)
|                   | +-rw ipv6?        inet:ipv6-
address
|               +-:(mac)
|                   | +-rw mac?        yang:mac-
address
|               +-:(distinguished-name)
|                   | +-rw distinguished-name?
distinguished-name
|           +-:(lcaf)
|               +-rw lcaf
|                   +-rw lcaf-type       lcaf-
ref
|               +-rw (address)?
|                   +-:(null-address)
|                       | +-rw null-address
|                           | +-rw address?    empty
|               +-:(afi-list)
|                   | +-rw afi-list
|                       | +-rw address-list*
simple-address
|               +-:(instance-id)

```

```
|           |   +-rw instance-id
|           |   +-rw instance-id?
instance-id-type
|           |   +-rw mask-length?    uint8
|           |   +-rw address?      simple-
address
|           |   +-:(as-number)
|           |   +-rw as-number
|           |   +-rw as?          inet:as-
number
|           |   +-rw address?      simple-
address
```

		+--:(application-data)
		+-rw application-data
		+-rw address?
simple-address		
		+-rw protocol?
uint8		
		+-rw ip-tos?
int32		
		+-rw local-port-low?
inet:port-number		
		+-rw local-port-high?
inet:port-number		
		+-rw remote-port-low?
inet:port-number		
		+-rw remote-port-high?
inet:port-number		
		+--:(geo-coordinates)
		+-rw geo-coordinates
		+-rw latitude?
bits		
		+-rw latitude-degrees?
uint8		
		+-rw latitude-minutes?
uint8		
		+-rw latitude-seconds?
uint8		
		+-rw longitude?
bits		
		+-rw longitude-degrees?
uint16		
		+-rw longitude-minutes?
uint8		
		+-rw longitude-seconds?
uint8		
		+-rw altitude?
int32		
		+-rw address?
simple-address		
		+--:(nat-traversal)
		+-rw nat-traversal
		+-rw ms-udp-port?
uint16		
		+-rw etr-udp-port?
uint16		
		+-rw global-etr-rloc?
simple-address		
		+-rw ms-rloc?
simple-address		

```

simple-address          |           +-rw private-etr-rloc?
simple-address          |           +-rw rtr-rlocs*
simple-address          |           +---(explicit-locator-path)
simple-address          |           |   +-rw explicit-locator-path
simple-address          |           |   +-rw hop* [address]
simple-address          |           |   +-rw address      simple-
address                |           |           +-rw lrs-bits?    bits
prefix                  |           |           +---(sourc-dest-key)
prefix                  |           |           +-rw sourc-dest-key
prefix                  |           |           +-rw source?     inet:ip-
prefix                  |           |           +-rw dest?       inet:ip-
prefix                  |           +-rw priority?    uint8
prefix                  |           +-rw weight?      uint8
prefix                  |           +-rw multicast-priority? uint8
prefix                  |           +-rw multicast-weight? uint8
augment /lisp:lisp-state/lisp:devices/lisp:device:
  +-ro itr-state
  +-ro learned-mappings
    +-ro mapping* [id]
      +-ro id          eid-id
      +-ro eid

```

```
|   +-+ro afi                  lisp-address-family-ref
|   +-+ro instance-id?         instance-id-type
|   +-+ro (address)?
|     +-+:ipv4
|       |   +-+ro ipv4?          inet:ipv4-address
|     +-+:ipv6
|       |   +-+ro ipv6?          inet:ipv6-address
|     +-+:mac
|       |   +-+ro mac?           yang:mac-address
|     +-:(distinguished-name)
|       |   +-+ro distinguished-name?  distinguished-name
|     +-:(lcaf)
|       +-+ro lcaf
|         +-+ro lcaf-type        lcaf-ref
|         +-+ro (address)?
|           +-:(null-address)
|             |   +-+ro null-address
|             |   +-+ro address?    empty
|           +-:(afi-list)
|             |   +-+ro afi-list
|               +-+ro address-list*  simple-address
|           +-:(instance-id)
|             |   +-+ro instance-id
|               +-+ro instance-id?  instance-id-type
|               +-+ro mask-length?  uint8
|               +-+ro address?      simple-address
|           +-:(as-number)
|             |   +-+ro as-number
|               +-+ro as?           inet:as-number
|               +-+ro address?      simple-address
|           +-:(application-data)
|             |   +-+ro application-data
|               +-+ro address?      simple-address
|               +-+ro protocol?      uint8
|               +-+ro ip-tos?        int32
|               +-+ro local-port-low?  inet:port-number
|               +-+ro local-port-high?  inet:port-number
|               +-+ro remote-port-low?  inet:port-number
|               +-+ro remote-port-high?  inet:port-number
|           +-:(geo-coordinates)
|             |   +-+ro geo-coordinates
|               +-+ro latitude?       bits
|               +-+ro latitude-degrees?  uint8
|               +-+ro latitude-minutes?  uint8
|               +-+ro latitude-seconds?  uint8
|               +-+ro longitude?       bits
|               +-+ro longitude-degrees?  uint16
|               +-+ro longitude-minutes?  uint8
```



```

|   |   +-+ro longitude-seconds?    uint8
|   |   +-+ro altitude?          int32
|   |   +-+ro address?           simple-address
|   +-:(nat-traversal)
|   |   +-+ro nat-traversal
|   |   +-+ro ms-udp-port?      uint16
|   |   +-+ro etr-udp-port?      uint16
|   |   +-+ro global-etr-rloc?   simple-address
|   |   +-+ro ms-rloc?           simple-address
|   |   +-+ro private-etr-rloc?  simple-address
|   |   +-+ro rtr-rlocs*        simple-address
|   +-:(explicit-locator-path)
|   |   +-+ro explicit-locator-path
|   |   +-+ro hop* [address]
|   |   |   +-+ro address      simple-address
|   |   +-+ro lrs-bits?         bits
|   +-:(sourc-dest-key)
|   |   +-+ro sourc-dest-key
|   |   +-+ro source?       inet:ip-prefix
|   |   +-+ro dest?         inet:ip-prefix
+-+ro ttl?             uint32
+-+ro authoritative?   bits
+-+ro (locator-list)?
  +-:(negative-mapping)
  |   +-+ro map-reply-action?  map-reply-action
  +-:(positive-mapping)
  |   +-+ro rlocs
  |   |   +-+ro rloc* [id]
  |   |   |   +-+ro id          string
  |   |   |   +-+ro (address-type)?
  |   |   |   |   +-:(interface-name)
  |   |   |   |   |   +-+ro interface?      if:interface-state-
ref
  |   |   |   +-:(address)
  |   |   |   +-+ro locator-address
  |   |   |   |   +-+ro afi          lisp-address-
family-ref
  |   |   |   +-+ro instance-id?     instance-id-type
  |   |   |   +-+ro (address)?
  |   |   |   |   +-:(ipv4)
  |   |   |   |   |   +-+ro ipv4?      inet:ipv4-
address
  |   |   |   +-:(ipv6)
  |   |   |   |   +-+ro ipv6?      inet:ipv6-
address
  |   |   |   +-:(mac)
  |   |   |   |   +-+ro mac?       yang:mac-
address

```

```
|      +--:(distinguished-name)
|          |  +-ro distinguished-name?
distinguished-name
|      +--:(lcaf)
|          +-ro lcaf
|              +-ro lcaf-type           lcaf-
|              ref
```

```

|           +-+ro (address)?
|           +-+:(null-address)
|           |   +-+ro null-address
|           |       +-+ro address?    empty
|           +-+:(afi-list)
|           |   +-+ro afi-list
|           |       +-+ro address-list*
simple-address
|           +-+:(instance-id)
|           |   +-+ro instance-id
|           |       +-+ro instance-id?
instance-id-type
|           |       +-+ro mask-length?    uint8
|           |       +-+ro address?      simple-
address
|           +-+:(as-number)
|           |   +-+ro as-number
|           |       +-+ro as?        inet:as-
number
|           |       +-+ro address?    simple-
address
|           +-+:(application-data)
|           |   +-+ro application-data
|           |       +-+ro address?
simple-address
|           |       +-+ro protocol?
uint8
|           |       +-+ro ip-tos?
int32
|           |       +-+ro local-port-low?
inet:port-number
|           |       +-+ro local-port-high?
inet:port-number
|           |       +-+ro remote-port-low?
inet:port-number
|           |       +-+ro remote-port-high?
inet:port-number
|           +-+:(geo-coordinates)
|           |   +-+ro geo-coordinates
|           |       +-+ro latitude?
bits
|           |       +-+ro latitude-degrees?
uint8
|           |       +-+ro latitude-minutes?
uint8
|           |       +-+ro latitude-seconds?
uint8
|           |       +-+ro longitude?

```

bits			+--ro longitude-degrees?
uint16			+--ro longitude-minutes?
uint8			+--ro longitude-seconds?
uint8			+--ro altitude?
int32			+--ro address?
simple-address		+--:(nat-traversal)	
		+--ro nat-traversal	
		+--ro ms-udp-port?	
uint16			+--ro etr-udp-port?
uint16			+--ro global-etr-rloc?
simple-address			+--ro ms-rloc?
simple-address			+--ro private-etr-rloc?
simple-address			+--ro rtr-rlocs*
simple-address		+--:(explicit-locator-path)	
		+--ro explicit-locator-path	
		+--ro hop* [address]	

address		+--ro address simple-
		+--ro lrs-bits? bits
		+--:(sourc-dest-key)
		+--ro sourc-dest-key
		+--ro source? inet:ip-
prefix		+--ro dest? inet:ip-
prefix		+--ro priority? uint8
		+--ro weight? uint8
		+--ro multicast-priority? uint8
		+--ro multicast-weight? uint8

[3.2. Module Definition](#)

```
module lisp-itr {
    namespace "urn:ietf:params:xml:ns:yang:lisp-itr";
    prefix lisp-itr;
    import ietf-lisp {
        prefix lisp;
    }
    import lisp-address-types {
        prefix lcaf;
    }
    import ietf-inet-types {
        prefix inet;
    }
    organization
        "IETF LISP (Locator/ID Separation Protocol) Working Group";
    contact
        "lisp@ietf.org";
    description
        "This YANG module defines the generic configuration
         data for a LISP ITR. The module can be extended by vendors
         to define vendor-specific configuration parameters and
         policies."
```

Copyright (c) 2015 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see
the RFC itself for full legal notices.

";

Ermagan, et al.

Expires January 7, 2016

[Page 22]

```
revision 2015-07-02 {
  description
    "Initial revision.";
  reference
    "https://tools.ietf.org/html/rfc6830";
}
identity itr {
  base lisp:lisp-device;
  description
    "LISP ITR.";
}
augment "/lisp:lisp/lisp:devices/lisp:device" {
  when "lisp:type = lisp-itr:itr" {
    description
      "Augment is valid when LISP device type is ITR.";
  }
  description
    "This augments LISP devices list with ITR specific
     parameters.";
  container itr-cfg {
    presence "LISP ITR operation enabled";
    description
      "ITR configuration";
    container rloc-probing {
      presence "RLOC probing active";
      description
        "RLOC-probing parameters";
      leaf interval {
        type uint16;
        units "seconds";
        description
          "Interval in seconds";
      }
      leaf retries {
        type uint8;
        description
          "Number of retries";
      }
      leaf retries-interval {
        type uint16;
        units "seconds";
        description
          "Interval in seconds between retries";
      }
    }
    container itr-rlocs {
      description
        "List of RLOCs of the ITR included in Map-Requests";
    }
  }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 23]

```
list itr-rloc {
    key "id";
    description
        "ITR's list of RLOCs.";
    leaf id {
        type string;
        description
            "Unique RLOC id.";
    }
    container address {
        uses lcaf:lisp-address;
        description
            "RLOC address in generic LISP address format.";
    }
}
container local-eids {
    description
        "Container for an ITR's local list of EIDs";
    list local-eid {
        key "id";
        min-elements 1;
        description
            "List of EIDs from which the ITR forwards traffic.";
        leaf id {
            type lisp:eid-id;
            description
                "Unique EID ID";
        }
        container eid-address {
            uses lcaf:lisp-address;
            description
                "Address in generic LISP address format";
        }
    }
}
container map-resolvers {
    description
        "The Map-Resolvers configured for the ITR.";
    list map-resolver {
        key "id";
        min-elements 1;
        description
            "List of Map-Resolvers configured for the ITR.";
        leaf id {
            type lisp:eid-id;
            description
                "Id of the EID for which the Map-Server is
```

Ermagan, et al.

Expires January 7, 2016

[Page 24]

```
        configured.";  
    }  
    container eid-address {  
        uses lcaf:lisp-address;  
        description  
            "EID for which the Map-Resolver is configured."  
    }  
    leaf-list map-resolver-address {  
        type inet:ip-address;  
        description  
            "Map-Resolver RLOC address."  
    }  
}  
}  
container proxy-etr {  
    description  
        "Proxy ETRs configured for the ITR."  
    list proxy-etr {  
        key "id";  
        description  
            "List of PETR configured for the ITR."  
        leaf id {  
            type lisp:eid-id;  
            description  
                "Id of the EID for which the PETR is configured."  
        }  
        container eid-address {  
            uses lcaf:lisp-address;  
            description  
                "EID for which the PETR is configured."  
        }  
        leaf-list proxy-etr-address{  
            type inet:ip-address;  
            description  
                "PETR RLOC address."  
        }  
    }  
}  
container static-mappings {  
    uses lisp:mappings;  
    description  
        "EID to RLOCs mappings cache."  
}  
}  
}  
augment "/lisp:lisp-state/lisp:devices/lisp:device" {  
    when "lisp:type = lisp-itr:itr" {  
        description
```

Ermagan, et al.

Expires January 7, 2016

[Page 25]

```
        "Augment is valid when LISP device type is ITR.";  
    }  
    description  
        "This augments LISP devices list state with ITR specific  
        parameters.";  
    container itr-state {  
        config false;  
        description  
            "ITR state.";  
        container learned-mappings {  
            uses lisp:mappings;  
            description  
                "EID to RLOCs mappings cache.";  
        }  
    }  
}  
}
```

4. LISP ETR Module

This module captures the configuration data model of a LISP ETR. The model also captures some operational data elements.

4.1. Module Structure

```
module: lisp-etr  
augment /lisp:lisp/lisp:devices/lisp:device:  
  +-rw etr-cfg!  
    +-rw local-eids  
      +-rw local-eid* [id]  
        +-rw id                      lisp:eid-id  
        +-rw eid-address  
          |  +-rw afi                  lisp-address-family-ref  
          |  +-rw instance-id?        instance-id-type  
          |  +-rw (address)?  
          |    +-:(ipv4)  
          |      |  +-rw ipv4?        inet:ipv4-address  
          |    +-:(ipv6)  
          |      |  +-rw ipv6?        inet:ipv6-address  
          |    +-:(mac)  
          |      |  +-rw mac?        yang:mac-address  
          |    +-:(distinguished-name)  
          |      |  +-rw distinguished-name?  distinguished-name  
          |    +-:(lcaf)  
          |      +-rw lcaf           lcaf-ref  
          |      +-rw lcaf-type       lcaf-ref  
          |      +-rw (address)?  
          |        +-:(null-address)
```

Ermagan, et al.

Expires January 7, 2016

[Page 26]

```
|   +-rw null-address
|     +-rw address?    empty
+--:(afi-list)
|   +-rw afi-list
|     +-rw address-list*  simple-address
+--:(instance-id)
|   +-rw instance-id
|     +-rw instance-id?  instance-id-type
|     +-rw mask-length?  uint8
|     +-rw address?      simple-address
+--:(as-number)
|   +-rw as-number
|     +-rw as?          inet:as-number
|     +-rw address?      simple-address
+--:(application-data)
|   +-rw application-data
|     +-rw address?      simple-address
|     +-rw protocol?    uint8
|     +-rw ip-tos?       int32
|     +-rw local-port-low?  inet:port-number
|     +-rw local-port-high?  inet:port-number
|     +-rw remote-port-low?  inet:port-number
|     +-rw remote-port-high?  inet:port-number
+--:(geo-coordinates)
|   +-rw geo-coordinates
|     +-rw latitude?     bits
|     +-rw latitude-degrees?  uint8
|     +-rw latitude-minutes?  uint8
|     +-rw latitude-seconds?  uint8
|     +-rw longitude?     bits
|     +-rw longitude-degrees?  uint16
|     +-rw longitude-minutes?  uint8
|     +-rw longitude-seconds?  uint8
|     +-rw altitude?       int32
|     +-rw address?        simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|     +-rw ms-udp-port?   uint16
|     +-rw etr-udp-port?   uint16
|     +-rw global-etr-rloc?  simple-address
|     +-rw ms-rloc?        simple-address
|     +-rw private-etr-rloc?  simple-address
|     +-rw rtr-rlocs*      simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|     +-rw hop* [address]
|       +-rw address      simple-address
|       +-rw lrs-bits?    bits
```

Ermagan, et al.

Expires January 7, 2016

[Page 27]

```

|           +-:(sourc-dest-key)
|           +-rw sourc-dest-key
|           +-rw source?    inet:ip-prefix
|           +-rw dest?      inet:ip-prefix
+-rw map-servers
|   +-rw map-server* [address]
|   +-rw address          inet:ip-address
|   +-rw auth-key?        string
|   +-rw auth-key-type?   lisp:auth-key-type
+-rw rlocs
|   +-rw rloc* [id]
|   +-rw id                string
|   +-rw (address-type)?
|   |   +-:(interface-name)
|   |   |   +-rw interface?      if:interface-state-ref
|   |   +-:(address)
|   |   +-rw locator-address
|   |   +-rw afi              lisp:address-family-ref
|   |   +-rw instance-id?     instance-id-type
|   |   +-rw (address)?
|   |   |   +-:(ipv4)
|   |   |   |   +-rw ipv4?       inet:ipv4-address
|   |   |   +-:(ipv6)
|   |   |   |   +-rw ipv6?       inet:ipv6-address
|   |   |   +-:(mac)
|   |   |   |   +-rw mac?       yang:mac-address
|   |   |   +-:(distinguished-name)
|   |   |   |   +-rw distinguished-name?  distinguished-name
|   |   |   +-:(lcaf)
|   |   |   +-rw lcaf
|   |   |   +-rw lcaf-type      lcaf-ref
|   |   |   +-rw (address)?
|   |   |   |   +-:(null-address)
|   |   |   |   |   +-rw null-address
|   |   |   |   |   +-rw address?   empty
|   |   |   |   +-:(afi-list)
|   |   |   |   |   +-rw afi-list
|   |   |   |   |   +-rw address-list* simple-
address
|   |   |   +-:(instance-id)
|   |   |   |   +-rw instance-id
|   |   |   |   +-rw instance-id?  instance-id-
type
|   |   |   |   +-rw mask-length?  uint8
|   |   |   |   +-rw address?     simple-
address
|   |   |   |   +-:(as-number)
|   |   |   |   |   +-rw as-number

```

```
|   |           |   +-rw as?      inet:as-number
|   |           |   +-rw address?  simple-address
|   |           +-:(application-data)
```

			+--rw application-data	
			+--rw address?	simple-
address				
			+--rw protocol?	uint8
			+--rw ip-tos?	int32
			+--rw local-port-low?	
inet:port-number				
			+--rw local-port-high?	
inet:port-number				
			+--rw remote-port-low?	
inet:port-number				
			+--rw remote-port-high?	
inet:port-number				
			+--:(geo-coordinates)	
			+--rw geo-coordinates	
			+--rw latitude?	bits
			+--rw latitude-degrees?	uint8
			+--rw latitude-minutes?	uint8
			+--rw latitude-seconds?	uint8
			+--rw longitude?	bits
			+--rw longitude-degrees?	uint16
			+--rw longitude-minutes?	uint8
			+--rw longitude-seconds?	uint8
			+--rw altitude?	int32
			+--rw address?	simple-
address				
			+--:(nat-traversal)	
			+--rw nat-traversal	
			+--rw ms-udp-port?	uint16
			+--rw etr-udp-port?	uint16
			+--rw global-etr-rloc?	simple-
address				
			+--rw ms-rloc?	simple-
address				
			+--rw private-etr-rloc?	simple-
address				
			+--rw rtr-rlocs*	simple-
address				
			+--:(explicit-locator-path)	
			+--rw explicit-locator-path	
			+--rw hop* [address]	
			+--rw address	simple-
address				
			+--rw lrs-bits?	bits
			+--:(sourc-dest-key)	
			+--rw sourc-dest-key	
			+--rw source?	inet:ip-prefix
			+--rw dest?	inet:ip-prefix

```
|     +-rw priority?          uint8
|     +-rw weight?           uint8
|     +-rw multicast-priority?  uint8
|     +-rw multicast-weight?   uint8
+-rw record-ttl?          uint32
+-rw want-map-notify?      boolean
+-rw proxy-reply?          boolean
+-rw registration-interval? uint16
```

[4.2.](#) Module Definition

```
module lisp-etr {
    namespace "urn:ietf:params:xml:ns:yang:lisp-etr";
    prefix lisp-etr;
    import ietf-lisp {
        prefix lisp;
    }
    import lisp-address-types {
        prefix lcaf;
    }
    import ietf-inet-types {
        prefix inet;
    }
    organization
        "IETF LISP (Locator/ID Separation Protocol) Working Group";
    contact
        "lisp@ietf.org";
    description
        "This YANG module defines the generic configuration
         data for a LISP ETR. The module can be extended by vendors
         to define vendor-specific configuration parameters and
         policies."}
```

Copyright (c) 2015 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see the RFC itself for full legal notices.

```
";  
revision 2015-07-02 {  
    description  
        "Initial revision.";  
    reference  
        "https://tools.ietf.org/html/rfc6830";  
}  
identity etr {  
    base lisp:lisp-device;  
    description  
        "LISP ETR.";  
}
```



```
augment "/lisp:lisp/lisp:devices/lisp:device" {
    when "lisp:type = lisp-etr:etr" {
        description
            "Augment is valid when LISP device type is ETR.";
    }
    description
        "This augments LISP devices list with ETR specific
         parameters.";
    container etr-cfg {
        presence "LISP ETR operation enabled";
        description
            "ETR configuration parameters.";
    container local-eids {
        description
            "EIDs served by the ETR.";
        list local-eid {
            key "id";
            min-elements 1;
            description
                "List of local EIDs.";
            leaf id {
                type lisp:eid-id;
                description
                    "Unique id of local EID.";
            }
            container eid-address {
                uses lcaf:lisp-address;
                description
                    "EID address in generic LISP address format.";
            }
            container map-servers {
                description
                    "Map-Servers configured for the ETR.";
                list map-server {
                    key "address";
                    description
                        "List of Map-Servers configured for the ETR.";
                    leaf address {
                        type inet:ip-address;
                        description
                            "Map-Server address.";
                    }
                    leaf auth-key {
                        type string;
                        description
                            "Map-Server authentication key.";
                    }
                    leaf auth-key-type {
```



```
    type lisp:auth-key-type;
    description
        "Map-Server authentication type.";
    }
}
}
container rlocs {
    uses lisp:locators;
    description
        "Locators mapped to local EID.";
}
leaf record-ttl {
    type uint32;
    description
        "Validity period of the EID to RLOCs mapping provided
         in Map-Replies.";
}
leaf want-map-notify {
    type boolean;
    description
        "Flag which if set in a Map-Register requests that a
         Map-Notify be sent in response.";
}
leaf proxy-reply {
    type boolean;
    description
        "Flag which if set in a Map-Register requests that the
         Map-Server proxy Map-Replies for the ETR.";
}
leaf registration-interval {
    type uint16;
    units "seconds";
    default "60";
    description
        "Interval between consecutive Map-Register messages.";
}
}
}
}
}
}
```

5. LISP Map Server Module

This module captures the configuration data model of a LISP Map Server [[RFC6833](#)]. The model also captures some operational data elements.

[5.1. Module Structure](#)

```

module: lisp-map-server
augment /lisp:lisp/lisp:devices/lisp:device:
  +-rw map-server-cfg!
    +-rw sites
      | +-rw site* [site-id]
      |   +-rw site-id     uint64
      |   +-rw devices
      |     +-rw device* [device-id]
      |       +-rw device-id     uint64
      |       +-rw auth-key
      |         | +-rw auth-key-value?   string
      |         | +-rw auth-key-type?  lisp:auth-key-type
      |       +-rw eids
      |         +-rw eid* [id]
      |           +-rw id                      lisp:eid-id
      |           +-rw eid-address
      |             | +-rw afi                  lisp-address-family-ref
      |             | +-rw instance-id?      instance-id-type
      |             | +-rw (address)?
      |               +-:(ipv4)
      |                 | +-rw ipv4?          inet:ipv4-address
      |               +-:(ipv6)
      |                 | +-rw ipv6?          inet:ipv6-address
      |               +-:(mac)
      |                 | +-rw mac?            yang:mac-address
      |               +-:(distinguished-name)
      |                 | +-rw distinguished-name?  distinguished-name
      |               +-:(lcaf)
      |                 +-rw lcaf
      |                   +-rw lcaf-type        lcaf-ref
      |                   +-rw (address)?
      |                     +-:(null-address)
      |                       | +-rw null-address
      |                         | +-rw address?    empty
      |                     +-:(afi-list)
      |                       | +-rw afi-list
      |                         +-rw address-list*  simple-
address
      |                         +-:(instance-id)
      |                           | +-rw instance-id
      |                             | +-rw instance-id?  instance-id-
type
      |                           |   +-rw mask-length?  uint8
      |                           |   +-rw address?      simple-
address
      |                           |   +-:(as-number)

```

```
|           |           |  +-rw as-number
|           |           |  +-rw as?          inet:as-number
|           |           |  +-rw address?    simple-address
```

```

|           |           +-:(application-data)
|           |           |   +-rw application-data
|           |           |   +-rw address?      simple-
address
|           |           |   +-rw protocol?     uint8
|           |           |   +-rw ip-tos?       int32
|           |           |   +-rw local-port-low?
inet:port-number
|           |           |   +-rw local-port-high?
inet:port-number
|           |           |   +-rw remote-port-low?
inet:port-number
|           |           |   +-rw remote-port-high?
inet:port-number
|           |           +-:(geo-coordinates)
|           |           |   +-rw geo-coordinates
|           |           |   +-rw latitude?       bits
|           |           |   +-rw latitude-degrees? uint8
|           |           |   +-rw latitude-minutes? uint8
|           |           |   +-rw latitude-seconds? uint8
|           |           |   +-rw longitude?      bits
|           |           |   +-rw longitude-degrees? uint16
|           |           |   +-rw longitude-minutes? uint8
|           |           |   +-rw longitude-seconds? uint8
|           |           |   +-rw altitude?       int32
|           |           |   +-rw address?      simple-
address
|           |           +-:(nat-traversal)
|           |           |   +-rw nat-traversal
|           |           |   +-rw ms-udp-port?    uint16
|           |           |   +-rw etr-udp-port?    uint16
|           |           |   +-rw global-etr-rloc?  simple-
address
|           |           |   +-rw ms-rloc?      simple-
address
|           |           |   +-rw private-etr-rloc? simple-
address
|           |           |   +-rw rtr-rlocs*    simple-
address
|           |           +-:(explicit-locator-path)
|           |           |   +-rw explicit-locator-path
|           |           |   +-rw hop* [address]
|           |           |   +-rw address      simple-
address
|           |           |   +-rw lrs-bits?    bits
+-:(sourc-dest-key)
|           |           +-rw sourc-dest-key
|           |           +-rw source?     inet:ip-prefix

```

```
| | | +--rw dest?          inet:ip-prefix
| | | +--rw more-specifics-accepted?    boolean
| | | +--rw mapping-expiration-timeout? int16
+--rw static-mappings
| +--rw mapping* [id]
| | +--rw id              eid-id
| | +--rw eid
| | | +--rw afi            lisp-address-family-ref
| | | +--rw instance-id?   instance-id-type
| | | +--rw (address)?
| | | | +--:(ipv4)
```

```
|   |   |   +-+rw ipv4?          inet:ipv4-address
|   |   +-:(ipv6)
|   |   |   +-+rw ipv6?          inet:ipv6-address
|   |   +-:(mac)
|   |   |   +-+rw mac?          yang:mac-address
|   |   +-:(distinguished-name)
|   |   |   +-+rw distinguished-name?  distinguished-name
|   |   +-:(lcaf)
|   |   |   +-+rw lcaf
|   |   |   |   +-+rw lcaf-type      lcaf-ref
|   |   |   |   +-+rw (address)?
|   |   |   |   |   +-:(null-address)
|   |   |   |   |   |   +-+rw null-address
|   |   |   |   |   |   +-+rw address?    empty
|   |   |   |   +-:(afi-list)
|   |   |   |   |   +-+rw afi-list
|   |   |   |   |   |   +-+rw address-list*  simple-address
|   |   |   +-:(instance-id)
|   |   |   |   +-+rw instance-id
|   |   |   |   |   +-+rw instance-id?  instance-id-type
|   |   |   |   |   +-+rw mask-length?  uint8
|   |   |   |   |   +-+rw address?      simple-address
|   |   |   +-:(as-number)
|   |   |   |   +-+rw as-number
|   |   |   |   |   +-+rw as?          inet:as-number
|   |   |   |   |   +-+rw address?      simple-address
|   |   |   +-:(application-data)
|   |   |   |   +-+rw application-data
|   |   |   |   |   +-+rw address?      simple-address
|   |   |   |   |   +-+rw protocol?     uint8
|   |   |   |   |   +-+rw ip-tos?       int32
|   |   |   |   |   +-+rw local-port-low?  inet:port-number
|   |   |   |   |   +-+rw local-port-high?  inet:port-number
|   |   |   |   |   +-+rw remote-port-low?  inet:port-number
|   |   |   |   |   +-+rw remote-port-high?  inet:port-number
|   |   |   +-:(geo-coordinates)
|   |   |   |   +-+rw geo-coordinates
|   |   |   |   |   +-+rw latitude?      bits
|   |   |   |   |   +-+rw latitude-degrees?  uint8
|   |   |   |   |   +-+rw latitude-minutes?  uint8
|   |   |   |   |   +-+rw latitude-seconds?  uint8
|   |   |   |   |   +-+rw longitude?      bits
|   |   |   |   |   +-+rw longitude-degrees?  uint16
|   |   |   |   |   +-+rw longitude-minutes?  uint8
|   |   |   |   |   +-+rw longitude-seconds?  uint8
|   |   |   |   |   +-+rw altitude?       int32
|   |   |   |   |   +-+rw address?      simple-address
|   |   |   +-:(nat-traversal)
```



```

|   |           +-rw nat-traversal
|   |           +-rw ms-udp-port?      uint16
|   |           +-rw etr-udp-port?    uint16
|   |           +-rw global-etr-rloc? simple-address
|   |           +-rw ms-rloc?        simple-address
|   |           +-rw private-etr-rloc? simple-address
|   |           +-rw rtr-rlocs*      simple-address
|   +-:(explicit-locator-path)
|       +-rw explicit-locator-path
|           +-rw hop* [address]
|               +-rw address      simple-address
|               +-rw lrs-bits?     bits
|   +-:(sourc-dest-key)
|       +-rw sourc-dest-key
|           +-rw source?      inet:ip-prefix
|           +-rw dest?        inet:ip-prefix
+-rw ttl?          uint32
+-rw authoritative? bits
+-rw (locator-list)?
    +-:(negative-mapping)
    |   +-rw map-reply-action? map-reply-action
    +-:(positive-mapping)
        +-rw rlocs
            +-rw rloc* [id]
                +-rw id          string
            +-rw (address-type)?
                +-:(interface-name)
                |   +-rw interface?      if:interface-state-
ref
    |   +-:(address)
    |       +-rw locator-address
    |           +-rw afi          lisp-address-
family-ref
    |   +-rw instance-id?      instance-id-type
    |   +-rw (address)?
        +-:(ipv4)
        |   +-rw ipv4?          inet:ipv4-
address
    |   +-:(ipv6)
    |       |   +-rw ipv6?          inet:ipv6-
address
    |   +-:(mac)
    |       |   +-rw mac?          yang:mac-
address
    |   +-:(distinguished-name)
    |       |   +-rw distinguished-name?
distinguished-name
    |   +-:(lcaf)

```

```
|           |           +-rw lcaf
|           |           +-rw lcaf-type          lcaf-
ref
|           |           +-rw (address)?
|           |           +-:(null-address)
|           |           |   +-rw null-address
|           |           |           +-rw address?   empty
```

```

|   |   |   +--:(afi-list)
|   |   |   |   +-rw afi-list
|   |   |   |   +-rw address-list*
simple-address
|   |   |   +--:(instance-id)
|   |   |   |   +-rw instance-id
|   |   |   |   +-rw instance-id?
instance-id-type
|   |   |   |   +-rw mask-length?    uint8
|   |   |   |   +-rw address?      simple-
address
|   |   |   |   +--:(as-number)
|   |   |   |   +-rw as-number
|   |   |   |   +-rw as?          inet:as-
number
|   |   |   |   +-rw address?    simple-
address
|   |   |   |   +--:(application-data)
|   |   |   |   +-rw application-data
|   |   |   |   +-rw address?
simple-address
|   |   |   |   +-rw protocol?
uint8
|   |   |   |   +-rw ip-tos?
int32
|   |   |   |   +-rw local-port-low?
inet:port-number
|   |   |   |   +-rw local-port-high?
inet:port-number
|   |   |   |   +-rw remote-port-low?
inet:port-number
|   |   |   |   +-rw remote-port-high?
inet:port-number
|   |   |   |   +--:(geo-coordinates)
|   |   |   |   +-rw geo-coordinates
|   |   |   |   +-rw latitude?
bits
|   |   |   |   +-rw latitude-degrees?
uint8
|   |   |   |   +-rw latitude-minutes?
uint8
|   |   |   |   +-rw latitude-seconds?
uint8
|   |   |   |   +-rw longitude?
bits
|   |   |   |   +-rw longitude-degrees?
uint16
|   |   |   |   +-rw longitude-minutes?

```

```

uint8
  |
  |
  |           |           |     +-rw longitude-seconds?
uint8
  |
  |
  |           |           |     +-rw altitude?
int32
  |
  |
  |           |           |     +-rw address?

simple-address
  |
  |
  |           |           |     +-:(nat-traversal)
  |           |           |       +-rw nat-traversal
  |           |           |       +-rw ms-udp-port?

uint16
  |
  |
  |           |           |     +-rw etr-udp-port?

uint16
  |
  |
  |           |           |     +-rw global-etr-rloc?

simple-address
  |
  |
  |           |           |     +-rw ms-rloc?

simple-address
  |
  |
  |           |           |     +-rw private-etr-rloc?

simple-address
  |
  |
  |           |           |     +-rw rtr-rlocs*

simple-address
  |
  |
  |           |           |     +-:(explicit-locator-path)
  |           |           |       +-rw explicit-locator-path
  |           |           |       +-rw hop* [address]
  |           |           |       +-rw address      simple-
address
  |
  |
  |           |           |     +-rw lrs-bits?    bits
  |
  |           |           |     +-:(sourc-dest-key)
  |           |           |       +-rw sourc-dest-key

```

```
|           |           +-rw source?    inet:ip-
prefix      |           |           +-rw dest?      inet:ip-
|           |           +-rw priority?   uint8
prefix      |           |           +-rw weight?     uint8
|           |           +-rw multicast-priority?  uint8
|           |           +-rw multicast-weight?   uint8
+-rw (mapping-system)
  +-:(ddt-mapping-system)
    +-rw ddt-mapping-system!
      +-rw ddt-root*          inet:ip-address
      +-rw authoritative-eids
        +-rw authoritative-eid* [id]
        +-rw id                lisp:eid-id
        +-rw eid-address
          +-rw afi              lisp-address-family-ref
          +-rw instance-id?     instance-id-type
          +-rw (address)?
            +-:(ipv4)
            |   +-rw ipv4?        inet:ipv4-address
            +-:(ipv6)
            |   +-rw ipv6?        inet:ipv6-address
            +-:(mac)
            |   +-rw mac?         yang:mac-address
            +-:(distinguished-name)
            |   +-rw distinguished-name?  distinguished-name
            +-:(lcaf)
              +-rw lcaf
                +-rw lcaf-type      lcaf-ref
                +-rw (address)?
                  +-:(null-address)
                  |   +-rw null-address
                  |   +-rw address?    empty
                  +-:(afi-list)
                  |   +-rw afi-list
                  |   +-rw address-list*  simple-address
                  +-:(instance-id)
                  |   +-rw instance-id
                  |   +-rw instance-id?  instance-id-type
                  |   +-rw mask-length?  uint8
                  |   +-rw address?     simple-address
                  +-:(as-number)
                  |   +-rw as-number
                  |   +-rw as?          inet:as-number
                  |   +-rw address?     simple-address
                  +-:(application-data)
                  |   +-rw application-data
```

address		+--rw address?	simple-
		+--rw protocol?	uint8

```

    |           |   +-rw ip-tos?          int32
    |           |   +-rw local-port-low?  inet:port-
number  |
    |           |   +-rw local-port-high?  inet:port-
number  |
    |           |   +-rw remote-port-low?  inet:port-
number  |
    |           |   +-rw remote-port-high?  inet:port-
number  |
    |           |   +-:(geo-coordinates)
    |           |       +-rw geo-coordinates
    |           |           +-rw latitude?          bits
    |           |           +-rw latitude-degrees?  uint8
    |           |           +-rw latitude-minutes?  uint8
    |           |           +-rw latitude-seconds?  uint8
    |           |           +-rw longitude?          bits
    |           |           +-rw longitude-degrees?  uint16
    |           |           +-rw longitude-minutes?  uint8
    |           |           +-rw longitude-seconds?  uint8
    |           |           +-rw altitude?          int32
    |           |           +-rw address?          simple-
address |
    |           |   +-:(nat-traversal)
    |           |       +-rw nat-traversal
    |           |       +-rw ms-udp-port?      uint16
    |           |       +-rw etr-udp-port?      uint16
    |           |       +-rw global-etr-rloc?  simple-
address |
    |           |       +-rw ms-rloc?          simple-
address |
    |           |       +-rw private-etr-rloc?  simple-
address |
    |           |       +-rw rtr-rlocs*        simple-
address |
    |           |   +-:(explicit-locator-path)
    |           |       +-rw explicit-locator-path
    |           |       +-rw hop* [address]
    |           |           +-rw address      simple-address
    |           |           +-rw lrs-bits?    bits
    |           |   +-:(sourc-dest-key)
    |           |       +-rw sourc-dest-key
    |           |       +-rw source?     inet:ip-prefix
    |           |       +-rw dest?       inet:ip-prefix
    |           |   +-:(alt-mapping-system)
    |           |       +-rw alt-mapping-system!
augment /lisp:lisp-state/lisp:devices/lisp:device:
    +-ro ms-state
    +-ro registered-mappings

```

```
+--ro mapping* [id]
  +-+ro id                      eid-id
  +-+ro eid
  |  +-+ro afi                  lisp-address-family-ref
  |  +-+ro instance-id?         instance-id-type
  |  +-+ro (address)?
  |    +--+:(ipv4)
  |    |  +-+ro ipv4?           inet:ipv4-address
  |    +--+:(ipv6)
```

```
|   |   +-+ro ipv6?           inet:ipv6-address
|   +-:(mac)
|   |   +-+ro mac?          yang:mac-address
|   +-:(distinguished-name)
|   |   +-+ro distinguished-name?  distinguished-name
|   +-:(lcaf)
|   |   +-+ro lcaf
|   |   |   +-+ro lcaf-type      lcaf-ref
|   |   |   +-+ro (address)?
|   |   |   |   +-:(null-address)
|   |   |   |   |   +-+ro null-address
|   |   |   |   |   +-+ro address?    empty
|   |   |   +-:(afi-list)
|   |   |   |   +-+ro afi-list
|   |   |   |   |   +-+ro address-list*  simple-address
|   |   |   +-:(instance-id)
|   |   |   |   +-+ro instance-id
|   |   |   |   |   +-+ro instance-id?  instance-id-type
|   |   |   |   |   +-+ro mask-length?  uint8
|   |   |   |   |   +-+ro address?      simple-address
|   |   |   +-:(as-number)
|   |   |   |   +-+ro as-number
|   |   |   |   |   +-+ro as?          inet:as-number
|   |   |   |   |   +-+ro address?      simple-address
|   |   |   +-:(application-data)
|   |   |   |   +-+ro application-data
|   |   |   |   |   +-+ro address?      simple-address
|   |   |   |   |   +-+ro protocol?     uint8
|   |   |   |   |   +-+ro ip-tos?       int32
|   |   |   |   |   +-+ro local-port-low?  inet:port-number
|   |   |   |   |   +-+ro local-port-high?  inet:port-number
|   |   |   |   |   +-+ro remote-port-low?  inet:port-number
|   |   |   |   |   +-+ro remote-port-high?  inet:port-number
|   |   |   +-:(geo-coordinates)
|   |   |   |   +-+ro geo-coordinates
|   |   |   |   |   +-+ro latitude?      bits
|   |   |   |   |   +-+ro latitude-degrees?  uint8
|   |   |   |   |   +-+ro latitude-minutes?  uint8
|   |   |   |   |   +-+ro latitude-seconds?  uint8
|   |   |   |   |   +-+ro longitude?      bits
|   |   |   |   |   +-+ro longitude-degrees?  uint16
|   |   |   |   |   +-+ro longitude-minutes?  uint8
|   |   |   |   |   +-+ro longitude-seconds?  uint8
|   |   |   |   |   +-+ro altitude?       int32
|   |   |   |   |   +-+ro address?      simple-address
|   |   |   +-:(nat-traversal)
|   |   |   |   +-+ro nat-traversal
|   |   |   |   |   +-+ro ms-udp-port?    uint16
```



```

|           |   +-+ro etr-udp-port?      uint16
|           |   +-+ro global-etr-rloc?    simple-address
|           |   +-+ro ms-rloc?        simple-address
|           |   +-+ro private-etr-rloc?   simple-address
|           |   +-+ro rtr-rlocs*       simple-address
|           +-+:(explicit-locator-path)
|           |   +-+ro explicit-locator-path
|           |   +-+ro hop* [address]
|           |       +-+ro address      simple-address
|           |       +-+ro lrs-bits?     bits
|           +-+:(sourc-dest-key)
|               +-+ro sourc-dest-key
|               +-+ro source?      inet:ip-prefix
|               +-+ro dest?        inet:ip-prefix
+-+ro ttl?          uint32
+-+ro authoritative?  bits
+-+ro (locator-list)?
    +-+:(negative-mapping)
    |   +-+ro map-reply-action?  map-reply-action
    +-+:(positive-mapping)
        +-+ro rlocs
            +-+ro rloc* [id]
                +-+ro id             string
                +-+ro (address-type)?
                |   +-+:(interface-name)
                |   |   +-+ro interface?      if:interface-state-
ref
    +-+:(address)
        +-+ro locator-address
        +-+ro afi            lisp-address-
family-ref
    +-+ro instance-id?      instance-id-type
    +-+ro (address)?
        +-+:(ipv4)
            |   +-+ro ipv4?      inet:ipv4-
address
    +-+:(ipv6)
        |   +-+ro ipv6?      inet:ipv6-
address
    +-+:(mac)
        |   +-+ro mac?        yang:mac-
address
    +-+:(distinguished-name)
        |   +-+ro distinguished-name?
distinguished-name
    +-+:(lcaf)
        +-+ro lcaf
            +-+ro lcaf-type    lcaf-

```

```
ref
|      +-+ro (address)?
|          +-+:(null-address)
|              |  +-+ro null-address
|                  |      +-+ro address?    empty
|          +-+:(afi-list)
|              |  +-+ro afi-list
```

		+--ro address-list*
simple-address		+--:(instance-id)
		+--ro instance-id
		+--ro instance-id?
instance-id-type		+--ro mask-length? uint8
		+--ro address? simple-
address		+--:(as-number)
		+--ro as-number
number		+--ro as? inet:as-
		+--ro address? simple-
address		+--:(application-data)
		+--ro application-data
		+--ro address?
simple-address		+--ro protocol?
uint8		+--ro ip-tos?
int32		+--ro local-port-low?
inet:port-number		+--ro local-port-high?
inet:port-number		+--ro remote-port-low?
inet:port-number		+--ro remote-port-high?
inet:port-number		+--:(geo-coordinates)
		+--ro geo-coordinates
bits		+--ro latitude?
		+--ro latitude-degrees?
uint8		+--ro latitude-minutes?
uint8		+--ro latitude-seconds?
uint8		+--ro longitude?
bits		+--ro longitude-degrees?
uint16		+--ro longitude-minutes?
uint8		+--ro longitude-seconds?

```

uint8
int32
simple-address
  |           +-+ro altitude?
  |           +-+ro address?
  |           +--+:(nat-traversal)
  |           |   +-+ro nat-traversal
  |           |   +-+ro ms-udp-port?
  |
  uint16
  |           +-+ro etr-udp-port?
  |
  uint16
  |           +-+ro global-etr-rloc?
  |
  simple-address
  |           +-+ro ms-rloc?
  |
  simple-address
  |           +-+ro private-etr-rloc?
  |
  simple-address
  |           +-+ro rtr-rlocs*
  |
  simple-address
  |           +--+:(explicit-locator-path)
  |           |   +-+ro explicit-locator-path
  |           |   +-+ro hop* [address]
  |           |           +-+ro address      simple-
  address
  |           |           +-+ro lrs-bits?    bits
  |           +--+:(sourc-dest-key)
  |           |           +-+ro sourc-dest-key
  |           |           +-+ro source?     inet:ip-
  |
  prefix
  |           +-+ro dest?      inet:ip-
  |
  prefix

```

```
+--ro priority?          uint8
+--ro weight?            uint8
+--ro multicast-priority? uint8
+--ro multicast-weight?  uint8
```

5.2. Module Definition

```
module lisp-map-server {
    namespace "urn:ietf:params:xml:ns:yang:lisp-map-server";
    prefix lisp-ms;
    import ietf-lisp {
        prefix lisp;
    }
    import lisp-address-types {
        prefix lcaf;
    }
    import ietf-inet-types {
        prefix inet;
    }
    organization
        "IETF LISP (Locator/ID Separation Protocol) Working Group";
    contact
        "lisp@ietf.org";
    description
        "This YANG module defines the generic configuration
         data for a LISP Map-Server. The module can be extended by
         vendors to define vendor-specific configuration parameters
         and policies.

    Copyright (c) 2015 IETF Trust and the persons identified as
    authors of the code. All rights reserved.

    Redistribution and use in source and binary forms, with or
    without modification, is permitted pursuant to, and subject
    to the license terms contained in, the Simplified BSD License
    set forth in Section 4.c of the IETF Trust's Legal Provisions
    Relating to IETF Documents
    (http://trustee.ietf.org/license-info).

    This version of this YANG module is part of RFC 6338; see
    the RFC itself for full legal notices.

    ";

    revision 2015-07-02 {
        description
            "Initial revision.";
        reference
            "https://tools.ietf.org/html/rfc6833";
```

Ermagan, et al.

Expires January 7, 2016

[Page 43]

```
}

identity ms {
    base lisp:lisp-device;
    description
        "LISP Map-Server.";
}

augment "/lisp:lisp/lisp:devices/lisp:device" {
    when "lisp:type = lisp-ms:ms" {
        description
            "Augment is valid when LISP device type is Map-Server.";
    }
    description
        "This augments LISP devices list with Map-Server specific
         parameters.";
}

container map-server-cfg {
    presence "LISP Map-Server operation enabled";
    description
        "Map-Server configuration parameters.";
}

container sites {
    description
        "Sites for which the Map-Server accepts registrations.";
    list site {
        key "site-id";
        description
            "List of sites for which the Map-Server accepts
             registrations.";
        leaf site-id {
            type uint64;
            description
                "Site identifier.";
        }
    }
    //VINA: can be augmented to have below for per site auth-key
    //      leaf auth-key {
    //          description "clear text authentication key";
    //          type string;
    //      }
    container devices {
        description
            "Site devices registered with the Map-Server.";
        list device {
            key "device-id";
            description
                "List of site devices registered with the
                 Map-Server.";
            leaf device-id {
                type uint64;
                description
                    "Device identifier.";
            }
        }
    }
}
```



```
}

container auth-key {
    description
        "Device authentication key.";
    leaf auth-key-value {
        type string;
        description
            "Clear text authentication key";
    }
    leaf auth-key-type {
        type lisp:auth-key-type;
        description
            "Authentication key type.";
    }
}

container eids {
    description
        "EIDs registered by device.";
    list eid {
        key "id";
        description
            "List of EIDs registered by device.";
        leaf id {
            type lisp:eid-id;
            description
                "Id of the EID registered.";
        }
    }
    container eid-address {
        uses lcaf:lisp-address;
        description
            "EID in generic LISP address format registered
             with the Map-Server.";
    }
    leaf more-specifics-accepted {
        type boolean;
        description
            "Flag indicating if more specific prefixes
             can be registered.";
    }
    leaf mapping-expiration-timeout {
        type int16;
        units "seconds";
        default "180"; //3 times the mapregister int
        description
            "Time before mapping is expired if no new
             registrations are received.";
    }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 45]

```
// VINA: can be augmented to have below for per-eid auth-key
//         leaf auth-key {
//             description "clear text authentication key";
//             type string;
//         }
//     }
// }
}
}

container static-mappings {
    uses lisp:mappings;
    description
        "Datastore of statically registered mappings.";
}

choice mapping-system {
    mandatory true;
    description
        "Interface to Mapping System.";
    container ddt-mapping-system {
        presence "DDT Mapping System in use";
        description
            "DDT Mapping System interface.";
        leaf-list ddt-root {
            type inet:ip-address;
            description
                "List of DDT root address.";
        }
    }
    container authoritative-eids {
        description
            "Authoritative EIDs";
        list authoritative-eid {
            key "id";
            description
                "List of authoritative EIDs.";
            leaf id {
                type lisp:eid-id;
                description
                    "EID id.";
            }
            container eid-address {
                uses lcaf:lisp-address;
                description
                    "EID in generic LISP address format.";
            }
        }
    }
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 46]

```

    }
  container alt-mapping-system {
    presence "ALT Mapping System in use";
    description
      "ALT Mapping System interface.";
    // TBD
  }
}
}

augment "/lisp:lisp-state/lisp:devices/lisp:device" {
  when "lisp:type = lisp-ms:ms" {
    description
      "Augment is valid when LISP device type is Map-Server.";
  }
  description
    "This augments LISP devices list state with Map-Server
     specific parameters.";
  container ms-state {
    config false;
    description
      "Map-Server state.";
    container registered-mappings {
      uses lisp:mappings;
      description
        "Datastore of registered mappings.";
    }
  }
}
}
}

```

6. LISP Map Resolver Module

This module captures the configuration data model of a LISP Map Resolver [RFC6833]. The model also captures some operational data elements.

6.1. Module Structure

```

module: lisp-map-resolver
augment /lisp:lisp/lisp:devices/lisp:device:
  +-rw map-resolver-cfg!
    +-rw (mapping-system)
      +-:(ddt-mapping-system)
        |  +-rw ddt-mapping-system!
        |    +-rw ddt-root*  inet:ip-address
      +-:(alt-mapping-system)
        +-rw alt-mapping-system!

```

Ermagan, et al.

Expires January 7, 2016

[Page 47]

[6.2.](#) Module Definition

```
module lisp-map-resolver {
    namespace "urn:ietf:params:xml:ns:yang:lisp-map-resolver";
    prefix lisp-mr;
    import ietf-lisp {
        prefix lisp;
    }
    import ietf-inet-types {
        prefix inet;
    }
    organization
        "IETF LISP (Locator/ID Separation Protocol) Working Group";
    contact
        "lisp@ietf.org";
    description
        "This YANG module defines the generic configuration
         data for a LISP Map-Resolver. The module can be extended by
         vendors to define vendor-specific configuration parameters
         and policies."
```

Copyright (c) 2015 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see the RFC itself for full legal notices.

```
";  
revision 2015-07-02 {  
    description  
        "Initial revision.";  
    reference  
        "https://tools.ietf.org/html/rfc6833";  
}  
identity mr {  
    base lisp:lisp-device;  
    description  
        "LISP Map-Resolver.";  
}  
augment "/lisp:lisp/lisp:devices/lisp:device" {  
    when "lisp:type = lisp-mr:mr" {  
        description
```

Ermagan, et al.

Expires January 7, 2016

[Page 48]

```
        "Augment is valid when LISP device type is Map-Resolver.";  
    }  
    description  
        "This augments LISP devices list with Map-Resolver specific  
        parameters.";  
    container map-resolver-cfg {  
        presence "LISP Map-Resolver operation enabled";  
        description  
            "Map-Resolver configuration parameters.";  
        choice mapping-system {  
            mandatory true;  
            description  
                "Mapping system interface.";  
            container ddt-mapping-system {  
                presence "DDT Mapping System in use";  
                description  
                    "DDT mapping system interface.";  
                leaf-list ddt-root {  
                    type inet:ip-address;  
                    description  
                        "List of DDT root addresses.";  
                }  
            }  
            container alt-mapping-system{  
                presence "ALT Mapping System in use";  
                description  
                    "ALT mapping system interface.";  
                // TBD  
            }  
        }  
        // VE: move to operational model/container  
        // container mappings {  
        //     config false;  
        //     uses mappings;  
        // }  
    }  
    // FC : should we add as operational data  
    // cached mappings?  
}
```

7. LISP Proxy ITR Module

This module captures the configuration data model of a LISP Proxy ITR [RFC6832]. The model may also capture some operational data elements.

Ermagan, et al.

Expires January 7, 2016

[Page 49]

[7.1.](#) Module Structure

```
module: lisp-pitr
augment /lisp:lisp/lisp:devices/lisp:device:
  +-rw proxy-itr-cfg!
  +-rw servicing-eids
  |  +-rw eid* [id]
  |    +-rw id          lisp:eid-id
  |    +-rw eid-address
  |      +-rw afi          lisp-address-family-ref
  |      +-rw instance-id?  instance-id-type
  |      +-rw (address)?
  |        +-:(ipv4)
  |          +-rw ipv4?      inet:ipv4-address
  |        +-:(ipv6)
  |          +-rw ipv6?      inet:ipv6-address
  |        +-:(mac)
  |          +-rw mac?       yang:mac-address
  |        +-:(distinguished-name)
  |          +-rw distinguished-name?  distinguished-name
  |        +-:(lcaf)
  |          +-rw lcaf
  |            +-rw lcaf-type      lcaf-ref
  |            +-rw (address)?
  |              +-:(null-address)
  |                +-rw null-address
  |                +-rw address?   empty
  |              +-:(afi-list)
  |                +-rw afi-list
  |                  +-rw address-list*  simple-address
  |              +-:(instance-id)
  |                +-rw instance-id
  |                  +-rw instance-id?  instance-id-type
  |                  +-rw mask-length? uint8
  |                  +-rw address?     simple-address
  |              +-:(as-number)
  |                +-rw as-number
  |                  +-rw as?         inet:as-number
  |                  +-rw address?   simple-address
  |              +-:(application-data)
  |                +-rw application-data
  |                  +-rw address?     simple-address
  |                  +-rw protocol?   uint8
  |                  +-rw ip-tos?     int32
  |                  +-rw local-port-low?  inet:port-number
  |                  +-rw local-port-high?  inet:port-number
  |                  +-rw remote-port-low?  inet:port-number
  |                  +-rw remote-port-high?  inet:port-number
```



```
+--:(geo-coordinates)
|   +-rw geo-coordinates
|   |   +-rw latitude?          bits
|   |   +-rw latitude-degrees?  uint8
|   |   +-rw latitude-minutes?  uint8
|   |   +-rw latitude-seconds?  uint8
|   |   +-rw longitude?         bits
|   |   +-rw longitude-degrees? uint16
|   |   +-rw longitude-minutes? uint8
|   |   +-rw longitude-seconds? uint8
|   |   +-rw altitude?          int32
|   |   +-rw address?           simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|   |   +-rw ms-udp-port?      uint16
|   |   +-rw etr-udp-port?      uint16
|   |   +-rw global-etr-rloc?   simple-address
|   |   +-rw ms-rloc?           simple-address
|   |   +-rw private-etr-rloc?  simple-address
|   |   +-rw rtr-rlocs*        simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|   |   +-rw hop* [address]
|   |   |   +-rw address      simple-address
|   |   |   +-rw lrs-bits?    bits
+--:(sourc-dest-key)
|   +-rw sourc-dest-key
|   |   +-rw source?   inet:ip-prefix
|   |   +-rw dest?     inet:ip-prefix
+-rw map-resolvers
|   +-rw map-resolver* [id]
|   |   +-rw id          lisp:eid-id
|   |   +-rw eid
|   |   |   +-rw afi          lisp:address-family-ref
|   |   |   +-rw instance-id?  instance-id-type
|   |   |   +-rw (address)?
|   |   |   |   +-:(ipv4)
|   |   |   |   |   +-rw ipv4?      inet:ipv4-address
|   |   |   |   |   +-:(ipv6)
|   |   |   |   |   |   +-rw ipv6?      inet:ipv6-address
|   |   |   |   |   +-:(mac)
|   |   |   |   |   |   +-rw mac?      yang:mac-address
|   |   |   |   |   +-:(distinguished-name)
|   |   |   |   |   |   +-rw distinguished-name?  distinguished-name
|   |   |   |   |   +-:(lcaf)
|   |   |   |   |   |   +-rw lcaf
|   |   |   |   |   |   |   +-rw lcaf-type      lcaf-ref
|   |   |   |   |   |   |   +-rw (address)?
```



```
+--:(null-address)
|   +-rw null-address
|   +-rw address?    empty
+--:(afi-list)
|   +-rw afi-list
|   +-rw address-list*  simple-address
+--:(instance-id)
|   +-rw instance-id
|   +-rw instance-id?  instance-id-type
|   +-rw mask-length? uint8
|   +-rw address?      simple-address
+--:(as-number)
|   +-rw as-number
|   +-rw as?          inet:as-number
|   +-rw address?      simple-address
+--:(application-data)
|   +-rw application-data
|   +-rw address?      simple-address
|   +-rw protocol?    uint8
|   +-rw ip-tos?      int32
|   +-rw local-port-low?  inet:port-number
|   +-rw local-port-high?  inet:port-number
|   +-rw remote-port-low?  inet:port-number
|   +-rw remote-port-high?  inet:port-number
+--:(geo-coordinates)
|   +-rw geo-coordinates
|   +-rw latitude?     bits
|   +-rw latitude-degrees?  uint8
|   +-rw latitude-minutes?  uint8
|   +-rw latitude-seconds?  uint8
|   +-rw longitude?     bits
|   +-rw longitude-degrees?  uint16
|   +-rw longitude-minutes?  uint8
|   +-rw longitude-seconds?  uint8
|   +-rw altitude?      int32
|   +-rw address?      simple-address
+--:(nat-traversal)
|   +-rw nat-traversal
|   +-rw ms-udp-port?   uint16
|   +-rw etr-udp-port?   uint16
|   +-rw global-etr-rloc?  simple-address
|   +-rw ms-rloc?      simple-address
|   +-rw private-etr-rloc?  simple-address
|   +-rw rtr-rlocs*    simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|   +-rw hop* [address]
|       +-rw address      simple-address
```



```
|      |      +--rw lrs-bits?    bits
|      |      +--:(sourc-dest-key)
|      |          +--rw sourc-dest-key
|      |              +--rw source?    inet:ip-prefix
|      |              +--rw dest?      inet:ip-prefix
|      +--rw address*   inet:ip-address
+--rw static-mappings
    +--rw mapping* [id]
        +--rw id                  eid-id
        +--rw eid
            |  +--rw afi                lisp-address-family-ref
            |  +--rw instance-id?       instance-id-type
            |  +--rw (address)?
            |      +--:(ipv4)
            |          |  +--rw ipv4?        inet:ipv4-address
            |      +--:(ipv6)
            |          |  +--rw ipv6?        inet:ipv6-address
            |      +--:(mac)
            |          |  +--rw mac?        yang:mac-address
            |      +--:(distinguished-name)
            |          |  +--rw distinguished-name?  distinguished-name
            |      +--:(lcaf)
            |          +--rw lcaf
            |              +--rw lcaf-type           lcaf-ref
            |              +--rw (address)?
            |                  +--:(null-address)
            |                      |  +--rw null-address
            |                      |  +--rw address?    empty
            |                  +--:(afi-list)
            |                      |  +--rw afi-list
            |                          +--rw address-list*   simple-address
            |                  +--:(instance-id)
            |                      |  +--rw instance-id
            |                          +--rw instance-id?  instance-id-type
            |                      +--rw mask-length?  uint8
            |                      +--rw address?      simple-address
            |                  +--:(as-number)
            |                      |  +--rw as-number
            |                          +--rw as?          inet:as-number
            |                          +--rw address?    simple-address
            |                  +--:(application-data)
            |                      |  +--rw application-data
            |                          +--rw address?      simple-address
            |                          +--rw protocol?    uint8
            |                          +--rw ip-tos?      int32
            |                          +--rw local-port-low?  inet:port-number
            |                          +--rw local-port-high?  inet:port-number
            |                          +--rw remote-port-low?  inet:port-number
```



```

|   +-+rw remote-port-high?    inet:port-number
+-:(geo-coordinates)
|   +-+rw geo-coordinates
|       +-+rw latitude?          bits
|       +-+rw latitude-degrees?  uint8
|       +-+rw latitude-minutes?  uint8
|       +-+rw latitude-seconds?  uint8
|       +-+rw longitude?         bits
|       +-+rw longitude-degrees? uint16
|       +-+rw longitude-minutes? uint8
|       +-+rw longitude-seconds? uint8
|       +-+rw altitude?          int32
|       +-+rw address?           simple-address
+-:(nat-traversal)
|   +-+rw nat-traversal
|       +-+rw ms-udp-port?      uint16
|       +-+rw etr-udp-port?      uint16
|       +-+rw global-etr-rloc?   simple-address
|       +-+rw ms-rloc?           simple-address
|       +-+rw private-etr-rloc?  simple-address
|       +-+rw rtr-rlocs*        simple-address
+-:(explicit-locator-path)
|   +-+rw explicit-locator-path
|       +-+rw hop* [address]
|           +-+rw address      simple-address
|           +-+rw lrs-bits?     bits
+-:(sourc-dest-key)
|   +-+rw sourc-dest-key
|       +-+rw source?        inet:ip-prefix
|       +-+rw dest?          inet:ip-prefix
+-+rw ttl?            uint32
+-+rw authoritative?  bits
+-+rw (locator-list)?
    +-:(negative-mapping)
    |   +-+rw map-reply-action? map-reply-action
    +-:(positive-mapping)
        +-+rw rlocs
            +-+rw rloc* [id]
                +-+rw id             string
                +-+rw (address-type)?
                    |   +-:(interface-name)
                    |   |   +-+rw interface?      if:interface-state-
ref
    |   +-:(address)
    |       +-+rw locator-address
    |       +-+rw afi            lisp-address-
family-ref
    |   +-+rw instance-id?      instance-id-type

```

```
|      +-> rw (address)?  
|          +->:(ipv4)
```

```

address          |   +-rw ipv4?           inet:ipv4-
address          |   +-:(ipv6)
address          |   |   +-rw ipv6?           inet:ipv6-
address          |   |   +-:(mac)
address          |   |   |   +-rw mac?           yang:mac-
distinguished-name |   |   +-:(distinguished-name)
distinguished-name |   |   |   +-rw distinguished-name?
ref              |   |   +-:(lcaf)
ref              |   |   |   +-rw lcaf
ref              |   |   |   +-rw lcaf-type        lcaf-
simple-address   |   |   +-rw (address)?
simple-address   |   |   |   +-:(null-address)
simple-address   |   |   |   |   +-rw null-address
simple-address   |   |   |   |   |   +-rw address?    empty
simple-address   |   |   |   +-:(afi-list)
simple-address   |   |   |   |   +-rw afi-list
simple-address   |   |   |   |   |   +-rw address-list*
instance-id-type |   |   +-:(instance-id)
instance-id-type |   |   |   +-rw instance-id
instance-id-type |   |   |   +-rw instance-id?
address          |   |   +-rw mask-length?  uint8
address          |   |   +-rw address?      simple-
number          |   |   +-:(as-number)
number          |   |   |   +-rw as-number
number          |   |   |   |   +-rw as?           inet:as-
address          |   |   +-rw address?      simple-
simple-address   |   |   +-:(application-data)
simple-address   |   |   |   +-rw application-data
simple-address   |   |   |   +-rw address?
uint8            |   |   +-rw protocol?
int32            |   |   +-rw ip-tos?
inet:port-number |   |   +-rw local-port-low?
inet:port-number |   |   +-rw local-port-high?

```

			+--rw remote-port-low?
inet:port-number			+--rw remote-port-high?
inet:port-number			+---:(geo-coordinates)
			+--rw geo-coordinates
			+--rw latitude?
bits			+--rw latitude-degrees?
uint8			+--rw latitude-minutes?
uint8			+--rw latitude-seconds?
uint8			+--rw longitude?
bits			+--rw longitude-degrees?
uint16			+--rw longitude-minutes?
uint8			+--rw longitude-seconds?
uint8			+--rw altitude?
int32			+--rw address?
simple-address			+---:(nat-traversal)

```

          |           |   +-+rw nat-traversal
          |           |   +-+rw ms-udp-port?
uint16
          |           |   +-+rw etr-udp-port?
uint16
          |           |   +-+rw global-etr-rloc?
simple-address
          |           |   +-+rw ms-rloc?
simple-address
          |           |   +-+rw private-etr-rloc?
simple-address
          |           |   +-+rw rtr-rlocs*
simple-address
          |           +-+:(explicit-locator-path)
          |           |   +-+rw explicit-locator-path
          |           |   +-+rw hop* [address]
          |           |   +-+rw address      simple-
address
          |           |   +-+rw lrs-bits?    bits
          |           +-+:(sourc-dest-key)
          |           |   +-+rw sourc-dest-key
          |           |   +-+rw source?     inet:ip-
prefix
          |           |   +-+rw dest?       inet:ip-
prefix
          |           +-+rw priority?      uint8
          |           +-+rw weight?        uint8
          |           +-+rw multicast-priority? uint8
          |           +-+rw multicast-weight? uint8
augment /lisp:lisp-state/lisp:devices/lisp:device:
  +-+ro pitr-state
  +-+ro learned-mappings
    +-+ro mapping* [id]
      +-+ro id                  eid-id
      +-+ro eid
      |   +-+ro afi                lisp-address-family-ref
      |   +-+ro instance-id?       instance-id-type
      |   +-+ro (address)?
      |   |   +-+:(ipv4)
      |   |   |   +-+ro ipv4?         inet:ipv4-address
      |   |   +-+:(ipv6)
      |   |   |   +-+ro ipv6?         inet:ipv6-address
      |   |   +-+:(mac)
      |   |   |   +-+ro mac?         yang:mac-address
      |   |   +-+:(distinguished-name)
      |   |   |   +-+ro distinguished-name?  distinguished-name
      |   |   +-+:(lcaf)
      |   |   |   +-+ro lcaf

```

```
|      +-+ro lcaf-type          lcaf-ref
|      +-+ro (address)?
|      |      +-+:null-address
|      |      |      +-+ro null-address
|      |      |      +-+ro address?   empty
|      |      +-+:afi-list
|      |      |      +-+ro afi-list
|      |      |      +-+ro address-list*   simple-address
|      |      +-+:instance-id
```

```
|   +-+ro instance-id
|   +-+ro instance-id?    instance-id-type
|   +-+ro mask-length?   uint8
|   +-+ro address?       simple-address
+---:(as-number)
|   +-+ro as-number
|   +-+ro as?            inet:as-number
|   +-+ro address?       simple-address
+---:(application-data)
|   +-+ro application-data
|   +-+ro address?       simple-address
|   +-+ro protocol?      uint8
|   +-+ro ip-tos?
|   +-+ro local-port-low?  inet:port-number
|   +-+ro local-port-high?  inet:port-number
|   +-+ro remote-port-low?  inet:port-number
|   +-+ro remote-port-high?  inet:port-number
+---:(geo-coordinates)
|   +-+ro geo-coordinates
|   +-+ro latitude?        bits
|   +-+ro latitude-degrees?  uint8
|   +-+ro latitude-minutes?  uint8
|   +-+ro latitude-seconds?  uint8
|   +-+ro longitude?        bits
|   +-+ro longitude-degrees?  uint16
|   +-+ro longitude-minutes?  uint8
|   +-+ro longitude-seconds?  uint8
|   +-+ro altitude?         int32
|   +-+ro address?          simple-address
+---:(nat-traversal)
|   +-+ro nat-traversal
|   +-+ro ms-udp-port?     uint16
|   +-+ro etr-udp-port?     uint16
|   +-+ro global-etr-rloc?  simple-address
|   +-+ro ms-rloc?          simple-address
|   +-+ro private-etr-rloc?  simple-address
|   +-+ro rtr-rlocs*        simple-address
+---:(explicit-locator-path)
|   +-+ro explicit-locator-path
|   +-+ro hop* [address]
|   +-+ro address          simple-address
|   +-+ro lrs-bits?         bits
+---:(sourc-dest-key)
|   +-+ro sourc-dest-key
|   +-+ro source?          inet:ip-prefix
|   +-+ro dest?            inet:ip-prefix
+-+ro ttl?                uint32
+-+ro authoritative?      bits
```



```

    +-+ro (locator-list)?
    +-+:negative-mapping)
    |  +-+ro map-reply-action?  map-reply-action
    +-+:positive-mapping)
    |  +-+ro rlocs
    |  +-+ro rloc* [id]
    |  +-+ro id                  string
    |  +-+ro (address-type)?
    |  |  +-+:interface-name)
    |  |  |  +-+ro interface?      if:interface-state-
ref
    |  |  +-+:address)
    |  |  +-+ro locator-address
    |  |  +-+ro afi                lisp-address-
family-ref
    |  |  +-+ro instance-id?      instance-id-type
    |  |  +-+ro (address)?
    |  |  |  +-+:ipv4)
    |  |  |  |  +-+ro ipv4?        inet:ipv4-
address
    |  |  +-+:ipv6)
    |  |  |  +-+ro ipv6?        inet:ipv6-
address
    |  |  +-+:mac)
    |  |  |  +-+ro mac?        yang:mac-
address
    |  |  +-+:distinguished-name)
    |  |  |  +-+ro distinguished-name?
distinguished-name
    |  |  +-+:lcaf)
    |  |  |  +-+ro lcaf
    |  |  |  +-+ro lcaf-type      lcaf-
ref
    |  |  +-+ro (address)?
    |  |  |  +-+:null-address)
    |  |  |  |  +-+ro null-address
    |  |  |  |  |  +-+ro address?  empty
    |  |  |  +-+:afi-list)
    |  |  |  |  +-+ro afi-list
    |  |  |  |  |  +-+ro address-list*
simple-address
    |  |  +-+:instance-id)
    |  |  |  +-+ro instance-id
    |  |  |  |  +-+ro instance-id?
instance-id-type
    |  |  |  +-+ro mask-length?  uint8
    |  |  |  |  +-+ro address?    simple-
address

```

```
|           +--:(as-number)
|           |   +-ro as-number
|           |   |   +-ro as?          inet:as-
number
|           |   |   +-ro address?    simple-
address
|           |           +--:(application-data)
|           |           |   +-ro application-data
|           |           |   +-ro address?
simple-address
|           |           |   +-ro protocol?
uint8
|           |           |   +-ro ip-tos?
int32
|           |           |   +-ro local-port-low?
inet:port-number
```

inet:port-number			+--ro local-port-high?
inet:port-number			+--ro remote-port-low?
inet:port-number			+--ro remote-port-high?
		++:(geo-coordinates)	
			+--ro geo-coordinates
			+--ro latitude?
bits			+--ro latitude-degrees?
uint8			+--ro latitude-minutes?
uint8			+--ro latitude-seconds?
uint8			+--ro longitude?
bits			+--ro longitude-degrees?
uint16			+--ro longitude-minutes?
uint8			+--ro longitude-seconds?
uint8			+--ro altitude?
int32			+--ro address?
simple-address		++:(nat-traversal)	
			+--ro nat-traversal
			+--ro ms-udp-port?
uint16			+--ro etr-udp-port?
uint16			+--ro global-etr-rloc?
simple-address			+--ro ms-rloc?
simple-address			+--ro private-etr-rloc?
simple-address			+--ro rtr-rlocs*
simple-address		++:(explicit-locator-path)	
			+--ro explicit-locator-path
			+--ro hop* [address]
			+--ro address simple-
address			+--ro lrs-bits? bits

```

|           +--:(sourc-dest-key)
|           +--ro sourc-dest-key
|           +--ro source?    inet:ip-
prefix
|           +--ro dest?      inet:ip-
prefix
|           +--ro priority?   uint8
|           +--ro weight?     uint8
|           +--ro multicast-priority? uint8
|           +--ro multicast-weight?  uint8

```

[7.2.](#) Module Definition

```

module lisp-pitr {
  namespace "urn:ietf:params:xml:ns:yang:lisp-pitr";
  prefix lisp-pitr;
  import ietf-lisp {
    prefix lisp;
  }
  import lisp-address-types {
    prefix lcaf;
  }
}

```

```
import ietf-inet-types {
    prefix inet;
}
organization
    "IETF LISP (Locator/ID Separation Protocol) Working Group";
contact
    "lisp@ietf.org";
description
    "This YANG module defines the generic configuration
     data for a LISP PITR. The module can be extended by vendors
     to define vendor-specific configuration parameters and
     policies."
```

Copyright (c) 2015 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see the RFC itself for full legal notices.

```
";  
revision 2015-07-02 {  
    description  
        "Initial revision.";  
    reference  
        "https://tools.ietf.org/html/rfc6832";  
}  
identity pitr {  
    base lisp:lisp-device;  
    description  
        "LISP PITR.";  
}  
augment "/lisp:lisp/lisp:devices/lisp:device" {  
    when "lisp:type = lisp-pitr:pitr" {  
        description  
            "Augment is valid when LISP device type is PITR.";  
    }  
    description  
        "This augments LISP devices list with PITR specific  
         parameters.";  
    container proxy-itrcfg {  
        presence "LISP PITR operation enabled";  
        description
```



```
"Proxy-ITR configuration parameters.";  
container servicing-eids {  
    description  
        "EIDs serviced by the PITR.";  
    list eid {  
        key "id";  
        description  
            "List of EIDs serviced by the PITR.";  
        leaf id {  
            type lisp:eid-id;  
            description  
                "Id of serviced EID.";  
        }  
        container eid-address {  
            uses lcaf:lisp-address;  
            description  
                "Serviced EID address in generic LISP address format.";  
        }  
    }  
}  
  
container map-resolvers {  
    description  
        "Map-Resolvers configured for PITR.";  
    list map-resolver {  
        key "id";  
        description  
            "List of Map-Resolvers configured for PITR.";  
        leaf id {  
            type lisp:eid-id;  
            description  
                "Id of EID for which the Map-Resolver is used.";  
        }  
        container eid {  
            uses lcaf:lisp-address;  
            description  
                "EID for which the Map-Resolver is used.";  
        }  
        leaf-list address {  
            type inet:ip-address;  
            min-elements 1;  
            description  
                "List of Map-Resolver's addresses.";  
        }  
    }  
}  
container static-mappings{  
    uses lisp:mappings;
```



```

        description
          "EID to RLOCs mappings cache.";
    }
}
}

augment "/lisp:lisp-state/lisp:devices/lisp:device" {
  when "lisp:type = lisp-pitr:pitr" {
    description
      "Augment is valid when LISP device type is PITR.";
  }
  description
    "This augments LISP devices list state with PITR specific
     parameters.";
  container pitr-state {
    config false;
    description
      "ITR state.";
    container learned-mappings {
      uses lisp:mappings;
      description
        "EID to RLOCs mappings cache.";
    }
  }
}
}
}
}
}
```

[8. LISP Proxy ETR Module](#)

This module captures the configuration data model of a LISP Proxy ETR [[RFC6832](#)]. The model may also capture some operational data elements.

[8.1. Module Structure](#)

```

module: lisp-petr
augment /lisp:lisp/lisp:devices/lisp:device:
  +-rw proxy-etr-cfg!
  +-rw servicing-eids
    +-rw eid* [id]
      +-rw id                  lisp:eid-id
      +-rw eid-address
        +-rw afi                  lisp-address-family-ref
        +-rw instance-id?         instance-id-type
        +-rw (address)?
          +-:(ipv4)
            | +-rw ipv4?           inet:ipv4-address
          +-:(ipv6)
            | +-rw ipv6?           inet:ipv6-address

```



```
+--:(mac)
|  +-rw mac?                      yang:mac-address
+--:(distinguished-name)
|  +-rw distinguished-name?    distinguished-name
+--:(lcaf)
|  +-rw lcaf
|    +-rw lcaf-type             lcaf-ref
|    +-rw (address)?
|      +--:(null-address)
|        +-rw null-address
|        +-rw address?    empty
|      +--:(afi-list)
|        +-rw afi-list
|          +-rw address-list*   simple-address
|      +--:(instance-id)
|        +-rw instance-id
|          +-rw instance-id?  instance-id-type
|          +-rw mask-length? uint8
|          +-rw address?    simple-address
|      +--:(as-number)
|        +-rw as-number
|          +-rw as?          inet:as-number
|          +-rw address?    simple-address
|      +--:(application-data)
|        +-rw application-data
|          +-rw address?    simple-address
|          +-rw protocol?   uint8
|          +-rw ip-tos?     int32
|          +-rw local-port-low?  inet:port-number
|          +-rw local-port-high?  inet:port-number
|          +-rw remote-port-low?  inet:port-number
|          +-rw remote-port-high?  inet:port-number
|      +--:(geo-coordinates)
|        +-rw geo-coordinates
|          +-rw latitude?    bits
|          +-rw latitude-degrees?  uint8
|          +-rw latitude-minutes?  uint8
|          +-rw latitude-seconds?  uint8
|          +-rw longitude?    bits
|          +-rw longitude-degrees?  uint16
|          +-rw longitude-minutes?  uint8
|          +-rw longitude-seconds?  uint8
|          +-rw altitude?     int32
|          +-rw address?    simple-address
|      +--:(nat-traversal)
|        +-rw nat-traversal
|        +-rw ms-udp-port?   uint16
|        +-rw etr-udp-port?  uint16
```



```

|   +-rw global-etr-rloc?      simple-address
|   +-rw ms-rloc?            simple-address
|   +-rw private-etr-rloc?    simple-address
|   +-rw rtr-rlocs*          simple-address
+--:(explicit-locator-path)
|   +-rw explicit-locator-path
|   +-rw hop* [address]
|       +-rw address      simple-address
|       +-rw lrs-bits?     bits
+--:(sourc-dest-key)
    +-rw sourc-dest-key
        +-rw source?    inet:ip-prefix
        +-rw dest?      inet:ip-prefix

```

[8.2. Module Definition](#)

```

module lisp-petr {
  namespace "urn:ietf:params:xml:ns:yang:lisp-petr";
  prefix lisp-petr;
  import ietf-lisp {
    prefix lisp;
  }
  import lisp-address-types {
    prefix lcaf;
  }
  organization
    "IETF LISP (Locator/ID Separation Protocol) Working Group";
  contact
    "lisp@ietf.org";
  description
    "This YANG module defines the generic configuration
     data for a LISP PETR. The module can be extended by vendors to
     define vendor-specific configuration parameters and policies.

  Copyright (c) 2015 IETF Trust and the persons identified as
  authors of the code. All rights reserved.

  Redistribution and use in source and binary forms, with or
  without modification, is permitted pursuant to, and subject
  to the license terms contained in, the Simplified BSD License
  set forth in Section 4.c of the IETF Trust's Legal Provisions
  Relating to IETF Documents
  (http://trustee.ietf.org/license-info).

  This version of this YANG module is part of RFC 6338; see
  the RFC itself for full legal notices.
";
revision 2015-07-02 {

```



```
description
  "Initial revision.";
reference
  "https://tools.ietf.org/html/rfc6832";
}
identity petr {
  base lisp:lisp-device;
  description
    "LISP PETR.";
}
augment "/lisp:lisp/lisp:devices/lisp:device" {
  when "lisp:type = lisp-petr:petr" {
    description
      "Augment is valid when LISP device type is PETR.";
  }
  description
    "This augments LISP devices list with PETR specific
     parameters.";
  container proxy-etr-cfg {
    presence "LISP PETR operation enabled";
    description
      "Proxy ETR configuration parameters.";
  container servicing-eids {
    description
      "EIDs serviced by the PETR.";
    list eid {
      key "id";
      description
        "List of EIDs serviced by the PETR.";
      leaf id {
        type lisp:eid-id;
        description
          "Id of serviced EID.";
      }
      container eid-address {
        uses lcaf:lisp-address;
        description
          "Serviced EID in generic LISP address format.";
      }
    }
  }
}
}
```

Ermagan, et al.

Expires January 7, 2016

[Page 65]

[9.](#) LISP Address Types

This module captures the various LISP address types, and is an essential building block used in other LISP modules.

[9.1.](#) Module Definition

```
module lisp-address-types {
    namespace "urn:ietf:params:xml:ns:yang:lisp-address-types";
    prefix laddr;
    import ietf-inet-types {
        prefix inet;
    }
    import ietf-yang-types {
        prefix yang;
    }
    organization
        "IETF LISP (Locator/ID Separation Protocol) Working Group";
    contact
        "lisp@ietf.org";
    description
        "This YANG module defines the LISP Canonical Address Formats
         (LCAF) for LISP. The module can be extended by vendors to
         define vendor-specific parameters."
```

Copyright (c) 2014 IETF Trust and the persons identified as authors of the code. All rights reserved.

Redistribution and use in source and binary forms, with or without modification, is permitted pursuant to, and subject to the license terms contained in, the Simplified BSD License set forth in [Section 4.c](#) of the IETF Trust's Legal Provisions Relating to IETF Documents
(<http://trustee.ietf.org/license-info>).

This version of this YANG module is part of [RFC 6338](#); see the RFC itself for full legal notices.

```
";  
revision 2015-03-09 {  
    description  
        "Initial revision.";  
    reference  
        "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10";  
}  
identity lisp-address-family {  
    description  
        "Base identity from which identities describing LISP address
```



```
    families are derived.";  
}  
identity ipv4 {  
    base lisp-address-family;  
    description  
        "IANA IPv4 address family.";  
}  
identity ipv6 {  
    base lisp-address-family;  
    description  
        "IANA IPv6 address family.";  
}  
identity mac {  
    base lisp-address-family;  
    description  
        "IANA MAC address family.";  
}  
identity distinguished-name {  
    base lisp-address-family;  
    description  
        "IANA Distinguished Name address family.";  
}  
identity lcaf {  
    base lisp-address-family;  
    description  
        "IANA LISP Canonical Address Format address family.";  
}  
identity null-address {  
    base lcaf;  
    description  
        "Null body LCAF type.";  
}  
identity afi-list {  
    base lcaf;  
    description  
        "AFI-List LCAF type.";  
}  
identity instance-id {  
    base lcaf;  
    description  
        "Instance-ID LCAF type.";  
}  
identity as-number {  
    base lcaf;  
    description  
        "AS Number LCAF type.";  
}  
identity application-data {
```



```
base lcaf;
description
  "Application Data LCAF type.";
}
identity geo-coordinates {
  base lcaf;
  description
  "Geo-coordinates LCAF type.";
}
identity opaque-key {
  base lcaf;
  description
  "Opaque Key LCAF type.";
}
identity nat-traversal {
  base lcaf;
  description
  "NAT-Traversal LCAF type.";
}
identity nonce-locator {
  base lcaf;
  description
  "Nonce-Locator LCAF type.";
}
identity multicast-info {
  base lcaf;
  description
  "Multicast Info LCAF type.";
}
identity explicit-locator-path {
  base lcaf;
  description
  "Explicit Locator Path LCAF type.";
}
identity security-key {
  base lcaf;
  description
  "Security Key LCAF type.";
}
identity source-dest-key {
  base lcaf;
  description
  "Source/Dest LCAF type.";
}
identity replication-list {
  base lcaf;
  description
  "Replication-List LCAF type.";
```

Ermagan, et al.

Expires January 7, 2016

[Page 68]

```
}

identity json-data-model {
    base lcaf;
    description
        "JSON Data Model LCAF type.";
}

identity key-value-address {
    base lcaf;
    description
        "Key-Value LCAF type.";
}

identity encapsulation-format {
    base lcaf;
    description
        "Encapsulation Format LCAF type.";
}

typedef instance-id-type {
    type uint32 {
        range "0..16777214";
    }
    description
        "Defines the range of values for an Instance ID.";
}

typedef simple-address {
    type union {
        type inet:ip-address;
        type inet:ip-prefix;
        type yang:mac-address;
        type distinguished-name;
    }
    description
        "Union of address types that can be part of LCAFs.";
}

typedef distinguished-name {
    type string;
    description
        "Distinguished Name address.";
    reference
        "http://www.iana.org/assignments/address-family-numbers/
            address-family-numbers.xhtml";
}

typedef lisp-address-family-ref {
    type identityref {
        base lisp-address-family;
    }
    description
        "LISP address family reference.";
}
```



```
typedef lcaf-ref {
  type identityref {
    base lcaf;
  }
  description
    "LCAF types reference.";
}
grouping lcaf-address {
  description
    "Group of all the LCAF types.";
  leaf lcaf-type {
    type lcaf-ref;
    mandatory true;
    description
      "Enumeration of LCAF types.";
  }
  choice address {
    description "The LCAF addresses.";
    container null-address {
      when "../../lcaf-type = null" {
        description
          "When LCAF type is null.";
      }
      description
        "Null body LCAF type";
      leaf address {
        type empty;
        description
          "AFI address.";
      }
    }
    container afi-list {
      when "../../lcaf-type = afi-list" {
        description
          "When LCAF type is AFI-List.";
      }
      description
        "AFI-List LCAF type.";
      reference
        "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
          #section-4.16.1";
      leaf-list address-list {
        type simple-address;
        description
          "List of AFI addresses.";
      }
    }
    container instance-id {
```



```
when "../../lcaf-type = instance-id" {
    description
        "When LCAF type is Instance-ID";
}
description
    "Instance ID LCAF type.";
reference
    "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
     #section-4.2";
leaf instance-id {
    type instance-id-type;
    description
        "Instance ID value.";
}
leaf mask-length {
    type uint8;
    description
        "Mask length.";
}
leaf address {
    type simple-address;
    description
        "AFI address.";
}
}
container as-number {
    when "../../lcaf-type = as-number" {
        description
            "When LCAF type is AS-Number.";
    }
    description
        "AS Number LCAF type.";
    reference
        "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
         #section-4.3";
    leaf as {
        type inet:as-number;
        description
            "AS number.";
    }
    leaf address {
        type simple-address;
        description
            "AFI address.";
    }
}
container application-data {
    when "../../lcaf-type = application-data" {
```



```
    description
      "When LCAF type is Application Data.";
  }
  description
    "Application Data LCAF type.";
  reference
    "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
     #section-4.4";
  leaf address {
    type simple-address;
    description
      "AFI address.";
  }
  leaf protocol {
    type uint8;
    description
      "Protocol number.";
  }
  leaf ip-tos {
    type int32;
    description
      "Type of service field.";
  }
  leaf local-port-low {
    type inet:port-number;
    description
      "Low end of local port range.";
  }
  leaf local-port-high {
    type inet:port-number;
    description
      "High end of local port range.";
  }
  leaf remote-port-low {
    type inet:port-number;
    description
      "Low end of remote port range.";
  }
  leaf remote-port-high {
    type inet:port-number;
    description
      "High end of remote port range.";
  }
}
container geo-coordinates {
  when "../../lcaf-type = geo-coordinates" {
    description
      "When LCAF type is Geo-coordinates.";
```

Ermagan, et al.

Expires January 7, 2016

[Page 72]

```
}

description
  "Geo-coordinates LCAF type.";
reference
  "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
   #section-4.5";
leaf latitude {
  type bits {
    bit N {
      description
        "Latitude bit.";
    }
  }
  description
    "Bit that selects between North and South latitude.";
}
leaf latitude-degrees {
  type uint8 {
    range "0 .. 90";
  }
  description
    "Degrees of latitude.";
}
leaf latitude-minutes {
  type uint8 {
    range "0..59";
  }
  description
    "Minutes of latitude.";
}
leaf latitude-seconds {
  type uint8 {
    range "0..59";
  }
  description
    "Seconds of latitude.";
}
leaf longitude {
  type bits {
    bit E {
      description
        "Longitude bit.";
    }
  }
  description
    "Bit that selects between East and West longitude.";
}
leaf longitude-degrees {
```



```
type uint16 {
    range "0 .. 180";
}
description
  "Degrees of longitude.";
}
leaf longitude-minutes {
  type uint8 {
    range "0..59";
  }
  description
    "Minutes of longitude.";
}
leaf longitude-seconds {
  type uint8 {
    range "0..59";
  }
  description
    "Seconds of longitude.";
}
leaf altitude {
  type int32;
  description
    "Height relative to sea level in meters.";
}
leaf address {
  type simple-address;
  description
    "AFI address.";
}
}
container nat-traversal {
when ".../lcaf-type = nat-traversal" {
  description
    "When LCAF type is NAT-Traversal.";
}
  description
    "NAT-Traversal LCAF type.";
  reference
    "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
      #section-4.6";
}
leaf ms-udp-port {
  type uint16;
  description
    "Map-Server UDP port (set to 4342).";
}
leaf etr-udp-port {
  type uint16;
```

Ermagan, et al.

Expires January 7, 2016

[Page 74]

```
    description
      "ETR UDP port.";
  }
leaf global-etr-rloc {
  type simple-address;
  description
    "Global ETR RLOC address.";
}
leaf ms-rloc {
  type simple-address;
  description
    "Map-Server RLOC address.";
}
leaf private-etr-rloc {
  type simple-address;
  description
    "Private ETR RLOC address.";
}
leaf-list rtr-rlocs {
  type simple-address;
  description
    "List of RTR RLOC addresses.";
}
}
container explicit-locator-path {
  when "../../lcaf-type = explicit-locator-path" {
    description
      "When LCAF type type is Explicit Locator Path.";
  }
  description
    "Explicit Locator Path LCAF type.";
  reference
    "http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
      #section-4.9";
  list hop {
    key "address";
    description
      "List of locator hops forming the explicit path.";
  leaf address {
    type simple-address;
    description
      "AFI address.";
  }
  leaf lrs-bits {
    type bits{
      bit lookup {
        description
          "Lookup bit.";
```



```
        }
        bit rloc-probe {
            description
            "RLOC-probe bit.";
        }
        bit strict {
            description
            "Strict bit.";
        }
    }
    description
    "Flag bits per hop.";
}
}

container sourc-dest-key {
when "../../lcaf-type = source-dest-key" {
    description
    "When LCAF type type is Source/Dest.";
}
description
"Source/Dest LCAF type.";
reference
"http://tools.ietf.org/html/draft-ietf-lisp-lcaf-10
#section-4.11";
leaf source {
    type inet:ip-prefix;
    description
    "Source prefix.";
}
leaf dest {
    type inet:ip-prefix;
    description
    "Destination prefix.";
}
}
}

grouping lisp-address {
    description
    "Generic LISP address.";
leaf afi {
    type lisp-address-family-ref;
    mandatory true;
    description
    "LISP address family AFI.";
}
leaf instance-id {
```



```
type instance-id-type;
description
  "Instance ID of the address.";
}
choice address {
  leaf ipv4 {
    when "../../afi = 'laddr:ipv4'" {
      description
        "When AFI is IPv4.";
    }
    type inet:ipv4-address;
    description
      "IPv4 address.";
  }
  leaf ipv6 {
    when "../../afi = 'laddr:ipv6'" {
      description
        "When AFI is IPv6.";
    }
    type inet:ipv6-address;
    description
      "IPv6 address.";
  }
  leaf mac {
    when "../../afi = 'laddr:mac'" {
      description
        "When AFI is MAC.";
    }
    type yang:mac-address;
    description
      "MAC address.";
  }
  leaf distinguished-name {
    when "../../afi = 'laddr:distinguished-name'" {
      description
        "When AFI is distinguished-name.";
    }
    type distinguished-name;
    description
      "Distinguished Name address.";
  }
  container lcaf {
    when "../../afi = 'laddr:lcaf'" {
      description
        "When AFI is LCAF.";
    }
    uses lcaf-address;
    description
```



```
        "LCAF address.";
    }
    description
      "Selection of address type.";
}
}
}
```

10. Acknowledgments

The tree view and the YANG model shown in this document have been formated with the 'pyang' tool.

11. IANA Considerations

This memo includes no request to IANA.

12. Security Considerations

Security Considerations TBD

13. Normative References

- [I-D.ietf-lisp-ddt]
Fuller, V., Lewis, D., Ermagan, V., and A. Jain, "LISP Delegated Database Tree", [draft-ietf-lisp-ddt-03](#) (work in progress), April 2015.
- [I-D.ietf-lisp-lcaf]
Farinacci, D., Meyer, D., and J. Snijders, "LISP Canonical Address Format (LCAF)", [draft-ietf-lisp-lcaf-10](#) (work in progress), June 2015.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [RFC6830] Farinacci, D., Fuller, V., Meyer, D., and D. Lewis, "The Locator/ID Separation Protocol (LISP)", [RFC 6830](#), January 2013.
- [RFC6832] Lewis, D., Meyer, D., Farinacci, D., and V. Fuller, "Interworking between Locator/ID Separation Protocol (LISP) and Non-LISP Sites", [RFC 6832](#).
- [RFC6833] Fuller, V. and D. Farinacci, "Locator/ID Separation Protocol (LISP) Map-Server Interface", [RFC 6833](#), January 2013.

[RFC6836] Fuller, V., Farinacci, D., Meyer, D., and D. Lewis,
"Locator/ID Separation Protocol Alternative Logical
Topology (LISP+ALT)", [RFC 6836](#), January 2013.

Authors' Addresses

Vina Ermagan
Cisco Systems
170 Tasman Drive
San Jose, CA
USA

Email: vermagan@cisco.com

Alberto Rodriguez-Natal
Technical University of Catalonia
Barcelona
Spain

Email: arnatal@ac.upc.edu

Florin Coras
Technical University of Catalonia
Barcelona
Spain

Email: fcoras@ac.upc.edu

Carl Moberg
Cisco Systems
170 W Tasman Dr
San Jose, CA
USA

Email: camoberg@cisco.com

Albert Cabellos-Aparicio
Technical University of Catalonia
Barcelona
Spain

Email: acabelllo@ac.upc.edu

Fabio Maino
Cisco Systems
170 Tasman Drive
San Jose, CA
USA

Email: fmaino@cisco.com