INTERNET-DRAFT
"Internet Protocol Five Fields - User Datagram Protocol",
Alexey Eromenko, 2015-12-10,
<<u>draft-eromenko-ipff-udp-00.txt</u>>
expiration date: 2016-06-10

Intended status: Standards Track

A.Eromenko December 2015

User Datagram Protocol

for Internet Protocol "Five Fields" (IP-FF) Specification draft

Abstract

Minor modification of the UDP protocol to reduce overhead by 2 bytes. Intended to be used with Internet Protocol "Five Fields".

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of <u>BCP 78</u> and <u>BCP 79</u>.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <u>http://datatracker.ietf.org/drafts/current/</u>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on December 9, 2014.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to <u>BCP 78</u> and the IETF Trust's Legal Provisions Relating to IETF Documents (<u>http://trustee.ietf.org/license-info</u>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Introduction

This User Datagram Protocol (UDP) is defined to make available a datagram mode of packet-switched computer communication in the environment of an interconnected set of computer networks. This protocol assumes that the Internet Protocol (IP) [1] is used as the underlying protocol.

This protocol provides a procedure for application programs to send messages to other programs with a minimum of protocol mechanism. The protocol is transaction oriented, and delivery and duplicate protection are not guaranteed. Applications requiring ordered reliable delivery of streams of data should use the Transmission Control Protocol (TCP) [2].

Format

- - - - - -

User Datagram Header Format

0	78	15 16	23 24	31
+	+	+	+	+
	Source	I	Destination	
	Port	I	Port	
+	+	+	+	+
		I		
	Checksum		data	
+	+	+		+
	more	data c	octets	
+				

Fields

- - - - - -

Source Port is an optional field, when meaningful, it indicates the port of the sending process, and may be assumed to be the port to which a reply should be addressed in the absence of any other information. If not used, a value of zero is inserted.

Destination Port has a meaning within the context of a particular internet destination address.

Length of the data is taken from upper level IPFF protocol.

Checksum is the 16-bit one's complement of the one's complement sum of a pseudo header of information from the IP header, the UDP header, and the

data, padded with zero octets at the end (if necessary) to make a multiple of two octets.

The pseudo header conceptually prefixed to the UDP header contains the source address, the destination address, the protocol, and the UDP length. This information gives protection against misrouted datagrams. This checksum procedure is the same as is used in TCP.

The header structure must be taken from [IPFF] document RFC.

If the computed checksum is zero, it is transmitted as all ones (the equivalent in one's complement arithmetic). An all zero transmitted checksum value means that the transmitter generated no checksum (for debugging or for higher level protocols that don't care).

User Interface

A user interface should allow the creation of new receive ports, receive operations on the receive ports that return the data octets and an indication of source port and source address, and an operation that allows a datagram to be sent, specifying the data, source and destination ports and addresses to be sent.

IP Interface

The UDP module must be able to determine the source and destination internet addresses and the protocol field from the internet header. One possible UDP/IP interface would return the whole internet datagram including all of the internet header in response to a receive operation. Such an interface would also allow the UDP to pass a full internet datagram complete with header to the IP to send. The IP would verify certain fields for consistency and compute the internet header checksum.

Protocol Application

The major uses of this protocol is the Internet Domain Name Server (DNS), the Trivial File Transfer Protocol (TFTP) and the Dynamic Host Configuration Protocol (DHCP).

Protocol Number

This is protocol 17 when used in the Internet Protocol.

Acknowledgement

Originally written by J.Postel as <u>RFC-768</u>, modified by Alexey Eromenko

for the purposes of Internet Protocol "Five Fields".

Author Contacts

Alexey Eromenko Israel

Skype: Fenix_NBK_ EMail: al4321@gmail.com

INTERNET-DRAFT Alexey

expiration date: 2016-06-10