

Global Routing Operations  
Internet-Draft  
Updates: [7854](#) (if approved)  
Intended Status: Standards Track  
Expires: October 1, 2017

T. Evens  
S. Bayraktar  
Cisco Systems  
P. Lucente  
NTT Communications  
P. Mi  
Tencent  
S. Zhuang  
Huawei  
March 30, 2017

Support for Adj-RIB-Out in BGP Monitoring Protocol (BMP)  
draft-evens-grow-bmp-adj-rib-out-01

## Abstract

The BGP Monitoring Protocol (BMP) defines access to only the Adj-RIB-In Routing Information Bases (RIBs). This document updates the BGP Monitoring Protocol (BMP) [RFC 7854](#) by adding access to the Adj-RIB-Out RIBs. It adds a new flag to the peer header to distinguish Adj-RIB-In and Adj-RIB-Out.

## Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/lid-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>

This Internet-Draft will expire on October 1, 2017.

Internet-Draft

BMP Adj-RIB-Out

March, 2017

## Copyright and License Notice

Copyright (c) 2017 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## Table of Contents

<a href="#">1.</a>	Introduction . . . . .	<a href="#">3</a>
<a href="#">1.1.</a>	Terminology . . . . .	<a href="#">3</a>
<a href="#">2.</a>	Definitions . . . . .	<a href="#">4</a>
<a href="#">3.</a>	Per-Peer Header . . . . .	<a href="#">4</a>
<a href="#">4.</a>	Adj-RIB-Out . . . . .	<a href="#">4</a>
<a href="#">4.1.</a>	Post-Policy . . . . .	<a href="#">4</a>
<a href="#">4.2.</a>	Pre-Policy . . . . .	<a href="#">4</a>
<a href="#">5.</a>	BMP Messages . . . . .	<a href="#">5</a>
<a href="#">5.1.</a>	Route Monitoring and Route Mirroring . . . . .	<a href="#">5</a>
<a href="#">5.2.</a>	Statistics Report . . . . .	<a href="#">5</a>
<a href="#">5.3.</a>	Peer Down and Up Notifications . . . . .	<a href="#">5</a>
<a href="#">6.</a>	Security Considerations . . . . .	<a href="#">6</a>
<a href="#">7.</a>	IANA Considerations . . . . .	<a href="#">6</a>
<a href="#">7.1.</a>	BMP Peer Flags . . . . .	<a href="#">6</a>
<a href="#">7.2.</a>	BMP Statistics Types . . . . .	<a href="#">6</a>
<a href="#">8.</a>	References . . . . .	<a href="#">6</a>
<a href="#">8.1.</a>	URIs . . . . .	<a href="#">6</a>
<a href="#">8.2.</a>	Normative References . . . . .	<a href="#">6</a>
	Acknowledgments . . . . .	<a href="#">8</a>
	Contributors . . . . .	<a href="#">8</a>
	Authors' Addresses . . . . .	<a href="#">9</a>

Internet-Draft

BMP Adj-RIB-Out

March, 2017

## 1. Introduction

BGP Monitoring Protocol (BMP) defines monitoring of the received (e.g. Adj-RIB-In) Routing Information Bases (RIBs) per peer. The Adj-RIB-In pre-policy conveys to a BMP receiver all RIB data before any policy has been applied. The Adj-RIB-In post-policy conveys to a BMP receiver all RIB data after policy filters and/or modifications have been applied. An example of pre-policy verses post-policy is when an inbound policy applies attribute modification or filters. Pre-policy would contain information prior to the inbound policy changes or filters of data. Post policy would convey the changed data or would not contain the filtered data.

Monitoring the received updates that the router received before any policy has been applied is the primary level of monitoring for most use-cases. Inbound policy validation and auditing is the primary use-case for enabling post-policy monitoring.

In order for a BMP receiver to receive any BGP data, the BMP sender (e.g. router) needs to have an established BGP peering session and actively be receiving updates for an Adj-RIB-In.

Being able to only monitor the Adj-RIB-In puts a restriction on what data is available to BMP receivers via BMP senders (e.g. routers). This is an issue when the receiving end of the BGP peer is not enabled for BMP or when it is not accessible for administrative reasons. For example, a service provider advertises prefixes to a customer, but the service provider cannot see what it advertises via BMP. Asking the customer to enable BMP and monitoring of the Adj-RIB-In is not feasible.

This document updates BGP Monitoring Protocol (BMP) [RFC 7854](#) [RFC7854] peer header by adding a new flag to distinguish Adj-RIB-In verses Adj-RIB-Out.

Adding Adj-RIB-Out enables the ability for a BMP sender to send to a

BMP receiver what it advertises to BGP peers, which can be used for outbound policy validation and to monitor RIBs that were advertised.

## 1.1. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Evens, et al.

Expires October 1, 2017

[Page 3]

---

Internet-Draft

BMP Adj-RIB-Out

March, 2017

## 2. Definitions

- o Adj-RIB-Out: As defined in [[RFC4271](#)], "The Adj-RIBs-Out contains the routes for advertisement to specific peers by means of the local speaker's UPDATE messages."
- o Pre-Policy Adj-RIB-Out: The result before applying the outbound policy to an Adj-RIB-Out. This normally would match what is in the local RIB.
- o Post-Policy Adj-RIB-Out: The result of applying outbound policy to an Adj-RIB-Out. This MUST be what is actually sent to the peer.

## 3. Per-Peer Header

The per-peer header has the same structure and flags as defined in [section 4.2](#) [[RFC7854](#)] with the following 0 flag addition:

```
  0 1 2 3 4 5 6 7
+--+--+--+--+--+--+
|V|L|A|O| Resv |
+--+--+--+--+--+--+
```

- o The 0 flag indicates Adj-RIB-In if set to 0 and Adj-RIB-Out if set to 1.

The remaining bits are reserved for future use. They MUST be

transmitted as 0 and their values MUST be ignored on receipt.

## [4.](#) Adj-RIB-Out

### [4.1.](#) Post-Policy

The primary use-case in monitoring Adj-RIB-Out is to monitor the updates transmitted to the BGP peer after outbound policy has been applied. These updates reflect the result after modifications and filters have been applied (e.g. Adj-RIB-Out Post-Policy). The L flag MUST be set to 1 in this case to indicate post-policy.

### [4.2.](#) Pre-Policy

As with Adj-RIB-In policy validation, there are use-cases that pre-policy Adj-RIB-Out is used to validate and audit outbound policies. For example, a comparison between pre-policy and post-policy can be used to validate the outbound policy. The L flag MUST be set to 0 in

Evens, et al.

Expires October 1, 2017

[Page 4]

---

Internet-Draft

BMP Adj-RIB-Out

March, 2017

this case to indicate pre-policy.

## [5.](#) BMP Messages

Many BMP messages have a per-peer header but some are not applicable to Adj-RIB-In or Adj-RIB-Out monitoring. Unless otherwise defined, the O flag should be set to 0 in the per-peer header in BMP messages.

### [5.1.](#) Route Monitoring and Route Mirroring

The O flag MUST be set accordingly to indicate if the route monitor or route mirroring message conveys Adj-RIB-In or Adj-RIB-Out.

### [5.2.](#) Statistics Report

Statistics report message has Stat Type field to indicate the statistic carried in the Stat Data field. Statistics report messages are not specific to Adj-RIB-In or Adj-RIB-Out and MUST have the O flag set to zero. The O flag SHOULD be ignored by the BMP receiver. The following new statistic types are added:

- o Stat Type = TBD: (64-bit Gauge) Number of routes in Adj-RIBs-Out Pre-Policy.
- o Stat Type = TBD: (64-bit Gauge) Number of routes in Adj-RIBs-Out Post-Policy.
- o Stat Type = TBD: Number of routes in per-AFI/SAFI Adj-RIB-Out Pre-Policy. The value is structured as: 2-byte Address Family Identifier (AFI), 1-byte Subsequent Address Family Identifier (SAFI), followed by a 64-bit Gauge.
- o Stat Type = TBD: Number of routes in per-AFI/SAFI Adj-RIB-Out Post-Policy. The value is structured as: 2-byte Address Family Identifier (AFI), 1-byte Subsequent Address Family Identifier (SAFI), followed by a 64-bit Gauge.

### [5.3.](#) Peer Down and Up Notifications

PEER UP and DOWN notifications convey BGP peering session state to BMP receivers. The state is independent of whether or not route monitoring or route mirroring messages will be sent for Adj-RIB-In, Adj-RIB-Out, or both. BMP receiver implementations SHOULD ignore the 0 flag in PEER UP and DOWN notifications.

## [6.](#) Security Considerations

It is not believed that this document adds any additional security considerations.

## [7.](#) IANA Considerations

This document requests that IANA assign the following BMP new parameters to the BMP parameters name space [[1](#)].

### [7.1.](#) BMP Peer Flags

This document defines a new flag ([Section 3](#)):

- o Flag 3 as 0 flag

## 7.2. BMP Statistics Types

This document defines four new statistic types for statistics reporting ([Section 4.2](#)):

- o Stat Type = TBD: (64-bit Gauge) Number of routes in Adj-RIBs-Out Pre-Policy.
- o Stat Type = TBD: (64-bit Gauge) Number of routes in Adj-RIBs-Out Post-Policy.
- o Stat Type = TBD: Number of routes in per-AFI/SAFI Adj-RIB-Out Pre-Policy. The value is structured as: 2-byte Address Family Identifier (AFI), 1-byte Subsequent Address Family Identifier (SAFI), followed by a 64-bit Gauge.
- o Stat Type = TBD: Number of routes in per-AFI/SAFI Adj-RIB-Out Post-Policy. The value is structured as: 2-byte Address Family Identifier (AFI), 1-byte Subsequent Address Family Identifier (SAFI), followed by a 64-bit Gauge.

## 8. References

### 8.1. URIs

- [1] <https://www.iana.org/assignments/bmp-parameters/bmp-parameters.xhtml>

### 8.2. Normative References

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<http://www.rfc-editor.org/info/rfc2119>>.

[RFC4271] Rekhter, Y., Ed., Li, T., Ed., and S. Hares, Ed., "A Border Gateway Protocol 4 (BGP-4)", [RFC 4271](#), DOI 10.17487/RFC4271, January 2006, <<http://www.rfc->

[editor.org/info/rfc4271](http://www.rfc-editor.org/info/rfc4271)>.

[RFC7854] Scudder, J., Ed., Fernando, R., and S. Stuart, "BGP Monitoring Protocol (BMP)", [RFC 7854](https://www.rfc-editor.org/info/rfc7854), DOI 10.17487/RFC7854, June 2016, <<http://www.rfc-editor.org/info/rfc7854>>.



The authors would like to thank John Scudder for his valuable input.

## Contributors

Manish Bhardwaj  
Cisco Systems  
3700 Cisco Way  
San Jose, CA 95134  
USA

Email: manbhard@cisco.com

Xianyuzheng  
Tencent  
Tencent Building, Kejizhongyi Avenue,  
Hi-techPark, Nanshan District, Shenzhen 518057, P.R.China

Weiguo  
Tencent  
Tencent Building, Kejizhongyi Avenue,  
Hi-techPark, Nanshan District, Shenzhen 518057, P.R.China

Shugang cheng  
H3C

Authors' Addresses

Tim Evens  
Cisco Systems  
2901 Third Avenue, Suite 600  
Seattle, WA 98121  
USA

Email: [tievens@cisco.com](mailto:tievens@cisco.com)

Serpil Bayraktar  
Cisco Systems  
3700 Cisco Way  
San Jose, CA 95134  
USA

Email: [serpil@cisco.com](mailto:serpil@cisco.com)

Paolo Lucente  
NTT Communications  
Siriusdreef 70-72  
Hoofddorp 2132 WT  
NL

Email: [paolo@ntt.net](mailto:paolo@ntt.net)

Penghui Mi  
Tencent  
Tengyun Building, Tower A ,No. 397 Tianlin Road  
Shanghai 200233  
China

Email: [kevinmi@tencent.com](mailto:kevinmi@tencent.com)

Shunwan Zhuang  
Huawei  
Huawei Bld., No.156 Beiqing Rd.

Beijing 100095  
China

Evens, et al.

Expires October 1, 2017

[Page 9]

---

Internet-Draft

BMP Adj-RIB-Out

March, 2017

Email: [zhuangshunwan@huawei.com](mailto:zhuangshunwan@huawei.com)

