

NETMOD WG
Internet-Draft
Intended status: Informational
Expires: April 18, 2016

I. Farrer
Q. Sun
S. Zoric
Deutsche Telekom AG
M. Abrahamsson
T-Systems
October 16, 2015

**YANG Models Required for Managing Customer Premises Equipment (CPE)
Devices**
[draft-faq-netmod-cpe-yang-profile-00](#)

Abstract

This document collects together the YANG models necessary for managing NETCONF-enabled Customer Premises Equipment (CPE) devices.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on April 18, 2016.

Copyright Notice

Copyright (c) 2015 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4.e](#) of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1. Introduction	3
2. Terminology	3
3. Management Requirements	3
3.1. Interfaces	3
3.1.1. Requirements	4
3.1.2. Development Status of Relevant YANG Models	4
3.2. IP Management	5
3.2.1. Requirements	5
3.2.2. Development of Relevant YANG Models	5
3.3. Routing and Multicast Management	5
3.3.1. Requirements	5
3.3.2. Development of Relevant YANG Models	6
3.4. CPE NETCONF Server Management	6
3.4.1. Requirements	6
3.4.2. Development Status of Relevant YANG Models	6
3.5. DHCP/SLAAC/ND Management	7
3.5.1. Requirements	7
3.5.2. Development Status of Relevant YANG Models	7
3.6. NAT Management	8
3.6.1. Requirements	8
3.6.2. Development Status of Relevant YANG Models	8
3.7. IPv6 Transition Mechanisms Management	8
3.7.1. Requirements	8
3.7.2. Development of Relevant YANG Models	9
3.8. Management of Specific Services	9
3.8.1. Requirements	9
3.8.2. Development of Relevant YANG Models	9
3.9. Management of Security Components	10
3.9.1. Requirements	10
3.9.2. Development of Relevant YANG Models	10
3.10. Remote CPE Software Upgrade	10
3.10.1. Requirements	10
3.10.2. Development of Relevant YANG Models	11
4. Security Considerations	11
5. IANA Considerations	11
6. Acknowledgements	11
7. References	11
7.1. Normative References	11
7.2. Informative References	14
Authors' Addresses	15

Farrer, et al.

Expires April 18, 2016

[Page 2]

1. Introduction

This document defines the requirements and specifies the necessary YANG models for managing residential CPE devices using NETCONF and YANG. Implementing NETCONF on CPE devices, along with the relevant YANG models, provides operators with a flexible and extensible management interface.

Many of the YANG models referenced here are in various stages in the development process. In some cases there is currently no existing work. The aim of this document is to catalog which models are necessary, and for each referenced YANG model, provide information about the current status of the existing work. It is intended as a 'living document', which will be updated as the required / referenced YANG models progress. Once finalised, the goal of the document is to serve as a CPE YANG 'Device profile' that can be used as a reference for operators and implementors who are adding YANG management capabilities to their devices.

2. Terminology

CPE	Customer Premises Equipment; provides access between a customer's LAN connected devices and their ISP's network. In the context of this document, the CPE device implements NETCONF/YANG. This document focuses on the type of residential CPE that typically exists between the Internet Service Provider access line and residential customer home, doing similar functions that for example [RFC7084] lists.
Existing RFCs	Lists YANG models defined in published RFCs.
Work In Progress	YANG models under development in active Internet Drafts, or relevant documents being produced by SDOs other than the IETF.
To Be Defined	YANG models that are identified as necessary for CPE management, but are not currently known to be in development at the time of writing.

3. Management Requirements

3.1. Interfaces

A CPE has a number of network interfaces, usually including some of the following interface types: Ethernet LAN, Ethernet WAN, Ethernet 802.1q, Ethernet 802.1ag, and WLAN (802.11a/b/n/g/ac). [[RFC7223](#)] defines a YANG model for general interface management, which identifies these (and other) interface types. However, Ethernet

Farrer, et al.

Expires April 18, 2016

[Page 3]

standardisation is carried out by the IEEE, so it is probable where YANG models for managing these interfaces would be developed.

NB - The list of interface types necessary for a complete, general HGW model needs to include xDSL (BBF) and DOCSIS (ITU) interfaces. These will be included in a future version of this document.

3.1.1. Requirements

The following requirements are necessary for basic CPE management functionality.

INT-1: The CPE YANG implementation MUST implement general interface management.

INT-2: The CPE YANG implementation MUST enable the configuration and management for the following interface types:

- o Ethernet LAN
- o Ethernet 802.1q
- o Ethernet 802.1ag (including Ethernet CFM)
- o Ethernet WAN
- o WLAN (802.11a/b/n/g/ac)

INT-3: The CPE YANG implementation MUST provide support for optical parameter configuration for the Ethernet WAN interface YANG model.

3.1.2. Development Status of Relevant YANG Models

Existing RFCs:

- o YANG Data Model for Interface Management [[RFC7223](#)].
- o IANA Interface Type YANG Module [[RFC7224](#)].

Work In Progress:

- o IEEE 802.1q YANG Model [[IEEE-ETH-YANG](#)]
- o Common Interface Extension YANG Data Models:
[[I-D.wilton-netmod-intf-ext-yang](#)].
- o Interface VLAN YANG Data Models:
[[I-D.wilton-netmod-intf-vlan-yang](#)].

To Be Defined:

- o Ethernet WAN
- o Ethernet 802.1ag
- o Ethernet LAN
- o WLAN (802.11a/b/n/g/ac)

Farrer, et al.

Expires April 18, 2016

[Page 4]

3.2. IP Management

3.2.1. Requirements

The following requirements are necessary for the management and configuration of IPv4 and IPv6.

- IP-1: The CPE YANG implementation MUST enable the configuration and management of IPv4 addresses and associated parameters on L3 interfaces.
- IP-2: The CPE YANG implementation MUST enable the configuration and management of IPv6 addresses and associated parameters on L3 interfaces.

3.2.2. Development of Relevant YANG Models

Existing RFCs:

- o YANG Data Model for IP Management [[RFC7277](#)].

Work In Progress:

- o YANG Model for DiffServ: [[I-D.asechoud-netmod-diffserv-model](#)].

To Be Defined:

- o None

3.3. Routing and Multicast Management

3.3.1. Requirements

The following requirements are necessary for routing management.

- ROUT-1: The CPE YANG implementation MUST provide support for the configuration and management of relevant IPv4/IPv6 dynamic routing protocols (for instance the ones relevant to IETF HOMENET WG).
- ROUT-2: The CPE YANG implementation MUST include YANG models for the management of static IPv4/IPv6 routes.
- ROUT-3: The CPE YANG implementation MUST provide support for the management of Protocol Independent Multicast (PIM).
- ROUT-4: The CPE YANG implementation MUST provide support for the management of static multicast routes.

3.3.2. Development of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o YANG Data Model for Routing Management:
[[I-D.ietf-netmod-routing-cfg](#)].
- o YANG model for static IPv4/IPv6 route: [Appendix B](#) in
[[I-D.ietf-netmod-routing-cfg](#)].
- o YANG Data Model for ISIS protocol: [[I-D.ietf-isis-yang-isis-cfg](#)].
- o YANG model for PIM: [[I-D.mcallister-pim-yang](#)].
- o YANG model for IGMP and MLD: [[I-D.liu-pim-igmp-mld-yang](#)].

To Be Defined:

- o Static Multicast Route
- o What is the HOMENET relevant dynamic routing protocol.

3.4. CPE NETCONF Server Management

3.4.1. Requirements

The following requirements are necessary for management of the CPE's NETCONF Server.

- NETCONF-1: The CPE YANG implementation MUST provide support for management and configuration of its local NETCONF server using the NETCONF protocol.
- NETCONF-2: The CPE YANG implementation MUST provide support for the base notification function in order to allow a NETCONF client to retrieve notifications for common system events.
- NETCONF-3: The CPE YANG implementation MUST be able to retrieve NETCONF server configuration automatically during the bootstrap process (ZeroTouch).
- NETCONF-4: The CPE YANG implementation as a NETCONF server MUST provide support for the Call Home function so that a secure connection to a NETCONF client can be initiated.

3.4.2. Development Status of Relevant YANG Models

Existing RFCs:

- o YANG Module for NETCONF Monitoring: [[RFC6022](#)].
- o NETCONF Base Notifications: [[RFC6470](#)].

Farrer, et al.

Expires April 18, 2016

[Page 6]

Work In Progress:

- o ZeroTouch: [[I-D.ietf-netconf-zerotouch](#)].
- o NETCONF Call Home: [[I-D.ietf-netconf-call-home](#)].
- o NETCONF Server Configuration Models:
[[I-D.ietf-netconf-server-model](#)].

To Be Defined:

- o None

3.5. DHCP/SLAAC/ND Management

3.5.1. Requirements

The following requirements are necessary for management of DHCP, SLAAC and ND.

- V6CONF-1: The CPE YANG implementation MUST provide support for management of its DHCPv4 server, which typically runs at the IPv4 LAN side.
- V6CONF-2: The CPE YANG implementation MUST provide support for the management of its DHCPv6 server, which can run at the IPv6 LAN side.
- V6CONF-3: The CPE YANG implementation MUST provide support for the management of its DHCPv6 client, which typically runs at the IPv6 WAN side.
- V6CONF-4: The CPE YANG implementation MUST provide support for the management of its DHCPv6 Prefix Delegation configuration (as a requesting router).
- V6CONF-5: The CPE YANG implementation MUST provide support for the management of SLAAC for stateless IPv6 configuration.

3.5.2. Development Status of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o YANG models for DHCPv4: [[I-D.liu-dhc-dhcp-yang-model](#)].
- o YANG Data Model for DHCPv6 Configuration:
[[I-D.cui-dhc-dhcpv6-yang](#)].

To Be Defined:

- o YANG model for SLAAC (Router Advertisement)

Farrer, et al.

Expires April 18, 2016

[Page 7]

- o YANG model for Neighbour Discovery Protocol (NDP)
- o YANG model for DHCPv6 Prefix Delegation (requesting router)
- o YANG model for IPCP.
- o YANG model for IPv6CP.

3.6. NAT Management

3.6.1. Requirements

The following requirements are necessary for NAT Management.

- NAT-1: The CPE YANG implementation MUST provide support for management of NAT44 configuration, as well as NAPT44 configuration.

3.6.2. Development Status of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o YANG Data Model for NAT44 and stateful NAT64 function [[I-D.sivakumar-yang-nat](#)].

To Be Defined:

- o None

3.7. IPv6 Transition Mechanisms Management

3.7.1. Requirements

The following requirements are necessary for management of IPv6 Transition Mechanisms.

- TRAN-2: The CPE YANG implementation must include configuration and management for 6rd [[RFC5969](#)].
- TRAN-2: The CPE YANG implementation must include configuration and management for DS-Lite [[RFC6333](#)].
- TRAN-3: The CPE YANG implementation must include configuration and management for Lightweight 4over6 [[RFC7596](#)].
- TRAN-4: The CPE YANG implementation must include configuration and management for MAP-E [[RFC7597](#)].
- TRAN-5: The CPE YANG implementation must include configuration and management for MAP-T [[RFC7599](#)].

3.7.2. Development of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o YANG model for IPv4-in-IPv6 Softwire: [[I-D.sun-softwire-yang](#)].
- o YANG Data Model for the DS-Lite Address Family Transition Router (AFTR): [[I-D.boucadair-softwire-dslite-yang](#)].

To Be Defined:

- o YANG model for 6rd.
- o DHCP 4o6 client: May be combined in DHCPv6 YANG model as a feature.
- o DNS64
- o Stateless NAT64 (required for MAP-T and 464xlat).

3.8. Management of Specific Services

3.8.1. Requirements

The following requirements are necessary for management of specific services which the CPE may offer.

- SERVICE-1: The CPE YANG implementation MUST provide support for the management of a SIP client.
- SERVICE-2: The CPE YANG implementation MUST provide support for the management of a the CPEs Web server (used to provide a local management interface).
- SERVICE-3: The CPE YANG implementation MUST provide support for the management of an NTP client and server.
- SERVICE-4: The CPE YANG implementation MUST provide support for the management of the SSH server.

3.8.2. Development of Relevant YANG Models

Existing RFCs:

- o NTP Client: [[RFC7317](#)]

Work In Progress:

- o None

To Be Defined:

Farrer, et al.

Expires April 18, 2016

[Page 9]

- o SIP Client
- o Web server, used by the customer for configuring their CPE device.
- o NTP server
- o SSH server

3.9. Management of Security Components

3.9.1. Requirements

The following requirements are necessary for management of security components.

- SEC-1: The CPE YANG implementation MUST provide support for the management of IPv4 firewall and ACL functions.
- SEC-1: The CPE YANG implementation MUST provide support for the management of IPv6 firewall and ACL functions.

3.9.2. Development of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o IPv4 Firewall configuration: [[I-D.ietf-netmod-acl-model](#)]
- o IPv6 Firewall configuration: [[I-D.ietf-netmod-acl-model](#)]
- o Access Control List (ACL): [[I-D.ietf-netmod-acl-model](#)]

To Be Defined:

- o IPv4/v6 Firewall (if needed in addition to the above)
- o Parental controls

3.10. Remote CPE Software Upgrade

3.10.1. Requirements

The following requirements are necessary to perform remote CPE Software file transfer and software upgrades.

- SWUPG-1: The CPE implementation must provide a YANG model for the upgrade of firmware and software packages in order to fix bugs, enable new features, and resolve security issues.
- SWUPG-2: The CPE YANG implementation MUST enable RPCs for file transfer in order to retrieve files from an operator-managed data centre, or upload logging.

3.10.2. Development of Relevant YANG Models

Existing RFCs:

- o None

Work In Progress:

- o File transfer: [[I-D.sf-netmod-file-transfer-yang](#)]

To Be Defined:

- o YANG model for firmware upgrade RPCs

4. Security Considerations

A NETCONF/YANG managed CPE should follow the [Section 3.9](#) for enabling and managing IPv4/IPv6 firewalls. Security considerations from the related documents should be followed.

5. IANA Considerations

There are no IANA considerations for this document.

6. Acknowledgements

The authors would like to thank xxx for their contributions to this work.

7. References

7.1. Normative References

[I-D.asechoud-netmod-diffserv-model]

Choudhary, A., Shah, S., Jethanandani, M., Liu, B., and N. Strahle, "YANG Model for Diffserv", [draft-asechoud-netmod-diffserv-model-03](#) (work in progress), June 2015.

[I-D.boucadair-softwire-dslite-yang]

Boucadair, M., Jacquet, C., and S. Sivakumar, "YANG Data Model for the DS-Lite Address Family Transition Router (AFTR)", [draft-boucadair-softwire-dslite-yang-02](#) (work in progress), September 2015.

[I-D.cui-dhc-dhcpv6-yang]

Cui, Y., Wang, H., Sun, L., Lemon, T., and I. Farrer, "YANG Data Model for DHCPv6 Configuration", [draft-cui-dhc-dhcpv6-yang-04](#) (work in progress), September 2015.

[I-D.ietf-isis-yang-isis-cfg]

Litkowski, S., Yeung, D., Lindem, A., Zhang, J., and L. Lhotka, "YANG Data Model for ISIS protocol", [draft-ietf-isis-yang-isis-cfg-06](#) (work in progress), September 2015.

[I-D.ietf-netconf-call-home]

Watsen, K., "NETCONF Call Home and RESTCONF Call Home", [draft-ietf-netconf-call-home-11](#) (work in progress), September 2015.

[I-D.ietf-netconf-server-model]

Watsen, K. and J. Schoenwaelder, "NETCONF Server and RESTCONF Server Configuration Models", [draft-ietf-netconf-server-model-08](#) (work in progress), October 2015.

[I-D.ietf-netconf-zerotouch]

Watsen, K., Clarke, J., and M. Abrahamsson, "Zero Touch Provisioning for NETCONF Call Home (ZeroTouch)", [draft-ietf-netconf-zerotouch-03](#) (work in progress), July 2015.

[I-D.ietf-netmod-acl-model]

Bogdanovic, D., Sreenivasa, K., Huang, L., and D. Blair, "Network Access Control List (ACL) YANG Data Model", [draft-ietf-netmod-acl-model-03](#) (work in progress), June 2015.

[I-D.ietf-netmod-routing-cfg]

Lhotka, L. and A. Lindem, "A YANG Data Model for Routing Management", [draft-ietf-netmod-routing-cfg-19](#) (work in progress), May 2015.

[I-D.liu-dhc-dhcp-yang-model]

Liu, B. and K. Lou, "A YANG Data Model for DHCP Configuration", [draft-liu-dhc-dhcp-yang-model-01](#) (work in progress), July 2015.

[I-D.liu-pim-igmp-mld-yang]

Liu, Y. and F. Guo, "Yang Model for Internet Group Management Protocol (IGMP) and Multicast Listener Discovery (MLD)", [draft-liu-pim-igmp-mld-yang-01](#) (work in progress), March 2015.

[I-D.mcallister-pim-yang]

Liu, X., McAllister, P., and A. Peter, "A YANG data model for Protocol-Independent Multicast (PIM)", [draft-mcallister-pim-yang-00](#) (work in progress), July 2015.

Farrer, et al.

Expires April 18, 2016

[Page 12]

[I-D.perrault-behave-natv2-mib]

Perreault, S., Tsou, T., Sivakumar, S., and T. Taylor,
"Definitions of Managed Objects for Network Address
Translators (NAT)", [draft-perrault-behave-natv2-mib-05](#)
(work in progress), June 2015.

[I-D.sf-netmod-file-transfer-yang]

Sun, Q. and I. Farrer, "A YANG Data Model for Transferring
Files", [draft-sf-netmod-file-transfer-yang-00](#) (work in
progress), March 2015.

[I-D.sivakumar-yang-nat]

Sivakumar, S., Boucadair, M., and S. <>, "YANG Data Model
for Network Address Translation (NAT)", [draft-sivakumar-](#)
[yang-nat-03](#) (work in progress), September 2015.

[I-D.sun-softwire-yang]

Sun, Q., Wang, H., Cui, Y., Farrer, I., Boucadair, M., and
R. Asati, "YANG Data Model for IPv4-in-IPv6 Softwire",
[draft-sun-softwire-yang-04](#) (work in progress), October
2015.

[I-D.wilton-netmod-intf-ext-yang]

Wilton, R., Ball, D., Singh, T., and S. Sivaraj, "Common
Interface Extension YANG Data Models", [draft-wilton-](#)
[netmod-intf-ext-yang-00](#) (work in progress), July 2015.

[I-D.wilton-netmod-intf-vlan-yang]

Wilton, R., Ball, D., Singh, T., and S. Sivaraj,
"Interface VLAN YANG Data Models", [draft-wilton-netmod-](#)
[intf-vlan-yang-00](#) (work in progress), July 2015.

[IEEE-ETH-YANG]

"IEEE 802.1q YANG Model",
<http://www.ieee802.org/1/files/public/docs2015/>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate
Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/
[RFC2119](#), March 1997,
<http://www.rfc-editor.org/info/rfc2119>.

[RFC6022] Scott, M. and M. Bjorklund, "YANG Module for NETCONF
Monitoring", [RFC 6022](#), DOI 10.17487/RFC6022, October 2010,
<http://www.rfc-editor.org/info/rfc6022>.

[RFC6470] Bierman, A., "Network Configuration Protocol (NETCONF)
Base Notifications", [RFC 6470](#), DOI 10.17487/RFC6470,
February 2012, <http://www.rfc-editor.org/info/rfc6470>.

Farrer, et al.

Expires April 18, 2016

[Page 13]

- [RFC7223] Bjorklund, M., "A YANG Data Model for Interface Management", [RFC 7223](#), DOI 10.17487/RFC7223, May 2014, <<http://www.rfc-editor.org/info/rfc7223>>.
- [RFC7224] Bjorklund, M., "IANA Interface Type YANG Module", [RFC 7224](#), DOI 10.17487/RFC7224, May 2014, <<http://www.rfc-editor.org/info/rfc7224>>.
- [RFC7277] Bjorklund, M., "A YANG Data Model for IP Management", [RFC 7277](#), DOI 10.17487/RFC7277, June 2014, <<http://www.rfc-editor.org/info/rfc7277>>.
- [RFC7317] Bierman, A. and M. Bjorklund, "A YANG Data Model for System Management", [RFC 7317](#), DOI 10.17487/RFC7317, August 2014, <<http://www.rfc-editor.org/info/rfc7317>>.

7.2. Informative References

- [RFC5969] Townsley, W. and O. Troan, "IPv6 Rapid Deployment on IPv4 Infrastructures (6rd) -- Protocol Specification", [RFC 5969](#), DOI 10.17487/RFC5969, August 2010, <<http://www.rfc-editor.org/info/rfc5969>>.
- [RFC6333] Durand, A., Droms, R., Woodyatt, J., and Y. Lee, "Dual-Stack Lite Broadband Deployments Following IPv4 Exhaustion", [RFC 6333](#), DOI 10.17487/RFC6333, August 2011, <<http://www.rfc-editor.org/info/rfc6333>>.
- [RFC7084] Singh, H., Beebee, W., Donley, C., and B. Stark, "Basic Requirements for IPv6 Customer Edge Routers", [RFC 7084](#), DOI 10.17487/RFC7084, November 2013, <<http://www.rfc-editor.org/info/rfc7084>>.
- [RFC7596] Cui, Y., Sun, Q., Boucadair, M., Tsou, T., Lee, Y., and I. Farrer, "Lightweight 4over6: An Extension to the Dual-Stack Lite Architecture", [RFC 7596](#), DOI 10.17487/RFC7596, July 2015, <<http://www.rfc-editor.org/info/rfc7596>>.
- [RFC7597] Troan, O., Ed., Dec, W., Li, X., Bao, C., Matsushima, S., Murakami, T., and T. Taylor, Ed., "Mapping of Address and Port with Encapsulation (MAP-E)", [RFC 7597](#), DOI 10.17487/[RFC7597](#), July 2015, <<http://www.rfc-editor.org/info/rfc7597>>.
- [RFC7599] Li, X., Bao, C., Dec, W., Ed., Troan, O., Matsushima, S., and T. Murakami, "Mapping of Address and Port using Translation (MAP-T)", [RFC 7599](#), DOI 10.17487/RFC7599, July 2015, <<http://www.rfc-editor.org/info/rfc7599>>.

Farrer, et al.

Expires April 18, 2016

[Page 14]

Authors' Addresses

Ian Farrer
Deutsche Telekom AG
CTO-ATI, Landgrabenweg 151
Bonn, NRW 53227
Germany

Email: ian.farrer@telekom.de

Qi Sun
Deutsche Telekom AG
CTO-ATI, Landgrabenweg 151
Bonn, NRW 53227
Germany

Email: sunqi.ietf@gmail.com

Sladjana Zoric
Deutsche Telekom AG
CTO-IPT, Landgrabenweg 151
Bonn, NRW 53227
Germany

Email: sladjana.zoric@telekom.de

Mikael Abrahamsson
T-Systems

Email: mikael.abrahamsson@t-systems.se

