

Internet Engineering Task Force  
INTERNET-DRAFT  
[draft-floyd-rfc3448bis-00.txt](#)  
Expires: December 2006

M. Handley  
University College London  
S. Floyd  
ICIR  
J. Padhye  
Microsoft  
J. Widmer  
University of Mannheim  
18 June 2006

## **TCP Friendly Rate Control (TFRC): Protocol Specification**

### Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.

This Internet-Draft will expire on December 2006.

## Abstract

This document specifies TCP-Friendly Rate Control (TFRC). TFRC is a congestion control mechanism for unicast flows operating in a best-effort Internet environment. It is reasonably fair when competing for bandwidth with TCP flows, but has a much lower variation of throughput over time compared with TCP, making it more suitable for applications such as telephony or streaming media where a relatively smooth sending rate is of importance.

## Table of Contents

<a href="#">1.</a>	<a href="#">Introduction</a>	<a href="#">6</a>
<a href="#">2.</a>	<a href="#">Conventions</a>	<a href="#">7</a>
<a href="#">3.</a>	<a href="#">Protocol Mechanism</a>	<a href="#">7</a>
<a href="#">3.1.</a>	<a href="#">TCP Throughput Equation</a>	<a href="#">8</a>
<a href="#">3.2.</a>	<a href="#">Packet Contents</a>	<a href="#">9</a>
<a href="#">3.2.1.</a>	<a href="#">Data Packets</a>	<a href="#">10</a>
<a href="#">3.2.2.</a>	<a href="#">Feedback Packets</a>	<a href="#">10</a>
<a href="#">4.</a>	<a href="#">Data Sender Protocol</a>	<a href="#">11</a>
<a href="#">4.1.</a>	<a href="#">Measuring the Segment Size</a>	<a href="#">11</a>
<a href="#">4.2.</a>	<a href="#">Sender Initialization</a>	<a href="#">12</a>
<a href="#">4.3.</a>	<a href="#">Sender behavior when a feedback packet is received</a>	<a href="#">13</a>
<a href="#">4.4.</a>	<a href="#">Expiration of nofeedback timer</a>	<a href="#">14</a>
<a href="#">4.5.</a>	<a href="#">Sending a packet after an idle period</a>	<a href="#">15</a>
<a href="#">4.6.</a>	<a href="#">Preventing Oscillations</a>	<a href="#">15</a>
<a href="#">4.7.</a>	<a href="#">Scheduling of Packet Transmissions</a>	<a href="#">16</a>
<a href="#">5.</a>	<a href="#">Calculation of the Loss Event Rate (p)</a>	<a href="#">17</a>
<a href="#">5.1.</a>	<a href="#">Detection of Lost or Marked Packets</a>	<a href="#">17</a>
<a href="#">5.2.</a>	<a href="#">Translation from Loss History to Loss Events</a>	<a href="#">18</a>
<a href="#">5.3.</a>	<a href="#">Inter-loss Event Interval</a>	<a href="#">19</a>
<a href="#">5.4.</a>	<a href="#">Average Loss Interval</a>	<a href="#">19</a>
<a href="#">5.5.</a>	<a href="#">History Discounting</a>	<a href="#">20</a>
<a href="#">6.</a>	<a href="#">Data Receiver Protocol</a>	<a href="#">23</a>
<a href="#">6.1.</a>	<a href="#">Receiver behavior when a data packet is received</a>	<a href="#">23</a>
<a href="#">6.2.</a>	<a href="#">Expiration of feedback timer</a>	<a href="#">24</a>
<a href="#">6.3.</a>	<a href="#">Receiver initialization</a>	<a href="#">24</a>
<a href="#">6.3.1.</a>	<a href="#">Initializing the Loss History after the First Loss Event</a>	<a href="#">25</a>
<a href="#">7.</a>	<a href="#">Sender-based Variants</a>	<a href="#">25</a>
<a href="#">8.</a>	<a href="#">Implementation Issues</a>	<a href="#">26</a>
<a href="#">9.</a>	<a href="#">Changes from <a href="#">RFC 3448</a></a>	<a href="#">27</a>
<a href="#">10.</a>	<a href="#">Security Considerations</a>	<a href="#">28</a>
<a href="#">11.</a>	<a href="#">IANA Considerations</a>	<a href="#">28</a>
<a href="#">12.</a>	<a href="#">Acknowledgments</a>	<a href="#">28</a>
<a href="#">13.</a>	<a href="#">Normative References</a>	<a href="#">29</a>
<a href="#">14.</a>	<a href="#">Informational References</a>	<a href="#">29</a>
<a href="#">15.</a>	<a href="#">Authors' Addresses</a>	<a href="#">30</a>
	<a href="#">Full Copyright Statement</a>	<a href="#">31</a>
	<a href="#">Intellectual Property</a>	<a href="#">31</a>



NOTE TO RFC EDITOR: PLEASE DELETE THIS NOTE UPON PUBLICATION.

Changes from [RFC 3448](#):

- \* Incorporated changes in the [RFC 3448](#) errata:
  - "If the sender does not receive a feedback report for four round trip times, it cuts its sending rate in half." ("Two" changed to "four", for consistency with the rest of the document. Reported by Joerg Widmer).
  - "If the nofeedback timer expires when the sender does not yet have an RTT sample, and has not yet received any feedback from the receiver, or when  $p == 0, \dots$ " (Added "or when  $p == 0,$ ", reported by Wim Heirman).
  - In [Section 5.5](#), changed:

```
for (i = 1 to n) { DF_i = 1; }
to:
for (i = 0 to n) { DF_i = 1; }
```

Reported by Michele R.
- \* Changed [RFC 3448](#) to correspond to the larger initial windows specified in [RFC 3390](#). This includes the following:
  - Incorporated [Section 5.1](#) from [[RFC4342](#)], saying that when reducing the sending rate after an idle period, don't reduce the sending rate below the initial sending rate.
  - Change for a datalimited sender:  
When the sender has been datalimited, the sender doesn't let the receive rate limit it to a sending rate less than the initial rate.
  - Small change to slow-start:  
Changed so that for the first feedback packet received, or for the first feedback packet received after an idle period, the receive rate is not used to limit the sending rate. This is because the receiver might not yet have seen an entire window of data.
- \* Clarified how the average loss interval is calculated when the receiver has not yet seen eight loss intervals.
- \* Discussed more about estimating the average segment size:
  - For initializing the loss history after the first loss event, either the receiver knows the sender's value for  $s$ , or the receiver uses the throughput equation for  $X_{pps}$  and does



not need to know an estimate for  $s$ .

- Added a discussion about estimating the average segment size  $s$  in [Section 4.1](#) on "Measuring the Segment Size".
- Changed "packet size" to "segment size".

END OF NOTE TO RFC EDITOR.

## **1. Introduction**

This document specifies TCP-Friendly Rate Control (TFRC). TFRC is a congestion control mechanism designed for unicast flows operating in an Internet environment and competing with TCP traffic [[FHPW00](#)]. Instead of specifying a complete protocol, this document simply specifies a congestion control mechanism that could be used in a transport protocol such as DCCP (Datagram Congestion Control Protocol) [[RFC4340](#)], in an application incorporating end-to-end congestion control at the application level, or in the context of endpoint congestion management [[BRS99](#)]. This document does not discuss packet formats or reliability. Implementation-related issues are discussed only briefly, in [Section 8](#).

TFRC is designed to be reasonably fair when competing for bandwidth with TCP flows, where a flow is "reasonably fair" if its sending rate is generally within a factor of two of the sending rate of a TCP flow under the same conditions. However, TFRC has a much lower variation of throughput over time compared with TCP, which makes it more suitable for applications such as telephony or streaming media where a relatively smooth sending rate is of importance.

The penalty of having smoother throughput than TCP while competing fairly for bandwidth is that TFRC responds slower than TCP to changes in available bandwidth. Thus TFRC should only be used when the application has a requirement for smooth throughput, in particular, avoiding TCP's halving of the sending rate in response to a single packet drop. For applications that simply need to transfer as much data as possible in as short a time as possible we recommend using TCP, or if reliability is not required, using an Additive-Increase, Multiplicative-Decrease (AIMD) congestion control scheme with similar parameters to those used by TCP.

TFRC is designed for applications that use a fixed segment size, and vary their sending rate in packets per second in response to congestion. TFRC can also be used by applications that don't have a fixed segment size, but where the segment size varies according to the needs of the application (e.g., video applications).

Some applications (e.g., some audio applications) require a fixed interval of time between packets and vary their segment size instead of their packet rate in response to congestion. The congestion control mechanism in this document is not designed for those applications; TFRC-SP (Small-Packet TFRC) is a variant of TFRC for applications that have a fixed sending rate in packets per second but either use small packets, or vary their packet size in response to congestion. TFRC-SP will be specified in a later document.





This document specifies TFRC as a receiver-based mechanism, with the calculation of the congestion control information (i.e., the loss event rate) in the data receiver rather in the data sender. This is well-suited to an application where the sender is a large server handling many concurrent connections, and the receiver has more memory and CPU cycles available for computation. In addition, a receiver-based mechanism is more suitable as a building block for multicast congestion control. However, it is also possible to implement TFRC in sender-based variants, as allowed in DCCP's Congestion Control ID 3 (CCID 3) [[RFC4342](#)].

## **2. Conventions**

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#).

## **3. Protocol Mechanism**

For its congestion control mechanism, TFRC directly uses a throughput equation for the allowed sending rate as a function of the loss event rate and round-trip time. In order to compete fairly with TCP, TFRC uses the TCP throughput equation, which roughly describes TCP's sending rate as a function of the loss event rate, round-trip time, and segment size. We define a loss event as one or more lost or marked packets from a window of data, where a marked packet refers to a congestion indication from Explicit Congestion Notification (ECN) [[RFC3168](#)].

Generally speaking, TFRC's congestion control mechanism works as follows:

- o The receiver measures the loss event rate and feeds this information back to the sender.
- o The sender also uses these feedback messages to measure the round-trip time (RTT).
- o The loss event rate and RTT are then fed into TFRC's throughput equation, giving the acceptable transmit rate.
- o The sender then adjusts its transmit rate to match the calculated rate.

The dynamics of TFRC are sensitive to how the measurements are performed and applied. We recommend specific mechanisms below to perform and apply these measurements. Other mechanisms are possible, but it is important to understand how the interactions



between mechanisms affect the dynamics of TFRC.

### 3.1. TCP Throughput Equation

Any realistic equation giving TCP throughput as a function of loss event rate and RTT should be suitable for use in TFRC. However, we note that the TCP throughput equation used must reflect TCP's retransmit timeout behavior, as this dominates TCP throughput at higher loss rates. We also note that the assumptions implicit in the throughput equation about the loss event rate parameter have to be a reasonable match to how the loss rate or loss event rate is actually measured. While this match is not perfect for the throughput equation and loss rate measurement mechanisms given below, in practice the assumptions turn out to be close enough.

The throughput equation we currently recommend for TFRC is a slightly simplified version of the throughput equation for Reno TCP from [PFTK98]. Ideally we'd prefer a throughput equation based on SACK TCP, but no one has yet derived the throughput equation for SACK TCP, and from both simulations and experiments, the differences between the two equations are relatively minor.

The throughput equation is:

$$X = \frac{s}{R \sqrt{2bp/3} + (t_{\text{RTO}} * (3 \sqrt{3bp/8} * p * (1 + 32p^2)))}$$

Where:

X is the transmit rate in bytes/second.

s is the segment size in bytes.

R is the round trip time in seconds.

p is the loss event rate, between 0 and 1.0, of the number of loss events as a fraction of the number of packets transmitted.

t\_RTO is the TCP retransmission timeout value in seconds.

b is the number of packets acknowledged by a single TCP acknowledgement.



We further simplify this by setting  $t_{RT0} = 4 \cdot R$ . A more accurate calculation of  $t_{RT0}$  is possible, but experiments with the current setting have resulted in reasonable fairness with existing TCP implementations [W00]. Another possibility would be to set  $t_{RT0} = \max(4R, \text{one second})$ , to match the recommended minimum of one second on the RTT [RFC2988].

Many current TCP connections use delayed acknowledgements, sending an acknowledgement for every two data packets received, and thus have a sending rate modeled by  $b = 2$ . However, TCP is also allowed to send an acknowledgement for every data packet, and this would be modeled by  $b = 1$ . Because many TCP implementations do not use delayed acknowledgements, we recommend  $b = 1$ .

In future, different TCP equations may be substituted for this equation. The requirement is that the throughput equation be a reasonable approximation of the sending rate of TCP for conformant TCP congestion control.

The throughput equation can also be expressed as

$$X = X_{pps} \cdot s ,$$

with  $X_{pps}$ , the sending rate in packets per second, given as

$$X_{pps} = \frac{1}{R \cdot \sqrt{2 \cdot b \cdot p / 3} + (t_{RT0} \cdot (3 \cdot \sqrt{3 \cdot b \cdot p / 8}) \cdot p \cdot (1 + 32 \cdot p^2))}$$

The parameters  $s$  (segment size),  $p$  (loss event rate) and  $R$  (RTT) need to be measured or calculated by a TFRC implementation. The measurement of  $s$  is specified in [Section 4.1](#), measurement of  $R$  is specified in [Section 4.3](#), and measurement of  $p$  is specified in [Section 5](#). In the rest of this document all data rates are measured in bytes/second.

### **[3.2.](#) Packet Contents**

Before specifying the sender and receiver functionality, we describe the contents of the data packets sent by the sender and feedback packets sent by the receiver. As TFRC will be used along with a transport protocol, we do not specify packet formats, as these depend on the details of the transport protocol used.



### **3.2.1. Data Packets**

Each data packet sent by the data sender contains the following information:

- o A sequence number. This number is incremented by one for each data packet transmitted. The field must be sufficiently large that it does not wrap causing two different packets with the same sequence number to be in the receiver's recent packet history at the same time.
- o A timestamp indicating when the packet is sent. We denote by  $ts_i$  the timestamp of the packet with sequence number  $i$ . The resolution of the timestamp should typically be measured in milliseconds.  
This timestamp is used by the receiver to determine which losses belong to the same loss event. The timestamp is also echoed by the receiver to enable the sender to estimate the round-trip time, for senders that do not save timestamps of transmitted data packets.  
We note that as an alternative to a timestamp incremented in milliseconds, a "timestamp" that increments every quarter of a round-trip time would be sufficient for determining when losses belong to the same loss event, in the context of a protocol where this is understood by both sender and receiver, and where the sender saves the timestamps of transmitted data packets.
- o The sender's current estimate of the round trip time. The estimate reported in packet  $i$  is denoted by  $R_i$ . The round-trip time estimate is used by the receiver, along with the timestamp, to determine when multiple losses belong to the same loss event. If the sender sends a coarse-grained "timestamp" that increments every quarter of a round-trip time, as discussed above, then the sender does not need to send its current estimate of the round trip time.

### **3.2.2. Feedback Packets**

Each feedback packet sent by the data receiver contains the following information:

- o The timestamp of the last data packet received. We denote this by  $t_{recvdata}$ . If the last packet received at the receiver has sequence number  $i$ , then  $t_{recvdata} = ts_i$ .  
This timestamp is used by the sender to estimate the round-trip time, and is only needed if the sender does not save timestamps





of transmitted data packets.

- o The amount of time elapsed between the receipt of the last data packet at the receiver, and the generation of this feedback report. We denote this by  $t_{\text{delay}}$ .
- o The rate at which the receiver estimates that data was received since the last feedback report was sent. We denote this by  $X_{\text{recv}}$ .
- o The receiver's current estimate of the loss event rate,  $p$ .

#### **4. Data Sender Protocol**

The data sender sends a stream of data packets to the data receiver at a controlled rate. When a feedback packet is received from the data receiver, the data sender changes its sending rate, based on the information contained in the feedback report. If the sender does not receive a feedback report for four round trip times, it cuts its sending rate in half. This is achieved by means of a timer called the nofeedback timer.

We specify the sender-side protocol in the following steps:

- o Measurement of the mean segment size being sent.
- o The sender behavior when a feedback packet is received.
- o The sender behavior when the nofeedback timer expires.
- o Oscillation prevention (optional)
- o Scheduling of transmission on non-realtime operating systems.

##### **4.1. Measuring the Segment Size**

The parameter  $s$  (segment size) is normally known to an application. This may not be so in two cases:

- o (1) The segment size naturally varies depending on the data. In this case, although the segment size varies, that variation is not coupled to the transmit rate. The TFRC sender can either compute the average segment size or use the maximum segment size for the segment size  $s$ .



- o (2) The application needs to change the segment size rather than the number of segments per second to perform congestion control. This would normally be the case with packet audio applications where a fixed interval of time needs to be represented by each packet. Such applications need to have a completely different way of measuring parameters.

For the first class of applications where the segment size varies depending on the data, the sender MAY estimate the segment size  $s$  as the average segment size over the last four loss intervals. The sender MAY also estimate the average segment size over longer time intervals, if so desired. The TFRC sender uses the segment size  $s$  in the throughput equation, in the setting of the maximum receive rate and the minimum sending rate, and in the setting of the nofeedback timer.

The TFRC receiver may use the average segment size  $s$  in initializing the loss history after the first loss event, but [Section 6.3.1](#) also gives an alternate procedure that does not use the average segment size  $s$ .

The second class of applications are discussed separately in a separate document on TFRC-SP. For the remainder of this section we assume the sender can estimate the segment size, and that congestion control is performed by adjusting the number of packets sent per second.

#### [4.2.](#) Sender Initialization

The initial values for  $X$  and  $tld$  are undefined until they are set as described below. If the sender is ready to send data when it does not yet have a round trip sample, the value of  $X$  is set to 1 packet/second, the nofeedback timer is set to expire after 2 seconds, and the  $tld$ , the Time Last Doubled during slow-start, is set to -1. Upon receiving a round trip time measurement (e.g., after the first feedback packet),  $tld$  is set to the current time, and the transmit rate  $X$  is set to  $W_{init}/R$ , for  $W_{init}$  below from [\[RFC3390\]](#):

$$W_{init} = \min(4 * MSS, \max(2 * MSS, 4380)),$$

for  $MSS$  the Maximum Segment Size. For responding to the initial feedback packet, this replaces step (4) of [Section 4.3](#) below.

If the sender does have a round trip sample when it is ready to first send data (e.g., from the SYN exchange or from a previous



connection [[RFC2140](#)]), the initial transmit rate  $X$  is set to  $W_{init}/R$ , and  $tld$  is set to the current time.

#### **4.3. Sender behavior when a feedback packet is received**

The sender knows its current sending rate,  $X$ , and maintains an estimate of the current round trip time,  $R$ , and an estimate of the timeout interval,  $t_{RTO}$ .

When a feedback packet is received by the sender at time  $t_{now}$ , the following actions should be performed:

- 1) Calculate a new round trip sample.  
 $R_{sample} = (t_{now} - t_{recvdata}) - t_{delay}$ .

- 2) Update the round trip time estimate:

```
If no feedback has been received before
    R = R_sample;
Else
    R = q*R + (1-q)*R_sample;
```

TFRC is not sensitive to the precise value for the filter constant  $q$ , but we recommend a default value of 0.9.

- 3) Update the timeout interval:

```
 $t_{RTO} = 4 * R$ .
```

- 4) Update the sending rate as follows:

```
If (sender has been idle or data-limited)
    min_rate = max(2*X_recv, W_init/R);
Else
    min_rate = 2*X_recv;
If (p > 0)
    Calculate X_calc using the TCP throughput equation.
    X = max(min(X_calc, min_rate), s/t_mbi);
Else if (not the first feedback packet, and
    not the first feedback packet after a nofeedback timer)
    If (t_now - tld >= R)
        X = max(min(2*X, min_rate), s/R);
        tld = t_now;
```



The condition ``if (sender has been idle or data-limited)'' prevents an idle or data-limited sender from having to reduce the sending rate to less than the initial sending rate as a result of limitations from a small receive rate. The condition ``if (not the first feedback packet, and not the first feedback packet after a nofeedback timer)'' prevents a sender from reducing the sending rate in response to a feedback packet that reports the receipt of only a few packets after start-up or after an idle period.

Note that if  $p == 0$ , then the sender is in slow-start phase, where it approximately doubles the sending rate each round-trip time until a loss occurs. The  $s/R$  term gives a minimum sending rate during slow-start of one packet per RTT. The parameter  $t\_mbi$  is 64 seconds, and represents the maximum inter-packet backoff interval in the persistent absence of feedback. Thus, when  $p > 0$  the sender sends at least one packet every 64 seconds.

- 5) Reset the nofeedback timer to expire after  $\max(4 \cdot R, 2 \cdot s/X)$  seconds.

#### **4.4. Expiration of nofeedback timer**

If the nofeedback timer expires, the sender should perform the following actions:

- 1) Cut the sending rate in half. If the sender has received feedback from the receiver, this is done by modifying the sender's cached copy of  $X\_recv$  (the receive rate). Because the sending rate is limited to at most twice  $X\_recv$ , modifying  $X\_recv$  limits the current sending rate, but allows the sender to slow-start, doubling its sending rate each RTT, if feedback messages resume reporting no losses.

```
If ( $X\_calc > 2 \cdot X\_recv$ )
     $X\_recv = \max(X\_recv/2, s/(2 \cdot t\_mbi));$ 
Else
     $X\_recv = X\_calc/4;$ 
```

The term  $s/(2 \cdot t\_mbi)$  limits the backoff to one packet every 64 seconds in the case of persistent absence of feedback.

- 2) The value of  $X$  must then be recalculated as described under point (4) above.

If the nofeedback timer expires when the sender does not yet have an RTT sample and has not yet received any feedback from





the receiver, or when  $p == 0$ , then step (1) can be skipped, and the sending rate cut in half directly:

$$X = \max(X/2, s/t_{mbi})$$

- 3) Restart the nofeedback timer to expire after  $\max(4*R, 2*s/X)$  seconds.

Note that when the sender stops sending, the receiver will stop sending feedback. This will cause the nofeedback timer to start to expire and decrease  $X_{recv}$ . If the sender subsequently starts to send again,  $X_{recv}$  will limit the transmit rate, and a normal slowstart phase will occur until the transmit rate reaches  $X_{calc}$ .

#### **4.5. Sending a packet after an idle period**

If the sender has been idle (unable to send because there is no data from the application), the allowed sending rate could have been reduced due to the nofeedback timer, as specified in the section above. Because the sender is always restricted to sending at most twice the receive rate reported by the receiver, the sender will be limited to at most doubling its sending rate each round-trip time, until the sending rate reaches the allowed sending rate calculated by the throughput equation.

#### **4.6. Preventing Oscillations**

To prevent oscillatory behavior in environments with a low degree of statistical multiplexing it is useful to modify sender's transmit rate to provide congestion avoidance behavior by reducing the transmit rate as the queuing delay (and hence RTT) increases. To do this the sender maintains an estimate of the long-term RTT and modifies its sending rate depending on how the most recent sample of the RTT differs from this value. The long-term sample is  $R_{sqmean}$ , and is set as follows:

```
If no feedback has been received before
     $R_{sqmean} = \sqrt{R_{sample}}$ ;
Else
     $R_{sqmean} = q2 * R_{sqmean} + (1-q2) * \sqrt{R_{sample}}$ ;
```

Thus  $R_{sqmean}$  gives the exponentially weighted moving average of the square root of the RTT samples. The constant  $q2$  should be set similarly to  $q$ , and we recommend a value of 0.9 as the default.



The sender obtains the base transmit rate,  $X$ , from the throughput function. It then calculates a modified instantaneous transmit rate  $X_{\text{inst}}$ , as follows:

$$X_{\text{inst}} = X * R_{\text{sqmean}} / \text{sqrt}(R_{\text{sample}});$$

When  $\text{sqrt}(R_{\text{sample}})$  is greater than  $R_{\text{sqmean}}$  then the queue is typically increasing and so the transmit rate needs to be decreased for stable operation.

Note: This modification is not always strictly required, especially if the degree of statistical multiplexing in the network is high. However, we recommend that it is done because it does make TFRC behave better in environments with a low level of statistical multiplexing. If it is not done, we recommend using a very low value of  $q$ , such that  $q$  is close to or exactly zero.

#### **4.7. Scheduling of Packet Transmissions**

As TFRC is rate-based, and as operating systems typically cannot schedule events precisely, it is necessary to be opportunistic about sending data packets so that the correct average rate is maintained despite the coarse-grain or irregular scheduling of the operating system. Thus a typical sending loop will calculate the correct inter-packet interval,  $t_{\text{ipi}}$ , as follows:

$$t_{\text{ipi}} = s/X_{\text{inst}};$$

When a sender first starts sending at time  $t_0$ , it calculates  $t_{\text{ipi}}$ , and calculates a nominal send time  $t_1 = t_0 + t_{\text{ipi}}$  for packet 1. When the application becomes idle, it checks the current time,  $t_{\text{now}}$ , and then requests re-scheduling after  $(t_{\text{ipi}} - (t_{\text{now}} - t_0))$  seconds. When the application is re-scheduled, it checks the current time,  $t_{\text{now}}$ , again. If  $(t_{\text{now}} > t_1 - \text{delta})$  then packet 1 is sent.

Now a new  $t_{\text{ipi}}$  may be calculated, and used to calculate a nominal send time  $t_2$  for packet 2:  $t_2 = t_1 + t_{\text{ipi}}$ . The process then repeats, with each successive packet's send time being calculated from the nominal send time of the previous packet.

In some cases, when the nominal send time,  $t_i$ , of the next packet is calculated, it may already be the case that  $t_{\text{now}} > t_i - \text{delta}$ . In such a case the packet should be sent immediately. Thus if the operating system has coarse timer granularity and the transmit rate is high, then TFRC may send short bursts of several packets separated by intervals of the OS timer granularity.



The parameter `delta` is to allow a degree of flexibility in the send time of a packet. If the operating system has a scheduling timer granularity of `t_gran` seconds, then `delta` would typically be set to:

$$\text{delta} = \min(t_{\text{ipi}}/2, t_{\text{gran}}/2);$$

`t_gran` is 10ms on many Unix systems. If `t_gran` is not known, a value of 10ms can be safely assumed.

## **5. Calculation of the Loss Event Rate (p)**

Obtaining an accurate and stable measurement of the loss event rate is of primary importance for TFRC. Loss rate measurement is performed at the receiver, based on the detection of lost or marked packets from the sequence numbers of arriving packets. We describe this process before describing the rest of the receiver protocol.

### **5.1. Detection of Lost or Marked Packets**

TFRC assumes that all packets contain a sequence number that is incremented by one for each packet that is sent. For the purposes of this specification, we require that if a lost packet is retransmitted, the retransmission is given a new sequence number that is the latest in the transmission sequence, and not the same sequence number as the packet that was lost. If a transport protocol has the requirement that it must retransmit with the original sequence number, then the transport protocol designer must figure out how to distinguish delayed from retransmitted packets and how to detect lost retransmissions.

The receiver maintains a data structure that keeps track of which packets have arrived and which are missing. For the purposes of specification, we assume that the data structure consists of a list of packets that have arrived along with the receiver timestamp when each packet was received. In practice this data structure will normally be stored in a more compact representation, but this is implementation-specific.

The loss of a packet is detected by the arrival of at least NDUPACK packets with a higher sequence number than the lost packet, for NDUPACK set to 3. The requirement for NDUPACK subsequent packets is the same as with TCP, and is to make TFRC more robust in the presence of reordering. In contrast to TCP, if a packet arrives late (after NDUPACK subsequent packets arrived) in TFRC, the late packet can fill the hole in TFRC's reception record, and the receiver can recalculate the loss event rate. Future versions of TFRC might make the requirement for NDUPACK subsequent packets adaptive based on experienced packet reordering, but we do not



specify such a mechanism here.

For an ECN-capable connection, a marked packet is detected as a congestion event as soon as it arrives, without having to wait for the arrival of subsequent packets.

## **5.2. Translation from Loss History to Loss Events**

TFRC requires that the loss fraction be robust to several consecutive packets lost where those packets are part of the same loss event. This is similar to TCP, which (typically) only performs one halving of the congestion window during any single RTT. Thus the receiver needs to map the packet loss history into a loss event record, where a loss event is one or more packets lost in an RTT. To perform this mapping, the receiver needs to know the RTT to use, and this is supplied periodically by the sender, typically as control information piggy-backed onto a data packet. TFRC is not sensitive to how the RTT measurement sent to the receiver is made, but we recommend using the sender's calculated RTT,  $R$ , (see [Section 4.3](#)) for this purpose.

To determine whether a lost or marked packet should start a new loss event, or be counted as part of an existing loss event, we need to compare the sequence numbers and timestamps of the packets that arrived at the receiver. For a marked packet  $S_{\text{new}}$ , its reception time  $T_{\text{new}}$  can be noted directly. For a lost packet, we can interpolate to infer the nominal "arrival time". Assume:

$S_{\text{loss}}$  is the sequence number of a lost packet.

$S_{\text{before}}$  is the sequence number of the last packet to arrive with sequence number before  $S_{\text{loss}}$ .

$S_{\text{after}}$  is the sequence number of the first packet to arrive with sequence number after  $S_{\text{loss}}$ .

$T_{\text{before}}$  is the reception time of  $S_{\text{before}}$ .

$T_{\text{after}}$  is the reception time of  $S_{\text{after}}$ .

Note that  $T_{\text{before}}$  can either be before or after  $T_{\text{after}}$  due to reordering.

For a lost packet  $S_{\text{loss}}$ , we can interpolate its nominal "arrival time" at the receiver from the arrival times of  $S_{\text{before}}$  and  $S_{\text{after}}$ . Thus:





$$T_{\text{loss}} = T_{\text{before}} + ( (T_{\text{after}} - T_{\text{before}}) \\ * (S_{\text{loss}} - S_{\text{before}}) / (S_{\text{after}} - S_{\text{before}}) );$$

Note that if the sequence space wrapped between  $S_{\text{before}}$  and  $S_{\text{after}}$ , then the sequence numbers must be modified to take this into account before performing this calculation. If the largest possible sequence number is  $S_{\text{max}}$ , and  $S_{\text{before}} > S_{\text{after}}$ , then modifying each sequence number  $S$  by  $S' = (S + (S_{\text{max}} + 1)/2) \bmod (S_{\text{max}} + 1)$  would normally be sufficient.

If the lost packet  $S_{\text{old}}$  was determined to have started the previous loss event, and we have just determined that  $S_{\text{new}}$  has been lost, then we interpolate the nominal arrival times of  $S_{\text{old}}$  and  $S_{\text{new}}$ , called  $T_{\text{old}}$  and  $T_{\text{new}}$  respectively.

If  $T_{\text{old}} + R \geq T_{\text{new}}$ , then  $S_{\text{new}}$  is part of the existing loss event. Otherwise  $S_{\text{new}}$  is the first packet in a new loss event.

### 5.3. Inter-loss Event Interval

If a loss interval,  $A$ , is determined to have started with packet sequence number  $S_A$  and the next loss interval,  $B$ , started with packet sequence number  $S_B$ , then the number of packets in loss interval  $A$  is given by  $(S_B - S_A)$ .

### 5.4. Average Loss Interval

To calculate the loss event rate  $p$ , we first calculate the average loss interval. This is done using a filter that weights the  $n$  most recent loss event intervals in such a way that the measured loss event rate changes smoothly.

Weights  $w_0$  to  $w_{(n-1)}$  are calculated as:

```
If (i < n/2)
    w_i = 1;
Else
    w_i = 1 - (i - (n/2 - 1))/(n/2 + 1);
```

Thus if  $n=8$ , the values of  $w_0$  to  $w_7$  are:

1.0, 1.0, 1.0, 1.0, 0.8, 0.6, 0.4, 0.2



The value  $n$  for the number of loss intervals used in calculating the loss event rate determines TFRC's speed in responding to changes in the level of congestion. As currently specified, TFRC should not be used for values of  $n$  significantly greater than 8, for traffic that might compete in the global Internet with TCP. At the very least, safe operation with values of  $n$  greater than 8 would require a slight change to TFRC's mechanisms to include a more severe response to two or more round-trip times with heavy packet loss.

When calculating the average loss interval we need to decide whether to include the interval since the most recent packet loss event. We only do this if it is sufficiently large to increase the average loss interval.

Let the most recent loss intervals be  $I_0$  to  $I_k$ , where  $I_0$  is the interval since the most recent loss event. If there have been at least  $n$  loss intervals, then  $k$  is set to  $n$ ; otherwise  $k$  is the maximum number of loss intervals seen so far. We calculate the average loss interval  $I_{\text{mean}}$  is:

```
I_tot0 = 0;
I_tot1 = 0;
W_tot = 0;
for (i = 0 to k-1) {
    I_tot0 = I_tot0 + (I_i * w_i);
    W_tot = W_tot + w_i;
}
for (i = 1 to k) {
    I_tot1 = I_tot1 + (I_i * w_(i-1));
}
I_tot = max(I_tot0, I_tot1);
I_mean = I_tot/W_tot;
```

The loss event rate,  $p$  is simply:

$$p = 1 / I_{\text{mean}};$$

### 5.5. History Discounting

As described in [Section 5.4](#), the most recent loss interval is only assigned  $1/(0.75*n)$  of the total weight in calculating the average loss interval, regardless of the size of the most recent loss interval. This section describes an optional history discounting mechanism, discussed further in [\[FHPW00a\]](#) and [\[W00\]](#), that allows the TFRC receiver to adjust the weights, concentrating more of the relative weight on the most recent loss interval, when the most recent loss interval is more than twice as large as the computed



average loss interval.

To carry out history discounting, we associate a discount factor  $DF_i$  with each loss interval  $L_i$ , for  $i > 0$ , where each discount factor is a floating point number. The discount array maintains the cumulative history of discounting for each loss interval. At the beginning, the values of  $DF_i$  in the discount array are initialized to 1:

```
for (i = 0 to n) {  
     $DF_i = 1$ ;  
}
```

History discounting also uses a general discount factor  $DF$ , also a floating point number, that is also initialized to 1. First we show how the discount factors are used in calculating the average loss interval, and then we describe later in this section how the discount factors are modified over time.

As described in [Section 5.4](#) the average loss interval is calculated using the  $n$  previous loss intervals  $I_1, \dots, I_n$ , and the interval  $I_0$  that represents the number of packets received since the last loss event. The computation of the average loss interval using the discount factors is a simple modification of the procedure in [Section 5.4](#), as follows:

```
 $I_{tot0} = I_0 * w_0$   
 $I_{tot1} = 0$ ;  
 $W_{tot0} = w_0$   
 $W_{tot1} = 0$ ;  
for (i = 1 to n-1) {  
     $I_{tot0} = I_{tot0} + (I_i * w_i * DF_i * DF)$ ;  
     $W_{tot0} = W_{tot0} + w_i * DF_i * DF$ ;  
}  
for (i = 1 to n) {  
     $I_{tot1} = I_{tot1} + (I_i * w_{(i-1)} * DF_i)$ ;  
     $W_{tot1} = W_{tot1} + w_{(i-1)} * DF_i$ ;  
}  
 $p = \min(W_{tot0}/I_{tot0}, W_{tot1}/I_{tot1})$ ;
```

The general discounting factor,  $DF$  is updated on every packet arrival as follows. First, the receiver computes the weighted average  $I_{mean}$  of the loss intervals  $I_1, \dots, I_n$ :



```
I_tot = 0;
W_tot = 0;
for (i = 1 to n) {
    W_tot = W_tot + w_(i-1) * DF_i;
    I_tot = I_tot + (I_i * w_(i-1) * DF_i);
}
I_mean = I_tot / W_tot;
```

This weighted average  $I_{\text{mean}}$  is compared to  $I_0$ , the number of packets received since the last loss event. If  $I_0$  is greater than twice  $I_{\text{mean}}$ , then the new loss interval is considerably larger than the old ones, and the general discount factor  $DF$  is updated to decrease the relative weight on the older intervals, as follows:

```
if ( $I_0 > 2 * I_{\text{mean}}$ ) {
     $DF = 2 * I_{\text{mean}} / I_0$ ;
    if ( $DF < \text{THRESHOLD}$ )
         $DF = \text{THRESHOLD}$ ;
} else
     $DF = 1$ ;
```

A nonzero value for  $\text{THRESHOLD}$  ensures that older loss intervals from an earlier time of high congestion are not discounted entirely. We recommend a  $\text{THRESHOLD}$  of 0.5. Note that with each new packet arrival,  $I_0$  will increase further, and the discount factor  $DF$  will be updated.

When a new loss event occurs, the current interval shifts from  $I_0$  to  $I_1$ , loss interval  $I_i$  shifts to interval  $I_{(i+1)}$ , and the loss interval  $I_n$  is forgotten. The previous discount factor  $DF$  has to be incorporated into the discount array. Because  $DF_i$  carries the discount factor associated with loss interval  $I_i$ , the  $DF_i$  array has to be shifted as well. This is done as follows:

```
for (i = 1 to n) {
     $DF_i = DF * DF_i$ ;
}
for (i = n-1 to 0 step -1) {
     $DF_{(i+1)} = DF_i$ ;
}
 $I_0 = 1$ ;
 $DF_0 = 1$ ;
 $DF = 1$ ;
```

This completes the description of the optional history discounting mechanism. We emphasize that this is an optional mechanism whose





sole purpose is to allow TFRC to response somewhat more quickly to the sudden absence of congestion, as represented by a long current loss interval.

## **6. Data Receiver Protocol**

The receiver periodically sends feedback messages to the sender. Feedback packets should normally be sent at least once per RTT, unless the sender is sending at a rate of less than one packet per RTT, in which case a feedback packet should be send for every data packet received. A feedback packet should also be sent whenever a new loss event is detected without waiting for the end of an RTT, and whenever an out-of-order data packet is received that removes a loss event from the history.

If the sender is transmitting at a high rate (many packets per RTT) there may be some advantages to sending periodic feedback messages more than once per RTT as this allows faster response to changing RTT measurements, and more resilience to feedback packet loss. However, there is little gain from sending a large number of feedback messages per RTT.

### **6.1. Receiver behavior when a data packet is received**

When a data packet is received, the receiver performs the following steps:

- 1) Add the packet to the packet history.
- 2) Let the previous value of  $p$  be  $p_{\text{prev}}$ . Calculate the new value of  $p$  as described in [Section 5](#).
- 3) If  $p > p_{\text{prev}}$ , cause the feedback timer to expire, and perform the actions described in [Section 6.2](#)

If  $p \leq p_{\text{prev}}$  no action need be performed.

However an optimization might check to see if the arrival of the packet caused a hole in the packet history to be filled and consequently two loss intervals were merged into one. If this is the case, the receiver might also send feedback immediately. The effects of such an optimization are normally expected to be small.



## **6.2. Expiration of feedback timer**

When the feedback timer at the receiver expires, the action to be taken depends on whether data packets have been received since the last feedback was sent.

Let the maximum sequence number of a packet at the receiver so far be  $S_m$ , and the value of the RTT measurement included in packet  $S_m$  be  $R_m$ . If data packets have been received since the previous feedback was sent, the receiver performs the following steps:

- 1) Calculate the average loss event rate using the algorithm described above.
- 2) Calculate the measured receive rate,  $X_{recv}$ , based on the packets received within the previous  $R_m$  seconds.
- 3) Prepare and send a feedback packet containing the information described in [Section 3.2.2](#)
- 4) Restart the feedback timer to expire after  $R_m$  seconds.

If no data packets have been received since the last feedback was sent, no feedback packet is sent, and the feedback timer is restarted to expire after  $R_m$  seconds.

## **6.3. Receiver initialization**

The receiver is initialized by the first packet that arrives at the receiver. Let the sequence number of this packet be  $i$ .

When the first packet is received:

- o Set  $p=0$
- o Set  $X_{recv} = 0$ .
- o Prepare and send a feedback packet.
- o Set the feedback timer to expire after  $R_i$  seconds.



### **6.3.1. Initializing the Loss History after the First Loss Event**

The number of packets until the first loss can not be used to compute the sending rate directly, as the sending rate changes rapidly during this time. TFRC assumes that the correct data rate after the first loss is half of the sending rate when the loss occurred. TFRC approximates this target rate by  $X_{recv}$ , the receive rate over the most recent round-trip time. After the first loss, instead of initializing the first loss interval to the number of packets sent until the first loss, the TFRC receiver calculates the loss interval that would be required to produce the data rate  $X_{recv}$ , and uses this synthetic loss interval to seed the loss history mechanism.

TFRC does this by finding some value  $p$  for which the throughput equation in [Section 3.1](#) gives a sending rate within 5% of  $X_{recv}$ , given the round-trip time  $R$ , and the first loss interval is then set to  $1/p$ . If the receiver knows the segment size  $s$  used by the sender, then the receiver can use the throughput equation for  $X$ ; otherwise, the receiver can measure the receive rate in packets per second instead of bytes per second for this purpose, and use the throughput equation for  $X_{pps}$ . (The 5% tolerance is introduced simply because the throughput equation is difficult to invert, and we want to reduce the costs of calculating  $p$  numerically.)

## **7. Sender-based Variants**

It would be possible to implement a sender-based variant of TFRC, where the receiver uses reliable delivery to send information about packet losses to the sender, and the sender computes the packet loss rate and the acceptable transmit rate. However, we do not specify the details of a sender-based variant in this document.

The main advantages of a sender-based variant of TFRC would be that the sender would not have to trust the receiver's calculation of the packet loss rate. However, with the requirement of reliable delivery of loss information from the receiver to the sender, a sender-based TFRC would have much tighter constraints on the transport protocol in which it is embedded.

In contrast, the receiver-based variant of TFRC specified in this document is robust to the loss of feedback packets, and therefore does not require the reliable delivery of feedback packets. It is also better suited for applications such as streaming media from web servers, where it is typically desirable to offload work from the server to the client as much as possible.



The sender-based and receiver-based variants also have different properties in terms of upgrades. For example, for changes in the procedure for calculating the packet loss rate, the sender would have to be upgraded in the sender-based variant, and the receiver would have to be upgraded in the receiver-based variant.

## 8. Implementation Issues

This document has specified the TFRC congestion control mechanism, for use by applications and transport protocols. This section mentions briefly some of the few implementation issues.

For  $t_{RTT} = 4 \cdot R$  and  $b = 1$ , the throughput equation in [Section 3.1](#) can be expressed as follows:

$$X = \frac{s}{R * f(p)}$$

for

$$f(p) = \sqrt{2 \cdot p / 3} + (12 \cdot \sqrt{3 \cdot p / 8} * p * (1 + 32 \cdot p^2)).$$

A table lookup could be used for the function  $f(p)$ .

Many of the multiplications (e.g.,  $q$  and  $1-q$  for the round-trip time average, a factor of 4 for the timeout interval) are or could be by powers of two, and therefore could be implemented as simple shift operations.

We note that the optional sender mechanism for preventing oscillations described in [Section 4.6](#) uses a square-root computation.

The calculation of the average loss interval in [Section 5.4](#) involves multiplications by the weights  $w_0$  to  $w_{(n-1)}$ , which for  $n=8$  are:

1.0, 1.0, 1.0, 1.0, 0.8, 0.6, 0.4, 0.2.

With a minor loss of smoothness, it would be possible to use weights that were powers of two or sums of powers of two, e.g.,

1.0, 1.0, 1.0, 1.0, 0.75, 0.5, 0.25, 0.25.





The optional history discounting mechanism described in [Section 5.5](#) is used in the calculation of the average loss rate. The history discounting mechanism is invoked only when there has been an unusually long interval with no packet losses. For a more efficient operation, the discount factor `DF_i` could be restricted to be a power of two.

## 9. Changes from [RFC 3448](#)

The changes from [RFC 3448](#) are as follows:

- o Changes to the initial sending rate: In [RFC 3448](#), the initial sending rate was two packets per round trip time. In this document, the initial sending rate can be as high as four packets per round trip time, following [RFC 3390](#).

Following [Section 5.1](#) from [[RFC4342](#)], this document also specifies that when the sending rate is reduced after an idle period, it is not reduced below the initial sending rate. In addition, when the sender has been data-limited and the sender is reducing the allowed transmit rate to twice the receive rate,, the sender doesn't reduce the allowed transmit rate to less than the initial sending rate.

A larger initial sending rate is of little use if the receiver sends a feedback packet after the first packet is received, and the sender in response reduces the allowed sending rate to at most twice the receive rate. In the current document, the sender does not reduce the allowed sending rate to at most twice the receive rate in response to the first feedback packet.

- o [RFC 3448](#) had contradictory text about whether the sender halved its sending rate after *\*two\** round-trip times without receiving a feedback report, or after *\*four\** round-trip times. This document clarifies that the sender halves its sending rate after four round-trip times without receiving a feedback report [[RFC3448errata](#)].
- o [Section 4.4](#) was clarified to specify that on the expiration of the nofeedback timer, if `p = 0`, step (2) applies instead of step (1) [[RFC3448errata](#)].
- o A line in [Section 5.5](#) was changed from ``for (i = 1 to n) { DF_i = 1; }'` to ``for (i = 0 to n) { DF_i = 1; }'` [[RFC3448errata](#)].
- o [Section 5.4](#) was modified to clarify the receiver's calculation of the average loss interval when the receiver has not yet seen



eight loss intervals.

- o [Section 4.1](#) was modified to give a specific algorithm that could be used for estimating the average segment size.

## **10. Security Considerations**

TFRC is not a transport protocol in its own right, but a congestion control mechanism that is intended to be used in conjunction with a transport protocol. Therefore security primarily needs to be considered in the context of a specific transport protocol and its authentication mechanisms.

Congestion control mechanisms can potentially be exploited to create denial of service. This may occur through spoofed feedback. Thus any transport protocol that uses TFRC should take care to ensure that feedback is only accepted from the receiver of the data. The precise mechanism to achieve this will however depend on the transport protocol itself.

In addition, congestion control mechanisms may potentially be manipulated by a greedy receiver that wishes to receive more than its fair share of network bandwidth. A receiver might do this by claiming to have received packets that in fact were lost due to congestion. Possible defenses against such a receiver would normally include some form of nonce that the receiver must feed back to the sender to prove receipt. However, the details of such a nonce would depend on the transport protocol, and in particular on whether the transport protocol is reliable or unreliable.

We expect that protocols incorporating ECN with TFRC will also want to incorporate feedback from the receiver to the sender using the ECN nonce [[RFC3540](#)]. The ECN nonce is a modification to ECN that protects the sender from the accidental or malicious concealment of marked packets. Again, the details of such a nonce would depend on the transport protocol, and are not addressed in this document.

## **11. IANA Considerations**

There are no IANA actions required for this document.

## **12. Acknowledgments**

We would like to acknowledge feedback and discussions on equation-based congestion control with a wide range of people, including members of the Reliable Multicast Research Group, the Reliable



Multicast Transport Working Group, and the End-to-End Research Group. We would like to thank Wim Heirman, Ken Lofgren, Mike Luby, Michele R., Vladica Stanisic, Randall Stewart, Eduardo Urzaiz, Shushan Wen, and Wendy Lee (lhh@zsu.edu.cn) for feedback on earlier versions of this document, and to thank Mark Allman for his extensive feedback from using the document to produce a working implementation.

### **13. Normative References**

### **14. Informational References**

- [BRS99] Balakrishnan, H., Rahul, H., and Seshan, S., "An Integrated Congestion Management Architecture for Internet Hosts," Proc. ACM SIGCOMM, Cambridge, MA, September 1999.
- [FHPW00] S. Floyd, M. Handley, J. Padhye, and J. Widmer, "Equation-Based Congestion Control for Unicast Applications", August 2000, Proc SIGCOMM 2000.
- [FHPW00a] S. Floyd, M. Handley, J. Padhye, and J. Widmer, "Equation-Based Congestion Control for Unicast Applications: the Extended Version", ICSI tech report TR-00-03, March 2000.
- [PFTK98] Padhye, J. and Firoiu, V. and Towsley, D. and Kurose, J., "Modeling TCP Throughput: A Simple Model and its Empirical Validation", Proc ACM SIGCOMM 1998.
- [RFC2119] S. Bradner, Key Words For Use in RFCs to Indicate Requirement Levels, [RFC 2119](#).
- [RFC2140] J. Touch, "TCP Control Block Interdependence", [RFC 2140](#), April 1997.
- [RFC2988] V. Paxson and M. Allman, "Computing TCP's Retransmission Timer", [RFC 2988](#), November 2000.
- [RFC3168] K. Ramakrishnan and S. Floyd, "The Addition of Explicit Congestion Notification (ECN) to IP", [RFC 3168](#), September 2001.
- [RFC3390] Allman, M., Floyd, S., and C. Partridge, "Increasing TCP's Initial Window", [RFC 3390](#), October 2002.



- [RFC3448Err] [RFC 3448](#) Errata, URL  
`http://www.icir.org/tfrc/rfc3448.errata'.
- [RFC3540] Wetherall, D., Ely, D., and Spring, N., "Robust ECN Signaling with Nonces", [RFC 3540](#), Experimental, June 2003
- [RFC4340] Kohler, E., Handley, M., and S. Floyd, "Datagram Congestion Control Protocol (DCCP)", [RFC 4340](#), March 2006.
- [RFC4342] Floyd, S., Kohler, E., and J. Padhye, "Profile for Datagram Congestion Control Protocol (DCCP) Congestion Control ID 3: TCP-Friendly Rate Control (TFRC)", [RFC 4342](#), March 2006.
- [W00] Widmer, J., "Equation-Based Congestion Control", Diploma Thesis, University of Mannheim, February 2000. URL "http://www.icir.org/tfrc/".

## [15.](#) Authors' Addresses





Mark Handley,  
Department of Computer Science  
University College London  
Gower Street  
London WC1E 6BT  
UK  
EMail: M.Handley@cs.ucl.ac.uk

Sally Floyd  
ICIR/ICSI  
1947 Center St, Suite 600  
Berkeley, CA 94708  
floyd@icir.org

Jitendra Padhye  
Microsoft Research  
padhye@microsoft.com

Joerg Widmer  
Lehrstuhl Praktische Informatik IV  
Universitat Mannheim  
L 15, 16 - Room 415  
D-68131 Mannheim  
Germany  
widmer@informatik.uni-mannheim.de

## Full Copyright Statement

Copyright (C) The Internet Society 2006. This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

## Intellectual Property

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described



in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at [ietf-ipr@ietf.org](mailto:ietf-ipr@ietf.org).

