

Network Working Group
Internet-Draft
Intended status: Informational
Expires: July 16, 2019

E. Foudil

Y. Shafranovich
Nightwatch Cybersecurity
January 12, 2019

**A Method for Web Security Policies
draft-foudil-securitytxt-05**

Abstract

When security vulnerabilities are discovered by independent security researchers, they often lack the channels to report them properly. As a result, security vulnerabilities may be left unreported. This document defines a format ("security.txt") to help organizations describe the process for security researchers to follow in order to report security vulnerabilities.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on July 16, 2019.

Copyright Notice

Copyright (c) 2019 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in [Section 4](#).e of

the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
1.1.	Motivation and Prior Work	3
1.2.	Terminology	3
2.	Note to Readers	4
3.	The Specification	4
3.1.	Scope	5
3.2.	Comments	5
3.3.	Separate Fields	5
3.4.	Digital signature	6
3.5.	Field Definitions	6
3.5.1.	Acknowledgments	6
3.5.2.	Canonical	6
3.5.3.	Contact	7
3.5.4.	Encryption	7
3.5.5.	Hiring	8
3.5.6.	Policy	8
3.5.7.	Preferred-Languages	8
3.6.	Example of an unsigned "security.txt" file	9
3.7.	Example of a signed "security.txt" file	9
4.	Location of the security.txt file	9
4.1.	Web-based services	10
4.2.	Filesystems	10
4.3.	Internal hosts	11
4.4.	Extensibility	11
5.	File Format Description and ABNF Grammar	11
6.	Security considerations	12
7.	IANA Considerations	13
7.1.	Well-Known URIs registry	13
7.2.	Registry for security.txt Header Fields	13
8.	Contributors	15
9.	References	15
9.1.	Normative References	15
9.2.	Informative References	17
Appendix A.	Note to Readers	17
Appendix B.	Document History	18
B.1.	Since draft-foudil-securitytxt-00	18
B.2.	Since draft-foudil-securitytxt-01	18
B.3.	Since draft-foudil-securitytxt-02	19
B.4.	Since draft-foudil-securitytxt-03	19
B.5.	Since draft-foudil-securitytxt-04	19
	Authors' Addresses	20

1. Introduction

1.1. Motivation and Prior Work

Many security researchers encounter situations where they are unable to report security vulnerabilities to organizations because there is no course of action laid out or no way indicated to contact the owner of a particular resource.

As per [section 4 of \[RFC2142\]](#), there is an existing convention of using the <SECURITY@domain> email address for communications regarding security vulnerabilities. That convention provides only a single, email-based channel of communication for security vulnerabilities per domain, and does not provide a way for domain owners to publish information about their security disclosure policies.

There are also contact conventions prescribed for Internet Service Providers (ISPs) in [section 2 of \[RFC3013\]](#), for Computer Security Incident Response Teams (CSIRTs) in [section 3.2 of \[RFC2350\]](#) and for site operators in [section 5.2 of \[RFC2196\]](#). As per [\[RFC7485\]](#), there is also contact information provided by Regional Internet Registries (RIRs) and domain registries for owners of IP addresses, autonomous system numbers (ASNs) and domain names. However, none of these address the issue of how security researchers can locate disclosure policies and contact information for organizations in order to report security vulnerabilities.

In this document, we define a richer, machine-parsable and more extensible way for organizations to communicate information about their security disclosure policies, which is not limited to email and also allows for additional features such as encryption. This format is designed to help assist with the security disclosure process by making it easier for organizations to designate the preferred steps for researchers to take when trying to reach out to them with security vulnerabilities.

1.2. Terminology

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "NOT RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [BCP 14 \[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

2. Note to Readers

Note to the RFC Editor: Please remove this section prior to publication.

Development of this draft takes place on Github at:

<https://github.com/securitytxt/security-txt>

3. The Specification

This document defines a text file to be placed in a known location that provides information for security researchers to assist in disclosing security vulnerabilities.

The file is named "security.txt", and this file SHOULD be placed under the /.well-known/ path ("/.well-known/security.txt") [RFC5785] of a domain name or IP address for web properties. If it is not possible to place the security.txt file in the /.well-known/ path or setup a redirect, web-based services MAY place the file in the top-level path of a given web domain or IP address ("/security.txt") as a fall back option. For web-based services, the file MUST be accessible via the Hypertext Transfer Protocol [RFC1945] as a resource of Internet Media Type "text/plain" with the default charset parameter set to "utf-8" per section 4.1.3 of [RFC2046], and it is RECOMMENDED that this file be served with "https" (as per section 2.7.2 of [RFC7230]). For file systems and version control repositories a "security.txt" file SHOULD be placed in the root directory of a particular file system or source code project.

This text file contains multiple directives with different values. The "directive" is the first part of a field all the way up to the colon ("Contact:") and follows the syntax defined for "field-name" in section 3.6.8 of [RFC5322]. Directives MUST be case-insensitive (as per section 2.3 of [RFC5234]). The "value" comes after the directive ("https://example.com/security") and follows the syntax defined for "unstructured" in section 3.2.5 of [RFC5322].

A "field" MUST always consist of a directive and a value ("Contact: https://example.com/security"). A security.txt file can have an unlimited number of fields. It is important to note that you MUST have a separate line for every field. One MUST NOT chain multiple values for a single directive and everything MUST be in a separate field. Unless otherwise indicated in a definition of a particular field, any directive MAY appear multiple times.

3.1. Scope

A "security.txt" file MUST only apply to the domain in the URI used to retrieve it, not to any of its subdomains or parent domains. A "security.txt" file that is found in a file system or version control repository MUST only apply to the folder or repository in which it is located, and not to any of its parent or sibling folders, or repositories. However, it will apply to all subfolders.

Some examples appear below:

```
# The following only applies to example.com.
```

```
https://example.com/.well-known/security.txt
```

```
# This only applies to subdomain.example.com.
```

```
https://subdomain.example.com/.well-known/security.txt
```

```
# This security.txt file applies to IPv4 address of 192.0.2.0.
```

```
https://192.0.2.0/.well-known/security.txt
```

```
# This security.txt file applies to IPv6 address of 2001:db8:8:4::2.
```

```
https://[2001:db8:8:4::2]/.well-known/security.txt
```

```
# This security.txt file applies to the /example/folder1 directory.
```

```
/example/folder1/security.txt
```

3.2. Comments

Any line beginning with the "#" (%x30) symbol MUST be interpreted as a comment. The content of the comment may contain any ASCII or Unicode characters in the %x21-7E and %x80-FFFF ranges plus the tab (%x09) and space (%x20) characters.

Example:

```
# This is a comment.
```

You MAY use one or more comments as descriptive text immediately before the field. Parsers SHOULD associate the comments with the respective field.

3.3. Separate Fields

A separate line is REQUIRED for every new value and field. You MUST NOT chain everything into a single field. Every line MUST end either with a carriage return and line feed characters (CRLF / %x0D %x0A) or just a line feed character (LF / %x0A).

3.4. Digital signature

It is RECOMMENDED that a security.txt file be digitally signed using an OpenPGP cleartext signature as described in [section 7 of \[RFC4880\]](#). When digital signatures are used, it is also RECOMMENDED that implementors use the "Canonical" directive as per [Section 3.5.2](#), thus allowing the digital signature to authenticate the location of the file.

When it comes to verifying the key used to generate the signature, it is always the security researcher's responsibility to make sure the key being used is indeed one they trust.

3.5. Field Definitions

3.5.1. Acknowledgments

This directive allows you to link to a page where security researchers are recognized for their reports. The page being linked to SHOULD list individuals or organizations that reported security vulnerabilities and worked with you to remediate the issue. Organizations SHOULD be careful to limit the vulnerability information being published in order to prevent future attacks.

Example:

Acknowledgments: <https://example.com/hall-of-fame.html>

Example security acknowledgments page:

We would like to thank the following researchers:

(2017-04-15) Frank Denis - Reflected cross-site scripting
(2017-01-02) Alice Quinn - SQL injection
(2016-12-24) John Buchner - Stored cross-site scripting
(2016-06-10) Anna Richmond - A server configuration issue

3.5.2. Canonical

This directive indicates the canonical URI where the security.txt file is located, which is usually something like "<https://example.com/.well-known/security.txt>".

This directive MUST NOT appear more than once.

Canonical: <https://example.com/.well-known/security.txt>

3.5.3. Contact

This directive allows you to provide an address that researchers SHOULD use for reporting security vulnerabilities. The value MAY be an email address, a phone number and/or a web page with contact information. The "Contact:" directive MUST always be present in a security.txt file. If this directive indicates a web URL, then it RECOMMENDED that it begins with "https://" (as per [section 2.7.2 of \[RFC7230\]](#)). Security email addresses SHOULD use the conventions defined in [section 4 of \[RFC2142\]](#).

The value MUST follow the URI syntax described in [\[RFC3986\]](#). This means that "mailto" and "tel" URI schemes MUST be used when specifying email addresses and telephone numbers, as defined in [\[RFC6068\]](#) and [\[RFC3966\]](#).

The precedence SHOULD be in listed order. The first field is the preferred method of contact. In the example below, the e-mail address is the preferred method of contact.

Contact: mailto:security@example.com

Contact: tel:+1-201-555-0123

Contact: https://example.com/security-contact.html

3.5.4. Encryption

This directive allows you to point to an encryption key that security researchers SHOULD use for encrypted communication. You MUST NOT directly add your key to the field, instead the value of this field MUST be a URI pointing to a location where the key can be retrieved from. If this directive indicates a web URL, then it is RECOMMENDED to always use "https://" URLs (as per [section 2.7.2 of \[RFC7230\]](#)).

When it comes to verifying the authenticity of the key, it is always the security researcher's responsibility to make sure the key being specified is indeed one they trust. Researchers MUST NOT assume that this key is used to generate the digital signature referenced in [Section 3.4](#).

Example of an OpenPGP key available from a web server:

Encryption: https://example.com/pgp-key.txt

Example of an OpenPGP key available from an OPENPGPKEY DNS record:

Encryption: dns:5d2d37ab76d47d36._openpgpkey.example.com?type=OPENPGPKEY

Example of an OpenPGP key being referenced by its fingerprint:

Encryption: openpgp4fpr:5f2de5521c63a801ab59ccb603d49de44b29100f

3.5.5. Hiring

The "Hiring" directive is used for linking to the vendor's security-related job positions. If this directive indicates a web URL, then it is RECOMMENDED to always use "https://" URLs (as per [section 2.7.2 of \[RFC7230\]](#)).

Hiring: https://example.com/jobs.html

3.5.6. Policy

This directive allows you to link to where your security policy and/or disclosure policy is located. This can help security researchers understand what you are looking for and how to report security vulnerabilities. If this directive indicates a web URL, then it is RECOMMENDED to always use "https://" URLs (as per [section 2.7.2 of \[RFC7230\]](#)).

Example:

Policy: https://example.com/security-policy.html

3.5.7. Preferred-Languages

This directive can be used to indicate a set of natural languages that are preferred when submitting security reports. This set MAY list multiple values, separated by commas. If this directive is included then at least one value MUST be listed. The values within this set are language tags (as defined in [\[RFC5646\]](#)). If this directive is absent, security researchers MAY assume that English is the default language to be used (as per [section 4.5 of \[RFC2277\]](#)).

The order in which they appear MUST NOT be interpreted as an indication of priority - rather these MUST BE interpreted as all being of equal priority.

This directive MUST NOT appear more than once.

Example:

Preferred-Languages: en, es, fr

3.6. Example of an unsigned "security.txt" file

```
# Our security address
Contact: mailto:security@example.com

# Our OpenPGP key
Encryption: https://example.com/pgp-key.txt

# Our security policy
Policy: https://example.com/security-policy.html

# Our security acknowledgments page
Acknowledgments: https://example.com/hall-of-fame.html
```

3.7. Example of a signed "security.txt" file

```
-----BEGIN PGP SIGNED MESSAGE-----
Hash: SHA256

# Canonical URL
Canonical: https://example.com/.well-known/security.txt

# Our security address
Contact: mailto:security@example.com


# Our OpenPGP key
Encryption: https://example.com/pgp-key.txt

# Our security policy
Policy: https://example.com/security-policy.html

# Our security acknowledgments page
Acknowledgments: https://example.com/hall-of-fame.html
-----BEGIN PGP SIGNATURE-----
Version: GnuPG v1

[signature]
-----END PGP SIGNATURE-----
```

4. Location of the security.txt file



4.1. Web-based services

Web-based services SHOULD place the security.txt file under the `/well-known/` path; e.g. `https://example.com/.well-known/security.txt`. A security.txt file located under the top-level path SHOULD either redirect (as per [section 6.4 of \[RFC7231\]](#)) to the security.txt file under the `/well-known/` path or be used as a fall back.

4.2. Filesystems

File systems SHOULD place the "security.txt" file under the root directory; e.g., `"/security.txt"`, `"C:\security.txt"`.

Example file system:

```

/example-directory-1/
/example-directory-2/
/example-directory-3/
/example-file
/security.txt

```


4.3. Internal hosts

A "security.txt" file SHOULD be placed in the root directory of an internal host.

4.4. Extensibility

Like many other formats and protocols, this format may need to be extended over time to fit the ever-changing landscape of the Internet. Therefore, extensibility is provided via an IANA registry for directives as defined in [Section 7.2](#). Any directives registered via that process MUST be considered optional. To encourage extensibility and interoperability, implementors MUST ignore any fields they do not explicitly support.

5. File Format Description and ABNF Grammar

The expected file format of the security.txt file is plain text (MIME type "text/plain") as defined in [section 4.1.3 of \[RFC2046\]](#) and is encoded using UTF-8 [\[RFC3629\]](#) in Net-Unicode form [\[RFC5198\]](#).

The following is an ABNF definition of the security.txt format, using the conventions defined in [\[RFC5234\]](#).

```
body                = signed / unsigned

signed              = sign-header unsigned sign-footer

sign-header         = <headers and line from section 7 of \[RFC4880\]>

sign-footer         = <OpenPGP signature from section 7 of \[RFC4880\]>

unsigned            = *line (canonical-field eol) (lang-field eol) *line

line                = (field / comment) eol

eol                 = *WSP [CR] LF

field               = ack-field /
                    contact-field /
                    encryption-field /
                    hiring-field /
                    policy-field /
                    ext-field

fs                 = ":"

comment             = "#" *(WSP / VCHAR / %x80-FFFF)
```


ack-field = "Acknowledgments" fs SP uri

canonical-field = "Canonical" fs SP uri

contact-field = "Contact" fs SP uri

lang-tag = <Language-Tag from [section 2.1 of \[RFC5646\]](#)>

uri = <URI as per [\[RFC3986\]](#)>

encryption-field = "Encryption" fs SP uri

hiring-field = "Hiring" fs SP uri

policy-field = "Policy" fs SP uri

lang-field = "Preferred-Languages" fs SP lang-values

lang-values = lang-tag *(", " [WSP] lang-tag)

ext-field = field-name fs SP unstructured

field-name = <imported from [section 3.6.8 of \[RFC5322\]](#)>

unstructured = <imported from [section 3.2.5 of \[RFC5322\]](#)>

"ext-field" refers to extension fields, which are discussed in [Section 4.4](#)

6. Security considerations

Organizations creating security.txt files will need to consider several security-related issues. These include exposure to sensitive information and attacks where limited access to a server could grant the ability to modify the contents of the security.txt file or affect how it is served. Organizations SHOULD also monitor their security.txt files regularly to detect tampering. Organizations SHOULD also ensure that any resources such as web pages, email addresses and telephone numbers references by a "security.txt" file are kept current, are accessible and controlled by the organization, and are kept secure.

To ensure the authenticity of the security.txt file, organizations SHOULD digitally sign this file with OpenPGP as per [Section 3.4](#) and SHOULD also use the "Canonical" directive as per [Section 3.5.2](#). As stated in [Section 3.5.4](#), it is RECOMMENDED that encryption keys be loaded over HTTPS (as per [section 2.7.2 of \[RFC7230\]](#)).

Websites SHOULD reserve the security.txt namespace to ensure no third-party can create a page with the "security.txt" name.

7. IANA Considerations

example.com is used in this document following the uses indicated in [\[RFC2606\]](#).

192.0.2.0 and 2001:db8:8:4::2 are used in this document following the uses indicated in [\[RFC6890\]](#).

7.1. Well-Known URIs registry

The "Well-Known URIs" registry should be updated with the following additional values (using the template from [\[RFC5785\]](#)):

URI suffix: security.txt

Change controller: IETF

Specification document(s): this document

7.2. Registry for security.txt Header Fields

IANA is requested to create the "security.txt Header Fields" registry in accordance with [\[RFC8126\]](#). This registry will contain header fields for use in security.txt files, defined by this specification.

New registrations or updates MUST be published in accordance with the "Expert Review" guidelines as described in [section 4.5 of \[RFC8126\]](#). Any new field thus registered is considered optional by this specification unless a new version of this specification is published.

New registrations and updates MUST contain the following information:

1. Name of the field being registered or updated
2. Short description of the field
3. Whether the field can appear more than once
4. The document in which the specification of the field is published
5. New or updated status, which MUST be one of: current: The field is in current use deprecated: The field is in current use, but its use is discouraged historic: The field is no longer in current use

An update may make a notation on an existing registration indicating that a registered field is historical or deprecated if appropriate.

The initial registry contains these values:

Field Name: Acknowledgments

Description: link to page where security researchers are recognized

Multiple Appearances: Yes

Published in: this document

Status: current

Field Name: Canonical

Description: canonical URL for this file

Multiple Appearances: No

Published in: this document

Status: current

Field Name: Contact

Description: contact information to use for reporting vulnerabilities

Multiple Appearances: Yes

Published in: this document

Status: current

Field Name: Encryption

Description: link to a key to be used for encrypted communication

Multiple Appearances: Yes

Published in: this document

Status: current

Field Name: Hiring

Description: link to the vendor's security-related job positions

Multiple Appearances: Yes

Published in: this document

Status: current

Field Name: Policy

Description: link to security policy page

Multiple Appearances: Yes

Published in: this document

Status: current

Field Name: Preferred-Languages

Description: list of preferred languages for security reports

Multiple Appearances: No

Published in: this document

Status: current

8. Contributors

The authors would like to acknowledge the help provided during the development of this document by Tom Hudson, Jobert Abma, Gerben Janssen van Doorn, Austin Heap, Stephane Bortzmeyer, Eduardo Vela and Krzysztof Kotowicz.

The authors would also like to acknowledge the feedback provided by multiple members of IETF's SAAG and SEC-DISPATCH lists.

9. References

9.1. Normative References

- [RFC1945] Berners-Lee, T., Fielding, R., and H. Frystyk, "Hypertext Transfer Protocol -- HTTP/1.0", [RFC 1945](#), DOI 10.17487/RFC1945, May 1996, <<https://www.rfc-editor.org/info/rfc1945>>.
- [RFC2046] Freed, N. and N. Borenstein, "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), DOI 10.17487/RFC2046, November 1996, <<https://www.rfc-editor.org/info/rfc2046>>.
- [RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.
- [RFC2142] Crocker, D., "Mailbox Names for Common Services, Roles and Functions", [RFC 2142](#), DOI 10.17487/RFC2142, May 1997, <<https://www.rfc-editor.org/info/rfc2142>>.
- [RFC2277] Alvestrand, H., "IETF Policy on Character Sets and Languages", [BCP 18](#), [RFC 2277](#), DOI 10.17487/RFC2277, January 1998, <<https://www.rfc-editor.org/info/rfc2277>>.
- [RFC3629] Yergeau, F., "UTF-8, a transformation format of ISO 10646", STD 63, [RFC 3629](#), DOI 10.17487/RFC3629, November 2003, <<https://www.rfc-editor.org/info/rfc3629>>.
- [RFC3966] Schulzrinne, H., "The tel URI for Telephone Numbers", [RFC 3966](#), DOI 10.17487/RFC3966, December 2004, <<https://www.rfc-editor.org/info/rfc3966>>.

- [RFC3986] Berners-Lee, T., Fielding, R., and L. Masinter, "Uniform Resource Identifier (URI): Generic Syntax", STD 66, [RFC 3986](#), DOI 10.17487/RFC3986, January 2005, <<https://www.rfc-editor.org/info/rfc3986>>.
- [RFC4880] Callas, J., Donnerhacke, L., Finney, H., Shaw, D., and R. Thayer, "OpenPGP Message Format", [RFC 4880](#), DOI 10.17487/RFC4880, November 2007, <<https://www.rfc-editor.org/info/rfc4880>>.
- [RFC5198] Klensin, J. and M. Padlipsky, "Unicode Format for Network Interchange", [RFC 5198](#), DOI 10.17487/RFC5198, March 2008, <<https://www.rfc-editor.org/info/rfc5198>>.
- [RFC5234] Crocker, D., Ed. and P. Overell, "Augmented BNF for Syntax Specifications: ABNF", STD 68, [RFC 5234](#), DOI 10.17487/RFC5234, January 2008, <<https://www.rfc-editor.org/info/rfc5234>>.
- [RFC5322] Resnick, P., Ed., "Internet Message Format", [RFC 5322](#), DOI 10.17487/RFC5322, October 2008, <<https://www.rfc-editor.org/info/rfc5322>>.
- [RFC5646] Phillips, A., Ed. and M. Davis, Ed., "Tags for Identifying Languages", [BCP 47](#), [RFC 5646](#), DOI 10.17487/RFC5646, September 2009, <<https://www.rfc-editor.org/info/rfc5646>>.
- [RFC5785] Nottingham, M. and E. Hammer-Lahav, "Defining Well-Known Uniform Resource Identifiers (URIs)", [RFC 5785](#), DOI 10.17487/RFC5785, April 2010, <<https://www.rfc-editor.org/info/rfc5785>>.
- [RFC6068] Duerst, M., Masinter, L., and J. Zawinski, "The 'mailto' URI Scheme", [RFC 6068](#), DOI 10.17487/RFC6068, October 2010, <<https://www.rfc-editor.org/info/rfc6068>>.
- [RFC7230] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Message Syntax and Routing", [RFC 7230](#), DOI 10.17487/RFC7230, June 2014, <<https://www.rfc-editor.org/info/rfc7230>>.
- [RFC7231] Fielding, R., Ed. and J. Reschke, Ed., "Hypertext Transfer Protocol (HTTP/1.1): Semantics and Content", [RFC 7231](#), DOI 10.17487/RFC7231, June 2014, <<https://www.rfc-editor.org/info/rfc7231>>.

- [RFC8174] Leiba, B., "Ambiguity of Uppercase vs Lowercase in [RFC 2119](#) Key Words", [BCP 14](#), [RFC 8174](#), DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

9.2. Informative References

- [RFC2196] Fraser, B., "Site Security Handbook", FYI 8, [RFC 2196](#), DOI 10.17487/RFC2196, September 1997, <<https://www.rfc-editor.org/info/rfc2196>>.
- [RFC2350] Brownlee, N. and E. Guttman, "Expectations for Computer Security Incident Response", [BCP 21](#), [RFC 2350](#), DOI 10.17487/RFC2350, June 1998, <<https://www.rfc-editor.org/info/rfc2350>>.
- [RFC2606] Eastlake 3rd, D. and A. Panitz, "Reserved Top Level DNS Names", [BCP 32](#), [RFC 2606](#), DOI 10.17487/RFC2606, June 1999, <<https://www.rfc-editor.org/info/rfc2606>>.
- [RFC3013] Killalea, T., "Recommended Internet Service Provider Security Services and Procedures", [BCP 46](#), [RFC 3013](#), DOI 10.17487/RFC3013, November 2000, <<https://www.rfc-editor.org/info/rfc3013>>.
- [RFC6890] Cotton, M., Vegoda, L., Bonica, R., Ed., and B. Haberman, "Special-Purpose IP Address Registries", [BCP 153](#), [RFC 6890](#), DOI 10.17487/RFC6890, April 2013, <<https://www.rfc-editor.org/info/rfc6890>>.
- [RFC7485] Zhou, L., Kong, N., Shen, S., Sheng, S., and A. Servin, "Inventory and Analysis of WHOIS Registration Objects", [RFC 7485](#), DOI 10.17487/RFC7485, March 2015, <<https://www.rfc-editor.org/info/rfc7485>>.
- [RFC8126] Cotton, M., Leiba, B., and T. Narten, "Guidelines for Writing an IANA Considerations Section in RFCs", [BCP 26](#), [RFC 8126](#), DOI 10.17487/RFC8126, June 2017, <<https://www.rfc-editor.org/info/rfc8126>>.

Appendix A. Note to Readers

Note to the RFC Editor: Please remove this section prior to publication.

Development of this draft takes place on Github at <https://github.com/securitytxt/security-txt>

Appendix B. Document History

Note to the RFC Editor: Please remove this section prior to publication.

B.1. Since [draft-foudil-securitytxt-00](#)

- o Moved to use IETF's markdown tools for draft updates
- o Added table of contents and a fuller list of references
- o Moved file to .well-known URI and added IANA registration (#3)
- o Added extensibility with an IANA registry for fields (#34)
- o Added text explaining relationship to [RFC 2142](#) / security@ email address (#25)
- o Scope expanded to include internal hosts, domains, IP addresses and file systems
- o Support for digital signatures added (#19)

The full list of changes can be viewed via the IETF document tracker:
<https://tools.ietf.org/html/draft-foudil-securitytxt-01>

B.2. Since [draft-foudil-securitytxt-01](#)

- o Added appendix with pointer to Github and document history
- o Added external signature file to the well known URI registry (#59)
- o Added policy field (#53)
- o Added diagram explaining the location of the file on public vs. internal systems
- o Added recommendation that external signature files should use HTTPS (#55)
- o Added recommendation that organizations should monitor their security.txt files (#14)

The full list of changes can be viewed via the IETF document tracker:
<https://tools.ietf.org/html/draft-foudil-securitytxt-02>

B.3. Since [draft-foudil-securitytxt-02](#)

- o Use "mailto" and "tel" (#62)
- o Fix typo in the "Example" section (#64)
- o Clarified that the root directory is a fall back option (#72)
- o Defined content-type for the response (#68)
- o Clarify the scope of the security.txt file (#69)
- o Cleaning up text based on the NITS tools suggestions (#82)
- o Added clarification for newline values
- o Clarified the encryption field language, added examples of DNS-stored encryption keys (#28 and #94)
- o Added "Hiring" field

B.4. Since [draft-foudil-securitytxt-03](#)

- o Added "Hiring" field to the registry section
- o Added an encryption example using a PGP fingerprint (#107)
- o Added reference to the mailing list (#111)
- o Added a section referencing related work (#113)
- o Fixes for idnits (#82)
- o Changing some references to informative instead of normative
- o Adding "Permission" field (#30)
- o Fixing remaining ABNF issues (#83)
- o Additional editorial changes and edits

B.5. Since [draft-foudil-securitytxt-04](#)

- o Addressing IETF feedback (#118)
- o Case sensitivity clarification (#127)
- o Syntax fixes (#133, #135 and #136)

- o Removed permission directive (#30)
- o Removed signature directive and switched to inline signatures (#93 and #128)
- o Adding canonical directive (#100)
- o Text and ABNF grammar improvements plus ABNF changes for comments (#123)
- o Changed ".security.txt" to "security.txt" to be consistent

Full list of changes can be viewed via the IETF document tracker:

<https://tools.ietf.org/html/draft-foudil-securitytxt>

Authors' Addresses

Edwin Foudil

Email: contact@edoverflow.com

Yakov Shafranovich

Nightwatch Cybersecurity

Email: yakov+ietf@nightwatchcybersecurity.com

