

MIME Parameter Value and Encoded Word Extensions:  
Character Sets, Languages, and Continuations

June 1997

**Status of this Memo**

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months. Internet-Drafts may be updated, replaced, or obsoleted by other documents at any time. It is not appropriate to use Internet-Drafts as reference material or to cite them other than as a "working draft" or "work in progress".

To learn the current status of any Internet-Draft, please check the `1id-abstracts.txt` listing contained in the Internet-Drafts Shadow Directories on `ds.internic.net` (US East Coast), `nic.nordu.net` (Europe), `ftp.isi.edu` (US West Coast), or `munari.oz.au` (Pacific Rim).

The current draft of this memo reflects comments received during the last call period. In particular, a reference to RFC [2119](#) has been added, as have some directives on how to handle character sets with embedded language tagging facilities.

**1. Abstract**

This memo defines extensions to the [RFC 2045](#) media type and RFC CDISP disposition parameter value mechanisms to provide

- (1) a means to specify parameter values in character sets other than US-ASCII,

- (2) to specify the language to be used should the value be displayed, and
- (3) a continuation mechanism for long parameter values to avoid problems with header line wrapping.

This memo also defines an extension to the encoded words defined in [RFC 2047](#) to allow the specification of the language to be used for display as well as the character set.

## **2. Introduction**

The Multipurpose Internet Mail Extensions, or MIME [[RFC-2045](#), [RFC-2046](#), [RFC-2047](#), [RFC-2048](#), [RFC-2049](#)], define a message format that allows for

- (1) textual message bodies in character sets other than US-ASCII,
- (2) non-textual message bodies,
- (3) multi-part message bodies, and
- (4) textual header information in character sets other than US-ASCII.

MIME is now widely deployed and is used by a variety of Internet protocols, including, of course, Internet email. However, MIME's success has resulted in the need for additional mechanisms that were not provided in the original protocol specification.

In particular, existing MIME mechanisms provide for named media type (content-type field) parameters as well as named disposition (content-disposition field). A MIME media type may specify any number of parameters associated with all of its subtypes, and any specific subtype may specify additional parameters for its own use. A MIME disposition value may specify any number of associated parameters, the most important of which is probably the attachment disposition's filename parameter.

These parameter names and values end up appearing in the content-type and content-disposition header fields in Internet

Expires December 1997

[Page 2]

email. This inherently imposes three crucial limitations:

- (1) Lines in Internet email header fields are folded according to [RFC 822](#) folding rules. This makes long parameter values problematic.
- (2) MIME headers, like the [RFC 822](#) headers they often appear in, are limited to 7bit US-ASCII, and the encoded-word mechanisms of [RFC 2047](#) are not available to parameter values. This makes it impossible to have parameter values in character sets other than US-ASCII without specifying some sort of private per-parameter encoding.
- (3) It has recently become clear that character set information is not sufficient to properly display some sorts of information -- language information is also needed [[RFC-2130](#)]. For example, support for handicapped users may require reading text string aloud. The language the text is written in is needed for this to be done correctly. Some parameter values may need to be displayed, hence there is a need to allow for the inclusion of language information.

The last problem on this list is also an issue for the encoded words defined by [RFC 2047](#), as encoded words are intended primarily for display purposes.

This document defines extensions that address all of these limitations. All of these extensions are implemented in a fashion that is completely compatible at a syntactic level with existing MIME implementations. In addition, the extensions are designed to have as little impact as possible on existing uses of MIME.

**IMPORTANT NOTE:** These mechanisms end up being somewhat glibous when they actually are used. As such, use of these mechanisms should not be used lightly; they should be reserved for situations where a real need for them exists.

### **2.1. Requirements notation**

This document occasionally uses terms that appear in capital letters. When the terms "MUST", "SHOULD", "MUST NOT", "SHOULD

Expires December 1997

[Page 3]

NOT", and "MAY" appear capitalized, they are being used to indicate particular requirements of this specification. A discussion of the meanings of these terms appears in [RFC-2119].

### **3. Parameter Value Continuations**

Long MIME media type or disposition parameter values do not interact well with header line wrapping conventions. In particular, proper header line wrapping depends on there being places where linear whitespace (LWSP) is allowed, which may or may not be present in a parameter value, and even if present may not be recognizable as such since specific knowledge of parameter value syntax may not be available to the agent doing the line wrapping. The result is that long parameter values may end up getting truncated or otherwise damaged by incorrect line wrapping implementations.

A mechanism is therefore needed to break up parameter values into smaller units that are amenable to line wrapping. Any such mechanism **MUST** be compatible with existing MIME processors. This means that

- (1) the mechanism **MUST NOT** change the syntax of MIME media type and disposition lines, and
- (2) the mechanism **MUST NOT** depend on parameter ordering since MIME states that parameters are not order sensitive. Note that while MIME does prohibit modification of MIME headers during transport, it is still possible that parameters will be reordered when user agent level processing is done.

The obvious solution, then, is to use multiple parameters to contain a single parameter value and to use some kind of distinguished name to indicate when this is being done. And this obvious solution is exactly what is specified here: The asterisk character ("\*") followed by a decimal count is employed to indicate that multiple parameters are being used to encapsulate a single parameter value. The count starts at **0** and increments by 1 for each subsequent section of the parameter value. Decimal values are used and neither leading zeroes nor gaps in the sequence are allowed.

Expires December 1997

[Page 4]

The original parameter value is recovered by concatenating the various sections of the parameter, in order. For example, the content-type field

```
Content-Type: message/external-body; access-type=URL;
  URL*0="ftp://";
  URL*1="cs.utk.edu/pub/moore/bulk-mailer/bulk-mailer.tar"
```

is semantically identical to

```
Content-Type: message/external-body; access-type=URL;
  URL="ftp://cs.utk.edu/pub/moore/bulk-mailer/bulk-mailer.tar"
```

Note that quotes around parameter values are part of the value syntax; they are NOT part of the value itself. Furthermore, it is explicitly permitted to have a mixture of quoted and unquoted continuation fields.

#### **4. Parameter Value Character Set and Language Information**

Some parameter values may need to be qualified with character set or language information. It is clear that a distinguished parameter name is needed to identify when this information is present along with a specific syntax for the information in the value itself. In addition, a lightweight encoding mechanism is needed to accommodate 8 bit information in parameter values.

Asterisks ("\*") are reused to provide the indicator that language and character set information is present and encoding is being used. A single quote ("'") is used to delimit the character set and language information at the beginning of the parameter value. Percent signs ("%") are used as the encoding flag, which agrees with [RFC 2047](#).

Specifically, an asterisk at the end of a parameter name acts as an indicator that character set and language information may appear at the beginning of the parameter value. A single quote is used to separate the character set, language, and actual value information in the parameter value string, and an percent sign is used to flag octets encoded in hexadecimal. For example:

```
Content-Type: application/x-stuff;
```

Expires December 1997

[Page 5]

```
title*=us-ascii'en-us'This%20is%20%2A%2A%2Afun%2A%2A%2A
```

Note that it is perfectly permissible to leave either the character set or language field blank. Note also that the single quote delimiters MUST be present even when one of the field values is omitted. This is done when either character set, language, or both are not relevant to the parameter value at hand. This MUST NOT be done in order to indicate a default character set or language -- parameter field definitions MUST NOT assign a default character set or lanugage.

#### **4.1. Combining Character Set, Language, and Parameter Continuations**

Character set and language information may be combined with the parameter continuation mechanism. For example:

```
Content-Type: application/x-stuff
title*1*=us-ascii'en'This%20is%20even%20more%20
title*2*=%2A%2A%2Afun%2A%2A%2A%20
title*3*="isn't it!"
```

Note that:

- (1) Language and character set information only appear at the beginning of a given parameter value.
- (2) Continuations do not provide a facility for using more than one character set or language in the same parameter value.
- (3) A value presented using multiple continuations may contain a mixture of encoded and unencoded segments.
- (4) The first segment of a continuation MUST be encoded if language and character set information are given.
- (5) If the first segment of a continued parameter value is encoded the language and character set field delimiters MUST be present even when the fields are left blank.

Expires December 1997

[Page 6]

## 5. Language specification in Encoded Words

[RFC 2047](#) provides support for non-US-ASCII character sets in [RFC 822](#) message header comments, phrases, and any unstructured text field. This is done by defining an encoded word construct which can appear in any of these places. Given that these are fields intended for display, it is sometimes necessary to associate language information with encoded words as well as just the character set. This specification extends the definition of an encoded word to allow the inclusion of such information. This is simply done by suffixing the character set specification with an asterisk followed by the language tag. For example:

```
From: =?US-ASCII*EN?Q?Keith_Moore?= <moore@cs.utk.edu>
```

## 6. IMAP4 Handling of Parameter Values

IMAP4 [[RFC-2060](#)] servers SHOULD decode parameter value continuations when generating the BODY and BODYSTRUCTURE fetch attributes.

## 7. Modifications to MIME ABNF

The ABNF for MIME parameter values given in [RFC 2045](#) is:

```
parameter := attribute "=" value
attribute := token
              ; Matching of attributes
              ; is ALWAYS case-insensitive.
```

This specification changes this ABNF to:

```
parameter := regular-parameter / extended-parameter
regular-parameter := regular-parameter-name "=" value
regular-parameter-name := attribute [section]
attribute := 1*attribute-char
```

Expires December 1997

[Page 7]

attribute-char := <any (US-ASCII) CHAR except SPACE, CTLs,  
"\"", "'", "%", or tspecials>

section := initial-section / other-sections

initial-section := "\*"1"

other-sections := "\*" (( "2" / "3" / "4" / "5" /  
"6" / "7" / "8" / "9" ) \*DIGIT) /  
("1" 1\*DIGIT))

extended-parameter := (extended-initial-name "="  
extended-value) /  
(extended-other-names "="  
extended-other-values)

extended-initial-name := attribute [initial-section] "\*" "

extended-other-names := attribute other-sections "\*" "

extended-initial-value := [charset] "" [language] ""  
extended-other-values

extended-other-values := \*(ext-octet / attribute-char)

ext-octet := "%" 2(DIGIT / "A" / "B" / "C" / "D" / "E" / "F")

charset := <registered character set name>

language := <registered language tag [[RFC-1766](#)]>

The ABNF given in [RFC 2047](#) for encoded-words is:

encoded-word := "=?" charset "?" encoding "?" encoded-text "?="

This specification changes this ABNF to:

encoded-word := "=?" charset ["\*" language] "?" encoded-text "?="

## **8. Character sets which allow specification of language**

In the future it is likely that some character sets will provide facilities for inline language labelling. Such

Expires December 1997

[Page 8]

facilities are inherently more flexible than those defined here as they allow for language switching in the middle of a string.

If and when such facilities are developed they SHOULD be used in preference to the language labelling facilities specified here. Note that all the mechanisms defined here allow for the omission of language labels so as to be able to accomodate this possible future usage.

## **9. Security Considerations**

This RFC does not discuss security issues and is not believed to raise any security issues not already endemic in electronic mail and present in fully conforming implementations of MIME.

## **10. References**

[RFC-822]

Crocker, D., "Standard for the Format of ARPA Internet Text Messages", [RFC 822](#) August, 1982.

[RFC-1766]

Alvestrand, H., "Tags for the Identification of Languages", [RFC 1766](#), March, 1995.

[RFC-2045]

Freed, N. and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part One: Format of Internet Message Bodies", [RFC 2045](#), Innosoft, First Virtual Holdings, December 1996.

[RFC-2046]

Freed, N. and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part Two: Media Types", [RFC 2046](#), Innosoft, First Virtual Holdings, December 1996.

Expires December 1997

[Page 9]

## [RFC-2047]

Moore, K., "Multipurpose Internet Mail Extensions (MIME) Part Three: Representation of Non-ASCII Text in Internet Message Headers", [RFC 2047](#), University of Tennessee, December 1996.

## [RFC-2048]

Freed, N., Klensin, J., Postel, J., "Multipurpose Internet Mail Extensions (MIME) Part Four: MIME Registration Procedures", [RFC 2048](#), Innosoft, MCI, ISI, December 1996.

## [RFC-2049]

Freed, N. and Borenstein, N., "Multipurpose Internet Mail Extensions (MIME) Part Five: Conformance Criteria and Examples", [RFC 2049](#), Innosoft, First Virtual Holdings, December 1996.

## [RFC-2060]

Crispin, M., "Internet Message Access Protocol - Version 4rev1", [RFC 2060](#), December 1996.

## [RFC-2119]

Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [RFC 2119](#), March 1997.

## [RFC-2130]

Weider, C., Preston, C., Simonsen, K., Alvestrand, H., Atkinson, R., Crispin, M., Svanberg, P., "Report from the IAB Character Set Workshop", [RFC 2130](#), April 1997.

## [RFC-CDISP]

Troost, R., Dorner, S., and Moore, K., "Communicating Presentation Information in Internet Messages: The Content-Disposition Header", Internet Draft, February 1997.

Expires December 1997

[Page 10]

**11. Authors' Addresses**

Ned Freed  
Innosoft International, Inc.  
**1050 East Garvey Avenue South**  
West Covina, CA 91790  
USA  
tel: +1 818 919 3600  
email: ned@innosoft.com

fax: +1 818 919 3614

Keith Moore  
Computer Science Dept.  
University of Tennessee  
**107 Ayres Hall**  
Knoxville, TN 37996-1301  
USA  
email: moore@cs.utk.edu