

DHC Working Group
Internet-Draft
Expires: June 4, 2006

T. Fujisaki
A. Matsumoto
J. Kato
S. Niinobe
NTT
Dec 2005

**Distributing Default Address Selection Policy using DHCPv6
draft-fujisaki-dhc-addr-select-opt-01.txt**

Status of this Memo

By submitting this Internet-Draft, each author represents that any applicable patent or other IPR claims of which he or she is aware have been or will be disclosed, and any of which he or she becomes aware will be disclosed, in accordance with [Section 6 of BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at <http://www.ietf.org/ietf/1id-abstracts.txt>.

The list of Internet-Draft Shadow Directories can be accessed at <http://www.ietf.org/shadow.html>.


This Internet-Draft will expire on June 4, 2006.

Copyright Notice

Copyright (C) The Internet Society (2005).

Abstract

This document describes a new DHCPv6 option for distributing default address selection policy information to a client. With this option, site administrators can distribute address selection policy to control the node's address selection behavior.



[Fig. 1]

Fields:

option-code: OPTION_DASP (TBD)

option-len: The total length of the label fields, precedence fields, zone-index fields, prefix-len fields, and prefix fields in octets.

label: An 8-bit unsigned integer; this value is used to make a combination of source address prefixes and destination address prefixes.

precedence: An 8-bit unsigned integer; this value is used for sorting destination addresses.

zone-index: An 8-bit unsigned integer; this value is used to specify zones for scoped addresses.

prefix-len: An 8-bit unsigned integer; the number of leading bits in the prefix that are valid. The value ranges from 0 to 128. The Prefix field is 0, 4, 8, 12, or 16 octets, depending on the length.

Prefix: A variable-length field containing an IP address or the

prefix of an IP address. IPv4-mapped address [mapped] must be used to represent an IPv4 address as a prefix value.

4. Appearance of this Option

The Default Address Selection Policy option MUST NOT appear in any messages other than the following ones : Solicit, Advertise, Request, Renew, Rebind, Information-Request, and Reply.

5. Implementation Considerations

- o The value 'label' is passed as an unsigned integer, but there is no special meaning for the value, that is whether it is a large or small number. It is used to select a preferred source address prefix corresponding to a destination address prefix by matching the same label value within this DHCP message. DHCPv6 clients need to convert this label to a representation specified by each implementation (e.g., string).
- o Currently, the value label, precedence, and zone indices are defined as 8-bit unsigned integers. In almost all cases, this value will be enough.
- o The 'precedence' is used to sort destination addresses. There might be some cases where precedence values will conflict when a client already has a selection policy configured or a client receives multiple policies from multiple DHCP servers (e.g., when a home gateway in a user network is connected to multiple upstream ISPs). In such cases, manual configuration of the policy will be necessary.

6. Discussion

- o The 'zone index' value is used to specify a particular zone for scoped addresses. This can be used effectively to control address selection in the site scope (e.g., to tell a node to use a specified source address corresponding to a site-scoped multicast address). However, in some cases such as a link-local scope address, the value specifying one zone is only meaningful locally within that node. There might be some cases where the administrator knows which clients are on the network and wants specific interfaces to be used though. However, it is hard to use this value in general case.

7. Security Considerations

A rogue DHCPv6 server could issue bogus default address selection policies to a client. This might lead to incorrect address selection by the client, and the affected packets might be blocked at an outgoing ISP because of ingress filtering.

To guard against such attacks, both DHCP clients and servers SHOULD use DHCP authentication, as described in [section 21 of RFC 3315](#), "Authentication of DHCP messages."

8. References

[A. Matsumoto]

Matsumoto, A., Fujisaki, T., and J. Kato, "Practical Usages of Default Address Selection Policy Distribution", [draft-arifumi-ipv6-policy-dist-00.txt](#)-00.txt. (Work In Progress) (work in progress), Dec 1 2005.

[RFC2460] Deering, S. and R. Hinden, "Internet Protocol, Version 6 (IPv6) Specification", [RFC 2460](#), December 1998.

[RFC3315] Droms, R., Bound, J., Volz, B., Lemon, T., Perkins, C., and M. Carney, "Dynamic Host Configuration Protocol for IPv6 (DHCPv6)", [RFC 3315](#), July 2003.

[RFC3484] Draves, R., "Default Address Selection for Internet Protocol version 6 (IPv6)", [RFC 3484](#), February 2003.

Authors' Addresses

Tomohiro Fujisaki
NTT PF Lab
3-9-11 Midori-Cho
Musashino-shi, Tokyo 180-8585
Japan

Phone: +81 422 59 7351
Email: fujisaki.tomohiroi@lab.ntt.co.jp

Arifumi Matsumoto
NTT PF Lab
3-9-11 Midori-Cho
Musashino-shi, Tokyo 180-8585
Japan

Phone: +81 422 59 3334
Email: arifumi@nttv6.net

Jun-ya Kato
NTT PF Lab
3-9-11 Midori-Cho
Musashino-shi, Tokyo 180-8585
Japan

Phone: +81 422 59 2939
Email: kato@syce.net

Shirou Niinobe
NTT PF Lab
3-9-11 Midori-Cho
Musashino-shi, Tokyo 180-8585
Japan

Phone: +81 422 59 4949
Email: nin@syce.net

Intellectual Property Statement

The IETF takes no position regarding the validity or scope of any Intellectual Property Rights or other rights that might be claimed to pertain to the implementation or use of the technology described in this document or the extent to which any license under such rights might or might not be available; nor does it represent that it has made any independent effort to identify any such rights. Information on the procedures with respect to rights in RFC documents can be found in [BCP 78](#) and [BCP 79](#).

Copies of IPR disclosures made to the IETF Secretariat and any assurances of licenses to be made available, or the result of an attempt made to obtain a general license or permission for the use of such proprietary rights by implementers or users of this specification can be obtained from the IETF on-line IPR repository at <http://www.ietf.org/ipr>.

The IETF invites any interested party to bring to its attention any copyrights, patents or patent applications, or other proprietary rights that may cover technology that may be required to implement this standard. Please address the information to the IETF at ietf-ipr@ietf.org.

Disclaimer of Validity

This document and the information contained herein are provided on an "AS IS" basis and THE CONTRIBUTOR, THE ORGANIZATION HE/SHE REPRESENTS OR IS SPONSORED BY (IF ANY), THE INTERNET SOCIETY AND THE INTERNET ENGINEERING TASK FORCE DISCLAIM ALL WARRANTIES, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO ANY WARRANTY THAT THE USE OF THE INFORMATION HEREIN WILL NOT INFRINGE ANY RIGHTS OR ANY IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.

Copyright Statement

Copyright (C) The Internet Society (2005). This document is subject to the rights, licenses and restrictions contained in [BCP 78](#), and except as set forth therein, the authors retain all their rights.

Acknowledgment

Funding for the RFC Editor function is currently provided by the Internet Society.

