

Workgroup: MPLS Working Group
Internet-Draft: draft-gandhi-mpls-ioam-04
Updates: [5586](#) (if approved)
Published: 2 March 2022
Intended Status: Standards Track
Expires: 3 September 2022
Authors: R. Gandhi, Ed. Z. Ali
 Cisco Systems, Inc. Cisco Systems, Inc.
 F. Brockners B. Wen B. Decraene V. Kozak
 Cisco Systems, Inc. Comcast Orange Comcast
 MPLS Data Plane Encapsulation for In-situ OAM Data

Abstract

In-situ Operations, Administration, and Maintenance (IOAM) is used for recording and collecting operational and telemetry information while the packet traverses a path between two points in the network. This document defines how IOAM data fields are transported with MPLS data plane encapsulation using new Generic Associated Channel (G-ACh) and updates the RFC 5586.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 3 September 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this

document must include Revised BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Revised BSD License.

Table of Contents

- [1. Introduction](#)
- [2. Conventions](#)
 - [2.1. Requirement Language](#)
 - [2.2. Abbreviations](#)
- [3. MPLS Extensions for IOAM Data Fields](#)
 - [3.1. IOAM Generic Associated Channel](#)
 - [3.2. IOAM Indicators](#)
- [4. Edge-to-Edge IOAM](#)
 - [4.1. IOAM Indicator](#)
 - [4.2. Procedure for Edge-to-Edge IOAM](#)
- [5. Hop-By-Hop IOAM](#)
 - [5.1. Hop-By-Hop Indicator](#)
 - [5.2. Procedure for Hop-By-Hop IOAM](#)
- [6. Considerations for IOAM](#)
 - [6.1. Considerations for ECMP](#)
 - [6.2. Node Capability](#)
 - [6.3. Nested MPLS Encapsulation](#)
- [7. Security Considerations](#)
- [8. IANA Considerations](#)
- [9. Appendix](#)
 - [9.1. MPLS Encapsulation with Control Word and Another G-ACh for IOAM Data Fields](#)
- [10. References](#)
 - [10.1. Normative References](#)
 - [10.2. Informative References](#)
- [Acknowledgements](#)
- [Authors' Addresses](#)

1. Introduction

In-situ Operations, Administration, and Maintenance (IOAM) is used for recording and collecting operational and telemetry information while the packet traverses a path between two points in the network. The term "in-situ" refers to the fact that the IOAM data fields are added to the data packets rather than being sent within the probe packets specifically dedicated to OAM. The IOAM data fields are defined in [[I-D.ietf-ippm-ioam-data](#)]. The IOAM data fields are further updated in [[I-D.ietf-ippm-ioam-direct-export](#)] for direct export use-cases.

This document defines how IOAM data fields are transported with MPLS data plane encapsulations using new Generic Associated Channel (G-ACh) and updates the [[RFC5586](#)].

2. Conventions

2.1. Requirement Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [\[RFC2119\]](#) [\[RFC8174\]](#) when, and only when, they appear in all capitals, as shown here.

2.2. Abbreviations

Abbreviations used in this document:

IOI IOAM Indicator

ECMP Equal Cost Multi-Path

E2E Edge-To-Edge

EL Entropy Label

ELI Entropy Label Indicator

ELC Entropy Label Control

G-ACh Generic Associated Channel

HBH Hop-By-Hop

HBI Hop-By-Hop Indicator

IOAM In-situ Operations, Administration, and Maintenance

MPLS Multiprotocol Label Switching

OAM Operations, Administration, and Maintenance

POT Proof-of-Transit

PW PseudoWire

3. MPLS Extensions for IOAM Data Fields

3.1. IOAM Generic Associated Channel

The IOAM header is added containing different IOAM-Data-Fields in the MPLS header as shown in Figure 1. The IOAM-Data-Fields MUST follow the definitions corresponding to IOAM-Option-Types (e.g. see Section 5 of [\[I-D.ietf-ippm-ioam-data\]](#) and Section 3.2 of [\[I-D.ietf-ippm-ioam-direct-export\]](#)). More than one trace options can be present in the IOAM-Data-Fields.

IP Version Number 0001b:

The first four octets are IP Version Field part of a G-ACh header, as defined in [[RFC5586](#)].

Version: The Version field is set to 0, as defined in [[RFC4385](#)].

Length: Length of IOAM G-ACh data in 4-octet units. Note that this field is marked as Reserved in [[RFC5586](#)] and is updated for the new IOAM G-ACh type by this document.

IOAM G-ACh: Generic Associated Channel (G-ACh) Type (value TBA1) for IOAM [[RFC5586](#)].

Reserved: Reserved Bits MUST be set to zero upon transmission and ignored upon receipt.

Block Number: The Block Number can be used to aggregate the IOAM data collected in data plane, e.g. to compute measurement metrics for each block of a data flow. It is also used to correlate the IOAM data on different nodes.

IOAM-OPT-Type: 8-bit field defining the IOAM Option type, as defined in the "IOAM Option-Type Registry" specified in [[I-D.ietf-ippm-ioam-data](#)].

IOAM HDR Length: 8-bit unsigned integer. Length of the IOAM Header in 4-octet units.

IOAM Option and Data Space: IOAM-Data-Fields as specified by the IOAM-OPT-Type field. IOAM-Data-Fields are defined corresponding to the IOAM-Option-Type (e.g. see Section 5 of [[I-D.ietf-ippm-ioam-data](#)] and Section 3.2 of [[I-D.ietf-ippm-ioam-direct-export](#)]).

3.2. IOAM Indicators

An IOAM Indicator MUST be used to indicate the presence of the IOAM-Data-Fields in the MPLS header. If both edge and intermediate nodes need to process IOAM data then both IOAM Indicator and HBH Indicator MUST be used. The HBH Indicator allows to optimize the IOAM processing on intermediate nodes and avoids the need to check all IOAM-Data-Fields.

A flag called IOI (IOAM Indicator) in the TTL of the X-Label is defined in this document to indicate the presence of IOAM. A flag called HBI (Hop-By-Hop Indicator) in the TTL of the X-Label is defined to indicate that HBH processing is required. The bit positions of these flags in the TTL field can be user-defined, consistently in the network. Alternatively, the bit positions of these flag can be allocated by IANA.

The X-Label can be a Special Purpose Label (value TBA1) assigned by IANA or a Network Programming Label (NPL) provisioned by a user [[I-D.jags-mpls-ext-hdr](#)] or an Entropy Label [[I-D.decraene-mpls-slid-encoded-entropy-label-id](#)].

4. Edge-to-Edge IOAM

4.1. IOAM Indicator

The IOAM Indicator is used to indicate the presence of the IOAM-Data-Fields in the MPLS header as shown in Figure 2.




Figure 2: Example MPLS Encapsulation for IOAM

The E2E IOAM-Data-Fields carry the Option-Type(s) that require processing on the encapsulating and decapsulating nodes only. The IOAM Option-Type carried can be IOAM Edge-to-Edge Option-Type [[I-D.ietf-ippm-ioam-data](#)]. The E2E IOAM-Data-Fields SHOULD NOT carry any IOAM Option-Type that require IOAM processing on the intermediate nodes as it will not be processed by them.

4.2. Procedure for Edge-to-Edge IOAM

The E2E IOM procedure is summarized as following:

- *The encapsulating node inserts the X-Label with the IOAM Indicator (Flag IOI) below the label whose FEC is the end (decapsulating) node and one or more IOAM-Data-Fields in the MPLS header.
- *The intermediate nodes do not process IOAM-Data-Fields.
- *The penultimate node MUST NOT remove the MPLS header. This is ensured by the encapsulating node by adding required MPLS header.

*The decapsulating node MAY punt a copy of the packet with the receive timestamp to the slow path for IOAM-Data-Fields processing when the node recognizes the IOAM Indicator. The receive timestamp is required by the various E2E OAM use-cases, including streaming telemetry. Note that the packet is not necessarily punted to the control-plane.

*The decapsulating node processes the IOAM-Data-Fields using the procedures defined in [[I-D.ietf-ippm-ioam-data](#)]. An example of IOAM processing is to export the IOAM-Data-Fields, send IOAM-Data-Fields via streaming telemetry, etc.

*The decapsulating node MUST remove the IOAM-Data-Fields from the received packet. The decapsulated packet is forwarded downstream or terminated locally similar to the regular IOAM-Data-Fields.

5. Hop-By-Hop IOAM

5.1. Hop-By-Hop Indicator

The IOAM Indicator (Flag IOI) along with Hop-By-Hop Indicator (Flag HBI) are used to indicate the presence of the HBH IOAM-Data-Fields in the MPLS header as shown in Figure 3.




Figure 3: Example MPLS Encapsulation for HBH IOAM

The HBH IOAM-Data-Fields carry the Option-Type(s) that require processing at the intermediate and/or encapsulating and decapsulating nodes. The IOAM Option-Type carried can be IOAM Pre-allocated Trace Option-Type, IOAM Incremental Trace Option-Type and IOAM Proof of Transit (POT) Option-Type, as well as Edge-to-Edge Option-Type [[I-D.ietf-ippm-ioam-data](#)].

5.2. Procedure for Hop-By-Hop IOAM

The HBH IOAM procedure is summarized as following:

- *The encapsulating node inserts the X-Label with the IOAM Indicator (Flag IOI) and HBH Indicator (Flag HBI) below the label whose FEC is the end (decapsulating) node and one or more IOAM-Data-Fields in the MPLS header.
- *The intermediate node enabled with HBH IOAM function processes the data packet including the IOAM-Data-Fields as defined in [[I-D.ietf-ippm-ioam-data](#)] when the node recognizes the HBH Indicator in the MPLS header.
- *The intermediate node MAY punt a copy of the packet with the receive timestamp to the slow path for IOAM-Data-Fields processing when the node recognizes the HBH Indicator. The receive timestamp is required by the various HBH OAM use-cases, including streaming telemetry. Note that the packet is not necessarily punted to the control-plane.
- *The intermediate node forwards a copy of the processed data packet downstream.
- *The penultimate node MUST NOT remove the MPLS header. This is ensured by the encapsulating node by adding required MPLS header.
- *The processing on the decapsulating node is same as E2E case.

6. Considerations for IOAM

6.1. Considerations for ECMP

The encapsulating node needs to make sure the IOAM-Data-Fields do not start with a well-known IP Version Number (e.g. 0x4 for IPv4 and 0x6 for IPv6) as that can alter the hashing function for ECMP that uses the IP header. This is achieved by using the IOAM G-ACh with IP Version Number 0001b after the MPLS label stack [[RFC5586](#)].

When entropy label [[RFC6790](#)] is used for hashing function for ECMP, the procedure defined in this document does not alter the ECMP behaviour.

6.2. Node Capability

The decapsulating node that has to remove the IOAM-Data-Fields and perform the IOAM function may not be capable of supporting it. The encapsulating node needs to know if the decapsulating node can support the IOAM function. The signaling extension for this capability exchange is outside the scope of this document.

The intermediate node that is not capable of supporting the IOAM functions defined in this document, can simply skip the IOAM processing.

6.3. Nested MPLS Encapsulation

When a packet is received with IOAM, the nested MPLS encapsulating node that supports a different IOAM, the node MUST add a new X-Label with the supported IOAM as part of the new MPLS encapsulation.

7. Security Considerations

The security considerations of IOAM in general are discussed in [[I-D.ietf-ippm-ioam-data](#)] and apply to the procedure defined in this document.

IOAM is considered a "per domain" feature, where one or several operators decide on configuring IOAM according to their needs. IOAM is intended for deployment in limited domains [[RFC8799](#)]. As such, it assumes that a node involved in IOAM operation has previously verified the integrity of the path. Still, operators need to properly secure the IOAM domain to avoid malicious configuration and use, which could include injecting malicious IOAM packets into the domain.

Routers that support G-ACh are subject to the same security considerations as defined in [[RFC4385](#)] and [[RFC5586](#)].

8. IANA Considerations

IANA maintains G-ACh Type Registry (see <https://www.iana.org/assignments/g-ach-parameters/g-ach-parameters.xhtml>). IANA is requested to allocate a value for IOAM G-ACh Type from "MPLS Generalized Associated Channel (G-ACh) Types (including Pseudowire Associated Channel Types)" registry.

Value	Description	Reference
TBA1	IOAM G-ACh Type	This document

Table 1: IOAM G-ACh Type

9. Appendix

9.1. MPLS Encapsulation with Control Word and Another G-ACh for IOAM Data Fields

The IOAM-Data-Fields, including IOAM G-ACh header are added in the MPLS encapsulation immediately after the MPLS header. Any Control Word [[RFC4385](#)] or another G-ACh [[RFC5586](#)] MUST be added after the IOAM-Data-Fields in the packet as shown in the Figure 6 and Figure

7, respectively. This allows the intermediate nodes to easily access the HBH IOAM-Data-Fields located immediately after the MPLS header. The decapsulating node can remove the MPLS encapsulation including the IOAM-Data-Fields and then process the Control Word or another G-ACh following it. The subsequent G-ACh and Control Word are located through the use of the "Length" field in the IOAM G-ACh.




Figure 4: Example MPLS Encapsulation with Generic PW Control Word with HBH IOAM




Figure 5: Example MPLS Encapsulation with Another G-ACh with HBH IOAM

10. References

10.1. Normative References

[I-D.ietf-ippm-ioam-data] Brockners, F., Bhandari, S., and T. Mizrahi, "Data Fields for In-situ OAM", Work in Progress, Internet-Draft, draft-ietf-ippm-ioam-data-17, 13 December 2021, <<https://www.ietf.org/archive/id/draft-ietf-ippm-ioam-data-17.txt>>.

[I-D.ietf-ippm-ioam-direct-export] Song, H., Gafni, B., Zhou, T., Li, Z., Brockners, F., Bhandari, S., Sivakolundu, R., and T. Mizrahi, "In-situ OAM Direct Exporting", Work in Progress, Internet-Draft, draft-ietf-ippm-ioam-direct-export-07, 13 October 2021, <<https://www.ietf.org/archive/id/draft-ietf-ippm-ioam-direct-export-07.txt>>.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", BCP 14, RFC 2119, DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC5586]

Bocci, M., Ed., Vigoureux, M., Ed., and S. Bryant, Ed., "MPLS Generic Associated Channel", RFC 5586, DOI 10.17487/RFC5586, June 2009, <<https://www.rfc-editor.org/info/rfc5586>>.

[RFC6790]

Kompella, K., Drake, J., Amante, S., Henderickx, W., and L. Yong, "The Use of Entropy Labels in MPLS Forwarding", RFC 6790, DOI 10.17487/RFC6790, November 2012, <<https://www.rfc-editor.org/info/rfc6790>>.

[RFC8174]

Leiba, B., "Ambiguity of Uppercase vs Lowercase in RFC 2119 Key Words", BCP 14, RFC 8174, DOI 10.17487/RFC8174, May 2017, <<https://www.rfc-editor.org/info/rfc8174>>.

10.2. Informative References

[I-D.dekraene-mpls-slid-encoded-entropy-label-id]

Decraene, B., Filsfils, C., Henderickx, W., Saad, T., Beeram, V. P., and L. Jalil, "Using Entropy Label for Network Slice Identification in MPLS networks.", Work in Progress, Internet-Draft, draft-dekraene-mpls-slid-encoded-entropy-label-id-03, 11 February 2022, <<https://www.ietf.org/archive/id/draft-dekraene-mpls-slid-encoded-entropy-label-id-03.txt>>.

[I-D.jags-mpls-ext-hdr]

Rajamanickam, J., Gandhi, R., Bhattacharya, J., Decraene, B., Zigler, R., Cheng, W., and L. Jalil, "MPLS Extension Header Encodings Using Entropy Label", Work in Progress, Internet-Draft, draft-jags-mpls-ext-hdr-00, 2 March 2022, <<https://www.ietf.org/archive/id/draft-jags-mpls-ext-hdr-00.txt>>.

[RFC4385]

Bryant, S., Swallow, G., Martini, L., and D. McPherson, "Pseudowire Emulation Edge-to-Edge (PWE3) Control Word for Use over an MPLS PSN", RFC 4385, DOI 10.17487/RFC4385, February 2006, <<https://www.rfc-editor.org/info/rfc4385>>.

[RFC8799]

Carpenter, B. and B. Liu, "Limited Domains and Internet Protocols", RFC 8799, DOI 10.17487/RFC8799, July 2020, <<https://www.rfc-editor.org/info/rfc8799>>.

Acknowledgements

The authors would like to thank Patrick Khordoc, Sagar Soni, Shwetha Bhandari, Clarence Filsfils, and Vengada Prasad Govindan for the discussions on IOAM. The authors would also like to thank Tarek Saad, Loa Andersson, Greg Mirsky, Stewart Bryant, Xiao Min, and

Cheng Li for providing many useful comments. The authors would also like to thank Mach Chen, Andrew Malis, Matthew Bocci, and Nick Delregno for the MPLS-RT reviews.

Authors' Addresses

Rakesh Gandhi (editor)
Cisco Systems, Inc.
Canada

Email: rgandhi@cisco.com

Zafar Ali
Cisco Systems, Inc.

Email: zali@cisco.com

Frank Brockners
Cisco Systems, Inc.
Hansaallee 249, 3rd Floor
DUESSELDORF, NORDRHEIN-WESTFALEN 40549
Germany

Email: fbrockne@cisco.com

Bin Wen
Comcast

Email: Bin_Wen@cable.comcast.com

Bruno Decraene
Orange

Email: bruno.decraene@orange.com

Voitek Kozak
Comcast

Email: Voitek_Kozak@comcast.com