

Network Working Group
Internet-Draft
Intended status: Experimental
Expires: October 16, 2021

X. Geng
Z. Hu
Huawei
April 14, 2021

YANG Model for Scalable VTN
draft-geng-teas-enhanced-vpn-scalable-vtn-yang-00

Abstract

This document defines the Yang data model for scalable Virtual Transport Network(VTN).

Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [RFC 2119](#) [[RFC2119](#)].

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on October 16, 2021.

Copyright Notice

Copyright (c) 2021 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must

Internet-Draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	2
2.	VTN Yang Module Requirement	3
2.1.	VTN Creation	3
2.2.	VTN Initiation	4
2.3.	VTN Traffic Steering	4
3.	VTN Yang Module Tree	5
4.	VTN Yang Module	6
5.	IANA Considerations	10
6.	Contributor	10
7.	References	10
7.1.	Normative References	11
7.2.	Informative References	12
Appendix A.	An Appendix	12
Authors' Addresses		12

[1.](#) Introduction

[I-D.ietf-teas-ietf-network-slice-definition] defines IETF network slices that provide connectivity coupled with network resources commitment between a number of endpoints over a shared network infrastructure.

Enhanced VPN (VPN+) aims to provide enhancements to existing VPN services to support network slicing. VPN+ is composed of a VPN overlay and an underlying Virtual Transport Network (VTN) which has a customized network topology and a set of dedicated or shared resources in the underlay network. VPN+ and VTN are defined in [I-D.ietf-teas-enhanced-vpn].

[I-D.dong-teas-enhanced-vpn-vtn-scalability] describes the scalability considerations in the control plane and data plane to enable VPN+ services. In control plane, decoupling the topology and resource attributes of VTN allows that multiple VTNs share the same topology. In data plane, a global VTN-ID in the data packet is used to determine the set of resources reserved for the corresponding VTN.

This document defines the configuration yang model for scalable VTN

solution.

Internet-Draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

[2.](#) VTN Yang Module Requirement

The general process of VTN configuration includes:

1. Creat VTN instance based on the network slice requirement
2. Configure the overlay network to initiate VTN in the network
3. Steer the traffic to the corresponding VTN to provide network slice service

The corresponding requirement of VTN configuration data model during the process is defined in this section.

[2.1.](#) VTN Creation

After collecting information about the underlying network topology and available resources. Each VTN can have a customized topology and a set of network resources allocated. Flexible combination is allowed when multiple VTNs may shared the same topology, or multiple VTNs may share the same set of network resources.

VTN is created with the following attributes:

- o VTN Topology: Based on the existing work in IETF, topology specification for VTN could be implemented by Multi-Topology Routing (MTR) which defined in [[RFC4915](#)], [[RFC5120](#)], or Flex-algo which is defined in [[I-D.ietf-lsr-flex-algo](#)]. Correspondingly, the topology attribute of a VTN could be determined by MT-ID or algorithm ID; Signaling extensions for VTN topology is defined in [[I-D.zhu-lsr-isis-sr-vtn-flexalgo](#)] and [[I-D.ietf-lsr-isis-sr-vtn-mt](#)] respectively.
- o Network Resource: network resource is allocated for VTN based on the requirement. For example, VTN could be bound with a layer 2 sub-interface with a subset of the link bandwidth.

- o VTN Data Plane Identifier: VTN data plane identifier is used to identify network resource that has been allocated for the VTN. VTN data plane identifier depends on the encapsulation type of the traffic, for example IPv6 defined in [\[I-D.dong-6man-enhanced-vpn-vtn-id\]](#). VTN data plane identifier is not mandatory when there are other methods to distinguish VTN instances.

Internet-Draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

[2.2.](#) VTN Initiation

VTN initiation in the network also includes two aspects: resource allocation and traffic steering through VTN specified topology. Resource allocation is defined in this section and traffic steering is defined in the next section.

Several technologies could be used for resource allocation in the network device, for example: TSN defined in IEEE 802.1 introduces the concept of time aware shaping; FlexE provides the ability to multiplex multiple channels over one or more Ethernet links; Existing Diffserv scheduling/shaping allow the construction of virtual sub-interfaces. All these technologies could be used to dedicated resource in a shared physical interface.

The configuration of these technologies play the role of VTN initiation when the allocated resource is bound with a specified VTN instance.

[2.3.](#) VTN Traffic Steering

Just as color in SR policy defined in [\[I-D.ietf-spring-segment-routing-policy\]](#), color is defined as an attribute of VTN to steer the traffic.

With SR policy, traffic could be steered into a SR policy by :

- o SR policy with color is provisioned to the headend;

- o The route with some particular color matches the SR policy with the corresponding color, which could satisfy the requirement of the route
- o Traffic with the route is steered into the SR policy;

Similarly, traffic could be steered into VTN by:

- o VTN is configured with the attribute of color;
- o The route with some particular color matches VTN with the corresponding color, which could satisfy the requirement of the route
- o Traffic with the route is steered to the VTN

SR policy could also be bound with VTN to provide resource reservation in the network. BGP SR Policy extensions for VTN is defined in [[I-D.dong-idr-sr-policy-vtn](#)] and similarly, YANG model

Internet-Draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

which is used to bound SR policy to a specified VTN is defined in this document by:

- o SR policy with color is provisioned to the headend; The preferred candidate path is bound to VTN;
- o The route with some particular color matches the SR policy with the corresponding color, which could satisfy the requirement of the route
- o Traffic with the route is steered into the SR policy; Packet is encapsulated with the VTN data plane identifier.

[3.](#) VTN Yang Module Tree

```

module: ietf-vtn
  +--rw vtn-instance
  |   +--rw vtn-instance* [vtn-id]
  |       +--rw vtn-id                               uint32
  |       +--rw vtn-topology
  |           | +--rw (vtn-topolgy-type)?
  |           | +--:(flex-algo)

```

```

|         |         |   +---rw flex-algo
|         |         |       +---rw flex-algo-id?   uint32
|         |         +---:(multi-topology)
|         |             +---rw multi-topology-id?   uint32
|         +---rw vtn-data-plane-identifier?   uint32
+---rw sr-policy-extension
    +---rw vtn
        +---rw vtn-id?   uint32

augment /if:interfaces/if:interface:
    +---rw interface-configuration-for-vtn
        +---rw (vtn-interface-binding-type)?
            +---:(layer-2-sub-interface)
                |   +---rw layer-2-sub-interface
                |       +---rw sub-interface-id?   uint32
                |       +---rw vtn-id?             uint32
                |       +---rw bandwidth?          uint32
            +---:(queue)
                +---rw queue
                    +---rw queue-id?   uint32
                    +---rw vtn-id?     uint32
                    +---rw bandwidth?  uint32
augment /ni:network-instances/ni:network-instance:
    +---rw vtn-traffic-steering
        +---rw color-index?   uint32
        +---rw vtn-id?        uint32

```

[4.](#) VTN Yang Module

```

module ietf-vtn {
  yang-version 1.1;
  namespace "urn:ietf:params:xml:ns:yang:ietf-vtn";
  prefix "ietf-vtn";

  import ietf-inet-types {
    prefix "inet";
  }

  import ietf-routing {
    prefix "rt";
  }

```

```

import ietf-routing-types {
    prefix "rt-types";
}

import ietf-yang-types {
    prefix "yang";
}

import ietf-interfaces {
    prefix "if";
}

import ietf-network-instance {
    prefix "ni";
}

organization "IETF TEAS Working Group";

contact
    "
        WG Web: <http://tools.ietf.org/wg/teas/>
        WG List:<mailto:teas@ietf.org>

        Editor: Xuesong Geng
                <mailto:gengxuesong@huawei.com>
        Editor: Zhibo Hu
                <mailto:huzhibo@huawei.com>
    ";

description
    "This YANG module defines a data model for VTN(Virtual Transport Network)";

revision "2021-04-14" {

```

```

    description
        "This is the initial version of VTN yang module";
    reference
        "RFC XXX: YANG Data Model for VTN";
}

grouping vtn-instances{
    description

```

```

        "VTN instances";
list vtn-instance {
    key "vtn-id";
    description
        "vtn instance list";
    leaf vtn-id {
        type uint32;
        description
            "vtn-id";
    }
    container vtn-topology {
        description
            "vtn topology is nt";
        choice vtn-topology-type{
            description
                "customized topology of VTN";
            case flex-algo {
                container flex-algo {
                    description
                        "flex-algo could be used as topology specification";
                    leaf flex-algo-id {
                        type uint32;
                        description
                            "flex-algo-id for VTN";
                    }
                }
            }
            case multi-topology {
                description
                    "MT could be used as topology specification for VTN";
                leaf multi-topology-id{
                    type uint32;
                    description
                        "MT-id for VTN";
                }
            }
        }
    }
    leaf vtn-data-plane-identifier {
        type uint32;
    }
}

```



```

        "VTN identifier of data plane for vtn distinguishment";
    }
}

```

```

grouping interface-configuration-for-vtn{
    description
        "interface configuration for vtn";
    container interface-configuration-for-vtn {
        description
            "interface configuration for vtn";
        choice vtn-interface-binding-type{
            description
                "vtn interface binding type";
            case layer-2-sub-interface {
                description
                    "vtn is bound to a layer-2 sub-interface";
                container layer-2-sub-interface {
                    description
                        "sub-interface configuration";
                    leaf sub-interface-id {
                        type uint32;
                        description
                            "sub-interface id";
                    }
                    leaf vtn-id {
                        type uint32;
                        description
                            "vtn-id";
                    }
                    leaf bandwidth {
                        type uint32;
                        description
                            "bandwidth allocation for the slice";
                    }
                }
            }
            case queue {
                description
                    "vtn is bound to a queue in the interface";
                container queue {
                    description
                        "queue configuration";
                    leaf queue-id {
                        type uint32;
                        description
                            "queue id";
                    }
                }
            }
        }
    }
}

```

```
    }
    leaf vtn-id {
        type uint32;
        description
            "queue id";
    }
    leaf bandwidth {
        type uint32;
        description
            "bandwidth allocation for the slice";
    }
}
}
}
}

grouping sr-policy-traffic-steering{
    container vtn{
        description
            "candidate path is bound to VTN";
        leaf vtn-id{
            type uint32;
            description
                "vtn";
        }
    }
}

grouping vtn-traffic-steering{
    container vtn-traffic-steering {
        leaf color-index {
            type uint32;
            description
                "color index";
        }
        leaf vtn-id {
            type uint32;
            description
                "vtn id";
        }
    }
}

container vtn-instance {
    description
```

```
    "vtn instance configuraiton";
    uses vtn-instances;
```

Internet-Draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

```
    }

    augment "/if:interfaces/if:interface" {
        description
            "interface model extension for vtn";
        uses interface-configuration-for-vtn;
    }

    augment /ni:network-instances/ni:network-instance{
        description
            "network instance model extension for vtn";
        uses vtn-traffic-steering;
    }

    container sr-policy-extension {
        description
            "sr policy extension for vtn";
        uses sr-policy-traffic-steering;
    }
}
```

[5.](#) IANA Considerations

This document makes no request of IANA.

Note to RFC Editor: this section may be removed on publication as an RFC.

[6.](#) Contributor

Zhenbin Li
Huawei

Email: lizhenbin@huawei.com

Jie Dong

Huawei

Email: jie.dong@huawei.com

7. References

Geng & Hu

Expires October 16, 2021

[Page 10]

Internet-Draft-draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

7.1. Normative References

[I-D.dong-6man-enhanced-vpn-vtn-id]

Dong, J., Li, Z., Xie, C., and C. Ma, "Carrying Virtual Transport Network Identifier in IPv6 Extension Header", [draft-dong-6man-enhanced-vpn-vtn-id-02](#) (work in progress), November 2020.

[I-D.dong-idr-sr-policy-vtn]

Dong, J., Hu, Z., and R. Pang, "BGP SR Policy Extensions for Virtual Transport Network", [draft-dong-idr-sr-policy-vtn-00](#) (work in progress), October 2020.

[I-D.dong-teas-enhanced-vpn-vtn-scalability]

Dong, J., Li, Z., Qin, F., and G. Yang, "Scalability Considerations for Enhanced VPN (VPN+)", [draft-dong-teas-enhanced-vpn-vtn-scalability-01](#) (work in progress), November 2020.

[I-D.ietf-lsr-flex-algo]

Psenak, P., Hegde, S., Filsfils, C., Talaulikar, K., and A. Gulko, "IGP Flexible Algorithm", [draft-ietf-lsr-flex-algo-13](#) (work in progress), October 2020.

[I-D.ietf-lsr-isis-sr-vtn-mt]

Xie, C., Ma, C., Dong, J., and Z. Li, "Using IS-IS Multi-Topology (MT) for Segment Routing based Virtual Transport Network", [draft-ietf-lsr-isis-sr-vtn-mt-00](#) (work in progress), March 2021.

[I-D.ietf-spring-segment-routing-policy]

Filsfils, C., Talaulikar, K., Voyer, D., Bogdanov, A., and

P. Mattes, "Segment Routing Policy Architecture", [draft-ietf-spring-segment-routing-policy-09](#) (work in progress), November 2020.

[I-D.ietf-teas-enhanced-vpn]

Dong, J., Bryant, S., Li, Z., Miyasaka, T., and Y. Lee, "A Framework for Enhanced Virtual Private Networks (VPN+) Service", [draft-ietf-teas-enhanced-vpn-06](#) (work in progress), July 2020.

[I-D.ietf-teas-ietf-network-slice-definition]

Rokui, R., Homma, S., Makhijani, K., Contreras, L., and J. Tantsura, "Definition of IETF Network Slices", [draft-ietf-teas-ietf-network-slice-definition-00](#) (work in progress), January 2021.

Internet-Draft draft-geng-teas-enhanced-vpn-scalable-vtn-yang-0 April 2021

[I-D.zhu-lsr-isis-sr-vtn-flexalgo]

Zhu, Y., Dong, J., and Z. Hu, "Using Flex-Algo for Segment Routing based VTN", [draft-zhu-lsr-isis-sr-vtn-flexalgo-01](#) (work in progress), September 2020.

[RFC2119] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), DOI 10.17487/RFC2119, March 1997, <<https://www.rfc-editor.org/info/rfc2119>>.

[RFC4915] Psenak, P., Mirtorabi, S., Roy, A., Nguyen, L., and P. Pillay-Esnault, "Multi-Topology (MT) Routing in OSPF", [RFC 4915](#), DOI 10.17487/RFC4915, June 2007, <<https://www.rfc-editor.org/info/rfc4915>>.

[RFC5120] Przygienda, T., Shen, N., and N. Sheth, "M-ISIS: Multi Topology (MT) Routing in Intermediate System to Intermediate Systems (IS-ISs)", [RFC 5120](#), DOI 10.17487/RFC5120, February 2008, <<https://www.rfc-editor.org/info/rfc5120>>.

[7.2.](#) Informative References

[InfRef] , 2004.

[Appendix A](#). An Appendix

Authors' Addresses

Xuesong Geng
Huawei

Email: gengxuesong@huawei.com

Zhibo Hu
Huawei

Email: huzhibo@huawei.com