

Network Working Group
INTERNET-DRAFT
Updates: [RFC1035](#), [RFC1183](#)
Category: Experimental

Arnt Gulbrandsen
Troll Technologies
Paul Vixie
Vixie Enterprises
January 1996

A DNS RR for specifying the location of services

Abstract

This document describes a DNS RR which specifies the location of the server(s) for a specific protocol and domain (like a more general form of MX).

Status of this memo

This document is an Internet-Draft. Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as ``work in progress.''

To learn the current status of any Internet-Draft, please check the "lid-abstracts.txt" listing contained in the Internet-Drafts Shadow Directories on ds.internic.net (US East Coast), nic.nordu.net (Europe), ftp.isi.edu (US West Coast), or munnari.oz.au (Pacific Rim).

This draft has file name "[draft-gulbrandsen-dns-rr-srvcs-02.txt](#)" and expires on July 20, 1996.

Overview and rationale

Currently, one must either know the exact address of a server to contact it, or broadcast a question. This has led to e.g. ftp.whatever.com aliases, the SMTP-specific MX RR, and using MAC-level broadcasts to locate servers.

The SRV RR allows administrators to use several servers for a single domain, to move services from host to host with little fuss, and to

Expires July 1996

DNS Service Pointer RR

May 1995

designate some hosts as primary servers for a service and others as backups.

Clients ask for a specific service/protocol for a specific domain (the word domain is used here in the strict [RFC1034](#) sense), and get back the names of any available servers.

Introductory example

When a SRV-cognizant web browser wants to retrieve

<http://www.asdf.com/>

it does a lookup of

http.tcp.www.asdf.com

and retrieves the document from one of the servers in the reply. The example zone file near the end of the draft contains answering RRs for this query.

The format of the SRV RR

Here is the format of the SRV RR:

service.protocol.name ttl class SRV priority weight port target

(There is an example near the end of the RFC.)

Service

The symbolic name of the desired service, as defined in Assigned Numbers or locally.

Some widely used services, notably POP, don't have a single universal name. If Assigned Numbers names the service indicated, that name is the only name which is legal for SRV lookups. Only locally defined services may be named locally.

The Service is case insensitive (it has to be, it's part of the DNS look-up key).

Protocol

The symbolic name of the desired protocol. TCP and UDP are at present the most useful values for this field, though any name defined by Assigned Numbers or locally may be used (as for Service). Case insensitive.

Expires July 1996

DNS Service Pointer RR

May 1995

Name

The domain this RR refers to. The SRV RR is unique in that the name one searches for is not this name; the example near the end shows this clearly.

TTL

Standard DNS meaning.

Class

Standard DNS meaning.

Priority

As for MX, the priority of this target host. A client MUST attempt to contact the target host with the lowest-numbered priority it can reach; target hosts with the same priority SHOULD be tried in pseudorandom order. The range is 0-65535.

Weight

Load balancing mechanism. When selecting a target host among the those that have the same priority, the chance of trying this one first SHOULD be proportional to its weight. The range of this number is 1-65535. Domain administrators are urged to use Weight 0 when there isn't any load balancing to do, to make the RR easier to read for humans (less noisy).

Port

The port on this target host of this service. The range is 0-65535. This is often as specified in Assigned Numbers but need not be.

Target

As for MX, the domain name of the target host. There MUST be one or more A records for this name. Implementors are urged, but not required, to return the A record(s) in the Additional Data section. Name compression is to be used for this field.

A Target of "." means that the service is decidedly not available at this domain.

Domain administrator advice

Asking everyone to update their telnet (for example) clients when the first internet site adds a SRV RR for Telnet/TCP is futile (even if desirable). Therefore SRV will have to coexist with A record lookups for a long time, and DNS administrators should try to provide A records to support old clients:

Gulbrandsen and Vixie

[Page 3]

Expires July 1996

DNS Service Pointer RR

May 1995

- Where the services for a single domain are spread over several hosts, it seems advisable to have a list of A RRs at the same DNS node as the SRV RR, listing reasonable (if perhaps suboptimal) fallback hosts for Telnet, NNTP and other protocols likely to be used with this name. Note that some programs only try the first address they get back from e.g. `gethostbyname()`, and we don't know how widespread this behaviour is.
- Where one service is provided by several hosts, one can either provide A records for all the hosts (in which case the round-robin mechanism, where available, will share the load equally) or just for one (presumably the fastest).
- If a host is intended to provide a service only when the main server(s) is/are down, it probably shouldn't be listed in A records.
- Hosts that are referenced by backup A records must use the port number specified in Assigned Numbers for the service.

Currently there's a practical limit of 512 bytes for DNS replies. Until all resolvers can handle larger responses, domain administrators are strongly advised to keep their SRV replies below 512 bytes.

All round numbers, wrote Dr. Johnson, are false, and these numbers are very round: A reply packet has a 30-byte overhead plus the name of the service ("telnet.tcp.asdf.com" for instance); each SRV RR adds 20 bytes plus the name of the target host; each NS RR in the NS section is 15 bytes plus the name of the name server host; and finally

each A RR in the additional data section is 20 bytes or so, and there are A's for each SRV and NS RR mentioned in the answer. This size estimate is extremely crude, but shouldn't underestimate the actual answer size by much. If an answer may be close to the limit, using e.g. "dig" to look at the actual answer is a good idea.

The "Weight" field

Weight, the load balancing field, is not quite satisfactory, but the actual load on typical servers changes much too quickly to be kept around in DNS caches. It seems to the authors that offering administrators a way to say "this machine is three times as fast as that one" is the best that can practically be done.

The only way the authors can see of getting a "better" load figure is asking a separate server when the client selects a server and contacts it. For short-lived services like SMTP an extra step in the connection establishment seems too expensive, and for long-lived

services like telnet, the load figure may well be thrown off a minute after the connection is established when someone else starts or finishes a heavy job.

The Port number

Currently, the translation from service name to port number happens at the client, often using a file such as /etc/services.

Moving this information to the DNS makes it less necessary to update these files on every single computer of the net every time a new service is added, and makes it possible to move standard services out of the "root-only" port range on unix.

Usage rules

A SRV-cognizant client SHOULD use this procedure to locate a list of servers and connect to the preferred one:

Do a lookup for QNAME=service.protocol.target, QCLASS=IN,

QTYPE=SRV.

If the reply is NOERROR, ANCOUNT>0 and there is at least one SRV RR which specifies the requested Service and Protocol in the reply:

If there is precisely one SRV RR, and its Target is "." (the root domain), abort.

Else, for all such RR's, build a list of (Priority, Weight, Target) tuples

Sort the list by priority (lowest number first)

Create a new empty list

For each distinct priority level

While there are still elements left at this priority level

Select an element randomly, with probability Weight, and move it to the tail of the new list

For each element in the new list

query the DNS for A RR's for the Target or use any RR's found in the Additional Data section of the

earlier SRV query.

for each A RR found, try to connect to the (protocol, address, service).

else if the service desired is SMTP

skip to [RFC974](#) (MX).

else

Do a lookup for QNAME=target, QCLASS=IN, QTYPE=A

for each A RR found, try to connect to the (protocol, address, service)

Notes:

- Port numbers SHOULD NOT be used in place of the symbolic service or protocol names (for the same reason why variant names cannot be allowed: Applications would have to do two or more lookups).
- If a truncated response comes back from an SRV query, and the Additional Data section has at least one complete RR in it, the answer MUST be considered complete and the client resolver SHOULD NOT retry the query using TCP, but use normal UDP queries for A RR's missing from the Additional Data section.
- A client MAY use means other than Weight to choose among target hosts with equal Priority.
- A client MUST parse all of the RR's in the reply.
- If the Additional Data section doesn't contain A RR's for all the SRV RR's and the client may want to connect to the target host(s) involved, the client MUST look up the A RR(s). (This happens quite often when the A RR has shorter TTL than the SRV or NS RR's.)
- SRV RRs with Protocol TCP and Service SMTP override MX RR's. This allows firewalled organizations with several SMTP relays to control the load distribution using the Weight field.
- Designers of new protocols are urged to specify that SRV lookups be mandatory for those protocols.

Fictional example

Gulbrandsen and Vixie

[Page 6]

Expires July 1996

DNS Service Pointer RR

May 1995

This is (part of) the zone file for asdf.com, a still-unused domain:

```
$ORIGIN asdf.com.  
@          SOA server.asdf.com. root.asdf.com. (   
              1995032001 3600 3600 604800 86400 )  
          NS  server.asdf.com.  
          NS  ns1.ip-provider.net.  
          NS  ns2.ip-provider.net.
```

```

ftp.tcp          SRV 0 0 21 server.asdf.com.
finger.tcp       SRV 0 0 79 server.asdf.com.
; telnet - use old-slow-box or new-fast-box if either is
; available, make three quarters of the logins go to
; new-fast-box.
telnet.tcp        SRV 0 1 23 old-slow-box.asdf.com.
                  SRV 0 3 23 new-fast-box.asdf.com.
; if neither old-slow-box or new-fast-box is up, switch to
; using the sysadmin's box and the server
                  SRV 1 0 23 sysadmins-box.asdf.com.
                  SRV 1 0 23 server.asdf.com.
; HTTP - server is the main server, new-fast-box is the backup
; (On new-fast-box, the HTTP daemon runs on port 8000)
http.tcp          SRV 0 0 80 server.asdf.com.
                  SRV 10 0 8000 new-fast-box.asdf.com.
; since we want to support both http://asdf.com/ and
; http://www.asdf.com/ we need the next two RRs as well
http.tcp.www      SRV 0 0 80 server.asdf.com.
                  SRV 10 0 8000 new-fast-box.asdf.com.
; SMTP - mail goes to the server, and to the IP provider if
; the net is down
smtp.tcp          SRV 0 0 25 server.asdf.com.
                  SRV 1 0 25 mailhost.ip-provider.net.
@                MX 0 server.asdf.com.
                  MX 1 mailhost.ip-provider.net.
; NNTP - use the IP providers's NNTP server
nntp.tcp          SRV 0 0 119 nntphost.ip-provider.net.
; IDB is an locally defined protocol
idb.tcp           SRV 0 0 2025 new-fast-box.asdf.com.
; addresses
server            A 172.30.79.10
old-slow-box      A 172.30.79.11
sysadmins-box    A 172.30.79.12
new-fast-box      A 172.30.79.13
; backup A records - new-fast-box and old-slow-box are
; included, naturally, and server is too, but might go
; if the load got too bad
@                A 172.30.79.10
                  A 172.30.79.11
                  A 172.30.79.13

```



```
www           A           172.30.79.10
; NO other services are supported
*.tcp         SRV  0 0 0 .
*.udp         SRV  0 0 0 .
```

In this example, a telnet connection to "asdf.com." needs an SRV lookup of "telnet.tcp.asdf.com." and possibly A lookups of "new-fast-box.asdf.com." and/or the other hosts named. The size of the SRV reply is approximately 365 bytes:

```
30 bytes general overhead
20 bytes for the query string, "telnet.tcp.asdf.com."
130 bytes for 4 SRV RR's, 20 bytes each plus the lengths of "new-
fast-box", "old-slow-box", "server" and "sysadmins-box" -
"asdf.com" in the query section is quoted here and doesn't need
to be counted again.
75 bytes for 3 NS RR's, 15 bytes each plus the lengths of "server",
"ns1.ip-provider.net." and "ns2" - again, "ip-provider.net." is
quoted and only needs to be counted once.
120 bytes for the 6 A RR's mentioned by the SRV and NS RR's.
```

References

[RFC 1794](#): T. Brisco, "DNS Support for Load Balancing", 04/20/1995.

[RFC 1713](#): A. Romao, "Tools for DNS debugging", 11/03/1994.

[RFC 1712](#): C. Farrell, M. Schulze, S. Pleitner, D. Baldoni, "DNS Encoding of Geographical Location", 11/01/1994.

[RFC 1706](#): B. Manning, R. Colella, "DNS NSAP Resource Records", 10/26/1994.

[RFC 1700](#): J. Reynolds, J. Postel, "ASSIGNED NUMBERS", 10/20/1994.

[RFC 1536](#): A. Kumar, J. Postel, C. Neuman, P. Danzig, S. Miller, "Common DNS Implementation Errors and Suggested Fixes.", 10/06/1993.

[RFC 1183](#): R. Ullmann, P. Mockapetris, L. Mamakos, C. Everhart, "New DNS RR Definitions", 10/08/1990.

[RFC 1101](#): P. Mockapetris, "DNS encoding of network names and other types", 04/01/1989.

[RFC 1035](#): P. Mockapetris, "Domain names - implementation and specification", 11/01/1987.

[RFC 1034](#): P. Mockapetris, "Domain names - concepts and facilities", 11/01/1987.

[RFC 1033](#): M. Lottor, "Domain administrators operations guide", 11/01/1987.

[RFC 1032](#): M. Stahl, "Domain administrators guide", 11/01/1987.

[RFC 974](#): C. Partridge, "Mail routing and the domain system", 01/01/1986.

Security Considerations

The authors believes this RR to not cause any new security problems. Some problems become more visible, though.

- The ability to specify ports on a fine-grained basis obviously changes how a router can filter packets. It becomes impossible to block internal clients from accessing specific external services, slightly harder to block internal users from running unauthorised services, and more important for the router operations and DNS operations personnel to cooperate.
- There is no way a site can keep its hosts from being referenced as servers (as, indeed, some sites become unwilling secondary MXes today). This could lead to denial of service.
- With SRV, DNS spoofers can supply false port numbers, as well as host names and addresses. The authors do not see any practical effect of this.

We assume that as the DNS-security people invent new features, DNS servers will return the relevant RRs in the Additional Data section when answering an SRV query.

Authors' Addresses

Arnt Gulbrandsen
Troll Tech
Postboks 6133 Etterstad
N-0602 Oslo
Norway

Phone: +47 22646966

Mail: agulbra@troll.no

Gulbrandsen and Vixie

[Page 9]

Expires July 1996

DNS Service Pointer RR

May 1995

Paul Vixie
Vixie Enterprises
Star Route 159A
Woodside, CA 94062

Phone: (415) 747-0204

Mail: paul@vix.com

