

Internet Engineering Task Force
INTERNET DRAFT
26 June 2000
Expires in six months

Erik Guttman
Sun Microsystems

Vendor Extensions for Service Location Protocol, Version 2
[draft-guttman-svrloc-vendor-ext-03.txt](#)

Status of this Memo

This document is an individual contribution for consideration by the Internet Engineering Task Force. Comments should be submitted to the svrloc@svrloc.org mailing list. This document is intended to be submitted to the IESG for consideration as an Informational RFC.

Distribution of this memo is unlimited.

This document is an Internet-Draft and is in full conformance with all provisions of [Section 10 of RFC2026](#). Internet-Drafts are working documents of the Internet Engineering Task Force (IETF), its areas, and its working groups. Note that other groups may also distribute working documents as Internet-Drafts.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

The list of current Internet-Drafts can be accessed at:

<http://www.ietf.org/ietf/1id-abstracts.txt>

The list of Internet-Draft Shadow Directories can be accessed at:

<http://www.ietf.org/shadow.html>.

Copyright (C) The Internet Society 1999. All Rights Reserved.

Abstract

The Service Location Protocol, Version 2 [[1](#)] contains a number of features which are left up to vendors. This document describes how each of these features can be used safely (with no possibility of name collisions). This document also describes how vendors can extend the protocol safely without requiring any IETF standardization work. Finally, this document defines a new extension to the SLPv2: The Vendor Opaque extension.

This document UPDATES [RFC 2608](#).

Table of Contents

1.0	Introduction	2
1.1	Terminology	2
2.0	Enterprise Numbers	3
3.0	Naming Authorities	3
4.0	Vendor Defined Attributes	4
5.0	Vendor Opaque Extension	5
5.1	Vendor Opaque Extension Format	6
5.2	Example: Acme Extension for UA Authentication	6
6.0	Extensions Requiring IETF Action	7
7.0	IANA Considerations	8
8.0	Security Considerations	8
	References	8
	Author's Address	9

[1.0](#) Introduction

The Service Location Protocol, Version 2 [[1](#)] defines a number of features which are extensible. This document clarifies exactly which mechanisms can be used to that end (Sections [3-5](#)) and which cannot ([Section 6](#)). Conventions are specified which ensure that the protocol extension mechanisms in the SLPv2 specification will not possibly have ambiguous interpretations.

This specification introduces only one new protocol element, the Vendor Opaque Extension. This Extension makes it possible for a vendor to extend SLP independently, once the vendor has registered itself with IANA and obtained an Enterprise Number. This is useful for vendor-specific applications, for which interoperability with other vendors may not be required or even desirable.

[1.1](#) Terminology

In this document, the key words "MAY", "MUST", "MUST NOT", "optional", "recommended", "SHOULD", and "SHOULD NOT", are to be interpreted as

described in [\[2\]](#).

E. Guttman

Expires: 16 April 2001

[Page 2]

Service Location Protocol terminology is defined in [1]. IANA registration terminology is defined in [6].

2.0 Enterprise Number

Enterprise Numbers are used to distinguish different vendors in IETF protocols. Vendor Extensions to SLPv2 SHOULD use these values to avoid any possibility of a name space collision. Each vendor is responsible for ensuring that vendor extensions under their own authority are non-conflicting.

[RFC 1700](#) lists the Enterprise Numbers registered at the time of publication as well as rules on how to register new numbers:

To request an assignment of an Enterprise Number send the complete company name, address, and phone number; and the contact's person complete name, address, phone number, and email mailbox in an email message to <iana-mib@isi.edu>. [3]

The complete up-to-date list is maintained by IANA [4].

All a Vendor must do is register their Vendor ID and they are then able to extend SLPv2 in many ways without requiring any additional interaction with any standards organization.

3.0 Naming Authorities

Naming Authorities are defined by SLPv2 [1] as an agency or group which catalogues Service Types and attributes.

A Service Type is a string representing a service which can be discovered by SLPv2. Attributes may be associated with a particular Service Type which is advertised by SLPv2.

Service Type strings and service attributes may be registered with IANA by creating a Service Template [5]. The template is included in an internet draft and an email message is sent to srvloc-list@iana.org requesting that the template be included in the Service Template registry. In this case the naming authority for the service type is IANA.

It is also possible for a Vendor to create their own naming authority. In this case, any service type or attributes may be used. SLPv2 allows arbitrary naming authorities to coexist. To use an explicit naming authority, a vendor simply employs their Enterprise Number as a naming authority. For example, for the following (fictitious) Enterprise Number

the Naming Authority string to use would be "9999". A service: URL

E. Guttman

Expires: 16 April 2001

[Page 3]

which used this Naming Authority to advertise a Roadrunner Detector service could look like

```
service:roadrunner-detector.9999://neato.org:9341
```

Service types which are defined under a naming authority based on an Enterprise Number are guaranteed not to conflict with other service type strings which mean something entirely different. That is also true of attributes defined for service types defined under a naming authority.

To create a safe naming authority with no possibility of name collisions, a vendor SHOULD use their Enterprise Number as a naming authority.

4.0 Vendor Defined Attributes

SLPv2 [\[1\]](#) suggests that

Non-standard attribute names SHOULD begin with "x-", because no standard attribute name will ever have those initial characters.

It is possible that two non-standard attributes will conflict that both use the "x-" prefix notation. For that reason, vendors SHOULD use "x-" followed by their Enterprise Number followed by a "-" to guarantee that the non-standard attribute name's interpretation is not ambiguous.

For example, Acme, Inc.'s Enterprise Number is 9999. Say the Service Template for NetHive (a fictitious game) was:

```
-----
template-type=NetHive

template-version=1.0

template-description=
  The popular NetHive game.

template-url-syntax=
  url-path = ; There is no path for a NetHive service URL.

features= string M 0
# The list of optional features the NetHive server supports.
secure session, fast mode

current-users= string M
# The list of users currently playing
```

E. Guttman


Expires: 16 April 2001

[Page 4]

Acme's server advertises a feature which is not on the list of standard features, "x-9999-cheat-mode". Only an Acme client would request this attribute to discover servers, since it is not standard.

5.0 Vendor Opaque Extension

SLPv2 [1] defines a protocol extensibility mechanism. SLPv2 Extensions are added at the end of a message and have the following format:



The format of the Extension Data depends on the Extension ID. Refer to [6] for a full description of different mechanisms available for registration of values with IANA.

Extension ID Range	Assignment By	Protocol Action
0x0000 - 0x3FFF	Designated Expert	Ignore Extension if Extension ID unrecognized
0x4000 - 0x7FFF	Designated Expert	Drop message if Extension ID unrecognized
0x8000 - 0x8FFF	(No one!)	Ignore Extension if Extension ID unrecognized
0x9000 - 0xFFFF	(No one!)	Reserved.

Vendors may extend SLPv2 in any of three ways. First, they may define a new extension to SLPv2 in an internet draft. The vendor then requests that the IESG contact the designated expert for SLP who will review the document. If the document is sound, the document will be published as an Informational RFC with the new Extension ID assigned.

An experimental extension may be done using the range 0x8000 to 0x8FFF. There is always the risk, however, that another vendor will use the same ID, since these IDs are not registered.

Finally, the following OPTIONAL to implement extension allows a

E. Guttman

Expires: 16 April 2001

[Page 5]

Vendor to define their own extensions which are guaranteed to have a unique interpretation.

5.1. Vendor Opaque Extension Format

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
|      Extension ID = 0x0003      |      Next Extension Offset      |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Offset, contd. |      Enterprise Number      |
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Ent. #, contd. |      Extension Data      /
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

The Enterprise Number is included in the Extension as a 4 byte unsigned integer value. The Extension Data following is guaranteed to have an unambiguous interpretation determined by the vendor.

5.2 Example: Acme Extension for UA Authentication

For example, the Acme Corporation, whose Enterprise Number is 9999, can define three extensions to SLP to create an application level access control to service information. (Note that the first byte in the Extension Data is used to differentiate the different extensions under the authority of the vendor.)

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Client ID = 1 |      Client ID Length      |      Client ID      /
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

The Acme UA multicasts a SLP request includes the Vendor Opaque Extension, with the Enterprise Number set to 9999 and the Extension Data as above. The Client ID is a string formatted in the Acme Client ID format (not described here).

```

      0               1               2               3
    0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Challenge = 2 |      Challenge Length      | Challenge data /
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

An Acme SA which receives a SLP request for 'restricted services' will ignore it unless the request includes a Vendor Opaque Extension with an Acme Client ID. In that case it sends a reply to the requesting

UA with zero results and a Vendor Opaque Extension with the Enterprise ID set to 9999 and containing the above "Challenge" data in the

E. Guttman

Expires: 16 April 2001

[Page 6]

Extension Data. The challenge is in the Acme Challenge format (not described here).

```

      0               1               2               3
      0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1 2 3 4 5 6 7 8 9 0 1
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+
| Response = 3 |           Response Length           |   Response   /
+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+--+

```

An Acme UA which receives a reply with zero results and a Vendor Opaque Extension with a "challenge", as above, may unicast a request to the SA which sent the challenge. The request will be the same as the initial one (which contained the "Client ID" Acme vendor extension), however in this case it will include a Vendor Opaque extension with the Enterprise Number set to 9999 and the Extension data including the "Response" data as above. The "Response" data is in the Acme format (not described here).

The SA will then process the response and if the UA has authenticated itself, the SA will unicast a reply including the requested information.

6.0 Extensions Requiring IETF Action

Terminology and procedures for IETF Actions related to registration of IDs with IANA are defined in [6].

SLPv2 [1] defines a number of features whose modification cannot be done by simple vendor extension. These include:

- Block Structure Descriptors (BSD) identifies the format of the Authenticator in the Authentication Block included in some SLP messages. BSD values from 0x0003-0x7FFF are assigned by IETF Consensus.
- New function-IDs in the range 12-255 are standardized by the method of IETF Consensus.
- New error numbers in the range 15-65535 are assigned on the basis of a Standards Action.
- New SLP Extensions with types in the range 2-65535 are registered following the review of the Designated Expert.
- New Service Types are defined and registered with IANA following the review of the Designated Expert. See [5].

Only changes to the base "required to implement" protocol require

IETF Consensus. Extensions are all defined to be done using the approval of a Designated Expert, though in some cases this involves

publishing an Informational RFC.

7.0 IANA Considerations

This document discusses vendor extensibility to SLPv2 but does not introduce any new number or name spaces which need to be administered by IANA. The techniques described in this document make it possible for vendors to extend SLPv2 by doing nothing more than registering an Enterprise Number with IANA (as described in [RFC 1700](#) [4]).

According to [RFC 2608](#):

New SLP Extensions with types in the range 2-65535 may be registered following review by a Designated Expert [5].

The extension ID number for the Vendor Extension is 0x0003.

8.0 Security Considerations

Vendor extensions may introduce additional security considerations into SLP.

This memo describes mechanisms which are standardized elsewhere [1] [3] [5]. The only protocol mechanism described in this document (see [Section 5](#) above) is no less secure than 'private use' extensions defined in SLPv2 [1].

The example in [Section 5.2](#) above shows how Vendor Opaque Extensions can be used to include a challenge response mechanism to SLP so that SAs can enforce an access control policy using a cryptographically secure authentication mechanism. This is merely an example and protocol details were intentionally not provided. A vendor could, however, create a mechanism similar to this one and provide additional security services to SLPv2 in the manner indicated in the example.

References

- [1] Guttman, E., Perkins, C., Veizades, J., Day, M., "Service Location Protocol, Version 2", [RFC 2608](#), July 1999.
- [2] Bradner, S., "Key words for use in RFCs to Indicate Requirement Levels", [BCP 14](#), [RFC 2119](#), March 1997.
- [3] Reynolds, J., Postel, J., "Assigned Numbers", [RFC 1700](#), October 1994.

[4] <ftp://ftp.isi.edu/in-notes/iana/assignments/enterprise-numbers>

E. Guttman

Expires: 16 April 2001

[Page 8]

- [5] Guttman, E., Perkins, C., Kempf, J., "Service Templates and URLs", [RFC 2609](#), July 1999.
- [6] Narten, T. and H. Alvestrand, "Guidelines for Writing an IANA Considerations Section in RFCs, [BCP 26](#), [RFC 2434](#), October 1998.

Author's Address

Erik Guttman
Sun Labs, Network and Security Center
Sun Microsystems
Eichhoelzelstr. 7
74915 Waibstadt
Germany

Phone: +49 7263 911 701
Messages: + 1 650 786 5992
Email: erik.guttman@sun.com

