

Internet Engineering Task Force
Internet-Draft
Updates: [5575](#) (if approved)
Intended status: Standards Track
Expires: August 9, 2014

J. Haas, Ed.
Juniper Networks
February 5, 2014

**Clarification of the Flowspec Redirect Extended Community
draft-haas-idr-flowspec-redirect-rt-bis-01**

Abstract

This document clarifies the formatting of the the BGP Flowspec Redirect Extended Community, originally documented in [RFC 5575](#).

Status of this Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on August 9, 2014.

Copyright Notice

Copyright (c) 2014 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

Table of Contents

1.	Introduction	3
2.	IANA Considerations	4
3.	Security Considerations	5
4.	Acknowledgements	5
5.	Normative References	5
	Author's Address	6

1. Introduction

Dissemination of Flow Specification Rules [[RFC5575](#)], commonly known as BGP Flowspec, provided for a BGP Extended Community [[RFC4360](#)] that served to redirect traffic to a VRF routing instance that matched the flow specification NLRI. In that RFC, the Redirect Extended Community was documented as follows:

```

: +-----+-----+-----+-----+
: | type   | extended community | encoding          |
: +-----+-----+-----+-----+
: | 0x8008 | redirect           | 6-byte Route Target |
: +-----+-----+-----+-----+
:
: [...]
:
: Redirect: The redirect extended community allows the traffic to be
: redirected to a VRF routing instance that lists the specified
: route-target in its import policy. If several local instances
: match this criteria, the choice between them is a local matter
: (for example, the instance with the lowest Route Distinguisher
: value can be elected). This extended community uses the same
: encoding as the Route Target extended community [RFC4360].
: [...]
:
: 11. IANA Considerations
: [...]
:
: The following traffic filtering flow specification rules have been
: allocated by IANA from the "BGP Extended Communities Type -
: Experimental Use" registry as follows:
: [...]
:
: 0x8008 - Flow spec redirect

```

The IANA registry of BGP Extended Communities clearly identifies communities of specific formats. For example, "Two-octet AS Specific Extended Community" [[RFC4360](#)], "Four-octet AS Specific Extended Community" [[RFC5668](#)] and "IPv4 Address Specific Extended Community" [[RFC4360](#)]. Route Targets [[RFC4360](#)] identify this format in the high-order (Type) octet of the Extended Community and set the value of the low-order (Sub-Type) octet to 0x02. The Value field of the Route Target Extended Community is intended to be interpreted in the context of its format.

Since the Redirect Extended Community only registered a single code-point in the IANA BGP Extended Community registry, a common interpretation of the Redirect Extended Community's "6-byte Route

Haas

Expires August 9, 2014

[Page 3]

Target" has been to look for any matching Route Target sharing the same Value portion of its Extended Community. Thus, multiple Route Targets provisioned in a router's VRFs might match even though the format was different.

This "Value wildcard" behavior does not matched deployed implementations of BGP Flowspec. Deployed implementations of BGP Flowspec use the following formatting for the Redirect Extended Community:

type	extended community	encoding
0x8008	redirect AS-2byte	2-octet AS, 4-octet Value
0x8108	redirect IPv4	4-octet IPv4 Address, 2-octet Value
0x8208	redirect AS-4byte	4-octet AS, 2-octet Value

It should be noted that the low-order nybble of the Redirect's Type field corresponds to the Route Target Extended Community format field (Type). (See [[RFC4360](#)], Secs. 3.1, 3.2 and [[RFC5668](#)], Sec. 2.) The low order octet (Sub-Type) of the Redirect Extended Community remains 0x08, contrasted to 0x02 for Route Targets.

The IANA Registries for BGP Extended Communities [[I-D.ietf-idr-extcomm-iana](#)] document was written to update the previously-mentioned IANA registries to better document BGP Extended Community formats. The IANA Considerations section below further amends those registry updates in order to properly document the flowspec redirect communities.

2. IANA Considerations

IANA is requested to update the BGP GENERIC TRANSITIVE EXPERIMENTAL USE EXTENDED COMMUNITY SUB-TYPES registry as follows:

0x08 - Flow spec redirect AS-2byte format.

IANA is requested to update the BGP TRANSITIVE EXTENDED COMMUNITY TYPES registry as follows:

- 0x81 - Generic Transitive Experimental Extended Community Part 2 (Sub-Types are defined in the "Generic Transitive Experimental Extended Community Part 2 Sub-Types" Registry)
- 0x82 - Generic Transitive Experimental Extended Community Part 3 (Sub-Types are defined in the "Generic Transitive Experimental Extended Community Part 3 Sub-Types" Registry)

IANA is requested to create the GENERIC TRANSITIVE EXPERIMENTAL EXTENDED COMMUNITY PART 2 SUB-TYPES registry. It should be seeded with the following Sub-Type:

0x08 - Flow spec redirect IPv4 format.

IANA is requested to create the GENERIC TRANSITIVE EXPERIMENTAL EXTENDED COMMUNITY PART 3 SUB-TYPES registry. It should be seeded with the following Sub-Type:

0x08 - Flow spec redirect AS-4byte format.

3. Security Considerations

This document introduces no additional security considerations than those already covered in [[RFC5575](#)].

4. Acknowledgements

The contents of this document was raised as part of implementation discussions of BGP Flowspec with the following individuals:

Andrew Karch (Cisco)

Robert Raszuk (NTT I3)

Adam Simpson (Alcatel-Lucent)

Matthieu Texier (Arbor Networks)

Kaliraj Vairavakkalai (Juniper)

5. Normative References

[I-D.ietf-idr-extcomm-iana]

Rosen, E. and Y. Rekhter, "IANA Registries for BGP Extended Communities", [draft-ietf-idr-extcomm-iana-02](#) (work in progress), December 2013.

[RFC4360] Sangli, S., Tappan, D., and Y. Rekhter, "BGP Extended Communities Attribute", [RFC 4360](#), February 2006.

[RFC5575] Marques, P., Sheth, N., Raszuk, R., Greene, B., Mauch, J., and D. McPherson, "Dissemination of Flow Specification Rules", [RFC 5575](#), August 2009.

[RFC5668] Rekhter, Y., Sangli, S., and D. Tappan, "4-Octet AS Specific BGP Extended Community", [RFC 5668](#), October 2009.

Author's Address

Jeffrey Haas (editor)
Juniper Networks
1194 N. Mathilda Ave.
Sunnyvale, CA 94089
US

Email: jhaas@juniper.net