

Network Working Group
Internet-Draft
Intended status: Informational
Expires: 22 October 2022

P. M. Hallam-Baker
20 April 2022

Binary Encodings for JavaScript Object Notation: JSON-B, JSON-C, JSON-D
[draft-hallambaker-jsonbcd-22](#)

Abstract

Three binary encodings for JavaScript Object Notation (JSON) are presented. JSON-B (Binary) is a strict superset of the JSON encoding that permits efficient binary encoding of intrinsic JavaScript data types. JSON-C (Compact) is a strict superset of JSON-B that supports compact representation of repeated data strings with short numeric codes. JSON-D (Data) supports additional binary data types for integer and floating-point representations for use in scientific applications where conversion between binary and decimal representations would cause a loss of precision.

This document is also available online at
<http://mathmesh.com/Documents/draft-hallambaker-jsonbcd.html>.

Status of This Memo

This Internet-Draft is submitted in full conformance with the provisions of [BCP 78](#) and [BCP 79](#).

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <https://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on 22 October 2022.

Copyright Notice

Copyright (c) 2022 IETF Trust and the persons identified as the document authors. All rights reserved.

Internet-Draft

JSON-B, JSON-C, JSON-D

April 2022

This document is subject to [BCP 78](#) and the IETF Trust's Legal Provisions Relating to IETF Documents (<https://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document.

Table of Contents

1.	Introduction	2
1.1.	Objectives	3
2.	Definitions	4
2.1.	Requirements Language	4
2.2.	Defined Terms	4
2.3.	Related Specifications	5
2.4.	Terminology	5
3.	Extended JSON Grammar	5
4.	JSON-B	7
4.1.	JSON-B Examples	9
5.	JSON-C	10
5.1.	JSON-C Examples	11
6.	JSON-D (Data)	12
7.	JBCD Frames and Records	13
8.	JSON-BCD Application Binding	15
8.1.	JSON Binding	15
8.2.	JSON-B Binding	16
8.3.	Examples	17
9.	Acknowledgements	17
10.	Security Considerations	17
11.	IANA Considerations	18
12.	Normative References	18
13.	Informative References	19

[1.](#) Introduction

JavaScript Object Notation (JSON) is a simple text encoding for the JavaScript Data model that has found wide application beyond its original field of use. In particular JSON has rapidly become a preferred encoding for Web Services.

JSON encoding supports just four fundamental data types (integer, floating point, string and boolean), arrays and objects which consist of a list of tag-value pairs.

Although the JSON encoding is sufficient for many purposes it is not always efficient. In particular there is no efficient representation for blocks of binary data. Use of base64 encoding increases data volume by 33%. This overhead increases exponentially in applications where nested binary encodings are required making use of JSON encoding unsatisfactory in cryptographic applications where nested binary structures are frequently required.

Another source of inefficiency in JSON encoding is the repeated occurrence of object tags. A JSON encoding containing an array of a hundred objects such as `{"first":1,"second":2}` will contain a hundred occurrences of the string "first" (seven bytes) and a hundred occurrences of the string "second" (eight bytes). Using two byte code sequences in place of strings allows a saving of 11 bytes per object without loss of information, a saving of 50%.

A third objection to the use of JSON encoding is that floating point numbers can only be represented in decimal form and this necessarily involves a loss of precision when converting between binary and decimal representations. While such issues are rarely important in network applications they can be critical in scientific applications. It is not acceptable for saving and restoring a data set to change the result of a calculation.

[1.1](#). Objectives

The following were identified as core objectives for a binary JSON encoding:

- * Easy to convert existing encoders and decoders to add binary support
- * Efficient encoding of binary data
- * Ability to convert from JSON to binary encoding in a streaming mode (i.e. without reading the entire binary data block before

beginning encoding.

- * Lossless encoding of JavaScript data types
- * The ability to support JSON tag compression and extended data types are considered desirable but not essential for typical network applications.

Three binary encodings are defined:

JSON-B (Binary) Encodes JSON data in binary. Only the JavaScript

data model is supported (i.e. atomic types are integers, double or string). Integers may be 8, 16, 32 or 64 bits either signed or unsigned. Floating points are IEEE 754 binary64 format [[IEEE754](#)]. Supports chunked encoding for binary and UTF-8 string types.

JSON-C (Compact) As JSON-B but with support for representing JSON tags in numeric code form (16 bit code space). This is done for both compact encoding and to allow simplification of encoders/decoders in constrained environments. Codes may be defined inline or by reference to a known dictionary of codes referenced via a digest value.

JSON-D (Data) As JSON-C but with support for representing additional data types without loss of precision. In particular other IEEE 754 floating point formats, both binary and decimal and Intel's 80 bit floating point, plus 128 bit integers and bignum integers.

Each encoding is a proper superset of JSON, JSON-C is a proper superset of JSON-B and JSON-D is a proper superset of JSON-C. Thus a single decoder MAY be used for all three new encodings and for JSON. Figure 1 shows these relationships graphically:

(Artwork only available as svg: No external link available, see [draft-hallambaker-jsonbcd-22.html](#) for artwork.)

Figure 1: Encoding Relationships.

[2.](#) Definitions

This section presents the related specifications and standard, the terms that are used as terms of art within the documents and the terms used as requirements language.

[2.1.](#) Requirements Language

The key words "MUST", "MUST NOT", "REQUIRED", "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "RECOMMENDED", "MAY", and "OPTIONAL" in this document are to be interpreted as described in [[RFC2119](#)].

[2.2.](#) Defined Terms

The terms of art used in this document are described in the `_Mesh Architecture Guide_` [[draft-hallambaker-mesh-architecture](#)].

Hallam-Baker

Expires 22 October 2022

[Page 4]

Internet-Draft

JSON-B, JSON-C, JSON-D

April 2022

[2.3.](#) Related Specifications

The JSON-B, JSON-C and JSON-D encodings are all based on the JSON grammar [[RFC7159](#)]. IEEE 754 Floating Point Standard is used for encoding floating point numbers [[IEEE754](#)],

[2.4.](#) Terminology

No new terms of art are defined

[3.](#) Extended JSON Grammar

The JSON-B, JSON-C and JSON-D encodings are all based on the JSON grammar [[RFC7159](#)] using the same syntactic structure but different lexical encodings.

JSON-B0 and JSON-C0 replace the JSON lexical encodings for strings and numbers with binary encodings. JSON-B1 and JSON-C1 allow either lexical encoding to be used. Thus, any valid JSON encoding is a valid JSON-B1 or JSON-C1 encoding.

The grammar of JSON-B, JSON-C and JSON-D is a superset of the JSON

grammar. The following productions are added to the grammar:

x-value Binary encodings for data values. As the binary value encodings are all self-delimiting

x-member An object member where the value is specified as an X-value and thus does not require a value-separator.

b-value Binary data encodings defined in JSON-B.

b-string Defined length string encoding defined in JSON-B.

c-def Tag code definition defined in JSON-C. These may only appear before the beginning of an Object or Array and before any preceding white space.

c-tag Tag code value defined in JSON-C.

d-value Additional binary data encodings defined in JSON-D for use in scientific data applications.

The JSON grammar is modified to permit the use of x-value productions in place of (value value-separator) :

JSON-text = (object / array)

object = *cdef begin-object [
 *(member value-separator | x-member)
 (member | x-member)] end-object

member = tag value

x-member = tag x-value

tag = string name-separator | b-string | c-tag

array = *cdef begin-array [*(value value-separator | x-value)
 (value | x-value)] end-array

x-value = b-value / d-value

value = false / null / true / object / array / number / string

name-separator = ws %x3A ws ; : colon

value-separator = ws %x2C ws ; , comma

The following lexical values are unchanged:

begin-array = ws %x5B ws ; [left square bracket

begin-object = ws %x7B ws ; { left curly bracket

end-array = ws %x5D ws ;] right square bracket

end-object = ws %x7D ws ; } right curly bracket

ws = *(%x20 %x09 %x0A %x0D)

false = %x66.61.6c.73.65 ; false

null = %x6e.75.6c.6c ; null

true = %x74.72.75.65 ; true

The productions number and string are defined as before:

number = [minus] int [frac] [exp]

decimal-point = %x2E ; .

digit1-9 = %x31-39 ; 1-9

e = %x65 / %x45 ; e E

exp = e [minus / plus] 1*DIGIT

frac = decimal-point 1*DIGIT

int = zero / (digit1-9 *DIGIT)

minus = %x2D ; -

```

plus = %x2B          ; +
zero = %x30          ; 0

string = quotation-mark *char quotation-mark
char = unescaped /
escape ( %x22 / %x5C / %x2F / %x62 / %x66 /
%x6E / %x72 / %x74 / %x75 4HEXDIG )

escape = %x5C          ; \
quotation-mark = %x22  ; "
unescaped = %x20-21 / %x23-5B / %x5D-10FFFF

```

4. JSON-B

The JSON-B encoding defines the b-value and b-string productions:

```

b-value = b-atom | b-string | b-data | b-integer |
b-float

```

```

b-string = *( string-chunk ) string-term
b-data = *( data-chunk ) data-last

```

```

b-integer = p-int8 | p-int16 | p-int32 | p-int64 | p-bignum16 |
n-int8 | n-int16 | n-int32 | n-int64 | n-bignum16

```

```

b-float = binary64

```

The lexical encodings of the productions are defined in the following tables where the column 'tag' specifies the byte code that begins the production, 'Fixed' specifies the number of data bytes that follow and 'Length' specifies the number of bytes used to define the length of a variable length field following the data bytes:

Production	Tag	Fixed	Length	Data Description
string-term	x80	-	1	Terminal String 8 bit length
string-term	x81	-	2	Terminal String

string-term	x82	-	4	Terminal String 32 bit length
string-term	x83	-	8	Terminal String 64 bit length
string-chunk	x84	-	1	Terminal String 8 bit length
string-chunk	x85	-	2	Terminal String 16 bit length
string-chunk	x86	-	4	Terminal String 32 bit length
string-chunk	x87	-	8	Terminal String 64 bit length
data-term	x88	-	1	Terminal String 8 bit length
data-term	x89	-	2	Terminal String 16 bit length
data-term	x8A	-	4	Terminal String 32 bit length
data-term	x8B	-	8	Terminal String 64 bit length
data-chunk	X8C	-	1	Terminal String 8 bit length
data-chunk	x8D	-	2	Terminal String 16 bit length
data-chunk	x8E	-	4	Terminal String 32 bit length
data-chunk	x8F	-	8	Terminal String 64 bit length

Table 1

Table 1: Codes for String and Data items

Production	Tag	Fixed	Length	Data Description
p-int8	xA0	1	-	Positive 8 bit Integer
p-int16	xA1	2	-	Positive 16 bit Integer
p-int32	xA2	4	-	Positive 32 bit Integer
p-int64	xA3	8	-	Positive 64 bit Integer
p-bignum16	Xa7	-	2	Positive Bignum
n-int8	xA8	1	-	Negative 8 bit Integer
n-int16	xA9	2	-	Negative 16 bit Integer
n-int32	xAA	4	-	Negative 32 bit Integer
n-int64	xAB	8	-	Negative 64 bit Integer
n-bignum16	xAF	-	2	Negative Bignum
binary64	x92	8	-	IEEE 754 Floating Point Binary 64 bit
b-value	xB0	-	-	True
b-value	xB1	-	-	False
b-value	xB2	-	-	Null

Table 2

Table 2: Codes for Integers, 64 Bit Floating Point, Boolean and Null items.

A data type commonly used in networking that is not defined in this scheme is a datetime representation. To define such a data type, a string containing a date-time value in Internet type format is typically used.

[4.1.](#) JSON-B Examples

The following examples show examples of using JSON-B encoding:

Internet-Draft

JSON-B, JSON-C, JSON-D

April 2022

A0 2A	42 (as 8 bit integer)
A1 00 2A	42 (as 16 bit integer)
A2 00 00 00 2A	42 (as 32 bit integer)
A3 00 00 00 00 00 00 2A	42 (as 64 bit integer)
A5 00 01 42	42 (as Bignum)
80 05 48 65 6c 6c 6f	"Hello" (single chunk)
81 00 05 48 65 6c 6c 6f	"Hello" (single chunk)
84 05 48 65 6c 6c 6f 80 00	"Hello" (as two chunks)
92 3f f0 00 00 00 00 00	1.0
92 40 24 00 00 00 00 00	10.0
92 40 09 21 fb 54 44 2e ea	3.14159265359
92 bf f0 00 00 00 00 00	-1.0
B0	true
B1	false
B2	null

5. JSON-C

JSON-C (Compressed) permits numeric code values to be substituted for strings and binary data. Tag codes MAY be 8, 16 or 32 bits long encoded in network byte order.

Tag codes MUST be defined before they are referenced. A Tag code MAY be defined before the corresponding data or string value is used or at the same time that it is used.

A dictionary is a list of tag code definitions. An encoding MAY incorporate definitions from a dictionary using the dict-hash production. The dict hash production specifies a (positive) offset value to be added to the entries in the dictionary followed by the UDF fingerprint [[draft-hallambaker-udf](#)] of the dictionary to be used.

Production	Tag	Fixed	Length	Data Description
c-tag	xC0	1	-	8 bit tag code
c-tag	xC1	2	-	16 bit tag code
c-tag	xC2	4	-	32 bit tag code
c-def	xC4	1	-	8 bit tag definition
c-def	xC5	2	-	16 bit tag definition
c-def	xC6	4	-	32 bit tag definition
c-tag	xC8	1	-	8 bit tag code and definition
c-tag	xC9	2	-	16 bit tag code and definition
c-tag	xCA	4	-	32 bit tag code and definition
c-def	xCC	1	-	8 bit tag dictionary definition
c-def	xCD	2	-	16 bit tag dictionary definition
c-def	xCE	4	-	32 bit tag dictionary definition

dict-hash	xD0	4	1	UDF fingerprint of dictionary
-----------	-----	---	---	-------------------------------

Table 3

Table 3: Codes Used for Compression

All integer values are encoded in Network Byte Order (most significant byte first).

5.1. JSON-C Examples

The following examples show examples of using JSON-C encoding:

Hallam-Baker Expires 22 October 2022 [Page 11]

Internet-Draft JSON-B, JSON-C, JSON-D April 2022

```

C8 20 80 05 48 65 6c 6c 6f      "Hello"    20 = "Hello"
C4 21 80 05 48 65 6c 6c 6f      "Hello"    21 = "Hello"
C0 20                             "Hello"
C1 00 20                          "Hello"

D0 00 00 01 00 20                Insert dictionary at code 256
e3 b0 c4 42 98 fc 1c 14
9a fb f4 c8 99 6f b9 24
27 ae 41 e4 64 9b 93 4c
a4 95 99 1b 78 52 b8 55          UDF (C4 21 80 05 48 65 6c 6c 6f)

```

6. JSON-D (Data)

JSON-B and JSON-C only support the two numeric types defined in the JavaScript data model: Integers and 64 bit floating point values. JSON-D (Data) defines binary encodings for additional data types that are commonly used in scientific applications. These comprise positive and negative 128 bit integers, six additional floating point representations defined by IEEE 754 [IEEE754] and the Intel extended precision 80 bit floating point representation [INTEL].

Should the need arise, even bigger bignums could be defined with the length specified as a 32 bit value permitting bignums of up to 2³⁵ bits to be represented.

d-value = d-integer | d-float

d-float = binary16 | binary32 | binary128 | binary80 |
decimal32 | decimal64 | decimal 128

The codes for these values are as follows:

Production	Tag	Fixed	Length	Data Description
p-int128	xA4	16	-	Positive 128 bit Integer
n-int128	xAC	16	-	Negative 128 bit Integer
binary16	x90	2	-	IEEE 754 Floating Point Binary 16 bit
binary32	x91	4	-	IEEE 754 Floating Point Binary 32 bit
binary128	x94	16	-	IEEE 754 Floating Point Binary 64 bit
Intel80	x95	10	-	Intel extended Floating Point 80 bit

decimal32	x96	4	-	IEEE 754 Floating Point Decimal 32
Decimal64	x97	8	-	IEEE 754 Floating Point Decimal 64
Decimal128	x98	16	-	IEEE 754 Floating Point Decimal 128

Table 4

Table 4: Additional Codes for Scientific Data

7. JBCD Frames and Records

Tag codes in the range xF0–XFF are reserved for specifying markers for `_frames_` and `_records_`. These tags are not used to encode JSON data, they are only used to encapsulate opaque binary data blobs as a unit.

A JBCD record consists of consist of the tag, a length and the data item. The length indication provided by the record format allows efficient traversal of a sequence of records in the forward direction only.

A JBCD Frames consists of consist of the tag, a length and the data item followed by the tag-length sequence repeated with the bytes written in the reverse order. The first length indication allows efficient traversal of a sequence of records in the forward direction and the second allows efficient traversal in the reverse direction.

(Artwork only available as svg: No external link available, see [draft-hallambaker-jsonbcd-22.html](#) for artwork.)

Figure 2: JBCD Records and Frames

The JBCD-Frame tags currently defined are:

Production	Tag	Fixed	Length	Data Description
uframe	xF0	-	1	Record, 8 bit length
uframe	xF1	-	2	Record, 16 bit length
uframe	xF2	-	4	Record, 32 bit length
uframe	xF3	-	8	Record, 64 bit length
bframe	xF4	-	1	Frame, 8 bit length
bframe	xF5	-	2	Frame, 16 bit length
bframe	xF6	-	4	Frame, 32 bit length
bframe	xF7	-	8	Frame, 64 bit length
	xF8-xFF	-	-	Reserved

Table 5

The author does not expect additional framing tags to be added but codes F8-FF are reserved in case this is desired.

It may prove convenient to represent message digest values as large integers rather than binary strings. While very few platforms or programming languages support mathematical operations on fixed size integers larger than 64, this is not a major concern since message digests are rarely used for any purpose other than comparison for equality.

Production	Tag	Fixed	Length	Data Description
p-int128	Xa4	16	-	Positive 128 bit Integer

p-int256	Xa5	32	-	Positive 256 bit Integer
p-int512	Xa6	64	-	Positive 512 bit Integer

Table 6

8. JSON-BCD Application Binding

The JSON serialization format is intentionally limited in the range of data types it supports. To serialize data not supported by the JSON data model, it is necessary to specify a means of transforming the unsupported data type into a supported one.

In particular JSON does not provide a Date-Time object or a means of encoding binary data except as an array of bytes.

The JSON-BCD Application Binding specifies a data model designed to support the needs of specifying network protocols and associated static data. The data model is close to that of JSON with three additional types:

- * Binary data
- * DateTime
- * Object of specified type

8.1. JSON Binding

The following data field types are specified:

Integer

Integer values are encoded as JSON number values.

Float

Float values are encoded as JSON number values.

String

Test strings are encoded as JSON text strings.

Boolean

Boolean values are encoded as JSON 'false', 'true' or 'null' tokens according to value.

Sequence

Sequences of data items that are encoded as JSON arrays

Object of known type

Objects whose type is known to the receiver are encoded as JSON objects

Object of variable type

Objects whose type is not known to the receiver are encoded as JSON objects containing a single field whose name describes the type of the object value and whose value contains the value.

Binary Data

Byte sequences are converted to BASE64-url encoding [[RFC4648](#)] and encoded as JSON string values.

Date Time

Date Time values are converted to Internet time format as described in [[RFC3339](#)] and encoded as JSON string values.

[8.2.](#) JSON-B Binding

The JSON-B value allows a superset of the JSON encodings to be used.

Integer

Integer values are encoded as JSON number values or as JSON-B b-integer values.

Float

Float values are encoded as JSON number values or as JSON-B b-integer or b-float values.

String

Test strings are encoded as JSON text strings or as JSON-B b-string values.

Boolean

Boolean values are encoded as JSON 'false', 'true' or 'null' tokens or as JSON-B b-atom values according to value

Sequence

Sequences of data items that are encoded as JSON arrays

Object of known type

Objects whose type is known to the receiver are encoded as JSON objects

Object of variable type

Objects whose type is not known to the receiver are encoded as JSON objects containing a single field whose name describes the type of the object value and whose value contains the value.

Binary Data

Byte sequences are converted to BASE64-url encoding [[RFC4648](#)] and encoded as JSON string values or as JSON-B b-data values.

Date Time

Date Time values are converted to Internet time format as described in [[RFC3339](#)] and encoded as JSON string values or as JSON-B b-string values.

[8.3](#). Examples

[9](#). Acknowledgements

This work was assisted by conversations with Nico Williams and other participants on the applications area mailing list.

10. Security Considerations

A correctly implemented data encoding mechanism should not introduce new security vulnerabilities. However, experience demonstrates that some data encoding approaches are more prone to introduce vulnerabilities when incorrectly implemented than others.

Hallam-Baker

Expires 22 October 2022

[Page 17]

Internet-Draft

JSON-B, JSON-C, JSON-D

April 2022

In particular, whenever variable length data formats are used, the possibility of a buffer overrun vulnerability is introduced. While best practice suggests that a coding language with native mechanisms for bounds checking is the best protection against such errors, such approaches are not always followed. While such vulnerabilities are most commonly seen in the design of decoders, it is possible for the same vulnerabilities to be exploited in encoders.

A common source of such errors is the case where nested length encodings are used. For example, a decoder relies on an outermost length encoding that specifies a length of 50 bytes to allocate memory for the entire result and then attempts to copy a string with a declared length of 1000 bytes within the sequence.

The extensions to the JSON encoding described in this document are designed to avoid such errors. Length encodings are only used to define the length of x-value constructions which are always terminal and cannot have nested data entries.

11. IANA Considerations

[TBS list out all the code points that require an IANA registration]

12. Normative References

[[draft-hallambaker-udf](#)]

Hallam-Baker, P., "Uniform Data Fingerprint (UDF)", Work in Progress, Internet-Draft, [draft-hallambaker-udf-12](#), 6 January 2019, <<https://datatracker.ietf.org/doc/html/draft-hallambaker-udf-12>>.

[IEEE754] IEEE Computer Society, "IEEE Standard for Floating-Point Arithmetic", IEEE 754-2008,

DOI 10.1109/IEEESTD.2008.4610935, 29 August 2008,
<<https://doi.org/10.1109/IEEESTD.2008.4610935>>.

[INTEL] Intel Corp., "Unknown".

[RFC3339] Klyne, G. and C. Newman, "Date and Time on the Internet: Timestamps", [RFC 3339](#), DOI 10.17487/RFC3339, July 2002, <<https://www.rfc-editor.org/rfc/rfc3339>>.

[RFC4648] Josefsson, S., "The Base16, Base32, and Base64 Data Encodings", [RFC 4648](#), DOI 10.17487/RFC4648, October 2006, <<https://www.rfc-editor.org/rfc/rfc4648>>.

Hallam-Baker

Expires 22 October 2022

[Page 18]

Internet-Draft

JSON-B, JSON-C, JSON-D

April 2022

[RFC7159] Bray, T., "The JavaScript Object Notation (JSON) Data Interchange Format", [RFC 7159](#), DOI 10.17487/RFC7159, March 2014, <<https://www.rfc-editor.org/rfc/rfc7159>>.

13. Informative References

[[draft-hallambaker-mesh-architecture](#)]

Hallam-Baker, P., "Mathematical Mesh 3.0 Part I: Architecture Guide", Work in Progress, Internet-Draft, [draft-hallambaker-mesh-architecture-19](#), 25 October 2021, <<https://datatracker.ietf.org/doc/html/draft-hallambaker-mesh-architecture-19>>.

