

v6ops Working Group	N. Hilliard
Internet-Draft	INEX
Intended status: Informational	July 04, 2011
Expires: January 05, 2012	

A Discard Prefix for IPv6

draft-hilliard-v6ops-ipv6-discard-prefix-00

## [Abstract](#)

Remote triggered black hole filtering describes a method of mitigating against denial-of-service attacks by selectively discarding traffic based on source or destination address. This document explains why a unique IPv6 prefix should be formally assigned by IANA for the purpose of facilitating IPv6 remote triggered black hole filtering.

## [Status of this Memo](#)

This Internet-Draft is submitted in full conformance with the provisions of BCP 78 and BCP 79.

Internet-Drafts are working documents of the Internet Engineering Task Force (IETF). Note that other groups may also distribute working documents as Internet-Drafts. The list of current Internet-Drafts is at <http://datatracker.ietf.org/drafts/current/>.

Internet-Drafts are draft documents valid for a maximum of six months and may be updated, replaced, or obsoleted by other documents at any time. It is inappropriate to use Internet-Drafts as reference material or to cite them other than as "work in progress."

This Internet-Draft will expire on January 05, 2012.

## [Copyright Notice](#)

Copyright (c) 2011 IETF Trust and the persons identified as the document authors. All rights reserved.

This document is subject to BCP 78 and the IETF Trust's Legal Provisions Relating to IETF Documents (<http://trustee.ietf.org/license-info>) in effect on the date of publication of this document. Please review these documents carefully, as they describe your rights and restrictions with respect to this document. Code Components extracted from this document must include Simplified BSD License text as described in Section 4.e of the Trust Legal Provisions and are provided without warranty as described in the Simplified BSD License.

## [Table of Contents](#)

- \*1. [Introduction](#)
- \*2. [A Discard Prefix for IPv6](#)
- \*3. [Operational Implications](#)

- \*4. [IANA Considerations](#)
- \*5. [Security Considerations](#)
- \*6. [References](#)
  - \*6.1. [Normative References](#)
  - \*6.2. [Informative References](#)
- \*[Author's Address](#)

## **[1. Introduction](#)**

Remote triggered black hole (RTBH) filtering describes a class of methods of blocking IP traffic to or from a specific destination on a network. These methods operate by setting the next-hop address of an IP packet with a specified source or destination address to be a unicast prefix which is wired locally or remotely to a router's discard or null interface. Typically, this information is propagated throughout an autonomous system using a dynamic routing protocol. By deploying RTBH systems across a network, traffic to or from specific destinations may be selectively black-holed in a manner which is efficient, scalable and straightforward to implement. For IPv4, some networks configure RTBH installations using [\[RFC1918\]](#) address space or the address blocks reserved for documentation in [\[RFC5737\]](#).

However RTBH configurations are not documentation, but operationally important features of many public-facing production networks.

Furthermore, [\[RFC3849\]](#) specifies that the IPv6 documentation prefix should be filtered in both local and public contexts. On this basis, it is suggested that both private network address blocks and documentation prefixes described in [\[RFC5737\]](#) are inappropriate for the purpose of RTBH configurations.

While it could be argued that there are other addresses and address prefixes which could be used for this purpose (e.g. `::/128`), or that an operator could assign an address block from their own address space for this purposes, there is currently no operational clarity on what address block would be appropriate or inappropriate to use for this purpose. By creating an assigned discard prefix for IPv6, the IETF will introduce operational clarity and good practice for implementation of IPv6 RTBH configurations.

## **[2. A Discard Prefix for IPv6](#)**

For the purposes of implementing an IPv6 remote triggered black hole filter, a unicast address block is required. There are currently no IPv6 unicast address blocks which are specifically nominated for the purposes of implementing RTBH filters.

As [\[RFC5635\]](#) describes situations where more than one discard address may be used for implementing multiple remote triggered black holes, a

single assigned prefix is not sufficient to cover all likely RTBH filtering situations. Consequently, an address block is required. The prefix allocated by IANA for the purpose of implementing IPv6 remote triggered black holes is xxx::/32.

### **3. Operational Implications**

This assignment MAY be carried in a dynamic routing protocol within an autonomous system. The assignment SHOULD NOT be announced to third party autonomous systems and IPv6 traffic with an destination address within this prefix SHOULD NOT be forwarded to third party autonomous systems.

On networks which implement IPv6 remote triggered black holes, some or all of this network block MAY be configured with a destination of a discard or null interface on any or all IPv6 routers within the autonomous system.

### **4. IANA Considerations**

IANA is requested to assign a unique /32 unicast address prefix in the IPv6 address registry for the purpose of facilitating remote triggered black hole configurations.

### **5. Security Considerations**

IPv6 addressing documents do not have any direct impact on Internet infrastructure security.

### **6. References**

#### **6.1. Normative References**

<b>[RFC5635]</b>	Kumari, W. and D. McPherson, " <a href="#">Remote Triggered Black Hole Filtering with Unicast Reverse Path Forwarding (uRPF)</a> ", RFC 5635, August 2009.
------------------	--

#### **6.2. Informative References**

<b>[RFC1918]</b>	<a href="#">Rekhter, Y.</a> , <a href="#">Moskowitz, R.</a> , <a href="#">Karrenberg, D.</a> , <a href="#">Groot, G.</a> and <a href="#">E. Lear</a> , " <a href="#">Address Allocation for Private Internets</a> ", BCP 5, RFC 1918, February 1996.
<b>[RFC3849]</b>	Huston, G., Lord, A. and P. Smith, " <a href="#">IPv6 Address Prefix Reserved for Documentation</a> ", RFC 3849, July 2004.
<b>[RFC5226]</b>	Narten, T. and H. Alvestrand, " <a href="#">Guidelines for Writing an IANA Considerations Section in RFCs</a> ", BCP 26, RFC 5226, May 2008.
<b>[RFC5737]</b>	Arkko, J., Cotton, M. and L. Vegoda, " <a href="#">IPv4 Address Blocks Reserved for Documentation</a> ", RFC 5737, January 2010.

### Author's Address

Nick Hilliard Hilliard INEX 4027 Kingswood Road Dublin, 24 IE EMail:  
[nick@inex.ie](mailto:nick@inex.ie)